

# PARTIAL TEST REPORT

No.: 18-1-0050701T04a\_C02

According to:  
**FCC Regulations**  
 Part 15.205  
 Part 15.209  
 Part 15.407  
**ISED-Regulations**  
 RSS-Gen, Issue 4, RSS-247, Issue 2  
 for  
 Datalogic S.r.l.

**Joya Touch A6**  
**A00AN04HLXGT0AN**

**FCC ID: U4GJTADG**  
**ISED ID: 3862E-JTADG**  
**HVIN JTADG GUN**  
**HVIN JTADG HH**

| Laboratory Accreditation and Listings                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                       |                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Accredited EMC-Test Laboratory                                                                                                                                                                                                                                                                                                      | <br>Industry Canada<br>Reg. No.: 3462D-1<br>Reg. No.: 3462D-2<br>Reg. No.: 3462D-3 | <br>Voluntary Controls for Electromagnetic Emissions<br>Reg. No.:<br>R-4552, C-20009,<br>T-20006, G-20013 |
| <br>AUTHORIZED RF LABORATORY                                                                                                                                                                                                                                                                                                            | <br>Lab Code: 20011130-00                                                          | <br>MRA US-EU 0003                                                                                        |
| accredited according to DIN EN ISO/IEC 17025                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                       |                                                                                                                                                                                                |
| <p align="center"> <b>CETECOM GmbH</b><br/>           Laboratory Radio Communications &amp; Electromagnetic Compatibility<br/>           Im Teelbruch 116 • 45219 Essen • Germany<br/>           Registered in Essen, Germany, Reg. No.: HRB Essen 8984<br/>           Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964<br/>           E-mail: info@cetecom.com • Internet: www.cetecom.com         </p> |                                                                                                                                                                       |                                                                                                                                                                                                |

## Table of Contents

|                                                                                                      |           |
|------------------------------------------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF TEST RESULTS.....</b>                                                               | <b>3</b>  |
| 1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C and RSS-247, Issue 2 ..... | 3         |
| 1.2. Attestation:.....                                                                               | 6         |
| <b>2. ADMINISTRATIVE DATA .....</b>                                                                  | <b>7</b>  |
| 2.1. Identification of the testing laboratory .....                                                  | 7         |
| 2.2. Test location .....                                                                             | 7         |
| 2.3. Organizational items .....                                                                      | 7         |
| 2.4. Applicant's details .....                                                                       | 7         |
| 2.5. Manufacturer's details .....                                                                    | 7         |
| <b>3. EQUIPMENT UNDER TEST (EUT).....</b>                                                            | <b>8</b>  |
| 3.1. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant .....                  | 8         |
| 3.2. EUT: Type, S/N etc. and short descriptions used in this test report .....                       | 9         |
| 3.3. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions .....                           | 9         |
| 3.4. EUT set-ups .....                                                                               | 9         |
| 3.5. EUT operating modes .....                                                                       | 9         |
| <b>4. DESCRIPTION OF TEST SYSTEM SET-UP'S .....</b>                                                  | <b>11</b> |
| 4.1. Test system set-up for conducted measurements on antenna port .....                             | 11        |
| 4.2. Test system set-up for radiated magnetic field measurements below 30 MHz .....                  | 13        |
| 4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz .....                | 14        |
| 4.4. Test system set-up for radiated electric field measurement above 1 GHz .....                    | 15        |
| <b>5. MEASUREMENTS .....</b>                                                                         | <b>16</b> |
| 5.1. Duty-Cycle.....                                                                                 | 16        |
| 5.2. RF-Parameter - Transmitter Peak output power (conducted and radiated).....                      | 17        |
| 5.3. General Limit - Radiated field strength emissions below 30 MHz .....                            | 20        |
| 5.4. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz.....                          | 23        |
| 5.5. General Limit - Radiated emissions, above 1 GHz.....                                            | 25        |
| 5.6. RF-Parameter - Radiated Band-Edge compliance measurements.....                                  | 28        |
| 5.7. Measurement uncertainties .....                                                                 | 31        |
| <b>6. ABBREVIATIONS USED IN THIS REPORT .....</b>                                                    | <b>32</b> |
| <b>7. ACCREDITATION DETAILS OF CETECOM'S LABORATORIES AND TEST SITES .....</b>                       | <b>32</b> |
| <b>8. INSTRUMENTS AND ANCILLARY.....</b>                                                             | <b>33</b> |
| TC" .....                                                                                            | 33        |
| <b>9. VERSIONS OF TEST REPORTS (CHANGE HISTORY) .....</b>                                            | <b>37</b> |

| Table of Annex                                              |                             |                                    |             |
|-------------------------------------------------------------|-----------------------------|------------------------------------|-------------|
| Annex No.                                                   | Contents                    | Reference Description              | Total Pages |
| Annex 1                                                     | Test results                | CETECOM_TR18-1-0050701T04-A1       | 72          |
| Annex 2                                                     | External photographs of EUT | JTA6DG External Pictures           | 11          |
| Annex 3                                                     | Internal photographs of EUT | Internal Pictures JOYA TOUCH A6 DG | 8           |
| Annex 4                                                     | Test set-up photographs     | CETECOM_TR18-1-0050701T02-A4       | 7           |
| The listed attachments are an integral part of this report. |                             |                                    |             |

## 1. Summary of test results

The test results apply exclusively to the test samples as presented in this report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests. Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.

The presented Equipment Under Test (in this report, hereinafter referred as EUT) : **Joya Touch** integrates total 1 of pre-certified module **SIMT 1502 (FCC ID: UDV-20170406 and IC: 8430A-20170406)** & supports following technologies :

EUT supported Technologies which are not tested within this test report

| EUT supported Technology                       | Test Report Reference          |
|------------------------------------------------|--------------------------------|
| Bluetooth FHSS (BR-EDR) Modes: 2402 – 2480 MHz | CETECOM_TR18-1-0050701T02a_C01 |
| Bluetooth Low Energy Modes: 2402 – 2480 MHz    | CETECOM_TR18-1-0096701T01a_C02 |
| WLAN 802.11b/g/n(HT20) Modes: 2412 – 2462 MHz  | CETECOM_TR18-1-0050701T03a_C01 |

EUT supported Technologies which are tested within this test report

- **WLAN 802.11a/n(HT20) Modes: 5150–5850 MHz**

Following test cases have been performed to show compliance with valid Part 15.205/15.209/15.407 of the FCC CFR Title 47 Rules, Edition October 2017 and Canadian RSS-247, Issue 2 standard.

### 1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C and RSS-247, Issue 2

| Test cases                      | Port                         | References and Limits        |                              |                                              | EUT set-up | EUT op. mode | Result    |
|---------------------------------|------------------------------|------------------------------|------------------------------|----------------------------------------------|------------|--------------|-----------|
|                                 |                              | FCC Standard                 | RSS Standard                 | Test limit                                   |            |              |           |
| TX-Mode                         |                              |                              |                              |                                              |            |              |           |
| 99% occupied bandwidth          | Antenna terminal (conducted) | 2.1049(h)                    | RSS-Gen, Issue 4 Chapter 6.6 | 99% Power bandwidth                          | --         | --           | Remark 2) |
| 26 dB bandwidth                 | Antenna terminal (conducted) | §15.303 + §15.407(a)(2)(5)   | RSS-Gen, Issue 4 Chapter 6.6 | 26 dB spectral density bandwidth             | --         | --           | Remark 2) |
| Duty-Cycle                      | Antenna terminal (conducted) | KDB789033 + ANSI C63.10:2013 | KDB789033 + ANSI C63.10:2013 | No Limit Criteria                            | 2          | 1            | pass      |
| Transmitter frequency stability | Antenna terminal (conducted) | § 2.1055 + §15.407(g)        |                              | Operation within designated operational band | --         | --           | Remark 2) |

|                             |                                             |                                                                                                                            |                                                                      |                                                                                                                                                                          |    |    |                                                            |
|-----------------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|----|------------------------------------------------------------|
| Maximum output power        | Antenna terminal (conducted)                | §15.407(a)<br>(1)(iv)<br>5.15-5.25 GHz Client devices<br>(2)<br>5.25-5.35 GHz &<br>5.47-5.725 GHz<br>(3)<br>5.725-5.85 GHz | RSS-247, Issue 2 Chapter<br>6.2.1.1<br>6.2.2.1<br>6.2.3.1<br>6.2.4.1 | Power Limits (if Antenna Gain < 6 dBi)<br>250 mW<br>lesser of 250mW or 11dBm+10logB<br>1 W                                                                               | 2  | 1  | Pass                                                       |
| Peak Power Spectral density | Antenna terminal (conducted)                | §15.407(a)<br>(1)(iv)<br>5.15-5.25 GHz Client devices<br>(2)<br>5.25-5.35 GHz &<br>5.47-5.725 GHz<br>(3)<br>5.725-5.85 GHz | RSS-247, Issue 2 Chapter<br>6.2.1.1<br>6.2.2.1<br>6.2.3.1<br>6.2.4.1 | Power Spectral Density Limits (if Antenna Gain < 6 dBi)<br>11dBm/MHz<br>11dBm/MHz<br>30dBm/500kHz                                                                        | -- | -- | Remark 2)                                                  |
| Maximum e.i.r.p. power      | Antenna terminal (conducted) + Antenna Gain | §15.407(a)<br>(1)(iv)<br>5.15-5.25 GHz Client devices<br>(2)<br>5.25-5.35 GHz &<br>5.47-5.725 GHz<br>(3)<br>5.725-5.85 GHz | RSS-247, Issue 2 Chapter<br>6.2.1.1<br>6.2.2.1<br>6.2.3.1<br>6.2.4.1 | e.i.r.p. Limits (if Antenna Gain < 6 dBi)<br>250 mW + 6 dBi<br>lesser of 250mW or 11dBm+10logB + 6 dBi<br>1 W + 6 dBi                                                    | 2  | 1  | Not Tested + Applicants declaration: Antenna Gain 4.62 dBi |
| Antenna gain information    | Antenna terminal (conducted)                | §15.407(a)<br>(1)(2)(3)                                                                                                    | RSS-247, Issue 2 chapter<br>6.2.1.1<br>6.2.2.1<br>6.2.3.1<br>6.2.4.1 | < 6dBi or if Antenna directional Gain > 6dBi reduction of Max. power & power spectral density by the amount in dB that the directional gain of the antenna exceeds 6 dBi | -- | -- | Applicants declaration: Antenna Gain 4.62 dBi              |

|                                                                                                |                                                |                                                             |                                                                                                                                                                                    |                                                                                                                                                                                                                                              |    |    |                                                        |
|------------------------------------------------------------------------------------------------|------------------------------------------------|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|----|--------------------------------------------------------|
| General field strength emissions within restricted bands<br>+<br>Band-Edge compliance radiated | Enclosure + Inter-connecting cables (radiated) | §15.407(b)(1)(2)(3)(4)(5)(6)(7)(8)<br><br>§15.205 + §15.209 | RSS-Gen., Issue 4 +<br>RSS-247, Issue 2 Chapter 6.2.1.2, 6.2.2.2, 6.2.3.2, +<br>6.2.4.2<br>RSS-Gen., Issue 4 +<br>RSS-247, Issue 2 Chapter 6.2.1.2, 6.2.2.2, 6.2.3.2, +<br>6.2.4.2 | 5150-5250 MHz   5250-5350 MHz 5470-5725 MHz<br>all emissions outside operating band shall not exceed -27 dBm/MHz e.i.r.p.<br><br>5725-5850 MHz Spectrum Mask acc. to (4)(i)<br><br>Restricted band limits +<br>General field strength limits | 1  | 1  | Pass                                                   |
| Transmit power control +<br>Dynamic frequency selection (DFS)                                  | Antenna terminal (conducted)                   | §15.407 (h1)(h2)                                            | RSS-Gen., Issue 4 +<br>RSS-247, Issue 2 Chapter 6.3                                                                                                                                | Requirements:<br>Masters<br>Active clients<br>Passive clients                                                                                                                                                                                | -- | -- | Remark 3)                                              |
| Discontinuous transmissions +<br>Device security                                               | FIRMWARE                                       | §15.407(c) +<br>§15.407(i)                                  | RSS-247, Issue 2 Chapter 6.4 a + b + c                                                                                                                                             | No transmissions in case of either absence of information to transmit or operational failure +<br>Protection of firmware by unauthorized parties                                                                                             | -- | -- | Not tested<br>Applicants declaration of implementation |
| AC-Power Lines Conducted Emissions                                                             | AC-Power lines or Battery Charger              | §15.207(a)                                                  | RSS-Gen., Issue 4: Chapter 8.8 Table 3                                                                                                                                             | AC Power line conducted limits                                                                                                                                                                                                               | -- | -- | Remark 1)                                              |

Remark 1) : **Not tested in this report as Bluetooth test configuration was operated using fully charged internal battery**

**Refer separate report 18-1-0050701T05a**

Remark 2): Refer SIMT 1502 (FCC ID: UDV-20170406) Report No. ER/2017/50038, issue date Aug 09,2017

Remark 3): Refer SIMT 1502 (FCC ID: UDV-20170406) Report No. ER/2017/50039, issue date Jun 13,2017

| Specific Absorption Rate (SAR) Measurements<br>(separation distance user to RF-radiating element within 20cm) |                                                              |                                                                      |                                                                                                                                                                                     |               |                    |                                                           |
|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------|-----------------------------------------------------------|
| Test cases                                                                                                    | Port                                                         | References & Limits                                                  |                                                                                                                                                                                     | EUT<br>set-up | EUT<br>op.<br>mode | Result                                                    |
|                                                                                                               |                                                              | FCC Standard                                                         | Test Limit                                                                                                                                                                          |               |                    |                                                           |
| Specific<br>Absorption<br>Rate (SAR)<br>requirements                                                          | Cabinet<br>+<br>Inter-<br>connecting<br>cables<br>(radiated) | §2.1091<br>§2.1093<br>+<br>IEEE 1528-2013<br>+<br>KDB 865664D01v0r04 | <b>Specific Absorption<br/>Rate (SAR)</b> for<br>Devices Used by the<br>General Public<br><b>(Uncontrolled<br/>Environment)</b><br>: 1.6 W/Kg as<br>averaged over any 1 g<br>tissue | --            | --                 | Refer test report<br>Test report no.:<br>18-1-0050701T01a |

General remark: results valid with power 12.5 setting, see document JTA6DG Test instructions

Test report 18-1-0050701T04a\_C02 dated 2018-09-25 replace test report 18-1-0050701T04a\_C01, dated 2018-09-07. The replaced report gets invalid herewith.

## 1.2. Attestation:

I declare that all measurements were performed by me or under my supervision and that all measurements have been performed and are correct to my best knowledge and belief to Innovation , Science and Economic Development (ISED) Canada standards. All requirements as shown in above table are met in accordance with enumerated standards.

 Digital unterschrieben  
von Niels Jeß  
DN: cn=Niels Jeß,  
o=CETECOM GmbH,  
ou=Branch  
Duesseldorf,  
email=niels.jess@cete  
com.com, c=DE  
Datum: 2018.09.25  
23:15:01 +02'00'

.....  
Dipl.-Ing. Niels Jeß  
Responsible for test section

 Digital unterschrieben  
von B.Sc. Mohamed  
Ahmed  
DN: cn=B.Sc. Mohamed  
Ahmed, o=Cetecom  
GmbH, ou=RC/EMC,  
email=mohamed.ahmed  
@cetecom.com, c=DE  
Datum: 2018.09.25  
13:05:18 +02'00'

.....  
B.Sc. Mohamed Ahmed  
Responsible for test report

## 2. Administrative Data

### 2.1. Identification of the testing laboratory

|                                     |                                                      |
|-------------------------------------|------------------------------------------------------|
| Company name:                       | CETECOM GmbH                                         |
| Address:                            | Im Teelbruch 116<br>45219 Essen - Kettwig<br>Germany |
| Responsible for testing laboratory: | Dipl.-Ing. Niels Jeß                                 |

### 2.2. Test location

#### 2.2.1. Test laboratory “CTC”

|               |                                                           |
|---------------|-----------------------------------------------------------|
| Company name: | see chapter 2.1. Identification of the testing laboratory |
|---------------|-----------------------------------------------------------|

### 2.3. Organizational items

|                              |                          |
|------------------------------|--------------------------|
| Responsible for test report: | B.Sc. Mohamed Ahmed      |
| Responsible for project:     | Dipl.-Ing. Ninovic Perez |
| Receipt of EUT:              | 2018-01-08               |
| Date(s) of test:             | 2018-03-12 - 2018-03-20  |
| Date of report:              | 2018-09-25               |
| -----                        |                          |
| Version of template:         | 13.02                    |

### 2.4. Applicant's details

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| Applicant's name: | Datalogic S.r.l.                                                       |
| Address:          | Via S. Vitalino, 13<br>40012, Lippo di Calderara di Reno (BO)<br>ITALY |
| Contact :         | Mr. Francesco Rossi                                                    |

### 2.5. Manufacturer's details

|                      |                   |
|----------------------|-------------------|
| Manufacturer's name: | same as Applicant |
| Address:             | same as Applicant |

### 3. Equipment under test (EUT)

#### 3.1. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant

|                                                                                                                   |                                                                                                                                                                                                                                                                |                                                          |                                                      |
|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|------------------------------------------------------|
| Frequency   Channel   B.W.<br>(USA bands only)**                                                                  | U-NII 1: 5150-5250 MHz                                                                                                                                                                                                                                         | <input checked="" type="checkbox"/> Ch 36   40   44   48 | <input checked="" type="checkbox"/> Bandwidth 20 MHz |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input type="checkbox"/> Ch. 38   46                     | <input type="checkbox"/> Bandwidth 40 MHz            |
|                                                                                                                   | U-NII2A: 5250-5350 MHz                                                                                                                                                                                                                                         | <input checked="" type="checkbox"/> Ch 52   56   60   64 | <input checked="" type="checkbox"/> Bandwidth 20 MHz |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input type="checkbox"/> Ch. 54   62                     | <input type="checkbox"/> Bandwidth 40 MHz            |
|                                                                                                                   | U-NII 2C: 5470-5725 MHz                                                                                                                                                                                                                                        | <input checked="" type="checkbox"/> Ch 100   104   108   | <input checked="" type="checkbox"/> Bandwidth 20 MHz |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input checked="" type="checkbox"/> Ch 112   116   120   |                                                      |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input checked="" type="checkbox"/> Ch 124   128   132   |                                                      |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input checked="" type="checkbox"/> Ch 136   140         |                                                      |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input type="checkbox"/> Ch. 102   110   118             |                                                      |
|                                                                                                                   |                                                                                                                                                                                                                                                                | <input type="checkbox"/> Ch 126   134                    | <input type="checkbox"/> Bandwidth 40 MHz            |
| U-NII 3: 5725 -5850 MHz                                                                                           | <input checked="" type="checkbox"/> Ch 149   153   157                                                                                                                                                                                                         | <input checked="" type="checkbox"/> Bandwidth 20 MHz     |                                                      |
|                                                                                                                   | <input checked="" type="checkbox"/> Ch 161   165                                                                                                                                                                                                               |                                                          |                                                      |
|                                                                                                                   | <input type="checkbox"/> Ch 151   159                                                                                                                                                                                                                          | <input type="checkbox"/> Bandwidth 40 MHz                |                                                      |
| Channels Power Settings                                                                                           | +20 dBm (According to Applicant's Declaration Max. Rated Power Values)                                                                                                                                                                                         |                                                          |                                                      |
| 802.11a – Mode OFDM<br>Modulation   Data Rates                                                                    | <input checked="" type="checkbox"/> BPSK   6 Mbit / 9 Mbit<br><input checked="" type="checkbox"/> QPSK   12 Mbit / 18 Mbit<br><input checked="" type="checkbox"/> 16-QAM   24 Mbit / 36 Mbit<br><input checked="" type="checkbox"/> 64-QAM   48 Mbit / 54 Mbit |                                                          |                                                      |
| 802.11n – Mode OFDM<br>Modulation   Data Rates                                                                    | <input checked="" type="checkbox"/> HT20 (MCS0 – MCS7)   7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbit<br><input type="checkbox"/> HT40 (MCS0 – MCS7)   15/30/45/60/90/120/135/150 Mbit                                                                            |                                                          |                                                      |
| Antenna Details                                                                                                   | Integrated (ANT1 & ANT2)                                                                                                                                                                                                                                       |                                                          |                                                      |
| Antenna Connections                                                                                               | Primary Antenna: ANT1(WLAN 5 GHz)   Secondary Antenna: ANT2 not used                                                                                                                                                                                           |                                                          |                                                      |
| ANT1 Gain (Peak)                                                                                                  | 4.62 dBi (4900 MHz – 5900 MHz) (According to Applicant's Declaration)                                                                                                                                                                                          |                                                          |                                                      |
| ANT2 Gain (Peak)                                                                                                  | 2.14 dBi (2400 MHz – 2482,5 MHz) (According to Applicant's Declaration)                                                                                                                                                                                        |                                                          |                                                      |
| Total Number of Modules                                                                                           | 1                                                                                                                                                                                                                                                              |                                                          |                                                      |
| Total Number of Antennas                                                                                          | 2   Primary ANT1 : WLAN 5 GHz   Secondary ANT2: not used                                                                                                                                                                                                       |                                                          |                                                      |
| Test Mode Settings                                                                                                | Datalogic WiFi Test Application                                                                                                                                                                                                                                |                                                          |                                                      |
| MAX Field Strength<br>(Radiated@3m)                                                                               | U-NII 1: 5150-5250 MHz                                                                                                                                                                                                                                         | 102.998 dBµV/m (PK)                                      | 93.098 dBµV/m (AV)                                   |
|                                                                                                                   | U-NII2A: 5250-5350 MHz                                                                                                                                                                                                                                         | 104 dBµV/m (PK)                                          | 93.521 dBµV/m (AV)                                   |
|                                                                                                                   | U-NII 2C: 5470-5725 MHz                                                                                                                                                                                                                                        | 102.806 dBµV/m (PK)                                      | 92.872 dBµV/m (AV)                                   |
|                                                                                                                   | U-NII 3: 5725-5850 MHz                                                                                                                                                                                                                                         | 95.754 dBµV/m (PK)                                       | 85.051 dBµV/m (AV)                                   |
| Power Supply                                                                                                      | <input checked="" type="checkbox"/> Internal Battery: Li-ion   3.75- 4.35VDC 3030mAh                                                                                                                                                                           |                                                          |                                                      |
| Special EMI Components                                                                                            | --                                                                                                                                                                                                                                                             |                                                          |                                                      |
| EUT Sample Type                                                                                                   | <input type="checkbox"/> Production                                                                                                                                                                                                                            | <input checked="" type="checkbox"/> Pre-Production       | <input type="checkbox"/> Engineering                 |
| Firmware                                                                                                          | <input type="checkbox"/> for normal use   <input checked="" type="checkbox"/> Special version for test execution : Datalogic WiFi Test                                                                                                                         |                                                          |                                                      |
| FCC label attached                                                                                                | <input type="checkbox"/> Yes                                                                                                                                                                                                                                   | <input checked="" type="checkbox"/> No                   |                                                      |
| For further details refer Applicants Declaration & following technical documents                                  |                                                                                                                                                                                                                                                                |                                                          |                                                      |
| Description of Reference Document (supplied by applicant)                                                         | Version                                                                                                                                                                                                                                                        |                                                          | Total Pages                                          |
| Operational Description_JOYA TOUCH A6                                                                             | Rev: 02 Date: 11-May-2018                                                                                                                                                                                                                                      |                                                          | 9                                                    |
| JTA6_FCC_Safety_&_Regulatory_addendum                                                                             | Rev: A Date: April-2018                                                                                                                                                                                                                                        |                                                          | 15                                                   |
| JTA: Test Instructions                                                                                            | Rev: 01 Date: 17-May-2018                                                                                                                                                                                                                                      |                                                          | 18                                                   |
| ** Until further notice, devices subject to RSS-247, Issue 2, February 2017 section 6.2.3                         |                                                                                                                                                                                                                                                                |                                                          |                                                      |
| <b>Operating in Frequency bands 5470-5600 MHz and 5650-5725 MHz shall not transmit in the band 5600-5650 MHz.</b> |                                                                                                                                                                                                                                                                |                                                          |                                                      |
| This restriction is for the protection of Environment Canada's weather radars operating in this band.             |                                                                                                                                                                                                                                                                |                                                          |                                                      |

### 3.2. EUT: Type, S/N etc. and short descriptions used in this test report

| Short Description*) | EUT                                      | Type                | Serial Number | Hardware Status | Software Status |
|---------------------|------------------------------------------|---------------------|---------------|-----------------|-----------------|
| EUT A               | Joya Touch A6<br>(Gun Variant)           | A00AN04HLXGT0A<br>N | G18D03796     | BETA            | 02.12           |
| EUT B               | Joya Touch A6<br>(Gun Variant conducted) | A00AN04HLXGT0AN     | G18D03791     | BETA            | 02.12           |
| EUT C               | Joya Touch A6<br>(Handheld Variant)      | A00AN04HLXHT0AN     | G18D03794     | BETA            | 02.12           |

\*) EUT short description is used to simplify the identification of the EUT in this test report.

### 3.3. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

| AE short description *) | Auxiliary Equipment | Type | S/N serial number | HW hardware status | SW software status |
|-------------------------|---------------------|------|-------------------|--------------------|--------------------|
| AE 1                    | --                  | --   | --                | --                 | --                 |

\*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

### 3.4. EUT set-ups

| EUT set-up no. *) | Combination of EUT and AE | Description              |
|-------------------|---------------------------|--------------------------|
| set. 1            | EUT A                     | Used for radiated tests  |
| set. 2            | EUT B                     | Used for conducted tests |
| set. 3            | EUT C                     | Used for radiated tests  |

\*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.


### 3.5. EUT operating modes

| EUT operating mode no. *1) | Description of operating modes | Additional information                                                                                                         |
|----------------------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| op. 1                      | TX-Mode                        | With help of special test Software (CTA-WIFI Test Tool, Version: 1.0.0) a continuous traffic mode in duty cycle was set-up *2) |

\*1) EUT operating mode no. is used to simplify the test report.

\*2) ) Please refer to document “20180613\_FCC\_JTA\_Test-Tools\_Quick\_Start\_Instructions” dated 2018-06-13 for additional information regarding operating mode setup and output power levels.

The Test Software CTA-WIFI Test Tool was implemented on the EUT



Wifi Settings for each mode and Channel:

|       |         |           |                  |               |      |
|-------|---------|-----------|------------------|---------------|------|
| 5 GHz | 802.11a | 54Mbps    | 802.11 a/g rates | 11A_54_MBPS   | 11   |
|       |         | 48Mbps    | 802.11 a/g rates | 11A_48_MBPS   | 12   |
|       |         | 36Mbps    | 802.11 a/g rates | 11A_36_MBPS   | 12.5 |
|       |         | 24Mbps    | 802.11 a/g rates | 11A_24_MBPS   | 12.5 |
|       |         | 18Mbps    | 802.11 a/g rates | 11A_18_MBPS   | 12.5 |
|       |         | 12Mbps    | 802.11 a/g rates | 11A_12_MBPS   | 12.5 |
|       |         | 9Mbps     | 802.11 a/g rates | 11A_9_MBPS    | 12.5 |
|       |         | 6Mbps     | 802.11 a/g rates | 11A_6_MBPS    | 12.5 |
|       | 802.11n | MCS7-HT20 | MCS (20MHz)      | MCS_72_2_MBPS | 9    |
|       |         | MCS6-HT20 | MCS (20MHz)      | MCS_58_5_MBPS | 10.5 |
|       |         | MCS5-HT20 | MCS (20MHz)      | MCS_52_MBPS   | 12   |
|       |         | MCS4-HT20 | MCS (20MHz)      | MCS_39_MBPS   | 12.5 |
|       |         | MCS3-HT20 | MCS (20MHz)      | MCS_26_MBPS   | 12.5 |
|       |         | MCS2-HT20 | MCS (20MHz)      | MCS_19_5_MBPS | 12.5 |
|       |         | MCS1-HT20 | MCS (20MHz)      | MCS_13_MBPS   | 12.5 |
|       |         | MCS0-HT20 | MCS (20MHz)      | MCS_6_5_MBPS  | 12.5 |

## 4. Description of test system set-up's

### 4.1. Test system set-up for conducted measurements on antenna port


#### Conducted Set-up W1

##### Conducted RF-Setup 1 (W1 Set-up)

#### General description:

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to the power meter (3) for conducted power measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings.

#### Schematic:



#### Testing method:

ANSI C63.10:2013,  
KDB 789033 D02 General UNII Test Procedures New Rules v01r03

#### Used Equipment

##### Passive Elements

- ☒ 20 dB Attenuator
- ☒ Low loss RF-cables
- ☒

##### Test Equipment

- ☒ Power Meter
- ☒ DC-Power Supply
- ☒ Spectrum-Analyser

##### Remark:

See List of equipment under each test case and chapter 6 for calibration info

#### Measurement uncertainty

See chapter 5.7


## Conducted Set-up W2

### Conducted RF-Setup 2 (W2 Set-up)

#### General description:

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to spectrum-analyzer (4) for RF-conducted measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings of the spectrum-analyzer.

#### Schematic:



#### Testing method:

ANSI C63.10:2013,  
KDB 789033 D02 General UNII Test Procedures New Rules v01r03

#### Used Equipment

| Passive Elements                                       | Test Equipment                                        | Remark:                                                                       |
|--------------------------------------------------------|-------------------------------------------------------|-------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> 20 dB Attenuator   | <input checked="" type="checkbox"/> Power Meter       | See List of equipment under each test case and chapter 6 for calibration info |
| <input checked="" type="checkbox"/> Low loss RF-cables | <input checked="" type="checkbox"/> DC-Power Supply   |                                                                               |
|                                                        | <input checked="" type="checkbox"/> Spectrum-Analyser |                                                                               |

#### Measurement uncertainty

See chapter 5.7


## 4.2. Test system set-up for radiated magnetic field measurements below 30 MHz

**Specification:** ANSI C63.4-2014 §5.3, §8.2.1, §8.3.1.1+§8.3.2.1 , ANSI C63.10-2013 chapter 6.4 (§6.4.4.2)

**General Description:** Evaluating the radiated field emissions are done first by an exploratory emission measurement and a final measurement for most critical frequencies determined.

The loop antenna was placed at 1 m height above ground plane and 3 m measurement distance from set-up for investigations. Because of reduced measurement distance, correction data were applied, as stated in chapter “General Limit - Radiated field strength emissions below 30 MHz“. The tests are performed in the semi anechoic room recognized by the regulatory commission.

**Schematic:**



**Testing method:**

### Exploratory, preliminary measurement

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (step 90°, range 0° to 360°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT), the emission spectrum was recorded. The loop antenna was moved at least to 2-perpendicular axes (antenna vector in direction of EUT and parallel to EUT) in order to maximize the emissions. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a data reduction table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position).

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A$$

$$M = L_T - E_C$$

AF = Antenna factor

C<sub>L</sub> = Cable loss

D<sub>F</sub> = Distance correction factor

E<sub>C</sub> = Electrical field – corrected value

E<sub>R</sub> = Receiver reading

G<sub>A</sub> = Gain of pre-amplifier (if used)

L<sub>T</sub> = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

**Distance correction:**

Reference for applied correction (extrapolating) factors due to reduced measurement distance:


ANSI C63.10:2013, §6.4.4.2 - Equations (2) + (3) + (4)

### 4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz

**Specification:** ANSI C63.4-2014 chapter 8.2.3, ANSI C63.10-2013 chapter 6.5

**General Description:** Evaluating the field emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a NSA-compliant semi anechoic room (SAR) recognized by the regulatory commissions.

**Schematic:**



**Testing method:**

#### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 90°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

Measurement antenna: horizontal and vertical, heights: 1,0 m and 1,82 m as worst-case determined by an exploratory emission measurements. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

#### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc. either on 10m OATS or 3m semi-anechoic room.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position). The measurement antenna height between 1 m and 4 m.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

AF = Antenna factor

C<sub>L</sub> = Cable loss

D<sub>F</sub> = Distance correction factor (if used)

E<sub>C</sub> = Electrical field – corrected value

E<sub>R</sub> = Receiver reading

G<sub>A</sub> = Gain of pre-amplifier (if used)

L<sub>T</sub> = Limit

M = Margin


All units are dB-units, positive margin means value is below limit.

## 4.4. Test system set-up for radiated electric field measurement above 1 GHz

**Specification:** ANSI C63.4-2014 chapter 8.3, ANSI C63.10-2013 chapter 6.6.3.3 & 6.6.4

**General Description:** Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 16-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

**Schematic:**



**Testing method:**

### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.55 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 15°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined. Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out. On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

$E_C$  = Electrical field – corrected value  
 $E_R$  = Receiver reading  
 $M$  = Margin  
 $L_T$  = Limit  
 $AF$  = Antenna factor  
 $C_L$  = Cable loss  
 $D_F$  = Distance correction factor (if used)  
 $G_A$  = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

## 5. Measurements

### 5.1. Duty-Cycle

5.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

|                             |                                                         |                                              |                                                                                |                                                    |                                          |                                      |
|-----------------------------|---------------------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------|----------------------------------------------------|------------------------------------------|--------------------------------------|
| Ambient Climatic conditions |                                                         |                                              | Temperature: (22±2)°C                                                          |                                                    | Rel. humidity: (45±15)%                  |                                      |
| Test Site                   | <input type="checkbox"/> 441 EMI SAR                    | <input type="checkbox"/> 348 EMI cond.       | <input type="checkbox"/> 443 EMI FAR                                           | <input checked="" type="checkbox"/> 347 Radio.lab. | <input type="checkbox"/> 337 OATS        | <input type="checkbox"/>             |
| Equipment                   | <input type="checkbox"/> 331 HC 4055                    | <input type="checkbox"/>                     | <input type="checkbox"/>                                                       | <input checked="" type="checkbox"/> 693 TS8997     | <input type="checkbox"/>                 | <input type="checkbox"/>             |
| Spectr. Analys.             | <input checked="" type="checkbox"/> 683 FSU26           | <input type="checkbox"/> 120 FSEM            | <input type="checkbox"/> 264 FSEK                                              | <input checked="" type="checkbox"/> 693 TS8997     | <input type="checkbox"/>                 | <input type="checkbox"/>             |
| Power Meter                 | <input type="checkbox"/> 262 NRV-S                      | <input type="checkbox"/> 266 NRV-Z31         | <input type="checkbox"/> 265 NRV-Z33                                           | <input type="checkbox"/> 261 NRV-Z55               | <input type="checkbox"/> 356 NRV-Z1      | <input type="checkbox"/>             |
| Multimeter                  | <input type="checkbox"/> 341 Fluke 112                  | <input type="checkbox"/>                     | <input type="checkbox"/>                                                       | <input type="checkbox"/>                           | <input type="checkbox"/>                 | <input type="checkbox"/>             |
| DC Power                    | <input type="checkbox"/> 086 LNG50-10                   | <input type="checkbox"/> 087 EA3013          | <input type="checkbox"/> 354 NGPE 40                                           | <input type="checkbox"/> 349 car battery           | <input type="checkbox"/> 350 Car battery | <input type="checkbox"/> 463 HP3245A |
| Supply Voltage              | <input type="checkbox"/> 230 V 50 Hz via public mains   |                                              | <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery) |                                                    |                                          |                                      |
| Otherwise                   | <input checked="" type="checkbox"/> 530 Attenuator 10dB | <input checked="" type="checkbox"/> K4 Cable |                                                                                |                                                    |                                          |                                      |

Method of measurement: ☒ conducted  
☐ radiated

**A special firmware program is used for test purposes. In contrast to normal operating mode a higher duty-cycle is set in order to facilitate the measurements. This is maximized at the extent possible.**

The necessary duty-cycle correction factor is determined on nominal conditions on 1 channel for all sub-bands. It is assumed that no noticeable changes occur when tested on other channels or climatic conditions.

Calculated with following formulas:

|             |                                                   |                                                           |
|-------------|---------------------------------------------------|-----------------------------------------------------------|
| Duty cycle: | $x = \frac{T_{x_{on}}}{T_{x_{on}} + T_{x_{off}}}$ | Duty cycle factor [dB]: $10 \log\left(\frac{1}{x}\right)$ |
|-------------|---------------------------------------------------|-----------------------------------------------------------|

| DUTY-CYCLE Measurement                     |          |          |          |                                 |                                  |               |                                        |            |
|--------------------------------------------|----------|----------|----------|---------------------------------|----------------------------------|---------------|----------------------------------------|------------|
| WLAN 5 GHz                                 | Marker 1 | Marker 2 | Marker 3 | TX ON<br>Marker 2 -<br>Marker 1 | TX OFF<br>Marker 3 -<br>Marker 2 | Duty Cycle    | Correction-<br>Factor:<br>100log(1/DC) | Plot No.   |
| Data Rate                                  | ms       | ms       | ms       | ms                              | ms                               | (%)           | (dB)                                   | (Remark 1) |
| WLAN 5 GHz a-Mode   Ch 36 (5180 MHz)       |          |          |          |                                 |                                  |               |                                        |            |
| 6MBit                                      | 0,496440 | 1,856090 | 2,054107 | 1,359650                        | 0,19802                          | <b>87,29</b>  | <b>0,59</b>                            | 1          |
| 18MBit                                     | 0,050641 | 0,516824 | 0,717051 | 0,466183                        | 0,20023                          | <b>69,95</b>  | <b>1,55</b>                            | 1          |
| 54MBit                                     | 0,166026 | 0,336536 | 0,536763 | 0,170510                        | 0,20023                          | <b>45,99</b>  | <b>3,37</b>                            | 2          |
| WLAN 5 GHz n(HT20)-Mode   Ch 36 (5180 MHz) |          |          |          |                                 |                                  |               |                                        |            |
| MCS0                                       | 1,306821 | 2,443859 | 2,629782 | 1,13704                         | 0,18592                          | <b>85,95%</b> | <b>0,66</b>                            | 3          |
| MCS4                                       | 0,288622 | 0,530642 | 0,731474 | 0,24202                         | 0,20083                          | <b>54,65%</b> | <b>2,62</b>                            | 4          |
| MCS7                                       | 0,607141 | 0,767869 | 0,966506 | 0,16073                         | 0,19864                          | <b>44,73%</b> | <b>3,49</b>                            | 4          |

For power averaging (RMS) factor 10\*log10(1/x) was used

- ☒ The results were corrected in order to evaluate for worst-case result each time when average values are necessary for example average radiated emissions or similar  
☐ No correction necessary: Duty-Cycle > 98%

## 5.2. RF-Parameter - Transmitter Peak output power (conducted and radiated)

### 5.2.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

|                 |                                                                    |                                                |                                                                                |                                                    |                                                    |                                      |
|-----------------|--------------------------------------------------------------------|------------------------------------------------|--------------------------------------------------------------------------------|----------------------------------------------------|----------------------------------------------------|--------------------------------------|
| test location   | <input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1) |                                                | <input type="checkbox"/> 443 System CTC-FAR-EMI-                               |                                                    | <input type="checkbox"/> Please see Chapter. 2.2.3 |                                      |
| test site       | <input type="checkbox"/> 441 EMI SAR                               | <input type="checkbox"/> 487 SAR NSA           | <input type="checkbox"/> 337 OATS                                              | <input checked="" type="checkbox"/> 347 Radio.lab. | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| receiver        | <input type="checkbox"/> 377 ESCS30                                | <input type="checkbox"/> 001 ESS               | <input type="checkbox"/> 489 ESU 40                                            | <input type="checkbox"/> 620 ESU 26                | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| otherwise       | <input checked="" type="checkbox"/> 600 NRVD                       | <input checked="" type="checkbox"/> 357 NRV-Z1 | <input checked="" type="checkbox"/> 693 TS8997                                 |                                                    |                                                    |                                      |
| spectr. analys. | <input type="checkbox"/> 215 FSU                                   | <input type="checkbox"/> 120 FSEM              | <input type="checkbox"/> 264 FSEK                                              | <input type="checkbox"/>                           | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| power supply    | <input type="checkbox"/> 456 EA 3013A                              | <input type="checkbox"/> 457 EA 3013A          | <input type="checkbox"/> 459 EA 2032-50                                        | <input type="checkbox"/> 268 EA- 3050              | <input type="checkbox"/> 494 AG6632A               | <input type="checkbox"/> 354 NGPE 40 |
| otherwise       | <input checked="" type="checkbox"/> 613 20 dB Attenuator           | <input type="checkbox"/> 248 6 dB Attenuator   | <input type="checkbox"/> 529 Power divider                                     | <input type="checkbox"/> - cable OTA20             | <input type="checkbox"/> 530 10dB Atten            | <input type="checkbox"/> K5 Cable    |
| Supply voltage  | <input type="checkbox"/> 230 V 50 Hz via public mains              |                                                | <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery) |                                                    |                                                    |                                      |

### 5.2.2. Reference:

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FCC</b>              | <input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(a)(1)(2)(3)(4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>ISED</b>             | <input checked="" type="checkbox"/> RSS-247, Issue 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>ANSI</b>             | <input checked="" type="checkbox"/> C63.10-2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>KDB Guidance no.</b> | <input checked="" type="checkbox"/> KDB 789033 D02 General UNII Test Procedures New Rules v01r03: Subchapter E, <u>Method PM (3)(a)</u><br><input type="checkbox"/> KDB 662911 D01 Multiple Transmitter Output v02r01 ( MIMO, Smart-antenna)                                                                                                                                                                                                                                                                                                                                                     |
| <b>Limits</b>           | <input checked="" type="checkbox"/> U-NII 1: 5.15-5.25 GHz:<br><b>FCC Outdoor access point:</b> 1W + antenna gain max. 6dBi + Elevation > 30° 21 dBm EIRP<br><b>FCC Indoor Access Point:</b> 1W + antenna gain max. 6dBi<br><b>FCC Mobile &amp; Portable client:</b> 250mW + antenna gain max. 6dBi<br><br><b>ISED:</b><br><input checked="" type="checkbox"/> E.I.R.P. max. 200mW or $10+10\log_{10}(B)$ whichever power is less<br><input type="checkbox"/> OEM device installed on vehicles: 30mW EIRP or $1.76 + 10\log_{10}(B) + \text{TPC capability}$                                     |
|                         | <input checked="" type="checkbox"/> U-NII2: 5.25-5.35 GHz:<br><b>FCC:</b> lesser of 250mW or $11\text{dBm}+10\log_{10}(B)$<br><br><b>ISED:</b><br><input checked="" type="checkbox"/> max. conducted output power: 250mW or $11\text{dBm}+10\log_{10}(B) + \text{Antenna gain} < 6\text{dBi}$<br><input type="checkbox"/> EIRP Elevation Mask requirements if max. EIRP>200mW<br><input type="checkbox"/> Max. EIRP 1Watt or $17+10\log_{10}(B)$ whichever power less<br><input type="checkbox"/> OEM device installed on vehicles: 30mW EIRP or $1.76 + 10\log_{10}(B) + \text{TPC capability}$ |
|                         | <input checked="" type="checkbox"/> U-NII2extension: 5.470-5.725 GHz:<br><b>FCC:</b> lesser of 250mW or $11\text{dBm}+10\log_{10}(B) + \text{Antenna gain} < 6\text{dBi}$<br><br><b>ISED:</b><br><input checked="" type="checkbox"/> Lesser of: lesser of 250mW or $11\text{dBm}+10\log_{10}(B)$<br><input checked="" type="checkbox"/> Max. EIRP 1Watt or $17+10\log_{10}(B)$ whichever power less<br><input type="checkbox"/> TPC required if MAX. EIRP > 500mW                                                                                                                                |
|                         | <input checked="" type="checkbox"/> U-NII3: 5.725-5.850 GHz:<br><b>FCC/ISED:</b><br><input checked="" type="checkbox"/> max. conducted power: 1 Watt (30dBm)<br><input checked="" type="checkbox"/> Antenna gain less 6dBi<br><input type="checkbox"/> Antenna gain more 6dBi (-> reduction necessary)                                                                                                                                                                                                                                                                                           |

### 5.2.3. Antenna characteristics:

- ☒ directional gain < 6 dBi (Applicants declaration)  
☐ directional gain > 6 dBi (measured / applicant's declaration) -> conducted power reduction necessary

### 5.2.4. EUT settings:

The EUT was instructed to send with maximum power (if adjustable) according applicants instructions.

### 5.2.5. Measurement method:

| Method used                                     | Reference to KDB                                                | Remarks:                                                                                                                                                                                                                                                                    |
|-------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> SA                     | KDB 789033 D02 General UNII Test Procedures<br>New Rules v01r03 | Integration bandwidth method                                                                                                                                                                                                                                                |
| <input checked="" type="checkbox"/> Power Meter | a.) Method PM                                                   | A wideband thermocouple RF-power meter as described by KDB was used.<br><input checked="" type="checkbox"/> Duty-Cycle correction necessary<br><input type="checkbox"/> A value correction is not necessary since the EUT is transmitting continuously at duty-cycle > 98%. |

### 5.2.6. Conducted power measurement and EIRP calculations

- Applicant's declared Maximum Directional Antenna Peak Gain : 4.62 dBi at 5 GHz Band Range

### 5.2.7. Results for a-Mode:

| FCC15.407 Limits & Verdict              |                                  |                                   |                                   |                            |
|-----------------------------------------|----------------------------------|-----------------------------------|-----------------------------------|----------------------------|
| Operational Bands:                      | U-NII 1 (Conducted + EIRP limit) | U-NII-2A (conducted + EIRP limit) | U-NII 2C (conducted + EIRP limit) | U-NII 3 (conducted + EIRP) |
| Highest Conducted Value Subband [dBm]   | 12,41                            | 12,17                             | 10,35                             | 11,88                      |
| Duty-Cycle correction [dB]              | 1,55                             | 1,55                              | 1,55                              | 1,55                       |
| Conducted value including DC-correction | 13,96                            | 13,72                             | 11,90                             | 13,43                      |
| Conducted Limits or EIRP [dBm]          | 23,97                            | 23,36                             | 23,36                             | 30,00                      |
| Conducted value - margin to Limit [dB]  | 11,56                            | 11,19                             | 13,02                             | 18,12                      |
| Conducted Verdict PASS / FAIL ?         | PASS                             | PASS                              | PASS                              | PASS                       |
| Antenna Gain [dBi]                      | 4,62                             | 4,62                              | 4,62                              | 4,62                       |
| Highest E.I.R.P. Value Subband [dBm]    | 18,58                            | 18,34                             | 16,52                             | 18,05                      |
| E.I.R.P. Limits [dBm]                   | 29,98                            | 29,36                             | 29,36                             | 36,00                      |
| Margin to E.I.R.P. Limits [dB]          | 11,40                            | 11,02                             | 12,85                             | 17,95                      |
| E.I.R.P. Verdict PASS / FAIL ?          | PASS                             | PASS                              | PASS                              | PASS                       |

| RSS-247, Issue 2, Limits & Verdict           |                      |                                   |                                   |                            |
|----------------------------------------------|----------------------|-----------------------------------|-----------------------------------|----------------------------|
| Operational Bands:                           | U-NII 1 (EIRP limit) | U-NII-2A (conducted + EIRP limit) | U-NII 2C (conducted + EIRP limit) | U-NII 3 (conducted + EIRP) |
| Highest Conducted Value Subband [dBm]        | 12,41                | 12,17                             | 10,35                             | 11,88                      |
| Duty-Cycle correction [dB]                   | 1,55                 | 1,55                              | 1,55                              | 1,55                       |
| Conducted value including DC-correction [dB] | 13,96                | 13,72                             | 11,90                             | 13,43                      |
| Conducted Limits or EIRP [dBm]               | --                   | 23,36                             | 23,36                             | 30,00                      |
| Conducted value - margin to Limit [dB]       | --                   | 11,19                             | 13,02                             | 18,12                      |
| Conducted Verdict PASS / FAIL ?              | --                   | PASS                              | PASS                              | PASS                       |
| Antenna Gain [dBi]                           | 4,62                 | 4,62                              | 4,62                              | 4,62                       |
| Highest E.I.R.P. Value Subband [dBm]         | 18,58                | 18,34                             | 16,52                             | 18,05                      |
| E.I.R.P. Limits [dBm]                        | 22,36                | 29,36                             | 29,36                             | 36,00                      |
| Margin to E.I.R.P. Limits [dB]               | 3,78                 | 11,02                             | 12,85                             | 17,95                      |
| E.I.R.P. Verdict PASS / FAIL ?               | PASS                 | PASS                              | PASS                              | PASS                       |

## 5.2.8. Results for n-Mode:

| FCC15.407 Limits & Verdict                   |                                  |                                   |                                   |                            |
|----------------------------------------------|----------------------------------|-----------------------------------|-----------------------------------|----------------------------|
| Operational Bands:                           | U-NII 1 (Conducted + EIRP limit) | U-NII-2A (conducted + EIRP limit) | U-NII 2C (conducted + EIRP limit) | U-NII 3 (conducted + EIRP) |
| Highest Conducted Value Subband [dBm]        | 12,37                            | 12,21                             | 10,23                             | 12,00                      |
| Duty-Cycle correction [dB]                   | 2,62                             | 0,66                              | 2,62                              | 2,62                       |
| Conducted value including DC-correction [dB] | 14,99                            | 12,87                             | 12,85                             | 14,62                      |
| Conducted Limits or EIRP [dBm]               | 23,97                            | 23,55                             | 23,55                             | 30,00                      |
| Conducted value - margin to Limit [dB]       | 11,61                            | 11,34                             | 13,32                             | 18,00                      |
| Conducted Verdict PASS / FAIL ?              | PASS                             | PASS                              | PASS                              | PASS                       |
| Antenna Gain[dBi]                            | 4,62                             | 4,62                              | 4,62                              | 4,62                       |
| Highest E.I.R.P. Value                       | 19,61                            | 17,49                             | 17,47                             | 19,24                      |
| E.I.R.P. Limits[dBm]                         | 29,98                            | 29,55                             | 29,36                             | 36,00                      |
| Margin to E.I.R.P. Limits [dB]               | 10,38                            | 12,06                             | 11,89                             | 16,76                      |
| E.I.R.P. Verdict PASS / FAIL ?               | PASS                             | PASS                              | PASS                              | PASS                       |

| RSS-247, Issue 2, Limits & Verdict           |                      |                                   |                                   |                            |
|----------------------------------------------|----------------------|-----------------------------------|-----------------------------------|----------------------------|
| Operational Bands:                           | U-NII 1 (EIRP limit) | U-NII-2A (conducted + EIRP limit) | U-NII 2C (conducted + EIRP limit) | U-NII 3 (conducted + EIRP) |
| Highest Conducted Value Subband [dBm]        | 12,37                | 12,21                             | 10,23                             | 12,00                      |
| Duty-Cycle correction [dB]                   | 2,62                 | 0,66                              | 2,62                              | 2,62                       |
| Conducted value including DC-correction [dB] | 14,99                | 12,87                             | 12,85                             | 14,62                      |
| Conducted Limits or EIRP [dBm]               | --                   | 23,55                             | 23,36                             | 30,00                      |
| Conducted value - margin to Limit [dB]       | --                   | 11,34                             | 13,13                             | 18,00                      |
| Conducted Verdict PASS / FAIL ?              | --                   | PASS                              | PASS                              | PASS                       |
| Antenna Gain[dBi]                            | 4,62                 | 4,62                              | 4,62                              | 4,62                       |
| Highest E.I.R.P. Value Subband [dBm]         | 19,61                | 17,49                             | 17,47                             | 19,24                      |
| E.I.R.P. Limits[dBm]                         | 22,55                | 29,55                             | 29,36                             | 36,00                      |
| Margin to E.I.R.P. Limits [dB]               | 2,95                 | 12,06                             | 11,89                             | 16,76                      |
| E.I.R.P. Verdict PASS / FAIL ?               | PASS                 | PASS                              | PASS                              | PASS                       |

## 5.2.9. Verdict: Pass

### 5.3. General Limit - Radiated field strength emissions below 30 MHz

#### 5.3.1. Test location and equipment

|                 |                                                                    |                                             |                                                                                |                                            |                                                    |                                      |
|-----------------|--------------------------------------------------------------------|---------------------------------------------|--------------------------------------------------------------------------------|--------------------------------------------|----------------------------------------------------|--------------------------------------|
| test location   | <input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1) |                                             | <input type="checkbox"/> Please see Chapter. 2.2.2                             |                                            | <input type="checkbox"/> Please see Chapter. 2.2.3 |                                      |
| test site       | <input checked="" type="checkbox"/> 441 EMI SAR                    | <input type="checkbox"/> 487 SAR NSA        | <input type="checkbox"/> 347 Radio.lab.                                        |                                            | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| receiver        | <input type="checkbox"/> 377 ESCS30                                | <input checked="" type="checkbox"/> 001 ESS | <input type="checkbox"/>                                                       | <input type="checkbox"/>                   | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| spectr. analys. | <input type="checkbox"/> 584 FSU                                   | <input type="checkbox"/> 120 FSEM           | <input type="checkbox"/> 264 FSEK                                              | <input type="checkbox"/>                   | <input type="checkbox"/>                           | <input type="checkbox"/>             |
| antenna         | <input type="checkbox"/> 574 BTA-L                                 | <input type="checkbox"/> 133 EMCO3115       | <input type="checkbox"/> 302 BBHA9170                                          | <input type="checkbox"/> 289 CBL 6141      | <input checked="" type="checkbox"/> 030 HFH-Z2     | <input type="checkbox"/> 477 GPS     |
| signaling       | <input type="checkbox"/> 392 MT8820A                               | <input type="checkbox"/> 371 CBT32          | <input type="checkbox"/> 547 CMU                                               | <input type="checkbox"/> 594 CMW           |                                                    |                                      |
| otherwise       | <input type="checkbox"/> 400 FTC40x15E                             | <input type="checkbox"/> 401 FTC40x15E      | <input type="checkbox"/> 110 USB LWL                                           | <input type="checkbox"/> 482 Filter Matrix | <input type="checkbox"/> 378 RadiSense             |                                      |
| DC power        | <input type="checkbox"/> 671 EA-3013S                              | <input type="checkbox"/> 457 EA 3013A       | <input type="checkbox"/> 459 EA 2032-50                                        | <input type="checkbox"/> 268 EA- 3050      | <input type="checkbox"/> 494 AG6632A               | <input type="checkbox"/> 354 NGPE 40 |
| Supply voltage  | <input type="checkbox"/> 230 V 50 Hz via public mains              |                                             | <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery) |                                            |                                                    |                                      |

#### 5.3.2. Requirements

|                 |                                         |                       |              |                                                           |
|-----------------|-----------------------------------------|-----------------------|--------------|-----------------------------------------------------------|
| <b>FCC</b>      | Part 15, Subpart C, §15.205 & §15.209   |                       |              |                                                           |
| <b>ISED</b>     | RSS-Gen: Issue 5: §8.9 Table 6          |                       |              |                                                           |
| <b>ANSI</b>     | C63.10-2013                             |                       |              |                                                           |
| Frequency [MHz] | Field strength limit<br>[μV/m] [dBμV/m] |                       | Distance [m] | Remarks                                                   |
| 0.009 – 0.490   | 2400/f (kHz)                            | 67.6 – 20Log(f) (kHz) | 300          | Correction factor used due to measurement distance of 3 m |
| 0.490 – 1.705   | 24000/f (kHz)                           | 87.6 – 20Log(f) (kHz) | 30           | Correction factor used due to measurement distance of 3 m |
| 1.705 – 30      | 30                                      | 29.5                  | 30           | Correction factor used due to measurement distance of 3 m |

#### 5.3.3. Test condition and test set-up

|                                       |                  |                                                                                                                                                                                                                 |                                            |                                                |
|---------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|------------------------------------------------|
| Signal link to test system (if used): |                  | <input type="checkbox"/> air link                                                                                                                                                                               | <input type="checkbox"/> cable connection  | <input checked="" type="checkbox"/> none       |
| EUT-grounding                         |                  | <input checked="" type="checkbox"/> none                                                                                                                                                                        | <input type="checkbox"/> with power supply | <input type="checkbox"/> additional connection |
| Equipment set up                      |                  | <input checked="" type="checkbox"/> table top                                                                                                                                                                   |                                            | <input type="checkbox"/> floor standing        |
| Climatic conditions                   |                  | Temperature: (22±3°C)                                                                                                                                                                                           |                                            | Rel. humidity: (40±20)%                        |
| EMI-Receiver or Analyzer Settings     | Scan data        | <input checked="" type="checkbox"/> 9 – 150 kHz RBW/VBW = 200 Hz Scan step = 80 Hz<br><input checked="" type="checkbox"/> 150 kHz – 30 MHz RBW/VBW = 9 kHz Scan step = 4 kHz<br><input type="checkbox"/> other: |                                            |                                                |
|                                       | Scan-Mode        | <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3dB Spectrum analyser Mode                                                                                                  |                                            |                                                |
|                                       | Detector         | Peak (pre-measurement) and Quasi-PK/Average (final if applicable)                                                                                                                                               |                                            |                                                |
|                                       | Mode: Sweep-Time | Repetitive-Scan, max-hold<br>Coupled – calibrated display if continuous signal otherwise adapted to EUT's individual transmission duty-cycle                                                                    |                                            |                                                |
| General measurement procedures        |                  | Please see chapter "Test system set-up radiated magnetic field measurements below 30 MHz"                                                                                                                       |                                            |                                                |

### 5.3.4. Radiated Field Strength Emissions – 9 kHz to 30 MHz Results

Table of measurement results:

| Diagram No. | Carrier Channel |                | Frequency range of measurement | Set-up no. | OP-mode no. | Remark                      | Used detector                       |                          |                          | Result        |
|-------------|-----------------|----------------|--------------------------------|------------|-------------|-----------------------------|-------------------------------------|--------------------------|--------------------------|---------------|
|             | Range [MHz]     | Channel        |                                |            |             |                             | PK                                  | AV                       | QP                       |               |
| 2.01a       | 5150-5250       | 36             | 9 kHz-30 MHz                   | 1 + 3      | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.01b       |                 | 36             |                                |            |             | EUT laying position         | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.02a       |                 | 48             | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.03a       | 5250-5350       | 52             | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.04a       |                 | 64             | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.05a       | 5470-5700       | 100            | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| --          |                 | <b>120-128</b> | 9 kHz-30 MHz                   | --         | --          | <b>Not usable in Canada</b> | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> | <b>remark</b> |
| 2.06a       |                 | 140            | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.07a       | 5725-5850       | 149            | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |
| 2.08a       |                 | 165            | 9 kHz-30 MHz                   | 1          | 1           | EUT standing position       | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed        |

**Remark:** no channel shall be used between 5600-5650MHz in Canada according RSS-247, Issue 2 regulations

### 5.3.5. Correction factors due to reduced meas. distance ( $f < 30$ MHz)

The used correction factors when the measurement distance is reduced compared to regulatory measurement distance, are calculated according Extrapolation formulas valid for EUT's with maximum dimension of  $0.625 \times \text{Lambda}$ . Formula 2+3+4 as presented in ANSI C63.10, Chapter 6.4.4 are used for the calculations of proper extrapolation factors.

| Frequency<br>-Range | f [kHz/MHz] | Lambda [m] | Far-Field<br>Point [m] | Distance Limit<br>accord. 15.209 [m] | 1st Condition<br>(dmeas <<br>$D_{\text{near-field}}$ ) | 2te Condition<br>(Limit distance<br>bigger $d_{\text{near-field}}$ ) | Distance Correction<br>accord. Formula |
|---------------------|-------------|------------|------------------------|--------------------------------------|--------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| kHz                 | 9,00E+03    | 33333,33   | 5305,17                | 300                                  | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 1,00E+04    | 30000,00   | 4774,65                |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 2,00E+04    | 15000,00   | 2387,33                |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 3,00E+04    | 10000,00   | 1591,55                |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 4,00E+04    | 7500,00    | 1193,66                |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 5,00E+04    | 6000,00    | 954,93                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 6,00E+04    | 5000,00    | 795,78                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 7,00E+04    | 4285,71    | 682,09                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 8,00E+04    | 3750,00    | 596,83                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 9,00E+04    | 3333,33    | 530,52                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 1,00E+05    | 3000,00    | 477,47                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 1,25E+05    | 2400,00    | 381,97                 |                                      | fulfilled                                              | not fulfilled                                                        | -80,00                                 |
|                     | 2,00E+05    | 1500,00    | 238,73                 | 30                                   | fulfilled                                              | fulfilled                                                            | -78,02                                 |
|                     | 3,00E+05    | 1000,00    | 159,16                 |                                      | fulfilled                                              | fulfilled                                                            | -74,49                                 |
|                     | 4,00E+05    | 750,00     | 119,37                 |                                      | fulfilled                                              | fulfilled                                                            | -72,00                                 |
|                     | 4,90E+05    | 612,24     | 97,44                  |                                      | fulfilled                                              | fulfilled                                                            | -70,23                                 |
|                     | 5,00E+05    | 600,00     | 95,49                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 6,00E+05    | 500,00     | 79,58                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 7,00E+05    | 428,57     | 68,21                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 8,00E+05    | 375,00     | 59,68                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 9,00E+05    | 333,33     | 53,05                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 1,00        | 300,00     | 47,75                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
| MHz                 | 1,59        | 188,50     | 30,00                  |                                      | fulfilled                                              | not fulfilled                                                        | -40,00                                 |
|                     | 2,00        | 150,00     | 23,87                  |                                      | fulfilled                                              | fulfilled                                                            | -38,02                                 |
|                     | 3,00        | 100,00     | 15,92                  |                                      | fulfilled                                              | fulfilled                                                            | -34,49                                 |
|                     | 4,00        | 75,00      | 11,94                  |                                      | fulfilled                                              | fulfilled                                                            | -32,00                                 |
|                     | 5,00        | 60,00      | 9,55                   |                                      | fulfilled                                              | fulfilled                                                            | -30,06                                 |
|                     | 6,00        | 50,00      | 7,96                   |                                      | fulfilled                                              | fulfilled                                                            | -28,47                                 |
|                     | 7,00        | 42,86      | 6,82                   |                                      | fulfilled                                              | fulfilled                                                            | -27,13                                 |
|                     | 8,00        | 37,50      | 5,97                   |                                      | fulfilled                                              | fulfilled                                                            | -25,97                                 |
|                     | 9,00        | 33,33      | 5,31                   |                                      | fulfilled                                              | fulfilled                                                            | -24,95                                 |
|                     | 10,00       | 30,00      | 4,77                   |                                      | fulfilled                                              | fulfilled                                                            | -24,04                                 |
|                     | 10,60       | 28,30      | 4,50                   |                                      | fulfilled                                              | fulfilled                                                            | -23,53                                 |
|                     | 11,00       | 27,27      | 4,34                   |                                      | fulfilled                                              | fulfilled                                                            | -23,21                                 |
|                     | 12,00       | 25,00      | 3,98                   |                                      | fulfilled                                              | fulfilled                                                            | -22,45                                 |
|                     | 13,56       | 22,12      | 3,52                   |                                      | fulfilled                                              | fulfilled                                                            | -21,39                                 |
|                     | 15,00       | 20,00      | 3,18                   |                                      | fulfilled                                              | fulfilled                                                            | -20,51                                 |
|                     | 15,92       | 18,85      | 3,00                   |                                      | fulfilled                                              | fulfilled                                                            | -20,00                                 |
|                     | 17,00       | 17,65      | 2,81                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 18,00       | 16,67      | 2,65                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 20,00       | 15,00      | 2,39                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 21,00       | 14,29      | 2,27                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 23,00       | 13,04      | 2,08                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 25,00       | 12,00      | 1,91                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 27,00       | 11,11      | 1,77                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 29,00       | 10,34      | 1,65                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |
|                     | 30,00       | 10,00      | 1,59                   |                                      | not fulfilled                                          | fulfilled                                                            | -20,00                                 |

## 5.4. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz

### 5.4.1. Test location and equipment

|                 |                                                                                                                                                                                                                                      |                                                                         |                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------|
| test location   | <input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)                                                                                                                                                                   | <input type="checkbox"/> Please see Chapter. 2.2.2                      | <input type="checkbox"/> Please see Chapter. 2.2.3 |
| test site       | <input checked="" type="checkbox"/> 441 EMISAR <input checked="" type="checkbox"/> 487 SAR NSA                                                                                                                                       |                                                                         |                                                    |
| receiver        | <input type="checkbox"/> 377 ESCS30 <input checked="" type="checkbox"/> 001 ESS                                                                                                                                                      | <input type="checkbox"/> 489 ESU 40 <input type="checkbox"/> 620 ESU 26 |                                                    |
| spectr. analys. | <input type="checkbox"/> 584 FSU <input type="checkbox"/> 120 FSEM <input type="checkbox"/> 264 FSEK                                                                                                                                 |                                                                         |                                                    |
| antenna         | <input checked="" type="checkbox"/> 574 BTA-L <input type="checkbox"/> 133 EMCO3115 <input type="checkbox"/> 302 BBHA9170 <input type="checkbox"/> 289 CBL 6141 <input type="checkbox"/> 030 HFH-Z2 <input type="checkbox"/> 477 GPS |                                                                         |                                                    |
| signaling       | <input type="checkbox"/> 392 MT8820A <input type="checkbox"/> 371 CBT32 <input type="checkbox"/> 547 CMU <input type="checkbox"/> 594 CMW                                                                                            |                                                                         |                                                    |
| otherwise       | <input type="checkbox"/> 400 FTC40x15E <input type="checkbox"/> 401 FTC40x15E <input type="checkbox"/> 110 USB LWL <input checked="" type="checkbox"/> 482 Filter Matrix                                                             |                                                                         |                                                    |
| DC power        | <input type="checkbox"/> 671 EA-3013S <input type="checkbox"/> 457 EA 3013A <input type="checkbox"/> 459 EA 2032-50 <input type="checkbox"/> 268 EA- 3050 <input type="checkbox"/> 494 AG6632A <input type="checkbox"/> 498 NGPE     |                                                                         |                                                    |
| Supply voltage  | <input type="checkbox"/> 230 V 50 Hz via public mains <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery)                                                                                                 |                                                                         |                                                    |

### 5.4.2. Requirements/Limits

|           |                 |                                                                                                                                                                                                        |                           |
|-----------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| FCC       |                 | Part 15 Subpart C, §15.209, §15.407(b)(6)                                                                                                                                                              |                           |
| ISED (IC) |                 | <input checked="" type="checkbox"/> RSS-Gen., Issue 5, table 5+7<br><input type="checkbox"/> ICES-003, Issue 5, table 4 (class A)<br><input checked="" type="checkbox"/> RSS-247, Issue 2, Chapter 6.2 |                           |
| ANSI      |                 | <input type="checkbox"/> C63.4-2014<br><input checked="" type="checkbox"/> C63.10-2013                                                                                                                 |                           |
| Limit     | Frequency [MHz] | Radiated emissions limits, 10 meters                                                                                                                                                                   |                           |
|           |                 | QUASI-Peak [ $\mu$ V/m]                                                                                                                                                                                | QUASI-Peak [dB $\mu$ V/m] |
|           | 30-88           | 90                                                                                                                                                                                                     | 39.0                      |
|           | 88-216          | 150                                                                                                                                                                                                    | 43.5                      |
|           | 216-960         | 210                                                                                                                                                                                                    | 46.4                      |
|           | above 960       | 300                                                                                                                                                                                                    | 49.5                      |

### 5.4.3. Restricted bands of operation (FCC §15.205)

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 0.495-0.505       | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.20725-4.20775   | 37.5-38.25          | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 73-74.6             | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 74.8-75.2           | 1718.8-1722.2 | 13.25-13.4  |
| 6.31175-6.31225   | 108-121.94          | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 123-138             | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 149.9-150.05        | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.52475-156.52525 | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 156.7-156.9         | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 162.0125-167.17     | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 167.72-173.2        | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 240-285             | 3600-4400     | --          |
| 13.36-13.41       | 322-335.4           | --            | --          |

Remark: only spurious emissions are allowed within these frequency bands not exceeding the limits per §15.209

#### 5.4.4. Test condition and measurement test set-up

|                                       |                       |                                                                                                                 |                                            |                                                |
|---------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------|------------------------------------------------|
| Signal link to test system (if used): |                       | <input type="checkbox"/> air link                                                                               | <input type="checkbox"/> cable connection  | <input checked="" type="checkbox"/> none       |
| EUT-grounding                         |                       | <input checked="" type="checkbox"/> none                                                                        | <input type="checkbox"/> with power supply | <input type="checkbox"/> additional connection |
| Equipment set up                      |                       | <input checked="" type="checkbox"/> table top 0.8m height                                                       | <input type="checkbox"/> floor standing    |                                                |
| Climatic conditions                   |                       | Temperature: (22±3°C)                                                                                           |                                            | Rel. humidity: (40±20)%                        |
| EMI-Receiver<br>(Analyzer) Settings   | Scan frequency range: | <input checked="" type="checkbox"/> 30 – 1000 MHz <input type="checkbox"/> other:                               |                                            |                                                |
|                                       | Scan-Mode             | <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB spectrum analyser mode |                                            |                                                |
|                                       | Detector              | Peak / Quasi-peak                                                                                               |                                            |                                                |
|                                       | RBW/VBW               | 100 kHz/300 kHz                                                                                                 |                                            |                                                |
|                                       | Mode:                 | Repetitive-Scan, max-hold                                                                                       |                                            |                                                |
|                                       |                       | 80 kHz                                                                                                          |                                            |                                                |
|                                       |                       | Coupled – calibrated display if continuous tx-signal otherwise adapted to EUT's individual duty-cycle           |                                            |                                                |
| General measurement procedures        |                       | Please see chapter "Test system set-up for electric field measurement in the range 30 MHz to 1 GHz"             |                                            |                                                |

#### 5.4.5. Radiated Field Strength Emissions – 30 MHz to 1 GHz Results

Table of measurement results:

| Dia-gram no. | Carrier Channel |     | Frequency range | Set-up no. | OP-mode no. | Remark               | Used detector                       |                          |                          | Result |
|--------------|-----------------|-----|-----------------|------------|-------------|----------------------|-------------------------------------|--------------------------|--------------------------|--------|
|              | Range           | No. |                 |            |             |                      | PK                                  | AV                       | QP                       |        |
| 3.01a        | Low             | 36  | 30 MHz – 1 GHz  | 1 + 3      | 1           | 18Mbit, EUT laying   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.01b        | Low             | 36  | 30 MHz – 1 GHz  | 1          | 1           | 18Mbit, EUT standing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.02b        | high            | 48  | 30 MHz – 1 GHz  | 1          | 1           | MCS4, EUT standing   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.03b        | Low             | 52  | 30 MHz – 1 GHz  | 1          | 1           | MCS4, EUT standing   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.04b        | High            | 64  | 30 MHz – 1 GHz  | 1          | 1           | 18Mbit, EUT standing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.05         | Low             | 100 | 30 MHz – 1 GHz  | 1          | 1           | 18Mbit, EUT standing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.06         | Middle          | 140 | 30 MHz – 1 GHz  | 1          | 1           | MCS4, EUT standing   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.07         | High            | 149 | 30 MHz – 1 GHz  | 1          | 1           | 18Mbit, EUT standing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.08         | High            | 165 | 30 MHz – 1 GHz  | 1          | 1           | MCS4, EUT standing   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |
| 3.04         | Low             | 36  | 30 MHz – 1 GHz  | 3          | 1           | MCS4, EUT standing   | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | passed |

Remark: for further details see Annex 1 (18-1-0050701T04-A1)

## 5.5. General Limit - Radiated emissions, above 1 GHz

### 5.5.1. Test location and equipment FAR

|                 |                                                       |                                        |                                                                                |                                                   |                                                  |                                  |
|-----------------|-------------------------------------------------------|----------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------|--------------------------------------------------|----------------------------------|
| test site       | <input type="checkbox"/> 441 EMI SAR                  | <input type="checkbox"/> 348 EMI cond. | <input checked="" type="checkbox"/> 443 EMI FAR                                | <input type="checkbox"/> 347 Radio.lab.           | <input type="checkbox"/> 337 OATS                | <input type="checkbox"/>         |
| spectr. analys. | <input type="checkbox"/> 584 FSU                      | <input type="checkbox"/> 120 FSEM      | <input type="checkbox"/> 264 FSEK                                              | <input checked="" type="checkbox"/> 489 ESU 40    | <input type="checkbox"/>                         | <input type="checkbox"/>         |
| antenna meas    | <input type="checkbox"/> 574 BTA-L                    | <input type="checkbox"/> 289 CBL 6141  | <input type="checkbox"/> 608 HL 562                                            | <input checked="" type="checkbox"/> 549 HL025     | <input checked="" type="checkbox"/> 302 BBHA9170 | <input type="checkbox"/> 477 GPS |
| antenna meas    | <input type="checkbox"/> 123 HUF-Z2                   | <input type="checkbox"/> 132 HUF-Z3    | <input type="checkbox"/> 030 HFH-Z2                                            | <input checked="" type="checkbox"/> 376 BBHA9120E |                                                  | <input type="checkbox"/>         |
| antenna subst   | <input type="checkbox"/> 071 HUF-Z2                   | <input type="checkbox"/> 020 EMCO3115  | <input type="checkbox"/> 063 LP 3146                                           | <input type="checkbox"/> 303 BBHA9170             | <input type="checkbox"/>                         | <input type="checkbox"/>         |
| multimeter      | <input type="checkbox"/> 341 Fluke 112                | <input type="checkbox"/>               | <input type="checkbox"/>                                                       | <input type="checkbox"/>                          | <input type="checkbox"/>                         | <input type="checkbox"/>         |
| signaling       | <input type="checkbox"/> 392 MT8820A                  | <input type="checkbox"/> 371 CBT32     | <input type="checkbox"/> 547 CMU                                               | <input type="checkbox"/> 594 CMW                  |                                                  |                                  |
| DCpower         | <input type="checkbox"/> 611 E3632A                   | <input type="checkbox"/> 087 EA3013    | <input type="checkbox"/> 354 NGPE 40                                           | <input type="checkbox"/> 349 car battery          | <input type="checkbox"/> 350 Car battery         | <input type="checkbox"/>         |
| Supply voltage  | <input type="checkbox"/> 230 V 50 Hz via public mains |                                        | <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery) |                                                   |                                                  |                                  |

### 5.5.2. Requirements/Limits

| <b>FCC</b>                                                                                            | <input type="checkbox"/> Part 15 Subpart B, §15.109 class B<br><input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205<br><input type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)                                                                                                                                                                     |                |                |                                                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ISED</b>                                                                                           | <input checked="" type="checkbox"/> RSS-Gen., Issue 5, Chapter 8.9, Table 5+6+7 (transmitter licence exempt)<br><input type="checkbox"/> RSS-Gen., Issue 5, Chapter 7.3, Table 3 (receiver)<br><input type="checkbox"/> ICES-003, Issue 6, Chapter 6.2.2, Table 7 (class B)<br><input type="checkbox"/> RSS-247, Issue 2, Chapter 5.5<br><input checked="" type="checkbox"/> RSS-247, Issue 2, Chapter 6.2 |                |                |                                                                                                                                                                               |
| <b>ANSI</b>                                                                                           | <input type="checkbox"/> C63.4-2014<br><input checked="" type="checkbox"/> C63.10-2013                                                                                                                                                                                                                                                                                                                     |                |                |                                                                                                                                                                               |
| Frequency [MHz]                                                                                       | Limits                                                                                                                                                                                                                                                                                                                                                                                                     |                |                |                                                                                                                                                                               |
|                                                                                                       | AV<br>[µV/m]                                                                                                                                                                                                                                                                                                                                                                                               | AV<br>[dBµV/m] | Peak<br>[µV/m] | Peak<br>[dBµV/m] or [dBm/MHz]                                                                                                                                                 |
| above 1 GHz<br>for frequencies as<br>defined in §15.205<br>or<br>RSS-Gen., Issue 9,<br>§8.9 - Table 5 | 500                                                                                                                                                                                                                                                                                                                                                                                                        | 54.0           | 5000           | 74.0 dBµV/m                                                                                                                                                                   |
| §15.407(b)(1)(2)(3)(4)                                                                                | --                                                                                                                                                                                                                                                                                                                                                                                                         | --             | --             | (b)(1): 5.15-5.25GHz: -27dBm eirp<br>(b)(2): 5.25-5.35GHz: -27dBm eirp<br>(b)(3): 5.47-5.725 GHz: -27dBm eirp<br>(-17dBm/MHz eirp)<br>(b)(4): 5.725-5.85GHz: Spectrum<br>mask |
| RSS-247, Issue 2                                                                                      | --                                                                                                                                                                                                                                                                                                                                                                                                         | --             | --             | §6.2.1.2<br>§6.2.2.2<br>§6.2.3.3<br>-27dBm/MHz<br>(68.2 dBµV/m)                                                                                                               |
|                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                            |                |                | §6.2.4.2:<br>Spectrum mask<br>27 to 15.6dBm<br>15.6dBm to 10dBm                                                                                                               |

### 5.5.3. Test condition and measurement test set-up

|                                       |                       |                                                                                                                                                                     |                                            |                                                |
|---------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|------------------------------------------------|
| Signal link to test system (if used): |                       | <input type="checkbox"/> air link                                                                                                                                   | <input type="checkbox"/> cable connection  | <input checked="" type="checkbox"/> none       |
| EUT-grounding                         |                       | <input checked="" type="checkbox"/> none                                                                                                                            | <input type="checkbox"/> with power supply | <input type="checkbox"/> additional connection |
| Equipment set up                      |                       | <input checked="" type="checkbox"/> table top 1.5m height                                                                                                           |                                            | <input type="checkbox"/> floor standing        |
| Climatic conditions                   |                       | Temperature: (22±3°C)                                                                                                                                               |                                            |                                                |
|                                       |                       | Rel. humidity: (40±20)%                                                                                                                                             |                                            |                                                |
| Spectrum-Analyzer settings            | Scan frequency range: | <input checked="" type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input checked="" type="checkbox"/> 18 – 40 GHz <input type="checkbox"/> other: |                                            |                                                |
|                                       | Scan-Mode             | <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB Spectrum analyser Mode                                                     |                                            |                                                |
|                                       | Detector              | Peak and Average                                                                                                                                                    |                                            |                                                |
|                                       | RBW/VBW               | 1 MHz / 3 MHz                                                                                                                                                       |                                            |                                                |
|                                       | Mode:                 | Repetitive-Scan, max-hold                                                                                                                                           |                                            |                                                |
|                                       |                       | 400 kHz                                                                                                                                                             |                                            |                                                |
|                                       |                       | Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle                                                                          |                                            |                                                |
| General measurement procedures        |                       | Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz"                                                                        |                                            |                                                |

#### 5.5.4. Radiated Field Strength Emissions Results:

| Dia-gram no. | Carrier Channel |     | Frequency range | Set-up no. | OP-mode no. | Remark | Used detector                       |                                     |                          | Result |
|--------------|-----------------|-----|-----------------|------------|-------------|--------|-------------------------------------|-------------------------------------|--------------------------|--------|
|              | Range           | No. |                 |            |             |        | PK                                  | AV                                  | QP                       |        |
| 4.01a        | Low             | 36  | 1-7GHz          | 1          | 1           | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.02a        | High            | 48  |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.03a        | Low             | 52  |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.04a        | High            | 64  |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.05a        | Low             | 100 |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.06b        | High            | 140 |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.06a        | high            | 165 |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.07a        | low             | 149 |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.04a        | Low             | 36  |                 | 3          |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |

Remark:

- 1.) see diagrams in annex 1 for more details
- 2.) Results valid with power 12.5 power setting, see document JTA6DG Test instructions

| Dia-gram no. | Carrier Channel |     | Frequency range | Set-up no. | OP-mode no. | Remark | Used detector                       |                                     |                          | Result |
|--------------|-----------------|-----|-----------------|------------|-------------|--------|-------------------------------------|-------------------------------------|--------------------------|--------|
|              | Range           | No. |                 |            |             |        | PK                                  | AV                                  | QP                       |        |
| 8.01b        | Low             | 36  | 7-18 GHz        | 1          | 1           | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.02b        | High            | 48  |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.03b        | Low             | 52  |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.04b        | High            | 64  |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.05b        | Low             | 100 |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.06b        | high            | 140 |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.07b        | low             | 149 |                 |            |             | 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 8.08b        | high            | 165 |                 |            |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.04b        | Low             | 36  |                 | 3          |             | MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |

Remark:

- 1.) see diagrams in annex 1 for more details
- 2.) Results valid with power 12.5 setting, see document JTA6DG Test instructions
- 3.) for

| Diagram no. | Carrier Channel |     | Frequency range | Set-up no. | OP-mode no. | Remark         | Used detector                       |                                     |                          | Result |
|-------------|-----------------|-----|-----------------|------------|-------------|----------------|-------------------------------------|-------------------------------------|--------------------------|--------|
|             | Range           | No. |                 |            |             |                | PK                                  | AV                                  | QP                       |        |
| 4.10c       | Low             | 36  | 18-40 GHz       | 1          | 1           | a-Mode, 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.11c       | High            | 48  |                 |            |             | n-Mode, MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.12c       | Low             | 52  |                 |            |             | n-Mode, MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.13c       | High            | 64  |                 |            |             | a-Mode, 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.14c       | Low             | 100 |                 |            |             | a-Mode, 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.15c       | high            | 140 |                 |            |             | n-Mode, MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.16b       | low             | 149 |                 |            |             | a-Mode, 18Mbit | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.17b       | high            | 165 |                 |            |             | n-Mode, MCS4   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |
| 4.04c       | Low             | 36  |                 | 3          |             | MCS4           | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | passed |

Remark:

- 1.) see diagrams in annex 1 for more details
- 2.) Results valid with power 12.5 setting, see document JTA6DG Test instructions

## 5.6. RF-Parameter - Radiated Band-Edge compliance measurements

### 5.6.1. Test location and equipment FAR

|                 |                                                       |                                        |                                                                                |                                                |                                          |                                  |
|-----------------|-------------------------------------------------------|----------------------------------------|--------------------------------------------------------------------------------|------------------------------------------------|------------------------------------------|----------------------------------|
| test site       | <input type="checkbox"/> 441 EMI SAR                  | <input type="checkbox"/> 348 EMI cond. | <input checked="" type="checkbox"/> 443 EMI FAR                                | <input type="checkbox"/> 347 Radio.lab.        | <input type="checkbox"/> 337 OATS        | <input type="checkbox"/>         |
| spectr. analys. | <input type="checkbox"/> 584 FSU                      | <input type="checkbox"/> 120 FSEM      | <input type="checkbox"/> 264 FSEK                                              | <input checked="" type="checkbox"/> 489 ESU 40 | <input type="checkbox"/>                 | <input type="checkbox"/>         |
| antenna meas    | <input type="checkbox"/> 574 BTA-L                    | <input type="checkbox"/> 289 CBL 6141  | <input type="checkbox"/> 608 HL 562                                            | <input checked="" type="checkbox"/> 549 HL025  | <input type="checkbox"/> 302 BBHA9170    | <input type="checkbox"/> 477 GPS |
| antenna meas    | <input type="checkbox"/> 123 HUF-Z2                   | <input type="checkbox"/> 132 HUF-Z3    | <input type="checkbox"/> 030 HFH-Z2                                            | <input type="checkbox"/>                       | <input type="checkbox"/>                 | <input type="checkbox"/>         |
| antenna subst   | <input type="checkbox"/> 071 HUF-Z2                   | <input type="checkbox"/> 020 EMCO3115  | <input type="checkbox"/> 063 LP 3146                                           | <input type="checkbox"/> 303 BBHA9170          | <input type="checkbox"/>                 | <input type="checkbox"/>         |
| multimeter      | <input type="checkbox"/> 341 Fluke 112                | <input type="checkbox"/>               | <input type="checkbox"/>                                                       | <input type="checkbox"/>                       | <input type="checkbox"/>                 | <input type="checkbox"/>         |
| signaling       | <input type="checkbox"/> 392 MT8820A                  | <input type="checkbox"/> 371 CBT32     | <input type="checkbox"/> 547 CMU                                               | <input type="checkbox"/> 594 CMW               | <input type="checkbox"/>                 | <input type="checkbox"/>         |
| DC power        | <input type="checkbox"/> 611 E3632A                   | <input type="checkbox"/> 087 EA3013    | <input type="checkbox"/> 354 NGPE 40                                           | <input type="checkbox"/> 349 car battery       | <input type="checkbox"/> 350 Car battery | <input type="checkbox"/>         |
| Supply voltage  | <input type="checkbox"/> 230 V 50 Hz via public mains |                                        | <input checked="" type="checkbox"/> 3.77 V DC (fully charged internal battery) |                                                |                                          |                                  |

### 5.6.2. Requirements/Limits

| <b>FCC</b>                                                                                            | <input type="checkbox"/> Part 15 Subpart B, §15.109 class B<br><input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205<br><input type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)                                                                                                                                                                     |                |                |                                                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ISED</b>                                                                                           | <input checked="" type="checkbox"/> RSS-Gen., Issue 5, Chapter 8.9, Table 5+6+7 (transmitter licence exempt)<br><input type="checkbox"/> RSS-Gen., Issue 5, Chapter 7.3, Table 3 (receiver)<br><input type="checkbox"/> ICES-003, Issue 6, Chapter 6.2.2, Table 7 (class B)<br><input type="checkbox"/> RSS-247, Issue 2, Chapter 5.5<br><input checked="" type="checkbox"/> RSS-247, Issue 2, Chapter 6.2 |                |                |                                                                                                                                                                               |
| <b>ANSI</b>                                                                                           | <input type="checkbox"/> C63.4-2014<br><input checked="" type="checkbox"/> C63.10-2013                                                                                                                                                                                                                                                                                                                     |                |                |                                                                                                                                                                               |
| Frequency [MHz]                                                                                       | Limits                                                                                                                                                                                                                                                                                                                                                                                                     |                |                |                                                                                                                                                                               |
|                                                                                                       | AV<br>[µV/m]                                                                                                                                                                                                                                                                                                                                                                                               | AV<br>[dBµV/m] | Peak<br>[µV/m] | Peak<br>[dBµV/m] or [dBm/MHz]                                                                                                                                                 |
| above 1 GHz<br>for frequencies as<br>defined in §15.205<br>or<br>RSS-Gen., Issue 9,<br>§8.9 - Table 5 | 500                                                                                                                                                                                                                                                                                                                                                                                                        | 54.0           | 5000           | 74.0 dBµV/m                                                                                                                                                                   |
| §15.407(b)(1)(2)(3)(4)                                                                                | --                                                                                                                                                                                                                                                                                                                                                                                                         | --             | --             | (b)(1): 5.15-5.25GHz: -27dBm eirp<br>(b)(2): 5.25-5.35GHz: -27dBm eirp<br>(b)(3): 5.47-5.725 GHz: -27dBm eirp<br>(-17dBm/MHz eirp)<br>(b)(4): 5.725-5.85GHz: Spectrum<br>mask |
| RSS-247, Issue 2                                                                                      | --                                                                                                                                                                                                                                                                                                                                                                                                         | --             | --             | §6.2.1.2<br>§6.2.2.2<br>§6.2.3.3<br>-27dBm/MHz<br>(68.2 dBµV/m)                                                                                                               |
|                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                            |                |                | §6.2.4.2:<br>Spectrum mask<br>27 to 15.6dBm<br>15.6dBm to 10dBm                                                                                                               |

### 5.6.3. Test condition and measurement test set-up

|                                       |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                            |                                                |
|---------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|------------------------------------------------|
| Signal link to test system (if used): |  | <input type="checkbox"/> air link                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <input type="checkbox"/> cable connection  | <input checked="" type="checkbox"/> none       |
| EUT-grounding                         |  | <input checked="" type="checkbox"/> none                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <input type="checkbox"/> with power supply | <input type="checkbox"/> additional connection |
| Equipment set up                      |  | <input checked="" type="checkbox"/> table top 1.5m height                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                            | <input type="checkbox"/> floor standing        |
| Climatic conditions                   |  | Temperature: (22±3°C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                            |                                                |
| Spectrum-Analyzer settings            |  | Rel. humidity: (40±20)%<br>Scan frequency range: <input type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input type="checkbox"/> 18 – 40 GHz <input checked="" type="checkbox"/> other: see diagrams<br>Scan-Mode: <input type="checkbox"/> 6 dB EMI-Receiver Mode <input checked="" type="checkbox"/> 3 dB Spectrum analyzer Mode<br>Detector: Peak and Average<br>RBW/VBW: Left band-edge: 100kHz/300kHz<br>Right band-edge: 1 MHz / 3 MHz<br>Mode: Repetitive-Scan, max-hold<br>Scan step: 40kHz or 400 kHz<br>Sweep-Time: Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle |                                            |                                                |
| General measurement procedures        |  | Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz" for general measurements procedures in anechoic chamber.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                            |                                                |

#### 5.6.4. Measurement Method

For uncritical results where a measurement resolution bandwidth of 1MHz can clearly show the compliance without influencing the results, a field strength measurement was performed to show compliance.

For critical results a Marker-Delta marker method was used for showing compliance to restricted bands. The method is according ANSI C63.10:2013, Chapter 6.10.6 “Marker-Delta method”,. The method consists of three independent steps:

- 1. Step:** Prior to the measurement the fundamental radiated In-Band field strength was performed. The determined value is used as reference value.
- 2. Step:** Second step consist of finding the relative attenuation between the fundamental emission and the maximum local out-of-band emission (within 2 MHz range around the band edge either on the band-edge directly or some modulation product if the level is greater than that on the band-edge) when measured with lower resolution bandwidth.
- 3. Step:** The delta value recorded in step 2 will be subtracted from value recorded in step 1, thus giving the required field strength at the band-edge. This value must fulfil the requirements for radiated spurious emissions in restricted bands in FCC §15.205 with the general limits of FCC §15.209.

#### 5.6.5. EUT settings

The EUT was instructed to send with maximum power (if adjustable) according to applicants instructions, **see document JTA6DG Test instructions**

#### 5.6.6. Results:

##### 5.6.6.1. Non-restricted bands - limits according to FCC §15.407 /RSS-247, Issue 2

| Diagram no. | Channel no. | Restricted band ? | Fundamental Value [dBuV/m] |                | Peak-Value at Band-Edge [dBuV/m] | Limit [dBuV/m @3m] | Margin [dB] | Verdict | Remark:                 |
|-------------|-------------|-------------------|----------------------------|----------------|----------------------------------|--------------------|-------------|---------|-------------------------|
|             |             |                   | Peak -Value                | Average -Value |                                  |                    |             |         |                         |
| 9.05        | 100         | no                | 104,19                     | 93,56          | 61,0                             | 68,2               | 7,2         | PASS    | PWR-VALUE=12.5 dBm used |
| 9.06        | 140         | no                | 101,96                     | 90,75          | 59,8                             | 68,2               | 8,4         | PASS    | PWR-VALUE=12.5 dBm used |
| 9.07        | 149         | no                | 98,99                      | 88,06          | 67,6                             | 122,2              | 54,6        | PASS    | PWR-VALUE=12.5 dBm used |
| 9.08        | 165         | no                | 99,46                      | 88,56          | 61,1                             | 122,2              | 61,1        | PASS    | PWR-VALUE=12.5 dBm used |
| 9.13        | 100         | no                | 105,05                     | 94,1           | 57,17                            | 68,2               | 11,03       | PASS    | PWR-VALUE=12.5 dBm used |
| 9.14        | 140         | no                | 102,16                     | 90,37          | 59,8                             | 68,2               | 8,4         | PASS    | PWR-VALUE=12.5 dBm used |
| 9.15        | 149         | no                | 98,94                      | 88,29          | 69,0                             | 122,2              | 53,2        | PASS    | PWR-VALUE=12.5 dBm used |
| 9.16        | 165         | no                | 100,13                     | 88,92          | 61,89                            | 122,2              | 60,31       | PASS    | PWR-VALUE=12.5 dBm used |

##### Handheld Variant

| Diagram no. | Channel no. | Restrict ed band ? | Fundamental Value [dBuV/m] |                | Peak-Value at Band-Edge [dBuV/m] | Limit [dBuV/m@ 3m] | Margin [dB] | Verdict | Remark:                              |
|-------------|-------------|--------------------|----------------------------|----------------|----------------------------------|--------------------|-------------|---------|--------------------------------------|
|             |             |                    | Peak -Value                | Average -Value |                                  |                    |             |         |                                      |
| 9.09        | 100         | no                 | 102,99                     | 91,214         | 61,1                             | 68,2               | 7,1         | PASS    | HH Variant   PWR-VALUE=12.5 dBm used |
| 9.10        | 140         | no                 | 100,92                     | 91,337         | 59,8                             | 68,2               | 8,4         | PASS    | HH Variant   PWR-VALUE=12.5 dBm used |
| 9.11        | 149         | no                 | 98,53                      | 85,198         | 68,9                             | 122,2              | 53,3        | PASS    | HH Variant   PWR-VALUE=12.5 dBm used |

Limit for channels 100/140: -27dBm/MHz (68.2 dBμV/m at 3m measurement distance)

Limit for channels 149/165: 27dBm/MHz (122.2 dBμV/m at 3m measurement distance)

### 5.6.6.2. Results for restricted bands near-by with limits accord. FCC §15.205 / §15.209

| Diagramm no. | Channel no. | Restricted band ? | Fundamental Value |               | Value at Band-Edge |               | Limits     |               | Duty-Cycle [dB] | Margin |         | Verdict | Remark:                 |
|--------------|-------------|-------------------|-------------------|---------------|--------------------|---------------|------------|---------------|-----------------|--------|---------|---------|-------------------------|
|              |             |                   | Peak-Value        | Average-Value | Peak-Value         | Average-Value | Peak-Value | Average-Value |                 | Peak   | Average |         |                         |
| 9.01         | 36          | yes               | 102,73            | 93,23         | 57,0               | 44,0          | 74         | 54            | 1,55            | 17     | 8,5     | PASS    | PWR-Level 12.5 dBm used |
| 9.02         | 48          | yes               | 102,26            | 91,73         | 52,23              | 40,3          | 74         | 54            | 1,55            | 21,77  | 12,15   | PASS    | PWR-Level 12.5 dBm used |
| 9.04         | 64          | yes               | 102,45            | 91,89         | 54,51              | 42,13         | 74         | 54            | 1,55            | 19,49  | 10,32   | PASS    | PWR-Level 12.5 dBm used |
| 9.09         | 36          | yes               | 103,44            | 93,03         | 57,35              | 44,2          | 74         | 54            | 2,62            | 16,65  | 7,18    | PASS    | PWR-Level 12.5 dBm used |
| 9.10         | 48          | yes               | 87,43             | 78,27         | 52,0               | 40,0          | 74         | 54            | 2,62            | 22     | 11,38   | PASS    | PWR-Level 12.5 dBm used |
| 9.12         | 64          | yes               | 102,93            | 91,35         | 56,13              | 42,69         | 74         | 54            | 2,62            | 17,87  | 8,69    | PASS    | PWR-Level 12.5 dBm used |

### HH Variant Spot checks

| Diagramm no. | Channel no. | Restricted band ? | Fundamental Value |               | Value at Band-Edge |               | Limits     |               | Duty-Cycle [dB] | Margin |         | Verdict | Remark:                              |
|--------------|-------------|-------------------|-------------------|---------------|--------------------|---------------|------------|---------------|-----------------|--------|---------|---------|--------------------------------------|
|              |             |                   | Peak-Value        | Average-Value | Peak-Value         | Average-Value | Peak-Value | Average-Value |                 | Peak   | Average |         |                                      |
| 9.07         | 36          | yes               | 99,49             | 89,229        | 59,8               | 44,8          | 74         | 54            | 1,55            | 14,203 | 7,7     | PASS    | HH Variant   PWR-Level 12.5 dBm used |
| 9.08         | 64          | yes               | 96,564            | 87,58         | 55,081             | 42,881        | 74         | 54            | 1,55            | 18,919 | 9,569   | PASS    | HH Variant   PWR-Level 12.5 dBm used |

### 5.6.7. Results for restricted emissions in 5250-5350MHz band when TX operable in 5150-5250MHz band

#### Requirement Canada RSS-247, Issue 2, Chapter 6.2.1.2

See annex 1 for results and calculations (Diagram 3 and 4)

**Verdict:** pass

### 5.6.8. Results for restricted power density in 5150-5250MHz band when TX operable in 5250-5350MHz band

#### Requirement Canada RSS-247, Issue 2, Chapter 6.2.2.2 b)

**Diagram 9.03 and 9.11** - Max. power density at 5250MHz point on operable channel 52: -10.7dBm/MHz < 10dBm/MHz

**Verdict:** pass with restriction to labelling requirement

**Device must be labelled: “for indoor use only”**

### 5.6.9. Verdict: Pass

## 5.7. Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

| RF-Measurement                            | Reference    | Frequency range                     | Calculated uncertainty based on a confidence level of 95% |        |      |      |      |    |                      | Remarks                                   |
|-------------------------------------------|--------------|-------------------------------------|-----------------------------------------------------------|--------|------|------|------|----|----------------------|-------------------------------------------|
| Conducted emissions (U <sub>CISPR</sub> ) | CISPR 16-2-1 | 9 kHz - 150 kHz<br>150 kHz - 30 MHz | 4.0 dB<br>3.6 dB                                          |        |      |      |      |    |                      | -                                         |
| Radiated emissions Enclosure              | CISPR 16-2-3 | 30 MHz - 1 GHz<br>1 GHz - 18 GHz    | 4.2 dB<br>5.1 dB                                          |        |      |      |      |    |                      | E-Field                                   |
| Disturbance power                         | CISPR 16-2-2 | 30 MHz - 300 MHz                    | -                                                         |        |      |      |      |    |                      | -                                         |
| Power Output radiated                     | -            | 30 MHz - 4 GHz                      | 3.17 dB                                                   |        |      |      |      |    |                      | Substitution method                       |
| Power Output conducted                    | -            | Set-up No.                          | Cel-C1                                                    | Cel-C2 | BT1  | W1   | W2   | -- | -                    |                                           |
|                                           |              | 9 kHz - 12.75 GHz                   | N/A                                                       | 0.60   | 0.7  | 0.25 | N/A  | -- |                      |                                           |
|                                           |              | 12.75 - 26.5GHz                     | N/A                                                       | 0.82   | --   | N/A  | N/A  | -- |                      |                                           |
| Conducted emissions on RF-port            | -            | 9 kHz - 2.8 GHz                     | 0.70                                                      | N/A    | 0.70 | N/A  | 0.69 | -- | N/A - not applicable |                                           |
|                                           |              | 2.8 GHz - 12.75GHz                  | 1.48                                                      | N/A    | 1.51 | N/A  | 1.43 | -- |                      |                                           |
|                                           |              | 12.75 GHz - 18GHz                   | 1.81                                                      | N/A    | 1.83 | N/A  | 1.77 | -- |                      |                                           |
|                                           |              | 18 GHz - 26.5GHz                    | 1.83                                                      | N/A    | 1.85 | N/A  | 1.79 | -- |                      |                                           |
| Occupied bandwidth                        | -            | 9 kHz - 4 GHz                       | 0.1272 ppm (Delta Marker)                                 |        |      |      |      |    |                      | Frequency error                           |
|                                           |              |                                     | 1.0 dB                                                    |        |      |      |      |    |                      | Power                                     |
| Emission bandwidth                        | -            | 9 kHz - 4 GHz                       | 0.1272 ppm (Delta Marker)                                 |        |      |      |      |    |                      | Frequency error                           |
|                                           | -            |                                     | See above: 0.70 dB                                        |        |      |      |      |    |                      | Power                                     |
| Frequency stability                       | -            | 9 kHz - 20 GHz                      | 0.0636 ppm                                                |        |      |      |      |    |                      | -                                         |
| Radiated emissions Enclosure              | -            | 150 kHz - 30 MHz                    | 5.0 dB                                                    |        |      |      |      |    |                      | Magnetic field<br>E-field<br>Substitution |
|                                           |              | 30 MHz - 1 GHz                      | 4.2 dB                                                    |        |      |      |      |    |                      |                                           |
|                                           |              | 1 GHz - 20 GHz                      | 3.17 dB                                                   |        |      |      |      |    |                      |                                           |

**Table: measurement uncertainties, valid for conducted/radiated measurements**

## 6. Abbreviations used in this report

| The abbreviations |                                                                                   |
|-------------------|-----------------------------------------------------------------------------------|
| ANSI              | American National Standards Institute                                             |
| AV . AVG, CAV     | Average detector                                                                  |
| EIRP              | Equivalent isotropically radiated power. determined within a separate measurement |
| EGPRS             | Enhanced General Packet Radio Service                                             |
| EUT               | Equipment Under Test                                                              |
| FCC               | Federal Communications Commission. USA                                            |
| IC                | Industry Canada                                                                   |
| n.a.              | not applicable                                                                    |
| Op-Mode           | Operating mode of the equipment                                                   |
| PK                | Peak                                                                              |
| RBW               | resolution bandwidth                                                              |
| RF                | Radio frequency                                                                   |
| RSS               | Radio Standards Specification. Documents from Industry Canada                     |
| Rx                | Receiver                                                                          |
| TCH               | Traffic channel                                                                   |
| Tx                | Transmitter                                                                       |
| QP                | Quasi peak detector                                                               |
| VBW               | Video bandwidth                                                                   |
| ERP               | Effective radiated power                                                          |

## 7. Accreditation details of CETECOM's laboratories and test sites

| Ref.-No.                        | Accreditation Certificate                | Valid for laboratory area or test site                                                                                                                                                                                                                                      | Accreditation Body                                                                          |
|---------------------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| -                               | D-PL-12047-01-01                         | All laboratories and test sites of CETECOM GmbH, Essen                                                                                                                                                                                                                      | DAkkS, Deutsche Akkreditierungsstelle GmbH                                                  |
| 337<br>487<br>558<br>348<br>348 | (MRA US-EU 0003)                         | Radiated Measurements 30 MHz to 1 GHz. 3 m / 10 m (OATS)<br>Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR)<br>Radiated Measurements above 1 GHz. 3 m (FAR)<br>Mains Ports Conducted Interference Measurements<br>Telecommunication Ports Conducted Interference Measurem. | FCC, Federal Communications Commission<br>Laboratory Division, USA                          |
| 337<br>487<br>550<br>558        | 3462D-1<br>3462D-2<br>3462D-2<br>3462D-3 | Radiated Measurements 30 MHz to 1 GHz. 3 m / 10 m (OATS)<br>Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR)<br>Radiated Measurements 1 GHz to 6 GHz. 3 m (SAR)<br>Radiated Measurements above 1 GHz. 3 m (FAR)                                                             | IC, Industry Canada Certification and Engineering Bureau                                    |
| 487<br>550<br>348<br>348        | R-2666<br>G-301<br>C-2914<br>T-1967      | Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR)<br>Radiated Measurements 1 GHz to 6 GHz. 3 m (SAR)<br>Mains Ports Conducted Interference Measurements<br>Telecommunication Ports Conducted Interference Measurem.                                                          | VCCI, Voluntary Control Council for Interference by Information Technology Equipment, Japan |

OATS = Open Area Test Site, SAR = Semi Anechoic Room, FAR = Fully Anechoic Room

## 8. Instruments and Ancillary

TC”

The “Ref.-No” in the left column of the following tables allows the clear identification of the laboratory equipment.

### 8.1.1. Test software and firmware of equipment

| Ref.-No. | Equipment                               | Type                   | Serial-No.     | Version of Firmware or Software during the test                                                 |
|----------|-----------------------------------------|------------------------|----------------|-------------------------------------------------------------------------------------------------|
| 001      | EMI Test Receiver                       | ESS                    | 825132/017     | Firm.= 1.21 , OTP=2.0, GRA=2.0                                                                  |
| 012      | Signal Generator (EMS-cond.)            | SMY 01                 | 839069/027     | Firm.= V 2.02                                                                                   |
| 013      | Power Meter (EMS cond.)                 | NRVD                   | 839111/003     | Firm.= V 1.51                                                                                   |
| 017      | Digital Radiocommunication Tester       | CMD 60 M               | 844365/014     | Firmware = V 3.52 .22.01.99, DECT = D2.87 13.01.99                                              |
| 053      | Audio Analyzer                          | UPA3                   | 860612/022     | Firm. V 4.3                                                                                     |
| 119      | RT Harmonics Analyzer dig. Flickermeter | B10                    | G60547         | Firm.= V 3.1DHG                                                                                 |
| 140      | Signal Generator                        | SMHU                   | 831314/006     | Firm.= 3.21                                                                                     |
| 261      | Thermal Power Sensor                    | NRV-Z55                | 825083/0008    | EPROM-Datum 02.12.04, SE EE 1 B                                                                 |
| 262      | Power Meter                             | NRV-S                  | 825770/0010    | Firm.= 2.6                                                                                      |
| 263      | Signal Generator                        | SMP 04                 | 826190/0007    | Firm.=3.21                                                                                      |
| 295      | Racal Digital Radio Test Set            | 6103                   | 1572           | UNIT Firmware= 4.04, SW-Main=4.04, SW-BBP=1.04, SW-DSP=1.02, Hardboot=1.02, Softboot=2.02       |
| 298      | Univ. Radio Communication Tester        | CMU 200                | 832221/091     | R&S Test Firmware =3.53 /3.54 (current Testsoftw. f. all band used                              |
| 323      | Digital Radiocommunication Tester       | CMD 55                 | 825878/0034    | Firm.= 3.52 .22.01.99                                                                           |
| 335      | CTC-EMS-Conducted                       | System EMS Conducted   | -              | EMC 32 V 8.52                                                                                   |
| 340      | Digital Radiocommunication Tester       | CMD 55                 | 849709/037     | Firm.= 3.52 .22.01.99                                                                           |
| 355      | Power Meter                             | URV 5                  | 891310/027     | Firm.= 1.31                                                                                     |
| 365      | 10V Insertion Unit 50 Ohm               | URV5-Z2                | 100880         | Eprom Data = 31.03.08                                                                           |
| 366      | Ultra Compact Simulator                 | UCS 500 M4             | V0531100594    | Firm. UCS 500=001925/3.06a02, rc=ISMIEC 4.10                                                    |
| 371      | Bluetooth Tester                        | CBT32                  | 100153         | CBT V5.30+ SW-Option K55, K57                                                                   |
| 377      | EMI Test Receiver                       | ESCS 30                | 100160         | Firm.= 2.30, OTP= 02.01, GRA= 02.36                                                             |
| 378      | Broadband RF Field Monitor              | RadiSense III          | 03D00013SNO-08 | Firm.= V.03D13                                                                                  |
| 389      | Digital Multimeter                      | Keithley 2000          | 0583926        | Firm. = A13 (Mainboard) A02 (Display)                                                           |
| 392      | Radio Communication Tester              | MT8820A                | 6K00000788     | Firm.= 4.50 #005, IPL=4.01#001, OS=4.02#001, GSM=4.41#013, W-CDMA= 4.54#004, scenario= 4.52#002 |
| 436      | Univ. Radio Communication Tester        | CMU 200                | 103083         | R&S Test Firmware Base=5.14, Mess-Software= GSM:5.14 WCDMA:5.14 (current Testsoftw. F. all band |
| 441      | CTC-SAR-EMI Cable Loss                  | System EMI field (SAR) | -              | EMC 32 Version 8.52                                                                             |
| 442      | CTC-SAR-EMS                             | System EMS field (SAR) | -              | EMC 32 Version 8.40                                                                             |
| 443      | CTC-FAR-EMI-RSE                         | System CTC-FAR-EMI-RSE | -              | Spuri 7.2.5 or EMC 32 Ver. 9.15.00                                                              |
| 444      | CTC-FAR-EMS field                       | System-EMS-Field (FAR) | -              | EMC 32 Version 9.15.00                                                                          |
| 460      | Univ. Radio Communication Tester        | CMU 200                | 108901         | R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used,    |
| 489      | EMI Test Receiver                       | ESU40                  | 1000-30        | Firmware=4.43 SP3, Bios=V5.1-16-3, Spec. =01.00                                                 |
| 491      | ESD Simulator dito                      | ESD dito               | dito307022     | V 2.30                                                                                          |
| 524      | Voltage Drop Simulator                  | VDS 200                | 0196-16        | Software Nr. 000037 Version V4.20a01                                                            |
| 526      | Burst Generator                         | EFT 200 A              | 0496-06        | Software Nr. 000034 Version V2.32                                                               |
| 527      | Micro Pulse Generator                   | MPG 200 B              | 0496-05        | Software-Nr. 000030 Version V2.43                                                               |
| 528      | Load Dump Simulator                     | LD 200B                | 0496-06        | Software-Nr. 000031 Version V2.35a01                                                            |
| 546      | Univ. Radio Communication Tester        | CMU 200                | 106436         | R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used     |
| 547      | Univ. Radio Communication Tester        | CMU 200                | 835390/014     | R&S Test Firmware Base=V5.1403 (current Testsoftw., f. all band used, GSM = 5.14 WCDMA: = 5.14  |
| 584      | Spectrum Analyzer                       | FSU 8                  | 100248         | 2.82_SP3                                                                                        |
| 597      | Univ. Radio Communication Tester        | CMU 200                | 100347         | R&S Test Firmware Base=5.01, GSM=5.02 WCDMA= not installed, Mainboard= µP1=V.850                |
| 598      | Spectrum Analyzer                       | FSEM 30                | 831259/013     | Firmware Bios 3.40 , Analyzer 3.40 Sp 2                                                         |
| 607      | Signal Generator                        | SMR 20                 | 832033/011     | V1.25                                                                                           |
| 620      | EMI Test Receiver                       | ESU 26                 | 100362         | 4.43_SP3                                                                                        |
| 642      | Wideband Radio Communication Tester     | CMW 500                | 126089         | Setup V03.26, Test programm component V03.02.20                                                 |
| 670      | Univ. Radio Communication Tester        | CMU 200                | 106833         | µP1 =V8.50, Firmware = V.20                                                                     |
| 689      | Vector Signal Generator                 | SMU200                 | 100970         | 02.20.360.142                                                                                   |
| 692      | Bluetooth Tester                        | CBT 32                 | 100236         | CBT V 5.40, FW: V.2.41 (FPGA Digital, V. 3.09 FPGA RF)                                          |

### 8.1.2. Single instruments and test systems

| Ref.-No. | Equipment                               | Type                  | Serial-No.  | Manufacturer          | Interval of calibration | Remark | Cal due    |
|----------|-----------------------------------------|-----------------------|-------------|-----------------------|-------------------------|--------|------------|
| 001      | EMI Test Receiver                       | ESS                   | 825132/017  | Rohde & Schwarz       | 12 M                    | -      | 16.05.2019 |
| 005      | AC - LISN (50 Ohm/50µH, test site 1)    | ESH2-Z5               | 861741/005  | Rohde & Schwarz       | 12 M                    | -      | 16.05.2019 |
| 007      | Single-Line V-Network (50 Ohm/5µH)      | ESH3-Z6               | 892563/002  | Rohde & Schwarz       | 12 M                    | -      | 16.05.2019 |
| 009      | Power Meter (EMS-radiated)              | NRV                   | 863056/017  | Rohde & Schwarz       | 24 M                    | -      | 15.05.2019 |
| 016      | Line Impedance Simulating Network       | Op. 24-D              | B6366       | Spitzenberger+Spies   | 36 M                    | -      | 30.05.2019 |
| 020      | Horn Antenna 18 GHz (Subst 1)           | 3115                  | 9107-3699   | EMCO                  | 36/12 M                 | -      | 31.07.2021 |
| 021      | Loop Antenna (H-Field)                  | 6502                  | 9206-2770   | EMCO                  | 36 M                    | -      | 30.05.2021 |
| 030      | Loop Antenna (H-field)                  | HFH-Z2                | 879604/026  | Rohde & Schwarz       | 36 M                    | -      | 30.04.2018 |
| 033      | RF-current probe (100kHz-30MHz)         | ESH2-Z1               | 879581/18   | Rohde & Schwarz       | 24 M                    | -      | 15.05.2019 |
| 057      | relay-switch-unit (EMS system)          | RSU                   | 494440/002  | Rohde & Schwarz       | pre-m                   | 1a     |            |
| 060      | power amplifier (DC-2kHz)               | PAS 5000              | B6363       | Spitzenberger+Spies   | -                       | 3      |            |
| 086      | DC - power supply, 0 -10 A              | LNG 50-10             | -           | Heinzinger Electronic | pre-m                   | 2      |            |
| 087      | DC - power supply, 0 -5 A               | EA-3013 S             | -           | Elektro Automatik     | pre-m                   | 2      |            |
| 091      | USB-LWL-Converter                       | OLS-1                 | 007/2006    | Ing. Büro Scheiba     | -                       | 4      |            |
| 099      | passive voltage probe                   | ESH2-Z3               | 299.7810.52 | Rohde & Schwarz       | 36 M                    | -      | 30.05.2021 |
| 100      | passive voltage probe                   | Probe TK 9416         | without     | Schwarzbeck           | 36 M                    | -      | 30.05.2021 |
| 110      | USB-LWL-Converter                       | OLS-1                 | -           | Ing. Büro Scheiba     | -                       | 4      |            |
| 119      | RT Harmonics Analyzer dig. Flickermeter | B10                   | G60547      | BOCONSULT             | 36 M                    | -      | 30.05.2019 |
| 133      | horn antenna 18 GHz (Meas 1)            | 3115                  | 9012-3629   | EMCO                  | 36 M                    | 1c     | 10.03.2020 |
| 134      | horn antenna 18 GHz (Subst 2)           | 3115                  | 9005-3414   | EMCO                  | 36 M                    | -      | 10.03.2020 |
| 248      | attenuator                              | SMA 6dB 2W            | -           | Radiall               | pre-m                   | 2      |            |
| 249      | attenuator                              | SMA 10dB 10W          | -           | Radiall               | pre-m                   | 2      |            |
| 252      | attenuator                              | N 6dB 12W             | -           | Radiall               | pre-m                   | 2      |            |
| 256      | attenuator                              | SMA 3dB 2W            | -           | Radiall               | pre-m                   | 2      |            |
| 257      | hybrid                                  | 4031C                 | 04491       | Narda                 | pre-m                   | 2      |            |
| 260      | hybrid coupler                          | 4032C                 | 11342       | Narda                 | pre-m                   | 2      |            |
| 261      | Thermal Power Sensor                    | NRV-Z55               | 825083/0008 | Rohde & Schwarz       | 24 M                    | -      | 30.05.2020 |
| 262      | Power Meter                             | NRV-S                 | 825770/0010 | Rohde & Schwarz       | 24 M                    | -      | 30.05.2019 |
| 263      | Signal Generator                        | SMP 04                | 826190/0007 | Rohde & Schwarz       | 36 M                    | -      | 30.05.2019 |
| 265      | peak power sensor                       | NRV-Z33, Model 04     | 840414/009  | Rohde & Schwarz       | 24 M                    | -      | 30.05.2020 |
| 266      | Peak Power Sensor                       | NRV-Z31, Model 04     | 843383/016  | Rohde & Schwarz       | 24 M                    | -      | 30.05.2020 |
| 267      | notch filter GSM 850                    | WRCA 800/960-6EEK     | 9           | Wainwright GmbH       | pre-m                   | 2      |            |
| 270      | termination                             | 1418 N                | BB6935      | Weinschel             | pre-m                   | 2      |            |
| 271      | termination                             | 1418 N                | BE6384      | Weinschel             | pre-m                   | 2      |            |
| 272      | attenuator (20 dB) 50 W                 | Model 47              | BF6239      | Weinschel             | pre-m                   | 2      |            |
| 273      | attenuator (10 dB) 100 W                | Model 48              | BF9229      | Weinschel             | pre-m                   | 2      |            |
| 274      | attenuator (10 dB) 50 W                 | Model 47 (10 dB) 50 W | BG0321      | Weinschel             | pre-m                   | 2      |            |
| 275      | DC-Block                                | Model 7003 (N)        | C5129       | Weinschel             | pre-m                   | 2      |            |
| 276      | DC-Block                                | Model 7006 (SMA)      | C7061       | Weinschel             | pre-m                   | 2      |            |
| 279      | power divider                           | 1515 (SMA)            | LH855       | Weinschel             | pre-m                   | 2      |            |
| 298      | Univ. Radio Communication Tester        | CMU 200               | 832221/091  | Rohde & Schwarz       | pre-m                   | 3      |            |
| 300      | AC LISN (50 Ohm/50µH, 1-phase)          | ESH3-Z5               | 892 239/020 | Rohde & Schwarz       | 12 M                    | -      | 17.05.2019 |
| 301      | attenuator (20 dB) 50W, 18GHz           | 47-20-33              | AW0272      | Lucas Weinschel       | pre-m                   | 2      |            |
| 302      | horn antenna 40 GHz (Meas 1)            | BBHA9170              | 155         | Schwarzbeck           | 36 M                    | -      | 14.03.2020 |
| 303      | horn antenna 40 GHz (Subst 1)           | BBHA9170              | 156         | Schwarzbeck           | 36 M                    | -      | 20.03.2020 |
| 331      | Climatic Test Chamber -40/+180 Grad     | HC 4055               | 43146       | Heraeus Vötsch        | 24 M                    | -      | 30.10.2018 |
| 341      | Digital Multimeter                      | Fluke 112             | 81650455    | Fluke                 | 24 M                    | -      | 30.05.2020 |
| 342      | Digital Multimeter                      | Voltcraft M-4660A     | IB 255466   | Voltcraft             | 24 M                    | -      | 17.05.2019 |
| 347      | laboratory site                         | radio lab.            | -           | -                     | -                       | 5      |            |

| Ref.-No. | Equipment                               | Type                          | Serial-No.             | Manufacturer                    | Interval of calibration | Remark | Cal due    |
|----------|-----------------------------------------|-------------------------------|------------------------|---------------------------------|-------------------------|--------|------------|
| 348      | laboratory site                         | EMI conducted                 | -                      | -                               | -                       | 5      |            |
| 354      | DC - Power Supply 40A                   | NGPE 40/40                    | 448                    | Rohde & Schwarz                 | pre-m                   | 2      |            |
| 357      | power sensor                            | NRV-Z1                        | 861761/002             | Rohde & Schwarz                 | 24 M                    | -      | 24.05.2019 |
| 371      | Bluetooth Tester                        | CBT32                         | 100153                 | R&S                             | 36 M                    | -      | 30.05.2019 |
| 373      | Single-Line V-Network (50 Ohm/5µH)      | ESH3-Z6                       | 100535                 | Rohde & Schwarz                 | 12 M                    | -      | 17.05.2019 |
| 377      | EMI Test Receiver                       | ESCS 30                       | 100160                 | Rohde & Schwarz                 | 12 M                    | -      | 30.05.2019 |
| 389      | Digital Multimeter                      | Keithley 2000                 | 0583926                | Keithley                        | pre-m                   | -      |            |
| 392      | Radio Communication Tester              | MT8820A                       | 6K00000788             | Anritsu                         | 12 M                    | -      | 30.06.2019 |
| 405      | Thermo-/Hygrometer                      | OPUS 10 THI                   | 126.0604.0003.3.3.3.22 | LUFFT Mess u. Regeltechnik GmbH | 24 M                    | -      | 30.03.2019 |
| 431      | Model 7405                              | Near-Field Probe Set          | 9305-2457              | EMCO                            | -                       | 4      |            |
| 436      | Univ. Radio Communication Tester        | CMU 200                       | 103083                 | Rohde & Schwarz                 | 12 M                    | -      | 06.03.2019 |
| 439      | UltraLog-Antenna                        | HL 562                        | 100248                 | Rohde & Schwarz                 | 36 M                    | -      | 10.03.2020 |
| 454      | Oscilloscope                            | HM 205-3                      | 9210 P 29661           | Hameg                           | -                       | 4      |            |
| 456      | DC-Power supply 0-5 A                   | EA 3013 S                     | 207810                 | Elektro Automatik               | pre-m                   | 2      |            |
| 459      | DC -Power supply 0-5 A , 0-32 V         | EA-PS 2032-50                 | 910722                 | Elektro Automatik               | pre-m                   | 2      |            |
| 460      | Univ. Radio Communication Tester        | CMU 200                       | 108901                 | Rohde & Schwarz                 | 12 M                    | -      | 30.05.2019 |
| 463      | Universal source                        | HP3245A                       | 2831A03472             | Agilent                         | -                       | 4      |            |
| 466      | Digital Multimeter                      | Fluke 112                     | 89210157               | Fluke USA                       | 24 M                    | -      | 30.05.2020 |
| 467      | Digital Multimeter                      | Fluke 112                     | 89680306               | Fluke USA                       | 36 M                    | -      | 30.05.2019 |
| 468      | Digital Multimeter                      | Fluke 112                     | 90090455               | Fluke USA                       | 36 M                    | -      | 30.04.2021 |
| 477      | ReRadiating GPS-System                  | AS-47                         | -                      | Automotive Cons. Fink           | -                       | 3      |            |
| 480      | power meter (Fula)                      | NRVS                          | 838392/031             | Rohde & Schwarz                 | 24 M                    | -      | 16.05.2019 |
| 482      | Filter matrix                           | Filter matrix SAR 1           | -                      | CETECOM (Brl)                   | -                       | 1d     |            |
| 487      | System CTC NSA-Verification SAR-EMI     | System EMI field (SAR) NSA    | -                      | ETS Lindgren / CETECOM          | 24 M                    | -      | 31.03.2019 |
| 489      | EMI Test Receiver                       | ESU40                         | 1000-30                | Rohde & Schwarz                 | 12 M                    | -      | 30.06.2019 |
| 502      | band reject filter                      | WRCG 1709/1786-1699/1796-     | SN 9                   | Wainwright                      | pre-m                   | 2      |            |
| 503      | band reject filter                      | WRCG 824/849-814/859-60/10SS  | SN 5                   | Wainwright                      | pre-m                   | 2      |            |
| 517      | relais switch matrix                    | HF Relais Box Keithley System | SE 04                  | Keithley                        | pre-m                   | 2      |            |
| 523      | Digital Multimeter                      | L4411A                        | MY46000154             | Agilent                         | 24 M                    | -      | 18.05.2019 |
| 529      | 6 dB Broadband resistive power divider  | Model 1515                    | LH 855                 | Weinschel                       | pre-m                   | 2      |            |
| 530      | 10 dB Broadband resistive power divider | R 416110000                   | LOT 9828               | -                               | pre-m                   | 2      |            |
| 546      | Univ. Radio Communication Tester        | CMU 200                       | 106436                 | R&S                             | 12 M                    | -      | 30.07.2019 |
| 547      | Univ. Radio Communication Tester        | CMU 200                       | 835390/014             | Rohde & Schwarz                 | 12 M                    | -      | 30.07.2019 |
| 549      | Log.Per-Antenna                         | HL025                         | 1000060                | Rohde & Schwarz                 | 36/12 M                 | -      | 31.07.2021 |
| 550      | System CTC S-VSWR Verification SAR-EMI  | System EMI Field SAR S-VSWR   | -                      | ETS Lindgren/CETECOM            | 24 M                    | -      | 30.03.2019 |
| 558      | System CTC FAR S-VSWR                   | System CTC FAR S-VSWR         | -                      | CTC                             | 24 M                    | -      | 08.08.2019 |
| 574      | Biconilog Hybrid Antenna                | BTA-L                         | 980026L                | Frankonia                       | 36/12 M                 | -      | 31.03.2019 |
| 584      | Spectrum Analyzer                       | FSU 8                         | 100248                 | Rohde & Schwarz                 | pre-m                   | -      |            |
| 594      | Wideband Radio Communication Tester     | CMW 500                       | 101757                 | Rohde & Schwarz                 | 12 M                    | -      | 30.05.2019 |
| 597      | Univ. Radio Communication Tester        | CMU 200                       | 100347                 | Rohde & Schwarz                 | pre-m                   | -      |            |
| 600      | power meter                             | NRVD (Reserve)                | 834501/018             | Rohde & Schwarz                 | 24 M                    | -      | 17.05.2019 |
| 601      | medium-sensitivity diode sensor         | NRV-Z5 (Reserve)              | 8435323/003            | Rohde & Schwarz                 | 24 M                    | -      | 15.05.2019 |
| 602      | peak power sensor                       | NRV-Z32 (Reserve)             | 835080                 | Rohde & Schwarz                 | 24 M                    | -      |            |
| 611      | DC power supply                         | E3632A                        | KR 75305854            | Agilent                         | pre-m                   | 2      |            |
| 612      | DC power supply                         | E3632A                        | MY 40001321            | Agilent                         | pre-m                   | 2      |            |
| 613      | Attenuator                              | R416120000 20dB 10W           | Lot. 9828              | Radiall                         | pre-m                   | 2      |            |
| 616      | Digitalmultimeter                       | Fluke 177                     | 88900339               | Fluke                           | 24 M                    | -      | 30.05.2020 |
| 617      | Power Splitter/Combiner                 | ZFSC-2-2-S+                   | S F987001108           | Mini Circuits                   | -                       | 2      |            |
| 618      | Power Splitter/Combiner                 | 50PD-634                      | 600994                 | JFW Industries USA              | -                       | 2      |            |
| 619      | Power Splitter/Combiner                 | 50PD-634                      | 600995                 | JFW Industries, USA             | -                       | 3      |            |
| 620      | EMI Test Receiver                       | ESU 26                        | 100362                 | Rohde-Schwarz                   | 12 M                    | -      | 30.05.2019 |
| 621      | Step Attenuator 0-139 dB                | RSP                           | 100017                 | Rohde & Schwarz                 | pre-m                   | 2      |            |

| Ref.-No. | Equipment                            | Type                           | Serial-No.             | Manufacturer                   | Interval of calibration | Remark | Cal due    |
|----------|--------------------------------------|--------------------------------|------------------------|--------------------------------|-------------------------|--------|------------|
| 625      | Generic Test Load USB                | Generic Test Load USB          | -                      | CETECOM                        | -                       | 2      |            |
| 627      | data logger                          | OPUS 1                         | 201.0999.9302.6.4.1.43 | G. Lufft GmbH                  | 24 M                    | -      | 30.03.2019 |
| 634      | Spectrum Analyzer                    | FSM (HF-Unit)                  | 826188/010             | Rohde & Schwarz                | pre-m                   | 2      |            |
| 637      | High Speed HDMI with Ethernet 1m     | HDMI cable with Ethernet 1m    | -                      | KogiLink                       | -                       | 2      |            |
| 638      | HDMI Kabel with Ethernet 1,5 m flach | HDMI cable with Ethernet 1,5m  | -                      | Reichelt                       | -                       | 2      |            |
| 640      | HDMI cable 2m rund                   | HDMI cable 2m rund             | -                      | Reichelt                       | -                       | 2      |            |
| 641      | HDMI cable with Ethernet             | Certified HDMI cable with      | -                      | PureLink                       | -                       | 2      |            |
| 642      | Wideband Radio Communication Tester  | CMW 500                        | 126089                 | Rohde&Schwarz                  | 24 M                    | -      | 24.05.2019 |
| 644      | Amplifier                            | ZX60-2534M+                    | SN865701299            | Mini-Circuits                  | -                       | -      |            |
| 670      | Univ. Radio Communication Tester     | CMU 200                        | 106833                 | Rohde & Schwarz                | 24 M                    | -      | 30.05.2020 |
| 671      | DC-power supply 0-5 A                | EA-3013S                       | -                      | Elektro Automatik              | pre-m                   | 2      |            |
| 678      | Power Meter                          | NRP                            | 101638                 | Rohde&Schwarz                  | pre-m                   | -      |            |
| 683      | Spectrum Analyzer                    | FSU 26                         | 200571                 | Rohde & Schwarz                | 12 M                    | -      | 30.05.2019 |
| 686      | Field Analyzer                       | EHP-200A                       | 160WX30702             | Narda Safety Test Solutions    | 24 M                    | -      | 29.03.2019 |
| 687      | Signal Generator                     | SMF 100A                       | 102073                 | Rohde&Schwarz                  | 12 M                    | -      | 30.05.2019 |
| 688      | Pre Amp                              | JS-18004000-40-8P              | 1750117                | Miteq                          | pre-m                   | -      |            |
| 690      | Spectrum Analyzer                    | FSU                            | 100302/026             | Rohde&Schwarz                  | 24 M                    | -      | 16.05.2019 |
| 691      | OSP120 Base Unit                     | OSP120                         | 106833                 | Rohde & Schwarz                | 12 M                    | -      | 30.05.2019 |
| 692      | Bluetooth Tester                     | CBT 32                         | 100236                 | Rohde & Schwarz                | 36 M                    | -      | 29.05.2020 |
| 693      | TS8997                               | CTC-Radio Lab 1_TS8997         | -                      | Rohde&Schwarz                  | 12 M                    | 5      | 30.05.2019 |
| 697      | Power Splitter                       | ZN4PD-642W-S+                  | 165001445              | Mini-Circuits                  | -                       | 2      |            |
| 701      | CMW500 wide, Radio Comm.             | CMW500                         | 158150                 | Rohde & Schwarz                | 12 M                    | -      | 30.07.2019 |
| 703      | INNCO Antennen Mast                  | MA 4010-KT080-XPET-ZSS3        | MA4170-KT100-XPET-ZSS3 | INNCO                          | pre-m                   | -      |            |
| 704      | INNCON Controller                    | CO 3000-4port                  | CO3000/933/38410516/L  | INNCO Systems GmbH             | pre-m                   | -      |            |
| 711      | Harmonic Mixer 90 GHz - 140GHz       | RPG FS-Z140                    | 101004                 | RPG                            | 36 M                    | -      | 22.02.2020 |
| 712      | Harmonic Mixer 75 GHz - 110GHz       | FS-Z110                        | 101468                 | Rohde & Schwarz                | 36 M                    | -      | 22.02.2020 |
| 713      | Harmonic Mixer, 50 GHz - 75GHz       | FS-Z75                         | 101022                 | Rohde & Schwarz                | 36 M                    | -      | 22.05.2020 |
| 714      | Signal Analyzer 67GHz                | FSW67                          | 104023                 | Rohde & Schwarz                | 24 M                    | -      | 28.02.2020 |
| 715      | Harmonic Mixer, 140 GHz - 220GHz     | FS-Z220                        | 101009                 | RPG Radiometer Physics         | 36 M                    | -      | 03.08.2020 |
| 716      | Harmonic Mixer 220 GHz to 325 GHZ    | FS-Z325                        | 101005                 | RPG Radiometer Physics         | 36 M                    | -      | 13.02.2020 |
| 747      | Spectrum Analyzer                    | FSU 26                         | 200152                 | Rohde & Schwarz                | 12 M                    | -      | 30.05.2019 |
| 748      | Pickett-Potter Horn Antenna          | FH-PP 4060                     | 010001                 | Radiometer Physics             | 36 M                    | -      |            |
| 749      | Pickett-potter Horn Antenna          | FH-PP 60-90                    | 010003                 | Radiometer Physics             | -                       | -      |            |
| 750      | Pickett-Potter Horn Antenna          | FH-PP 140-220                  | 010011                 | Radiometer Physics             | -                       | -      |            |
| 751      | Digital Optical System               | optoCAN-FD Transceiver         | 17-010416              | mk-messtechnik GmbH            | -                       | -      |            |
| 752      | Digital Optical System               | optoCAN-FD Transceiver         | 17-010083              | mk-messtechnik GmbH            | -                       | -      |            |
| 753      | Digital Optical System               | optoCAN-FD Transceiver         | 17-010084              | mk-messtechnik GmbH            | -                       | -      |            |
| 754      | Digital Optical System               | optoCAN-FD Transceiver         | 17-010415              | mk-messtechnik GmbH            | -                       | -      |            |
| 755      | Digital Optical System               | optoLAN-100-MAX Transceiver    | 17-010795              | mk-messtechnik GmbH            | -                       | -      |            |
| 757      | WIDEBAND RADIO COMMUNICATION         | CMW500                         | 163673                 | Rohde&Schwarz                  | 12 M                    | -      | 20.07.2018 |
| 758      | Signal Generator                     | SMU 200A                       | 100754                 | Rohde & Schwarz                | 24 M                    | -      | 11.10.2019 |
| 780      | Spectrum Analyzer                    | FSH3                           | 101726                 | Rohde & Schwarz                | 24 M                    | -      | 19.07.2019 |
| 781      | Power Supply                         | PS 2042-10 B                   | 2815450369             | Elektro-Automatik GmbH & Co.KG | -                       | -      |            |
| 782      | Power Supply                         | PS 2042-10 B                   | 2815450348             | Elektro-Automatik GmbH & Co.KG | -                       | -      |            |
| 783      | Spectrum Analyzer                    | FSU 26                         | 100414                 | Rohde & Schwarz                | 12 M                    | -      | 30.05.2019 |
| 784      | Power Supply                         | NGSM 32/10                     | 00196                  | Rohde & Schwarz                | 12 M                    | -      |            |
| 785      | RSP                                  | RF Step Attenuator 0...139.9dB | 860712/012             | Rohde & Schwarz                | 12 M                    | -      |            |
| 786      | SAR Probe                            | ES3DV3                         | 3340                   | Speag                          | 36 M                    | -      | 14.02.2021 |
| 787      | OSP                                  | OSP B157WX                     | 101264                 | Rohde & Schwarz                | 12 M                    | -      | 30.05.2019 |
| 788      | Precision Omnidirectional Dipole     | POD 618                        | 6182558/Q              | Seibersdorf Laboratories       | 36 M                    | -      | 30.06.2021 |
| 789      | Precision Omnidirectional Dipole     | POD 16                         | 162496/Q               | Seibersdorf Laboratories       | 36 M                    | -      | 30.06.2021 |

### 8.1.3. Legend

| Note / remarks |     | Calibrated during system calibration:                                                     |
|----------------|-----|-------------------------------------------------------------------------------------------|
|                | 1a  | System CTC-SAR-EMS (Ref.-No. 442)                                                         |
|                | 1b  | System-CTC-EMS-Conducted (Ref.-No. 335)                                                   |
|                | 1c  | System CTC-FAR-EMI-RSE (Ref.-No . 443)                                                    |
|                | 1d  | System CTC-SAR-EMI (Ref.-No . 441)                                                        |
|                | 1e  | System CTC-OATS (EMI radiated) (Ref.-No. 337)                                             |
|                | 1 f | System CTC-CTIA-OTA (Ref.-No . 420)                                                       |
|                | 1 g | System CTC-FAR-EMS (Ref.-No . 444)                                                        |
|                | 2   | Calibration or equipment check immediately before measurement                             |
|                | 3   | Regulatory maintained equipment for functional check or support purpose                   |
|                | 4   | Ancillary equipment without calibration e.g. mechanical equipment or monitoring equipment |
|                | 5   | Test System                                                                               |

|                         |         |                                                                               |
|-------------------------|---------|-------------------------------------------------------------------------------|
| Interval of calibration | 12 M    | 12 month                                                                      |
|                         | 24 M    | 24 month                                                                      |
|                         | 36 M    | 36 month                                                                      |
|                         | 24/12 M | Calibration every 24 months. between this every 12 months internal validation |
|                         | 36/12 M | Calibration every 36 months. between this every 12 months internal validation |
|                         | Pre-m   | Check before starting the measurement                                         |
|                         | -       | Without calibration                                                           |

## 9. Versions of test reports (change history)

| Version | Applied changes                       | Date of release |
|---------|---------------------------------------|-----------------|
| --      | Initial release                       | 2018-08-23      |
| C01     | SW Status updated                     | 2018-09-07      |
| C01     | FVIN updated, Module report reference | 2018-09-25      |