CFR 47 FCC PART 15 SUBPART E
ISED RSS-247 Issue 4

TEST REPORT

For

MOBILE COMPUTER WITH BARCODE READER

MODEL NUMBER: JTSHGUN

REPORT NUMBER: 4791876636-1-RF-4

ISSUE DATE: August 9, 2025

FCC ID: U4GJTSHGUN
IC:3862E-JTSHGUN

Prepared for

Datalogic S.r.l.
Via San Vitalino, 13
40012 Lippo di Calderara di Reno (BO) - Italy

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China

Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	August 9, 2025	Initial Issue	

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
ON TIME AND DUTY CYCLE	ANSI C63.10-2020, Clause 12.2	None; for reporting purposes only.	Pass
6dB AND 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	KDB 789033 D02 v02r01 Section C.1	FCC Part 15.407 (a)/(e), RSS-247 Issue 4, Clause 7.3.5.2 RSS-Gen Clause 6.7	Pass
CONDUCTED OUTPUT POWER	KDB 789033 D02 v02r01 Section E.3.a (Method PM)/KDB 789033 D02 v02r01 Section E.3.a (Method PM) Section E.2.d (Method SA-2)	FCC 15.407 (a) RSS-247 Clause 7.3	Pass
POWER SPECTRAL DENSITY	KDB 789033 D02 v02r01 Section F	FCC 15.407 (a) RSS-247 Clause 7.3	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2.	FCC 15.207 RSS-GEN Clause 8.8	Pass
Radiated Emissions and Band Edge Measurement	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	FCC 15.407 (b) FCC 15.209 FCC 15.205 RSS-247 Clause 7.3 RSS-GEN Clause 8.9	Pass
FREQUENCY STABILITY	ANSI C63.10-2020, Clause 6.8	FCC 15.407 (g)	Pass
Dynamic Frequency Selection (Slave)	KDB 905462 D03 Client Without DFS New Rules v01r02	FCC Part 15.407 (h), RSS-247 Issue 4 Clause 7.3.6	Pass
Antenna Requirement	N/A	FCC 47 CFR Part 15.203/ 15.407(a)(1) (2), RSS-Gen Issue 5, Clause 6.8	Pass

Note:
1. N/A: In this whole report not applicable.
2. For ISED, this report is also performed according to ANSI C63.10-2020+Cor.1-2023 standards.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.
*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART E, ISED RSS-247 Issue 4> when <Simple Acceptance> decision rule is applied.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

CONTENTS

1. ATTESTATION OF TEST RESULTS 6

2. TEST METHODOLOGY 7

3. FACILITIES AND ACCREDITATION 8

4. CALIBRATION AND UNCERTAINTY 9

4.1. MEASURING INSTRUMENT CALIBRATION 9

4.2. MEASUREMENT UNCERTAINTY 9

5. EQUIPMENT UNDER TEST 10

5.1. DESCRIPTION OF EUT 10

5.2. CHANNEL LIST 11

5.3. MAXIMUM POWER 12

5.4. TEST CHANNEL CONFIGURATION 13

5.5. THE WORSE CASE POWER SETTING PARAMETER 15

5.6. WORSE CASE CONFIGURATIONS 19

5.7. DESCRIPTION OF AVAILABLE ANTENNAS 21

5.8. SUPPORT UNITS FOR SYSTEM TEST 22

6. MEASURING EQUIPMENT AND SOFTWARE USED 24

7. ANTENNA PORT TEST RESULTS 27

7.1. ON TIME AND DUTY CYCLE 27

7.2. 6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH 28

7.3. CONDUCTED OUTPUT POWER 30

7.4. POWER SPECTRAL DENSITY 33

7.5. FREQUENCY STABILITY 35

7.6. DYNAMIC FREQUENCY SELECTION (SLAVE) 37

8. RADIATED TEST RESULTS 41

8.1. RESTRICTED BANDEDGE 50

8.2. RESTRICTED BANDEDGE PARTIAL RU 140

8.3. SPURIOUS EMISSIONS(1 GHZ~7 GHZ) 179

8.4. SPURIOUS EMISSIONS(7 GHZ~18 GHZ) 205

8.5. SPURIOUS EMISSIONS(7 GHZ~18 GHZ) PARTIAL RU 355

8.6. SPURIOUS EMISSIONS(9 KHZ~30 MHZ) 379

8.7. SPURIOUS EMISSIONS(18 GHZ~26 GHZ) 382

8.8. SPURIOUS EMISSIONS(26 GHZ~40 GHZ) 384

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.9. SPURIOUS EMISSIONS(30 MHZ~1 GHZ) 386

9. AC POWER LINE CONDUCTED EMISSION 388

10. ANTENNA REQUIREMENT 392

11. TEST DATA 393

11.1. APPENDIX A: EMISSION BANDWIDTH 393
11.1.1. Test Result 393
11.1.2. Test Graphs 398

11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH 481
11.2.1. Test Result 481
11.2.2. Test Graphs 486

11.3. APPENDIX C: MIN EMISSION BANDWIDTH 569
11.3.1. Test Result 569
11.3.2. Test Graphs 571

11.4. APPENDIX D: MAXIMUM CONDUCTED OUTPUT POWER 588
11.4.1. Test Result 588
11.4.2. Test Graphs 595

11.5. APPENDIX E: MAXIMUM POWER SPECTRAL DENSITY 607
11.5.1. Test Result 607
11.5.2. Test Graphs 614

11.6. APPENDIX F: FREQUENCY STABILITY 694
11.6.1. Test Result 694

11.7. APPENDIX G: DUTY CYCLE 695
11.7.1. Test Result 695
11.7.2. Test Graphs 696

11.8. APPENDIX H: DFS DETECTION THRESHOLDS 700
11.8.1. Test Result 700
11.8.2. Test Graphs 700

11.9. APPENDIX I: CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME 701
11.9.1. Test Result 701
11.9.2. Test Graphs 701

11.10. APPENDIX J: NON-OCCUPANCY PERIOD 702
11.10.1. Test Graphs 702

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	Datalogic S.r.l.
Address:	Via San Vitalino, 13 40012 Lippo di Calderara di Reno (BO) - Italy

Manufacturer Information

Company Name:	Datalogic S.r.l.
Address:	Via San Vitalino, 13 40012 Lippo di Calderara di Reno (BO) - Italy

EUT Information

EUT Name:	MOBILE COMPUTER WITH BARCODE READER
Model:	JTSHGUN
HVIN:	JTSH GUN
Brand:	DATALOGIC
Sample Received Date:	July 6, 2025
Sample Status:	Normal
Sample ID:	8740849
Date of Tested:	July 7, 2025 to August 9, 2025

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 FCC PART 15 SUBPART E **ISED RSS-247 Issue 4**	**Pass**

Prepared By:

Fanny Huang

Project Engineer

Checked By:

Kebo Zhang

Operations Leader

Approved By:

Stephen Guo

Operations Manager

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART E ISED RSS-247 Issue 4, ANSI C63.10-2020, ANSI C63.10-2020+Cor.1-2023, CFR 47 FCC Part 2, KDB 789033 D02 v02r01, RSS-GEN Issue 5, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02, KDB 905462 D03 UNII clients without radar detection New Rules v01r02, KDB 905462 D04 Operational Modes for DFS Testing New Rules v01 and KDB 905462 D06 802 11 Channel Plans New Rules v02.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	**A2LA (Certificate No.: 4102.01)** UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. **FCC (FCC Designation No.: CN1187)** UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. **ISED (Company No.: 21320)** UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. **VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202)** UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202

Note 1:
All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:
The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:
For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
	5.37 dB (26 GHz ~ 40 GHz)
Duty Cycle	±0.028%
Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.766 dB
Maximum Power Spectral Density Level	±1.22 dB
Frequency Stability	±2.76%
Dynamic Frequency Selection	±1.01 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	MOBILE COMPUTER WITH BARCODE READER
Model	JTSHGUN
HVIN	JTSH GUN

Frequency Range:	5180 MHz to 5240 MHz 5260 MHz to 5320 MHz 5500 MHz to 5720 MHz 5745 MHz to 5825 MHz
DFS Operational mode:	Slave without radar detection
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11a/n HT20/11n HT40/ ac VHT20/ac VHT40/ac VHT80/ac VHT160 ax HE20/ax HE40/ax HE80/ax HE160
Normal Test Voltage:	DC 3.635V via battery

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.2. CHANNEL LIST

UNII-1 (For Bandwidth=20MHz)		UNII-1 (For Bandwidth=40MHz)		UNII-1 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A (For Bandwidth=20MHz)		UNII-2A (For Bandwidth=40MHz)		UNII-2A (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2A (For Bandwidth=160 MHz)	
Channel	Frequency (MHz)
50	5250

UNII-2C (For Bandwidth=20MHz)		UNII-2C (For Bandwidth=40MHz)		UNII-2C (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	5600	142	5710		
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				
144	5720				

UNII-2C (For Bandwidth=160 MHz)	
Channel	Frequency (MHz)
114	5570

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

UNII-3 (For Bandwidth=20MHz)		UNII-3 (For Bandwidth=40MHz)		UNII-3 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

UNII-3 (For Bandwidth=240 MHz)	
Channel	Frequency (MHz)
130	5610

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Maximum EIRP (dBm)
a	5180 ~ 5825	25.59	26.09
n HT20		25.40	25.90
n HT40		23.13	23.63
ac VHT80		21.65	22.15
ac VHT160		18.88	19.38
ax HE20		24.92	25.42
ax HE40		22.77	23.27
ax HE80		21.39	21.89
ax HE160		18.71	19.21

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.4. TEST CHANNEL CONFIGURATION

UNII-1 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT80	CH 42(Low Channel)	5210 MHz
802.11ax HE20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11ax HE40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ax HE80	CH 42(Low Channel)	5210 MHz

UNII-2A Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT80	CH 58(Low Channel)	5290 MHz
802.11ax HE20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11ax HE40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ax HE80	CH 58(Low Channel)	5290 MHz

UNII-2C Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11n HT20	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11n HT40	CH 102(Low Channel), CH 110(MID Channel), CH 134(High Channel)	5510 MHz, 5550 MHz, 5670 MHz
802.11ac VHT80	CH 102(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz
802.11ac VHT160	CH 114(High Channel)	5570 MHz
802.11ax HE20	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11ax HE40	CH 102(Low Channel), CH 110(MID Channel), CH 134(High Channel)	5510 MHz, 5550 MHz, 5670 MHz
802.11ax HE80	CH 102(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz
802.11ax HE160	CH 114(High Channel)	5570 MHz

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

UNII-3 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ac VHT80	CH 155(Low Channel)	5775 MHz
802.11ax HE20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11ax HE40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ax HE80	CH 155(Low Channel)	5775 MHz

Straddle Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 144	5720 MHz
802.11n HT20	CH 144	5720 MHz
802.11n HT40	CH 142	5710 MHz
802.11ac VHT80	CH 138	5690 MHz
802.11ac VHT160	CH 50	5250 MHz
802.11ax HE20	CH 144	5720 MHz
802.11ax HE40	CH 142	5710 MHz
802.11ax HE80	CH 138	5690 MHz
802.11ax HE160	CH 50	5250 MHz

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter	
Test Software	QRCT

Mode	Freq(MHz)	Tx power from (dBm)
		ANT0 &ANT1
802.11a	5180	default
	5200	default
	5240	default
	5260	default
	5280	default
	5320	default
	5500	default
	5580	default
	5700	default
	5720-2C	default
	5720-3	default
	5745	default
	5785	default
	5825	default
802.11n 20M	5180	default
	5200	default
	5240	default
	5260	default
	5280	default
	5320	default
	5500	default
	5580	default
	5700	default
	5720-2C	default
	5720-3	default
	5745	default
	5785	default
	5825	default
802.11n 40M	5190	default
	5230	default
	5270	default
	5310	default
	5510	default

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	5550	default
	5670	default
	5710-2C	default
	5710-3	default
	5755	default
	5795	default
802.11ac 80M	5210	default
	5290	default
	5530	default
	5610	default
	5690-2C	default
	5690-3	default
	5775	default
802.11ac 160M	5250-1	default
	5250-2A	default
	5570	default

Mode	Freq(MHz)	RU size	RU Index	Tx power Level(dBm)
802.11ax 20M	5180	26	0	default
		52	37	default
		106	53	default
		SU	/	default
	5200	26	4	default
		52	38	default
		106	53	default
		SU	/	default
	5240	26	8	default
		52	40	default
		106	54	default
		SU	/	default
	5260	26	0	default
		52	37	default
		106	53	default
		SU	/	default
	5280	26	4	default
		52	38	default
		106	53	default
		SU	/	default

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	5320	26	8	default
		52	40	default
		106	54	default
		SU	/	default
	5500	26	0	default
		52	37	default
		106	53	default
		SU	/	default
	5580	26	4	default
		52	38	default
		106	53	default
		SU	/	default
	5700	26	8	default
		52	40	default
		106	54	default
		SU	/	default
	5720-2C	SU	/	default
	5720-3	SU	/	default
	5745	26	0	default
		52	37	default
		106	53	default
		SU	/	default
	5785	26	4	default
		52	38	default
		106	53	default
		SU	/	default
	5825	26	8	default
		52	40	default
		106	54	default
		SU	/	default
802.11ax 40M	5190	SU	/	default
	5230	SU	/	default
	5270	SU	/	default
	5310	SU	/	default
	5510	SU	/	default
	5550	SU	/	default
	5670	SU	/	default
	5710-2C	SU	/	default
	5710-3	SU	/	default
	5755	SU	/	default

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	5795	SU	/	default
802.11ax 80M	5210	SU	/	default
	5290	SU	/	default
	5530	SU	/	default
	5610	SU	/	default
	5690-2C	SU	/	default
	5690-3	SU	/	default
	5775	SU	/	default
802.11ax 160M	5250-1	SU	/	default
	5250-2A	SU	/	default
	5570	SU	/	default

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.6. WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

802.11a 20 mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0
802.11ac VHT20 mode: MCS0
802.11ac VHT40 mode: MCS0
802.11ac VHT80 mode: MCS0
802.11ac VHT160 mode: MCS0
802.11ax HE20 mode: MCS0
802.11ax HE40 mode: MCS0
802.11ax HE80 mode: MCS0
802.11ax HE160 mode: MCS0

All modes support MIMO mode.

SISO mode and MIMO mode have the same power setting, so only the worst case power mode(MIMO) will be record in the report.

The EUT has 2 separate antennas: antenna 0 and antenna 1, antenna 0 support BT and WIFI, antenna 1 support WIFI.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

802.11ax HE20/HE40/HE80/HE160 support Full RU, SU (Single User) and partial RU tone. According to Preliminary Investigation, Full RU and SU (Single User) have the same bandwidth and waveform performance, conducted power of Full RU modes are higher than SU (Single User) Tone modes. It was determined that Full RU modes were the worst case over SU Tone in every instance. Therefore, Full RU modes were tested to represent SU modes as the worst-case scenario.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Preliminary Investigation was performed for 802.11 ax modes were determined by the following:

Testing was performed 802.11ax HE20 26T, 52T, 106T and Full RU to cover HE40 26T, 52T, 106T and 242T.

Testing was performed 802.11ax HE20 26T, 52T, 106T, Full RU, HE40 Full RU & HE80 Full RU to cover HE80 26T, 52T, 106T, 242T and 484T.

Testing was performed 802.11ax HE20 26T, 52T, 106T, Full RU, HE40 Full RU & HE80 Full RU & HE160 Full RU to cover HE80 26T, 52T, 106T, 242T, 484T and 996T.

802.11ax HE20 26T Harmonics and Spurious Emissions were ran at maximum PSD between 26T, 52T, 104T, 242T and 484T modes across all bandwidths and bands to cover HE20 52T and 106, HE40 26T, 52T, 106T and 242T, HE80 26T, 52T, 106T, 242T and 484T, HE160 26T, 52T, 106T, 242T, 484T and 996T as worst-case PSD.

Full RU mode Harmonics and Spurious Emissions were ran at maximum power between 26T, 52T, 104T, 242T, 484T and Full RU modes across all bandwidths and bands to cover HE20 52T and 106, HE40 26T, 52T, 106T and 242T, HE80 26T, 52T,106T, 242T and 484T, HE160 26T, 52T, 106T, 242T, 484T and 996T as worst-case power.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency Band	Antenna Type	Max Antenna Gain (dBi)
0	5150-5850	FPC Antenna	0.5
1	5150-5850	FPC Antenna	0.5

The EUT support Space Time Coding(STBC) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the STBC results the Directional Gain was calculated in accordance with the following mothed.

Directional gain = 10 log[($10^{G1/10}$ + $10^{G2/10}$ + … + $10^{GN/10}$)/NANT] dBi

Directional gain = 0.5 dBi

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11n HT20	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11n HT40	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT20	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT40	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT80	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT160	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ax HE20	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ax HE40	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ax HE80	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.
802.11ax HE160	☒2TX, 2RX	ANT 0 and ANT 1 can be used as transmitting/receiving antenna.

Note: Only BT&WLAN 2.4G, BT & WLAN 5G, BT & WLAN 6G can transmit simultaneously. (declared by manufacturer)

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E14	/
2	AC Adaptor	/	2ACP0183C	Input: AC 100-240V, 0.5A, 50-60Hz Output: DC 5V, 3A,15W

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.5	/

ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/


TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.


This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

SETUP DIAGRAM FOR TESTS

For others:



For AC Power Line Conducted Emission:



This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer	Name	Version		
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32	10.60.10		
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name	Version		
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System	V3.2.22		

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Sep.28, 2024	Sep.27, 2025

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Software			
Description	Manufacturer	Name	Version
Test Software for Radiated Emissions	Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ EBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 22, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix G

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7.2. 6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15, Subpart E ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725 (For FCC) 5470 ~ 5600 (For ISED) 5650 ~ 5725 (For ISED)
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.
Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: ≥ 3*RBW For 26 dB Bandwidth: >3*RBW For 99 % Bandwidth: >3*RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

99 % Bandwidth of UNII-2C Band Portion = (5725-(5720-(21.00/2)) = 15.50 MHz

99 % Bandwidth of UNII-3 Band Portion = (5720+(21.00/2)-5725) = 5.50 MHz

Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion = 5725-5710.16=14.84 MHz

Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz


FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion = 5728.2-5725=3.2 MHz

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 21, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B&C

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	☐ Outdoor Access Point: 1 W (30 dBm) ☐ Indoor Access Point: 1 W (30 dBm) ☐ Fixed Point-To-Point Access Points: 1 W (30 dBm) ☒ Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power or e.i.r.p.	The maximum e.i.r.p. shall not exceed 200 mW (23 dBm) or 10 + 10 $\log_{10}$B, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz.	5150 ~ 5250
	a. The maximum conducted output power shall not exceed 250 mW (24 dBm) or 11 + 10 $\log_{10}$B dBm, whichever is less. b. The maximum e.i.r.p. shall not exceed 1.0 W (30 dBm) or 17 + 10 $\log_{10}$B dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	Shall not exceed 1 Watt (30 dBm). The e.i.r.p. shall not exceed 4 W	5725 ~ 5850

Note:
The above limits are based upon the maximum antenna gain does not exceed 6 dBi.
If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method SA-2 (trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction.):
(a) Measure the duty cycle D of the transmitter output signal.
(b) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.


This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

(c) Set RBW = 1 MHz.
(d) Set VBW ⩾ 3 MHz.
(e) Number of points in sweep ⩾ [2 × span / RBW]. (This gives bin-to-bin spacing ⩽ RBW / 2, so that narrowband signals are not lost between frequency bins.)
(f) Sweep time = auto.
(g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
(h) Do not use sweep triggering. Allow the sweep to "free run."
(i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
j) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.
k) Add [10 log (1 / D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add [10 log (1 / 0.25)] = 6 dB if the duty cycle is 25%.

Method PM (Measurement using an RF average power meter):
(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
(ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in II.B.
(iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
(iv) Adjust the measurement in dBm by adding 10 log (1/x) where x is the duty cycle (e.g., 10 log (1/0.25) if the duty cycle is 25 %).

Note: Method SA-2 was used for straddle channel output power test, and Method PM was used for testing rest channels

TEST SETUP



This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 22, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix D

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	☐ Outdoor Access Point: 17 dBm/MHz ☐ Indoor Access Point: 17 dBm/MHz ☐ Fixed Point-To-Point Access Points: 17 dBm/MHz ☒ Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	5150 ~ 5250
	The power spectral density shall not exceed 11 dBm inany 1.0 MHz band.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	30 dBm / 500 kHz	5725 ~ 5850

Note:
The above limits are based upon the maximum antenna gain does not exceed 6 dBi.
If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyzer and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	≥3 × RBW
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Average
Sweep time	Auto


This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	≥3 × RBW
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Average
Sweep time	Auto

Allow trace to fully stabilize and use the peak search function on the instrument to find the peak of the spectrum and record its value.
Add 10 log (1/x), where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 22, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix E

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7.5. FREQUENCY STABILITY

LIMITS

The frequency of the carrier signal shall be maintained within band of operation.

TEST PROCEDURE

1. The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between -10 °C ~ 50 °C (declared by customer).

2. The temperature was incremented by 10 °C intervals and the unit allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.

3. The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	10 kHz
VBW	≥3 × RBW
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

4. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup, and at 2 minutes, 5minutes, and 10 minutes after the EUT is energized.

5. Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.


TEST ENVIRONMENT

	Normal Test Conditions	Extreme Test Conditions
Relative Humidity	20 % ~ 75 %	/
Atmospheric Pressure	100 kPa ~ 102 kPa	/
Temperature	T_N (Normal Temperature): 25.1 °C	T_L (Low Temperature): -10 °C
		T_H (High Temperature): 50 °C
Supply Voltage	V_N (Normal Voltage): DC 3.635 V	V_L (Low Voltage): DC 3.2 V
		V_H (High Voltage): DC 4.2 V

Note: The manufacturer declares that the device operates at DC 3.2V~DC 4.2V.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 22, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix F

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7.6. DYNAMIC FREQUENCY SELECTION (SLAVE)

LIMITS

(1) DFS Detection Thresholds

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

(2) DFS Response Requirements

Table 4: DFS Response Requirement Values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required facilitating a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

APPLICABILITY OF DFS REQUIREMENTS

A U-NII network will employ a DFS function to detect signals from radar systems and to avoid co-channel operation with these systems. This applies to the 5250-5350 MHz and/or 5470-5725 MHz bands.
Within the context of the operation of the DFS function, a U-NII device will operate in either Master Mode or Client Mode. U-NII devices operating in Client Mode can only operate in a network controlled by a U-NII device operating in Master Mode.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	☐ Master	☒ Client Without Radar Detection	☐ Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

PARAMETERS OF RADAR TEST WAVEFORMS

This section provides the parameters for required test waveforms, minimum percentage of successful detections, and the minimum number of trials that must be used for determining DFS conformance. Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.


Table 5 Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A	$\text{Roundup}\left\{\left(\frac{1}{360}\right)\cdot\left(\frac{19\cdot10^6}{\text{PRI}_{\mu\text{sec}}}\right)\right\}$	60%	30
		Test B			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.
Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a
Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. Test aggregate is average of the percentage of successful detections of short pulse radar types 1-4.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3℃	Relative Humidity	55%

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Atmosphere Pressure	101kPa	Test Voltage	DC 3.635V

TEST DATE / ENGINEER

Test Date	July 22, 2025	Test By	Bairong Liu

TEST RESULTS

Please refer to section "Test Data" - Appendix H&I&J

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8. RADIATED TEST RESULTS

LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Refer to ISED RSS-GEN Clause 8.9, Clause 8.10 and ISED RSS-247 7.3.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz[Note 1]	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

ISED Restricted bands refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands[Note 1]		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

Note: [1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
[2]Above 38.6c

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISED RSS-247 7.3.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to Y-51.5 = Z dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1 GHz, the initial step of collecting radiated emission data is to set a spectrum analyzer peak detector mode, pre-scanning the measurement frequency range. Significant peaks then be marked and each peak mark is checked to be highest by slowing down the sweep time, rotated speed of turntable and lifting speed of receive antenna, then switch to receiver mode to read QP value for the marker whose margin is less than 3dB.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.


3. The EUT was placed on a turntable with 1.5 m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

For Restricted Bandedge:
Note:
1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):
Note:
1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5

For Radiate Spurious Emission (30 MHz ~ 1 GHz):
Note:
1. Result Level = Read Level + Correct Factor.
2. The peak value is compliant with the QP limit, and the margin is greater than 3dB, QP value is not captured.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 7 GHz):
1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.


This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

For Radiate Spurious Emission (7 GHz ~ 18 GHz):
Note:
1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):
Note:
1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


For Radiate Spurious emission (26 GHz ~ 40 GHz):
Note:
1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.

TEST SETUP




This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	21.3℃	Relative Humidity	58.9%
Atmosphere Pressure	101kPa	Test Voltage	

TEST DATE / ENGINEER


Test Date	August 6, 2025	Test By	Mason Wang

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

TEST RESULTS

8.1. RESTRICTED BANDEDGE


Test Mode:	802.11a 20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.940	19.73	38.88	58.61	74.00	-15.39	peak
2	5150.000	18.21	38.88	57.09	74.00	-16.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.940	5.60	38.88	44.48	54.00	-9.52	AVG
2	5150.000	5.78	38.88	44.66	54.00	-9.34	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5101.370	18.35	38.82	57.17	74.00	-16.83	peak
2	5150.000	17.13	38.88	56.01	74.00	-17.99	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5101.370	3.49	38.82	42.31	54.00	-11.69	AVG
2	5150.000	4.92	38.88	43.80	54.00	-10.20	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5069.280	18.34	38.79	57.13	74.00	-16.87	peak
2	5150.000	16.35	38.88	55.23	74.00	-18.77	peak
3	5350.000	16.13	39.25	55.38	74.00	-18.62	peak
4	5446.560	17.90	39.45	57.35	74.00	-16.65	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5069.280	2.98	38.79	41.77	54.00	-12.23	AVG
2	5150.000	3.12	38.88	42.00	54.00	-12.00	AVG
3	5350.000	2.99	39.25	42.24	54.00	-11.76	AVG
4	5446.560	3.48	39.45	42.93	54.00	-11.07	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5134.560	18.25	38.86	57.11	74.00	-16.89	peak
2	5150.000	16.88	38.88	55.76	74.00	-18.24	peak
3	5350.000	16.44	39.25	55.69	74.00	-18.31	peak
4	5397.600	17.76	39.36	57.12	74.00	-16.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5134.560	3.29	38.86	42.15	54.00	-11.85	AVG
2	5150.000	3.21	38.88	42.09	54.00	-11.91	AVG
3	5350.000	3.46	39.25	42.71	54.00	-11.29	AVG
4	5397.600	3.12	39.36	42.48	54.00	-11.52	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	27.07	39.25	66.32	74.00	-7.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	11.73	39.25	50.98	54.00	-3.02	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	22.04	39.48	61.52	74.00	-12.48	peak
2	5467.540	27.40	39.49	66.89	68.20	-1.31	peak
3	5470.000	26.96	39.50	66.46	68.20	-1.74	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	6.01	39.48	45.49	54.00	-8.51	AVG
2	5467.540	9.09	39.49	48.58	/	/	AVG
3	5470.000	10.09	39.50	49.59	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	27.08	39.94	67.02	68.20	-1.18	peak
2	5725.620	27.83	39.95	67.78	68.20	-0.42	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5649.590	26.26	39.86	66.12	68.20	-2.08	peak
2	5654.910	31.34	39.87	71.21	71.85	-0.64	peak
3	5725.000	55.96	39.94	95.90	122.20	-26.30	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	50.53	40.13	90.66	122.20	-31.54	peak
2	5926.860	25.10	40.30	65.40	68.20	-2.80	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5084.330	18.69	38.80	57.49	74.00	-16.51	peak
2	5150.000	17.83	38.88	56.71	74.00	-17.29	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5084.330	3.24	38.80	42.04	54.00	-11.96	AVG
2	5150.000	4.94	38.88	43.82	54.00	-10.18	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.280	18.48	38.45	56.93	74.00	-17.07	peak
2	5150.000	16.59	38.88	55.47	74.00	-18.53	peak
3	5350.000	15.74	39.25	54.99	74.00	-19.01	peak
4	5424.480	17.56	39.41	56.97	74.00	-17.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.280	3.85	38.45	42.30	54.00	-11.70	AVG
2	5150.000	3.22	38.88	42.10	54.00	-11.90	AVG
3	5350.000	3.20	39.25	42.45	54.00	-11.55	AVG
4	5424.480	3.10	39.41	42.51	54.00	-11.49	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5140.320	18.12	38.87	56.99	74.00	-17.01	peak
2	5150.000	16.41	38.88	55.29	74.00	-18.71	peak
3	5350.000	16.85	39.25	56.10	74.00	-17.90	peak
4	5428.320	17.43	39.41	56.84	74.00	-17.16	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5140.320	3.15	38.87	42.02	54.00	-11.98	AVG
2	5150.000	3.15	38.88	42.03	54.00	-11.97	AVG
3	5350.000	3.08	39.25	42.33	54.00	-11.67	AVG
4	5428.320	3.19	39.41	42.60	54.00	-11.40	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	29.94	39.25	69.19	74.00	-4.81	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	13.80	39.25	53.05	54.00	-0.95	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.360	24.98	39.48	64.46	74.00	-9.54	peak
2	5460.000	21.30	39.48	60.78	74.00	-13.22	peak
3	5469.880	27.54	39.50	67.04	68.20	-1.16	peak
4	5470.000	26.64	39.50	66.14	68.20	-2.06	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.360	7.05	39.48	46.53	54.00	-7.47	AVG
2	5460.000	7.71	39.48	47.19	54.00	-6.81	AVG
3	5469.880	10.24	39.50	49.74	/	/	AVG
4	5470.000	10.23	39.50	49.73	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	26.24	39.94	66.18	68.20	-2.02	peak
2	5725.260	26.50	39.95	66.45	68.20	-1.75	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5643.320	27.79	39.85	67.64	68.20	-0.56	peak
2	5725.000	56.32	39.94	96.26	122.20	-25.94	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	49.02	40.13	89.15	122.20	-33.05	peak
2	5927.090	25.96	40.30	66.26	68.20	-1.94	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.050	31.55	38.88	70.43	74.00	-3.57	peak
2	5150.000	30.01	38.88	68.89	74.00	-5.11	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 AV	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.050	10.48	38.88	49.36	54.00	-4.64	AVG
2	5150.000	12.76	38.88	51.64	54.00	-2.36	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.000	25.79	38.88	64.67	74.00	-9.33	peak
2	5150.000	24.60	38.88	63.48	74.00	-10.52	peak
3	5350.000	21.16	39.25	60.41	74.00	-13.59	peak
4	5370.720	22.70	39.30	62.00	74.00	-12.00	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 AV	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.000	11.39	38.88	50.27	54.00	-3.73	AVG
2	5150.000	11.43	38.88	50.31	54.00	-3.69	AVG
3	5350.000	7.99	39.25	47.24	54.00	-6.76	AVG
4	5370.720	6.51	39.30	45.81	54.00	-8.19	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.280	19.10	38.45	57.55	74.00	-16.45	peak
2	5150.000	17.20	38.88	56.08	74.00	-17.92	peak
3	5350.000	17.55	39.25	56.80	74.00	-17.20	peak
4	5353.440	19.00	39.26	58.26	74.00	-15.74	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 AV	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.280	3.95	38.45	42.40	54.00	-11.60	AVG
2	5150.000	3.94	38.88	42.82	54.00	-11.18	AVG
3	5350.000	5.48	39.25	44.73	54.00	-9.27	AVG
4	5353.440	5.14	39.26	44.40	54.00	-9.60	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	26.99	39.25	66.24	74.00	-7.76	peak
2	5351.320	27.42	39.26	66.68	74.00	-7.32	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	12.96	39.25	52.21	54.00	-1.79	AVG
2	5351.320	11.77	39.26	51.03	54.00	-2.97	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	23.83	39.48	63.31	74.00	-10.69	peak
2	5470.000	27.12	39.50	66.62	68.20	-1.58	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 AV	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	7.43	39.48	46.91	54.00	-7.09	AVG
2	5470.000	12.33	39.50	51.83	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	27.35	39.94	67.29	68.20	-0.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.650	26.28	39.85	66.13	68.20	-2.07	peak
2	5725.000	39.35	39.94	79.29	122.20	-42.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40 PK	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	35.97	40.13	76.10	122.20	-46.10	peak
2	5933.530	27.21	40.31	67.52	68.20	-0.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5141.480	27.62	38.87	66.49	74.00	-7.51	peak
2	5150.000	26.16	38.88	65.04	74.00	-8.96	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 AV	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5141.480	10.62	38.87	49.49	54.00	-4.51	AVG
2	5150.000	12.39	38.88	51.27	54.00	-2.73	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	27.71	39.25	66.96	74.00	-7.04	peak
2	5359.020	31.42	39.28	70.70	74.00	-3.30	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 AV	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	14.56	39.25	53.81	54.00	-0.19	AVG
2	5359.020	13.97	39.28	53.25	54.00	-0.75	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.250	25.41	39.48	64.89	74.00	-9.11	peak
2	5460.000	23.78	39.48	63.26	74.00	-10.74	peak
3	5467.530	28.31	39.49	67.80	68.20	-0.40	peak
4	5470.000	26.43	39.50	65.93	68.20	-2.27	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 AV	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.250	10.71	39.48	50.19	54.00	-3.81	AVG
2	5460.000	10.41	39.48	49.89	54.00	-4.11	AVG
3	5467.530	11.90	39.49	51.39	/	/	AVG
4	5470.000	11.64	39.50	51.14	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	27.79	39.94	67.73	68.20	-0.47	peak
2	5730.000	28.07	39.94	68.01	68.20	-0.19	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5645.200	26.90	39.85	66.75	68.20	-1.45	peak
2	5725.000	35.30	39.94	75.24	122.20	-46.96	peak
3	5850.000	29.99	40.13	70.12	122.20	-52.08	peak
4	5926.000	24.03	40.29	64.32	68.20	-3.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160 PK	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5139.360	22.11	38.87	60.98	74.00	-13.02	peak
2	5150.000	20.01	38.88	58.89	74.00	-15.11	peak
3	5350.000	25.82	39.25	65.07	74.00	-8.93	peak
4	5369.760	30.24	39.30	69.54	74.00	-4.46	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160 AV	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5139.360	7.06	38.87	45.93	54.00	-8.07	AVG
2	5150.000	6.70	38.88	45.58	54.00	-8.42	AVG
3	5369.760	13.67	39.30	52.97	54.00	-1.03	AVG
4	5379.360	14.19	39.31	53.50	54.00	-0.50	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160 PK	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.500	26.93	39.46	66.39	74.00	-7.61	peak
2	5459.000	26.16	39.48	65.64	74.00	-8.36	peak
3	5460.000	26.40	39.48	65.88	74.00	-8.12	peak
4	5467.500	27.77	39.49	67.26	68.20	-0.94	peak
5	5470.000	26.00	39.50	65.50	68.20	-2.70	peak
6	5725.000	24.91	39.94	64.85	68.20	-3.35	peak
7	5730.000	26.24	39.94	66.18	68.20	-2.02	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160 AV	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.500	13.62	39.46	53.08	54.00	-0.92	AVG
2	5459.000	13.72	39.48	53.20	54.00	-0.80	AVG
3	5460.000	13.31	39.48	52.79	54.00	-1.21	AVG
4	5467.500	13.46	39.49	52.95	/	/	AVG
5	5470.000	13.39	39.50	52.89	/	/	AVG
6	5725.000	10.55	39.94	50.49	/	/	AVG
7	5730.000	12.89	39.94	52.83	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	18.14	38.88	57.02	74.00	-16.98	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	5.30	38.88	44.18	54.00	-9.82	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4826.400	18.81	38.35	57.16	74.00	-16.84	peak
2	5150.000	17.79	38.88	56.67	74.00	-17.33	peak
3	5350.000	16.84	39.25	56.09	74.00	-17.91	peak
4	5421.600	17.84	39.40	57.24	74.00	-16.76	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4826.400	3.45	38.35	41.80	54.00	-12.20	AVG
2	5150.000	3.20	38.88	42.08	54.00	-11.92	AVG
3	5350.000	2.98	39.25	42.23	54.00	-11.77	AVG
4	5421.600	2.98	39.40	42.38	54.00	-11.62	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4878.240	18.56	38.46	57.02	74.00	-16.98	peak
2	5150.000	16.65	38.88	55.53	74.00	-18.47	peak
3	5350.000	16.50	39.25	55.75	74.00	-18.25	peak
4	5460.000	17.93	39.48	57.41	68.20	-10.79	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4878.240	3.76	38.46	42.22	54.00	-11.78	AVG
2	5150.000	2.99	38.88	41.87	54.00	-12.13	AVG
3	5350.000	3.02	39.25	42.27	54.00	-11.73	AVG
4	5460.000	3.18	39.48	42.66	54.00	-11.34	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	39.31	32.78	72.09	74.00	-1.91	peak
2	5350.350	40.63	32.78	73.41	74.00	-0.59	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	20.37	32.78	53.15	54.00	-0.85	AVG
2	5350.350	20.03	32.78	52.81	54.00	-1.19	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	23.39	39.48	62.87	74.00	-11.13	peak
2	5469.160	28.26	39.50	67.76	68.20	-0.44	peak
3	5470.000	24.82	39.50	64.32	68.20	-3.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	5.41	39.48	44.89	54.00	-9.11	AVG
2	5469.160	7.08	39.50	46.58	/	/	AVG
3	5470.000	7.42	39.50	46.92	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	26.67	39.94	66.61	68.20	-1.59	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.270	27.92	39.85	67.77	68.20	-0.43	peak
2	5725.000	56.09	39.94	96.03	122.20	-26.17	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	52.34	40.13	92.47	122.20	-29.73	peak
2	5927.320	27.21	40.30	67.51	68.20	-0.69	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.700	33.25	38.88	72.13	74.00	-1.87	peak
2	5150.000	31.24	38.88	70.12	74.00	-3.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.700	14.66	38.88	53.54	54.00	-0.46	AVG
2	5150.000	14.64	38.88	53.52	54.00	-0.48	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.120	25.66	38.88	64.54	74.00	-9.46	peak
2	5150.000	24.17	38.88	63.05	74.00	-10.95	peak
3	5350.000	21.69	39.25	60.94	74.00	-13.06	peak
4	5358.240	22.28	39.28	61.56	74.00	-12.44	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.120	5.64	38.88	44.52	54.00	-9.48	AVG
2	5150.000	8.74	38.88	47.62	54.00	-6.38	AVG
3	5350.000	5.00	39.25	44.25	54.00	-9.75	AVG
4	5358.240	4.32	39.28	43.60	54.00	-10.40	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	21.54	38.88	60.42	74.00	-13.58	peak
2	5350.000	24.85	39.25	64.10	74.00	-9.90	peak
3	5356.320	26.85	39.26	66.11	74.00	-7.89	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	4.75	38.88	43.63	54.00	-10.37	AVG
2	5350.000	9.04	39.25	48.29	54.00	-5.71	AVG
3	5356.320	7.99	39.26	47.25	54.00	-6.75	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	30.40	39.25	69.65	74.00	-4.35	peak
2	5350.560	32.51	39.26	71.77	74.00	-2.23	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	14.66	39.25	53.91	54.00	-0.09	AVG
2	5350.560	14.39	39.26	53.65	54.00	-0.35	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.250	24.13	39.48	63.61	74.00	-10.39	peak
2	5460.000	21.44	39.48	60.92	74.00	-13.08	peak
3	5469.700	27.21	39.50	66.71	68.20	-1.49	peak
4	5470.000	24.86	39.50	64.36	68.20	-3.84	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.250	6.31	39.48	45.79	54.00	-8.21	AVG
2	5460.000	6.43	39.48	45.91	54.00	-8.09	AVG
3	5469.700	10.46	39.50	49.96	/	/	AVG
4	5470.000	10.62	39.50	50.12	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	25.53	39.94	65.47	68.20	-2.73	peak
2	5726.310	27.92	39.95	67.87	68.20	-0.33	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5642.180	25.16	39.86	65.02	68.20	-3.18	peak
2	5725.000	40.59	39.94	80.53	122.20	-41.67	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	38.42	40.13	78.55	122.20	-43.65	peak
2	5928.930	26.19	40.30	66.49	68.20	-1.71	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5134.370	27.62	38.86	66.48	74.00	-7.52	peak
2	5150.000	27.57	38.88	66.45	74.00	-7.55	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 AV	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5134.370	9.66	38.86	48.52	54.00	-5.48	AVG
2	5150.000	14.01	38.88	52.89	54.00	-1.11	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	28.34	39.25	67.59	74.00	-6.41	peak
2	5350.660	30.07	39.26	69.33	74.00	-4.67	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 AV	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	14.50	39.25	53.75	54.00	-0.25	AVG
2	5350.660	14.09	39.26	53.35	54.00	-0.65	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.180	27.41	39.48	66.89	74.00	-7.11	peak
2	5460.000	23.52	39.48	63.00	74.00	-11.00	peak
3	5467.070	28.63	39.49	68.12	68.20	-0.08	peak
4	5470.000	26.78	39.50	66.28	68.20	-1.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 AV	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.180	10.45	39.48	49.93	54.00	-4.07	AVG
2	5460.000	10.40	39.48	49.88	54.00	-4.12	AVG
3	5467.070	12.16	39.49	51.65	/	/	AVG
4	5470.000	11.80	39.50	51.30	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5642.800	26.63	39.85	66.48	68.20	-1.72	peak
2	5725.000	32.73	39.94	72.67	122.20	-49.53	peak
3	5850.000	29.41	40.13	69.54	122.20	-52.66	peak
4	5930.000	22.97	40.30	63.27	68.20	-4.93	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160 PK	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.000	20.89	38.88	59.77	74.00	-14.23	peak
2	5150.000	19.14	38.88	58.02	74.00	-15.98	peak
3	5350.000	22.56	39.25	61.81	74.00	-12.19	peak
4	5380.160	26.00	39.31	65.31	74.00	-8.69	peak
5	5384.160	28.58	39.33	67.91	74.00	-6.09	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160 AV	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.000	7.28	38.88	46.16	54.00	-7.84	AVG
2	5150.000	7.15	38.88	46.03	54.00	-7.97	AVG
3	5350.000	10.45	39.25	49.70	54.00	-4.30	AVG
4	5380.320	14.11	39.31	53.42	54.00	-0.58	AVG
5	5384.160	12.14	39.33	51.47	54.00	-2.53	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160 PK	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.000	27.15	39.46	66.61	74.00	-7.39	peak
2	5460.000	25.21	39.48	64.69	74.00	-9.31	peak
3	5468.500	26.77	39.49	66.26	68.20	-1.94	peak
4	5470.000	25.98	39.50	65.48	68.20	-2.72	peak
5	5725.000	24.31	39.94	64.25	68.20	-3.95	peak
6	5740.000	26.14	39.96	66.10	68.20	-2.10	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11ax HE160 AV	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.000	12.00	39.46	51.46	54.00	-2.54	AVG
2	5460.000	12.31	39.48	51.79	54.00	-2.21	AVG
3	5468.500	12.29	39.49	51.78	/	/	AVG
4	5470.000	11.39	39.50	50.89	/	/	AVG
5	5725.000	12.05	39.94	51.99	/	/	AVG
6	5740.000	9.80	39.96	49.76	/	/	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.2. RESTRICTED BANDEDGE PARTIAL RU


Test Mode:	802.11ax HE20 Tone26 RU0 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5020.430	18.61	38.73	57.34	74.00	-16.66	peak
2	5150.000	16.96	38.88	55.84	74.00	-18.16	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5020.430	3.21	38.73	41.94	54.00	-12.06	AVG
2	5150.000	3.17	38.88	42.05	54.00	-11.95	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.150	18.65	38.36	57.01	74.00	-16.99	peak
2	5150.000	16.41	38.88	55.29	74.00	-18.71	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4830.150	3.55	38.36	41.91	54.00	-12.09	AVG
2	5150.000	3.27	38.88	42.15	54.00	-11.85	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4881.270	18.92	38.46	57.38	74.00	-16.62	peak
2	5150.000	17.44	38.88	56.32	74.00	-17.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4881.270	3.94	38.46	42.40	54.00	-11.60	AVG
2	5150.000	3.60	38.88	42.48	54.00	-11.52	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4870.560	18.48	38.44	56.92	74.00	-17.08	peak
2	5150.000	16.18	38.88	55.06	74.00	-18.94	peak
3	5350.000	17.17	39.25	56.42	74.00	-17.58	peak
4	5358.240	17.95	39.28	57.23	74.00	-16.77	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4870.560	3.88	38.44	42.32	54.00	-11.68	AVG
2	5150.000	3.07	38.88	41.95	54.00	-12.05	AVG
3	5350.000	2.99	39.25	42.24	54.00	-11.76	AVG
4	5358.240	2.95	39.28	42.23	54.00	-11.77	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4884.960	18.46	38.47	56.93	74.00	-17.07	peak
2	5150.000	16.46	38.88	55.34	74.00	-18.66	peak
3	5350.000	16.77	39.25	56.02	74.00	-17.98	peak
4	5435.040	17.72	39.43	57.15	74.00	-16.85	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4884.960	3.96	38.47	42.43	54.00	-11.57	AVG
2	5150.000	3.07	38.88	41.95	54.00	-12.05	AVG
3	5350.000	2.99	39.25	42.24	54.00	-11.76	AVG
4	5435.040	3.20	39.43	42.63	54.00	-11.37	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU54 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4925.280	18.63	38.55	57.18	74.00	-16.82	peak
2	5150.000	16.02	38.88	54.90	74.00	-19.10	peak
3	5350.000	17.16	39.25	56.41	74.00	-17.59	peak
4	5437.920	18.17	39.43	57.60	74.00	-16.40	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU54 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4925.280	3.56	38.55	42.11	54.00	-11.89	AVG
2	5150.000	3.15	38.88	42.03	54.00	-11.97	AVG
3	5350.000	2.93	39.25	42.18	54.00	-11.82	AVG
4	5437.920	3.22	39.43	42.65	54.00	-11.35	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5024.160	18.36	38.73	57.09	74.00	-16.91	peak
2	5150.000	15.78	38.88	54.66	74.00	-19.34	peak
3	5350.000	15.97	39.25	55.22	74.00	-18.78	peak
4	5450.400	17.78	39.46	57.24	74.00	-16.76	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5024.160	3.12	38.73	41.85	54.00	-12.15	AVG
2	5150.000	3.04	38.88	41.92	54.00	-12.08	AVG
3	5350.000	3.11	39.25	42.36	54.00	-11.64	AVG
4	5450.400	3.53	39.46	42.99	54.00	-11.01	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4911.840	18.98	38.52	57.50	74.00	-16.50	peak
2	5150.000	16.23	38.88	55.11	74.00	-18.89	peak
3	5350.000	16.35	39.25	55.60	74.00	-18.40	peak
4	5448.480	17.62	39.46	57.08	74.00	-16.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4911.840	3.60	38.52	42.12	54.00	-11.88	AVG
2	5150.000	3.08	38.88	41.96	54.00	-12.04	AVG
3	5350.000	3.08	39.25	42.33	54.00	-11.67	AVG
4	5448.480	3.55	39.46	43.01	54.00	-10.99	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 PK	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4900.320	18.84	38.50	57.34	74.00	-16.66	peak
2	5150.000	16.17	38.88	55.05	74.00	-18.95	peak
3	5350.000	16.63	39.25	55.88	74.00	-18.12	peak
4	5451.360	17.77	39.46	57.23	74.00	-16.77	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 AV	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4900.320	3.91	38.50	42.41	54.00	-11.59	AVG
2	5150.000	3.01	38.88	41.89	54.00	-12.11	AVG
3	5350.000	3.03	39.25	42.28	54.00	-11.72	AVG
4	5451.360	3.55	39.46	43.01	54.00	-10.99	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	33.73	39.25	72.98	74.00	-1.02	peak
2	5350.520	34.28	39.26	73.54	74.00	-0.46	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	5.56	39.25	44.81	54.00	-9.19	AVG
2	5350.520	5.35	39.26	44.61	54.00	-9.39	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	33.97	39.25	73.22	74.00	-0.78	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	5.56	39.25	44.81	54.00	-9.19	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU54 PK	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	34.50	39.25	73.75	74.00	-0.25	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU54 AV	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5350.000	8.86	39.25	48.11	54.00	-5.89	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5458.180	21.99	39.48	61.47	74.00	-12.53	peak
2	5460.000	17.34	39.48	56.82	68.20	-11.38	peak
3	5470.000	27.90	39.50	67.40	68.20	-0.80	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5458.180	5.08	39.48	44.56	54.00	-9.44	AVG
2	5460.000	4.68	39.48	44.16	54.00	-9.84	AVG
3	5470.000	5.09	39.50	44.59	68.20	-23.61	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.440	23.20	39.48	62.68	74.00	-11.32	peak
2	5460.000	18.85	39.48	58.33	68.20	-9.87	peak
3	5468.620	28.15	39.49	67.64	68.20	-0.56	peak
4	5470.000	27.97	39.50	67.47	68.20	-0.73	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5459.440	4.54	39.48	44.02	54.00	-9.98	AVG
2	5460.000	4.65	39.48	44.13	54.00	-9.87	AVG
3	5468.620	4.64	39.49	44.13	68.20	-24.07	AVG
4	5470.000	4.81	39.50	44.31	68.20	-23.89	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 PK	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.540	20.31	39.48	59.79	74.00	-14.21	peak
2	5460.000	19.31	39.48	58.79	68.20	-9.41	peak
3	5469.880	28.20	39.50	67.70	68.20	-0.50	peak
4	5470.000	27.98	39.50	67.48	68.20	-0.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 AV	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5458.540	4.12	39.48	43.60	54.00	-10.40	AVG
2	5460.000	4.30	39.48	43.78	54.00	-10.22	AVG
3	5469.880	6.98	39.50	46.48	68.20	-21.72	AVG
4	5470.000	7.00	39.50	46.50	68.20	-21.70	AVG

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5725.000	26.48	39.94	66.42	68.20	-1.78	peak
2	5725.260	27.22	39.95	67.17	68.20	-1.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5725.000	28.16	39.94	68.10	68.20	-0.10	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU54 PK	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5725.000	24.71	39.94	64.65	68.20	-3.55	peak
2	5725.260	27.60	39.95	67.55	68.20	-0.65	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5644.650	18.87	39.85	58.72	68.20	-9.48	peak
2	5725.000	48.82	39.94	88.76	122.20	-33.44	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU37 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5645.410	19.64	39.85	59.49	68.20	-8.71	peak
2	5725.000	49.05	39.94	88.99	122.20	-33.21	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone106 RU53 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5644.270	18.76	39.85	58.61	68.20	-9.59	peak
2	5725.000	55.21	39.94	95.15	122.20	-27.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	40.04	40.13	80.17	122.20	-42.03	peak
2	5957.450	20.13	40.36	60.49	68.20	-7.71	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone52 RU40 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5850.000	40.70	40.13	80.83	122.20	-41.37	peak
2	5946.410	19.90	40.33	60.23	68.20	-7.97	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11ax HE20 Tone106 RU54 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5850.000	43.48	40.13	83.61	122.20	-38.59	peak
2	5950.320	20.00	40.34	60.34	68.20	-7.86	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.3. SPURIOUS EMISSIONS(1 GHZ~7 GHZ)


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2818.000	43.78	-6.97	36.81	74.00	-37.19	peak
2	3220.000	43.63	-5.09	38.54	68.20	-29.66	peak
3	3814.000	42.83	-2.84	39.99	74.00	-34.01	peak
4	5002.000	40.92	1.90	42.82	74.00	-31.18	peak
5	5992.000	38.69	5.39	44.08	68.20	-24.12	peak
6	6862.000	36.66	6.63	43.29	68.20	-24.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1798.000	45.95	-10.09	35.86	68.20	-32.34	peak
2	2758.000	44.04	-7.20	36.84	74.00	-37.16	peak
3	3832.000	42.54	-2.81	39.73	74.00	-34.27	peak
4	4912.000	40.92	1.49	42.41	74.00	-31.59	peak
5	5902.000	40.02	4.90	44.92	68.20	-23.28	peak
6	6910.000	38.89	6.61	45.50	68.20	-22.70	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1750.000	45.20	-10.42	34.78	68.20	-33.42	peak
2	2860.000	43.31	-6.79	36.52	74.00	-37.48	peak
3	3634.000	43.18	-3.24	39.94	74.00	-34.06	peak
4	4648.000	42.15	0.37	42.52	74.00	-31.48	peak
5	5872.000	39.85	4.73	44.58	68.20	-23.62	peak
6	6694.000	36.94	6.37	43.31	68.20	-24.89	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1810.000	45.77	-10.09	35.68	68.20	-32.52	peak
2	2620.000	44.29	-7.73	36.56	68.20	-31.64	peak
3	4654.000	41.86	0.40	42.26	74.00	-31.74	peak
4	5200.000	41.33	2.06	43.39	68.20	-24.81	peak
5	6022.000	39.04	5.52	44.56	68.20	-23.64	peak
6	6670.000	37.75	6.30	44.05	68.20	-24.15	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1798.000	45.89	-10.09	35.80	68.20	-32.40	peak
2	2986.000	42.95	-6.27	36.68	68.20	-31.52	peak
3	3700.000	42.79	-3.09	39.70	74.00	-34.30	peak
4	4960.000	41.47	1.72	43.19	74.00	-30.81	peak
5	5968.000	38.93	5.26	44.19	68.20	-24.01	peak
6	6826.000	37.25	6.66	43.91	68.20	-24.29	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1756.000	46.26	-10.38	35.88	68.20	-32.32	peak
2	3640.000	43.12	-3.23	39.89	74.00	-34.11	peak
3	4516.000	42.01	-0.25	41.76	74.00	-32.24	peak
4	5242.000	40.07	2.23	42.30	68.20	-25.90	peak
5	6274.000	39.27	6.07	45.34	68.20	-22.86	peak
6	6700.000	37.24	6.39	43.63	68.20	-24.57	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2368.000	44.62	-8.77	35.85	74.00	-38.15	peak
2	3634.000	42.35	-3.24	39.11	74.00	-34.89	peak
3	4246.000	42.88	-1.53	41.35	74.00	-32.65	peak
4	5260.000	40.73	2.30	43.03	68.20	-25.17	peak
5	5992.000	39.64	5.39	45.03	68.20	-23.17	peak
6	6856.000	36.53	6.63	43.16	68.20	-25.04	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2776.000	44.74	-7.12	37.62	74.00	-36.38	peak
2	3484.000	44.06	-3.85	40.21	68.20	-27.99	peak
3	4708.000	43.19	0.60	43.79	74.00	-30.21	peak
4	5266.000	41.32	2.32	43.64	68.20	-24.56	peak
5	6046.000	40.04	5.62	45.66	68.20	-22.54	peak
6	6670.000	37.44	6.30	43.74	68.20	-24.46	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2644.000	45.50	-7.63	37.87	68.20	-30.33	peak
2	3718.000	43.20	-3.05	40.15	74.00	-33.85	peak
3	4810.000	41.40	1.02	42.42	74.00	-31.58	peak
4	5284.000	41.73	2.40	44.13	68.20	-24.07	peak
5	5956.000	39.01	5.19	44.20	68.20	-24.00	peak
6	6694.000	38.24	6.37	44.61	68.20	-23.59	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1870.000	45.26	-10.16	35.10	68.20	-33.10	peak
2	3388.000	43.20	-4.31	38.89	68.20	-29.31	peak
3	4510.000	42.05	-0.28	41.77	74.00	-32.23	peak
4	5278.000	41.13	2.37	43.50	68.20	-24.70	peak
5	6022.000	39.53	5.52	45.05	68.20	-23.15	peak
6	6856.000	36.88	6.63	43.51	68.20	-24.69	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2788.000	43.59	-7.09	36.50	74.00	-37.50	peak
2	3940.000	42.46	-2.62	39.84	74.00	-34.16	peak
3	4636.000	42.08	0.32	42.40	74.00	-31.60	peak
4	5320.000	42.93	2.54	45.47	68.20	-22.73	peak
5	5890.000	39.36	4.84	44.20	68.20	-24.00	peak
6	6664.000	36.91	6.29	43.20	68.20	-25.00	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2614.000	44.41	-7.75	36.66	68.20	-31.54	peak
2	3712.000	43.11	-3.06	40.05	74.00	-33.95	peak
3	4774.000	41.55	0.87	42.42	74.00	-31.58	peak
4	5326.000	41.69	2.57	44.26	68.20	-23.94	peak
5	6028.000	39.15	5.55	44.70	68.20	-23.50	peak
6	6664.000	37.62	6.29	43.91	68.20	-24.29	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2218.000	45.16	-9.39	35.77	74.00	-38.23	peak
2	3196.000	42.88	-5.21	37.67	68.20	-30.53	peak
3	3634.000	43.01	-3.24	39.77	74.00	-34.23	peak
4	5650.000	40.16	3.70	43.86	68.20	-24.34	peak
5	5974.000	39.19	5.28	44.47	68.20	-23.73	peak
6	6862.000	37.26	6.63	43.89	68.20	-24.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1798.000	46.06	-10.09	35.97	68.20	-32.23	peak
2	3670.000	42.65	-3.16	39.49	74.00	-34.51	peak
3	4834.000	41.78	1.12	42.90	74.00	-31.10	peak
4	5500.000	42.50	3.14	45.64	68.20	-22.56	peak
5	6022.000	39.30	5.52	44.82	68.20	-23.38	peak
6	6598.000	38.43	6.10	44.53	68.20	-23.67	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1810.000	46.18	-10.09	36.09	68.20	-32.11	peak
2	2842.000	43.89	-6.86	37.03	74.00	-36.97	peak
3	4066.000	42.63	-2.24	40.39	74.00	-33.61	peak
4	4780.000	41.40	0.89	42.29	74.00	-31.71	peak
5	5584.000	43.15	3.44	46.59	68.20	-21.61	peak
6	6850.000	36.88	6.64	43.52	68.20	-24.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2626.000	44.64	-7.69	36.95	68.20	-31.25	peak
2	3868.000	43.36	-2.75	40.61	74.00	-33.39	peak
3	4708.000	41.78	0.60	42.38	74.00	-31.62	peak
4	5578.000	40.45	3.42	43.87	68.20	-24.33	peak
5	5962.000	39.34	5.23	44.57	68.20	-23.63	peak
6	6700.000	39.09	6.39	45.48	68.20	-22.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1792.000	45.78	-10.13	35.65	68.20	-32.55	peak
2	2530.000	44.99	-8.08	36.91	68.20	-31.29	peak
3	3628.000	43.00	-3.26	39.74	74.00	-34.26	peak
4	4708.000	41.52	0.60	42.12	74.00	-31.88	peak
5	5704.000	45.27	3.94	49.21	68.20	-18.99	peak
6	6676.000	37.38	6.32	43.70	68.20	-24.50	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1798.000	45.83	-10.09	35.74	68.20	-32.46	peak
2	2704.000	45.11	-7.41	37.70	74.00	-36.30	peak
3	3634.000	42.96	-3.24	39.72	74.00	-34.28	peak
4	4786.000	42.50	0.92	43.42	74.00	-30.58	peak
5	6022.000	39.49	5.52	45.01	68.20	-23.19	peak
6	6838.000	38.04	6.65	44.69	68.20	-23.51	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1732.000	45.80	-10.53	35.27	68.20	-32.93	peak
2	2488.000	44.42	-8.26	36.16	74.00	-37.84	peak
3	3454.000	43.61	-3.98	39.63	68.20	-28.57	peak
4	4816.000	41.49	1.05	42.54	74.00	-31.46	peak
5	5722.000	48.25	4.01	52.26	68.20	-15.94	peak
6	6868.000	36.95	6.63	43.58	68.20	-24.62	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1810.000	45.24	-10.09	35.15	68.20	-33.05	peak
2	2548.000	44.60	-8.01	36.59	68.20	-31.61	peak
3	3682.000	42.29	-3.13	39.16	74.00	-34.84	peak
4	4708.000	42.38	0.60	42.98	74.00	-31.02	peak
5	5392.000	39.36	2.83	42.19	74.00	-31.81	peak
6	5998.000	39.18	5.42	44.60	68.20	-23.60	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1804.000	45.77	-10.08	35.69	68.20	-32.51	peak
2	2362.000	45.09	-8.78	36.31	74.00	-37.69	peak
3	3058.000	44.15	-5.92	38.23	68.20	-29.97	peak
4	4672.000	42.12	0.47	42.59	74.00	-31.41	peak
5	5746.000	45.24	4.11	49.35	68.20	-18.85	peak
6	6700.000	37.09	6.39	43.48	68.20	-24.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1930.000	45.39	-10.22	35.17	68.20	-33.03	peak
2	3106.000	42.36	-5.67	36.69	68.20	-31.51	peak
3	3862.000	42.90	-2.76	40.14	74.00	-33.86	peak
4	4798.000	41.55	0.97	42.52	74.00	-31.48	peak
5	5746.000	41.82	4.11	45.93	68.20	-22.27	peak
6	6718.000	36.78	6.43	43.21	68.20	-24.99	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1810.000	46.02	-10.09	35.93	68.20	-32.27	peak
2	2662.000	44.60	-7.56	37.04	68.20	-31.16	peak
3	3250.000	44.44	-4.96	39.48	68.20	-28.72	peak
4	4702.000	42.10	0.58	42.68	74.00	-31.32	peak
5	5788.000	41.47	4.30	45.77	68.20	-22.43	peak
6	6694.000	36.96	6.37	43.33	68.20	-24.87	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1798.000	45.41	-10.09	35.32	68.20	-32.88	peak
2	2782.000	44.49	-7.11	37.38	74.00	-36.62	peak
3	4312.000	42.69	-1.28	41.41	74.00	-32.59	peak
4	4798.000	41.47	0.97	42.44	74.00	-31.56	peak
5	5656.000	40.36	3.73	44.09	68.20	-24.11	peak
6	6694.000	37.52	6.37	43.89	68.20	-24.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1972.000	46.11	-10.27	35.84	68.20	-32.36	peak
2	3082.000	44.00	-5.79	38.21	68.20	-29.99	peak
3	4282.000	42.04	-1.40	40.64	74.00	-33.36	peak
4	4714.000	42.40	0.63	43.03	74.00	-30.97	peak
5	5944.000	39.56	5.13	44.69	68.20	-23.51	peak
6	6862.000	36.47	6.63	43.10	68.20	-25.10	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1816.000	45.68	-10.10	35.58	68.20	-32.62	peak
2	2800.000	43.23	-7.04	36.19	74.00	-37.81	peak
3	3886.000	43.28	-2.71	40.57	74.00	-33.43	peak
4	4672.000	41.44	0.47	41.91	74.00	-32.09	peak
5	6022.000	39.17	5.52	44.69	68.20	-23.51	peak
6	6682.000	36.10	6.34	42.44	68.20	-25.76	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.4. SPURIOUS EMISSIONS(7 GHZ~18 GHZ)


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7627.000	39.38	7.67	47.05	74.00	-26.95	peak
2	10212.000	37.17	13.35	50.52	68.20	-17.68	peak
3	12269.000	28.40	19.27	47.67	74.00	-26.33	peak
4	13490.000	27.35	22.40	49.75	68.20	-18.45	peak
5	16845.000	25.10	22.19	47.29	68.20	-20.91	peak
6	17989.000	21.86	28.40	50.26	74.00	-23.74	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	39.58	8.01	47.59	68.20	-20.61	peak
2	9266.000	37.98	11.62	49.60	68.20	-18.60	peak
3	10542.000	34.88	14.15	49.03	68.20	-19.17	peak
4	11807.000	29.49	17.95	47.44	74.00	-26.56	peak
5	13897.000	26.13	23.51	49.64	68.20	-18.56	peak
6	17989.000	21.55	28.40	49.95	74.00	-24.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	38.78	8.30	47.08	74.00	-26.92	peak
2	9244.000	37.98	11.56	49.54	68.20	-18.66	peak
3	10410.000	36.28	13.77	50.05	68.20	-18.15	peak
4	12511.000	27.50	19.80	47.30	74.00	-26.70	peak
5	13996.000	25.51	23.89	49.40	68.20	-18.80	peak
6	17978.000	21.95	28.31	50.26	74.00	-23.74	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7924.000	39.39	8.09	47.48	68.20	-20.72	peak
2	9717.000	35.57	13.50	49.07	68.20	-19.13	peak
3	11004.000	34.46	15.47	49.93	74.00	-24.07	peak
4	12247.000	27.74	19.22	46.96	74.00	-27.04	peak
5	13930.000	25.68	23.63	49.31	68.20	-18.89	peak
6	18000.000	21.28	28.51	49.79	74.00	-24.21	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	39.78	8.18	47.96	68.20	-20.24	peak
2	9233.000	38.37	11.52	49.89	68.20	-18.31	peak
3	11389.000	32.47	17.15	49.62	74.00	-24.38	peak
4	12247.000	28.55	19.22	47.77	74.00	-26.23	peak
5	13523.000	26.53	22.48	49.01	68.20	-19.19	peak
6	17989.000	21.33	28.40	49.73	74.00	-24.27	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8122.000	38.97	8.32	47.29	74.00	-26.71	peak
2	9596.000	36.33	13.26	49.59	68.20	-18.61	peak
3	11389.000	31.81	17.15	48.96	74.00	-25.04	peak
4	12577.000	27.18	19.87	47.05	74.00	-26.95	peak
5	13908.000	26.90	23.56	50.46	68.20	-17.74	peak
6	17956.000	21.92	28.10	50.02	74.00	-23.98	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8133.000	39.69	8.33	48.02	74.00	-25.98	peak
2	9728.000	36.54	13.52	50.06	68.20	-18.14	peak
3	10916.000	34.18	15.21	49.39	74.00	-24.61	peak
4	12698.000	27.02	20.20	47.22	74.00	-26.78	peak
5	13919.000	26.14	23.60	49.74	68.20	-18.46	peak
6	17945.000	22.28	28.01	50.29	74.00	-23.71	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	40.03	8.21	48.24	74.00	-25.76	peak
2	9134.000	37.26	11.13	48.39	74.00	-25.61	peak
3	10278.000	35.58	13.48	49.06	68.20	-19.14	peak
4	11631.000	30.90	17.88	48.78	74.00	-25.22	peak
5	13600.000	27.85	22.60	50.45	68.20	-17.75	peak
6	18000.000	21.70	28.51	50.21	74.00	-23.79	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	39.80	7.79	47.59	74.00	-26.41	peak
2	10124.000	35.98	13.28	49.26	68.20	-18.94	peak
3	11004.000	32.75	15.47	48.22	74.00	-25.78	peak
4	12654.000	26.64	20.06	46.70	74.00	-27.30	peak
5	14040.000	25.30	23.71	49.01	68.20	-19.19	peak
6	17923.000	22.71	27.79	50.50	74.00	-23.50	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	38.80	8.22	47.02	74.00	-26.98	peak
2	10190.000	36.38	13.32	49.70	68.20	-18.50	peak
3	11026.000	33.94	15.57	49.51	74.00	-24.49	peak
4	12676.000	26.97	20.14	47.11	74.00	-26.89	peak
5	13578.000	26.72	22.56	49.28	68.20	-18.92	peak
6	18000.000	21.40	28.51	49.91	74.00	-24.09	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7935.000	38.76	8.10	46.86	68.20	-21.34	peak
2	9574.000	36.34	13.13	49.47	68.20	-18.73	peak
3	10707.000	34.93	14.60	49.53	74.00	-24.47	peak
4	11653.000	30.29	17.88	48.17	74.00	-25.83	peak
5	14029.000	25.69	23.76	49.45	68.20	-18.75	peak
6	18000.000	21.65	28.51	50.16	74.00	-23.84	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7726.000	39.43	7.83	47.26	74.00	-26.74	peak
2	9673.000	35.69	13.42	49.11	68.20	-19.09	peak
3	11268.000	31.73	16.59	48.32	74.00	-25.68	peak
4	12555.000	28.74	19.84	48.58	74.00	-25.42	peak
5	13534.000	26.42	22.49	48.91	68.20	-19.29	peak
6	18000.000	21.84	28.51	50.35	74.00	-23.65	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8408.000	38.41	8.59	47.00	74.00	-27.00	peak
2	9266.000	37.62	11.62	49.24	68.20	-18.96	peak
3	11235.000	33.41	16.45	49.86	74.00	-24.14	peak
4	12665.000	27.64	20.09	47.73	74.00	-26.27	peak
5	13930.000	26.35	23.63	49.98	68.20	-18.22	peak
6	17978.000	22.51	28.31	50.82	74.00	-23.18	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7495.000	37.56	7.55	45.11	74.00	-28.89	peak
2	8793.000	39.60	9.57	49.17	68.20	-19.03	peak
3	10289.000	35.72	13.50	49.22	68.20	-18.98	peak
4	11411.000	33.43	17.24	50.67	74.00	-23.33	peak
5	13952.000	25.73	23.73	49.46	68.20	-18.74	peak
6	18000.000	21.23	28.51	49.74	74.00	-24.26	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.40	7.82	46.22	74.00	-27.78	peak
2	9574.000	36.05	13.13	49.18	68.20	-19.02	peak
3	10542.000	36.27	14.15	50.42	68.20	-17.78	peak
4	11873.000	30.95	18.16	49.11	74.00	-24.89	peak
5	13611.000	27.60	22.63	50.23	68.20	-17.97	peak
6	17714.000	24.29	25.96	50.25	74.00	-23.75	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8078.000	38.67	8.26	46.93	74.00	-27.07	peak
2	8925.000	39.13	10.20	49.33	68.20	-18.87	peak
3	11004.000	33.82	15.47	49.29	74.00	-24.71	peak
4	11829.000	30.80	18.02	48.82	74.00	-25.18	peak
5	13919.000	26.54	23.60	50.14	68.20	-18.06	peak
6	17978.000	21.47	28.31	49.78	74.00	-24.22	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8386.000	38.66	8.57	47.23	74.00	-26.77	peak
2	9706.000	35.77	13.49	49.26	68.20	-18.94	peak
3	10388.000	36.02	13.70	49.72	68.20	-18.48	peak
4	12643.000	27.14	20.03	47.17	74.00	-26.83	peak
5	13787.000	26.56	23.10	49.66	68.20	-18.54	peak
6	17967.000	21.59	28.21	49.80	74.00	-24.20	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	39.36	8.24	47.60	74.00	-26.40	peak
2	9728.000	36.26	13.52	49.78	68.20	-18.42	peak
3	11246.000	32.17	16.50	48.67	74.00	-25.33	peak
4	12566.000	27.27	19.85	47.12	74.00	-26.88	peak
5	13985.000	25.18	23.85	49.03	68.20	-19.17	peak
6	17978.000	21.64	28.31	49.95	74.00	-24.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	39.04	7.82	46.86	74.00	-27.14	peak
2	8914.000	37.63	10.15	47.78	68.20	-20.42	peak
3	10344.000	35.80	13.61	49.41	68.20	-18.79	peak
4	11840.000	30.30	18.06	48.36	74.00	-25.64	peak
5	13930.000	26.35	23.63	49.98	68.20	-18.22	peak
6	17956.000	22.22	28.10	50.32	74.00	-23.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7638.000	39.39	7.70	47.09	74.00	-26.91	peak
2	9310.000	37.33	11.75	49.08	74.00	-24.92	peak
3	10256.000	35.91	13.44	49.35	68.20	-18.85	peak
4	12665.000	27.47	20.09	47.56	74.00	-26.44	peak
5	13534.000	26.74	22.49	49.23	68.20	-18.97	peak
6	18000.000	20.93	28.51	49.44	74.00	-24.56	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.40	8.29	47.69	74.00	-26.31	peak
2	9442.000	36.91	12.29	49.20	74.00	-24.80	peak
3	10608.000	35.47	14.33	49.80	74.00	-24.20	peak
4	12676.000	27.99	20.14	48.13	74.00	-25.87	peak
5	13919.000	26.57	23.60	50.17	68.20	-18.03	peak
6	17945.000	22.50	28.01	50.51	74.00	-23.49	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.14	7.88	47.02	68.20	-21.18	peak
2	9530.000	36.30	12.85	49.15	68.20	-19.05	peak
3	10619.000	35.14	14.36	49.50	74.00	-24.50	peak
4	11840.000	29.72	18.06	47.78	74.00	-26.22	peak
5	13930.000	25.63	23.63	49.26	68.20	-18.94	peak
6	17934.000	22.55	27.90	50.45	74.00	-23.55	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7594.000	39.48	7.62	47.10	74.00	-26.90	peak
2	9211.000	37.62	11.45	49.07	68.20	-19.13	peak
3	10542.000	35.76	14.15	49.91	68.20	-18.29	peak
4	12709.000	27.57	20.24	47.81	68.20	-20.39	peak
5	13842.000	25.92	23.29	49.21	68.20	-18.99	peak
6	18000.000	21.18	28.51	49.69	74.00	-24.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7902.000	39.26	8.06	47.32	68.20	-20.88	peak
2	9761.000	36.12	13.58	49.70	68.20	-18.50	peak
3	11257.000	32.43	16.55	48.98	74.00	-25.02	peak
4	12665.000	27.44	20.09	47.53	74.00	-26.47	peak
5	13545.000	27.29	22.51	49.80	68.20	-18.40	peak
6	17978.000	22.08	28.31	50.39	74.00	-23.61	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	38.62	7.49	46.11	74.00	-27.89	peak
2	8243.000	39.00	8.44	47.44	74.00	-26.56	peak
3	10278.000	36.23	13.48	49.71	68.20	-18.49	peak
4	11840.000	30.32	18.06	48.38	74.00	-25.62	peak
5	13941.000	26.39	23.68	50.07	68.20	-18.13	peak
6	17978.000	21.47	28.31	49.78	74.00	-24.22	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.03	7.88	46.91	68.20	-21.29	peak
2	9673.000	36.72	13.42	50.14	68.20	-18.06	peak
3	10553.000	35.36	14.18	49.54	68.20	-18.66	peak
4	12665.000	28.30	20.09	48.39	74.00	-25.61	peak
5	13798.000	27.32	23.13	50.45	68.20	-17.75	peak
6	17989.000	21.54	28.40	49.94	74.00	-24.06	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	39.88	8.22	48.10	74.00	-25.90	peak
2	9211.000	38.87	11.45	50.32	68.20	-17.88	peak
3	10531.000	35.81	14.12	49.93	68.20	-18.27	peak
4	12632.000	28.43	19.99	48.42	74.00	-25.58	peak
5	13952.000	26.60	23.73	50.33	68.20	-17.87	peak
6	17989.000	22.07	28.40	50.47	74.00	-23.53	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7748.000	38.94	7.87	46.81	74.00	-27.19	peak
2	9805.000	36.23	13.66	49.89	68.20	-18.31	peak
3	11367.000	32.93	17.05	49.98	74.00	-24.02	peak
4	12324.000	28.90	19.43	48.33	74.00	-25.67	peak
5	13996.000	27.13	23.89	51.02	68.20	-17.18	peak
6	17989.000	22.15	28.40	50.55	74.00	-23.45	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	40.36	7.82	48.18	74.00	-25.82	peak
2	9552.000	36.57	12.98	49.55	68.20	-18.65	peak
3	10817.000	33.92	14.92	48.84	74.00	-25.16	peak
4	12731.000	26.72	20.32	47.04	68.20	-21.16	peak
5	13930.000	25.36	23.63	48.99	68.20	-19.21	peak
6	17978.000	21.03	28.31	49.34	74.00	-24.66	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7495.000	37.90	7.55	45.45	74.00	-28.55	peak
2	9167.000	37.79	11.28	49.07	74.00	-24.93	peak
3	10454.000	35.16	13.90	49.06	68.20	-19.14	peak
4	11664.000	29.64	17.88	47.52	74.00	-26.48	peak
5	13941.000	25.55	23.68	49.23	68.20	-18.97	peak
6	17934.000	21.83	27.90	49.73	74.00	-24.27	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7330.000	37.61	7.50	45.11	74.00	-28.89	peak
2	9255.000	37.65	11.59	49.24	68.20	-18.96	peak
3	10443.000	35.48	13.86	49.34	68.20	-18.86	peak
4	11400.000	32.26	17.20	49.46	74.00	-24.54	peak
5	13952.000	25.69	23.73	49.42	68.20	-18.78	peak
6	18000.000	20.93	28.51	49.44	74.00	-24.56	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	37.81	7.50	45.31	74.00	-28.69	peak
2	9409.000	37.47	12.08	49.55	74.00	-24.45	peak
3	10388.000	35.90	13.70	49.60	68.20	-18.60	peak
4	12577.000	27.21	19.87	47.08	74.00	-26.92	peak
5	13534.000	27.52	22.49	50.01	68.20	-18.19	peak
6	17725.000	23.53	26.03	49.56	74.00	-24.44	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	38.65	8.18	46.83	68.20	-21.37	peak
2	9167.000	38.37	11.28	49.65	74.00	-24.35	peak
3	10894.000	35.45	15.14	50.59	74.00	-23.41	peak
4	12577.000	27.65	19.87	47.52	74.00	-26.48	peak
5	13578.000	26.28	22.56	48.84	68.20	-19.36	peak
6	17989.000	20.98	28.40	49.38	74.00	-24.62	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8089.000	38.91	8.28	47.19	74.00	-26.81	peak
2	9816.000	35.90	13.63	49.53	68.20	-18.67	peak
3	10278.000	36.16	13.48	49.64	68.20	-18.56	peak
4	12665.000	27.14	20.09	47.23	74.00	-26.77	peak
5	13589.000	27.10	22.58	49.68	68.20	-18.52	peak
6	17967.000	21.66	28.21	49.87	74.00	-24.13	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7033.000	41.31	7.26	48.57	68.20	-19.63	peak
2	8892.000	39.61	10.04	49.65	68.20	-18.55	peak
3	10212.000	35.90	13.35	49.25	68.20	-18.95	peak
4	12577.000	27.41	19.87	47.28	74.00	-26.72	peak
5	14260.000	27.15	22.52	49.67	68.20	-18.53	peak
6	18000.000	21.85	28.51	50.36	74.00	-23.64	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.33	8.29	47.62	74.00	-26.38	peak
2	9244.000	37.64	11.56	49.20	68.20	-19.00	peak
3	10685.000	34.90	14.55	49.45	74.00	-24.55	peak
4	12621.000	26.87	19.94	46.81	74.00	-27.19	peak
5	13985.000	25.14	23.85	48.99	68.20	-19.21	peak
6	17791.000	23.55	26.58	50.13	74.00	-23.87	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7924.000	39.24	8.09	47.33	68.20	-20.87	peak
2	9585.000	36.18	13.19	49.37	68.20	-18.83	peak
3	10542.000	35.40	14.15	49.55	68.20	-18.65	peak
4	12632.000	27.85	19.99	47.84	74.00	-26.16	peak
5	13985.000	25.75	23.85	49.60	68.20	-18.60	peak
6	18000.000	21.20	28.51	49.71	74.00	-24.29	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7088.000	38.63	7.33	45.96	68.20	-22.24	peak
2	9519.000	37.15	12.77	49.92	68.20	-18.28	peak
3	10608.000	35.30	14.33	49.63	74.00	-24.37	peak
4	12687.000	27.00	20.17	47.17	74.00	-26.83	peak
5	14007.000	25.58	23.88	49.46	68.20	-18.74	peak
6	17978.000	21.81	28.31	50.12	74.00	-23.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7693.000	39.62	7.78	47.40	74.00	-26.60	peak
2	9343.000	37.54	11.86	49.40	74.00	-24.60	peak
3	10542.000	35.31	14.15	49.46	68.20	-18.74	peak
4	11411.000	32.27	17.24	49.51	74.00	-24.49	peak
5	13974.000	25.42	23.81	49.23	68.20	-18.97	peak
6	17714.000	23.72	25.96	49.68	74.00	-24.32	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7693.000	39.92	7.78	47.70	74.00	-26.30	peak
2	8793.000	39.45	9.57	49.02	68.20	-19.18	peak
3	10146.000	35.89	13.29	49.18	68.20	-19.02	peak
4	11378.000	32.50	17.10	49.60	74.00	-24.40	peak
5	13930.000	25.32	23.63	48.95	68.20	-19.25	peak
6	17967.000	21.34	28.21	49.55	74.00	-24.45	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	40.52	7.95	48.47	68.20	-19.73	peak
2	9200.000	37.97	11.42	49.39	68.20	-18.81	peak
3	10564.000	33.93	14.20	48.13	68.20	-20.07	peak
4	11807.000	29.82	17.95	47.77	74.00	-26.23	peak
5	13864.000	26.53	23.39	49.92	68.20	-18.28	peak
6	17967.000	22.19	28.21	50.40	74.00	-23.60	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	39.85	7.95	47.80	68.20	-20.40	peak
2	9101.000	38.16	10.99	49.15	74.00	-24.85	peak
3	10333.000	35.97	13.60	49.57	68.20	-18.63	peak
4	11444.000	31.42	17.35	48.77	74.00	-25.23	peak
5	13809.000	27.08	23.17	50.25	68.20	-17.95	peak
6	17967.000	20.81	28.21	49.02	74.00	-24.98	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8298.000	39.00	8.49	47.49	74.00	-26.51	peak
2	9244.000	37.78	11.56	49.34	68.20	-18.86	peak
3	10905.000	33.34	15.17	48.51	74.00	-25.49	peak
4	12676.000	27.31	20.14	47.45	74.00	-26.55	peak
5	13864.000	26.08	23.39	49.47	68.20	-18.73	peak
6	17989.000	21.77	28.40	50.17	74.00	-23.83	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.73	7.82	46.55	74.00	-27.45	peak
2	9310.000	37.40	11.75	49.15	74.00	-24.85	peak
3	11334.000	31.59	16.90	48.49	74.00	-25.51	peak
4	12258.000	30.22	19.25	49.47	74.00	-24.53	peak
5	14150.000	26.29	23.18	49.47	68.20	-18.73	peak
6	17967.000	21.75	28.21	49.96	74.00	-24.04	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	39.60	8.18	47.78	68.20	-20.42	peak
2	9640.000	36.04	13.36	49.40	68.20	-18.80	peak
3	10993.000	33.28	15.44	48.72	74.00	-25.28	peak
4	12632.000	26.89	19.99	46.88	74.00	-27.12	peak
5	13930.000	25.60	23.63	49.23	68.20	-18.97	peak
6	17945.000	22.48	28.01	50.49	74.00	-23.51	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8144.000	38.64	8.34	46.98	74.00	-27.02	peak
2	9211.000	38.39	11.45	49.84	68.20	-18.36	peak
3	10135.000	35.98	13.29	49.27	68.20	-18.93	peak
4	12588.000	26.97	19.87	46.84	74.00	-27.16	peak
5	13963.000	25.46	23.77	49.23	68.20	-18.97	peak
6	18000.000	21.15	28.51	49.66	74.00	-24.34	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	39.57	8.22	47.79	74.00	-26.21	peak
2	9563.000	36.36	13.05	49.41	68.20	-18.79	peak
3	10938.000	32.93	15.27	48.20	74.00	-25.80	peak
4	12533.000	27.41	19.82	47.23	74.00	-26.77	peak
5	13776.000	26.13	23.07	49.20	68.20	-19.00	peak
6	17714.000	23.95	25.96	49.91	74.00	-24.09	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	39.67	8.22	47.89	74.00	-26.11	peak
2	9255.000	37.76	11.59	49.35	68.20	-18.85	peak
3	10135.000	36.24	13.29	49.53	68.20	-18.67	peak
4	11257.000	31.58	16.55	48.13	74.00	-25.87	peak
5	13556.000	26.68	22.53	49.21	68.20	-18.99	peak
6	17945.000	22.17	28.01	50.18	74.00	-23.82	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	39.64	7.79	47.43	74.00	-26.57	peak
2	9211.000	37.82	11.45	49.27	68.20	-18.93	peak
3	10245.000	36.17	13.41	49.58	68.20	-18.62	peak
4	11796.000	29.98	17.93	47.91	74.00	-26.09	peak
5	13578.000	27.65	22.56	50.21	68.20	-17.99	peak
6	17978.000	22.11	28.31	50.42	74.00	-23.58	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.88	8.29	48.17	74.00	-25.83	peak
2	9244.000	38.46	11.56	50.02	68.20	-18.18	peak
3	10894.000	34.03	15.14	49.17	74.00	-24.83	peak
4	11785.000	31.21	17.92	49.13	74.00	-24.87	peak
5	13930.000	25.71	23.63	49.34	68.20	-18.86	peak
6	17989.000	21.68	28.40	50.08	74.00	-23.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	42.01	7.88	49.89	68.20	-18.31	peak
2	10168.000	36.35	13.30	49.65	68.20	-18.55	peak
3	10872.000	33.73	15.08	48.81	74.00	-25.19	peak
4	12731.000	27.21	20.32	47.53	68.20	-20.67	peak
5	13996.000	25.62	23.89	49.51	68.20	-18.69	peak
6	17967.000	21.19	28.21	49.40	74.00	-24.60	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.94	7.88	47.82	68.20	-20.38	peak
2	9211.000	38.38	11.45	49.83	68.20	-18.37	peak
3	10311.000	35.40	13.55	48.95	68.20	-19.25	peak
4	12654.000	27.37	20.06	47.43	74.00	-26.57	peak
5	13556.000	26.72	22.53	49.25	68.20	-18.95	peak
6	17978.000	21.57	28.31	49.88	74.00	-24.12	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7792.000	39.08	7.94	47.02	68.20	-21.18	peak
2	9717.000	35.86	13.50	49.36	68.20	-18.84	peak
3	11356.000	31.43	17.00	48.43	74.00	-25.57	peak
4	12720.000	27.04	20.27	47.31	68.20	-20.89	peak
5	14018.000	25.97	23.83	49.80	68.20	-18.40	peak
6	17956.000	21.23	28.10	49.33	74.00	-24.67	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7726.000	39.41	7.83	47.24	74.00	-26.76	peak
2	9640.000	36.56	13.36	49.92	68.20	-18.28	peak
3	10542.000	35.52	14.15	49.67	68.20	-18.53	peak
4	11433.000	32.06	17.31	49.37	74.00	-24.63	peak
5	14051.000	24.63	23.66	48.29	68.20	-19.91	peak
6	17824.000	21.77	26.88	48.65	74.00	-25.35	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7726.000	39.10	7.83	46.93	74.00	-27.07	peak
2	9178.000	38.60	11.32	49.92	74.00	-24.08	peak
3	10542.000	34.79	14.15	48.94	68.20	-19.26	peak
4	12643.000	27.58	20.03	47.61	74.00	-26.39	peak
5	13578.000	26.47	22.56	49.03	68.20	-19.17	peak
6	18000.000	22.07	28.51	50.58	74.00	-23.42	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7484.000	38.10	7.54	45.64	74.00	-28.36	peak
2	10256.000	35.97	13.44	49.41	68.20	-18.79	peak
3	11389.000	30.91	17.15	48.06	74.00	-25.94	peak
4	12709.000	27.56	20.24	47.80	68.20	-20.40	peak
5	13952.000	26.43	23.73	50.16	68.20	-18.04	peak
6	17923.000	22.58	27.79	50.37	74.00	-23.63	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8133.000	38.91	8.33	47.24	74.00	-26.76	peak
2	9728.000	36.26	13.52	49.78	68.20	-18.42	peak
3	11059.000	33.32	15.71	49.03	74.00	-24.97	peak
4	12698.000	27.57	20.20	47.77	74.00	-26.23	peak
5	13864.000	25.91	23.39	49.30	68.20	-18.90	peak
6	17978.000	21.97	28.31	50.28	74.00	-23.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8177.000	39.02	8.37	47.39	74.00	-26.61	peak
2	9211.000	37.82	11.45	49.27	68.20	-18.93	peak
3	10542.000	34.76	14.15	48.91	68.20	-19.29	peak
4	12643.000	26.79	20.03	46.82	74.00	-27.18	peak
5	13875.000	25.63	23.44	49.07	68.20	-19.13	peak
6	17934.000	21.82	27.90	49.72	74.00	-24.28	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	37.82	7.50	45.32	74.00	-28.68	peak
2	9794.000	36.07	13.64	49.71	68.20	-18.49	peak
3	10861.000	34.00	15.04	49.04	74.00	-24.96	peak
4	12346.000	27.95	19.50	47.45	74.00	-26.55	peak
5	13809.000	26.10	23.17	49.27	68.20	-18.93	peak
6	17989.000	21.89	28.40	50.29	74.00	-23.71	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7792.000	38.42	7.94	46.36	68.20	-21.84	peak
2	10443.000	35.38	13.86	49.24	68.20	-18.96	peak
3	11004.000	35.20	15.47	50.67	74.00	-23.33	peak
4	12610.000	29.52	19.92	49.44	74.00	-24.56	peak
5	14007.000	26.09	23.88	49.97	68.20	-18.23	peak
6	17791.000	23.19	26.58	49.77	74.00	-24.23	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	40.45	7.79	48.24	74.00	-25.76	peak
2	9585.000	37.50	13.19	50.69	68.20	-17.51	peak
3	11411.000	30.43	17.24	47.67	74.00	-26.33	peak
4	12698.000	27.47	20.20	47.67	74.00	-26.33	peak
5	14073.000	26.03	23.55	49.58	68.20	-18.62	peak
6	18000.000	21.98	28.51	50.49	74.00	-23.51	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	39.40	7.82	47.22	74.00	-26.78	peak
2	9233.000	38.21	11.52	49.73	68.20	-18.47	peak
3	10542.000	36.15	14.15	50.30	68.20	-17.90	peak
4	11290.000	32.88	16.69	49.57	74.00	-24.43	peak
5	13963.000	26.50	23.77	50.27	68.20	-17.93	peak
6	17978.000	22.41	28.31	50.72	74.00	-23.28	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	38.74	8.30	47.04	74.00	-26.96	peak
2	9596.000	36.81	13.26	50.07	68.20	-18.13	peak
3	10784.000	35.25	14.81	50.06	74.00	-23.94	peak
4	12599.000	27.89	19.88	47.77	74.00	-26.23	peak
5	13523.000	26.60	22.48	49.08	68.20	-19.12	peak
6	17989.000	21.57	28.40	49.97	74.00	-24.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.70	7.88	47.58	68.20	-20.62	peak
2	9200.000	38.18	11.42	49.60	68.20	-18.60	peak
3	10520.000	37.63	14.08	51.71	68.20	-16.49	peak
4	11510.000	30.57	17.57	48.14	74.00	-25.86	peak
5	14007.000	25.48	23.88	49.36	68.20	-18.84	peak
6	18000.000	20.69	28.51	49.20	74.00	-24.80	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7913.000	39.36	8.08	47.44	68.20	-20.76	peak
2	9211.000	37.74	11.45	49.19	68.20	-19.01	peak
3	11631.000	29.45	17.88	47.33	74.00	-26.67	peak
4	12676.000	26.53	20.14	46.67	74.00	-27.33	peak
5	13952.000	25.21	23.73	48.94	68.20	-19.26	peak
6	17978.000	21.57	28.31	49.88	74.00	-24.12	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8309.000	38.90	8.50	47.40	74.00	-26.60	peak
2	9640.000	36.77	13.36	50.13	68.20	-18.07	peak
3	10542.000	35.56	14.15	49.71	68.20	-18.49	peak
4	11840.000	29.85	18.06	47.91	74.00	-26.09	peak
5	13523.000	27.50	22.48	49.98	68.20	-18.22	peak
6	17967.000	21.57	28.21	49.78	74.00	-24.22	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7330.000	38.07	7.50	45.57	74.00	-28.43	peak
2	9508.000	37.21	12.71	49.92	68.20	-18.28	peak
3	10927.000	32.86	15.23	48.09	74.00	-25.91	peak
4	12687.000	27.54	20.17	47.71	74.00	-26.29	peak
5	14007.000	25.32	23.88	49.20	68.20	-19.00	peak
6	18000.000	22.26	28.51	50.77	74.00	-23.23	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	38.77	7.50	46.27	74.00	-27.73	peak
2	9266.000	37.64	11.62	49.26	68.20	-18.94	peak
3	10157.000	36.21	13.30	49.51	68.20	-18.69	peak
4	11268.000	33.82	16.59	50.41	74.00	-23.59	peak
5	13655.000	26.10	22.75	48.85	68.20	-19.35	peak
6	17813.000	23.02	26.78	49.80	74.00	-24.20	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7176.000	38.09	7.44	45.53	68.20	-22.67	peak
2	8056.000	39.21	8.24	47.45	74.00	-26.55	peak
3	9772.000	37.14	13.61	50.75	68.20	-17.45	peak
4	11477.000	31.83	17.46	49.29	74.00	-24.71	peak
5	14007.000	25.10	23.88	48.98	68.20	-19.22	peak
6	18000.000	21.57	28.51	50.08	74.00	-23.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8243.000	38.88	8.44	47.32	74.00	-26.68	peak
2	9651.000	35.95	13.38	49.33	68.20	-18.87	peak
3	11026.000	35.06	15.57	50.63	74.00	-23.37	peak
4	12280.000	29.09	19.32	48.41	74.00	-25.59	peak
5	13897.000	26.01	23.51	49.52	68.20	-18.68	peak
6	17989.000	22.19	28.40	50.59	74.00	-23.41	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	39.19	8.22	47.41	74.00	-26.59	peak
2	9574.000	36.16	13.13	49.29	68.20	-18.91	peak
3	10553.000	35.65	14.18	49.83	68.20	-18.37	peak
4	12676.000	26.93	20.14	47.07	74.00	-26.93	peak
5	13996.000	25.52	23.89	49.41	68.20	-18.79	peak
6	18000.000	20.74	28.51	49.25	74.00	-24.75	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	39.33	8.24	47.57	74.00	-26.43	peak
2	10388.000	36.24	13.70	49.94	68.20	-18.26	peak
3	11411.000	31.48	17.24	48.72	74.00	-25.28	peak
4	12984.000	27.42	20.47	47.89	68.20	-20.31	peak
5	13974.000	25.61	23.81	49.42	68.20	-18.78	peak
6	17802.000	23.15	26.68	49.83	74.00	-24.17	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8023.000	38.95	8.21	47.16	68.20	-21.04	peak
2	9222.000	38.25	11.49	49.74	68.20	-18.46	peak
3	10949.000	34.18	15.30	49.48	74.00	-24.52	peak
4	12698.000	27.04	20.20	47.24	74.00	-26.76	peak
5	13952.000	26.19	23.73	49.92	68.20	-18.28	peak
6	17967.000	21.98	28.21	50.19	74.00	-23.81	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	38.15	8.24	46.39	74.00	-27.61	peak
2	9277.000	37.91	11.66	49.57	68.20	-18.63	peak
3	10960.000	34.65	15.34	49.99	74.00	-24.01	peak
4	12698.000	27.00	20.20	47.20	74.00	-26.80	peak
5	13908.000	25.44	23.56	49.00	68.20	-19.20	peak
6	18000.000	21.23	28.51	49.74	74.00	-24.26	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	38.63	7.88	46.51	68.20	-21.69	peak
2	9266.000	37.78	11.62	49.40	68.20	-18.80	peak
3	10267.000	35.83	13.45	49.28	68.20	-18.92	peak
4	12236.000	27.45	19.19	46.64	74.00	-27.36	peak
5	13941.000	25.10	23.68	48.78	68.20	-19.42	peak
6	18000.000	20.82	28.51	49.33	74.00	-24.67	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8144.000	38.82	8.34	47.16	74.00	-26.84	peak
2	9816.000	36.07	13.63	49.70	68.20	-18.50	peak
3	11268.000	32.45	16.59	49.04	74.00	-24.96	peak
4	12236.000	28.27	19.19	47.46	74.00	-26.54	peak
5	13545.000	26.75	22.51	49.26	68.20	-18.94	peak
6	17989.000	20.63	28.40	49.03	74.00	-24.97	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	38.72	7.88	46.60	68.20	-21.60	peak
2	10003.000	35.99	13.24	49.23	68.20	-18.97	peak
3	10982.000	31.62	15.40	47.02	74.00	-26.98	peak
4	12676.000	26.63	20.14	46.77	74.00	-27.23	peak
5	13567.000	26.65	22.55	49.20	68.20	-19.00	peak
6	17945.000	21.94	28.01	49.95	74.00	-24.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	38.71	8.24	46.95	74.00	-27.05	peak
2	8848.000	39.27	9.83	49.10	68.20	-19.10	peak
3	9519.000	36.63	12.77	49.40	68.20	-18.80	peak
4	10619.000	33.81	14.36	48.17	74.00	-25.83	peak
5	14007.000	25.23	23.88	49.11	68.20	-19.09	peak
6	17989.000	20.76	28.40	49.16	74.00	-24.84	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7264.000	38.16	7.49	45.65	74.00	-28.35	peak
2	9596.000	36.36	13.26	49.62	68.20	-18.58	peak
3	11268.000	33.33	16.59	49.92	74.00	-24.08	peak
4	12676.000	27.52	20.14	47.66	74.00	-26.34	peak
5	13809.000	26.25	23.17	49.42	68.20	-18.78	peak
6	17956.000	21.94	28.10	50.04	74.00	-23.96	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	38.22	7.50	45.72	74.00	-28.28	peak
2	9189.000	37.84	11.37	49.21	74.00	-24.79	peak
3	10542.000	35.10	14.15	49.25	68.20	-18.95	peak
4	12577.000	26.73	19.87	46.60	74.00	-27.40	peak
5	13820.000	26.99	23.22	50.21	68.20	-17.99	peak
6	18000.000	22.33	28.51	50.84	74.00	-23.16	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7319.000	38.36	7.50	45.86	74.00	-28.14	peak
2	8144.000	39.49	8.34	47.83	74.00	-26.17	peak
3	9904.000	35.67	13.44	49.11	68.20	-19.09	peak
4	10894.000	33.54	15.14	48.68	74.00	-25.32	peak
5	13545.000	26.41	22.51	48.92	68.20	-19.28	peak
6	17934.000	21.65	27.90	49.55	74.00	-24.45	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.59	8.29	47.88	74.00	-26.12	peak
2	9244.000	38.58	11.56	50.14	68.20	-18.06	peak
3	10938.000	32.39	15.27	47.66	74.00	-26.34	peak
4	12709.000	26.82	20.24	47.06	68.20	-21.14	peak
5	13963.000	25.28	23.77	49.05	68.20	-19.15	peak
6	17967.000	21.80	28.21	50.01	74.00	-23.99	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8177.000	38.88	8.37	47.25	74.00	-26.75	peak
2	9629.000	36.07	13.33	49.40	68.20	-18.80	peak
3	11323.000	31.60	16.84	48.44	74.00	-25.56	peak
4	12247.000	28.06	19.22	47.28	74.00	-26.72	peak
5	13534.000	26.95	22.49	49.44	68.20	-18.76	peak
6	17989.000	21.57	28.40	49.97	74.00	-24.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	38.62	7.50	46.12	74.00	-27.88	peak
2	9266.000	37.30	11.62	48.92	68.20	-19.28	peak
3	10531.000	35.74	14.12	49.86	68.20	-18.34	peak
4	13050.000	26.97	20.67	47.64	68.20	-20.56	peak
5	13853.000	26.08	23.34	49.42	68.20	-18.78	peak
6	17967.000	22.10	28.21	50.31	74.00	-23.69	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7330.000	37.34	7.50	44.84	74.00	-29.16	peak
2	9596.000	36.02	13.26	49.28	68.20	-18.92	peak
3	10861.000	34.77	15.04	49.81	74.00	-24.19	peak
4	12544.000	27.61	19.83	47.44	74.00	-26.56	peak
5	13578.000	27.12	22.56	49.68	68.20	-18.52	peak
6	18000.000	21.51	28.51	50.02	74.00	-23.98	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160	Frequency(MHz):	5250
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8518.000	38.92	8.70	47.62	68.20	-20.58	peak
2	9343.000	37.40	11.86	49.26	74.00	-24.74	peak
3	10938.000	34.02	15.27	49.29	74.00	-24.71	peak
4	12346.000	28.44	19.50	47.94	74.00	-26.06	peak
5	13820.000	25.29	23.22	48.51	68.20	-19.69	peak
6	17780.000	23.34	26.50	49.84	74.00	-24.16	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7484.000	38.39	7.54	45.93	74.00	-28.07	peak
2	9530.000	36.67	12.85	49.52	68.20	-18.68	peak
3	10608.000	34.83	14.33	49.16	74.00	-24.84	peak
4	12720.000	27.36	20.27	47.63	68.20	-20.57	peak
5	13589.000	27.54	22.58	50.12	68.20	-18.08	peak
6	18000.000	21.80	28.51	50.31	74.00	-23.69	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ac VHT160	Frequency(MHz):	5570
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7880.000	38.62	8.04	46.66	68.20	-21.54	peak
2	9310.000	38.43	11.75	50.18	74.00	-23.82	peak
3	10916.000	32.98	15.21	48.19	74.00	-25.81	peak
4	12687.000	26.89	20.17	47.06	74.00	-26.94	peak
5	14172.000	26.33	23.06	49.39	68.20	-18.81	peak
6	17978.000	21.38	28.31	49.69	74.00	-24.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8089.000	40.14	8.28	48.42	74.00	-25.58	peak
2	9629.000	36.65	13.33	49.98	68.20	-18.22	peak
3	11037.000	31.81	15.62	47.43	74.00	-26.57	peak
4	12544.000	26.65	19.83	46.48	74.00	-27.52	peak
5	14007.000	24.89	23.88	48.77	68.20	-19.43	peak
6	18000.000	21.01	28.51	49.52	74.00	-24.48	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7671.000	39.08	7.75	46.83	74.00	-27.17	peak
2	9739.000	36.60	13.55	50.15	68.20	-18.05	peak
3	11037.000	32.96	15.62	48.58	74.00	-25.42	peak
4	12874.000	27.20	20.50	47.70	68.20	-20.50	peak
5	13864.000	26.02	23.39	49.41	68.20	-18.79	peak
6	17714.000	24.08	25.96	50.04	74.00	-23.96	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7671.000	38.77	7.75	46.52	74.00	-27.48	peak
2	9585.000	36.29	13.19	49.48	68.20	-18.72	peak
3	10553.000	34.11	14.18	48.29	68.20	-19.91	peak
4	11851.000	28.81	18.09	46.90	74.00	-27.10	peak
5	13985.000	25.40	23.85	49.25	68.20	-18.95	peak
6	17978.000	22.27	28.31	50.58	74.00	-23.42	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7737.000	38.36	7.84	46.20	74.00	-27.80	peak
2	9629.000	35.85	13.33	49.18	68.20	-19.02	peak
3	11015.000	34.20	15.52	49.72	74.00	-24.28	peak
4	12709.000	27.59	20.24	47.83	68.20	-20.37	peak
5	14062.000	25.99	23.60	49.59	68.20	-18.61	peak
6	18000.000	22.36	28.51	50.87	74.00	-23.13	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8133.000	39.12	8.33	47.45	74.00	-26.55	peak
2	9156.000	37.90	11.23	49.13	74.00	-24.87	peak
3	11510.000	31.50	17.57	49.07	74.00	-24.93	peak
4	13534.000	27.49	22.49	49.98	68.20	-18.22	peak
5	16251.000	25.28	21.46	46.74	68.20	-21.46	peak
6	17989.000	21.29	28.40	49.69	74.00	-24.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	39.32	8.44	47.76	74.00	-26.24	peak
2	9618.000	36.38	13.31	49.69	68.20	-18.51	peak
3	11026.000	33.31	15.57	48.88	74.00	-25.12	peak
4	12676.000	27.15	20.14	47.29	74.00	-26.71	peak
5	13996.000	25.88	23.89	49.77	68.20	-18.43	peak
6	17989.000	21.47	28.40	49.87	74.00	-24.13	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7770.000	39.40	7.90	47.30	68.20	-20.90	peak
2	9596.000	36.47	13.26	49.73	68.20	-18.47	peak
3	10894.000	34.86	15.14	50.00	74.00	-24.00	peak
4	12698.000	27.21	20.20	47.41	74.00	-26.59	peak
5	13930.000	25.85	23.63	49.48	68.20	-18.72	peak
6	18000.000	21.76	28.51	50.27	74.00	-23.73	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7913.000	38.46	8.08	46.54	68.20	-21.66	peak
2	9519.000	36.77	12.77	49.54	68.20	-18.66	peak
3	10619.000	33.96	14.36	48.32	74.00	-25.68	peak
4	11609.000	28.57	17.88	46.45	74.00	-27.55	peak
5	13842.000	24.94	23.29	48.23	68.20	-19.97	peak
6	18000.000	20.77	28.51	49.28	74.00	-24.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7033.000	42.83	7.26	50.09	68.20	-18.11	peak
2	8122.000	39.03	8.32	47.35	74.00	-26.65	peak
3	9266.000	37.57	11.62	49.19	68.20	-19.01	peak
4	10608.000	35.19	14.33	49.52	74.00	-24.48	peak
5	13941.000	25.94	23.68	49.62	68.20	-18.58	peak
6	17989.000	21.59	28.40	49.99	74.00	-24.01	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7913.000	40.05	8.08	48.13	68.20	-20.07	peak
2	9530.000	36.46	12.85	49.31	68.20	-18.89	peak
3	11620.000	30.33	17.88	48.21	74.00	-25.79	peak
4	12698.000	28.11	20.20	48.31	74.00	-25.69	peak
5	13908.000	26.95	23.56	50.51	68.20	-17.69	peak
6	17989.000	22.45	28.40	50.85	74.00	-23.15	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	38.59	7.79	46.38	74.00	-27.62	peak
2	8870.000	39.15	9.94	49.09	68.20	-19.11	peak
3	11048.000	34.39	15.66	50.05	74.00	-23.95	peak
4	12346.000	28.45	19.50	47.95	74.00	-26.05	peak
5	13523.000	26.76	22.48	49.24	68.20	-18.96	peak
6	17967.000	21.87	28.21	50.08	74.00	-23.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7088.000	38.76	7.33	46.09	68.20	-22.11	peak
2	9343.000	37.65	11.86	49.51	74.00	-24.49	peak
3	10894.000	35.37	15.14	50.51	74.00	-23.49	peak
4	12698.000	26.71	20.20	46.91	74.00	-27.09	peak
5	14007.000	25.45	23.88	49.33	68.20	-18.87	peak
6	17989.000	20.92	28.40	49.32	74.00	-24.68	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7693.000	40.63	7.78	48.41	74.00	-25.59	peak
2	9640.000	36.32	13.36	49.68	68.20	-18.52	peak
3	11389.000	31.56	17.15	48.71	74.00	-25.29	peak
4	12643.000	28.10	20.03	48.13	74.00	-25.87	peak
5	13930.000	26.88	23.63	50.51	68.20	-17.69	peak
6	17945.000	21.98	28.01	49.99	74.00	-24.01	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7693.000	43.21	7.78	50.99	74.00	-23.01	peak
2	9530.000	36.58	12.85	49.43	68.20	-18.77	peak
3	11378.000	30.81	17.10	47.91	74.00	-26.09	peak
4	12742.000	26.31	20.36	46.67	68.20	-21.53	peak
5	13875.000	25.86	23.44	49.30	68.20	-18.90	peak
6	17923.000	21.84	27.79	49.63	74.00	-24.37	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	43.20	7.95	51.15	68.20	-17.05	peak
2	9530.000	36.88	12.85	49.73	68.20	-18.47	peak
3	10542.000	36.09	14.15	50.24	68.20	-17.96	peak
4	12621.000	28.57	19.94	48.51	74.00	-25.49	peak
5	13974.000	26.28	23.81	50.09	68.20	-18.11	peak
6	17989.000	22.10	28.40	50.50	74.00	-23.50	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	43.37	7.95	51.32	68.20	-16.88	peak
2	8925.000	39.99	10.20	50.19	68.20	-18.01	peak
3	10377.000	35.54	13.69	49.23	68.20	-18.97	peak
4	12709.000	27.46	20.24	47.70	68.20	-20.50	peak
5	13534.000	27.78	22.49	50.27	68.20	-17.93	peak
6	17967.000	21.88	28.21	50.09	74.00	-23.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7968.000	42.64	8.13	50.77	68.20	-17.43	peak
2	9123.000	38.53	11.09	49.62	74.00	-24.38	peak
3	11026.000	33.61	15.57	49.18	74.00	-24.82	peak
4	12533.000	26.88	19.82	46.70	74.00	-27.30	peak
5	13908.000	26.22	23.56	49.78	68.20	-18.42	peak
6	17967.000	21.31	28.21	49.52	74.00	-24.48	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7968.000	40.64	8.13	48.77	68.20	-19.43	peak
2	9596.000	35.95	13.26	49.21	68.20	-18.99	peak
3	11037.000	32.29	15.62	47.91	74.00	-26.09	peak
4	12687.000	26.54	20.17	46.71	74.00	-27.29	peak
5	13963.000	26.02	23.77	49.79	68.20	-18.41	peak
6	17967.000	21.69	28.21	49.90	74.00	-24.10	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8001.000	42.81	8.17	50.98	68.20	-17.22	peak
2	9563.000	36.31	13.05	49.36	68.20	-18.84	peak
3	10553.000	35.62	14.18	49.80	68.20	-18.40	peak
4	11257.000	32.09	16.55	48.64	74.00	-25.36	peak
5	13600.000	27.43	22.60	50.03	68.20	-18.17	peak
6	17923.000	23.00	27.79	50.79	74.00	-23.21	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8001.000	41.50	8.17	49.67	68.20	-18.53	peak
2	9948.000	36.66	13.35	50.01	68.20	-18.19	peak
3	10630.000	34.51	14.40	48.91	74.00	-25.09	peak
4	12775.000	28.32	20.46	48.78	68.20	-19.42	peak
5	13941.000	26.52	23.68	50.20	68.20	-18.00	peak
6	17978.000	22.55	28.31	50.86	74.00	-23.14	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	42.22	8.21	50.43	74.00	-23.57	peak
2	9530.000	35.99	12.85	48.84	68.20	-19.36	peak
3	10795.000	35.01	14.85	49.86	74.00	-24.14	peak
4	12951.000	27.23	20.48	47.71	68.20	-20.49	peak
5	13963.000	26.13	23.77	49.90	68.20	-18.30	peak
6	18000.000	22.90	28.51	51.41	74.00	-22.59	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	41.01	8.21	49.22	74.00	-24.78	peak
2	9574.000	35.95	13.13	49.08	68.20	-19.12	peak
3	11356.000	32.23	17.00	49.23	74.00	-24.77	peak
4	12687.000	27.81	20.17	47.98	74.00	-26.02	peak
5	13952.000	26.50	23.73	50.23	68.20	-17.97	peak
6	18000.000	21.44	28.51	49.95	74.00	-24.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	41.21	8.29	49.50	74.00	-24.50	peak
2	9530.000	36.39	12.85	49.24	68.20	-18.96	peak
3	10641.000	34.05	14.43	48.48	74.00	-25.52	peak
4	12621.000	27.40	19.94	47.34	74.00	-26.66	peak
5	14018.000	25.75	23.83	49.58	68.20	-18.62	peak
6	17747.000	23.60	26.23	49.83	74.00	-24.17	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.69	8.29	47.98	74.00	-26.02	peak
2	9585.000	36.14	13.19	49.33	68.20	-18.87	peak
3	11059.000	33.46	15.71	49.17	74.00	-24.83	peak
4	12687.000	27.63	20.17	47.80	74.00	-26.20	peak
5	14007.000	26.25	23.88	50.13	68.20	-18.07	peak
6	17989.000	21.86	28.40	50.26	74.00	-23.74	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	41.33	7.88	49.21	68.20	-18.99	peak
2	9200.000	38.07	11.42	49.49	68.20	-18.71	peak
3	10520.000	36.16	14.08	50.24	68.20	-17.96	peak
4	11609.000	31.33	17.88	49.21	74.00	-24.79	peak
5	13864.000	26.00	23.39	49.39	68.20	-18.81	peak
6	17978.000	21.71	28.31	50.02	74.00	-23.98	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.52	7.88	47.40	68.20	-20.80	peak
2	9706.000	36.43	13.49	49.92	68.20	-18.28	peak
3	10993.000	33.27	15.44	48.71	74.00	-25.29	peak
4	12632.000	26.53	19.99	46.52	74.00	-27.48	peak
5	13809.000	26.17	23.17	49.34	68.20	-18.86	peak
6	17736.000	23.35	26.13	49.48	74.00	-24.52	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7726.000	39.39	7.83	47.22	74.00	-26.78	peak
2	8771.000	38.08	9.50	47.58	68.20	-20.62	peak
3	9640.000	35.86	13.36	49.22	68.20	-18.98	peak
4	11422.000	31.08	17.27	48.35	74.00	-25.65	peak
5	13919.000	25.77	23.60	49.37	68.20	-18.83	peak
6	17978.000	21.91	28.31	50.22	74.00	-23.78	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.43	8.29	47.72	74.00	-26.28	peak
2	9541.000	36.34	12.91	49.25	68.20	-18.95	peak
3	10146.000	36.37	13.29	49.66	68.20	-18.54	peak
4	11708.000	29.71	17.91	47.62	74.00	-26.38	peak
5	13974.000	25.29	23.81	49.10	68.20	-19.10	peak
6	18000.000	21.50	28.51	50.01	74.00	-23.99	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7649.000	38.98	7.71	46.69	74.00	-27.31	peak
2	9607.000	37.46	13.30	50.76	68.20	-17.44	peak
3	11026.000	33.24	15.57	48.81	74.00	-25.19	peak
4	13061.000	25.81	20.71	46.52	68.20	-21.68	peak
5	13567.000	26.34	22.55	48.89	68.20	-19.31	peak
6	17758.000	23.14	26.31	49.45	74.00	-24.55	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8067.000	38.91	8.25	47.16	74.00	-26.84	peak
2	9706.000	36.37	13.49	49.86	68.20	-18.34	peak
3	10553.000	35.05	14.18	49.23	68.20	-18.97	peak
4	12698.000	26.58	20.20	46.78	74.00	-27.22	peak
5	13798.000	26.47	23.13	49.60	68.20	-18.60	peak
6	17967.000	21.91	28.21	50.12	74.00	-23.88	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	38.60	8.30	46.90	74.00	-27.10	peak
2	9585.000	36.55	13.19	49.74	68.20	-18.46	peak
3	10377.000	35.85	13.69	49.54	68.20	-18.66	peak
4	12522.000	27.94	19.80	47.74	74.00	-26.26	peak
5	13798.000	27.35	23.13	50.48	68.20	-17.72	peak
6	17945.000	22.92	28.01	50.93	74.00	-23.07	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5270
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	38.91	7.49	46.40	74.00	-27.60	peak
2	9222.000	37.99	11.49	49.48	68.20	-18.72	peak
3	10542.000	36.05	14.15	50.20	68.20	-18.00	peak
4	12676.000	27.84	20.14	47.98	74.00	-26.02	peak
5	13919.000	26.49	23.60	50.09	68.20	-18.11	peak
6	17989.000	22.19	28.40	50.59	74.00	-23.41	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7935.000	38.79	8.10	46.89	68.20	-21.31	peak
2	9607.000	36.80	13.30	50.10	68.20	-18.10	peak
3	11356.000	31.49	17.00	48.49	74.00	-25.51	peak
4	12599.000	28.22	19.88	48.10	74.00	-25.90	peak
5	14007.000	27.11	23.88	50.99	68.20	-17.21	peak
6	17934.000	23.07	27.90	50.97	74.00	-23.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5310
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	39.19	8.30	47.49	74.00	-26.51	peak
2	9255.000	37.89	11.59	49.48	68.20	-18.72	peak
3	11059.000	33.63	15.71	49.34	74.00	-24.66	peak
4	13006.000	27.68	20.48	48.16	68.20	-20.04	peak
5	13787.000	27.21	23.10	50.31	68.20	-17.89	peak
6	17912.000	22.99	27.70	50.69	74.00	-23.31	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	44.07	7.79	51.86	74.00	-22.14	peak
2	9596.000	36.29	13.26	49.55	68.20	-18.65	peak
3	11345.000	32.20	16.96	49.16	74.00	-24.84	peak
4	12566.000	27.36	19.85	47.21	74.00	-26.79	peak
5	13930.000	26.87	23.63	50.50	68.20	-17.70	peak
6	17978.000	21.73	28.31	50.04	74.00	-23.96	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5510
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	41.12	7.82	48.94	74.00	-25.06	peak
2	9310.000	37.20	11.75	48.95	74.00	-25.05	peak
3	10597.000	35.54	14.31	49.85	68.20	-18.35	peak
4	12665.000	28.28	20.09	48.37	74.00	-25.63	peak
5	13919.000	26.89	23.60	50.49	68.20	-17.71	peak
6	17989.000	21.57	28.40	49.97	74.00	-24.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5550
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7770.000	43.04	7.90	50.94	68.20	-17.26	peak
2	9211.000	37.70	11.45	49.15	68.20	-19.05	peak
3	10608.000	34.75	14.33	49.08	74.00	-24.92	peak
4	11719.000	30.36	17.91	48.27	74.00	-25.73	peak
5	13963.000	27.13	23.77	50.90	68.20	-17.30	peak
6	17989.000	22.07	28.40	50.47	74.00	-23.53	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5550
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7748.000	40.78	7.87	48.65	74.00	-25.35	peak
2	9211.000	37.48	11.45	48.93	68.20	-19.27	peak
3	10267.000	35.66	13.45	49.11	68.20	-19.09	peak
4	11323.000	32.01	16.84	48.85	74.00	-25.15	peak
5	13534.000	27.74	22.49	50.23	68.20	-17.97	peak
6	17934.000	22.59	27.90	50.49	74.00	-23.51	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7935.000	43.55	8.10	51.65	68.20	-16.55	peak
2	8826.000	40.93	9.73	50.66	68.20	-17.54	peak
3	10399.000	35.78	13.73	49.51	68.20	-18.69	peak
4	11422.000	31.15	17.27	48.42	74.00	-25.58	peak
5	13600.000	27.55	22.60	50.15	68.20	-18.05	peak
6	18000.000	22.10	28.51	50.61	74.00	-23.39	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5670
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7935.000	41.86	8.10	49.96	68.20	-18.24	peak
2	9244.000	38.27	11.56	49.83	68.20	-18.37	peak
3	10971.000	33.45	15.37	48.82	74.00	-25.18	peak
4	12643.000	27.80	20.03	47.83	74.00	-26.17	peak
5	13798.000	27.29	23.13	50.42	68.20	-17.78	peak
6	17978.000	21.40	28.31	49.71	74.00	-24.29	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5710
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	40.44	8.18	48.62	68.20	-19.58	peak
2	9563.000	36.30	13.05	49.35	68.20	-18.85	peak
3	10993.000	32.66	15.44	48.10	74.00	-25.90	peak
4	12709.000	26.42	20.24	46.66	68.20	-21.54	peak
5	13996.000	25.49	23.89	49.38	68.20	-18.82	peak
6	17714.000	23.70	25.96	49.66	74.00	-24.34	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5710
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7990.000	39.14	8.16	47.30	68.20	-20.90	peak
2	9134.000	38.45	11.13	49.58	74.00	-24.42	peak
3	11433.000	31.52	17.31	48.83	74.00	-25.17	peak
4	12643.000	26.98	20.03	47.01	74.00	-26.99	peak
5	13820.000	26.70	23.22	49.92	68.20	-18.28	peak
6	17758.000	24.06	26.31	50.37	74.00	-23.63	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	41.17	8.21	49.38	74.00	-24.62	peak
2	9266.000	38.37	11.62	49.99	68.20	-18.21	peak
3	10157.000	36.09	13.30	49.39	68.20	-18.81	peak
4	12698.000	26.62	20.20	46.82	74.00	-27.18	peak
5	13974.000	26.93	23.81	50.74	68.20	-17.46	peak
6	17978.000	21.65	28.31	49.96	74.00	-24.04	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	39.95	8.24	48.19	74.00	-25.81	peak
2	9849.000	36.07	13.55	49.62	68.20	-18.58	peak
3	11037.000	32.38	15.62	48.00	74.00	-26.00	peak
4	12676.000	27.78	20.14	47.92	74.00	-26.08	peak
5	13941.000	26.42	23.68	50.10	68.20	-18.10	peak
6	17989.000	21.65	28.40	50.05	74.00	-23.95	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	39.75	8.29	48.04	74.00	-25.96	peak
2	9552.000	36.94	12.98	49.92	68.20	-18.28	peak
3	11048.000	33.39	15.66	49.05	74.00	-24.95	peak
4	12687.000	27.64	20.17	47.81	74.00	-26.19	peak
5	13633.000	27.35	22.68	50.03	68.20	-18.17	peak
6	17967.000	21.43	28.21	49.64	74.00	-24.36	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	39.53	8.30	47.83	74.00	-26.17	peak
2	9563.000	37.26	13.05	50.31	68.20	-17.89	peak
3	10542.000	35.15	14.15	49.30	68.20	-18.90	peak
4	12665.000	26.22	20.09	46.31	74.00	-27.69	peak
5	13952.000	24.65	23.73	48.38	68.20	-19.82	peak
6	17978.000	20.32	28.31	48.63	74.00	-25.37	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9640.000	36.43	13.36	49.79	68.20	-18.41	peak
2	11015.000	35.42	15.52	50.94	74.00	-23.06	peak
3	12599.000	30.83	19.88	50.71	74.00	-23.29	peak
4	13127.000	29.85	21.00	50.85	68.20	-17.35	peak
5	13996.000	26.68	23.89	50.57	68.20	-17.63	peak
6	18000.000	22.01	28.51	50.52	74.00	-23.48	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.73	11.56	49.29	68.20	-18.91	peak
2	10597.000	36.27	14.31	50.58	68.20	-17.62	peak
3	11235.000	33.66	16.45	50.11	74.00	-23.89	peak
4	12896.000	29.77	20.50	50.27	68.20	-17.93	peak
5	13853.000	27.23	23.34	50.57	68.20	-17.63	peak
6	17769.000	23.47	26.41	49.88	74.00	-24.12	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9574.000	37.29	13.13	50.42	68.20	-17.78	peak
2	11059.000	34.65	15.71	50.36	74.00	-23.64	peak
3	13952.000	26.88	23.73	50.61	68.20	-17.59	peak
4	14876.000	30.38	19.74	50.12	68.20	-18.08	peak
5	16251.000	28.76	21.46	50.22	68.20	-17.98	peak
6	17989.000	22.55	28.40	50.95	74.00	-23.05	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5290
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9079.000	38.78	10.90	49.68	74.00	-24.32	peak
2	10509.000	36.28	14.05	50.33	68.20	-17.87	peak
3	11246.000	34.06	16.50	50.56	74.00	-23.44	peak
4	12236.000	31.16	19.19	50.35	74.00	-23.65	peak
5	13534.000	28.15	22.49	50.64	68.20	-17.56	peak
6	17956.000	22.54	28.10	50.64	74.00	-23.36	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7737.000	42.58	7.84	50.42	74.00	-23.58	peak
2	10531.000	36.54	14.12	50.66	68.20	-17.54	peak
3	12192.000	31.66	19.07	50.73	74.00	-23.27	peak
4	13061.000	29.76	20.71	50.47	68.20	-17.73	peak
5	13930.000	26.40	23.63	50.03	68.20	-18.17	peak
6	18000.000	21.72	28.51	50.23	74.00	-23.77	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5530
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8848.000	39.63	9.83	49.46	68.20	-18.74	peak
2	10212.000	36.30	13.35	49.65	68.20	-18.55	peak
3	11048.000	34.88	15.66	50.54	74.00	-23.46	peak
4	11873.000	32.42	18.16	50.58	74.00	-23.42	peak
5	12698.000	30.36	20.20	50.56	74.00	-23.44	peak
6	17703.000	24.88	25.86	50.74	74.00	-23.26	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7858.000	42.76	8.01	50.77	68.20	-17.43	peak
2	9310.000	38.06	11.75	49.81	74.00	-24.19	peak
3	11884.000	32.79	18.20	50.99	74.00	-23.01	peak
4	12489.000	31.22	19.78	51.00	74.00	-23.00	peak
5	13534.000	28.19	22.49	50.68	68.20	-17.52	peak
6	18000.000	21.57	28.51	50.08	74.00	-23.92	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5610
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	40.68	8.01	48.69	68.20	-19.51	peak
2	8969.000	39.50	10.42	49.92	68.20	-18.28	peak
3	11334.000	34.09	16.90	50.99	74.00	-23.01	peak
4	12555.000	30.76	19.84	50.60	74.00	-23.40	peak
5	13963.000	25.88	23.77	49.65	68.20	-18.55	peak
6	18000.000	21.69	28.51	50.20	74.00	-23.80	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5690
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7935.000	41.34	8.10	49.44	68.20	-18.76	peak
2	9332.000	38.19	11.82	50.01	74.00	-23.99	peak
3	10806.000	35.13	14.88	50.01	74.00	-23.99	peak
4	11620.000	32.64	17.88	50.52	74.00	-23.48	peak
5	13501.000	28.38	22.44	50.82	68.20	-17.38	peak
6	17912.000	22.65	27.70	50.35	74.00	-23.65	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5690
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9101.000	38.64	10.99	49.63	74.00	-24.37	peak
2	10960.000	34.39	15.34	49.73	74.00	-24.27	peak
3	11444.000	32.81	17.35	50.16	74.00	-23.84	peak
4	12654.000	30.33	20.06	50.39	74.00	-23.61	peak
5	13941.000	26.49	23.68	50.17	68.20	-18.03	peak
6	17989.000	21.65	28.40	50.05	74.00	-23.95	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9167.000	37.85	11.28	49.13	74.00	-24.87	peak
2	10520.000	36.82	14.08	50.90	68.20	-17.30	peak
3	11268.000	34.89	16.59	51.48	74.00	-22.52	peak
4	12236.000	32.10	19.19	51.29	74.00	-22.71	peak
5	13116.000	29.45	20.96	50.41	68.20	-17.79	peak
6	17967.000	21.45	28.21	49.66	74.00	-24.34	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	38.32	11.59	49.91	68.20	-18.29	peak
2	9783.000	36.20	13.63	49.83	68.20	-18.37	peak
3	11268.000	33.87	16.59	50.46	74.00	-23.54	peak
4	12533.000	30.42	19.82	50.24	74.00	-23.76	peak
5	13413.000	28.08	22.09	50.17	68.20	-18.03	peak
6	18000.000	21.91	28.51	50.42	74.00	-23.58	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160	Frequency(MHz):	5250
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8870.000	38.60	9.94	48.54	68.20	-19.66	peak
2	9519.000	36.89	12.77	49.66	68.20	-18.54	peak
3	11147.000	34.78	16.07	50.85	74.00	-23.15	peak
4	12599.000	30.69	19.88	50.57	74.00	-23.43	peak
5	13589.000	28.15	22.58	50.73	68.20	-17.47	peak
6	18000.000	22.26	28.51	50.77	74.00	-23.23	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160	Frequency(MHz):	5250
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	38.67	11.62	50.29	68.20	-17.91	peak
2	11026.000	35.35	15.57	50.92	74.00	-23.08	peak
3	11444.000	33.65	17.35	51.00	74.00	-23.00	peak
4	12148.000	31.74	18.97	50.71	74.00	-23.29	peak
5	13116.000	29.73	20.96	50.69	68.20	-17.51	peak
6	17967.000	22.36	28.21	50.57	74.00	-23.43	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE160	Frequency(MHz):	5570
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.85	11.37	49.22	74.00	-24.78	peak
2	11048.000	35.24	15.66	50.90	74.00	-23.10	peak
3	12269.000	31.38	19.27	50.65	74.00	-23.35	peak
4	12665.000	30.91	20.09	51.00	74.00	-23.00	peak
5	13347.000	29.09	21.85	50.94	74.00	-23.06	peak
6	18000.000	22.37	28.51	50.88	74.00	-23.12	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11ax HE160	Frequency(MHz):	5570
Polarity:	Vertical	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8914.000	40.34	10.15	50.49	68.20	-17.71	peak
2	10630.000	35.96	14.40	50.36	74.00	-23.64	peak
3	11433.000	32.98	17.31	50.29	74.00	-23.71	peak
4	12720.000	30.36	20.27	50.63	68.20	-17.57	peak
5	14007.000	26.59	23.88	50.47	68.20	-17.73	peak
6	17802.000	23.49	26.68	50.17	74.00	-23.83	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.5. SPURIOUS EMISSIONS(7 GHZ~18 GHZ) PARTIAL RU


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	38.45	11.59	50.04	68.20	-18.16	peak
2	10784.000	35.47	14.81	50.28	74.00	-23.72	peak
3	11092.000	34.89	15.83	50.72	74.00	-23.28	peak
4	12511.000	30.70	19.80	50.50	74.00	-23.50	peak
5	13963.000	25.84	23.77	49.61	68.20	-18.59	peak
6	17769.000	22.77	26.41	49.18	74.00	-24.82	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9563.000	36.47	13.05	49.52	68.20	-18.68	peak
2	10806.000	36.10	14.88	50.98	74.00	-23.02	peak
3	11268.000	33.94	16.59	50.53	74.00	-23.47	peak
4	12687.000	30.06	20.17	50.23	74.00	-23.77	peak
5	14007.000	25.71	23.88	49.59	68.20	-18.61	peak
6	18000.000	22.17	28.51	50.68	74.00	-23.32	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8056.000	38.84	8.24	47.08	74.00	-26.92	peak
2	9244.000	37.47	11.56	49.03	68.20	-19.17	peak
3	11037.000	32.27	15.62	47.89	74.00	-26.11	peak
4	12676.000	27.96	20.14	48.10	74.00	-25.90	peak
5	13930.000	26.39	23.63	50.02	68.20	-18.18	peak
6	18000.000	21.37	28.51	49.88	74.00	-24.12	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7319.000	38.48	7.50	45.98	74.00	-28.02	peak
2	8276.000	39.51	8.47	47.98	74.00	-26.02	peak
3	9574.000	36.27	13.13	49.40	68.20	-18.80	peak
4	11345.000	30.81	16.96	47.77	74.00	-26.23	peak
5	13413.000	26.97	22.09	49.06	68.20	-19.14	peak
6	17989.000	21.75	28.40	50.15	74.00	-23.85	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7165.000	37.98	7.43	45.41	68.20	-22.79	peak
2	9211.000	38.08	11.45	49.53	68.20	-18.67	peak
3	11026.000	33.94	15.57	49.51	74.00	-24.49	peak
4	12181.000	28.64	19.05	47.69	74.00	-26.31	peak
5	13996.000	25.86	23.89	49.75	68.20	-18.45	peak
6	17989.000	21.70	28.40	50.10	74.00	-23.90	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7726.000	38.24	7.83	46.07	74.00	-27.93	peak
2	9552.000	36.89	12.98	49.87	68.20	-18.33	peak
3	10388.000	35.91	13.70	49.61	68.20	-18.59	peak
4	11675.000	28.82	17.90	46.72	74.00	-27.28	peak
5	13457.000	26.72	22.27	48.99	68.20	-19.21	peak
6	17989.000	21.26	28.40	49.66	74.00	-24.34	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7011.000	40.76	7.24	48.00	68.20	-20.20	peak
2	9563.000	36.13	13.05	49.18	68.20	-19.02	peak
3	10542.000	34.29	14.15	48.44	68.20	-19.76	peak
4	11873.000	29.96	18.16	48.12	74.00	-25.88	peak
5	13501.000	26.36	22.44	48.80	68.20	-19.40	peak
6	17934.000	21.68	27.90	49.58	74.00	-24.42	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7704.000	38.43	7.79	46.22	74.00	-27.78	peak
2	9640.000	35.85	13.36	49.21	68.20	-18.99	peak
3	11059.000	32.51	15.71	48.22	74.00	-25.78	peak
4	12731.000	26.67	20.32	46.99	68.20	-21.21	peak
5	14007.000	25.29	23.88	49.17	68.20	-19.03	peak
6	18000.000	21.34	28.51	49.85	74.00	-24.15	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7033.000	43.36	7.26	50.62	68.20	-17.58	peak
2	7869.000	39.45	8.02	47.47	68.20	-20.73	peak
3	9640.000	36.12	13.36	49.48	68.20	-18.72	peak
4	10553.000	35.05	14.18	49.23	68.20	-18.97	peak
5	14018.000	25.12	23.83	48.95	68.20	-19.25	peak
6	17934.000	21.96	27.90	49.86	74.00	-24.14	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7033.000	43.01	7.26	50.27	68.20	-17.93	peak
2	8254.000	39.21	8.46	47.67	74.00	-26.33	peak
3	9706.000	36.65	13.49	50.14	68.20	-18.06	peak
4	11389.000	31.01	17.15	48.16	74.00	-25.84	peak
5	13952.000	25.33	23.73	49.06	68.20	-19.14	peak
6	17978.000	20.86	28.31	49.17	74.00	-24.83	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7242.000	38.30	7.49	45.79	68.20	-22.41	peak
2	9255.000	37.63	11.59	49.22	68.20	-18.98	peak
3	10553.000	34.62	14.18	48.80	68.20	-19.40	peak
4	12654.000	26.94	20.06	47.00	74.00	-27.00	peak
5	14029.000	26.22	23.76	49.98	68.20	-18.22	peak
6	17989.000	21.33	28.40	49.73	74.00	-24.27	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	38.23	8.18	46.41	68.20	-21.79	peak
2	9530.000	36.87	12.85	49.72	68.20	-18.48	peak
3	10289.000	35.54	13.50	49.04	68.20	-19.16	peak
4	11433.000	30.78	17.31	48.09	74.00	-25.91	peak
5	13545.000	27.44	22.51	49.95	68.20	-18.25	peak
6	17978.000	21.42	28.31	49.73	74.00	-24.27	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7682.000	47.84	7.76	55.60	74.00	-18.40	peak
2	7682.000	38.62	7.76	46.38	54.00	-7.62	AVG
3	9211.000	38.09	11.45	49.54	68.20	-18.66	peak
4	11037.000	34.45	15.62	50.07	74.00	-23.93	peak
5	12247.000	28.20	19.22	47.42	74.00	-26.58	peak
6	13809.000	26.12	23.17	49.29	68.20	-18.91	peak
7	17989.000	21.81	28.40	50.21	74.00	-23.79	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7682.000	44.21	7.76	51.97	74.00	-22.03	peak
2	8793.000	40.14	9.57	49.71	68.20	-18.49	peak
3	11312.000	32.06	16.79	48.85	74.00	-25.15	peak
4	12654.000	29.84	20.06	49.90	74.00	-24.10	peak
5	13820.000	28.02	23.22	51.24	68.20	-16.96	peak
6	17714.000	24.97	25.96	50.93	74.00	-23.07	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	46.82	7.95	54.77	68.20	-13.43	peak
2	9607.000	35.67	13.30	48.97	68.20	-19.23	peak
3	11037.000	32.31	15.62	47.93	74.00	-26.07	peak
4	12676.000	29.16	20.14	49.30	74.00	-24.70	peak
5	13941.000	26.15	23.68	49.83	68.20	-18.37	peak
6	18000.000	21.16	28.51	49.67	74.00	-24.33	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7803.000	47.78	7.95	55.73	68.20	-12.47	peak
2	8925.000	39.72	10.20	49.92	68.20	-18.28	peak
3	11389.000	29.96	17.15	47.11	74.00	-26.89	peak
4	14018.000	25.42	23.83	49.25	68.20	-18.95	peak
5	17274.000	23.78	23.98	47.76	68.20	-20.44	peak
6	17989.000	21.15	28.40	49.55	74.00	-24.45	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7979.000	43.76	8.14	51.90	68.20	-16.30	peak
2	9673.000	35.56	13.42	48.98	68.20	-19.22	peak
3	11422.000	30.46	17.27	47.73	74.00	-26.27	peak
4	12302.000	27.36	19.37	46.73	74.00	-27.27	peak
5	13908.000	25.45	23.56	49.01	68.20	-19.19	peak
6	18000.000	21.58	28.51	50.09	74.00	-23.91	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7297.000	38.19	7.50	45.69	74.00	-28.31	peak
2	7979.000	43.00	8.14	51.14	68.20	-17.06	peak
3	9321.000	37.29	11.79	49.08	74.00	-24.92	peak
4	10960.000	33.97	15.34	49.31	74.00	-24.69	peak
5	13600.000	26.41	22.60	49.01	68.20	-19.19	peak
6	17989.000	21.54	28.40	49.94	74.00	-24.06	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	42.42	8.21	50.63	74.00	-23.37	peak
2	9739.000	35.89	13.55	49.44	68.20	-18.76	peak
3	11433.000	31.40	17.31	48.71	74.00	-25.29	peak
4	13105.000	27.33	20.90	48.23	68.20	-19.97	peak
5	14007.000	26.51	23.88	50.39	68.20	-17.81	peak
6	17989.000	22.43	28.40	50.83	74.00	-23.17	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU0	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8034.000	44.12	8.21	52.33	74.00	-21.67	peak
2	9596.000	36.11	13.26	49.37	68.20	-18.83	peak
3	10465.000	34.00	13.93	47.93	68.20	-20.27	peak
4	11862.000	29.89	18.13	48.02	74.00	-25.98	peak
5	13941.000	26.42	23.68	50.10	68.20	-18.10	peak
6	17989.000	21.20	28.40	49.60	74.00	-24.40	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	8089.000	40.20	8.28	48.48	74.00	-25.52	peak
2	9321.000	37.32	11.79	49.11	74.00	-24.89	peak
3	10916.000	32.09	15.21	47.30	74.00	-26.70	peak
4	12225.000	27.50	19.16	46.66	74.00	-27.34	peak
5	13545.000	26.25	22.51	48.76	68.20	-19.44	peak
6	17956.000	22.00	28.10	50.10	74.00	-23.90	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU4	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8100.000	42.27	8.29	50.56	74.00	-23.44	peak
2	9574.000	35.91	13.13	49.04	68.20	-19.16	peak
3	10542.000	34.48	14.15	48.63	68.20	-19.57	peak
4	12709.000	27.38	20.24	47.62	68.20	-20.58	peak
5	13985.000	24.89	23.85	48.74	68.20	-19.46	peak
6	17978.000	21.53	28.31	49.84	74.00	-24.16	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	7759.000	40.37	7.88	48.25	68.20	-19.95	peak
2	9541.000	36.15	12.91	49.06	68.20	-19.14	peak
3	11400.000	31.51	17.20	48.71	74.00	-25.29	peak
4	12577.000	28.18	19.87	48.05	74.00	-25.95	peak
5	13919.000	26.79	23.60	50.39	68.20	-17.81	peak
6	17945.000	22.27	28.01	50.28	74.00	-23.72	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11ax HE20 Tone26 RU8	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.15	7.88	47.03	68.20	-21.17	peak
2	9596.000	36.52	13.26	49.78	68.20	-18.42	peak
3	10531.000	35.42	14.12	49.54	68.20	-18.66	peak
4	11301.000	32.17	16.74	48.91	74.00	-25.09	peak
5	13930.000	27.10	23.63	50.73	68.20	-17.47	peak
6	18000.000	21.74	28.51	50.25	74.00	-23.75	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.6. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)


Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.0100	74.72	-101.40	-26.68	47.60	-78.18	-3.90	-74.28	peak
2	0.0189	69.99	-101.35	-31.36	42.07	-82.86	-9.43	-73.43	peak
3	0.0318	65.87	-101.40	-35.53	37.55	-87.03	-13.95	-73.08	peak
4	0.0582	61.24	-101.51	-40.27	32.30	-91.77	-19.20	-72.57	peak
5	0.0840	59.51	-101.67	-42.16	29.12	-93.66	-22.38	-71.28	peak
6	0.1242	56.01	-101.72	-45.71	25.72	-97.21	-25.78	-71.43	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.


Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.1524	76.80	-101.63	-24.83	23.94	-76.33	-27.56	-48.77	peak
2	0.1819	73.49	-101.68	-28.19	22.41	-79.69	-29.09	-50.60	peak
3	0.2217	71.41	-101.75	-30.34	20.69	-81.84	-30.81	-51.03	peak
4	0.2540	67.10	-101.80	-34.70	19.50	-86.20	-32.00	-54.20	peak
5	0.3163	63.70	-101.87	-38.17	17.60	-89.67	-33.90	-55.77	peak
6	0.3819	60.89	-101.94	-41.05	15.96	-92.55	-35.54	-57.01	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V




No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.5897	63.85	-62.08	1.77	32.19	-49.73	-19.31	-30.42	peak
2	0.9737	61.21	-62.25	-1.04	27.83	-52.54	-23.67	-28.87	peak
3	1.4933	59.80	-62.04	-2.24	24.12	-53.74	-27.38	-26.36	peak
4	3.0278	58.43	-61.57	-3.14	29.54	-54.64	-21.96	-32.68	peak
5	7.0117	56.42	-61.21	-4.79	29.54	-56.29	-21.96	-34.33	peak
6	16.7205	56.04	-60.95	-4.91	29.54	-56.41	-21.96	-34.45	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.7. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19176.000	49.69	-5.48	44.21	74.00	-29.79	peak
2	20200.000	50.04	-5.58	44.46	74.00	-29.54	peak
3	21064.000	48.49	-4.85	43.64	74.00	-30.36	peak
4	22480.000	47.69	-3.90	43.79	74.00	-30.21	peak
5	24008.000	47.64	-2.75	44.89	74.00	-29.11	peak
6	25000.000	46.86	-2.10	44.76	74.00	-29.24	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19008.000	50.01	-5.23	44.78	74.00	-29.22	peak
2	19784.000	49.57	-5.28	44.29	74.00	-29.71	peak
3	21088.000	48.78	-4.84	43.94	74.00	-30.06	peak
4	21912.000	48.39	-4.43	43.96	74.00	-30.04	peak
5	23088.000	48.52	-3.41	45.11	74.00	-28.89	peak
6	24616.000	47.30	-2.33	44.97	74.00	-29.03	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.8. SPURIOUS EMISSIONS(26 GHZ~40 GHZ)


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	27638.000	51.08	-3.49	47.59	74.00	-26.41	peak
2	28968.000	48.78	-1.30	47.48	74.00	-26.52	peak
3	30060.000	49.37	-1.28	48.09	74.00	-25.91	peak
4	33840.000	47.39	0.59	47.98	74.00	-26.02	peak
5	36108.000	44.91	3.69	48.60	74.00	-25.40	peak
6	38068.000	45.56	3.42	48.98	74.00	-25.02	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	27484.000	49.83	-3.47	46.36	74.00	-27.64	peak
2	29276.000	48.51	-1.01	47.50	74.00	-26.50	peak
3	31040.000	48.95	-0.72	48.23	74.00	-25.77	peak
4	32818.000	50.31	-1.08	49.23	74.00	-24.77	peak
5	35954.000	45.88	3.94	49.82	74.00	-24.18	peak
6	37438.000	46.76	3.18	49.94	74.00	-24.06	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

8.9. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	55.2200	25.05	-15.00	10.05	40.00	-29.95	peak
2	191.0200	22.58	-11.98	10.60	43.50	-32.90	peak
3	250.1900	31.85	-14.56	17.29	46.00	-28.71	peak
4	395.6900	39.36	-9.61	29.75	46.00	-16.25	peak
5	708.0300	24.27	-4.10	20.17	46.00	-25.83	peak
6	912.7000	28.13	-0.54	27.59	46.00	-18.41	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.635V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	54.2500	30.28	-15.02	15.26	40.00	-24.74	peak
2	161.9200	24.79	-12.64	12.15	43.50	-31.35	peak
3	250.1900	31.37	-14.56	16.81	46.00	-29.19	peak
4	394.7200	38.34	-9.60	28.74	46.00	-17.26	peak
5	716.7600	25.57	-4.00	21.57	46.00	-24.43	peak
6	913.6700	26.93	-0.54	26.39	46.00	-19.61	peak

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

9. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

TEST ENVIRONMENT

Temperature	24.1℃	Relative Humidity	62%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V_60Hz


TEST DATE / ENGINEER

Test Date	August 8, 2025	Test By	Deacon Tan

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

TEST RESULTS

Test Mode:	802.11a20	Frequency(MHz):	5180
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1960	21.61	9.65	31.26	63.78	-32.52	QP
2	0.1960	9.35	9.65	19.00	53.78	-34.78	AVG
3	0.6384	23.33	9.63	32.96	56.00	-23.04	QP
4	0.6384	17.03	9.63	26.66	46.00	-19.34	AVG
5	1.1197	14.04	9.64	23.68	56.00	-32.32	QP
6	1.1197	7.95	9.64	17.59	46.00	-28.41	AVG
7	2.1018	10.99	9.74	20.73	56.00	-35.27	QP
8	2.1018	5.33	9.74	15.07	46.00	-30.93	AVG
9	5.9112	8.72	9.73	18.45	60.00	-41.55	QP
10	5.9112	3.59	9.73	13.32	50.00	-36.68	AVG
11	9.1836	7.70	9.73	17.43	60.00	-42.57	QP
12	9.1836	2.90	9.73	12.63	50.00	-37.37	AVG

Note:
1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Test Mode:	802.11a20	Frequency(MHz):	5180
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1998	21.43	9.64	31.07	63.62	-32.55	QP
2	0.1998	7.44	9.64	17.08	53.62	-36.54	AVG
3	0.6339	20.55	9.63	30.18	56.00	-25.82	QP
4	0.6339	11.80	9.63	21.43	46.00	-24.57	AVG
5	1.1186	11.18	9.63	20.81	56.00	-35.19	QP
6	1.1186	3.11	9.63	12.74	46.00	-33.26	AVG
7	2.0280	8.18	9.64	17.82	56.00	-38.18	QP
8	2.0280	1.37	9.64	11.01	46.00	-34.99	AVG
9	4.8765	5.06	9.66	14.72	56.00	-41.28	QP
10	4.8765	-0.99	9.66	8.67	46.00	-37.33	AVG
11	9.6526	3.93	9.73	13.66	60.00	-46.34	QP
12	9.6526	-0.25	9.73	9.48	50.00	-40.52	AVG

Note:
1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

10. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.407(a)
For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

11. TEST DATA

11.1. APPENDIX A: EMISSION BANDWIDTH

11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Verdict
11A-MIMO	Ant0	5180	19.08	5170.56	5189.64	PASS
	Ant1	5180	19.00	5170.56	5189.56	PASS
	Ant0	5200	18.84	5190.48	5209.32	PASS
	Ant1	5200	19.16	5190.36	5209.52	PASS
	Ant0	5240	18.84	5230.52	5249.36	PASS
	Ant1	5240	19.32	5230.44	5249.76	PASS
	Ant0	5260	18.60	5250.68	5269.28	PASS
	Ant1	5260	18.56	5250.76	5269.32	PASS
	Ant0	5280	19.88	5269.88	5289.76	PASS
	Ant1	5280	18.96	5270.56	5289.52	PASS
	Ant0	5320	19.20	5310.36	5329.56	PASS
	Ant1	5320	19.04	5310.52	5329.56	PASS
	Ant0	5500	19.24	5490.32	5509.56	PASS
	Ant1	5500	19.44	5490.28	5509.72	PASS
	Ant0	5580	18.84	5570.48	5589.32	PASS
	Ant1	5580	19.36	5570.24	5589.60	PASS
	Ant0	5700	19.48	5690.12	5709.60	PASS
	Ant1	5700	18.76	5690.72	5709.48	PASS
	Ant0	5720	19.28	5710.28	5729.56	PASS
	Ant1	5720	18.88	5710.48	5729.36	PASS
	Ant0	5720_UNII-2C	14.72	5710.28	5725	PASS
	Ant1	5720_UNII-2C	14.52	5710.48	5725	PASS
	Ant0	5720_UNII-3	4.56	5725	5729.56	PASS
	Ant1	5720_UNII-3	4.36	5725	5729.36	PASS
	Ant0	5745	19.92	5734.92	5754.84	PASS
	Ant1	5745	19.52	5735.00	5754.52	PASS
	Ant0	5785	19.00	5775.60	5794.60	PASS
	Ant1	5785	19.40	5775.40	5794.80	PASS
	Ant0	5825	20.80	5814.48	5835.28	PASS
	Ant1	5825	19.48	5815.16	5834.64	PASS
11N20MIMO	Ant0	5180	19.92	5170.00	5189.92	PASS
	Ant1	5180	20.40	5169.68	5190.08	PASS
	Ant0	5200	20.64	5189.40	5210.04	PASS
	Ant1	5200	19.84	5190.04	5209.88	PASS
	Ant0	5240	20.40	5229.96	5250.36	PASS
	Ant1	5240	20.32	5229.84	5250.16	PASS
	Ant0	5260	20.16	5249.96	5270.12	PASS
	Ant1	5260	19.88	5250.04	5269.92	PASS
	Ant0	5280	20.12	5269.88	5290.00	PASS
	Ant1	5280	19.88	5270.00	5289.88	PASS
	Ant0	5320	20.28	5309.88	5330.16	PASS
	Ant1	5320	20.12	5309.88	5330.00	PASS
	Ant0	5500	20.40	5489.84	5510.24	PASS
	Ant1	5500	20.24	5489.84	5510.08	PASS
	Ant0	5580	20.40	5569.84	5590.24	PASS
	Ant1	5580	20.24	5569.92	5590.16	PASS
	Ant0	5700	20.40	5689.80	5710.20	PASS
	Ant1	5700	20.08	5689.96	5710.04	PASS
	Ant0	5720	20.80	5709.68	5730.48	PASS
	Ant1	5720	20.64	5709.64	5730.28	PASS
	Ant0	5720_UNII-2C	15.32	5709.68	5725	PASS

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	Ant1	5720_UNII-2C	15.36	5709.64	5725	PASS
	Ant0	5720_UNII-3	5.48	5725	5730.48	PASS
	Ant1	5720_UNII-3	5.28	5725	5730.28	PASS
	Ant0	5745	20.56	5734.60	5755.16	PASS
	Ant1	5745	20.16	5735.04	5755.20	PASS
	Ant0	5785	19.92	5775.04	5794.96	PASS
	Ant1	5785	20.24	5775.04	5795.28	PASS
	Ant0	5825	20.24	5814.84	5835.08	PASS
	Ant1	5825	20.32	5814.84	5835.16	PASS
11N40MIMO	Ant0	5190	40.80	5169.52	5210.32	PASS
	Ant1	5190	39.44	5170.32	5209.76	PASS
	Ant0	5230	39.76	5210.16	5249.92	PASS
	Ant1	5230	39.76	5210.08	5249.84	PASS
	Ant0	5270	40.24	5250.00	5290.24	PASS
	Ant1	5270	40.32	5250.00	5290.32	PASS
	Ant0	5310	39.76	5290.24	5330.00	PASS
	Ant1	5310	40.32	5289.68	5330.00	PASS
	Ant0	5510	40.48	5489.76	5530.24	PASS
	Ant1	5510	40.16	5489.84	5530.00	PASS
	Ant0	5550	40.08	5530.00	5570.08	PASS
	Ant1	5550	39.92	5530.08	5570.00	PASS
	Ant0	5670	40.32	5649.84	5690.16	PASS
	Ant1	5670	40.16	5650.08	5690.24	PASS
	Ant0	5710	40.72	5689.68	5730.40	PASS
	Ant1	5710	39.92	5690.08	5730.00	PASS
	Ant0	5710_UNII-2C	35.32	5689.68	5725	PASS
	Ant1	5710_UNII-2C	34.92	5690.08	5725	PASS
	Ant0	5710_UNII-3	5.4	5725	5730.40	PASS
	Ant1	5710_UNII-3	5	5725	5730.00	PASS
	Ant0	5755	39.92	5735.08	5775.00	PASS
	Ant1	5755	39.76	5735.08	5774.84	PASS
	Ant0	5795	40.16	5775.00	5815.16	PASS
	Ant1	5795	40.64	5774.44	5815.08	PASS
11AC80MIMO	Ant0	5210	82.56	5169.20	5251.76	PASS
	Ant1	5210	81.60	5169.20	5250.80	PASS
	Ant0	5290	80.96	5249.52	5330.48	PASS
	Ant1	5290	81.76	5249.04	5330.80	PASS
	Ant0	5530	81.60	5489.04	5570.64	PASS
	Ant1	5530	81.76	5489.04	5570.80	PASS
	Ant0	5610	81.76	5569.20	5650.96	PASS
	Ant1	5610	81.60	5569.20	5650.80	PASS
	Ant0	5690	81.76	5649.20	5730.96	PASS
	Ant1	5690	81.44	5649.20	5730.64	PASS
	Ant0	5690_UNII-2C	75.8	5649.20	5725	PASS
	Ant1	5690_UNII-2C	75.8	5649.20	5725	PASS
	Ant0	5690_UNII-3	5.96	5725	5730.96	PASS
	Ant1	5690_UNII-3	5.64	5725	5730.64	PASS
	Ant0	5775	82.40	5733.40	5815.80	PASS
	Ant1	5775	81.60	5734.04	5815.64	PASS
11AC160MIMO	Ant0	5250	164.48	5167.44	5331.92	PASS
	Ant1	5250	165.12	5167.76	5332.88	PASS
	Ant0	5250_UNII-1	82.56	5167.44	5250	PASS
	Ant1	5250_UNII-1	82.24	5167.76	5250	PASS
	Ant0	5250_UNII-2A	81.92	5250	5331.92	PASS
	Ant1	5250_UNII-2A	82.88	5250	5332.88	PASS
	Ant0	5570	164.80	5487.76	5652.56	PASS
	Ant1	5570	163.52	5488.40	5651.92	PASS
11AX20MIMO	Ant0	5180	20.96	5169.44	5190.40	PASS
	Ant1	5180	20.68	5169.56	5190.24	PASS
	Ant0	5200	20.92	5189.52	5210.44	PASS

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	Ant1	5200	20.80	5189.52	5210.32	PASS
	Ant0	5240	20.72	5229.68	5250.40	PASS
	Ant1	5240	20.56	5229.72	5250.28	PASS
	Ant0	5260	20.44	5249.76	5270.20	PASS
	Ant1	5260	20.48	5249.80	5270.28	PASS
	Ant0	5280	20.64	5269.76	5290.40	PASS
	Ant1	5280	20.72	5269.72	5290.44	PASS
	Ant0	5320	20.60	5309.68	5330.28	PASS
	Ant1	5320	20.48	5309.80	5330.28	PASS
	Ant0	5500	20.84	5489.44	5510.28	PASS
	Ant1	5500	20.80	5489.72	5510.52	PASS
	Ant0	5580	20.84	5569.52	5590.36	PASS
	Ant1	5580	20.76	5569.56	5590.32	PASS
	Ant0	5700	20.68	5689.64	5710.32	PASS
	Ant1	5700	20.56	5689.76	5710.32	PASS
	Ant0	5720	20.72	5709.68	5730.40	PASS
	Ant1	5720	20.64	5709.60	5730.24	PASS
	Ant0	5720_UNII-2C	15.32	5709.68	5725	PASS
	Ant1	5720_UNII-2C	15.4	5709.60	5725	PASS
	Ant0	5720_UNII-3	5.4	5725	5730.40	PASS
	Ant1	5720_UNII-3	5.24	5725	5730.24	PASS
	Ant0	5745	21.12	5734.48	5755.60	PASS
	Ant1	5745	20.76	5734.72	5755.48	PASS
	Ant0	5785	21.00	5774.40	5795.40	PASS
	Ant1	5785	20.80	5774.72	5795.52	PASS
	Ant0	5825	20.68	5814.76	5835.44	PASS
	Ant1	5825	20.48	5814.68	5835.16	PASS
11AX40MIMO	Ant0	5190	40.40	5169.84	5210.24	PASS
	Ant1	5190	40.40	5169.76	5210.16	PASS
	Ant0	5230	40.56	5209.76	5250.32	PASS
	Ant1	5230	40.48	5209.84	5250.32	PASS
	Ant0	5270	40.40	5249.76	5290.16	PASS
	Ant1	5270	40.48	5249.68	5290.16	PASS
	Ant0	5310	40.40	5289.76	5330.16	PASS
	Ant1	5310	40.40	5289.84	5330.24	PASS
	Ant0	5510	40.40	5489.84	5530.24	PASS
	Ant1	5510	40.40	5489.84	5530.24	PASS
	Ant0	5550	40.16	5529.92	5570.08	PASS
	Ant1	5550	40.48	5529.84	5570.32	PASS
	Ant0	5670	40.64	5649.52	5690.16	PASS
	Ant1	5670	40.48	5649.76	5690.24	PASS
	Ant0	5710	40.48	5689.84	5730.32	PASS
	Ant1	5710	40.32	5689.84	5730.16	PASS
	Ant0	5710_UNII-2C	35.16	5689.84	5725	PASS
	Ant1	5710_UNII-2C	35.16	5689.84	5725	PASS
	Ant0	5710_UNII-3	5.32	5725	5730.32	PASS
	Ant1	5710_UNII-3	5.16	5725	5730.16	PASS
	Ant0	5755	40.32	5734.84	5775.16	PASS
	Ant1	5755	40.40	5734.76	5775.16	PASS
	Ant0	5795	40.64	5774.76	5815.40	PASS
	Ant1	5795	40.40	5774.84	5815.24	PASS
11AX80MIMO	Ant0	5210	81.44	5169.36	5250.80	PASS
	Ant1	5210	82.40	5168.88	5251.28	PASS
	Ant0	5290	82.08	5249.04	5331.12	PASS
	Ant1	5290	81.28	5249.52	5330.80	PASS
	Ant0	5530	81.92	5489.04	5570.96	PASS
	Ant1	5530	81.60	5489.36	5570.96	PASS
	Ant0	5610	81.92	5569.04	5650.96	PASS
	Ant1	5610	82.08	5569.04	5651.12	PASS
	Ant0	5690	82.08	5648.88	5730.96	PASS

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

	Ant1	5690	82.08	5648.88	5730.96	PASS
	Ant0	5690_UNII-2C	76.12	5648.88	5725	PASS
	Ant1	5690_UNII-2C	76.12	5648.88	5725	PASS
	Ant0	5690_UNII-3	5.96	5725	5730.96	PASS
	Ant1	5690_UNII-3	5.96	5725	5730.96	PASS
	Ant0	5775	81.92	5734.04	5815.96	PASS
	Ant1	5775	81.92	5733.88	5815.80	PASS
11AX160MIMO	Ant0	5250	165.76	5167.12	5332.88	PASS
	Ant1	5250	164.80	5167.76	5332.56	PASS
	Ant0	5250_UNII-1	82.88	5167.12	5250	PASS
	Ant1	5250_UNII-1	82.24	5167.76	5250	PASS
	Ant0	5250_UNII-2A	82.88	5250	5332.88	PASS
	Ant1	5250_UNII-2A	82.56	5250	5332.56	PASS
	Ant0	5570	166.08	5487.44	5653.52	PASS
	Ant1	5570	165.44	5487.12	5652.56	PASS

Test Mode	Antenna	Channel	Ru Size	Ru Index	26db BW [MHz]	FL [MHz]	FH [MHz]	Verdict
11AX20MIMO	Ant0	5180	26Tone	RU0	20.68	5168.52	5189.20	PASS
			52Tone	RU37	20.72	5168.48	5189.20	PASS
			106Tone	RU53	21.52	5168.56	5190.08	PASS
	Ant1	5180	26Tone	RU0	20.24	5168.80	5189.04	PASS
			52Tone	RU37	20.08	5169.12	5189.20	PASS
			106Tone	RU53	21.56	5168.20	5189.76	PASS
	Ant0	5200	26Tone	RU4	18.24	5190.88	5209.12	PASS
			52Tone	RU38	18.24	5190.92	5209.16	PASS
			106Tone	RU53	20.68	5188.48	5209.16	PASS
	Ant1	5200	26Tone	RU4	18.68	5190.72	5209.40	PASS
			52Tone	RU38	18.80	5190.60	5209.40	PASS
			106Tone	RU53	20.60	5189.08	5209.68	PASS
	Ant0	5240	26Tone	RU8	20.28	5230.92	5251.20	PASS
			52Tone	RU40	21.08	5230.08	5251.16	PASS
			106Tone	RU54	20.40	5230.84	5251.24	PASS
	Ant1	5240	26Tone	RU8	20.44	5230.84	5251.28	PASS
			52Tone	RU40	20.24	5230.92	5251.16	PASS
			106Tone	RU54	20.92	5230.52	5251.44	PASS
	Ant0	5260	26Tone	RU0	20.44	5248.60	5269.04	PASS
			52Tone	RU37	21.28	5248.00	5269.28	PASS
			106Tone	RU53	20.76	5248.84	5269.60	PASS
	Ant1	5260	26Tone	RU0	19.52	5248.92	5268.44	PASS
			52Tone	RU37	20.92	5248.56	5269.48	PASS
			106Tone	RU53	21.08	5248.48	5269.56	PASS
	Ant0	5280	26Tone	RU4	19.16	5270.48	5289.64	PASS
			52Tone	RU38	18.20	5270.92	5289.12	PASS
			106Tone	RU53	21.04	5268.24	5289.28	PASS
	Ant1	5280	26Tone	RU4	18.16	5270.96	5289.12	PASS
			52Tone	RU38	19.04	5270.76	5289.80	PASS
			106Tone	RU53	21.32	5268.52	5289.84	PASS
	Ant0	5320	26Tone	RU8	20.88	5310.96	5331.84	PASS
			52Tone	RU40	20.84	5310.60	5331.44	PASS
			106Tone	RU54	20.96	5310.76	5331.72	PASS
	Ant1	5320	26Tone	RU8	20.32	5310.88	5331.20	PASS
			52Tone	RU40	20.84	5310.60	5331.44	PASS
			106Tone	RU54	20.68	5310.64	5331.32	PASS
	Ant0	5500	26Tone	RU0	20.08	5489.00	5509.08	PASS
			52Tone	RU37	20.56	5488.60	5509.16	PASS
			106Tone	RU53	21.44	5488.20	5509.64	PASS
	Ant1	5500	26Tone	RU0	20.48	5488.80	5509.28	PASS
			52Tone	RU37	20.64	5488.84	5509.48	PASS

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

			106Tone	RU53	21.16	5488.64	5509.80	PASS
	Ant0	5580	26Tone	RU4	18.48	5570.68	5589.16	PASS
			52Tone	RU38	18.96	5570.80	5589.76	PASS
			106Tone	RU53	21.00	5568.36	5589.36	PASS
	Ant1	5580	26Tone	RU4	18.60	5570.84	5589.44	PASS
			52Tone	RU38	17.80	5571.56	5589.36	PASS
			106Tone	RU53	20.80	5568.80	5589.60	PASS
	Ant0	5700	26Tone	RU8	20.36	5690.96	5711.32	PASS
			52Tone	RU40	20.28	5690.92	5711.20	PASS
			106Tone	RU54	20.60	5690.80	5711.40	PASS
	Ant1	5700	26Tone	RU8	20.12	5690.96	5711.08	PASS
			52Tone	RU40	20.60	5690.68	5711.28	PASS
			106Tone	RU54	21.12	5690.52	5711.64	PASS
	Ant0	5745	26Tone	RU0	20.20	5733.84	5754.04	PASS
			52Tone	RU37	21.32	5733.40	5754.72	PASS
			106Tone	RU53	20.80	5733.36	5754.16	PASS
	Ant1	5745	26Tone	RU0	20.24	5733.76	5754.00	PASS
			52Tone	RU37	21.28	5733.84	5755.12	PASS
			106Tone	RU53	21.56	5732.92	5754.48	PASS
	Ant0	5785	26Tone	RU4	18.96	5775.88	5794.84	PASS
			52Tone	RU38	19.32	5775.72	5795.04	PASS
			106Tone	RU53	22.32	5772.80	5795.12	PASS
	Ant1	5785	26Tone	RU4	18.04	5775.76	5793.80	PASS
			52Tone	RU38	18.36	5775.88	5794.24	PASS
			106Tone	RU53	24.52	5772.76	5797.28	PASS
	Ant0	5825	26Tone	RU8	20.56	5815.88	5836.44	PASS
			52Tone	RU40	21.88	5814.96	5836.84	PASS
			106Tone	RU54	21.64	5815.76	5837.40	PASS
	Ant1	5825	26Tone	RU8	20.76	5815.84	5836.60	PASS
			52Tone	RU40	20.32	5815.88	5836.20	PASS
			106Tone	RU54	20.92	5815.80	5836.72	PASS

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.