



Engineering Solutions & Electromagnetic Compatibility Services

RF Exposure Report for Uncontrolled Environments

FCC Part 1.1307, 1.1310, 2.1091, 2.1093; ISED RSS-102

**Alula, LLC
428 Minnesota Street
Suite 300
St. Paul, MN 55101 (USA)**

Model: Connect+Pro

**FCC ID: U5X-HUBPLUS
IC: 8310A-HUBPLUS**

June 21, 2024

Report Prepared by: Desmond A. Fraser

Document Number: 2024014RFE

*This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and L3Harris Corporation. Test results relate only to the item tested.
This report replaces R1.2*

These test(s) are accredited under Rhein Tech Laboratories, Inc. ISO/IEC 17025 accreditation issued by ANAB. Refer to certificate and scope of accreditation AT-1445.

RF Exposure FCC Part 1.1307, 1.1310, 2.1091, 2.1093; ISSED RSS-102

MPE Co-location Calculations

The maximum permissible RF exposure for an uncontrolled environment is specified in FCC 1.1310 Table 1B and RSS-102 Issue 6 Table 7.

From OET 65, $S = \text{EIRP} / 4\pi R^2$

where:

S = Power density (mW/cm²)

EIRP = Equivalent Isotropic Radiated Power

R = 20 cm separation distance

Power Density for Alula 433 MHz TX

1. The MPE limit for the above device operating at 433.92 MHz for uncontrolled environments is 0.3 mW/cm² for FCC and 3 W/m² for ISSED.
2. EUT fundamental field strength at 433.92 MHz = 100.6 dBuV/m at 3 meters* = 5.4 dBm.
3. EIRP + 1 dB tune-up tolerance = 6.4 dBm = 4.4 mW
4. $S = 0.00088 \text{ mW/cm}^2$ = at 20 cm separation
(*per Rhein Tech 15.231/RSS-210 test report)

Power Density for Alula Z-Wave 908.42 MHz LMA TX (FCC ID: U5X-RE934Z; IC: 8310A-RE934Z)

1. The MPE limit for the above device operating at 908.42 MHz for uncontrolled environments is 0.3 mW/cm² for FCC and 3 W/m² for ISSED.
2. EUT fundamental field strength at 908.42 MHz = 89.1 dBuV/m at 3 meters* = -6.1 dBm.
3. EIRP + 1 dB tune-up tolerance = -5.1 dBm = 0.31 mW
4. $S = 0.000062 \text{ mW/cm}^2$ = at 20 cm separation
(*per certified test report)

Power Density for Espressif Wi-Fi (FCC ID: 2AC7Z-ESP32WROOM32E; IC: 21098-ESPWROOM32E)

1. The MPE limit for the above device operating at 2402-2480 MHz for uncontrolled environments is 1 mW/cm² for FCC and 10 W/m for ISSED.
2. The worst-case conducted power for the low band is 10 mW (per FCC grant).
3. Maximum antenna gain for this frequency range of operation is 3.4 dBi /2.2 numeric
4. EIRP = Conducted Power + 1 dB tune-up tolerance + Antenna Gain = 13.4 dBm = 22 mW.
5. $S = 0.0044 \text{ mW/cm}^2$ = at 20 cm separation.

Power Density for Telit Cellular Modem (FCC ID: RI7ME310G1WW; IC: 5131A-ME310G1WW)

Note: Most major U.S. carriers have shut down their 2G networks, which include GPRS and EDGE technologies, to repurpose the spectrum for more advanced technologies like 4G LTE and 5G. As a result, most GPRS/EDGE networks in the 824-849 MHz and 1850-1910 MHz bands have been phased out in the United States as of August 2023. Thus, LTE Band 4 1700 MHz with a conducted power of 0.316 W and a 5 dBi antenna were chosen as the worst-case LTE RF power for the MPE calculation.

Co-Location Calculations			
Frequency (MHz)	Band	Power (Watt)	Antenna Gain (dBi) / Numeric
1710 - 1780	4	0.316	5 / 3.2

The table above includes the conducted output power and the antenna gain of the Telit cellular modem collocated in the EUT.

Calculation of Co-Location MPE per Section 7.2 of KDB 447498 D01 General RF Exposure Guidance v06 and ISSED Notice 2016-DRS001: Updated July 2020, Applicability of Latest FCC RF Exposure KDB 447898 D01 v06

1. The MPE limit for uncontrolled environments for the above device operating at 1710 - 1780 MHz, Band 4, is 1.0 mW/cm² for FCC and 10 W/m² for ISSED.
2. The worst-case conducted power for the above frequency range is 0.316 W (per cellular grant).
3. The maximum antenna gain for this frequency range of operation is 5 dBi / 3.2 numeric (from Telit).
4. The EIRP = Conducted Power + 1 dB tune-up tolerance + Antenna Gain = 31 dBm = 1259.0 mW.
5. S = 0.25 mW/cm² = at 20 cm separation.

Co-Location - Summary of MPE: Alula TX + Alula Z-Wave + Espressif Wi-Fi + Telit Cellular Modem

Transmitter	Frequency (MHz)	FCC MPE Result (mW/cm ²)	ISED MPE Result (W/m ²)	FCC Limit (mW/cm ²)	ISED Limit (W/m ²)	Ratio FCC	Ratio ISSED
Alula TX	433.92	0.00088	0.0088	0.3	3	0.003	0.003
Alula Z-Wave	908.24	0.000062	0.00062	0.6	6	0.00010	0.00010
Wi-Fi	2412 - 2462	0.0044	0.044	1.0	10	0.0044	0.0044
Cellular	1710 - 1780	0.251	2.51	1.0	4.24	0.251	0.6
Sum of Ratios						0.26	0.6

Rounding up the sum of the ratios per FCC/ISED RF exposure policies, the sum of the ratios must be <1.

The sum of ratios for both FCC = 0.26<1 and the sum of ratios for ISSED = 0.6<1

Thus, the EUT meets the uncontrolled exposure limit at 20 cm when all transmitters transmit simultaneously and does **NOT** require MPE measurement for both FCC and ISSED.

The collocation test report is on file.