

Resolution Products, Inc.

**Wireless Smoke Detector
FCC ID: U5X-RE214**

Certification Test Report

November 17 2017

Contents

1. Introduction.....	3
2. Statement of Compliance.....	3
2.1. FCC Part 2 §2.907.....	3
2.2. FCC Part 2 §2.911.....	3
2.3. FCC Part 2 §2.913.....	3
2.4. FCC Part 2 §2.915.....	3
2.5. FCC Part 2 §2.925.....	3
2.6. FCC Part 2 §2.943, 2.945.....	3
2.7. FCC Part 2 §2.947.....	3
2.8. FCC Part 2 §2.948.....	4
2.9. FCC Part 2 §2.1033.....	4
3. Discussion of Laboratory Measurements and Rules Compliance.....	4
3.1. FCC Part 15 §15.231(a)(1).....	4
3.2. FCC Part 15 §15.231(a)(3).....	4
3.3. FCC Part 15 §15.231(a)(4).....	5
3.4. FCC Part 15 §15.231(a)(5).....	5
3.5. FCC Part 15 §15.231(b).....	5
3.5.1. Raw Field Strength Limits.....	5
3.5.2. Duty Cycle Correction Factor and Resulting Limits.....	5
3.5.3. Measured Radiated Field Strength Data.....	5
3.6. FCC Part 15 §15.231(c).....	6

1. Introduction

There will be two models listed under FCC ID: U5X-RE214. These two models are RE214 and RE214T.

The RE214(T) is a wireless transmitter daughter board that plugs into a battery powered smoke detector. The transmitter gives wireless functionality to a smoke detector and sends alarms to a home security system. A PIC16LF18323 microcontroller monitors the smoke detector and transmits alarm packets when smoke is detected. The RE214(T) housing is a cylindrical shape with a diameter of 4.7” and height of 2.3”. The daughter board inside the RE214(T) measures 1.155” x 2.315” x 0.537” and weights 0.2 oz. The unit as a whole weights 7.5 oz.

The transmitter circuit consists of a 10.78125MHz crystal and a Micrel MICRF113YM6 PLL Chip. This chip multiplies the crystal frequency to 345MHz. It also includes a circuit that allows ASK modulation of the 345MHz signal. A wire antenna connected to the PCB radiates the RF signal.

The transmitted packet is ASK modulated and has an on-time of 8.64ms. Precautions are taken in the firmware to ensure there is at least 100ms between packets, and that the transmission ends within 5 seconds.

Certification is requested under FCC Rules, Part 15, Subpart C, Paragraph 15.231.

2. Statement of Compliance

Specific sections of FCC Rules Part 2 that require information or listing are given below.

2.1. FCC Part 2 §2.907

This is an application for certification of original equipment

2.2. FCC Part 2 §2.911

- a) This application has been filed electronically using form 731.
- b) All required information has been supplied in this application and its attachments.
- c) This application has been electronically signed by an officer of Resolution Products, Inc.
- d) The technical test data has been signed by the agency performing the testing.
- e) Signature supplied in appropriate block on form 731.
- f) Processing fee has been paid.
- g) Signatures have been supplied electronically.

2.3. FCC Part 2 §2.913

- a) This application has been filed electronically.
- b) Appropriate fees have been filed electronically.
- c) Equipment samples shall be supplied as requested.

2.4. FCC Part 2 §2.915

We are requesting a grant of certification. This application shows compliance with the technical standards.

2.5. FCC Part 2 §2.925

A label shall be affixed to each piece of equipment, showing the FCC identifier. The label shall read “FCC ID: U5X-RE214”. See Exhibit B for a photograph showing the label and location on the device.

2.6. FCC Part 2 §2.943, 2.945

Sample production equipment shall be submitted to the FCC upon request.

2.7. FCC Part 2 §2.947

- a) Measurement procedure follows ANSI C63.4: 2009.
- b) A description of utilized test equipment is contained in the report.

2.8. FCC Part 2 §2.948

Radiated measurements were taken at the following FCC-approved facility:

Rhein Tech Laboratories, Inc.
360 Herndon Parkway, Suite 1400
Herndon, VA 20170 USA
Contact: Rick McMurray
703-689-0368

Photographs of the test site are shown in Exhibit J.

2.9. FCC Part 2 §2.1033

- a) Form 731 has been filed electronically.
- b) The technical report, along with its exhibits, contains the information as follows:
 - (1) full name and mailing address of the manufacturer of the device and the applicant for certification:
Resolution Products, Inc.
1402 Heggen St.
Hudson, WI 54016
 - (2) FCC Identifier is U5X-RE214
 - (3) Copy of the installation/user instructions is furnished as Exhibit E.
 - (4) A brief description of the device and operation is furnished in Exhibit F. Schematic is furnished in Exhibit G.
 - (5) Block diagram furnished in Exhibit H.
 - (6) This document constitutes a technical test report.
 - (7) Internal and external photographs have been furnished in Exhibits A and C.
 - (8) Not applicable. There are no peripheral or accessory devices used with this device. It is a standalone device.
 - (9) This application not pursuant to the transition rules of section 15.37
 - (10) Not applicable. This device does not include a scanning receiver.
 - (11) Not applicable.
 - (12) Not applicable.
- c) Not applicable. This device shall operate under Part 15 of the rules.
- d) Not applicable.
- e) Not applicable. This is not a composite system.

3. Discussion of Laboratory Measurements and Rules Compliance

3.1. FCC Part 15 §15.231(a)(1)

The RE214(T) daughter board monitors the smoke detector output connector. When an alarm signal is detected, the transmitter on the RE214(T) is activated. Eight transmission packets are sent by the device upon all alarm conditions. The transmitted packets are 16.35mS in length. The spacing between each packet is randomized from 100mS to 240mS. In addition, there is a 1 second space between the 4th and 5th packets for RE214T. If the “test alarm” button on the smoke detector is pressed and held by a user, the device will continue to send packets with the same length and spacing for the pendency of the alarm condition, as allowed. After transmission is complete, the device will go into a sleep mode and not transmit again until an alarm condition is detected, the housing is opened, or “test alarm” button is pressed.

If there are no activations received for one hour, three supervisory packets are sent with the same spacing given above.

3.2. FCC Part 15 §15.231(a)(3)

If no alarm activations have been received for a period of one hour, three supervision packets are transmitted. These supervision packets are then transmitted every hour in the absence of alarm activations. The total transmission time resulting from these supervision transmissions is well under the allowed 2 seconds per hour. They conclude within the 5-second window.

3.3. **FCC Part 15 §15.231(a)(4)**

Device does not continue transmitting beyond the packets resulting from each activation.

3.4. **FCC Part 15 §15.231(a)(5)**

There is no setup information transmitted with this device.

3.5. **FCC Part 15 §15.231(b)**

3.5.1. **Raw Field Strength Limits**

Interpolation performed on the data in the §15.231(b) table yields raw field strength limits as follows:

Fundamental: 77.25dBuV/m

Spurious: 57.25dBuV/m

Certain harmonics of the transmitted signal fall in the restricted bands of §15.205. These harmonics are all above 960MHz and have the following limit as given in §15.209:

Restricted band limit = 500uV/m = 54dBuV/m.

3.5.2. **Duty Cycle Correction Factor and Resulting Limits**

The RE214 and RE214T transmitter uses ASK modulation. 64 bits are transmitted in each packet, and the “on” time for each bit is 135uS. The resulting “on” time per packet is 8.64mS. The transmitted packets are limited to one packet in a 100mS period. The transmitter duty cycle over a 100ms time period is therefore $8.64/100 = 8.64\%$.

Calculating the allowed duty cycle correction factor as given in §15.35(c):

$$20\log(8.64/100) = -21.27\text{dB}$$

This transmitter therefore qualifies for the maximum duty cycle correction factor allowed in §15.35(c). The maximum duty cycle correction factor allowed is 20dB. Resulting radiated field strength limits are as follows:

Fundamental: 77.25 dBuV/m + 20 dBuV/m = **97.25dBuV/m**

Spurious: 57.25 dBuV/m + 20 dBuV/m = **77.25dBuV/m**

Restricted Band: 54.00 dBuV/m + 20 dBuV/m = **74dBuV/m**

3.5.3. **Measured Radiated Field Strength Data**

Radiated fundamental and spurious emissions were tested at three meters. The EUT was tested in the three orthogonal planes with the receive antenna in both polarities. The emissions were maximized per ANSI C63.4:2003 8.3.1.2; that is, the measurement antenna height was varied between 1 and 4m, and the EUT was rotated through 360 degrees on a rotating turntable until the maximum emissions were found. Both horizontal and vertical measurement antenna polarizations were used. A resolution bandwidth of 100kHz was used for frequencies less than 1000MHz, and a resolution bandwidth of 1MHz was used for frequencies greater than or equal to 1000MHz. The video bandwidth was set to a value at least three times greater than the resolution bandwidth.

All spurious emissions in the applicable frequency range were investigated.

The EUT was adapted to continuously transmit for testing purposes.

The fundamental signal, at **95.5dBuV/m**, passed by **1.8dB**.

The highest spurious signal was the 2nd harmonic, at **58.4dBuV/m**, which passed by **18.9dB**.

Further details of measured radiated field strength is shown in Exhibit I.

3.6. FCC Part 15 §15.231(c)

Allowed 20dB bandwidth of the transmitted signal is 0.25% of the carrier frequency.

BW Limit = $0.0025 \times 345\text{MHz}$

BW Limit = 0.8625MHz

Bandwidth measurements were taken at the following FCC-approved facility:

Rhein Tech Laboratories, Inc.

360 Herndon Parkway, Suite 1400

Herndon, VA 20170 USA

Contact: Rick McMurray

703-689-0368

The plot below shows the modulated signal. The bandwidth of the modulated signal is 24.78kHz or 0.02478MHz. These measurements show compliance with the bandwidth requirements.

