



SD-PMU-LTE
Rear side

Model: BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Pismo021 LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-52V-200W-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Power Managment Unit LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD Power Managment Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Software-Defined Power Managment Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Pismo021 LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-52V-200W-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Power Managment Unit LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD Power Managment Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEPWAVE



FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Softwave-Defined Power Managment Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

PEP WAVE



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 Power

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 POWER

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Pismo021 LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-52V-200W-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: PMU-DD-LTE-US-T

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Power Managment Unit LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD PMU LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD Power Managment Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTE

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)

Input : 12V-56V DC 19A (Terminal Block)

Output : 12V DC 16.67A

Output : 13.8V DC 14.49A

Output : 19V DC 10.53A

Output : 24V DC 8.33A

Output : 48V DC 4.17A

Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE

Contains FCC ID: N7NMC7455

Contains IC: 2417C-MC7455

CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: SD-PMU-LTEA

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: Software-Defined Power Management Unit (LTE)

Product Code:PMU-DD-LTE-US-T

Serial No.:3900-1988-3218

LAN MAC:D8-F1-F0-00-40-D8

peplink



Default Access	Username: admin
https://192.168.50.1	Password: admin

Input : 12V-56V DC 4A (DC Jack)
Input : 12V-56V DC 19A (Terminal Block)
Output : 12V DC 16.67A
Output : 13.8V DC 14.49A
Output : 19V DC 10.53A
Output : 24V DC 8.33A
Output : 48V DC 4.17A
Output : 52V DC 3.85A

Made in Taiwan



M8 HW1

FCC ID: U8G-P1021LTE
Contains FCC ID: N7NMC7455
Contains IC: 2417C-MC7455
CAN ICES-3(A)/NMB-3(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.