



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: HKES170100014204
Page: 1 of 13

RF Exposure Evaluation Report

Application No: HKES1701000142IT
Applicant: Pismo Labs Technology Limited
Product Name: Peplink / Pepwave / Pismo Labs wireless product
Model No.(EUT): MAX HD4, MAX HD4 LTE, MAX HD4 LTEA , PIMSO803AC♣
♣ Please refer to section 4.2 of this report which indicates which model was actually tested and which were electrically identical.
FCC ID: U8G-P1803AC
Standards: 47 CFR Part 1.1307(2016)
47 CFR Part 1.1310(2016)
Date of Receipt: 2017-02-07
Date of Test: 2017-02-08 to 2017-03-03
Date of Issue: 2017-03-07

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 2 of 13

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-03-07		Original

Authorized for issue by:			
			
			2017-03-03
Tested By		Hank Yan /Project Engineer	Date
			
			2017-03-07
Checked By		Eric Fu /Reviewer	Date



3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION	6
4.4 TEST FACILITY	6
4.5 DEVIATION FROM STANDARDS.....	7
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	7
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5 RF EXPOSURE EVALUATION	8
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	8
5.1.1 Limits	8
5.1.2 Test Procedure.....	8
5.1.3 EUT RF EXPOSURE EVALUATION.....	9-13



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 4 of 13

4 General Information

4.1 Client Information

Applicant:	Pismo Labs Technology Limited
Address of Applicant:	Flat A5, HK Spinners Ind. Bldg, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong

4.2 General Description of EUT

Product Name:	Peplink / Pepwave / Pismo Labs wireless product			
Model No.:	MAX HD4			
Antenna Type:	MIMO*2			
Power Supply:	AC/DC Adapter:Model: ATS050T-P121 Input: AC 100-240V, 50-60Hz, 1.2A MAX Output: DC 12V, 4.2A Or DC 12V-48V			
For 2.4G WIFI				
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2472MHz IEEE 802.n(HT40): 2422MHz to 2462MHz			
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n (HT20)&(HT40): OFDM (64QAM, 16QAM,QPSK,BPSK)			
Antenna Gain:	3dBi			
For 5G WIFI				
Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac 20MHz	5180-5240	4
		IEEE 802.11n/ac 40MHz	5190-5230	2
		IEEE 802.11ac 80MHz	5210	1
	UNII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n/ac 20MHz	5745-5825	5
		IEEE 802.11n/ac 40MHz	5755-5795	2
		IEEE 802.11ac 80MHz	5775	1
Data Modulation:	For 802.11a: OFDM(BPSK/QPSK/16QAM/64QAM) For 802.11n: OFDM(8PSK/QPSK/16QAM/64QAM) For 802.11ac: OFDM(8PSK/QPSK/16QAM/64QAM)			
Antenna Gain:	Band I: 5.5dBi, Band III: 6dBi			



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 5 of 13

LTE module:	Model Number: MC7455
	FCC ID: N7NMC7455
Alternative LTE module:	Model Number: MC7354
	FCC ID: N7NMC7355
Antenna for LTE module:	Type: External Antenna Antenna Gain: 1.93dBi
Remark:	The device uses four LTE module, each module has two antennas (One main antenna and one DIV antenna)

Declaration of EUT Family Grouping:

Model No.: MAX HD4, MAX HD4 LTE, MAX HD4 LTEA , PIMSO803AC

Only the model MAX HD4 was tested, since the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different is the model number for commercial purpose.



4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 9 of 13

5.1.3 EUT RF Exposure Evaluation

For 2.4GHz

Antenna Gain: 3dBi

According to KDB 662911, the transmit signal is correlated,

So Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi = 3 + 3 = 6

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.98 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

WiFi Module 1:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
Lowest	2422	27.620	578.096	0.114	1	0.1145	PASS

WiFi Module 2:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
Lowest	2422	27.320	539.511	0.107	1	0.1068	PASS

Note: Refer to report No. HKES170100014202 for EUT test Max Conducted Peak Output Power value.

The distancer (5th column) calculated from the Fries transmission formula is far greater than 40 cm separation requirement.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 10 of 13

For 5GHz

Band I

Antenna Gain: 5.5dBi

According to KDB 662911, the transmit signal is correlated,

So Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi = 5.5 + 3 = 8.5

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7.08 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

WiFi Module 1:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
48	5240	13.510	22.439	0.008	1	0.0079	PASS

WiFi Module 2:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
40	5200	12.920	19.588	0.007	1	0.0069	PASS

Note: Refer to report No. HKES170100014203 for EUT test Max Conducted Peak Output Power value.

The distancer (5th column) calculated from the Fries transmission formula is far greater than 40 cm separation requirement.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 11 of 13

Band III

Antenna Gain: 6dBi

According to KDB 662911, the transmit signal is correlated,

So Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi = 6 + 3 = 9

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7.94 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

WiFi Module 1:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
155	5775	18.630	72.946	0.029	1	0.0288	PASS

WiFi Module 2:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
151	5755	18.910	77.804	0.031	1	0.0307	PASS

Note: Refer to report No. HKES170100014203 for EUT test Max Conducted Peak Output Power value.

The distancer (5th column) calculated from the Fries transmission formula is far greater than 40 cm separation requirement.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 12 of 13

LTE for MC7455

Antenna Gain: 1.93dBi (One main antenna and a DIV antenna)

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.56 in linear scale.

Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
699	23.000	199.526	0.015	0.466	0.0332	PASS

Note: Refer to MPE evaluation report of LTE modular(FCC ID:N7NMC7455) and find the maximum ratio of the measured power density with limit in channel 23010, so only choose the channel to do MPE evaluation.

LTE for MC7354

Antenna Gain: 1.93dBi (One main antenna and a DIV antenna)

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.56 in linear scale.

Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 40 cm (mW/cm ²)	Limit	MPE Ratios	Result
704	23.000	199.526	0.015	0.469	0.0330	PASS

Note: Refer to MPE evaluation report of LTE modular(FCC ID:N7NMC7355) and find the maximum ratio of the measured power density with limit in channel 23755, so only choose the channel to do MPE evaluation.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: HKES170100014204

Page: 13 of 13

Exposure conditions for simultaneous transmission operations

For LTE module MC7455

Σ of ratios simultaneous transmitting= Wi-Fi 2.4G + Wi-Fi 5G + WWAN*4

Ratio of Power Density of Wi-Fi 2.4G at R = 40 cm		Ratio of Power Density of Wi-Fi 5G at R = 40 cm		Ratio of Max. Power Density of WWAN 1 at R = 40 cm	Total ratios simultaneous transmitting at R =40 cm	Limit	Result
WiFi Module 1	WiFi Module 2	WiFi Module 1	WiFi Module 2				
0.1145	0.1068	0.0288	0.0307	0.0332 * 4	0.414	1.0	PASS

For LTE module MC7354

Σ of ratios simultaneous transmitting= Wi-Fi 2.4G + Wi-Fi 5G + WWAN*4

Ratio of Power Density of Wi-Fi 2.4G at R = 40 cm		Ratio of Power Density of Wi-Fi 5G at R = 40 cm		Ratio of Max. Power Density of WWAN 1 at R = 40 cm	Total ratios simultaneous transmitting at R =40 cm	Limit	Result
WiFi Module 1	WiFi Module 2	WiFi Module 1	WiFi Module 2				
0.1145	0.1068	0.0288	0.0307	0.0330 * 4	0.413	1.0	PASS