

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBCIC-WTW-P24100653 R3

FCC ID: U8G-P1AX02

Product: Peplink Pepwave Wireless Product

Brand:  **PEPWAVE**

Model No.: MAX BR1 Pro 5G

Series Model: MAX-BR1-PRO-5GK-T-PRM

Received Date: 2024/10/29

Test Date: 2024/12/4

Issued Date: 2025/1/14

Applicant: PISMO LABS TECHNOLOGY LIMITED

Address: A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Hong Kong

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration /

Designation Number: 788550 / TW0003

Approved by:



Jeremy Lin / Project Engineer

Date:

2025/1/14

This test report consists of 11 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Pettie Chen / Senior Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Applicable RF Exposure Limit	5
3 Test Results	7
4 Conclusion.....	10
5 Information of the Testing Laboratories	11

Release Control Record

Issue No.	Description	Date Issued
MFBCIC-WTW-P24100653	Original release.	2024/12/26
MFBCIC-WTW-P24100653 R1	Revise Sample Status	2024/12/31
MFBCIC-WTW-P24100653 R2	Revise all test results	2025/1/10
MFBCIC-WTW-P24100653 R3	Revise 5GNR Band 41 power & LTE Band 48 gain & Maximum ERP	2025/1/14

1 Certificate

Product: Peplink Pepwave Wireless Product

Brand:  **PEPWAVE**

Test Model: MAX BR1 Pro 5G

Series Model: MAX-BR1-PRO-5GK-T-PRM

Sample Status: Prototype

Applicant: PISMO LABS TECHNOLOGY LIMITED

Test Date: 2024/12/4

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Applicable RF Exposure Limit

§ 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

➤ Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	<30
1.34-30	824/f	2.19/f	(180/f ²)*	<30
30-300	27.5	0.073	0.2	<30
300-1,500	...	...	f/1500	<30
1,500-100,000	...	...	1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

➤ Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6

f = frequency in MHz. * = Plane-wave equivalent power density.

MPE-based Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.
- Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

RF Source frequency (MHz)	Minimum Distance		Threshold ERP (watts)
	$\lambda_L/ 2\pi$	$\lambda_H/ 2\pi$	
0.3-1.34	159 m–35.6 m		1,920 R ² .
1.34-30	35.6 m–1.6 m		3,450 R ² /f ² .
30-300	1.6 m–159 mm		3.83 R ² .
300-1,500	159 mm–31.8 mm		0.0128 R ² f.
1,500-100,000	31.8 mm–0.5 mm		19.2 R ² .
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.			

3 Test Results

Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
---------------------------	--------------	------------	-----------

5GNR

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
NR Band 2	1852.5-1907.5	281.838	2.14	281.19	20	3060	Pass
NR Band 5	826.5-846.5	281.838	2.34	294.442	20	1686.06	Pass
NR Band 7	2502.5-2567.5	281.838	4.38	470.977	20	3060	Pass
NR Band 12	701.5-713.5	251.189	1.5	216.272	20	1431.06	Pass
NR Band 13	779.5-784.5	251.189	1.5	216.272	20	1590.18	Pass
NR Band 14	790.5-795.5	251.189	0.64	177.419	20	1612.62	Pass
NR Band 25	1852.5-1912.5	281.838	2.14	281.19	20	3060	Pass
NR Band 26_Part 22	826.5-846.5	251.189	2.34	262.422	20	1686.06	Pass
NR Band 26_Part 90	816.5-821.5	251.189	2.34	262.422	20	1665.66	Pass
NR Band 30	2307.5-2312.5	199.526	3.58	277.332	20	3060	Pass
NR Band 38	2575-2615	316.228	3.58	439.542	20	3060	Pass
NR Band 41	2501.01-2685	794.328	4.38	1327.394	20	3060	Pass
NR Band 48	3555-3694.98	177.828	-5.5	30.549	20	3060	Pass
NR Band 66	1712.5-1777.5	281.838	2.56	309.742	20	3060	Pass
NR Band 71	665.5-695.5	281.838	1.5	242.661	20	1357.62	Pass
NR Band 77_Part 27O	3705-3975	794.328	-1.5	342.768	20	3060	Pass
NR Band 77_Part 27Q	3455.01-3544.98	794.328	-8.02	76.384	20	3060	Pass
NR Band 78_Part 27Q	3455.01-3544.98	794.328	-8.02	76.384	20	3060	Pass

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- The WWAN average power refer to WWAN module (Brand: Telit, Model: FN990A40-HP, FCC ID: R17FN990A40HP) certified report.
- After technical evaluation, the verification data results of LTE B43 are covered by LTE B48. After technical evaluation, the verification data results of 5G NR n78 (Part 27O, 3700 ~ 3800MHz) are covered by 5G NR n77.

Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
---------------------------	--------------	------------	-----------

LTE

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
LTE Band 2	1850.7-1909.3	251.189	2.14	250.611	20	768	Pass
LTE Band 4	1710.7-1754.3	251.189	2.56	276.058	20	768	Pass
LTE Band 5	824.7-848.3	251.189	2.34	262.422	20	422.246	Pass
LTE Band 7	2502.5-2567.5	251.189	4.38	419.76	20	768	Pass
LTE Band 12	699.7-715.3	251.189	1.5	216.272	20	358.246	Pass
LTE Band 13	779.5-784.5	251.189	1.5	216.272	20	399.104	Pass
LTE Band 14	790.5-795.5	251.189	0.64	177.419	20	404.736	Pass
LTE Band 17	706.5-713.5	251.189	1.5	216.272	20	361.728	Pass
LTE Band 25	1850.7-1914.3	251.189	2.14	250.611	20	768	Pass
LTE Band 26_Part 22	824.7-848.3	251.189	2.34	262.422	20	422.246	Pass
LTE Band 26_Part 90	814.7-823.3	251.189	2.34	262.422	20	417.126	Pass
LTE Band 30	2307.5-2312.5	199.526	3.58	277.332	20	768	Pass
LTE Band 38	2572.5-2617.5	251.189	3.58	349.141	20	768	Pass
LTE Band 41	2502.5-2687.5	446.684	4.38	746.449	20	768	Pass
LTE Band 42_Part 27Q	3452.5-3547.5	177.828	-8.02	17.1	20	768	Pass
LTE Band 42_Part 96	3552.5-3597.5	177.828	-8.02	17.1	20	768	Pass
LTE Band 48	3552.5-3697.5	177.828	-5.5	30.549	20	768	Pass
LTE Band 66	1710.7-1779.3	251.189	2.56	276.058	20	768	Pass
LTE Band 71	665.5-695.5	251.189	1.5	216.272	20	340.736	Pass

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The WWAN average power refer to WWAN module (Brand: Telit, Model: FN990A40-HP, FCC ID: RI7FN990A40HP) certified report.
3. After technical evaluation, the verification data results of LTE B43 are covered by LTE B48. After technical evaluation, the verification data results of 5G NR n78 (Part 270, 3700 ~ 3800MHz) are covered by 5G NR n77.

WCDMA

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
WCDMA II	1852.4-1907.6	281.838	2.14	281.19	20	768	Pass
WCDMA IV	1712.4-1752.6	281.838	2.56	309.742	20	768	Pass
WCDMA V	826.4-846.6	281.838	2.34	294.442	20	423.116	Pass

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The WWAN average power refer to WWAN module (Brand: Telit, Model: FN990A40-HP, FCC ID: RI7FN990A40HP) certified report.

Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
---------------------------	--------------	------------	-----------

Co-location

For Single RF Source

MPE-based Exemption §1.1307(b)(3)(i)(B)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
WLAN 2.4 GHz	2412-2462	264.241	2.44	282.488	20	3060	Pass
WLAN 5 GHz	5180-5240 5745-5825	422.669	4.73	765.597	20	3060	Pass
LTE Band 41	2502.5-2687.5	446.684	4.38	746.449	20	3060	Pass

Note:

1. After evaluation, the WiFi/WWAN antennas was used with the highest gain as the representative antenna for testing.
2. Regarding the evaluation of the maximum exposure, the above operation mode is a representative mode selected after evaluation and based on the Maximum ratio.

For Multiple RF Sources (Simultaneous Operations)

Multiple RF Sources (Simultaneous Operations)							
Exemption Evaluation					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio			
WLAN 2.4 GHz	2412-2462	282.488	3060	0.092	0.586	1	Pass
WLAN 5 GHz	5180-5240 5745-5825	765.597	3060	0.25			
LTE Band 41	2502.5-2687.5	746.449	3060	0.244			

Note:

1. After evaluation, the WiFi/WWAN antennas was used with the highest gain as the representative antenna for testing.
2. Regarding the evaluation of the maximum exposure, the above operation mode is a representative mode selected after evaluation and based on the Maximum ratio.

4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---