

RF Exposure Report

Report No.: MFBCIC-WTW-P24080108 R2

FCC ID: U8G-P1MT03A

Test Model: MAX BR2

Series Model: BR2, MAX-BR2-LTEA-US-T-PRM

Received Date: 2024/8/7

Evaluation Date: 2025/1/10

Issued Date: 2025/1/17

Applicant: PISMO LABS TECHNOLOGY LIMITED

Address: A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle
Peak Road, Cheung Sha Wan, Hong Kong

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result	6

Release Control Record

Issue No.	Description	Date Issued
MFBCIC-WTW-P24080108	Original Release	2025/1/3
MFBCIC-WTW-P24080108 R1	Revise standard to KDB 447498 D01 General RF Exposure Guidance v06	2025/1/13
MFBCIC-WTW-P24080108 R2	Update distance to 22cm	2025/1/17

1 Certificate of Conformity

Product: Peplink Pepwave Wireless Product

Brand:  **PEP WAVE**

Test Model: MAX BR2

Series Model: BR2, MAX-BR2-LTEA-US-T-PRM

Sample Status: Prototype

Applicant: PISMO LABS TECHNOLOGY LIMITED

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :  , **Date:** 2025/1/17
Vera Huang / Specialist

Approved by :  , **Date:** 2025/1/17
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 22 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation Result

The EUT contains two certified WWAN module (Brand: Sierra, Model: EM7411). For detail information about WWAN, please refer to FCC ID: N7NEM74B.

Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	24	2.39	22	0.072	1.000
WCDMA Band 4	24	1.98	22	0.065	1.000
WCDMA Band 5	24.3	2.92	22	0.087	0.549
LTE Band 2	24	2.39	22	0.072	1.000
LTE Band 4	24	1.98	22	0.065	1.000
LTE Band 5	24.3	2.92	22	0.087	0.549
LTE Band 7	23.8	3.12	22	0.081	1.000
LTE Band 12	24	3.58	22	0.094	0.466
LTE Band 13	24	3.66	22	0.096	0.518
LTE Band 14	24	3.78	22	0.099	0.525
LTE Band 25	24	2.39	22	0.072	1.000
LTE Band 26_Part 90	24	1.62	22	0.060	0.542
LTE Band 26_Part 22	24	2.92	22	0.081	0.549
LTE Band 41	23.8	1.5	22	0.056	1.000
LTE Band 48	23.8	-5.5	22	0.011	1.000
LTE Band 66	24	1.98	22	0.065	1.000
LTE Band 71	24	3.44	22	0.091	0.442

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The WWAN average power refer to WWAN module (Brand: Sierra, Model: EM7411, FCC ID: N7NEM74B) certified report.
3. After technical evaluation, the verification data results of LTE B42/B43 are covered by LTE B48.

Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	23.58	3.15	22	0.077	1.00
WLAN 5GHz	28.74	4.76	22	0.368	1.00

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Refer to DEKRA lab report No.: 2420117R-RFUSV01S-A (WLAN 2.4G) and 2420117R-RFUSV03S-A (WLAN 5G) for WLAN power.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WWAN + WWAN + WLAN 2.4GHz + WLAN 5GHz$$

$$= 0.091 / 0.442 + 0.094 / 0.466 + 0.077 / 1 + 0.368 / 1 = 0.854$$

Therefore, the maximum calculations of above situations are less than the "1" limit.

---END---