

MPE/RF EXPOSURE REPORT



Evaluation of: Alereon Inc.–Camouflage (AL5955),
Commander (AL5930) and Combat (AL5934)

To: FCC CFR 47 Part 1.1310

Report Serial No.: ALER01-U2 MPE Rev A

This report supersedes: NONE

Applicant: Alereon Inc.
10800 Pecan Park Blvd, STE 100
Austin, TX 78750
USA

Product Function: UWB Module with Parallel/Serial USB
interface

Issue Date: 12th December 2018

This Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: Alereon AL5955, AL5930, AL5934
To: FCC CFR 47 Part 1.1310
Serial #: ALER01-U2 MPE Rev A
Issue Date: 12th December 2018
Page: 2 of 4

MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm^2) = $\text{EIRP}/(4*\pi*d^2)$

$\text{EIRP} = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

The calculations in the table below use the highest conducted power values specified for the EUT. These calculations represent worst case in terms of the exposure levels. As the 3 units use the same RF Chipset with the same antenna, the MPE values are the same for each unit tested. Only one MPE value is reported.

Maximum Permissible Exposure

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm^2) @ 20cm	Power Density Limit (mW/cm^2)	Min Calculated safe distance for Limit (cm)
3168.0 – 8976.0	0.2	1.05	-41.5	7.05E-05	1.47E-08	1.0	0.00

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Alereon AL5955, AL5930, AL5934
To: FCC CFR 47 Part 1.1310
Serial #: ALER01-U2 MPE Rev A
Issue Date: 12th December 2018
Page: 3 of 4

Specification - Maximum Permissible Exposure Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com