

47 CFR PART 15 SUBPART C TEST REPORT

for

Wireless Towing Light

Model No.: PY-9371

FCC ID: UAB9371

Of

Applicant: Many Wain Enterprise Co., Ltd
Address: 10, LANE 808, CHUNG SHAN ROAD, SHIN HWA
TAINAN CITY 712 Taiwan

Tested and Prepared

By

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22605-25166-C-1

6F., No. 58, Ln. 188, Rueiguang Rd., Neihu Dist., Taipei City, Taiwan (R.O.C.)
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	General Information.....	2
1.1	Notes	2
1.2	Testing laboratory	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	Details of approval holder.....	3
1.4	Application details	4
1.5	Test item	4
1.6	Test standards	4
2	Technical test	5
2.1	Summary of test results.....	5
2.2	Test environment	5
2.3	Test Mode	5
2.4	Test equipment utilized.....	6
2.5	General Test Procedure.....	7
3	Test results (enclosure)	8
3.1	Transmission Requirements.....	9
3.1.1	Limit of Transmission Time	9
3.1.2	Active Time	9
3.2	Output Power (Field Strength).....	10
3.3	Out of Band Radiated Emissions	12
3.4	Transmitter Radiated Emissions in restricted Bands	13
3.5	Spurious Emission radiated, Transmitter.....	14
3.6	Channel Bandwidth.....	15
3.7	Antenna requirement.....	16
3.8	Duty Cycle	17
3.9	Conducted Measurement at (AC) Power Line.....	18

Appendix: Diagrams



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

July 13, 2026	Rick Chen	<i>Rick Chen.</i>
Date	WTS-Lab. Name	Signature

Technical responsibility for area of testing:

July 13, 2026	Kevin Wang	<i>Kevin Wang</i>
Date	WTS Name	Signature



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.
6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)
Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.
Accredited number: ./.
Street: ./.
Town: ./.
Country: ./.

1.3 Details of approval holder

Name: Many Wain Enterprise Co., Ltd
Street: 10, LANE 808, CHUNG SHAN ROAD, SHIN HWA
Town: TAINAN CITY 712
Country: Taiwan



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

1.4 Application details

Date of receipt of test item: June 04, 2026
Date of test: from June 05, 2026 to July 07, 2026

1.5 Test item

Description of test item: Wireless Towing Light
Type identification: PY-9371
Brand name: MANY WAIN
Multi-listing model number: ./.
Transmitting frequency: 434 MHz
Operation mode: Simplex
Voltage supply: Battery 12V
Antenna type: Helical antenna
Antenna gain: 1 dBi
Sample no.: #01

Manufacturer (if applicable)

Name: ./.
Street: ./.
Town: ./.
Country: ./.

1.6 Test standards

47 CFR PART 15 SUBPART C § 15.231 (a) (2024-10)

1.7 Test procedure

ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed. ☒

or

The deviations were ascertained in the course of the tests performed. ☐

2.2 Test environment

Relative humidity content: 20 ... 75 %


Air pressure: 86 ... 103 kPa

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Conducted Measurement at (AC) Power Line)	Expanded Uncertainty : AMN : 0.90 dB Voltage probe : 1.18 dB Include Pulse Limiter : 1.44 dB
Estimation Result of Uncertainty of Radiated Emission(3M-966A) (Output Power (Field Strength), Out of Band Radiated Emissions, Transmitter Radiated Emissions in restricted Bands, Spurious Emission radiated)	Expanded Uncertainty : 009-30 MHz : 1.85 dB 30-1000 MHz : 4.21 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB
Estimation Result of Uncertainty of Bandwidth Measurement (Channel Bandwidth)	Expanded Uncertainty : 0.37 kHz
Estimation Result of Uncertainty of Frequency Drift Measurement (Frequency Tolerance)	Expanded Uncertainty : 6.11 Hz
Estimation Result of Uncertainty of Duty Cycle Measurement (Active Time)	Expanded Uncertainty : 0.18 ms

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

2.3 Test Mode

This EUT is the portable device. So the EUT was tested on three different axes. Please see assessment test results as section 3 of this test report.



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

2.4 Test equipment utilized

MAX Output Power

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2026/4/17	2027/4/16
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	

966A

Spurious Emission

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2026/4/20	2027/4/19
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2025/7/11	2026/7/10
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2026/4/17	2027/4/16
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2026/3/26	2027/3/25
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	

Duration Time & 20dB Bandwidth

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2026/3/12	2027/3/11

Duty cycle

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

2.5 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.3 using a spectrum analyzer. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was the 100 kHz and the video bandwidth was 300 kHz.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
20 dB μ V + 10.36 dB/m + 6 dB = 36.36 dB μ V/m @3m

ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.2.2 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table). The EUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

3 Test results (enclosure)

☒ 1st test

☐ test after modification

☐ production test

TEST CASE	Para. Number	Required	Test passed	Test failed
Transmission Requirements	15.231(a)	☒	☒	☐
Radiated Emission	15.231(b)	☒	☒	☐
Bandwidth of Emission	15.231(c)	☒	☒	☐
Frequency Tolerance	15.231(d)	☐	☐	☐
Period Alternate Field Strength Requirements	15.231(b)	☒	☒	☐
Antenna Requirement	15.203	☒	☒	☐
Conducted Measurement at (AC) Power Line	15.207	☐	☐	☐

The following is intentionally left blank.



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

3.1 Transmission Requirements

FCC 15.231(a)

3.1.1 Limit of Transmission Time

☒ According to 15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

☐ According to 15.231(a)(2), a transmitter activated automatically shall cease transmission within 5 seconds after activation.

3.1.2 Active Time

Test date: June 04, 2026


Temperature: 27.6 °C

Humidity: 54.5 %


Tester: Rick

☒ This manually operated transmitter employs a switch that automatically deactivate the transmitter within 818.942308 ms of being released.

☐ This transmitter is operated by automatic activation and active will cease transmission in __ ms after activation.



Duration time
Date: 4.JUN.2026 21:35:10



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

3.2 Output Power (Field Strength)

Radiated Emission Measurement

Operator: Jeff

File :power

Data :#1


Date: 2026/6/9

Temperature:26.7 °C

130.0 dBuV/m

Time: 下午 02:45:20

Humidity:34.6 %



Site : 966A Chamber

Condition : FCC 15.231 (434MHz) Power(PK)

Polarization: *Horizontal*

EUT : W6M22605-25166

Power : 12 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 434MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	434.0470	67.86	peak	25.37	93.23	100.80	100	290	-7.57	
*	434.0470	49.15	AVG	25.37	74.52	80.80	100	290	-6.28	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

Radiated Emission Measurement

Operator: Jeff

File :power
130.0 dBuV/m


Data :#2

Date: 2026/6/9

Temperature:26.7 °C

Time: 下午 02:58:46

Humidity:34.6 %



Site : 966A Chamber

Condition : FCC 15.231 (434MHz) Power(PK)

Polarization: **Vertical**

EUT : W6M22605-25166

Power : 12 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 434MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.9515	68.88	peak	25.37	94.25	100.80	100	261	-6.55	
*	433.9515	50.17	AVG	25.37	75.54	80.80	100	261	-5.26	

Limit 15.231(b)

Fundamental Frequency (MHz)	Field strength of fundamental, limit $\mu\text{V/m}$
40.66 – 40.70	2,250
70 – 130	1,250
130 – 174	1,250 to 3,750
174 – 260	3,750
260 – 470	3,750 to 12,500** (434 MHz: 80.83 dB $\mu\text{V/m}$ = 11000.01 $\mu\text{V/m}$)
Above 470	12,500

** linear interpolation

Explanation: ./.



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

3.3 Out of Band Radiated Emissions

FCC Rule: 15.231(b) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Guidance on Measurement of pulsed emission: 15.35(c)

“the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.”

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms or one period})$

Limits:

For frequencies (Average measurements)

Correction factor conform 15.35 (c) (Average measurements)

Duty cycle correction :

Max. Peak reading – duty cycle correction

Max permitted average Limits = Max permitted Fundamental limit – 20 dB

For example for 434 fundamental carrier:

Max permitted average Limit: $80.83 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 60.83 \text{ dB}\mu\text{V/m}$

For frequencies above 1GHz (Peak measurements).

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.231 (b), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 8000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of pulsed emission:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

For frequencies above 1GHz (Average measurements).

The correction factor, based on the channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

No duty cycle correction was added to the reading

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)

Above 960 MHz

For mode DSSS CW: $54 \text{ dB}\mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB}\mu\text{V/m}$

Explanation: See attached diagrams in appendix.



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

3.5 Spurious Emission radiated, Transmitter

Spurious emission was measured with modulation (declared by manufacturer).

The limits on the field strength of the spurious emission in the table § 15.231(b) are based on the fundamental frequency of the intentional radiator. Spurious emission shall be attenuated to the average (or alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

In addition, radiated emission which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.


In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

Summary table with radiated data of the test plots

- Note**
- 1. Correction Factor = Antenna factor + Cable loss - Preamplifier**
 - 2. The formula of measured value as: Test Result = Reading + Correction Factor**
 - 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
 - 4. All not in the table noted test results are more than 20 dB below the relevant limits.**
 - 5. Up Line: PK Limit Line, Down Line: Ave Limit Line.**

All other not noted test plots do not contain significant test results in relation to the limits
Test results: The unit meet the FCC requirements.

Explanation: See attached diagrams in appendix.



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

3.6 Channel Bandwidth

Measurement of Necessary Bandwidth (BN)


Test date: June 04, 2026

Temperature: 27.6 °C

Humidity: 54.5 %

Tester: Rick

Used frequency	Bandwidth	Limit
434 MHz	434.05 MHz	1.085 MHz



20DB BANDWIDTH
Date: 4.JUN.2026 21:17:06

Limits:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.



Registration number: W6M22605-25166-C-1
FCC ID: UAB9371

3.7 Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

Explanation: This Helical antenna is integral antenna which passes antenna requirement.

The equipment meets the requirements	yes ☒	no ☐
--------------------------------------	--	--------------------------------



Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

3.8 Duty Cycle

The correction factor, based on the channel dwell time in a 100ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the measured value.

Average Reading = Peak Reading (dBuV/m) + Duty Cycle Correction

Test date: June 04, 2026

Temperature: 27.6 °C


Humidity: 54.5 %

Tester: Rick

Duty Cycle Correction = 20 log (Cycle)

In order to determine the Duty Cycle, the EUT is measured as:

Testing Mode	T period (ms)	T on (ms)	Duty Cycle	Duty Cycle Correction 20*log(Duty Cycle)
Transmitting mode	100	11.6	0.116	-18.71





Registration number: W6M22605-25166-C-1

FCC ID: UAB9371

3.9 Conducted Measurement at (AC) Power Line

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.


This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Note

- 1. The formula of measured value as: Test Result = Reading + Correction Factor**
- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss**
- 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.**
- 5. Up Line: QP Limit Line, Down Line: Ave Limit Line.**
- 6. This test is not required because the EUT is powered by battery.**

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50



Appendix

Measurement diagrams

Spurious Emissions radiated



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 1

Data : #1


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 03:03:28

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 30-300(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: *Horizontal*

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	51.8700	33.69	peak	-12.63	21.06	80.80	100	0	-59.74	
	144.7500	33.82	peak	-12.63	21.19	80.80	100	134	-59.61	
	156.0900	34.67	peak	-12.12	22.55	80.80	100	274	-58.25	
*	277.0500	35.70	peak	-12.48	23.22	46.00	100	33	-22.78	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File :1

Data :#2


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 03:04:12

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 30-300(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	50.2500	33.51	peak	-12.60	20.91	80.80	100	24	-59.89	
	142.8600	33.39	peak	-12.71	20.68	80.80	100	163	-60.12	
*	156.0900	35.36	peak	-12.12	23.24	80.80	100	236	-57.56	
	294.0600	34.24	peak	-11.95	22.29	80.80	100	158	-58.51	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 2

Data : #1


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 03:04:56

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 300-1000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: *Horizontal*

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	379.1000	33.87	peak	-9.84	24.03	80.80	100	238	-56.77	
	592.6000	33.69	peak	-5.06	28.63	80.80	100	211	-52.17	
	755.7000	33.81	peak	-2.03	31.78	80.80	100	339	-49.02	
*	868.4000	44.48	peak	-1.10	43.38	80.80	100	288	-37.42	

*:Maximum data x:Over limit !:over margin



Address: No.99, Sec.1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File :2

Data :#2


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 03:05:40

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 300-1000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	339.9000	35.51	peak	-10.99	24.52	80.80	100	175	-56.28	
	565.3000	34.39	peak	-5.98	28.41	80.80	100	32	-52.39	
	786.5000	33.32	peak	-1.78	31.54	80.80	100	32	-49.26	
*	868.4000	46.68	peak	-1.10	45.58	80.80	100	265	-35.22	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #1


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:14:15

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 1000-2000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Horizontal

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1302.000	56.09	peak	-7.90	48.19	74.00	150	73	-25.81	
	1736.000	47.16	peak	-6.93	40.23	80.80	150	217	-40.57	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #4


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:16:20

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 1000-2000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1302.000	56.82	peak	-7.90	48.92	74.00	150	124	-25.08	
	1737.000	49.12	peak	-6.92	42.20	80.80	150	320	-38.60	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #2


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:14:55

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 2000-4000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: *Horizontal*

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2170.000	46.13	peak	-4.10	42.03	80.80	150	87	-38.77	
	2604.000	48.95	peak	-3.16	45.79	80.80	150	143	-35.01	
	3038.000	46.04	peak	-1.71	44.33	80.80	150	207	-36.47	
	3472.000	45.07	peak	-0.85	44.22	80.80	150	16	-36.58	
*	3908.000	41.76	peak	1.93	43.69	74.00	150	225	-30.31	

*:Maximum data x:Over limit !:over margin



Address: No.99, Sec.1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File :3

Data :#5


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:17:02

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 2000-4000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2170.000	46.51	peak	-4.10	42.41	80.80	150	23	-38.39	
	2604.000	49.09	peak	-3.16	45.93	80.80	150	207	-34.87	
	3038.000	45.63	peak	-1.71	43.92	80.80	150	129	-36.88	
	3474.000	46.44	peak	-0.84	45.60	80.80	150	55	-35.20	
*	3908.000	42.84	peak	1.93	44.77	74.00	150	110	-29.23	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #3


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:15:36

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 4000-8000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Horizontal

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4340.000	38.34	peak	2.71	41.05	74.00	150	61	-32.95	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #6


Date: 2026/6/9

Temperature: 26.7 °C

100.0 dBuV/m

Time: 下午 04:17:44

Humidity: 34.6 %



Site : 966A Chamber

Condition : FCC 15.231(434MHz) 4000-8000(PK)

EUT : W6M22605-25166

M/N:

Test Mode : TX 434MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4340.000	39.45	peak	2.71	42.16	74.00	150	281	-31.84	

*:Maximum data x:Over limit !:over margin