

# FCC RF EXPOSURE REPORT

Lorex Technology Inc.

2.4G wireless receiver product

Model Number: LWB3801-W

FCC ID: UCZ-LWB3801-W

Prepared for : Lorex Technology Inc.

250 Royal Crest Court Markham, L3R 3S1 Ontario Canada

Prepared By :EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City,GuangDong,  
China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1706030

Date of Test : May 09~ June 15, 2017

Date of Report : June 16, 2017

## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-3.0               | 614                              | 1.63                              | (100)*                                  | 6                                                |
| 3.0-30                | 1842/f                           | 4.89/f                            | (900/f)*                                | 6                                                |
| 30-300                | 61.4                             | 0.163                             | 1.0                                     | 6                                                |
| 300-1500              |                                  |                                   | F/300                                   | 6                                                |
| 1500-10000            |                                  |                                   | 5                                       | 6                                                |

#### (b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-1.34              | 614                              | 1.63                              | (100)*                                  | 30                                               |
| 1.34-30               | 824/f                            | 2.19/f                            | (180/f)*                                | 30                                               |
| 30-300                | 27.5                             | 0.073                             | 0.2                                     | 30                                               |
| 300-1500              |                                  |                                   | F/1500                                  | 30                                               |
| 1500-10000            |                                  |                                   | 1.0                                     | 30                                               |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 3、Calculated Result and Limit

| Antenna a |                    |                          |                         |                          |              |          |                                                      |                                                                       |                |
|-----------|--------------------|--------------------------|-------------------------|--------------------------|--------------|----------|------------------------------------------------------|-----------------------------------------------------------------------|----------------|
| Mode      | Frequency<br>(MHz) | output<br>power<br>(dBm) | output<br>power<br>(mW) | Target<br>power<br>(dBm) | Antenna gain |          | Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Limited<br>of<br>Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Test<br>Result |
|           |                    |                          |                         |                          | (dBi)        | (Linear) |                                                      |                                                                       |                |
| DSSS      | 2406               | 17.94                    | 62.23                   | 17±1                     | 3            | 1.99     | 0.02505                                              | 1                                                                     | Compiles       |
|           | 2441               | 17.66                    | 58.34                   | 17±1                     | 3            | 1.99     | 0.02505                                              | 1                                                                     | Compiles       |
|           | 2469               | 18.52                    | 71.12                   | 18±1                     | 3            | 1.99     | 0.03153                                              | 1                                                                     | Compiles       |

| Antenna b |                    |                          |                         |                          |              |          |                                                      |                                                                       |                |
|-----------|--------------------|--------------------------|-------------------------|--------------------------|--------------|----------|------------------------------------------------------|-----------------------------------------------------------------------|----------------|
| Mode      | Frequency<br>(MHz) | output<br>power<br>(dBm) | output<br>power<br>(mW) | Target<br>power<br>(dBm) | Antenna gain |          | Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Limited<br>of<br>Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Test<br>Result |
|           |                    |                          |                         |                          | (dBi)        | (Linear) |                                                      |                                                                       |                |
| DSSS      | 2406               | 17.17                    | 52.12                   | 17±1                     | 3            | 1.99     | 0.02505                                              | 1                                                                     | Compiles       |
|           | 2441               | 16.94                    | 49.43                   | 16±1                     | 3            | 1.99     | 0.01989                                              | 1                                                                     | Compiles       |
|           | 2469               | 17.42                    | 55.21                   | 17±1                     | 3            | 1.99     | 0.02505                                              | 1                                                                     | Compiles       |