


5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

5965MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.9208G	59.82	74.00	-14.18	74.88	3	Horizontal	309.4	1.70	-	38.64	12.09	65.79			
AV	11.92824G	47.18	54.00	-6.82	62.22	3	Horizontal	309.4	1.70	-	38.66	12.09	65.79			
PK	17.91268G	47.00	74.00	-27.00	52.15	3	Horizontal	337	1.80	-	42.05	15.25	62.45			
AV	17.91276G	38.00	54.00	-16.00	43.15	3	Horizontal	337	1.80	-	42.05	15.25	62.45			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

5965MHz_TX




EUT_V_4TX
 Setting 26
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.8543G	50.56	83.54	-32.98	41.84	1	Vertical	321.7	1.84	-	39.09	17.29	47.66			
AV	23.85975G	42.09	63.54	-21.45	33.38	1	Vertical	321.7	1.84	-	39.08	17.29	47.66			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

5965MHz_TX




EUT_V_4TX
 Setting 26
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.8598G	52.66	83.54	-30.88	43.95	1	Horizontal	335.3	1.61	-	39.08	17.29	47.66			
AV	23.8598G	43.34	63.54	-20.20	34.63	1	Horizontal	335.3	1.61	-	39.08	17.29	47.66			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6205MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.40608G	60.61	74.00	-13.39	74.52	3	Vertical	359	1.80	-	38.91	12.55	65.37			
AV	12.41G	48.47	54.00	-5.53	62.36	3	Vertical	359	1.80	-	38.92	12.56	65.37			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6205MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.39672G	63.89	74.00	-10.11	77.83	3	Horizontal	303.7	1.57	-	38.90	12.54	65.38			
AV	12.4008G	51.20	54.00	-2.80	65.13	3	Horizontal	303.7	1.57	-	38.90	12.55	65.38			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6205MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.6125G	56.23	83.54	-27.31	51.57	1	Vertical	50.8	1.60	-	37.82	15.25	48.41			
AV	18.61545G	41.67	63.54	-21.87	37.01	1	Vertical	50.8	1.60	-	37.83	15.25	48.42			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6205MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.6114G	54.29	83.54	-29.25	49.63	1	Horizontal	310.1	1.75	-	37.82	15.25	48.41			
AV	18.61075G	40.98	63.54	-22.56	36.32	1	Horizontal	310.1	1.75	-	37.82	15.25	48.41			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6405MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.79624G	65.64	88.20	-22.56	78.15	3	Vertical	31.1	1.75	-	39.78	12.96	65.25			
RMS	12.80112G	51.58	68.20	-16.62	64.07	3	Vertical	31.1	1.75	-	39.80	12.96	65.25			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6405MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.79432G	66.85	88.20	-21.35	79.37	3	Horizontal	18	1.80	-	39.77	12.96	65.25			
RMS	12.81056G	52.33	68.20	-15.87	64.81	3	Horizontal	18	1.80	-	39.80	12.97	65.25			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6405MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.19835G	55.33	83.54	-28.21	51.10	1	Vertical	236	1.19	-	37.81	15.22	48.80			
AV	19.19G	42.11	63.54	-21.43	37.85	1	Vertical	236	1.19	-	37.84	15.22	48.80			

5.925-6.425GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6405MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.19745G	56.95	83.54	-26.59	52.72	1	Horizontal	310.1	1.75	-	37.81	15.22	48.80			
AV	19.1974G	42.14	63.54	-21.40	37.91	1	Horizontal	310.1	1.75	-	37.81	15.22	48.80			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6565MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.13432G	67.19	88.20	-21.01	78.81	3	Vertical	60	1.58	-	40.04	13.31	64.97			
RMS	13.142G	53.64	68.20	-14.56	65.20	3	Vertical	60	1.58	-	40.07	13.32	64.95			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6565MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.14528G	66.39	88.20	-21.81	77.94	3	Horizontal	352	1.46	-	40.08	13.32	64.95			
RMS	13.1388G	52.60	68.20	-15.60	64.19	3	Horizontal	352	1.46	-	40.06	13.31	64.96			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6565MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.7111G	55.15	83.54	-28.39	51.06	1	Vertical	210	2.68	-	37.70	15.19	48.80			
AV	19.713G	43.19	63.54	-20.35	39.10	1	Vertical	210	2.68	-	37.70	15.19	48.80			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6565MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.68815G	55.45	83.54	-28.09	51.36	1	Horizontal	27	1.56	-	37.70	15.19	48.80			
AV	19.71205G	42.29	63.54	-21.25	38.20	1	Horizontal	27	1.56	-	37.70	15.19	48.80			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6685MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-E-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	13.37656G	60.55	74.00	-13.45	71.14	3	Vertical	336.1	1.80	-	40.35	13.56	64.50			
AV	13.3696G	46.35	54.00	-7.65	56.95	3	Vertical	336.1	1.80	-	40.36	13.55	64.51			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6685MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.3756G	66.68	74.00	-7.32	77.27	3	Horizontal	325.7	1.79	-	40.35	13.56	64.50			
AV	13.37296G	52.36	54.00	-1.64	62.96	3	Horizontal	325.7	1.79	-	40.35	13.56	64.51			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6685MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.0747G	55.50	83.54	-28.04	51.26	1	Vertical	60	1.97	-	37.80	15.23	48.79			
AV	20.0691G	42.76	63.54	-20.78	38.52	1	Vertical	60	1.97	-	37.80	15.23	48.79			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6685MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.0755G	54.92	83.54	-28.62	50.67	1	Horizontal	47	2.48	-	37.80	15.23	48.78			
AV	20.0706G	42.78	63.54	-20.76	38.54	1	Horizontal	47	2.48	-	37.80	15.23	48.79			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6845MHz_TX




EUT_V_4TX
Setting 28
05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.69704G	66.37	88.20	-21.83	76.32	3	Vertical	336.4	1.93	-	40.50	13.89	64.34			
RMS	13.68872G	50.70	68.20	-17.50	60.65	3	Vertical	336.4	1.93	-	40.50	13.89	64.34			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6845MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.69264G	70.10	88.20	-18.10	80.05	3	Horizontal	326.5	1.80	-	40.50	13.89	64.34			
RMS	13.68944G	55.23	68.20	-12.97	65.18	3	Horizontal	326.5	1.80	-	40.50	13.89	64.34			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6845MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.52405G	54.30	83.54	-29.24	49.50	1	Vertical	102	1.11	-	37.90	15.60	48.70			
AV	20.5124G	43.98	63.54	-19.56	39.19	1	Vertical	102	1.11	-	37.90	15.59	48.70			

6.525-6.875GHz_802.11be EHT40-BF_Nss1,(MCS0)_4TX

6845MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.5148G	55.16	83.54	-28.38	50.37	1	Horizontal	0	2.23	-	37.90	15.59	48.70			
AV	20.51175G	41.98	63.54	-21.56	37.19	1	Horizontal	0	2.23	-	37.90	15.59	48.70			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	5.925G	80.52	88.20	-7.68	73.29	3	Vertical	183	1.61	-	34.30	8.51	35.58				
RMS	5.925G	67.07	68.20	-1.13	59.84	3	Vertical	183	1.61	-	34.30	8.51	35.58				
PK	5.9962G	116.18	Inf	-Inf	109.04	3	Vertical	183	1.61	-	34.21	8.54	35.61				
RMS	5.9678G	101.56	Inf	-Inf	94.37	3	Vertical	183	1.61	-	34.26	8.53	35.60				

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.921G	80.78	88.20	-7.42	73.56	3	Horizontal	183	1.46	-	34.30	8.50	35.58			
RMS	5.9246G	68.18	68.20	-0.02	60.95	3	Horizontal	183	1.46	-	34.30	8.51	35.58			
PK	6.0002G	115.71	Inf	-Inf	108.58	3	Horizontal	183	1.46	-	34.20	8.54	35.61			
RMS	6.0006G	105.10	Inf	-Inf	97.97	3	Horizontal	183	1.46	-	34.20	8.54	35.61			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-E-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	11.98864G	53.24	74.00	-20.76	68.09	3	Vertical	312.8	1.80	-	38.78	12.12	65.75				
AV	11.97832G	39.17	54.00	-14.83	54.04	3	Vertical	312.8	1.80	-	38.76	12.12	65.75				
PK	17.94652G	47.48	74.00	-26.52	52.40	3	Vertical	359	1.79	-	42.19	15.27	62.38				
AV	17.94676G	35.59	54.00	-18.41	40.51	3	Vertical	359	1.79	-	42.19	15.27	62.38				

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_Y_4TX
 Setting 26
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	11.98744G	55.55	74.00	-18.45	70.41	3	Horizontal	290.9	1.80	-	38.77	12.12	65.75				
AV	11.97064G	44.41	54.00	-9.59	59.32	3	Horizontal	290.9	1.80	-	38.74	12.11	65.76				
PK	17.94772G	48.29	74.00	-25.71	53.21	3	Horizontal	339	1.81	-	42.19	15.27	62.38				
AV	17.9438G	36.75	54.00	-17.25	41.69	3	Horizontal	339	1.81	-	42.18	15.27	62.39				

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_V_4TX
 Setting 26
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93932G	46.39	83.54	-37.15	37.70	1	Vertical	52	1.38	-	39.00	17.31	47.62			
AV	23.93979G	35.57	63.54	-27.97	26.88	1	Vertical	52	1.38	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

5985MHz_TX




EUT_V_4TX
 Setting 26
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93975G	48.53	83.54	-35.01	39.84	1	Horizontal	346	1.80	-	39.00	17.31	47.62			
AV	23.93979G	38.85	63.54	-24.69	30.16	1	Horizontal	346	1.80	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6225MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.46112G	63.41	74.00	-10.59	77.10	3	Vertical	28.6	1.76	-	39.02	12.61	65.32			
AV	12.45936G	50.32	54.00	-3.68	64.02	3	Vertical	28.6	1.76	-	39.02	12.61	65.33			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6225MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.46576G	61.18	74.00	-12.82	74.86	3	Horizontal	21.5	1.80	-	39.03	12.61	65.32			
AV	12.46624G	48.53	54.00	-5.47	62.21	3	Horizontal	21.5	1.80	-	39.03	12.61	65.32			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6225MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.68771G	54.97	83.54	-28.57	50.31	1	Vertical	28	1.61	-	37.90	15.25	48.49			
AV	18.68781G	42.13	63.54	-21.41	37.47	1	Vertical	28	1.61	-	37.90	15.25	48.49			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6225MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.67400G	43.92	83.54	-39.62	39.24	1	Horizontal	17	1.80	-	37.90	15.25	48.47			
AV	18.68484G	31.74	63.54	-31.80	27.07	1	Horizontal	17	1.80	-	37.90	15.25	48.48			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6385MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.76656G	62.40	88.20	-25.80	75.13	3	Vertical	26.7	1.77	-	39.60	12.93	65.26			
RMS	12.76912G	48.68	68.20	-19.52	61.40	3	Vertical	26.7	1.77	-	39.61	12.93	65.26			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6385MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.76488G	63.78	88.20	-24.42	76.52	3	Horizontal	19.7	1.80	-	39.59	12.93	65.26			
RMS	12.76768G	49.91	68.20	-18.29	62.63	3	Horizontal	19.7	1.80	-	39.61	12.93	65.26			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6385MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.14998G	38.95	83.54	-44.59	34.53	1	Vertical	26	1.78	-	38.00	15.22	48.80			
AV	19.14993G	27.10	63.54	-36.44	22.68	1	Vertical	26	1.78	-	38.00	15.22	48.80			

5.925-6.425GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6385MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.15940G	34.74	83.54	-48.80	30.36	1	Horizontal	80	1.80	-	37.96	15.22	48.80			
AV	19.15482G	23.71	63.54	-39.83	19.31	1	Horizontal	80	1.80	-	37.98	15.22	48.80			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6625MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.23488G	64.34	88.20	-23.86	75.70	3	Vertical	54	2.07	-	40.00	13.41	64.77			
RMS	13.24232G	48.47	68.20	-19.73	59.81	3	Vertical	54	2.07	-	40.00	13.42	64.76			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6625MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.23368G	64.10	88.20	-24.10	75.47	3	Horizontal	287	1.71	-	40.00	13.41	64.78			
RMS	13.24232G	49.50	68.20	-18.70	60.84	3	Horizontal	287	1.71	-	40.00	13.42	64.76			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6625MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.86180G	45.44	83.54	-38.10	41.36	1	Vertical	42	1.80	-	37.70	15.18	48.80			
AV	19.87935G	33.55	63.54	-29.99	29.47	1	Vertical	42	1.80	-	37.70	15.18	48.80			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6625MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.86210G	44.00	83.54	-39.54	39.92	1	Horizontal	322	1.73	-	37.70	15.18	48.80			
AV	19.86078G	32.27	63.54	-31.27	28.19	1	Horizontal	322	1.73	-	37.70	15.18	48.80			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6705MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.41848G	64.03	88.20	-24.17	74.43	3	Vertical	178	2.23	-	40.41	13.61	64.42			
RMS	13.41968G	50.88	68.20	-17.32	61.27	3	Vertical	178	2.23	-	40.42	13.61	64.42			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6705MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.42016G	64.79	88.20	-23.41	75.17	3	Horizontal	23	2.89	-	40.42	13.61	64.41			
RMS	13.42728G	50.91	68.20	-17.29	61.24	3	Horizontal	23	2.89	-	40.46	13.61	64.40			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6705MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.12830G	43.19	83.54	-40.35	38.89	1	Vertical	70	1.65	-	37.80	15.27	48.77			
AV	20.11941G	31.64	63.54	-31.90	27.35	1	Vertical	70	1.65	-	37.80	15.27	48.78			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6705MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.10730G	48.62	83.54	-34.92	44.34	1	Horizontal	26	1.66	-	37.80	15.26	48.78			
AV	20.1114G	36.66	63.54	-26.88	32.38	1	Horizontal	26	1.66	-	37.80	15.26	48.78			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6785MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.56504G	63.70	88.20	-24.50	73.39	3	Vertical	335.3	1.80	-	40.84	13.76	64.29			
RMS	13.57144G	49.94	68.20	-18.26	59.66	3	Vertical	335.3	1.80	-	40.81	13.76	64.29			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6785MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.56904G	68.30	88.20	-19.90	78.01	3	Horizontal	324.6	1.78	-	40.82	13.76	64.29			
RMS	13.56888G	54.36	68.20	-13.84	64.07	3	Horizontal	324.6	1.78	-	40.82	13.76	64.29			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6785MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.34710G	38.81	83.54	-44.73	34.20	1	Vertical	40	1.70	-	37.89	15.45	48.73			
AV	20.35479G	27.16	63.54	-36.38	22.54	1	Vertical	40	1.70	-	37.89	15.46	48.73			

6.525-6.875GHz_802.11be EHT80-BF_Nss1,(MCS0)_4TX

6785MHz_TX




EUT_V_4TX
 Setting 28
 05-L-V-1

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.34230G	44.11	83.54	-39.43	39.51	1	Horizontal	306	1.80	-	37.88	15.45	48.73			
AV	20.34903G	32.25	63.54	-31.29	27.63	1	Horizontal	306	1.80	-	37.90	15.45	48.73			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_Y_4TX
 Setting 27
 05-L-G-2-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.902G	75.18	88.20	-13.02	67.95	3	Vertical	190	1.51	-	34.30	8.50	35.57			
RMS	5.925G	64.06	68.20	-4.14	56.83	3	Vertical	190	1.51	-	34.30	8.51	35.58			
PK	6.097G	112.88	Inf	-Inf	105.51	3	Vertical	190	1.51	-	34.21	8.58	35.42			
RMS	6.0765G	97.74	Inf	-Inf	90.38	3	Vertical	190	1.51	-	34.25	8.57	35.46			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_Y_4TX
 Setting 27
 05-L-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.918G	78.21	88.20	-9.99	70.99	3	Horizontal	184	1.46	-	34.30	8.50	35.58			
RMS	5.9245G	68.17	68.20	-0.03	60.94	3	Horizontal	184	1.46	-	34.30	8.51	35.58			
PK	6.103G	116.45	Inf	-Inf	109.07	3	Horizontal	184	1.46	-	34.21	8.58	35.41			
RMS	6.103G	106.35	Inf	-Inf	98.97	3	Horizontal	184	1.46	-	34.21	8.58	35.41			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_V_4TX
 Setting 27
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.06872G	56.86	74.00	-17.14	71.40	3	Vertical	2.4	1.80	-	38.94	12.20	65.68			
AV	12.0568G	41.80	54.00	-12.20	56.39	3	Vertical	2.4	1.80	-	38.91	12.19	65.69			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_V_4TX
 Setting 27
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.06904G	55.95	74.00	-18.05	70.49	3	Horizontal	307.6	1.80	-	38.94	12.20	65.68			
AV	12.06904G	43.25	54.00	-10.75	57.79	3	Horizontal	307.6	1.80	-	38.94	12.20	65.68			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_V_4TX
 Setting 27
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.14745G	46.64	83.54	-36.90	42.08	1	Vertical	7	1.81	-	37.51	15.28	48.23			
AV	18.16425G	34.61	63.54	-28.93	30.03	1	Vertical	7	1.81	-	37.53	15.28	48.23			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6025MHz_TX




EUT_V_4TX
 Setting 27
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.1339G	47.89	83.54	-35.65	43.28	1	Horizontal	328	1.75	-	37.56	15.28	48.23			
AV	18.1301G	35.89	63.54	-27.65	31.26	1	Horizontal	328	1.75	-	37.58	15.28	48.23			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6185MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.3856G	58.32	74.00	-15.68	72.28	3	Vertical	21.5	1.80	-	38.90	12.53	65.39			
AV	12.36848G	44.74	54.00	-9.26	58.74	3	Vertical	21.5	1.80	-	38.90	12.51	65.41			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6185MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.38864G	61.91	74.00	-12.09	75.87	3	Horizontal	304.3	1.64	-	38.90	12.53	65.39			
AV	12.38824G	46.97	54.00	-7.03	60.93	3	Horizontal	304.3	1.64	-	38.90	12.53	65.39			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6185MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.53365G	45.35	83.54	-38.19	40.62	1	Vertical	305.9	1.80	-	37.80	15.26	48.33			
AV	18.57565G	34.73	63.54	-28.81	30.05	1	Vertical	305.9	1.80	-	37.80	15.26	48.38			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6185MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.6712G	46.91	83.54	-36.63	42.23	1	Horizontal	332.3	1.80	-	37.90	15.25	48.47			
AV	18.6131G	34.83	63.54	-28.71	30.16	1	Horizontal	332.3	1.80	-	37.83	15.25	48.41			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6345MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.6788G	62.51	74.00	-11.49	75.54	3	Vertical	28.1	1.74	-	39.40	12.84	65.27			
AV	12.67448G	49.08	54.00	-4.92	62.12	3	Vertical	28.1	1.74	-	39.40	12.83	65.27			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6345MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.68632G	64.49	74.00	-9.51	77.52	3	Horizontal	21.4	1.80	-	39.40	12.84	65.27			
AV	12.67392G	51.89	54.00	-2.11	64.93	3	Horizontal	21.4	1.80	-	39.40	12.83	65.27			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6345MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.1253G	47.24	83.54	-36.30	42.82	1	Vertical	2.5	1.81	-	38.00	15.22	48.80			
AV	19.09905G	36.34	63.54	-27.20	31.92	1	Vertical	2.5	1.81	-	38.00	15.22	48.80			

5.925-6.425GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6345MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.05285G	48.31	83.54	-35.23	43.97	1	Horizontal	6.6	1.65	-	37.91	15.23	48.80			
AV	19.04305G	37.03	63.54	-26.51	32.69	1	Horizontal	6.6	1.65	-	37.91	15.23	48.80			

6.525-6.875GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6665MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.33832G	58.34	74.00	-15.66	69.04	3	Vertical	14.2	1.80	-	40.35	13.52	64.57			
AV	13.3324G	46.28	54.00	-7.72	57.02	3	Vertical	14.2	1.80	-	40.33	13.52	64.59			

6.525-6.875GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6665MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	13.33448G	62.32	74.00	-11.68	73.04	3	Horizontal	324.1	1.80	-	40.34	13.52	64.58			
AV	13.3328G	50.10	54.00	-3.90	60.83	3	Horizontal	324.1	1.80	-	40.33	13.52	64.58			

6.525-6.875GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6665MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	19.99473G	44.42	83.54	-39.12	40.34	1	Vertical	89	2.90	-	37.71	15.17	48.80			
AV	19.98333G	32.24	63.54	-31.30	28.14	1	Vertical	89	2.90	-	37.73	15.17	48.80			

6.525-6.875GHz_802.11be EHT160-BF_Nss1,(MCS0)_4TX

6665MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	20.00802G	44.82	83.54	-38.72	40.72	1	Horizontal	253	2.84	-	37.72	15.18	48.80			
AV	19.98006G	32.14	63.54	-31.40	28.03	1	Horizontal	253	2.84	-	37.74	15.17	48.80			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_Y_4TX
 Setting 27
 05-L-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.921G	74.94	88.20	-13.26	67.72	3	Vertical	184	1.60	-	34.30	8.50	35.58			
RMS	5.923G	63.07	68.20	-5.13	55.84	3	Vertical	184	1.60	-	34.30	8.51	35.58			
PK	6.253G	111.49	Inf	-Inf	103.45	3	Vertical	184	1.60	-	34.50	8.65	35.11			
RMS	6.181G	97.51	Inf	-Inf	89.80	3	Vertical	184	1.60	-	34.36	8.61	35.26			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_Y_4TX
 Setting 27
 05-L-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.923G	78.49	88.20	-9.71	71.26	3	Horizontal	192	1.46	-	34.30	8.51	35.58			
RMS	5.925G	67.85	68.20	-0.35	60.62	3	Horizontal	192	1.46	-	34.30	8.51	35.58			
PK	6.113G	114.09	Inf	-Inf	106.66	3	Horizontal	192	1.46	-	34.23	8.59	35.39			
RMS	6.114G	103.99	Inf	-Inf	96.56	3	Horizontal	192	1.46	-	34.23	8.59	35.39			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_V_4TX
 Setting 27
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.22208G	55.25	74.00	-18.75	69.33	3	Vertical	336.2	1.80	-	39.10	12.36	65.54			
AV	12.20936G	40.55	54.00	-13.45	54.65	3	Vertical	336.2	1.80	-	39.10	12.35	65.55			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_V_4TX
 Setting 27
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.22744G	53.83	74.00	-20.17	67.90	3	Horizontal	312.2	1.80	-	39.10	12.37	65.54			
AV	12.20968G	40.99	54.00	-13.01	55.09	3	Horizontal	312.2	1.80	-	39.10	12.35	65.55			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_V_4TX
 Setting 27
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.32217G	43.34	83.54	-40.20	38.69	1	Vertical	212	2.74	-	37.64	15.27	48.26			
AV	18.32901G	31.30	63.54	-32.24	26.64	1	Vertical	212	2.74	-	37.66	15.27	48.27			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6105MHz_TX




EUT_V_4TX
 Setting 27
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.32403G	43.04	83.54	-40.50	38.38	1	Horizontal	222	1.25	-	37.65	15.27	48.26			
AV	18.32934G	31.42	63.54	-32.12	26.76	1	Horizontal	222	1.25	-	37.66	15.27	48.27			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6265MHz_TX




EUT_V_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.54376G	58.92	74.00	-15.08	72.40	3	Vertical	26.2	1.80	-	39.10	12.70	65.28			
AV	12.54608G	45.17	54.00	-8.83	58.65	3	Vertical	26.2	1.80	-	39.10	12.70	65.28			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6265MHz_TX




EUT_Y_4TX
 Setting 28
 05-L-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.54752G	63.21	74.00	-10.79	76.69	3	Horizontal	22.1	1.80	-	39.10	12.70	65.28			
AV	12.54864G	45.95	54.00	-8.05	59.43	3	Horizontal	22.1	1.80	-	39.10	12.70	65.28			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6265MHz_TX




EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.7809G	43.57	83.54	-39.97	39.01	1	Vertical	195	1.69	-	37.90	15.24	48.58			
AV	18.79788G	31.79	63.54	-31.75	27.25	1	Vertical	195	1.69	-	37.90	15.24	48.60			

5.925-6.425GHz_802.11be EHT320-BF_Nss1,(MCS0)_4TX

6265MHz_TX



EUT_V_4TX
 Setting 28
 05-L-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.79443G	44.35	83.54	-39.19	39.80	1	Horizontal	341	2.11	-	37.90	15.24	48.59			
AV	18.79353G	31.68	63.54	-31.86	27.13	1	Horizontal	341	2.11	-	37.90	15.24	48.59			



RSE TX above 1GHz_R4_Wide Beam_Multi-RU
(Parent Device / FCC ID: UDX-600216010)


Appendix E.12

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11be EHT320_Nss1,(MCS0)_4TX	Pass	RMS	5.9234G	68.05	68.20	-0.15	3	Vertical	351	1.68	-

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT_Y_1TX
Setting 20.5/10
02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9186G	81.07	88.20	-7.13	69.62	3	Vertical	27	1.54	-	34.20	7.88	30.63			
RMS	5.925G	67.13	68.20	-1.07	55.68	3	Vertical	27	1.54	-	34.20	7.88	30.63			
PK	6.0082G	112.84	Inf	-Inf	101.22	3	Vertical	27	1.54	-	34.30	7.94	30.62			
RMS	6.0226G	103.50	Inf	-Inf	91.86	3	Vertical	27	1.54	-	34.30	7.97	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT_Y_1TX
Setting 20.5/10
02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9234G	78.04	88.20	-10.16	66.59	3	Horizontal	331	1.54	-	34.20	7.88	30.63			
RMS	5.921G	64.94	68.20	-3.26	53.49	3	Horizontal	331	1.54	-	34.20	7.88	30.63			
PK	6.0146G	111.76	Inf	-Inf	100.14	3	Horizontal	331	1.54	-	34.30	7.95	30.63			
RMS	6.0218G	100.76	Inf	-Inf	89.13	3	Horizontal	331	1.54	-	34.30	7.96	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT Y_1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.9698G	49.29	74.00	-24.71	63.69	3	Vertical	31	1.79	-	39.30	12.06	65.76			
AV	11.97684G	37.28	54.00	-16.72	51.67	3	Vertical	31	1.79	-	39.30	12.07	65.76			
PK	17.96026G	55.36	74.00	-18.64	58.14	3	Vertical	45	1.39	-	46.78	12.80	62.36			
AV	17.96146G	43.51	54.00	-10.49	46.29	3	Vertical	45	1.39	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT_Y_1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.96962G	47.80	74.00	-26.20	62.20	3	Horizontal	63	2.20	-	39.30	12.06	65.76			
AV	11.97712G	36.00	54.00	-18.00	50.39	3	Horizontal	63	2.20	-	39.30	12.07	65.76			
PK	17.96008G	55.31	74.00	-18.69	58.09	3	Horizontal	148	1.54	-	46.78	12.80	62.36			
AV	17.95962G	43.37	54.00	-10.63	46.15	3	Horizontal	148	1.54	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT_V_1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93538G	50.01	83.54	-33.53	41.33	1	Vertical	133	1.50	-	39.00	17.31	47.63			
RMS	23.9411G	37.92	63.54	-25.62	29.23	1	Vertical	133	1.50	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_1TX

5985MHz_TX




EUT_V_1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	17.95799G	46.30	83.54	-37.24	41.52	1	Horizontal	226	1.15	-	37.61	15.26	48.09			
RMS	17.9545G	33.70	63.54	-29.84	28.92	1	Horizontal	226	1.15	-	37.60	15.26	48.08			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT_Y_1TX
Setting 16.5/12
02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9074G	69.66	88.20	-18.54	58.22	3	Vertical	29	1.56	-	34.20	7.87	30.63			
RMS	5.905G	57.52	68.20	-10.68	46.08	3	Vertical	29	1.56	-	34.20	7.87	30.63			
PK	6.0226G	113.83	Inf	-Inf	102.19	3	Vertical	29	1.56	-	34.30	7.97	30.63			
RMS	6.0226G	103.84	Inf	-Inf	92.20	3	Vertical	29	1.56	-	34.30	7.97	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT_Y_1TX
 Setting 16.5/12
 02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9178G	68.86	88.20	-19.34	57.41	3	Horizontal	15	1.69	-	34.20	7.88	30.63			
RMS	5.8994G	56.25	68.20	-11.95	44.82	3	Horizontal	15	1.69	-	34.20	7.86	30.63			
PK	6.021G	110.34	Inf	-Inf	98.71	3	Horizontal	15	1.69	-	34.30	7.96	30.63			
RMS	6.021G	99.82	Inf	-Inf	88.19	3	Horizontal	15	1.69	-	34.30	7.96	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT_Y_1TX
 Setting 16.5/12
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.97944G	47.64	74.00	-26.36	62.02	3	Vertical	102	1.92	-	39.30	12.07	65.75			
AV	11.97694G	36.11	54.00	-17.89	50.50	3	Vertical	102	1.92	-	39.30	12.07	65.76			
PK	17.95898G	55.46	74.00	-18.54	58.24	3	Vertical	179	1.51	-	46.78	12.80	62.36			
AV	17.96254G	43.32	54.00	-10.68	46.10	3	Vertical	179	1.51	-	46.77	12.80	62.35			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT Y_1TX
 Setting 16.5/12
 02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.96262G	47.46	74.00	-26.54	61.86	3	Horizontal	152	1.51	-	39.30	12.06	65.76			
AV	11.97668G	36.16	54.00	-17.84	50.55	3	Horizontal	152	1.51	-	39.30	12.07	65.76			
PK	17.94578G	55.06	74.00	-18.94	57.85	3	Horizontal	319	1.30	-	46.81	12.79	62.39			
AV	17.96054G	43.42	54.00	-10.58	46.20	3	Horizontal	319	1.30	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT_V_1TX
 Setting 16.5/12
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93875G	49.96	83.54	-33.58	41.27	1	Vertical	255	1.65	-	39.00	17.31	47.62			
RMS	23.93839G	37.93	63.54	-25.61	29.24	1	Vertical	255	1.65	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_1TX

5985MHz_TX




EUT_V_1TX
 Setting 16.5/12
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.94355G	49.57	83.54	-33.97	40.87	1	Horizontal	101	1.50	-	39.00	17.32	47.62			
RMS	23.94359G	37.92	63.54	-25.62	29.22	1	Horizontal	101	1.50	-	39.00	17.32	47.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 20.5/10
 02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9218G	74.99	88.20	-13.21	63.54	3	Vertical	27	1.58	-	34.20	7.88	30.63			
RMS	5.9242G	63.40	68.20	-4.80	51.95	3	Vertical	27	1.58	-	34.20	7.88	30.63			
PK	6.037G	111.45	Inf	-Inf	99.81	3	Vertical	27	1.58	-	34.30	7.99	30.65			
RMS	6.0586G	100.73	Inf	-Inf	89.05	3	Vertical	27	1.58	-	34.33	8.02	30.67			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 20.5/10
 02-R-E-3-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	5.9194G	74.17	88.20	-14.03	62.72	3	Horizontal	13	1.64	-	34.20	7.88	30.63
RMS	5.9242G	61.23	68.20	-6.97	49.78	3	Horizontal	13	1.64	-	34.20	7.88	30.63
PK	6.0778G	107.66	Inf	-Inf	95.89	3	Horizontal	13	1.64	-	34.41	8.05	30.69
RMS	6.0674G	97.61	Inf	-Inf	85.89	3	Horizontal	13	1.64	-	34.37	8.03	30.68

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05136G	47.53	74.00	-26.47	62.05	3	Vertical	10	2.18	-	39.10	12.07	65.69			
AV	12.04014G	35.96	54.00	-18.04	50.45	3	Vertical	10	2.18	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_V_1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04314G	48.07	74.00	-25.93	62.57	3	Horizontal	45	2.46	-	39.13	12.07	65.70			
AV	12.0408G	35.89	54.00	-18.11	50.38	3	Horizontal	45	2.46	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_V_1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07839G	45.76	83.54	-37.78	41.12	1	Vertical	222	2.71	-	37.57	15.29	48.22			
RMS	18.07959G	34.10	63.54	-29.44	29.45	1	Vertical	222	2.71	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_1TX

6025MHz_TX




EUT_V_1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07938G	46.16	83.54	-37.38	41.51	1	Horizontal	44	2.12	-	37.58	15.29	48.22			
RMS	18.07535G	34.19	63.54	-29.35	29.57	1	Horizontal	44	2.12	-	37.55	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
Setting 18.5/11
02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9242G	82.79	88.20	-5.41	71.34	3	Vertical	26	1.52	-	34.20	7.88	30.63			
RMS	5.925G	66.61	68.20	-1.59	55.16	3	Vertical	26	1.52	-	34.20	7.88	30.63			
PK	6.0898G	112.63	Inf	-Inf	100.81	3	Vertical	26	1.52	-	34.46	8.07	30.71			
RMS	6.0978G	102.07	Inf	-Inf	90.21	3	Vertical	26	1.52	-	34.49	8.08	30.71			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 18.5/11
 02-R-E-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.913G	72.31	88.20	-15.89	60.87	3	Horizontal	11	1.67	-	34.20	7.87	30.63			
RMS	5.925G	60.33	68.20	-7.87	48.88	3	Horizontal	11	1.67	-	34.20	7.88	30.63			
PK	6.1026G	108.35	Inf	-Inf	96.47	3	Horizontal	11	1.67	-	34.51	8.09	30.72			
RMS	6.1018G	98.00	Inf	-Inf	86.13	3	Horizontal	11	1.67	-	34.50	8.09	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 18.5/11
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0497G	47.68	74.00	-26.32	62.21	3	Vertical	59	1.38	-	39.10	12.07	65.70			
AV	12.04072G	35.54	54.00	-18.46	50.03	3	Vertical	59	1.38	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 18.5/11
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04678G	47.69	74.00	-26.31	62.21	3	Horizontal	239	2.60	-	39.11	12.07	65.70			
AV	12.04046G	35.65	54.00	-18.35	50.14	3	Horizontal	239	2.60	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 18.5/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07634G	46.09	83.54	-37.45	41.46	1	Vertical	140	1.10	-	37.56	15.29	48.22			
RMS	18.07962G	33.91	63.54	-29.63	29.26	1	Vertical	140	1.10	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 18.5/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07268G	46.29	83.54	-37.25	41.67	1	Horizontal	110	1.01	-	37.54	15.29	48.21			
RMS	18.07643G	34.03	63.54	-29.51	29.40	1	Horizontal	110	1.01	-	37.56	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 16/12.5
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9215G	68.66	88.20	-19.54	57.21	3	Vertical	26	1.53	-	34.20	7.88	30.63			
RMS	5.925G	56.44	68.20	-11.76	44.99	3	Vertical	26	1.53	-	34.20	7.88	30.63			
PK	6.09G	111.50	Inf	-Inf	99.68	3	Vertical	26	1.53	-	34.46	8.07	30.71			
RMS	6.1005G	101.04	Inf	-Inf	89.17	3	Vertical	26	1.53	-	34.50	8.09	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
Setting 16/12.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.911G	66.01	88.20	-22.19	54.57	3	Horizontal	14	1.63	-	34.20	7.87	30.63			
RMS	5.9235G	55.89	68.20	-12.31	44.44	3	Horizontal	14	1.63	-	34.20	7.88	30.63			
PK	6.071G	108.95	Inf	-Inf	97.22	3	Horizontal	14	1.63	-	34.38	8.04	30.69			
RMS	6.0995G	98.22	Inf	-Inf	86.36	3	Horizontal	14	1.63	-	34.50	8.08	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 16/12.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04152G	47.59	74.00	-26.41	62.09	3	Vertical	249	1.79	-	39.13	12.07	65.70			
AV	12.0407G	35.89	54.00	-18.11	50.38	3	Vertical	249	1.79	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 16/12.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05296G	48.03	74.00	-25.97	62.56	3	Horizontal	49	2.15	-	39.09	12.07	65.69			
AV	12.04374G	35.79	54.00	-18.21	50.29	3	Horizontal	49	2.15	-	39.13	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 16/12.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07587G	46.17	83.54	-37.37	41.54	1	Vertical	42	1.70	-	37.56	15.29	48.22			
RMS	18.07521G	34.19	63.54	-29.35	29.57	1	Vertical	42	1.70	-	37.55	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_1TX

6025MHz_TX




EUT Y 1TX
 Setting 16/12.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07579G	46.34	83.54	-37.20	41.72	1	Horizontal	105	2.54	-	37.55	15.29	48.22			
RMS	18.07748G	34.23	63.54	-29.31	29.60	1	Horizontal	105	2.54	-	37.56	15.29	48.22			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
 Setting 20.5/10
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9226G	79.35	88.20	-8.85	67.90	3	Vertical	29	1.59	-	34.20	7.88	30.63			
RMS	5.9242G	64.34	68.20	-3.86	52.89	3	Vertical	29	1.59	-	34.20	7.88	30.63			
PK	6.097G	108.04	Inf	-Inf	96.18	3	Vertical	29	1.59	-	34.49	8.08	30.71			
RMS	6.0546G	97.75	Inf	-Inf	86.09	3	Vertical	29	1.59	-	34.32	8.01	30.67			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
Setting 20.5/10
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9226G	76.34	88.20	-11.86	64.89	3	Horizontal	13	1.80	-	34.20	7.88	30.63			
RMS	5.9242G	60.96	68.20	-7.24	49.51	3	Horizontal	13	1.80	-	34.20	7.88	30.63			
PK	6.0826G	105.92	Inf	-Inf	94.13	3	Horizontal	13	1.80	-	34.43	8.06	30.70			
RMS	6.121G	95.53	Inf	-Inf	83.61	3	Horizontal	13	1.80	-	34.54	8.12	30.74			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.2001G	47.03	74.00	-26.97	61.64	3	Vertical	126	1.70	-	38.90	12.05	65.56			
AV	12.20634G	35.51	54.00	-18.49	50.12	3	Vertical	126	1.70	-	38.89	12.05	65.55			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
 Setting 20.5/10
 02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	12.21646G	47.13	74.00	-26.87	61.76	3	Horizontal	347	2.37	-	38.87	12.05	65.55			
AV	12.20228G	35.73	54.00	-18.27	50.34	3	Horizontal	347	2.37	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31582G	46.18	83.54	-37.36	41.54	1	Vertical	290	1.93	-	37.63	15.27	48.26			
RMS	18.31522G	34.93	63.54	-28.61	30.29	1	Vertical	290	1.93	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_1TX

6105MHz_TX




EUT Y 1TX
 Setting 20.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31164G	46.68	83.54	-36.86	42.05	1	Horizontal	196	2.87	-	37.62	15.27	48.26			
RMS	18.31084G	34.77	63.54	-28.77	30.14	1	Horizontal	196	2.87	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y 1TX
Setting 19.5/10
02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9202G	72.99	88.20	-15.21	61.54	3	Vertical	27	1.57	-	34.20	7.88	30.63			
RMS	5.9242G	60.22	68.20	-7.98	48.77	3	Vertical	27	1.57	-	34.20	7.88	30.63			
PK	6.0946G	108.16	Inf	-Inf	96.31	3	Vertical	27	1.57	-	34.48	8.08	30.71			
RMS	6.053G	97.86	Inf	-Inf	86.21	3	Vertical	27	1.57	-	34.31	8.01	30.67			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y ITX
Setting 19.5/10
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9226G	69.81	88.20	-18.39	58.36	3	Horizontal	12	1.68	-	34.20	7.88	30.63			
RMS	5.9242G	58.47	68.20	-9.73	47.02	3	Horizontal	12	1.68	-	34.20	7.88	30.63			
PK	6.081G	105.82	Inf	-Inf	94.04	3	Horizontal	12	1.68	-	34.42	8.06	30.70			
RMS	6.0994G	95.06	Inf	-Inf	83.20	3	Horizontal	12	1.68	-	34.50	8.08	30.72			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y 1TX
 Setting 19.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20636G	46.61	74.00	-27.39	61.22	3	Vertical	181	2.62	-	38.89	12.05	65.55			
AV	12.20016G	35.21	54.00	-18.79	49.82	3	Vertical	181	2.62	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y 1TX
 Setting 19.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20694G	47.39	74.00	-26.61	62.00	3	Horizontal	218	1.58	-	38.89	12.05	65.55			
AV	12.20528G	35.25	54.00	-18.75	49.87	3	Horizontal	218	1.58	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y 1TX
 Setting 19.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31404G	46.59	83.54	-36.95	41.95	1	Vertical	53	1.38	-	37.63	15.27	48.26			
RMS	18.31443G	34.58	63.54	-28.96	29.94	1	Vertical	53	1.38	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_1TX

6105MHz_TX




EUT Y 1TX
 Setting 19.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3121G	46.59	83.54	-36.95	41.96	1	Horizontal	99	2.35	-	37.62	15.27	48.26			
RMS	18.31054G	34.59	63.54	-28.95	29.96	1	Horizontal	99	2.35	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
Setting 18.5/10
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9234G	68.07	88.20	-20.13	56.62	3	Vertical	33	1.64	-	34.20	7.88	30.63			
RMS	5.925G	56.01	68.20	-12.19	44.56	3	Vertical	33	1.64	-	34.20	7.88	30.63			
PK	6.221G	108.73	Inf	-Inf	96.71	3	Vertical	33	1.64	-	34.60	8.26	30.84			
RMS	6.2106G	97.89	Inf	-Inf	85.87	3	Vertical	33	1.64	-	34.60	8.25	30.83			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
Setting 18.5/10
02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	5.9242G	66.33	88.20	-21.87	54.88	3	Horizontal	335	1.64	-	34.20	7.88	30.63
RMS	5.9194G	55.37	68.20	-12.83	43.92	3	Horizontal	335	1.64	-	34.20	7.88	30.63
PK	6.2578G	107.04	Inf	-Inf	95.04	3	Horizontal	335	1.64	-	34.58	8.30	30.88
RMS	6.2098G	95.66	Inf	-Inf	83.64	3	Horizontal	335	1.64	-	34.60	8.25	30.83

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
 Setting 18.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.2015G	47.94	74.00	-26.06	62.55	3	Vertical	248	2.16	-	38.90	12.05	65.56			
AV	12.20334G	35.01	54.00	-18.99	49.63	3	Vertical	248	2.16	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
 Setting 18.5/10
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21714G	47.12	74.00	-26.88	61.74	3	Horizontal	334	2.31	-	38.87	12.05	65.54			
AV	12.20674G	35.06	54.00	-18.94	49.67	3	Horizontal	334	2.31	-	38.89	12.05	65.55			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
 Setting 18.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31158G	47.11	83.54	-36.43	42.48	1	Vertical	114	2.68	-	37.62	15.27	48.26			
RMS	18.31345G	34.40	63.54	-29.14	29.76	1	Vertical	114	2.68	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_1TX

6105MHz_TX




EUT Y 1TX
 Setting 18.5/10
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3194G	46.66	83.54	-36.88	42.01	1	Horizontal	165	1.07	-	37.64	15.27	48.26			
RMS	18.31195G	34.40	63.54	-29.14	29.77	1	Horizontal	165	1.07	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
 Setting 21/11
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9238G	72.42	88.20	-15.78	60.97	3	Vertical	27	1.66	-	34.20	7.88	30.63			
RMS	5.9234G	59.74	68.20	-8.46	48.29	3	Vertical	27	1.66	-	34.20	7.88	30.63			
PK	6.0178G	116.34	Inf	-Inf	104.71	3	Vertical	27	1.66	-	34.30	7.96	30.63			
RMS	6.0178G	106.25	Inf	-Inf	94.62	3	Vertical	27	1.66	-	34.30	7.96	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
 Setting 21/11
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9142G	71.45	88.20	-16.75	60.01	3	Horizontal	14	1.46	-	34.20	7.87	30.63			
RMS	5.9134G	57.87	68.20	-10.33	46.43	3	Horizontal	14	1.46	-	34.20	7.87	30.63			
PK	6.0094G	115.92	Inf	-Inf	104.30	3	Horizontal	14	1.46	-	34.30	7.94	30.62			
RMS	6.0086G	105.53	Inf	-Inf	93.91	3	Horizontal	14	1.46	-	34.30	7.94	30.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
 Setting 21/11
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.96174G	48.90	74.00	-25.10	63.31	3	Vertical	10	1.57	-	39.30	12.06	65.77			
AV	11.97708G	36.38	54.00	-17.62	50.77	3	Vertical	10	1.57	-	39.30	12.07	65.76			
PK	17.95986G	55.69	74.00	-18.31	58.47	3	Vertical	339	2.83	-	46.78	12.80	62.36			
AV	17.95858G	43.43	54.00	-10.57	46.21	3	Vertical	339	2.83	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
Setting 21/11
02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.9675G	48.80	74.00	-25.20	63.20	3	Horizontal	205	2.71	-	39.30	12.06	65.76			
AV	11.96988G	36.39	54.00	-17.61	50.79	3	Horizontal	205	2.71	-	39.30	12.06	65.76			
PK	17.95946G	55.68	74.00	-18.32	58.46	3	Horizontal	58	2.02	-	46.78	12.80	62.36			
AV	17.96378G	43.32	54.00	-10.68	46.10	3	Horizontal	58	2.02	-	46.77	12.80	62.35			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
 Setting 21/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93603G	49.82	83.54	-33.72	41.14	1	Vertical	205	2.11	-	39.00	17.31	47.63			
RMS	23.93518G	37.73	63.54	-25.81	29.05	1	Vertical	205	2.11	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_2TX

5985MHz_TX




EUT Y 2TX
 Setting 21/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.94083G	50.15	83.54	-33.39	41.46	1	Horizontal	185	1.34	-	39.00	17.31	47.62			
RMS	23.93536G	37.73	63.54	-25.81	29.05	1	Horizontal	185	1.34	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
Setting 18.5/13.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9006G	69.27	88.20	-18.93	57.83	3	Vertical	28	1.67	-	34.20	7.87	30.63			
RMS	5.9034G	56.19	68.20	-12.01	44.75	3	Vertical	28	1.67	-	34.20	7.87	30.63			
PK	6.019G	117.00	Inf	-Inf	105.37	3	Vertical	28	1.67	-	34.30	7.96	30.63			
RMS	6.0182G	106.41	Inf	-Inf	94.78	3	Vertical	28	1.67	-	34.30	7.96	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
Setting 18.5/13.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9118G	70.91	88.20	-17.29	59.47	3	Horizontal	14	1.43	-	34.20	7.87	30.63			
RMS	5.911G	55.76	68.20	-12.44	44.32	3	Horizontal	14	1.43	-	34.20	7.87	30.63			
PK	6.0094G	115.79	Inf	-Inf	104.17	3	Horizontal	14	1.43	-	34.30	7.94	30.62			
RMS	6.0082G	105.29	Inf	-Inf	93.67	3	Horizontal	14	1.43	-	34.30	7.94	30.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
 Setting 18.5/13.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.9745G	47.37	74.00	-26.63	61.77	3	Vertical	143	1.17	-	39.30	12.06	65.76			
AV	11.97708G	35.82	54.00	-18.18	50.21	3	Vertical	143	1.17	-	39.30	12.07	65.76			
PK	17.96096G	55.59	74.00	-18.41	58.37	3	Vertical	95	1.72	-	46.78	12.80	62.36			
AV	17.963G	43.44	54.00	-10.56	46.22	3	Vertical	95	1.72	-	46.77	12.80	62.35			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
 Setting 18.5/13.5
 02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.97882G	47.75	74.00	-26.25	62.13	3	Horizontal	44	1.67	-	39.30	12.07	65.75			
AV	11.9795G	35.69	54.00	-18.31	50.07	3	Horizontal	44	1.67	-	39.30	12.07	65.75			
PK	17.9606G	55.04	74.00	-18.96	57.82	3	Horizontal	200	2.52	-	46.78	12.80	62.36			
AV	17.96052G	43.50	54.00	-10.50	46.28	3	Horizontal	200	2.52	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
 Setting 18.5/13.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93996G	49.67	83.54	-33.87	40.98	1	Vertical	322	1.81	-	39.00	17.31	47.62			
RMS	23.93815G	37.93	63.54	-25.61	29.24	1	Vertical	322	1.81	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_2TX

5985MHz_TX




EUT Y 2TX
 Setting 18.5/13.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.9436G	50.28	83.54	-33.26	41.58	1	Horizontal	255	1.50	-	39.00	17.32	47.62			
RMS	23.93915G	37.93	63.54	-25.61	29.24	1	Horizontal	255	1.50	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
 Setting 22.5/9.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.92G	76.49	88.20	-11.71	65.04	3	Vertical	26	1.55	-	34.20	7.88	30.63			
RMS	5.9215G	61.88	68.20	-6.32	50.43	3	Vertical	26	1.55	-	34.20	7.88	30.63			
PK	6.099G	114.48	Inf	-Inf	102.61	3	Vertical	26	1.55	-	34.50	8.08	30.71			
RMS	6.097G	104.93	Inf	-Inf	93.07	3	Vertical	26	1.55	-	34.49	8.08	30.71			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
Setting 22.5/9.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.906G	75.70	88.20	-12.50	64.26	3	Horizontal	336	1.65	-	34.20	7.87	30.63			
RMS	5.925G	60.17	68.20	-8.03	48.72	3	Horizontal	336	1.65	-	34.20	7.88	30.63			
PK	6.049G	114.41	Inf	-Inf	102.76	3	Horizontal	336	1.65	-	34.30	8.01	30.66			
RMS	6.068G	103.77	Inf	-Inf	92.04	3	Horizontal	336	1.65	-	34.37	8.04	30.68			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
 Setting 22.5/9.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04864G	47.43	74.00	-26.57	61.95	3	Vertical	302	2.62	-	39.11	12.07	65.70			
AV	12.04026G	35.62	54.00	-18.38	50.11	3	Vertical	302	2.62	-	39.14	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
 Setting 22.5/9.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0555G	47.05	74.00	-26.95	61.58	3	Horizontal	24	1.00	-	39.09	12.07	65.69			
AV	12.04746G	35.59	54.00	-18.41	50.11	3	Horizontal	24	1.00	-	39.11	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
 Setting 22.5/9.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07245G	45.64	83.54	-37.90	41.03	1	Vertical	27	1.25	-	37.53	15.29	48.21			
RMS	18.07957G	34.10	63.54	-29.44	29.45	1	Vertical	27	1.25	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_2TX

6025MHz_TX




EUT Y 2TX
 Setting 22.5/9.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07138G	45.90	83.54	-37.64	41.29	1	Horizontal	54	2.14	-	37.53	15.29	48.21			
RMS	18.07884G	34.26	63.54	-29.28	29.62	1	Horizontal	54	2.14	-	37.57	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
Setting 20/11
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9205G	74.69	88.20	-13.51	63.24	3	Vertical	25	1.54	-	34.20	7.88	30.63			
RMS	5.9225G	60.40	68.20	-7.80	48.95	3	Vertical	25	1.54	-	34.20	7.88	30.63			
PK	6.0965G	114.20	Inf	-Inf	102.34	3	Vertical	25	1.54	-	34.49	8.08	30.71			
RMS	6.097G	104.88	Inf	-Inf	93.02	3	Vertical	25	1.54	-	34.49	8.08	30.71			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 20/11
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.912G	74.77	88.20	-13.43	63.33	3	Horizontal	336	1.65	-	34.20	7.87	30.63			
RMS	5.911G	58.91	68.20	-9.29	47.47	3	Horizontal	336	1.65	-	34.20	7.87	30.63			
PK	6.087G	114.10	Inf	-Inf	102.29	3	Horizontal	336	1.65	-	34.45	8.06	30.70			
RMS	6.0295G	103.42	Inf	-Inf	91.78	3	Horizontal	336	1.65	-	34.30	7.98	30.64			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 20/11
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04974G	49.45	74.00	-24.55	63.98	3	Vertical	346	1.78	-	39.10	12.07	65.70			
AV	12.0499G	40.65	54.00	-13.35	55.18	3	Vertical	346	1.78	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 20/11
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0598G	48.64	74.00	-25.36	63.18	3	Horizontal	276	2.84	-	39.08	12.07	65.69			
AV	12.0499G	35.99	54.00	-18.01	50.52	3	Horizontal	276	2.84	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 20/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07206G	46.14	83.54	-37.40	41.53	1	Vertical	231	1.09	-	37.53	15.29	48.21			
RMS	18.07966G	33.91	63.54	-29.63	29.26	1	Vertical	231	1.09	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 20/11
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07403G	46.18	83.54	-37.36	41.56	1	Horizontal	317	1.13	-	37.54	15.29	48.21			
RMS	18.07986G	33.91	63.54	-29.63	29.26	1	Horizontal	317	1.13	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
Setting 18.5/11.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9195G	68.99	88.20	-19.21	57.54	3	Vertical	24	1.55	-	34.20	7.88	30.63			
RMS	5.923G	56.80	68.20	-11.40	45.35	3	Vertical	24	1.55	-	34.20	7.88	30.63			
PK	6.098G	114.40	Inf	-Inf	102.54	3	Vertical	24	1.55	-	34.49	8.08	30.71			
RMS	6.096G	104.39	Inf	-Inf	92.54	3	Vertical	24	1.55	-	34.48	8.08	30.71			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
Setting 18.5/11.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9245G	67.45	88.20	-20.75	56.00	3	Horizontal	336	1.68	-	34.20	7.88	30.63			
RMS	5.925G	56.38	68.20	-11.82	44.93	3	Horizontal	336	1.68	-	34.20	7.88	30.63			
PK	6.0875G	114.01	Inf	-Inf	102.19	3	Horizontal	336	1.68	-	34.45	8.07	30.70			
RMS	6.088G	104.58	Inf	-Inf	92.76	3	Horizontal	336	1.68	-	34.45	8.07	30.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 18.5/11.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05024G	47.77	74.00	-26.23	62.29	3	Vertical	24	1.74	-	39.10	12.07	65.69			
AV	12.04982G	36.44	54.00	-17.56	50.97	3	Vertical	24	1.74	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 18.5/11.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05138G	47.45	74.00	-26.55	61.97	3	Horizontal	159	1.99	-	39.10	12.07	65.69			
AV	12.04988G	36.44	54.00	-17.56	50.97	3	Horizontal	159	1.99	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 18.5/11.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07737G	45.97	83.54	-37.57	41.34	1	Vertical	136	2.90	-	37.56	15.29	48.22			
RMS	18.07539G	34.37	63.54	-29.17	29.75	1	Vertical	136	2.90	-	37.55	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_2TX

6025MHz_TX




EUT Y 2TX
 Setting 18.5/11.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07739G	46.06	83.54	-37.48	41.43	1	Horizontal	27	2.90	-	37.56	15.29	48.22			
RMS	18.07979G	34.29	63.54	-29.25	29.64	1	Horizontal	27	2.90	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
Setting 23/9
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9234G	80.16	88.20	-8.04	68.71	3	Vertical	25	1.52	-	34.20	7.88	30.63			
RMS	5.921G	63.56	68.20	-4.64	52.11	3	Vertical	25	1.52	-	34.20	7.88	30.63			
PK	6.1178G	112.84	Inf	-Inf	100.92	3	Vertical	25	1.52	-	34.54	8.11	30.73			
RMS	6.1378G	103.09	Inf	-Inf	91.13	3	Vertical	25	1.52	-	34.58	8.14	30.76			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/9
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9202G	78.82	88.20	-9.38	67.37	3	Horizontal	336	1.53	-	34.20	7.88	30.63			
RMS	5.9114G	62.24	68.20	-5.96	50.80	3	Horizontal	336	1.53	-	34.20	7.87	30.63			
PK	6.1474G	112.46	Inf	-Inf	100.48	3	Horizontal	336	1.53	-	34.59	8.16	30.77			
RMS	6.1266G	102.73	Inf	-Inf	90.79	3	Horizontal	336	1.53	-	34.55	8.13	30.74			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/9
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21622G	47.00	74.00	-27.00	61.63	3	Vertical	47	2.46	-	38.87	12.05	65.55			
AV	12.2011G	35.56	54.00	-18.44	50.17	3	Vertical	47	2.46	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/9
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20354G	47.38	74.00	-26.62	62.00	3	Horizontal	258	2.15	-	38.89	12.05	65.56			
AV	12.20224G	35.57	54.00	-18.43	50.18	3	Horizontal	258	2.15	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/9
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3158G	47.54	83.54	-36.00	42.90	1	Vertical	57	2.23	-	37.63	15.27	48.26			
RMS	18.31255G	34.77	63.54	-28.77	30.13	1	Vertical	57	2.23	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/9
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3101G	47.20	83.54	-36.34	42.57	1	Horizontal	285	1.79	-	37.62	15.27	48.26			
RMS	18.31722G	34.92	63.54	-28.62	30.28	1	Horizontal	285	1.79	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9242G	77.87	88.20	-10.33	66.42	3	Vertical	25	1.58	-	34.20	7.88	30.63			
RMS	5.9226G	64.17	68.20	-4.03	52.72	3	Vertical	25	1.58	-	34.20	7.88	30.63			
PK	6.0778G	113.39	Inf	-Inf	101.62	3	Vertical	25	1.58	-	34.41	8.05	30.69			
RMS	6.097G	103.17	Inf	-Inf	91.31	3	Vertical	25	1.58	-	34.49	8.08	30.71			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9106G	76.71	88.20	-11.49	65.27	3	Horizontal	334	1.54	-	34.20	7.87	30.63			
RMS	5.9122G	61.87	68.20	-6.33	50.43	3	Horizontal	334	1.54	-	34.20	7.87	30.63			
PK	6.1474G	112.48	Inf	-Inf	100.50	3	Horizontal	334	1.54	-	34.59	8.16	30.77			
RMS	6.1474G	102.47	Inf	-Inf	90.49	3	Horizontal	334	1.54	-	34.59	8.16	30.77			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21246G	46.78	74.00	-27.22	61.40	3	Vertical	47	1.26	-	38.88	12.05	65.55			
AV	12.20634G	35.23	54.00	-18.77	49.84	3	Vertical	47	1.26	-	38.89	12.05	65.55			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21096G	47.00	74.00	-27.00	61.62	3	Horizontal	45	1.47	-	38.88	12.05	65.55			
AV	12.20492G	35.17	54.00	-18.83	49.79	3	Horizontal	45	1.47	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31964G	46.21	83.54	-37.33	41.56	1	Vertical	67	1.84	-	37.64	15.27	48.26			
RMS	18.31021G	34.59	63.54	-28.95	29.96	1	Vertical	67	1.84	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_2TX

6105MHz_TX




EUT Y 2TX
 Setting 23/8
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31357G	47.70	83.54	-35.84	43.06	1	Horizontal	16	2.03	-	37.63	15.27	48.26			
RMS	18.31113G	34.59	63.54	-28.95	29.96	1	Horizontal	16	2.03	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9234G	73.13	88.20	-15.07	61.68	3	Vertical	34	1.51	-	34.20	7.88	30.63			
RMS	5.921G	56.69	68.20	-11.51	45.24	3	Vertical	34	1.51	-	34.20	7.88	30.63			
PK	6.2554G	114.18	Inf	-Inf	102.17	3	Vertical	34	1.51	-	34.59	8.30	30.88			
RMS	6.2362G	102.70	Inf	-Inf	90.68	3	Vertical	34	1.51	-	34.60	8.28	30.86			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.921G	70.10	88.20	-18.10	58.65	3	Horizontal	336	1.58	-	34.20	7.88	30.63			
RMS	5.925G	56.08	68.20	-12.12	44.63	3	Horizontal	336	1.58	-	34.20	7.88	30.63			
PK	6.2234G	112.67	Inf	-Inf	100.66	3	Horizontal	336	1.58	-	34.60	8.26	30.85			
RMS	6.2466G	102.62	Inf	-Inf	90.60	3	Horizontal	336	1.58	-	34.60	8.29	30.87			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20434G	47.73	74.00	-26.27	62.35	3	Vertical	321	1.78	-	38.89	12.05	65.56			
AV	12.20424G	34.92	54.00	-19.08	49.54	3	Vertical	321	1.78	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20408G	47.14	74.00	-26.86	61.76	3	Horizontal	135	2.33	-	38.89	12.05	65.56			
AV	12.20274G	34.95	54.00	-19.05	49.57	3	Horizontal	135	2.33	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31115G	46.38	83.54	-37.16	41.75	1	Vertical	125	1.19	-	37.62	15.27	48.26			
RMS	18.31279G	34.41	63.54	-29.13	29.77	1	Vertical	125	1.19	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_2TX

6105MHz_TX




EUT Y 2TX
 Setting 21.5/8.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31891G	46.92	83.54	-36.62	42.27	1	Horizontal	330	1.74	-	37.64	15.27	48.26			
RMS	18.31048G	34.41	63.54	-29.13	29.78	1	Horizontal	330	1.74	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
Setting 23.5/5.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9242G	73.24	88.20	-14.96	61.79	3	Vertical	344	1.50	-	34.20	7.88	30.63			
RMS	5.925G	61.19	68.20	-7.01	49.74	3	Vertical	344	1.50	-	34.20	7.88	30.63			
PK	6.013G	120.23	Inf	-Inf	108.60	3	Vertical	344	1.50	-	34.30	7.95	30.62			
RMS	6.0134G	109.21	Inf	-Inf	97.58	3	Vertical	344	1.50	-	34.30	7.95	30.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
Setting 23.5/5.5
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9162G	73.31	88.20	-14.89	61.86	3	Horizontal	338	1.56	-	34.20	7.88	30.63			
RMS	5.9158G	60.97	68.20	-7.23	49.52	3	Horizontal	338	1.56	-	34.20	7.88	30.63			
PK	6.0234G	118.53	Inf	-Inf	106.89	3	Horizontal	338	1.56	-	34.30	7.97	30.63			
RMS	6.0226G	108.66	Inf	-Inf	97.02	3	Horizontal	338	1.56	-	34.30	7.97	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.97956G	47.47	74.00	-26.53	61.85	3	Vertical	192	2.56	-	39.30	12.07	65.75			
AV	11.97918G	35.56	54.00	-18.44	49.94	3	Vertical	192	2.56	-	39.30	12.07	65.75			
PK	17.95336G	55.26	74.00	-18.74	58.04	3	Vertical	212	1.66	-	46.79	12.80	62.37			
AV	17.95902G	43.38	54.00	-10.62	46.16	3	Vertical	212	1.66	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
Setting 23.5/5.5
02-R-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.96734G	47.39	74.00	-26.61	61.79	3	Horizontal	313	1.16	-	39.30	12.06	65.76			
AV	11.97916G	35.72	54.00	-18.28	50.10	3	Horizontal	313	1.16	-	39.30	12.07	65.75			
PK	17.9628G	55.22	74.00	-18.78	58.00	3	Horizontal	80	1.87	-	46.77	12.80	62.35			
AV	17.95956G	43.21	54.00	-10.79	45.99	3	Horizontal	80	1.87	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93789G	50.06	83.54	-33.48	41.37	1	Vertical	331	1.87	-	39.00	17.31	47.62			
RMS	23.93752G	37.94	63.54	-25.60	29.25	1	Vertical	331	1.87	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 MRU 3_4TX

5985MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.9422G	50.19	83.54	-33.35	41.50	1	Horizontal	211	1.63	-	39.00	17.31	47.62			
RMS	23.93879G	37.93	63.54	-25.61	29.24	1	Horizontal	211	1.63	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9062G	73.70	88.20	-14.50	62.26	3	Vertical	345	1.69	-	34.20	7.87	30.63			
RMS	5.9066G	57.72	68.20	-10.48	46.28	3	Vertical	345	1.69	-	34.20	7.87	30.63			
PK	6.0126G	118.79	Inf	-Inf	107.16	3	Vertical	345	1.69	-	34.30	7.95	30.62			
RMS	6.0142G	109.52	Inf	-Inf	97.90	3	Vertical	345	1.69	-	34.30	7.95	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.8958G	71.51	88.20	-16.69	60.11	3	Horizontal	25	1.59	-	34.18	7.86	30.64			
RMS	5.895G	56.91	68.20	-11.29	45.51	3	Horizontal	25	1.59	-	34.18	7.86	30.64			
PK	6.0226G	117.31	Inf	-Inf	105.67	3	Horizontal	25	1.59	-	34.30	7.97	30.63			
RMS	6.0222G	108.48	Inf	-Inf	96.85	3	Horizontal	25	1.59	-	34.30	7.96	30.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.9767G	47.64	74.00	-26.36	62.03	3	Vertical	154	2.98	-	39.30	12.07	65.76			
AV	11.97686G	35.62	54.00	-18.38	50.01	3	Vertical	154	2.98	-	39.30	12.07	65.76			
PK	17.95228G	54.94	74.00	-19.06	57.71	3	Vertical	344	1.58	-	46.80	12.80	62.37			
AV	17.96334G	43.31	54.00	-10.69	46.09	3	Vertical	344	1.58	-	46.77	12.80	62.35			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.9754G	47.59	74.00	-26.41	61.99	3	Horizontal	295	2.83	-	39.30	12.06	65.76			
AV	11.97968G	35.72	54.00	-18.28	50.10	3	Horizontal	295	2.83	-	39.30	12.07	65.75			
PK	17.96152G	54.92	74.00	-19.08	57.70	3	Horizontal	56	2.29	-	46.78	12.80	62.36			
AV	17.9587G	43.29	54.00	-10.71	46.07	3	Horizontal	56	2.29	-	46.78	12.80	62.36			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.93544G	49.67	83.54	-33.87	40.99	1	Vertical	222	1.70	-	39.00	17.31	47.63			
RMS	23.93957G	37.93	63.54	-25.61	29.24	1	Vertical	222	1.70	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU242+RU242 MRU 1_4TX

5985MHz_TX




EUT Y 4TX
 Setting 19.5/7.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.94199G	49.95	83.54	-33.59	41.26	1	Horizontal	85	2.63	-	39.00	17.31	47.62			
RMS	23.93778G	37.93	63.54	-25.61	29.24	1	Horizontal	85	2.63	-	39.00	17.31	47.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.92G	69.91	88.20	-18.29	58.46	3	Vertical	336	1.49	-	34.20	7.88	30.63			
RMS	5.921G	57.64	68.20	-10.56	46.19	3	Vertical	336	1.49	-	34.20	7.88	30.63			
PK	6.0955G	116.30	Inf	-Inf	104.45	3	Vertical	336	1.49	-	34.48	8.08	30.71			
RMS	6.0755G	106.39	Inf	-Inf	94.63	3	Vertical	336	1.49	-	34.40	8.05	30.69			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.894G	70.99	88.20	-17.21	59.59	3	Horizontal	24	1.62	-	34.18	7.86	30.64			
RMS	5.9135G	57.57	68.20	-10.63	46.13	3	Horizontal	24	1.62	-	34.20	7.87	30.63			
PK	6.103G	115.45	Inf	-Inf	103.57	3	Horizontal	24	1.62	-	34.51	8.09	30.72			
RMS	6.103G	106.00	Inf	-Inf	94.12	3	Horizontal	24	1.62	-	34.51	8.09	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0526G	47.78	74.00	-26.22	62.31	3	Vertical	112	2.34	-	39.09	12.07	65.69			
AV	12.04634G	35.91	54.00	-18.09	50.43	3	Vertical	112	2.34	-	39.11	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0457G	47.80	74.00	-26.20	62.31	3	Horizontal	16	1.57	-	39.12	12.07	65.70			
AV	12.0483G	35.81	54.00	-18.19	50.33	3	Horizontal	16	1.57	-	39.11	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07978G	46.16	83.54	-37.38	41.51	1	Vertical	346	1.11	-	37.58	15.29	48.22			
RMS	18.07789G	34.25	63.54	-29.29	29.61	1	Vertical	346	1.11	-	37.57	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 MRU 2_4TX

6025MHz_TX




EUT Y 4TX
 Setting 23.5/5.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07914G	46.01	83.54	-37.53	41.37	1	Horizontal	86	1.39	-	37.57	15.29	48.22			
RMS	18.07746G	34.23	63.54	-29.31	29.60	1	Horizontal	86	1.39	-	37.56	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
Setting 21/7
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9245G	69.26	88.20	-18.94	57.81	3	Vertical	334	1.59	-	34.20	7.88	30.63			
RMS	5.925G	57.79	68.20	-10.41	46.34	3	Vertical	334	1.59	-	34.20	7.88	30.63			
PK	6.0335G	115.92	Inf	-Inf	104.29	3	Vertical	334	1.59	-	34.30	7.98	30.65			
RMS	6.0935G	107.01	Inf	-Inf	95.18	3	Vertical	334	1.59	-	34.47	8.07	30.71			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 21/7
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.916G	72.03	88.20	-16.17	60.58	3	Horizontal	338	1.64	-	34.20	7.88	30.63			
RMS	5.916G	57.50	68.20	-10.70	46.05	3	Horizontal	338	1.64	-	34.20	7.88	30.63			
PK	6.1025G	115.46	Inf	-Inf	103.58	3	Horizontal	338	1.64	-	34.51	8.09	30.72			
RMS	6.1035G	105.87	Inf	-Inf	93.99	3	Horizontal	338	1.64	-	34.51	8.09	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 21/7
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0492G	48.12	74.00	-25.88	62.65	3	Vertical	102	1.89	-	39.10	12.07	65.70			
AV	12.04886G	35.56	54.00	-18.44	50.09	3	Vertical	102	1.89	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 21/7
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05444G	47.43	74.00	-26.57	61.96	3	Horizontal	247	1.93	-	39.09	12.07	65.69			
AV	12.04734G	35.56	54.00	-18.44	50.08	3	Horizontal	247	1.93	-	39.11	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 21/7
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.076G	46.22	83.54	-37.32	41.59	1	Vertical	149	1.76	-	37.56	15.29	48.22			
RMS	18.07976G	33.91	63.54	-29.63	29.26	1	Vertical	149	1.76	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+3xRU242 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 21/7
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.0723G	45.87	83.54	-37.67	41.26	1	Horizontal	262	1.40	-	37.53	15.29	48.21			
RMS	18.07968G	33.91	63.54	-29.63	29.26	1	Horizontal	262	1.40	-	37.58	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.912G	67.12	88.20	-21.08	55.68	3	Vertical	335	1.53	-	34.20	7.87	30.63			
RMS	5.921G	56.18	68.20	-12.02	44.73	3	Vertical	335	1.53	-	34.20	7.88	30.63			
PK	6.0735G	116.64	Inf	-Inf	104.90	3	Vertical	335	1.53	-	34.39	8.04	30.69			
RMS	6.0745G	106.93	Inf	-Inf	95.17	3	Vertical	335	1.53	-	34.40	8.05	30.69			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9205G	70.03	88.20	-18.17	58.58	3	Horizontal	338	1.59	-	34.20	7.88	30.63			
RMS	5.9235G	56.26	68.20	-11.94	44.81	3	Horizontal	338	1.59	-	34.20	7.88	30.63			
PK	6.103G	115.58	Inf	-Inf	103.70	3	Horizontal	338	1.59	-	34.51	8.09	30.72			
RMS	6.103G	105.75	Inf	-Inf	93.87	3	Horizontal	338	1.59	-	34.51	8.09	30.72			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05266G	47.26	74.00	-26.74	61.79	3	Vertical	58	2.26	-	39.09	12.07	65.69			
AV	12.04998G	35.78	54.00	-18.22	50.31	3	Vertical	58	2.26	-	39.10	12.07	65.70			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04872G	47.56	74.00	-26.44	62.08	3	Horizontal	92	2.22	-	39.11	12.07	65.70			
AV	12.05026G	35.76	54.00	-18.24	50.28	3	Horizontal	92	2.22	-	39.10	12.07	65.69			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07205G	46.23	83.54	-37.31	41.62	1	Vertical	89	1.81	-	37.53	15.29	48.21			
RMS	18.07787G	34.25	63.54	-29.29	29.61	1	Vertical	89	1.81	-	37.57	15.29	48.22			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU484+RU484 MRU 1_4TX

6025MHz_TX




EUT Y 4TX
 Setting 19/8
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07203G	46.19	83.54	-37.35	41.58	1	Horizontal	79	1.02	-	37.53	15.29	48.21			
RMS	18.07323G	34.15	63.54	-29.39	29.53	1	Horizontal	79	1.02	-	37.54	15.29	48.21			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26/3
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.917G	79.69	88.20	-8.51	68.24	3	Vertical	352	1.67	-	34.20	7.88	30.63			
RMS	5.925G	66.55	68.20	-1.65	55.10	3	Vertical	352	1.67	-	34.20	7.88	30.63			
PK	6.1538G	115.45	Inf	-Inf	103.45	3	Vertical	352	1.67	-	34.60	8.17	30.77			
RMS	6.133G	106.28	Inf	-Inf	94.32	3	Vertical	352	1.67	-	34.57	8.14	30.75			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26/3
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9218G	81.05	88.20	-7.15	69.60	3	Horizontal	337	1.53	-	34.20	7.88	30.63			
RMS	5.9146G	65.28	68.20	-2.92	53.84	3	Horizontal	337	1.53	-	34.20	7.87	30.63			
PK	6.1642G	115.47	Inf	-Inf	103.47	3	Horizontal	337	1.53	-	34.60	8.18	30.78			
RMS	6.1426G	106.37	Inf	-Inf	94.39	3	Horizontal	337	1.53	-	34.59	8.15	30.76			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26/3
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.2051G	46.96	74.00	-27.04	61.58	3	Vertical	104	2.35	-	38.89	12.05	65.56			
AV	12.20346G	35.48	54.00	-18.52	50.10	3	Vertical	104	2.35	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
Setting 26/3
02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.2139G	47.01	74.00	-26.99	61.64	3	Horizontal	98	1.74	-	38.87	12.05	65.55			
AV	12.20338G	35.45	54.00	-18.55	50.07	3	Horizontal	98	1.74	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26/3
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31904G	46.48	83.54	-37.06	41.83	1	Vertical	358	2.01	-	37.64	15.27	48.26			
RMS	18.31793G	34.93	63.54	-28.61	30.28	1	Vertical	358	2.01	-	37.64	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 MRU 4_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26/3
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3147G	46.50	83.54	-37.04	41.86	1	Horizontal	151	2.57	-	37.63	15.27	48.26			
RMS	18.31605G	34.93	63.54	-28.61	30.29	1	Horizontal	151	2.57	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9242G	82.10	88.20	-6.10	70.65	3	Vertical	351	1.68	-	34.20	7.88	30.63			
RMS	5.9234G	68.05	68.20	-0.15	56.60	3	Vertical	351	1.68	-	34.20	7.88	30.63			
PK	6.1522G	116.53	Inf	-Inf	104.53	3	Vertical	351	1.68	-	34.60	8.17	30.77			
RMS	6.173G	106.73	Inf	-Inf	94.72	3	Vertical	351	1.68	-	34.60	8.20	30.79			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 02-R-G-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9138G	82.47	88.20	-5.73	71.03	3	Horizontal	337	1.67	-	34.20	7.87	30.63			
RMS	5.9146G	67.17	68.20	-1.03	55.73	3	Horizontal	337	1.67	-	34.20	7.87	30.63			
PK	6.1018G	116.17	Inf	-Inf	104.30	3	Horizontal	337	1.67	-	34.50	8.09	30.72			
RMS	6.1634G	105.99	Inf	-Inf	93.99	3	Horizontal	337	1.67	-	34.60	8.18	30.78			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20404G	46.96	74.00	-27.04	61.58	3	Vertical	101	2.69	-	38.89	12.05	65.56			
AV	12.20236G	35.51	54.00	-18.49	50.12	3	Vertical	101	2.69	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21732G	47.24	74.00	-26.76	61.86	3	Horizontal	352	1.80	-	38.87	12.05	65.54			
AV	12.20168G	35.66	54.00	-18.34	50.27	3	Horizontal	352	1.80	-	38.90	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31478G	46.72	83.54	-36.82	42.08	1	Vertical	60	2.08	-	37.63	15.27	48.26			
RMS	18.3145G	34.93	63.54	-28.61	30.29	1	Vertical	60	2.08	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 MRU 5_4TX

6105MHz_TX




EUT Y 4TX
 Setting 26.5/1.5
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31406G	46.98	83.54	-36.56	42.34	1	Horizontal	264	2.34	-	37.63	15.27	48.26			
RMS	18.31277G	34.77	63.54	-28.77	30.13	1	Horizontal	264	2.34	-	37.63	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX




EUT Y 4TX
Setting 24/3
02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.925G	68.58	88.20	-19.62	57.13	3	Vertical	0	1.51	-	34.20	7.88	30.63			
RMS	5.925G	56.55	68.20	-11.65	45.10	3	Vertical	0	1.51	-	34.20	7.88	30.63			
PK	6.2082G	115.22	Inf	-Inf	103.20	3	Vertical	0	1.51	-	34.60	8.25	30.83			
RMS	6.2082G	104.12	Inf	-Inf	92.10	3	Vertical	0	1.51	-	34.60	8.25	30.83			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX




EUT Y 4TX
 Setting 24/3
 02-R-G-5-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9146G	71.96	88.20	-16.24	60.52	3	Horizontal	338	1.57	-	34.20	7.87	30.63			
RMS	5.9154G	57.02	68.20	-11.18	45.57	3	Horizontal	338	1.57	-	34.20	7.88	30.63			
PK	6.2234G	115.12	Inf	-Inf	103.11	3	Horizontal	338	1.57	-	34.60	8.26	30.85			
RMS	6.2442G	106.63	Inf	-Inf	94.62	3	Horizontal	338	1.57	-	34.60	8.28	30.87			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX




EUT Y 4TX
Setting 24/3
02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.2024G	48.11	74.00	-25.89	62.72	3	Vertical	331	1.53	-	38.90	12.05	65.56			
AV	12.2039G	35.01	54.00	-18.99	49.63	3	Vertical	331	1.53	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX




EUT Y 4TX
 Setting 24/3
 02-R-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21022G	47.14	74.00	-26.86	61.76	3	Horizontal	129	2.70	-	38.88	12.05	65.55			
AV	12.20432G	35.08	54.00	-18.92	49.70	3	Horizontal	129	2.70	-	38.89	12.05	65.56			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX




EUT Y 4TX
 Setting 24/3
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.312G	46.72	83.54	-36.82	42.09	1	Vertical	149	2.96	-	37.62	15.27	48.26			
RMS	18.31009G	34.41	63.54	-29.13	29.78	1	Vertical	149	2.96	-	37.62	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996 MRU 1_4TX

6105MHz_TX



EUT Y 4TX
 Setting 24/3
 03-P-E-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31927G	46.79	83.54	-36.75	42.14	1	Horizontal	34	2.21	-	37.64	15.27	48.26			
RMS	18.31276G	34.41	63.54	-29.13	29.77	1	Horizontal	34	2.21	-	37.63	15.27	48.26			



RSE TX above 1GHz_R4_Wide Beam_Puncturing
(Parent Device / FCC ID: UDX-600216010)


Appendix E.13

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11be EHT160_Nss1,(MCS0)_2TX	Pass	RMS	5.923G	68.06	68.20	-0.14	3	Vertical	29	1.80	-

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_Y_1TX
 Setting 21
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	5.9226G	81.20	88.20	-7.00	76.13	3	Vertical	25	1.50	-	32.40	7.27	34.60
RMS	5.9246G	67.21	68.20	-0.99	62.14	3	Vertical	25	1.50	-	32.40	7.27	34.60
PK	6.0138G	113.42	Inf	-Inf	108.26	3	Vertical	25	1.50	-	32.50	7.33	34.67
RMS	6.0226G	101.92	Inf	-Inf	96.75	3	Vertical	25	1.50	-	32.50	7.33	34.66

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_Y_1TX
 Setting 21
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.925G	79.71	88.20	-8.49	74.64	3	Horizontal	9	1.50	-	32.40	7.27	34.60			
RMS	5.925G	65.78	68.20	-2.42	60.71	3	Horizontal	9	1.50	-	32.40	7.27	34.60			
PK	6.0234G	112.08	Inf	-Inf	106.91	3	Horizontal	9	1.50	-	32.50	7.33	34.66			
RMS	6.0226G	100.47	Inf	-Inf	95.30	3	Horizontal	9	1.50	-	32.50	7.33	34.66			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_Y_1TX
Setting 21
01-C-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	11.97558G	58.68	74.00	-15.32	53.02	3	Vertical	10	1.71	-	38.95	12.06	45.35				
AV	11.98182G	44.39	54.00	-9.61	38.72	3	Vertical	10	1.71	-	38.96	12.07	45.36				
PK	17.9685G	62.76	74.00	-11.24	41.26	3	Vertical	52	1.80	-	51.69	14.09	44.28				
AV	17.9685G	48.99	54.00	-5.01	27.49	3	Vertical	52	1.80	-	51.69	14.09	44.28				

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_Y_1TX
Setting 21
01-C-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	11.96142G	58.63	74.00	-15.37	53.01	3	Horizontal	81	1.72	-	38.92	12.05	45.35				
AV	11.96166G	44.16	54.00	-9.84	38.53	3	Horizontal	81	1.72	-	38.92	12.06	45.35				
PK	17.958G	62.10	74.00	-11.90	41.12	3	Horizontal	260	1.58	-	51.18	14.09	44.29				
AV	17.96952G	47.83	54.00	-6.17	26.28	3	Horizontal	260	1.58	-	51.74	14.09	44.28				

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_V_1TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.92248G	58.50	83.54	-25.04	49.82	1	Vertical	115	1.95	-	39.00	17.31	47.63			
AV	23.92G	44.33	63.54	-19.21	35.65	1	Vertical	115	1.95	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_1TX

5985MHz_TX




EUT_V_1TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.95744G	59.04	83.54	-24.50	50.33	1	Horizontal	319	1.48	-	39.01	17.32	47.62			
AV	23.92G	44.90	63.54	-18.64	36.22	1	Horizontal	319	1.48	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 21.5
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.925G	79.91	88.20	-8.29	74.84	3	Vertical	26	1.58	-	32.40	7.27	34.60			
RMS	5.925G	65.97	68.20	-2.23	60.90	3	Vertical	26	1.58	-	32.40	7.27	34.60			
PK	6.015G	110.33	Inf	-Inf	105.17	3	Vertical	26	1.58	-	32.50	7.33	34.67			
RMS	6.0605G	99.78	Inf	-Inf	94.55	3	Vertical	26	1.58	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.924G	77.86	88.20	-10.34	72.79	3	Horizontal	338	1.50	-	32.40	7.27	34.60			
RMS	5.925G	64.18	68.20	-4.02	59.11	3	Horizontal	338	1.50	-	32.40	7.27	34.60			
PK	6.048G	108.73	Inf	-Inf	103.51	3	Horizontal	338	1.50	-	32.50	7.35	34.63			
RMS	6.0595G	97.07	Inf	-Inf	91.84	3	Horizontal	338	1.50	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.06568G	62.55	74.00	-11.45	56.61	3	Vertical	309	1.63	-	39.26	12.08	45.40			
AV	12.0616G	47.46	54.00	-6.54	41.52	3	Vertical	309	1.63	-	39.25	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05728G	59.42	74.00	-14.58	53.50	3	Horizontal	3	1.51	-	39.23	12.08	45.39			
AV	12.04952G	44.79	54.00	-9.21	38.90	3	Horizontal	3	1.51	-	39.20	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_V_1TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.06984G	56.54	83.54	-27.00	51.94	1	Vertical	272	1.58	-	37.52	15.29	48.21			
AV	18.06884G	41.99	63.54	-21.55	37.40	1	Vertical	272	1.58	-	37.51	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_1TX

6025MHz_TX




EUT_V_1TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.07216G	56.54	83.54	-27.00	51.93	1	Horizontal	241	1.85	-	37.53	15.29	48.21			
AV	18.0744G	41.91	63.54	-21.63	37.28	1	Horizontal	241	1.85	-	37.55	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 22
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.901G	82.65	88.20	-5.55	77.58	3	Vertical	27	1.57	-	32.40	7.25	34.58			
RMS	5.925G	67.95	68.20	-0.25	62.88	3	Vertical	27	1.57	-	32.40	7.27	34.60			
PK	6.055G	112.81	Inf	-Inf	107.59	3	Vertical	27	1.57	-	32.50	7.35	34.63			
RMS	6.06G	100.80	Inf	-Inf	95.57	3	Vertical	27	1.57	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 22
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.904G	81.35	88.20	-6.85	76.28	3	Horizontal	12	1.48	-	32.40	7.25	34.58			
RMS	5.925G	65.93	68.20	-2.27	60.86	3	Horizontal	12	1.48	-	32.40	7.27	34.60			
PK	6.038G	109.61	Inf	-Inf	104.41	3	Horizontal	12	1.48	-	32.50	7.34	34.64			
RMS	6.0735G	98.35	Inf	-Inf	93.10	3	Horizontal	12	1.48	-	32.50	7.36	34.61			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP_2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0528G	58.04	74.00	-15.96	52.14	3	Vertical	136	1.79	-	39.21	12.08	45.39			
AV	12.03264G	43.87	54.00	-10.13	38.04	3	Vertical	136	1.79	-	39.13	12.08	45.38			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP_2_1TX

6025MHz_TX




EUT_Y_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.03456G	59.59	74.00	-14.41	53.75	3	Horizontal	210	1.98	-	39.14	12.08	45.38			
AV	12.0568G	45.14	54.00	-8.86	39.22	3	Horizontal	210	1.98	-	39.23	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP_2_1TX

6025MHz_TX



EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.05844G	56.58	83.54	-26.96	52.05	1	Vertical	284	1.93	-	37.45	15.29	48.21			
AV	18.055G	42.40	63.54	-21.14	37.89	1	Vertical	284	1.93	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 2_1TX

6025MHz_TX




EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.06364G	56.35	83.54	-27.19	51.79	1	Horizontal	33	1.92	-	37.48	15.29	48.21			
AV	18.055G	42.36	63.54	-21.18	37.85	1	Horizontal	33	1.92	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_1TX

6105MHz_TX




EUT_Y_1TX
Setting 22
06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.924G	79.82	88.20	-8.38	74.75	3	Vertical	26	1.59	-	32.40	7.27	34.60			
RMS	5.925G	66.53	68.20	-1.67	61.46	3	Vertical	26	1.59	-	32.40	7.27	34.60			
PK	6.058G	107.61	Inf	-Inf	102.38	3	Vertical	26	1.59	-	32.50	7.35	34.62			
RMS	6.059G	97.15	Inf	-Inf	91.92	3	Vertical	26	1.59	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.925G	76.20	88.20	-12.00	71.13	3	Horizontal	18	1.50	-	32.40	7.27	34.60			
RMS	5.925G	64.34	68.20	-3.86	59.27	3	Horizontal	18	1.50	-	32.40	7.27	34.60			
PK	6.219G	106.80	Inf	-Inf	100.88	3	Horizontal	18	1.50	-	32.95	7.44	34.47			
RMS	6.2455G	95.95	Inf	-Inf	89.77	3	Horizontal	18	1.50	-	33.16	7.46	34.44			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.19648G	56.88	74.00	-17.12	51.17	3	Vertical	237	1.43	-	39.11	12.07	45.47			
AV	12.19056G	42.92	54.00	-11.08	37.17	3	Vertical	237	1.43	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20632G	56.75	74.00	-17.25	51.08	3	Horizontal	35	1.82	-	39.07	12.07	45.47			
AV	12.19G	42.90	54.00	-11.10	37.15	3	Horizontal	35	1.82	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_6_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31352G	55.47	83.54	-28.07	50.83	1	Vertical	78	1.50	-	37.63	15.27	48.26			
AV	18.305G	41.80	63.54	-21.74	37.18	1	Vertical	78	1.50	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_6_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.32144G	56.17	83.54	-27.37	51.52	1	Horizontal	134	1.45	-	37.64	15.27	48.26			
AV	18.305G	41.76	63.54	-21.78	37.14	1	Horizontal	134	1.45	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22.5
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.921G	78.78	88.20	-9.42	73.72	3	Vertical	26	1.56	-	32.40	7.26	34.60			
RMS	5.925G	67.65	68.20	-0.55	62.58	3	Vertical	26	1.56	-	32.40	7.27	34.60			
PK	6.0778G	109.77	Inf	-Inf	104.51	3	Vertical	26	1.56	-	32.50	7.36	34.60			
RMS	6.0586G	98.15	Inf	-Inf	92.92	3	Vertical	26	1.56	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22.5
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.9178G	77.45	88.20	-10.75	72.38	3	Horizontal	27	1.74	-	32.40	7.26	34.59			
RMS	5.9242G	65.02	68.20	-3.18	59.95	3	Horizontal	27	1.74	-	32.40	7.27	34.60			
PK	6.233G	108.04	Inf	-Inf	101.98	3	Horizontal	27	1.74	-	33.06	7.45	34.45			
RMS	6.2578G	96.85	Inf	-Inf	90.62	3	Horizontal	27	1.74	-	33.20	7.46	34.43			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.19392G	57.70	74.00	-16.30	51.97	3	Vertical	159	1.46	-	39.12	12.07	45.46			
AV	12.1924G	43.11	54.00	-10.89	37.37	3	Vertical	159	1.46	-	39.13	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20224G	57.26	74.00	-16.74	51.57	3	Horizontal	302	1.84	-	39.09	12.07	45.47			
AV	12.19272G	43.08	54.00	-10.92	37.34	3	Horizontal	302	1.84	-	39.13	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.30856G	56.24	83.54	-27.30	51.61	1	Vertical	231	1.69	-	37.62	15.27	48.26			
AV	18.30516G	41.95	63.54	-21.59	37.33	1	Vertical	231	1.69	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31924G	55.95	83.54	-27.59	51.30	1	Horizontal	169	1.91	-	37.64	15.27	48.26			
AV	18.30536G	41.93	63.54	-21.61	37.31	1	Horizontal	169	1.91	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9194G	83.79	88.20	-4.41	78.72	3	Vertical	27	1.53	-	32.40	7.26	34.59			
RMS	5.925G	67.76	68.20	-0.44	62.69	3	Vertical	27	1.53	-	32.40	7.27	34.60			
PK	6.0986G	109.37	Inf	-Inf	104.08	3	Vertical	27	1.53	-	32.50	7.37	34.58			
RMS	6.069G	98.55	Inf	-Inf	93.30	3	Vertical	27	1.53	-	32.50	7.36	34.61			



5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
Setting 22
06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.921G	82.89	88.20	-5.31	77.83	3	Horizontal	13	1.60	-	32.40	7.26	34.60			
RMS	5.921G	66.55	68.20	-1.65	61.49	3	Horizontal	13	1.60	-	32.40	7.26	34.60			
PK	6.0986G	108.85	Inf	-Inf	103.56	3	Horizontal	13	1.60	-	32.50	7.37	34.58			
RMS	6.0746G	96.56	Inf	-Inf	91.31	3	Horizontal	13	1.60	-	32.50	7.36	34.61			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT_V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21864G	58.09	74.00	-15.91	52.47	3	Vertical	193	1.93	-	39.03	12.07	45.48			
AV	12.19848G	43.58	54.00	-10.42	37.87	3	Vertical	193	1.93	-	39.11	12.07	45.47			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT_Y_1TX
 Setting 22
 01-C-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	12.21136G	57.69	74.00	-16.31	52.04	3	Horizontal	327	1.67	-	39.05	12.07	45.47			
AV	12.19G	43.10	54.00	-10.90	37.35	3	Horizontal	327	1.67	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31356G	55.81	83.54	-27.73	51.17	1	Vertical	6	1.56	-	37.63	15.27	48.26			
AV	18.305G	41.83	63.54	-21.71	37.21	1	Vertical	6	1.56	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_1TX

6105MHz_TX




EUT V_1TX
 Setting 22
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31308G	56.76	83.54	-26.78	52.12	1	Horizontal	279	1.51	-	37.63	15.27	48.26			
AV	18.305G	41.76	63.54	-21.78	37.14	1	Horizontal	279	1.51	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	5.9202G	83.25	88.20	-4.95	78.19	3	Vertical	28	1.65	-	32.40	7.26	34.60
RMS	5.9206G	67.68	68.20	-0.52	62.62	3	Vertical	28	1.65	-	32.40	7.26	34.60
PK	6.0178G	116.57	Inf	-Inf	111.40	3	Vertical	28	1.65	-	32.50	7.33	34.66
RMS	6.0202G	106.51	Inf	-Inf	101.34	3	Vertical	28	1.65	-	32.50	7.33	34.66

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9098G	78.43	88.20	-9.77	73.35	3	Horizontal	339	1.50	-	32.40	7.26	34.58			
RMS	5.925G	65.99	68.20	-2.21	60.92	3	Horizontal	339	1.50	-	32.40	7.27	34.60			
PK	6.009G	116.58	Inf	-Inf	111.43	3	Horizontal	339	1.50	-	32.50	7.32	34.67			
RMS	6.009G	105.43	Inf	-Inf	100.28	3	Horizontal	339	1.50	-	32.50	7.32	34.67			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	11.97606G	59.32	74.00	-14.68	53.66	3	Vertical	32	1.77	-	38.95	12.06	45.35				
AV	11.97666G	45.09	54.00	-8.91	39.43	3	Vertical	32	1.77	-	38.95	12.06	45.35				
PK	17.96316G	61.16	74.00	-12.84	39.92	3	Vertical	0	1.80	-	51.43	14.09	44.28				
AV	17.9685G	47.51	54.00	-6.49	26.01	3	Vertical	0	1.80	-	51.69	14.09	44.28				

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.976G	57.69	74.00	-16.31	52.03	3	Horizontal	82	1.98	-	38.95	12.06	45.35			
AV	11.98308G	44.32	54.00	-9.68	38.64	3	Horizontal	82	1.98	-	38.97	12.07	45.36			
PK	17.96934G	61.08	74.00	-12.92	39.54	3	Horizontal	214	1.57	-	51.73	14.09	44.28			
AV	17.9685G	47.59	54.00	-6.41	26.09	3	Horizontal	214	1.57	-	51.69	14.09	44.28			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.95656G	57.44	83.54	-26.10	48.73	1	Vertical	353	1.55	-	39.01	17.32	47.62			
AV	23.92G	43.92	63.54	-19.62	35.24	1	Vertical	353	1.55	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT80_Nss1,(MCS0),RU484+RU242 CP 3_2TX

5985MHz_TX




EUT_Y_2TX
 Setting 20
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	23.95944G	57.01	83.54	-26.53	48.29	1	Horizontal	30	1.90	-	39.02	17.32	47.62			
AV	23.92G	43.81	63.54	-19.73	35.13	1	Horizontal	30	1.90	-	39.00	17.31	47.63			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 06-I-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	5.922G	80.54	88.20	-7.66	75.47	3	Vertical	26	1.80	-	32.40	7.27	34.60
RMS	5.9225G	67.83	68.20	-0.37	62.76	3	Vertical	26	1.80	-	32.40	7.27	34.60
PK	6.061G	114.53	Inf	-Inf	109.30	3	Vertical	26	1.80	-	32.50	7.35	34.62
RMS	6.0595G	103.81	Inf	-Inf	98.58	3	Vertical	26	1.80	-	32.50	7.35	34.62

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.914G	78.61	88.20	-9.59	73.54	3	Horizontal	336	1.61	-	32.40	7.26	34.59			
RMS	5.925G	66.35	68.20	-1.85	61.28	3	Horizontal	336	1.61	-	32.40	7.27	34.60			
PK	6.09G	113.98	Inf	-Inf	108.70	3	Horizontal	336	1.61	-	32.50	7.37	34.59			
RMS	6.0685G	103.52	Inf	-Inf	98.27	3	Horizontal	336	1.61	-	32.50	7.36	34.61			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.0636G	61.37	74.00	-12.63	55.43	3	Vertical	284	1.81	-	39.25	12.08	45.39			
AV	12.06176G	47.16	54.00	-6.84	41.22	3	Vertical	284	1.81	-	39.25	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.05808G	59.89	74.00	-14.11	53.97	3	Horizontal	197	1.96	-	39.23	12.08	45.39			
AV	12.04896G	45.07	54.00	-8.93	39.18	3	Horizontal	197	1.96	-	39.20	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.05884G	57.83	83.54	-25.71	53.30	1	Vertical	293	1.87	-	37.45	15.29	48.21			
AV	18.055G	43.02	63.54	-20.52	38.51	1	Vertical	293	1.87	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484+RU242 CP 5_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.069G	57.11	83.54	-26.43	52.52	1	Horizontal	311	1.39	-	37.51	15.29	48.21			
AV	18.055G	42.90	63.54	-20.64	38.39	1	Horizontal	311	1.39	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.921G	84.36	88.20	-3.84	79.30	3	Vertical	29	1.80	-	32.40	7.26	34.60			
RMS	5.923G	68.06	68.20	-0.14	62.99	3	Vertical	29	1.80	-	32.40	7.27	34.60			
PK	6.059G	115.45	Inf	-Inf	110.22	3	Vertical	29	1.80	-	32.50	7.35	34.62			
RMS	6.06G	104.18	Inf	-Inf	98.95	3	Vertical	29	1.80	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
Setting 21
06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.912G	79.49	88.20	-8.71	74.42	3	Horizontal	13	1.63	-	32.40	7.26	34.59			
RMS	5.925G	65.77	68.20	-2.43	60.70	3	Horizontal	13	1.63	-	32.40	7.27	34.60			
PK	5.99G	114.12	Inf	-Inf	109.00	3	Horizontal	13	1.63	-	32.48	7.31	34.67			
RMS	6.0305G	103.72	Inf	-Inf	98.53	3	Horizontal	13	1.63	-	32.50	7.34	34.65			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.04744G	58.44	74.00	-15.56	52.56	3	Vertical	348	1.78	-	39.19	12.08	45.39			
AV	12.05424G	43.88	54.00	-10.12	37.97	3	Vertical	348	1.78	-	39.22	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.03432G	59.25	74.00	-14.75	53.41	3	Horizontal	134	1.81	-	39.14	12.08	45.38			
AV	12.05688G	44.73	54.00	-9.27	38.81	3	Horizontal	134	1.81	-	39.23	12.08	45.39			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.08332G	56.33	83.54	-27.21	51.66	1	Vertical	202	1.74	-	37.60	15.29	48.22			
AV	18.055G	42.56	63.54	-20.98	38.05	1	Vertical	202	1.74	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT160_Nss1,(MCS0),RU996+RU484 CP 4_2TX

6025MHz_TX




EUT_Y_2TX
 Setting 21
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.05556G	56.69	83.54	-26.85	52.18	1	Horizontal	100	1.39	-	37.43	15.29	48.21			
AV	18.055G	42.34	63.54	-21.20	37.83	1	Horizontal	100	1.39	-	37.43	15.29	48.21			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP 6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9226G	78.45	88.20	-9.75	73.38	3	Vertical	28	1.58	-	32.40	7.27	34.60			
RMS	5.9218G	67.06	68.20	-1.14	61.99	3	Vertical	28	1.58	-	32.40	7.27	34.60			
PK	6.1194G	112.55	Inf	-Inf	107.14	3	Vertical	28	1.58	-	32.58	7.39	34.56			
RMS	6.0594G	101.46	Inf	-Inf	96.23	3	Vertical	28	1.58	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP 6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9146G	75.46	88.20	-12.74	70.39	3	Horizontal	23	1.66	-	32.40	7.26	34.59			
RMS	5.9114G	65.26	68.20	-2.94	60.19	3	Horizontal	23	1.66	-	32.40	7.26	34.59			
PK	6.1082G	111.82	Inf	-Inf	106.48	3	Horizontal	23	1.66	-	32.53	7.38	34.57			
RMS	6.129G	100.82	Inf	-Inf	95.36	3	Horizontal	23	1.66	-	32.62	7.39	34.55			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21544G	57.17	74.00	-16.83	51.54	3	Vertical	3	1.39	-	39.04	12.07	45.48			
AV	12.19088G	42.97	54.00	-11.03	37.22	3	Vertical	3	1.39	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP 6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	12.21456G	57.77	74.00	-16.23	52.14	3	Horizontal	268	1.71	-	39.04	12.07	45.48			
AV	12.19064G	42.96	54.00	-11.04	37.21	3	Horizontal	268	1.71	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.30808G	56.21	83.54	-27.33	51.58	1	Vertical	253	1.97	-	37.62	15.27	48.26			
AV	18.30504G	41.68	63.54	-21.86	37.06	1	Vertical	253	1.97	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996+RU484 CP_6_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.31228G	55.68	83.54	-27.86	51.05	1	Horizontal	85	1.53	-	37.62	15.27	48.26			
AV	18.305G	41.73	63.54	-21.81	37.11	1	Horizontal	85	1.53	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9226G	78.75	88.20	-9.45	73.68	3	Vertical	28	1.80	-	32.40	7.27	34.60			
RMS	5.9226G	65.26	68.20	-2.94	60.19	3	Vertical	28	1.80	-	32.40	7.27	34.60			
PK	6.0602G	112.81	Inf	-Inf	107.58	3	Vertical	28	1.80	-	32.50	7.35	34.62			
RMS	6.0602G	101.41	Inf	-Inf	96.18	3	Vertical	28	1.80	-	32.50	7.35	34.62			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9146G	76.50	88.20	-11.70	71.43	3	Horizontal	14	1.59	-	32.40	7.26	34.59			
RMS	5.913G	63.63	68.20	-4.57	58.56	3	Horizontal	14	1.59	-	32.40	7.26	34.59			
PK	6.209G	112.39	Inf	-Inf	106.56	3	Horizontal	14	1.59	-	32.87	7.44	34.48			
RMS	6.2482G	101.80	Inf	-Inf	95.59	3	Horizontal	14	1.59	-	33.19	7.46	34.44			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.21136G	56.91	74.00	-17.09	51.26	3	Vertical	62	1.51	-	39.05	12.07	45.47			
AV	12.1928G	43.11	54.00	-10.89	37.37	3	Vertical	62	1.51	-	39.13	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.19744G	57.57	74.00	-16.43	51.86	3	Horizontal	44	1.50	-	39.11	12.07	45.47			
AV	12.19008G	43.10	54.00	-10.90	37.35	3	Horizontal	44	1.50	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.30612G	55.75	83.54	-27.79	51.13	1	Vertical	111	1.51	-	37.61	15.27	48.26			
AV	18.305G	41.74	63.54	-21.80	37.12	1	Vertical	111	1.51	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),3xRU996 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.30768G	56.21	83.54	-27.33	51.58	1	Horizontal	331	1.74	-	37.62	15.27	48.26			
AV	18.305G	41.76	63.54	-21.78	37.14	1	Horizontal	331	1.74	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.921G	79.36	88.20	-8.84	74.30	3	Vertical	28	1.58	-	32.40	7.26	34.60			
RMS	5.9226G	66.78	68.20	-1.42	61.71	3	Vertical	28	1.58	-	32.40	7.27	34.60			
PK	6.0602G	113.57	Inf	-Inf	108.34	3	Vertical	28	1.58	-	32.50	7.35	34.62			
RMS	6.1586G	102.65	Inf	-Inf	97.04	3	Vertical	28	1.58	-	32.72	7.41	34.52			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 06-I-G-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	5.9114G	75.60	88.20	-12.60	70.53	3	Horizontal	19	1.66	-	32.40	7.26	34.59			
RMS	5.913G	64.62	68.20	-3.58	59.55	3	Horizontal	19	1.66	-	32.40	7.26	34.59			
PK	6.1674G	113.36	Inf	-Inf	107.74	3	Horizontal	19	1.66	-	32.73	7.41	34.52			
RMS	6.169G	102.33	Inf	-Inf	96.69	3	Horizontal	19	1.66	-	32.74	7.41	34.51			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20256G	57.67	74.00	-16.33	51.98	3	Vertical	13	1.93	-	39.09	12.07	45.47			
AV	12.19848G	43.51	54.00	-10.49	37.80	3	Vertical	13	1.93	-	39.11	12.07	45.47			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	12.20352G	57.93	74.00	-16.07	52.24	3	Horizontal	164	1.46	-	39.09	12.07	45.47			
AV	12.19G	43.13	54.00	-10.87	37.38	3	Horizontal	164	1.46	-	39.14	12.07	45.46			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX




EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.32172G	55.65	83.54	-27.89	51.00	1	Vertical	90	1.47	-	37.64	15.27	48.26			
AV	18.305G	41.74	63.54	-21.80	37.12	1	Vertical	90	1.47	-	37.61	15.27	48.26			

5.925-6.425GHz_802.11be EHT320_Nss1,(MCS0),2xRU996+RU484 CP 3_2TX

6105MHz_TX



EUT_Y_2TX
 Setting 21.5
 01-C-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	18.3094G	56.12	83.54	-27.42	51.49	1	Horizontal	318	1.66	-	37.62	15.27	48.26			
AV	18.305G	41.73	63.54	-21.81	37.11	1	Horizontal	318	1.66	-	37.61	15.27	48.26			