



L001010-01: SARDINE

Articulating Wide-Beamwidth Wi-Fi 7 Directional Dipole Antenna


Cisco Sardine is a 1-Port, Triple-band, Directional, outdoor antenna that can support a variety of deployments. With an IP67 rating, it works in both indoor and outdoor environments. This antenna is integrated with a one-wire EEPROM to support SIA (self-identifying Antenna) feature. Antenna includes the N-Type male connector plug and has an articulating joint which allows the antenna to pivot ± 90 degrees from the N-Connector axis.

ELECTRICAL			
TE P/N	L001010-01		
Cisco P/N	07-100959-01		
Cisco Mfg Number	CW-ANT-T-D3-N		
Self-Identifying Circuitry	Yes		
Number of Ports	1		
Frequency, MHz	2400 - 2500	5180 - 5900	6000 - 7125
VSWR, Max	< 2:1		
Gain (Peak), dBi	6.0	7.5	7.5
Gain (Ave), dBi	5.6	7.1	6.7
Efficiency (%)	>60 %		
Efficiency (Ave), %	79%	80%	78%
Azimuth 3dB Beamwidth, deg	125° $\pm$ 10°	90°(+15°/-10°)	90°(+15°/-10°)
Average Azimuth 3dB Beamwidth, deg	118°	89°	88°
Elevation 3dB Beamwidth, deg	70° $\pm$ 10°	60° $\pm$ 10°	60° $\pm$ 10°
Average Elevation 3dB Beamwidth, deg	73°	61°	58°
Average Front to back ratio, dB	20	20	15
Nominal Impedance, Ohm	50		

MECHANICAL	
Antenna Weight, g	73
Radome	PC (60% PCR)
Color	Cisco Medium Grey
RF Connector	N-Male

ENVIRONMENTAL	
Operating Temperature, °C	-40°C to +65°C
Storage Temperature, °C	-40°C to +85°C
Ingress Protection	IP66, IP67



PACKING INFORMATION





PACKAGED DIMENSIONS	MASTER CARTON	AIR PALLET	OCEAN PALLET
NUMBER OF ANTENNAS	40	4320	5280
HEIGHT-cm(in)	16.0 (6.3)	158.0 (62.21)	190.0 (74.81)
LENGTH-cm(in)	26.8 (10.56)	120 (47.24)	120 (47.24)
WIDTH-cm(in)	26.8 (10.56)	80 (31.5)	80 (31.5)
EST.SHIPPING WEIGHT-kg(lbs)	3.8 (8.38)	423 (932.56)	514 (1133.18)

Radiation Patterns


Radiation Patterns at 2400 - 2500 MHz



Radiation Patterns at 5100 - 6000 MHz



Radiation Patterns at 6000 – 7125 MHz



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use suitability determinations, as well as any applicable compliance and regulatory requirements. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2025 TE Connectivity. All Rights Reserved.

06/25 Original