

TEST REPORT

Application No.: GZEM2602001050HS
Applicant: Guangdong Galanz Enterprises Co., Ltd.
Address of Applicant: No. 25 South Ronggui Avenue, Ronggui Street, Shunde District, Foshan City, Guangdong Province, China
Manufacturer: Guangdong Galanz Appliances Manufacturing Co., Ltd.
Address of Manufacturer: No. 3, East Xingpu Avenue, Maxin Industrial Zone, Huangpu Town, Zhongshan City, Guangdong Province, China
Factory: Guangdong Galanz Appliances Manufacturing Co., Ltd.
Address of Factory: No. 3, East Xingpu Avenue, Maxin Industrial Zone, Huangpu Town, Zhongshan City, Guangdong Province, China
Product Name: Microwave Oven
Model No.: P110N30CPHV-SUC(L2),
 KMCS2020TBL**(* could be from 0 to 9 or from A to Z or blank),
 KMCS2020TPS**(* could be from 0 to 9 or from A to Z or blank),
 KMCS2020TWH**(* could be from 0 to 9 or from A to Z or blank) ♣
 ♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.
Trade Mark: Galanz, KitchenAid
Standard(s) : 47 CFR Part 18
Date of Receipt: 2026-02-04
Date of Test: 2026-02-07 to 2026-03-09
Date of Issue: 2026-03-17

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
 t (86-20) 82155555 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZEM260200105001	2026-03-17	Original

Authorized for issue by:			
			
		Damon Guan/Project Engineer	
Approved By			
		Terry Lai/Reviewer	



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 18	FCC/OST MP-5:1986	18.307	Pass
Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Radiated Emissions (30MHz-1GHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Radiated Emissions (above 1GHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Output Power Measurement		FCC OST/MP-5:1986	FCC OST/MP-5:1986 Clause 4.3	Pass
Operating Frequency Measurement		FCC OST/MP-5:1986	18.301	Pass
Radiation Hazard Test		FCC OST/MP-5:1986	1 mW/cm ²	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

♣ Declaration of EUT Family Grouping:

Model No.: P110N30CPHV-SUC(L2),

KMCS2020TBL**(* could be from 0 to 9 or from A to Z or blank),

KMCS2020TPS**(* could be from 0 to 9 or from A to Z or blank),

KMCS2020TWH**(* could be from 0 to 9 or from A to Z or blank)

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference on model name and trade mark.

Model No.	Trade mark
P110N30CPHV-SUC(L2)	Galanz
KMCS2020TBL**(* could be from 0 to 9 or from A to Z or blank), KMCS2020TPS**(* could be from 0 to 9 or from A to Z or blank), KMCS2020TWH**(* could be from 0 to 9 or from A to Z or blank)	KitchenAid

Therefore only one model P110N30CPHV-SUC(L2) was tested in this report.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	6
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Emission Test Results	11
6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)	11
6.1.1 E.U.T. Operation	11
6.1.1 Test Mode Description	11
6.1.2 Test Setup Diagram	11
6.1.3 Measurement Procedure and Data	12
6.2 Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)	14
6.2.1 E.U.T. Operation	14
6.2.2 Test Mode Description	14
6.2.3 Test Setup Diagram	14
6.2.4 Measurement Procedure and Data	15
6.3 Radiated Emissions (30MHz-1GHz)	19
6.3.1 E.U.T. Operation	19
6.3.2 Test Mode Description	19
6.3.3 Test Setup Diagram	19
6.3.4 Measurement Procedure and Data	20
6.4 Radiated Emissions (above 1GHz)	22
6.4.1 E.U.T. Operation	22
6.4.2 Test Mode Description	22
6.4.3 Test Setup Diagram	23
6.4.4 Measurement Procedure and Data	23
6.5 Output Power Measurement	34
6.5.1 E.U.T. Operation	34
6.5.2 Test Mode Description	34
6.5.3 Measurement Procedure and Data	35
6.6 Operating Frequency Measurement	36
6.6.1 E.U.T. Operation	36
6.6.2 Test Mode Description	37



6.6.3	Measurement Procedure and Data	37
6.7	Radiation Hazard Test	39
6.7.1	E.U.T. Operation	39
6.7.2	Test Mode Description	39
6.7.3	Measurement Procedure and Data	39
7	Test Setup Photo	40
8	EUT Constructional Details (EUT Photos)	41



4 General Information

4.1 Details of E.U.T.

Power supply: AC 120V 60Hz
Test voltage: AC 120V 60Hz
Microwave frequency: 2450MHz±50MHz
Cable(s): About 1.0m x 3 wires unscreened AC mains cable.

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

1100mL of water in the beaker for power output and frequency measurement.
One of 770 and the other of 330mL of water for second and third harmonic radiation measurement, just the worst case (770mL) was recorded in this report.
770mL of water for all other measurement

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at Mains Terminals (150kHz-30MHz)	3.13dB (150kHz to 30MHz)
Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)	± 3.12dB
Radiated Emissions (30MHz-1GHz)	4.61dB (30MHz-1GHz):3m; 4.38dB (30MHz-1GHz):10m
Radiated Emissions (above 1GHz)	4.72dB (1GHz-6GHz); 4.94dB (6GHz-18GHz)
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty) or U_{ETSI} (ETSI Uncertainty). Emission decision rule: – Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report. – Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report.	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663
Tel: +86 20 82155555
No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Coaxial Cable	HangTianXing	BL03-NMNM-6.00M	EMC0107	2025-08-12	2026-08-11
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	2025-08-14	2028-08-13
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2025-08-13	2026-08-12
EMI Test Receiver (9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2025-11-18	2026-11-17
Test Software E3r	Audix	Ver.6.191211	GZE100-77	N/A	N/A
Artificial Mains Network (LISN)	AFJ Instruments	LT32C	EMC2046	2025-08-12	2026-08-11

Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2025-08-13	2028-08-12
Coaxial cable	Mirco-COAX UTIFLEX	311A	EMC0540	2024-08-19	2026-08-18
Amplifier (9kHz-1.3GHz)	HP	8447F	EMC2065	2025-11-25	2026-11-24
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2024-04-16	2026-04-15
EMI Test Receiver (9kHz-7GHz)	Rohde & Schwarz	ESR7	EMC2220	2025-11-18	2026-11-17
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2025-08-13	2028-08-12
Coaxial cable	Mirco-COAX UTIFLEX	311A	EMC0540	2024-08-19	2026-08-18
Amplifier (9kHz-1.3GHz)	HP	8447F	EMC2065	2025-11-25	2026-11-24
EMI Test Receiver (9kHz-7GHz)	Rohde & Schwarz	ESR7	EMC2220	2025-11-18	2026-11-17
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2174	2025-04-21	2027-04-20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (CMAA, CNAS, EEC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Radiated Emissions (above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2025-08-11	2026-08-10
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2025-08-12	2026-08-11
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2025-08-12	2026-08-11
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Output Power Measurement					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Digital thermometer	FLUKE	51_2	EMC2200	2025-07-10	2026-07-09
Digital power analyzer for harmonics & flicker testing	EMTEST	DPA 500N	EMC2235	2025-11-18	2026-11-17
Programmable multifunctional ac/dc power source	EMTEST	NETWAVE 7-400	EMC2234	2025-11-18	2026-11-17
NET.Control	EMTEST	Ver 3.2.3	GZE100-80	N/A	N/A

Operating Frequency Measurement					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
Guangzhou Branch Testing Power EEC Laboratory. 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

Radiation Hazard Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Electric Field Probe(100KHz-3GHz)	WANDEL & GOLTERMANN	EMR-20	EMC0907	2025-05-14	2026-05-13

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2025-06-03	2026-06-02



6 Emission Test Results

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Test Engineer: Sunny Yang
 Limit:
 Frequency Range: 150kHz to 30MHz
 0.15 to 0.5 MHz: 66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
 0.5 to 5 MHz: 56dB(μV) quasi-peak, 46dB(μV) average
 5 to 30 MHz: 60dB(μV) quasi-peak, 50dB(μV) average
 Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz


6.1.1 E.U.T. Operation

Operating Environment:
 Temperature: 24.5 °C Humidity: 53.3 % RH Atmospheric Pressure: 1024 mbar

6.1.1 Test Mode Description

Pre-scan/	Mode	Description
Final test	Code	
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.1.2 Test Setup Diagram



6.1.3 Measurement Procedure and Data


Frequency range: 150KHz-30MHz

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

The red line show in graphic is the limit in standard used in this section.

Measured Level = Read level + Cable Loss + LISN Factor

Test Mode: 00; Line: Live line




Pol : LINE
Mode :
Model :
Power :

	Freque MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.152	32.98	0.04	9.57	42.59	55.91	-13.32	Average
2	0.152	48.91	0.04	9.57	58.52	65.91	-7.39	QP
3	0.277	33.29	0.04	9.56	42.89	50.90	-8.01	Average
4	0.277	46.64	0.04	9.56	56.24	60.90	-4.66	QP
5	0.354	29.49	0.05	9.58	39.12	48.87	-9.75	Average
6	0.354	41.00	0.05	9.58	50.63	58.87	-8.24	QP
7	0.683	27.60	0.06	9.59	37.25	46.00	-8.75	Average
8	0.683	39.32	0.06	9.59	48.97	56.00	-7.03	QP
9	1.065	21.57	0.08	9.54	31.19	46.00	-14.81	Average
10	1.065	32.69	0.08	9.54	42.31	56.00	-13.69	QP
11	24.142	32.99	0.42	9.84	43.25	50.00	-6.75	Average
12	24.142	45.14	0.42	9.84	55.40	60.00	-4.60	QP



Test Mode: 00; Line: Neutral Line



Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBUV	Cable Loss dB	LISN Factor dB	Measured Level dBUV	Limit Line dBUV	Over Limit dB	Remark
1	0.182	32.54	0.04	9.54	42.12	54.42	-12.30	Average
2	0.182	46.74	0.04	9.54	56.32	64.42	-8.10	QP
3	0.272	29.55	0.04	9.53	39.12	51.07	-11.95	Average
4	0.272	43.53	0.04	9.53	53.10	61.07	-7.97	QP
5	0.393	27.15	0.05	9.54	36.74	47.99	-11.25	Average
6	0.393	39.18	0.05	9.54	48.77	57.99	-9.22	QP
7	0.668	26.04	0.06	9.55	35.65	46.00	-10.35	Average
8	0.668	36.86	0.06	9.55	46.47	56.00	-9.53	QP
9	1.269	20.80	0.09	9.55	30.44	46.00	-15.56	Average
10	1.269	31.51	0.09	9.55	41.15	56.00	-14.85	QP
11	22.775	32.13	0.41	9.94	42.48	50.00	-7.52	Average
12	22.775	42.64	0.41	9.94	52.99	60.00	-7.01	QP



6.2 Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Test Engineer: Bob Qu
 Limit:
 Measurement Distance: 10 m
 Frequency Range: 9kHz to 30MHz
 Detector: Peak for pre-scan, Average for the final result
 (200Hz Resolution Bandwidth for 9kHz to 150kHz;
 9kHz Resolution Bandwidth for 150kHz to 30MHz)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	1059.0	Limit=20lg(25*SQRT(power/500))+20lg(300/10)= 60.76 dBuV/m @ 10m distance.

6.2.1 E.U.T. Operation


Operating Environment:

Temperature: 19.1 °C Humidity: 56.1 % RH Atmospheric Pressure: 1024 mbar

6.2.2 Test Mode Description

Pre-scan/ Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.2.3 Test Setup Diagram



6.2.4 Measurement Procedure and Data


Frequency range: 9KHz-30MHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by loop antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test Mode: 00; Polarity: Horizontal




Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.011	63.99	18.41	0.01	28.42	53.99	60.76	-6.77	HORIZONTAL	Average
2	0.014	64.87	16.23	0.01	28.47	52.64	60.76	-8.12	HORIZONTAL	Average
3	0.023	64.64	13.78	0.01	28.65	49.78	60.76	-10.98	HORIZONTAL	Average
4	0.033	65.66	12.79	0.02	29.05	49.42	60.76	-11.34	HORIZONTAL	Average
5	0.045	74.66	12.30	0.03	29.23	57.76	60.76	-3.00	HORIZONTAL	Average
6	0.090	59.05	11.96	0.03	29.38	41.66	60.76	-19.10	HORIZONTAL	Average



Test Mode: 00; Polarity: Horizontal




Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.169	65.81	11.87	0.04	29.40	48.32	60.76	-12.44	HORIZONTAL	Average
2	0.317	61.48	11.87	0.05	29.40	44.00	60.76	-16.76	HORIZONTAL	Average
3	0.529	59.24	11.80	0.07	29.40	41.71	60.76	-19.05	HORIZONTAL	Average
4	0.943	52.64	11.85	0.08	29.40	35.17	60.76	-25.59	HORIZONTAL	Average
5	3.381	43.09	11.77	0.19	29.34	25.71	60.76	-35.05	HORIZONTAL	Average
6	4.114	46.74	11.64	0.22	29.32	29.28	60.76	-31.48	HORIZONTAL	Average



Test Mode: 00; Polarity: Vertical




Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.010	64.27	18.54	0.01	28.42	54.40	60.76	-6.36	VERTICAL	Average
2	0.013	66.24	17.37	0.01	28.45	55.17	60.76	-5.59	VERTICAL	Average
3	0.022	68.14	13.93	0.01	28.63	53.45	60.76	-7.31	VERTICAL	Average
4	0.047	74.44	12.25	0.03	29.24	57.48	60.76	-3.28	VERTICAL	Average
5	0.057	68.98	12.12	0.03	29.30	51.83	60.76	-8.93	VERTICAL	Average
6	0.095	57.56	11.95	0.03	29.39	40.15	60.76	-20.61	VERTICAL	Average



Test Mode: 00; Polarity: Vertical



Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.156	66.86	11.88	0.03	29.40	49.37	60.76	-11.39	VERTICAL	Average
2	0.345	58.13	11.87	0.06	29.40	40.66	60.76	-20.10	VERTICAL	Average
3	0.535	55.16	11.80	0.07	29.40	37.63	60.76	-23.13	VERTICAL	Average
4	0.933	48.97	11.85	0.08	29.40	31.50	60.76	-29.26	VERTICAL	Average
5	3.417	43.16	11.77	0.20	29.34	25.79	60.76	-34.97	VERTICAL	Average
6	4.269	43.88	11.60	0.23	29.32	26.39	60.76	-34.37	VERTICAL	Average



6.3 Radiated Emissions (30MHz-1GHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Test Engineer: Bob Qu
 Limit:
 Measurement Distance: 10 m
 Frequency Range: 30 MHz to 1 GHz
 Detector: Peak for pre-scan, average for the final result
 (120 kHz Resolution Bandwidth for 30 MHz to 1 GHz)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	1059.0	Limit=20lg(25*SQRT(power/500))+20lg(300/10)= 60.76 dBuV/m @ 10m distance.


6.3.1 E.U.T. Operation

Operating Environment:
 Temperature: 19.1 °C Humidity: 54.7 % RH Atmospheric Pressure: 1024 mbar

6.3.2 Test Mode Description

Pre-scan/ Mode	Description
Final test Code	
Final test 00	Test the EUT in microwave mode with maximum power.
Pre-scan 01	Test the EUT in microwave mode with middle power.
Pre-scan 02	Test the EUT in microwave mode with lowest power.

6.3.3 Test Setup Diagram



6.3.4 Measurement Procedure and Data


Frequency range: 30MHz-1GHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test Mode: 00; Polarity: Horizontal




Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.127	24.04	13.06	0.64	28.00	9.74	60.76	-51.02	HORIZONTAL	Average
2	55.609	21.15	13.72	0.76	27.97	7.66	60.76	-53.10	HORIZONTAL	Average
3	110.569	29.43	10.51	0.87	27.89	12.92	60.76	-47.84	HORIZONTAL	Average
4	127.665	27.33	12.12	0.92	27.86	12.51	60.76	-48.25	HORIZONTAL	Average
5	213.015	25.57	10.16	1.28	27.42	9.59	60.76	-51.17	HORIZONTAL	Average
6	379.914	23.30	15.18	1.80	27.57	12.71	60.76	-48.05	HORIZONTAL	Average



Test Mode: 00; Polarity: Vertical



Site : SGS
Job :
Model :
Power :
Test Mode : Microwave

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.895	44.30	13.22	0.65	27.99	30.18	60.76	-30.58	VERTICAL	Average
2	44.431	38.19	13.93	0.72	27.99	24.85	60.76	-35.91	VERTICAL	Average
3	127.665	44.97	12.12	0.92	27.86	30.15	60.76	-30.61	VERTICAL	Average
4	135.506	40.82	12.80	0.94	27.84	26.72	60.76	-34.04	VERTICAL	Average
5	157.007	35.58	13.51	1.01	27.79	22.31	60.76	-38.45	VERTICAL	Average
6	236.645	31.29	11.46	1.47	27.32	16.90	60.76	-43.86	VERTICAL	Average



6.4 Radiated Emissions (above 1GHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Test Engineer: Lily Kuang
 Limit:
 Measurement Distance: 3 m
 Frequency Range: Above 1GHz
 Detector: Peak for pre-scan, Average for the final result
 (1MHz Resolution Bandwidth for 1000MHz Above)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	1059.0	Limit=20lg(25*SQRT(power/500))+20lg(300/3)= 71.22 dBuV/m @ 3m distance.

6.4.1 E.U.T. Operation


Operating Environment:
 Temperature: 23.6 °C Humidity: 54.9 % RH Atmospheric Pressure: 1007 mbar

6.4.2 Test Mode Description

Pre-scan/ Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.



6.4.3 Test Setup Diagram



6.4.4 Measurement Procedure and Data


Frequency range: Above 1GHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by Horn antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.


Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test Mode: 00; Polarity: Vertical




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2138.64	41.42	26.88	3.20	37.79	33.71	71.22	-37.51	VERTICAL	Average
2	4304.40	37.90	30.62	4.58	37.47	35.63	71.22	-35.59	VERTICAL	Average
3	8008.80	36.79	37.22	6.21	37.20	43.02	71.22	-28.20	VERTICAL	Average
4	9866.79	38.98	39.01	7.17	37.10	48.06	71.22	-23.16	VERTICAL	Average
5	12079.39	38.03	39.77	7.76	36.90	48.66	71.22	-22.56	VERTICAL	Average
6	14873.89	36.80	42.10	8.90	36.51	51.29	71.22	-19.93	VERTICAL	Average
7	16891.04	36.79	41.36	9.41	36.42	51.14	71.22	-20.08	VERTICAL	Average

Test Mode: 00; Polarity: Vertical




	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	18274.07	27.88	36.63	3.08	39.15	28.44	71.22	-42.78	VERTICAL	Average
2	19216.02	26.16	37.01	3.17	39.47	26.87	71.22	-44.35	VERTICAL	Average
3	20751.41	31.38	37.52	3.17	39.01	33.06	71.22	-38.16	VERTICAL	Average
4	21248.07	26.44	37.65	3.25	38.94	28.40	71.22	-42.82	VERTICAL	Average
5	22863.06	25.00	38.42	3.33	38.33	28.42	71.22	-42.80	VERTICAL	Average
6	23673.21	23.94	38.63	3.42	37.89	28.10	71.22	-43.12	VERTICAL	Average


Test Mode: 00; Polarity: Vertical



Test Mode: 00; Polarity: Vertical




Test Mode: 00; Polarity: Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2399.08	23.10	27.65	3.45	0.00	54.20	71.22	-17.02	VERTICAL	Average
2	2466.48	75.80	27.73	3.48	0.00	107.01	----	----	VERTICAL	Peak
3	2528.95	21.05	27.80	3.50	0.00	52.35	71.22	-18.87	VERTICAL	Average


Test Mode: 00; Polarity: Horizontal



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1910.65	45.65	26.59	3.08	37.85	37.47	71.22	-33.75	HORIZONTAL	Average
2	4311.10	41.92	30.65	4.59	37.47	39.69	71.22	-31.53	HORIZONTAL	Average
3	7417.51	36.45	36.52	6.01	37.18	41.80	71.22	-29.42	HORIZONTAL	Average
4	9923.99	40.46	39.07	7.19	37.10	49.62	71.22	-21.60	HORIZONTAL	Average
5	12947.07	41.35	39.78	8.11	36.83	52.41	71.22	-18.81	HORIZONTAL	Average
6	14873.89	40.37	42.10	8.90	36.51	54.86	71.22	-16.36	HORIZONTAL	Average
7	16988.97	40.43	41.79	9.43	36.42	55.23	71.22	-15.99	HORIZONTAL	Average




Test Mode: 00; Polarity: Horizontal




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	18588.91	28.49	36.93	3.14	39.24	29.32	71.22	-41.90	HORIZONTAL	Average
2	19825.16	27.17	37.04	3.00	40.35	26.86	71.22	-44.36	HORIZONTAL	Average
3	20901.92	30.38	37.64	3.21	38.83	32.40	71.22	-38.82	HORIZONTAL	Average
4	21692.40	29.63	37.56	3.31	39.67	30.83	71.22	-40.39	HORIZONTAL	Average
5	22945.83	28.85	38.46	3.33	38.23	32.41	71.22	-38.81	HORIZONTAL	Average
6	24152.38	26.36	38.70	3.45	38.02	30.49	71.22	-40.73	HORIZONTAL	Average




Test Mode: 00; Polarity: Horizontal



Test Mode: 00; Polarity: Horizontal



Test Mode: 00; Polarity: Horizontal



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2396.14	23.52	27.64	3.45	0.00	54.61	71.22	-16.61	HORIZONTAL	Average
2	2466.48	79.38	27.73	3.48	0.00	110.59	----	----	HORIZONTAL	Peak
3	2505.49	22.40	27.78	3.49	0.00	53.67	71.22	-17.55	HORIZONTAL	Average



6.5 Output Power Measurement

Test Requirement: 47 CFR Part 18
 Test Method: FCC OST/MP-5:1986
 Test Engineer: Lily Kuang
 Limit:

Power output Measurement:

Formula:

$$P = \frac{4,187 \cdot m_w (T_2 - T_1) + 0,55 \cdot m_c (T_2 - T_0)}{t}$$

NOTE :

P is the microwave power output, in watts
 m_w is the mass of the water, in grams
 m_c is the mass of the container, in grams
 T₀ is the ambient temperature, in degrees Celsius
 T₁ is the initial temperature of the water, in degrees Celsius
 T₂ is the final temperature of the water, in degrees Celsius
 t is the heating time, in seconds, excluding the magnetron filament heating-up time.

Input Power Measurement:

The EUT was set up according to the MP-5 for input power measurement, the input power and current was measured using a power analyzer. Water load in a beaker was located in the center of the oven and the microwave oven was set to maximum power.

Base on the measured input power it was found that the microwave oven can operating as the user manual's specifications.

6.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Humidity: 54.9 % RH Atmospheric Pressure: 1007 mbar

6.5.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	Test the EUT in microwave mode with maximum power.



6.5.3 Measurement Procedure and Data

Mass of water (g)	Mass of the container (g)	Ambient temperature (°C)	Initial temperature (°C)	Final temperature (°C)	Heating time (s)	Power output (W)
1101	657	20.1	10.1	20.2	44	1059.0

Input Voltage (V)	Input Current (A)	Power Factor	Measured input power (W)	Rated input power (W)
119.96	10.75	0.935	1206	1200



6.6 Operating Frequency Measurement

Test Requirement: 47 CFR Part 18
 Test Method: FCC OST/MP-5:1986
 Test Engineer: Lily Kuang
 Limit:
 Frequency Range: 2400-2500 MHz
 Detector: Average for the final result for outside ISM band(2450MHz±50MHz)
 Outside band limit: (a) ISM equipment operation on a frequency specified in §18.301 is permitted unlimited radiated energy in the band specified for that frequency.
 (b) The field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following:

RF Power generated by equipment(watts)	Field strength Limit(uV/m) @300m
Below 500	25
500 or more	25*SQRT(power/500)

Power =1059.0 W according to clause 6.1.2

Limit=20lg(25*SQRT(power/500))+20lg(300/3)=71.22dBuV/m @ 3m distance.

ISM band: ISM equipment may be operated on any frequency above 9 kHz.
 And the frequency band 2400-2500MHz is allocated for use by ISM equipment.

(§18.301)

ISM frequency	Tolerance
6.78MHz	±15.0kHz
13.56MHz	±7.0kHz
27.12MHz	±163.0kHz
40.68MHz	±20.0kHz
915MHz	±13.0MHz
2450MHz	±50.0MHz
5800MHz	±75.0MHz
24125MHz	±125.0MHz
61.25GHz	±250.0MHz
122.5GHz	±500.0MHz
245.00GHz	±1.0GHz

6.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 23.6 °C Humidity: 54.9 % RH Atmospheric Pressure: 1007 mbar




6.6.2 Test Mode Description

Pre-scan/	Mode	Description
Final test	Code	
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.6.3 Measurement Procedure and Data

Test Mode: 00; The variation of frequency with time



	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2399.08	23.10	27.65	3.45	0.00	54.20	71.22	-17.02	VERTICAL	Average
2	2466.48	75.80	27.73	3.48	0.00	107.01	---	---	VERTICAL	Peak
3	2528.95	21.05	27.80	3.50	0.00	52.35	71.22	-18.87	VERTICAL	Average

The variation of frequency with time

The operating frequency was measured using a spectrum analyzer, the supply voltage was setting at the rated AC voltage, measured was start with EUT at room temperature, the operating frequency was monitored until the water load was reduced to 20 percent of the original quantity.

Test record was found the worst situation is when the water load is reduced to 20 percent of the original quantity.

ISM frequency(MHz)	Tolerance(MHz)	Measurement Data(MHz)
2450	±50	2466.48



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Test Mode: 00; The variation of frequency with line voltage



	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2396.14	23.52	27.64	3.45	0.00	54.61	71.22	-16.61	HORIZONTAL	Average
2	2466.48	79.38	27.73	3.48	0.00	110.59	----	----	HORIZONTAL	Peak
3	2505.49	22.40	27.78	3.49	0.00	53.67	71.22	-17.55	HORIZONTAL	Average

The variation of frequency with line voltage.

The operating frequency was measured using a spectrum analyzer, the supply voltage was setting at the rated AC voltage, measured was start with EUT at room temperature. The EUT was started to warm by at least 10 minutes, the operating frequency was monitored as the rated voltage was varied from 80% to 125%.

Test record was found the worst situation is when the line voltage is 125% of rated AC voltage.

ISM frequency(MHz)	Tolerance(MHz)	Measurement Data(MHz)
2450	±50	2466.48

6.7 Radiation Hazard Test

Test Requirement: 47 CFR Part 18
 Test Method: FCC OST/MP-5:1986
 Test Engineer: Bob Qu

6.7.1 E.U.T. Operation

Operating Environment:
 Temperature: 19.1 °C Humidity: 54.7 % RH Atmospheric Pressure: 1024 mbar

6.7.2 Test Mode Description

Pre-scan/	Mode	Description
Final test	Code	
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.7.3 Measurement Procedure and Data

Maximum measure level (mW/cm ²)	Limit (mW/cm ²)	Test Result
0.088	1	Pass



7 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZEM260200105001



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

8 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for GZEM2602001050HS

- End of the Report -

