

TEST REPORT

Application No.: GZEM2509006414HS

Applicant: Guangdong Galanz Enterprises Co., Ltd.

Address of Applicant: 25 Ronggui Nan.Rd., Shunde, Foshan, Guangdong., China

Manufacturer: Guangdong Galanz Appliances Manufacturing Co., Ltd.

Address of Manufacturer: No. 3, East Xingpu Avenue, Maxin Industrial Zone, Huangpu Town, Zhongshan City, Guangdong Province, China

Factory: Guangdong Galanz Appliances Manufacturing Co., Ltd.

Address of Factory: No. 3, East Xingpu Avenue, Maxin Industrial Zone, Huangpu Town, Zhongshan City, Guangdong Province, China

Product Name: Microwave Oven

Model No.: D90D25ASPRIII-WF(L2), D90D25(X)RIII-(Y), D90D25(X)RIII-(Y)(L2)
Variable (X) may be AL, AP, APH, DAPH, ASL, ASP, ATL, ATP, EL, EP, ESL, ESP, ETL, ETP, ML, MP, MSL, MSP, MTL, MTP, MYL.
Variable (Y) may compose by one to five characters from A to Z and/or numbers from 0 to 9.
SMC0985KS, SMC0985KSC, ZSMC0985KS ♣

♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Trade Mark: Galanz, SHARP

Standard(s) : 47 CFR Part 18

Date of Receipt: 2025-09-29

Date of Test: 2025-10-11 to 2025-10-22



Date of Issue: 2025-11-04

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Revision Record			
Version	Report No.	Date	Remark
01	GZEM250900641402	2025-11-04	Original

Authorized for issue by:			
			
		Damon Guan/Project Engineer	
Approved By			
		Terry Lai/Reviewer	



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 18	FCC/OST MP-5:1986	18.307	Pass
Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Radiated Emissions (30MHz-1GHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Radiated Emissions (above 1GHz)		FCC/OST MP-5:1986	18.305(b)	Pass
Output Power Measurement		FCC OST/MP-5:1986	FCC OST/MP-5:1986 Clause 4.3	Pass
Operating Frequency Measurement		FCC OST/MP-5:1986	18.301	Pass
Radiation Hazard Test		FCC OST/MP-5:1986	1 mW/cm ²	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

♣Declaration of EUT Family Grouping:

Model No.: D90D25ASPRIII-WF(L2), D90D25(X)RIII-(Y), D90D25(X)RIII-(Y)(L2)

Variable (X) may be AL, AP, APH, DAPH, ASL, ASP, ATL, ATP, EL, EP, ESL, ESP, ETL, ETP, ML, MP, MSL, MSP, MTL, MTP, MYL.

Variable (Y) may compose by one to five characters from A to Z and/or numbers from 0 to 9.

SMC0985KS, SMC0985KSC, ZSMC0985KS

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference on the outer appearance, model name.

There are two kinds of DC motor (configure DC motor PCB)

Manufacture	Model
ZHAOLI	D6T30H2B02
Galanz	GAL-WBLDC001

Therefore only one model D90D25ASPRIII-WF(L2) with D6T30H2B02 motor was test full items, one model D90D25ASPRIII-WF(L2) with GAL-WBLDC001 motor was tested Conducted Emissions at Mains Terminals (150kHz-30MHz), Radiated Emissions (30MHz-1GHz) in this report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	6
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Emission Test Results	11
6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)	11
6.1.1 E.U.T. Operation	11
6.1.2 Test Mode Description	11
6.1.3 Test Setup Diagram	11
6.1.4 Measurement Procedure and Data	12
6.2 Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)	16
6.2.1 E.U.T. Operation	16
6.2.2 Test Mode Description	16
6.2.3 Test Setup Diagram	16
6.2.4 Measurement Procedure and Data	17
6.3 Radiated Emissions (30MHz-1GHz)	21
6.3.1 E.U.T. Operation	21
6.3.2 Test Mode Description	21
6.3.3 Test Setup Diagram	21
6.3.4 Measurement Procedure and Data	22
6.4 Radiated Emissions (above 1GHz)	26
6.4.1 E.U.T. Operation	26
6.4.2 Test Mode Description	26
6.4.3 Test Setup Diagram	26
6.4.4 Measurement Procedure and Data	27
6.5 Output Power Measurement	37
6.5.1 E.U.T. Operation	37
6.5.2 Test Mode Description	37
6.5.3 Measurement Procedure and Data	38
6.6 Operating Frequency Measurement	39
6.6.1 E.U.T. Operation	40
6.6.2 Test Mode Description	40
6.6.3 Measurement Procedure and Data	40
6.7 Radiation Hazard Test	43



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.7.1	E.U.T. Operation	43
6.7.2	Test Mode Description	43
6.7.3	Measurement Procedure and Data	43
7	Test Setup Photo	44
8	EUT Constructional Details (EUT Photos)	45



4 General Information

4.1 Details of E.U.T.

Power supply: AC 120V, 60Hz
Test voltage: AC 120V 60Hz
Microwave frequency: 2450MHz±50MHz
Cable(s): About 1.0m x 3 wires unscreened AC mains cable.

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

1000mL of water in the beaker for power output and frequency measurement.
One of 700 and the other of 300mL of water for second and third harmonic radiation measurement.
700mL of water for all other measurement

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at Mains Terminals (150kHz-30MHz)	3.22dB (150kHz to 30MHz)
Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)	± 3.12dB
Radiated Emissions (30MHz-1GHz)	5.14dB (30MHz-1GHz):3m; 4.90dB (30MHz-1GHz):10m
Radiated Emissions (above 1GHz)	4.88dB (1GHz-6GHz); 5.06dB (6GHz-18GHz)
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty) or U_{ETSI} (ETSI Uncertainty). Emission decision rule: – Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report. – Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report.	

4.4 Test Location

All tests were performed at:
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663
Tel: +86 20 82155555
No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Coaxial Cable	HangTianXing	2m	EMC0107	2025-08-12	2026-08-11
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	2025-08-14	2028-08-13
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2025-08-13	2026-08-12
EMI Test Receiver (9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2024-12-04	2025-12-03
Test Software E3r	Audix	Ver.6.191211	GZE100-77	N/A	N/A
Artificial Mains Network (LISN)	AFJ Instruments	LT32C	EMC2046	2025-08-12	2026-08-11

Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-12-03	2025-12-02
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2024-04-16	2026-04-15
EMI Test Receiver (1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-12-03	2025-12-02
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2024-12-04	2026-12-03

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-12-03	2025-12-02
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-12-03	2025-12-02
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2238	2025-03-24	2027-03-23
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2024-12-04	2026-12-03
Test Software E3	Audix	Ver.6.191211	GZE100-81	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-TRF-01 Rev 2.0

Report No.: GZEM250900641402

Page: 9 of 45

Radiated Emissions (above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2025-08-11	2026-08-10
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2025-08-12	2026-08-11
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2025-08-12	2026-08-11
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-23	2026-12-22
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Output Power Measurement					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Digital thermometer	FLUKE	51_2	EMC2200	2025-07-10	2026-07-09
Digital power analyzer for harmonics & flicker testing	EMTEST	DPA 500N	EMC2235	2024-12-04	2025-12-03
Programmable multifunctional ac/dc power source	EMTEST	NETWAVE 7-400	EMC2234	2024-12-04	2025-12-03
NET.Control	EMTEST	Ver 3.2.3	GZE100-80	N/A	N/A

Operating Frequency Measurement					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-23	2026-12-22
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiation Hazard Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Electric Field Probe(100KHz-3GHz)	WANDEL & GOLTERMANN	EMR-20	EMC0907	2025-05-14	2026-05-13



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (Inspection & Testing Services)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-TRF-01 Rev 2.0

Report No.: GZEM250900641402

Page: 10 of 45

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2025-06-03	2026-06-02



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC-TRF-01) EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

6 Emission Test Results

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	47 CFR Part 18
Test Method:	FCC/OST MP-5:1986
Limit:	
Frequency Range:	150kHz to 30MHz
0.15 to 0.5 MHz:	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5 to 5 MHz:	56dB(μV) quasi-peak, 46dB(μV) average
5 to 30 MHz:	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz


6.1.1 E.U.T. Operation

Operating Environment:			
Temperature:	21.8 °C	Humidity:	53.3 % RH
		Atmospheric Pressure:	1015 mbar

6.1.2 Test Mode Description

Pre-scan / Mode	Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.1.3 Test Setup Diagram



6.1.4 Measurement Procedure and Data


Frequency range: 150KHz-30MHz

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

The red line show in graphic is the limit in standard used in this section.

Measured Level = Read level + Cable Loss + LISN Factor

Test Mode: 00; Line: Live line; with GAL-WBLDC001 motor




Pol : LINE
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.162	26.43	0.04	9.55	36.02	55.34	-19.32	Average
2	0.162	43.79	0.04	9.55	53.38	65.34	-11.96	QP
3	0.252	12.07	0.04	9.60	21.71	51.69	-29.98	Average
4	0.252	23.94	0.04	9.60	33.58	61.69	-28.11	QP
5	0.513	8.05	0.05	9.58	17.68	46.00	-28.32	Average
6	0.513	21.60	0.05	9.58	31.23	56.00	-24.77	QP
7	1.094	0.40	0.08	9.53	10.01	46.00	-35.99	Average
8	1.094	10.88	0.08	9.53	20.49	56.00	-35.51	QP
9	2.765	-1.47	0.15	9.55	8.23	46.00	-37.77	Average
10	2.765	9.41	0.15	9.55	19.11	56.00	-36.89	QP
11	16.226	17.12	0.34	9.84	27.30	50.00	-22.70	Average
12	16.226	22.01	0.34	9.84	32.19	60.00	-27.81	QP



Test Mode: 00; Line: Live line; with D6T30H2B02 motor




Pol : LINE
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.174	14.58	0.04	9.54	24.16	54.77	-30.61	Average
2	0.174	37.68	0.04	9.54	47.26	64.77	-17.51	QP
3	0.263	13.09	0.04	9.58	22.71	51.34	-28.63	Average
4	0.263	33.11	0.04	9.58	42.73	61.34	-18.61	QP
5	0.393	12.69	0.05	9.54	22.28	47.99	-25.71	Average
6	0.393	26.10	0.05	9.54	35.69	57.99	-22.30	QP
7	1.619	1.94	0.11	9.60	11.65	46.00	-34.35	Average
8	1.619	13.73	0.11	9.60	23.44	56.00	-32.56	QP
9	2.237	-0.31	0.13	9.57	9.39	46.00	-36.61	Average
10	2.237	14.13	0.13	9.57	23.83	56.00	-32.17	QP
11	16.839	13.26	0.35	9.84	23.45	50.00	-26.55	Average
12	16.839	18.97	0.35	9.84	29.16	60.00	-30.84	QP



Test Mode: 00; Line: Neutral Line; with GAL-WBLDC001 motor




Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.152	24.15	0.04	9.51	33.70	55.87	-22.17	Average
2	0.152	44.41	0.04	9.51	53.96	65.87	-11.91	QP
3	0.252	12.36	0.04	9.53	21.93	51.69	-29.76	Average
4	0.252	26.94	0.04	9.53	36.51	61.69	-25.18	QP
5	0.507	6.45	0.05	9.58	16.08	46.00	-29.92	Average
6	0.507	21.33	0.05	9.58	30.96	56.00	-25.04	QP
7	1.010	-0.42	0.07	9.56	9.21	46.00	-36.79	Average
8	1.010	10.74	0.07	9.56	20.37	56.00	-35.63	QP
9	2.540	-1.14	0.14	9.58	8.58	46.00	-37.42	Average
10	2.540	8.52	0.14	9.58	18.24	56.00	-37.76	QP
11	16.226	22.02	0.34	9.90	32.26	50.00	-17.74	Average
12	16.226	24.98	0.34	9.90	35.22	60.00	-24.78	QP



Test Mode: 00; Line: Neutral Line; with D6T30H2B02 motor



Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.155	15.73	0.04	9.52	25.29	55.74	-30.45	Average
2	0.155	35.69	0.04	9.52	45.25	65.74	-20.49	QP
3	0.339	3.54	0.05	9.52	13.11	49.22	-36.11	Average
4	0.339	22.11	0.05	9.52	31.68	59.22	-27.54	QP
5	0.454	6.23	0.05	9.56	15.84	46.80	-30.96	Average
6	0.454	21.59	0.05	9.56	31.20	56.80	-25.60	QP
7	1.331	6.62	0.09	9.55	16.26	46.00	-29.74	Average
8	1.331	16.86	0.09	9.55	26.50	56.00	-29.50	QP
9	2.033	2.33	0.13	9.52	11.98	46.00	-34.02	Average
10	2.033	17.80	0.13	9.52	27.45	56.00	-28.55	QP
11	14.517	7.03	0.32	9.90	17.25	50.00	-32.75	Average
12	14.517	18.60	0.32	9.90	28.82	60.00	-31.18	QP



6.2 Radiated Emissions (Magnetic field Strength)(9kHz-30MHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Limit:
 Measurement Distance: 3 m
 Frequency Range: 9kHz to 30MHz
 Detector: Peak for pre-scan, Average for the final result
 (200Hz Resolution Bandwidth for 9kHz to 150kHz;
 9kHz Resolution Bandwidth for 150kHz to 30MHz)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	850.2	Limit= $20\lg(25*\text{SQRT}(\text{power}/500))+20\lg(300/3)=\mathbf{70.26}$ dBuV/m @ 3m distance.


6.2.1 E.U.T. Operation

Operating Environment:
 Temperature: 22.6 °C Humidity: 50.0 % RH Atmospheric Pressure: 1015 mbar

6.2.2 Test Mode Description

Pre-scan / Mode	Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.2.3 Test Setup Diagram



6.2.4 Measurement Procedure and Data


Frequency range: 9KHz-30MHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by loop antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test Mode: 00; Polarity: Horizontal




Site : 966 Chamber
job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.012	64.83	20.74	0.01	32.72	52.86	70.26	-17.40	HORIZONTAL	Average
2	0.024	66.39	16.46	0.01	32.72	50.14	70.26	-20.12	HORIZONTAL	Average
3	0.058	62.60	14.84	0.01	32.72	44.73	70.26	-25.53	HORIZONTAL	Average
4	0.086	57.44	14.50	0.01	32.72	39.23	70.26	-31.03	HORIZONTAL	Average
5	0.115	57.57	14.74	0.01	32.72	39.60	70.26	-30.66	HORIZONTAL	Average
6	0.144	54.38	14.71	0.01	32.72	36.38	70.26	-33.88	HORIZONTAL	Average



Test Mode: 00; Polarity: Horizontal




Site : 966 Chamber
 job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.214	64.76	14.67	0.01	32.72	46.72	70.26	-23.54	HORIZONTAL	Average
2	0.315	61.25	14.63	0.01	32.72	43.17	70.26	-27.09	HORIZONTAL	Average
3	0.393	63.92	14.55	0.01	32.72	45.76	70.26	-24.50	HORIZONTAL	Average
4	1.147	57.11	13.39	0.05	32.70	37.85	70.26	-32.41	HORIZONTAL	Average
5	18.135	40.32	9.65	0.23	32.72	17.48	70.26	-52.78	HORIZONTAL	Average
6	21.486	37.97	8.79	0.25	32.73	14.28	70.26	-55.98	HORIZONTAL	Average



Test Mode: 00; Polarity: Vertical;




Site : 966 Chamber
 Job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.010	63.74	21.69	0.01	32.72	52.72	70.26	-17.54	VERTICAL	Average
2	0.013	66.38	20.16	0.01	32.72	53.83	70.26	-16.43	VERTICAL	Average
3	0.058	62.47	14.84	0.01	32.72	44.60	70.26	-25.66	VERTICAL	Average
4	0.086	58.75	14.50	0.01	32.72	40.54	70.26	-29.72	VERTICAL	Average
5	0.115	55.84	14.74	0.01	32.72	37.87	70.26	-32.39	VERTICAL	Average
6	0.144	55.74	14.71	0.01	32.72	37.74	70.26	-32.52	VERTICAL	Average



Test Mode: 00; Polarity: Vertical;



Site : 966 Chamber
 job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	0.174	66.31	14.68	0.01	32.72	48.28	70.26	-21.98	VERTICAL	Average
2	0.202	65.07	14.67	0.01	32.72	47.03	70.26	-23.23	VERTICAL	Average
3	0.327	63.68	14.62	0.01	32.72	45.59	70.26	-24.67	VERTICAL	Average
4	0.419	62.88	14.53	0.01	32.72	44.70	70.26	-25.56	VERTICAL	Average
5	1.147	55.83	13.39	0.05	32.70	36.57	70.26	-33.69	VERTICAL	Average
6	18.524	39.01	9.57	0.23	32.72	16.09	70.26	-54.17	VERTICAL	Average



6.3 Radiated Emissions (30MHz-1GHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Limit:
 Measurement Distance: 3 m
 Frequency Range: 30 MHz to 1 GHz
 Detector: Peak for pre-scan, average for the final result
 (120 kHz Resolution Bandwidth for 30 MHz to 1 GHz)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	850.2	Limit=20lg(25*SQRT(power/500))+20lg(300/3)= 70.26 dBuV/m @ 3m distance.


6.3.1 E.U.T. Operation

Operating Environment:
 Temperature: 22.6 °C Humidity: 50.2 % RH Atmospheric Pressure: 1015 mbar

6.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.3.3 Test Setup Diagram



6.3.4 Measurement Procedure and Data


Frequency range: 30MHz-1GHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test Mode: 00; Polarity: Horizontal; with GAL-WBLDC001 motor



Site : 966 Chamber
job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	56.395	42.60	19.30	0.40	32.78	29.52	70.26	-40.74	HORIZONTAL	Average
2	58.203	42.12	19.09	0.41	32.78	28.84	70.26	-41.42	HORIZONTAL	Average
3	248.552	42.62	17.56	0.88	32.84	28.22	70.26	-42.04	HORIZONTAL	Average
4	308.913	42.59	19.55	0.99	32.87	30.26	70.26	-40.00	HORIZONTAL	Average
5	494.199	36.02	23.44	1.29	32.94	27.81	70.26	-42.45	HORIZONTAL	Average
6	739.661	35.58	27.56	1.58	31.72	33.00	70.26	-37.26	HORIZONTAL	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC) EEC Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Test Mode: 00; Polarity: Horizontal; with D6T30H2B02 motor




Site : 966 Chamber
 job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	57.796	45.99	19.09	0.41	32.78	32.71	70.26	-37.55	HORIZONTAL	Average
2	100.934	45.85	14.86	0.54	32.70	28.55	70.26	-41.71	HORIZONTAL	Average
3	246.815	47.13	17.52	0.87	32.84	32.68	70.26	-37.58	HORIZONTAL	Average
4	257.422	46.29	17.82	0.91	32.85	32.17	70.26	-38.09	HORIZONTAL	Average
5	742.259	32.34	27.60	1.58	31.72	29.80	70.26	-40.46	HORIZONTAL	Average
6	824.597	35.22	29.13	1.68	31.56	34.47	70.26	-35.79	HORIZONTAL	Average



Test Mode: 00; Polarity: Vertical; with GAL-WBLDC001 motor




Site : 966 Chamber
 job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	34.276	40.98	18.46	0.32	32.76	27.00	70.26	-43.26	VERTICAL	Average
2	58.203	57.26	19.09	0.41	32.78	43.98	70.26	-26.28	VERTICAL	Average
3	97.456	46.19	14.35	0.53	32.70	28.37	70.26	-41.89	VERTICAL	Average
4	245.951	49.02	17.49	0.87	32.83	34.55	70.26	-35.71	VERTICAL	Average
5	499.425	33.71	23.61	1.29	32.94	25.67	70.26	-44.59	VERTICAL	Average
6	742.259	42.92	27.60	1.58	31.72	40.38	70.26	-29.88	VERTICAL	Average



Test Mode: 00; Polarity: Vertical; with D6T30H2B02 motor



Site : 966 Chamber
 Job :
 Model :
 Power :
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	58.203	54.05	19.09	0.41	32.78	40.77	70.26	-29.49	VERTICAL	Average
2	117.360	47.29	16.71	0.59	32.71	31.88	70.26	-38.38	VERTICAL	Average
3	126.772	42.41	17.63	0.61	32.72	27.93	70.26	-42.33	VERTICAL	Average
4	245.951	41.84	17.49	0.87	32.83	27.37	70.26	-42.89	VERTICAL	Average
5	492.469	40.31	23.38	1.28	32.94	32.03	70.26	-38.23	VERTICAL	Average
6	734.491	33.90	27.47	1.57	31.74	31.20	70.26	-39.06	VERTICAL	Average



6.4 Radiated Emissions (above 1GHz)

Test Requirement: 47 CFR Part 18
 Test Method: FCC/OST MP-5:1986
 Limit:
 Measurement Distance: 3 m
 Frequency Range: Above 1GHz
 Detector: Peak for pre-scan, Average for the final result
 (1MHz Resolution Bandwidth for 1000MHz Above)

Equipment:	Operating frequency:	RF Power generated by equipment (watts):	Limit dB(uV/m) average:
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	850.2	Limit= $20\lg(25*\text{SQRT}(\text{power}/500))+20\lg(300/3)=\mathbf{70.26}$ dBuV/m @ 3m distance.


6.4.1 E.U.T. Operation

Operating Environment:
 Temperature: 25.5 °C Humidity: 61.4 % RH Atmospheric Pressure: 1015 mbar

6.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.4.3 Test Setup Diagram



6.4.4 Measurement Procedure and Data


Frequency range: Above 1GHz

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by Horn antenna with 2 orthogonal polarities.

The red line show in graphic is the limit in standard used in this section.

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor


Test Mode: 00; Polarity: Vertical;



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2101.866	49.09	26.81	3.17	37.79	41.28	70.26	-28.98	VERTICAL	Average
2	4901.927	36.12	31.67	4.86	37.34	35.31	70.26	-34.95	VERTICAL	Average
3	7368.164	35.89	36.41	6.00	37.18	41.12	70.26	-29.14	VERTICAL	Average
4	9809.916	41.86	38.95	7.14	37.10	50.85	70.26	-19.41	VERTICAL	Average
5	12290.700	32.33	39.39	7.86	36.88	42.70	70.26	-27.56	VERTICAL	Average
6	14788.150	39.92	42.17	8.79	36.51	54.37	70.26	-15.89	VERTICAL	Average
7	17186.530	33.98	42.61	9.48	36.41	49.66	70.26	-20.60	VERTICAL	Average




Test Mode: 00; Polarity:



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	18570.600	41.36	36.92	3.14	39.24	42.18	70.26	-28.08	VERTICAL	Average
2	19624.290	42.24	36.94	3.05	40.13	42.10	70.26	-28.16	VERTICAL	Average
3	20977.590	37.52	37.69	3.22	38.75	39.68	70.26	-30.58	VERTICAL	Average
4	21507.910	41.43	37.60	3.28	39.37	42.94	70.26	-27.32	VERTICAL	Average
5	23433.360	38.57	38.59	3.38	38.04	42.50	70.26	-27.76	VERTICAL	Average
6	24455.770	41.93	38.70	3.42	38.79	45.26	70.26	-25.00	VERTICAL	Average




Test Mode: 00; Polarity: Vertical;



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4903.518	32.74	31.67	4.86	37.34	31.93	70.26	-38.33	VERTICAL
									Average




Test Mode: 00; Polarity: Vertical;



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	7364.099	30.94	36.41	6.00	37.18	36.17	70.26	-34.09	VERTICAL
									Average




Test Mode: 00; Polarity: Vertical;



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2396.726	21.75	27.64	3.45	0.00	52.84	70.26	-17.42	VERTICAL	Average
2	2459.837	83.19	27.72	3.47	0.00	114.38	-----	-----	VERTICAL	peak
3	2503.958	25.74	27.78	3.49	0.00	57.01	70.26	-13.25	VERTICAL	Average




Test Mode: 00; Polarity: Horizontal;



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2151.034	49.87	26.91	3.21	37.79	42.20	70.26	-28.06	HORIZONTAL	Average
2	4900.324	41.19	31.67	4.86	37.35	40.37	70.26	-29.89	HORIZONTAL	Average
3	7351.150	45.26	36.35	5.99	37.18	50.42	70.26	-19.84	HORIZONTAL	Average
4	9809.916	47.42	38.95	7.14	37.10	56.41	70.26	-13.85	HORIZONTAL	Average
5	12290.700	35.95	39.39	7.86	36.88	46.32	70.26	-23.94	HORIZONTAL	Average
6	14702.910	38.89	42.24	8.65	36.52	53.26	70.26	-17.00	HORIZONTAL	Average
7	17186.530	34.89	42.61	9.48	36.41	50.57	70.26	-19.69	HORIZONTAL	Average




Test Mode: 00; Polarity: Horizontal;



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	18298.100	42.36	36.69	3.08	39.15	42.98	70.26	-27.28	HORIZONTAL	Average
2	18871.940	44.10	37.06	3.20	39.29	45.07	70.26	-25.19	HORIZONTAL	Average
3	19792.630	45.37	37.03	3.02	40.32	45.10	70.26	-25.16	HORIZONTAL	Average
4	20901.920	41.38	37.64	3.21	38.83	43.40	70.26	-26.86	HORIZONTAL	Average
5	23028.900	41.00	38.50	3.33	38.17	44.66	70.26	-25.60	HORIZONTAL	Average
6	24576.570	40.36	38.76	3.41	39.27	43.26	70.26	-27.00	HORIZONTAL	Average


Test Mode: 00; Polarity: Horizontal;



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4902.558	38.37	31.67	4.86	37.34	37.56	70.26	-32.70	HORIZONTAL Average




Test Mode: 00; Polarity: Horizontal;



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	7355.240	42.90	36.35	5.99	37.18	48.06	70.26	-22.20	HORIZONTAL Average



Test Mode: 00; Polarity: Horizontal;



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2399.078	24.56	27.65	3.45	0.00	55.66	70.26	-14.60	HORIZONTAL Average
2	2461.647	76.68	27.73	3.48	0.00	107.89	-----	-----	HORIZONTAL peak
3	2506.107	21.78	27.78	3.49	0.00	53.05	70.26	-17.21	HORIZONTAL Average



6.5 Output Power Measurement

Test Requirement: 47 CFR Part 18

Test Method: FCC OST/MP-5:1986

Limit:

Power output Measurement:

Formula:

$$P = \frac{4,187 \cdot m_w (T_2 - T_1) + 0,55 \cdot m_c (T_2 - T_0)}{t}$$

NOTE :

P is the microwave power output, in watts

m_w is the mass of the water, in grams

m_c is the mass of the container, in grams

T₀ is the ambient temperature, in degrees Celsius

T₁ is the initial temperature of the water, in degrees Celsius

T₂ is the final temperature of the water, in degrees Celsius

t is the heating time, in seconds, excluding the magnetron filament heating-up time.

Input Power Measurement:

The EUT was set up according to the MP-5 for input power measurement, the input power and current was measured using a power analyzer. Water load in a beaker was located in the center of the oven and the microwave oven was set to maximum power.

Base on the measured input power it was found that the microwave oven can operating as the user manual's specifications.

6.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22.4 °C

Humidity: 52.6 % RH

Atmospheric Pressure: 1015 mbar

6.5.2 Test Mode Description

Pre-scan /	Mode	Description
Final test	Code	
Final test	00	Test the EUT in microwave mode with maximum power.



6.5.3 Measurement Procedure and Data

Mass of water (g)	Mass of the container (g)	Ambient temperature (°C)	Initial temperature (°C)	Final temperature (°C)	Heating time (s)	Power output (W)
1003	474	19.9	10	20.3	51	850.2

Input Power Data

Input Voltage (V)	Input Current (A)	Power Factor	Measured input power (W)	Rated input power (W)
120.1	13.08	0.928	1458	1500



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.6 Operating Frequency Measurement

Test Requirement: 47 CFR Part 18
 Test Method: FCC OST/MP-5:1986
 Limit:
 Frequency Range: 2400-2500 MHz
 Detector: Average for the final result for outside ISM band(2450MHz±50MHz)
 Outside band limit: (a) ISM equipment operation on a frequency specified in §18.301 is permitted unlimited radiated energy in the band specified for that frequency.

(b) The field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following:

RF Power generated by equipment(watts)	Field strength Limit(uV/m) @300m
Below 500	25
500 or more	25*SQRT(power/500)

Power =**850.2W** according to clause 6.1.2

Limit=**20lg(25*SQRT(power/500))+20lg(300/3)=70.26dBuV/m @ 3m distance.**

ISM band: ISM equipment may be operated on any frequency above 9 kHz.

And the frequency band 2400-2500MHz is allocated for use by ISM equipment.

(§18.301)

ISM frequency	Tolerance
6.78MHz	±15.0kHz
13.56MHz	±7.0kHz
27.12MHz	±163.0kHz
40.68MHz	±20.0kHz
915MHz	±13.0MHz
2450MHz	±50.0MHz
5800MHz	±75.0MHz
24125MHz	±125.0MHz
61.25GHz	±250.0MHz
122.5GHz	±500.0MHz
245.00GHz	±1.0GHz



6.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C Humidity: 61.4 % RH Atmospheric Pressure: 1015 mbar


6.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.6.3 Measurement Procedure and Data



Test Mode: 00; Polarity: Vertical;



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2396.726	21.75	27.64	3.45	0.00	52.84	70.26	-17.42	VERTICAL
2	2459.837	83.19	27.72	3.47	0.00	114.38	-----	-----	VERTICAL
3	2503.958	25.74	27.78	3.49	0.00	57.01	70.26	-13.25	VERTICAL

The variation of frequency with time

The operating frequency was measured using a spectrum analyzer, the supply voltage was setting at the rated AC voltage, measured was start with EUT at room temperature, the operating frequency was monitored until the water load was reduced to 20 percent of the original quantity.

Test record was found the worst situation is when the water load is reduced to 20 percent of the original quantity.

ISM frequency(MHz)	Tolerance(MHz)	Measurement Data(MHz)
2450	±50	2459.837



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Test Mode: 00; Polarity: Horizontal;



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2399.078	24.56	27.65	3.45	0.00	55.66	70.26	-14.60	HORIZONTAL	Average
2461.647	76.68	27.73	3.48	0.00	107.89	-----	-----	HORIZONTAL	peak
2506.107	21.78	27.78	3.49	0.00	53.05	70.26	-17.21	HORIZONTAL	Average

The variation of frequency with line voltage.

The operating frequency was measured using a spectrum analyzer, the supply voltage was setting at the rated AC voltage, measured was start with EUT at room temperature. The EUT was started to warm by at least 10 minutes, the operating frequency was monitored as the rated voltage was varied from 80% to 125%.

Test record was found the worst situation is when the line voltage is 125% of rated AC voltage.

ISM frequency(MHz)	Tolerance(MHz)	Measurement Data(MHz)
2450	±50	2461.647



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC) EEC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

6.7 Radiation Hazard Test

Test Requirement: 47 CFR Part 18
Test Method: FCC OST/MP-5:1986

6.7.1 E.U.T. Operation

Operating Environment:
Temperature: 22.5 °C Humidity: 50.5 % RH Atmospheric Pressure: 1015 mbar

6.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	Test the EUT in microwave mode with maximum power.
Pre-scan	01	Test the EUT in microwave mode with middle power.
Pre-scan	02	Test the EUT in microwave mode with lowest power.

6.7.3 Measurement Procedure and Data

Maximum measure level (mW/cm ²)	Limit (mW/cm ²)	Test Result
0.579	1	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (EMC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

7 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZEM250900641402



8 EUT Constructional Details (EUT Photos)

Refer to Appendix - External and Internal Photos for GZEM2509006414HS

- End of the Report -

