

RF Exposure Report

Report No.: SA150122E07

FCC ID: UIDSBG6900

Test Model: SBG6900-AC

Received Date: Jan. 22, 2015

Test Date: Mar. 11 to 12, 2015

Issued Date: Mar. 24, 2015

Applicant: ARRIS Group, Inc.

Address: 3871 Lakefield Drive Suite 300 Suwanee, GA30024

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	5
4 Calculation Result of Maximum Conducted Power	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150122E07	Original release.	Mar. 24, 2015

1 Certificate of Conformity

Product: Wireless Cable Modem & Router

Brand: ARRIS

Test Model: SBG6900-AC

Sample Status: ENGINEERING SAMPLE

Applicant: ARRIS Group, Inc.

Test Date: Mar. 11 to 12, 2015


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Mar. 24, 2015
Lori Chung / Specialist

Approved by : , **Date:** Mar. 24, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 29cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

2.4GHz								
Antenna No.	PCB Chain No.	Brand	Model	Ant. Gain(dBi) <Including cable loss>	Frequency range (GHz to GHz)	Ant. Type	Connector Type	Cable Length (mm)
361.00624.005	1	FIT	FX02A04-0G-EF	3.72	2.4~2.4835	PCB	i-pex(MHF)	185
361.00625.005	2	FIT	FX02A05-0G-EF	4.59	2.4~2.4835	PCB	i-pex(MHF)	111
361.00626.005	0	FIT	FX02A06-0G-EF	4.2	2.4~2.4835	PCB	i-pex(MHF)	210
5GHz								
Antenna No.	PCB Chain No.	Brand	Model	Ant. Gain(dBi) <Including cable loss>	Frequency range (GHz to GHz)	Ant. Type	Connector Type	Cable Length (mm)
361.00628.005	1	FIT	FX02A07-0G-EF	5.59	5.15~5.85	PCB	i-pex(MHF)	120
361.00629.005	2	FIT	FX02A08-0G-EF	3.42	5.15~5.85	PCB	i-pex(MHF)	190
361.00630.005	0	FIT	FX02A10-0G-EF	3.88	5.15~5.85	PCB	i-pex(MHF)	255

4 Calculation Result of Maximum Conducted Power

CDD MODE

For 15.247:

802.11b

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	300.9	8.95	29	0.22357	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

802.11g

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	541.786	8.95	29	0.40255	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

VHT20

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	598.855	8.95	29	0.44495	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

VHT40

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2422-2452	223.357	8.95	29	0.16596	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

For 15.407:

802.11a

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	469.588	9.12	29	0.36284	1
5745-5825	638.049	9.12	29	0.49300	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

802.11ac (VHT20)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	483.992	9.12	29	0.37397	1
5745-5825	651.264	9.12	29	0.50321	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

802.11ac (VHT40)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5190-5230	267.197	9.12	29	0.20645	1
5755-5795	531.625	9.12	29	0.41077	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

802.11ac (VHT80)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5210	160.238	9.12	29	0.12381	1
5775	94.227	9.12	29	0.07281	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

Beamforming MODE

For 15.247:

VHT20

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	489.08	8.95	29	0.36339	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

VHT40

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2422-2452	186.699	8.95	29	0.13872	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.95\text{dBi}$$

For 15.407:

802.11ac (VHT20)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	306.853	9.12	29	0.23710	1
5745-5825	303.129	9.12	29	0.23422	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

802.11ac (VHT40)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5190-5230	248.09	9.12	29	0.19169	1
5755-5795	352.462	9.12	29	0.27234	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

802.11ac (VHT80)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5210	105.496	9.12	29	0.08151	1
5775	50.708	9.12	29	0.03918	1

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.12\text{dBi}$$

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.44495 + 0.50321 = 0.948

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---