



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313
33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372
3162 BELICK STREET • SANTA CLARA, CALIFORNIA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372
13501 MCCALLEN PASS • AUSTIN, TX 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

March 23, 2017

ARRIS Group, Inc.
3871 Lakefield Drive Suite 300
Suwanee, GA 30024

Dear Tony Figueiredo,

Enclosed is the EMC Wireless test report for compliance testing of the ARRIS Group, Inc., SBG7400 as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Title 47 of the CFR, Part 15.407, Subpart E (UNII 3).

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Joel Huna
Documentation Department

Reference: (\ARRIS Group, Inc.\ EMC89524B-FCC407 UNII 3 Rev. 1)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CALIFORNIA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

13501 MCCALLEN PASS • AUSTIN, TX 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

Electromagnetic Compatibility Criteria Test Report

for the

**ARRIS Group, Inc.
Model SBG7400**

Tested under
The FCC Certification Rules
contained in
Title 47 of the CFR
15.407 Subpart E

MET Report: EMC89524B-FCC407 UNII 3 Rev. 1

March 23, 2017

Prepared For:

**ARRIS Group, Inc.
3871 Lakefield Drive Suite 300
Suwanee, GA 30024**

Prepared By:
MET Laboratories, Inc.
914 West Patapsco Avenue,
Baltimore MD 21230

Electromagnetic Compatibility Criteria Test Report

for the

ARRIS Group, Inc.
Model SBG7400

Tested under
The FCC Certification Rules
contained in
Title 47 of the CFR
15.407 Subpart E



Hadid Jones, Project Engineer
Electromagnetic Compatibility Lab



Joel Huna
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of Parts 15.407, of the FCC Rules under normal use and maintenance.



Asad Bajwa,
Director, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	March 13, 2017	Initial Issue.
1	March 23, 2017	Engineer corrections.

Table of Contents

I.	Executive Summary	1
	A. Purpose of Test	2
	B. Executive Summary	2
II.	Equipment Configuration	3
	A. Overview	4
	B. References	5
	C. Test Site	5
	D. Description of Test Sample	5
	E. Equipment Configuration	6
	F. Support Equipment	6
	G. Ports and Cabling Information	6
	H. Mode of Operation	7
	I. Method of Monitoring EUT Operation	7
	J. Modifications	7
	a) Modifications to EUT	7
	b) Modifications to Test Standard	7
	K. Disposition of EUT	7
III.	Electromagnetic Compatibility Criteria for Intentional Radiators	8
	§ 15.203 Antenna Requirement	9
	§ 15.407(a)(3) Maximum Conducted Output Power	10
	§ 15.407(a)(3) Maximum Power Spectral Density	17
	§ 15.407(b)(4) & (6 - 7) Undesirable Emissions	24
	§ 15.407(b)(6) Conducted Emissions	34
	§ 15.407(e) 6 dB Bandwidth	36
	§ 15.247(i) Maximum Permissible Exposure	43
	§ 15.407(g) Frequency Stability	44
IV.	Test Equipment	51
V.	Certification & User's Manual Information	53
	A. Certification Information	54
	B. Label and User's Manual Information	58

List of Tables

Table 1. Executive Summary of EMC Part 15.407 Compliance Testing	2
Table 2. EUT Summary.....	4
Table 3. References	5
Table 4. Equipment Configuration	6
Table 5. Support Equipment.....	6
Table 6. Ports and Cabling Information	6
Table 7. Maximum Conducted Output Power, Test Results	11
Table 8. Power Spectral Density, Test Results.....	18
Table 9. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	34
Table 10. 6 dB Bandwidth, Test Results	37
Table 11. Test Equipment List	52

List of Figures

Figure 1. Block Diagram of Test Configuration.....	5
--	---

List of Plots

Plot 1. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211a, MSC0, P3230, CH0	12
Plot 2. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211ac, MCS24, P3230 CH0	12
Plot 3. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211n, MSC24, P3230, CH0	12
Plot 4. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211a, MSC0, P3230, CH0	13
Plot 5. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0	13
Plot 6. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211n, MSC24, P3230, CH0	13
Plot 7. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211a MSC0 P3230, CH0	14
Plot 8. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211ac, MSC24, P3230, CH0	14
Plot 9. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211n MSC24, P3230, CH0	14
Plot 10. Maximum Conducted Output Power, BW 40M, Ch 5755M, 80211ac, MCS24 P3230, CH0	15
Plot 11. Maximum Conducted Output Power, BW 40M, Ch 5755M, 80211n, MSC24 P3230, CH0	15
Plot 12. Maximum Conducted Output Power, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0	15
Plot 13. Maximum Conducted Output Power, BW 40M, Ch 5795M, 80211n, MSC24, P3230, CH0	16
Plot 14. Maximum Conducted Output Power, BW 80M, Ch 5775M, 80211ac, MSC24, P3230, CH0	16
Plot 15. Power Spectral Density, BW 20M, Ch 5745M, 80211a, MSC0, P3230, CH0	19
Plot 16. Power Spectral Density, BW 20M, Ch 5745M, 80211ac, MCS24, P3230, CH0	19
Plot 17. Power Spectral Density, BW 20M, Ch 5745M, 80211n, MSC24, P3230, CH0	19
Plot 18. Power Spectral Density, BW 20M, Ch 5785M, 80211a, MSC0, P3230, CH0	20
Plot 19. Power Spectral Density, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0	20
Plot 20. Power Spectral Density, BW 20M, Ch 5785M, 80211n, MSC24, P3230, CH0	20
Plot 21. Power Spectral Density, BW 20M, Ch 5825M, 80211a, MSC0, P3230, CH0	21
Plot 22. Power Spectral Density, BW 20M, Ch 5825M, 80211ac, MSC24, P3230, CH0	21
Plot 23. Power Spectral Density, BW 20M, Ch 5825M, 80211n, MSC24, P3230, CH0	21
Plot 24. Power Spectral Density, BW 40M, Ch 5755M, 80211ac, MCS24, P3230 CH0	22
Plot 25. Power Spectral Density, BW 40M, Ch 5755M, 80211n, MCS24, P3230, CH0	22
Plot 26. Power Spectral Density, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0	22
Plot 27. Power Spectral Density, BW 40M, Ch 5795M, 80211n, MSC24, P3230, CH0	23
Plot 28. Power Spectral Density, BW 80M, Ch 5775M, 80211ac, MSC24, P3230, CH0	23
Plot 29. Undesirable Emissions, BW 20M, Ch 5745M, 80211a, MCS0, P3230	25
Plot 30. Undesirable Emissions, BW 20M, Ch 5745M, 80211ac, MCS24, P3230	25
Plot 31. Undesirable Emissions, BW 20M, Ch 5745M, 80211n, MCS24, P3230	25
Plot 32. Undesirable Emissions, BW 20M, Ch 5825M, 80211a, MCS0, P3230	26

Plot 33. Undesirable Emissions, BW 20M, Ch 5825M, 80211ac, MCS24, P3230	26
Plot 34. Undesirable Emissions, BW 20M, Ch 5825M, 80211n, MCS24, P3230	26
Plot 35. Undesirable Emissions, BW 40M, Ch 5755M, 80211ac, MCS24, P3230	27
Plot 36. Undesirable Emissions, BW 40M, Ch 5755M, 80211n, MCS24, P3230	27
Plot 37. Undesirable Emissions, BW 40M, Ch 5795M, 80211ac, MCS24, P3230	27
Plot 38. Undesirable Emissions, BW 40M, Ch 5795M, 80211n, MCS24, P3230	28
Plot 39. Undesirable Emissions, BW 80M, Ch 5775M, 7-18GHz	28
Plot 40. Undesirable Emissions, BW 80M, Ch 5775M, 80211ac, MCS24, P3230	28
Plot 41. Undesirable Emissions, 7-18GHz	29
Plot 42. Undesirable Emissions, 30M – 1GHz-18GHz	29
Plot 43. Band Edge, BW 20M, Ch 5745M, 80211a, MCS0, P3230	30
Plot 44. Band Edge, BW 20M, Ch 5745M, 80211ac, MCS24, P3230	30
Plot 45. Band Edge, BW 20M, Ch 5745M, 80211n, MCS24, P3230	30
Plot 46. Band Edge, BW 20M, Ch 5825M, 80211a, MCS0, P3230	31
Plot 47. Band Edge, BW 20M, Ch 5825M, 80211ac, MCS24, P3230	31
Plot 48. Band Edge, BW 20M, Ch 5825M, 80211n, MCS24, P3230	31
Plot 49. Band Edge, BW 40M, Ch 5755M, 80211ac, MCS24, P3230	32
Plot 50. Band Edge, BW 40M, Ch 5755M, 80211n, MCS24, P3230	32
Plot 51. Band Edge, BW 40M, Ch 5795M, 80211ac, MCS24, P3230	32
Plot 52. Band Edge, BW 40M, Ch 5795M, 80211n, MCS24, P3230	33
Plot 53. Band Edge, BW 80M, Ch 5775M, 80211ac, MCS24, P3230	33
Plot 54. Conducted Emissions, Neutral	35
Plot 55. Conducted Emissions, Phase	35
Plot 56. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211a, MCS0, P3230, CH0	38
Plot 57. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211ac, MCS24, P3230, CH0	38
Plot 58. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211n, MCS16, P3230, CH0	38
Plot 59. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211a, MCS0, P3230, CH0	39
Plot 60. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0	39
Plot 61. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211n, MCS16, P3230, CH0	39
Plot 62. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211a, MCS0, P3230, CH0	40
Plot 63. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211ac, MCS24, P3230, CH0	40
Plot 64. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211n, MCS16, P3230, CH0	40
Plot 65. 6 dB Bandwidth, BW 40M, Ch 5755M, 80211ac, MCS24, P3230, CH0	41
Plot 66. 6 dB Bandwidth, BW 40M, Ch 5755M, 80211n, MCS16, P3230, CH0	41
Plot 67. 6 dB Bandwidth, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0	41
Plot 68. 6 dB Bandwidth, BW 40M, Ch 5795M, 80211n, MCS16, P3230, CH0	42
Plot 69. 6 dB Bandwidth, BW 80M, Ch 5775M, 80211ac, MCS24, P3230, CH0	42
Plot 70. Frequency Stability, 80211a BW 20MHz	45
Plot 71. Frequency Stability, 80211ac BW 20MHz	45
Plot 72. Frequency Stability, 80211n BW 20MHz	45
Plot 73. Frequency Stability, 80211n BW 40MHz	46
Plot 74. Frequency Stability, 80211ac BW 40MHz	46
Plot 75. Frequency Stability, 80211ac BW 80MHz	46
Plot 76. Frequency Stability, 80211a BW 20MHz	47
Plot 77. Frequency Stability, 80211ac BW 20MHz	47
Plot 78. Frequency Stability, 80211n BW 20MHz	47
Plot 79. Frequency Stability, 80211n BW 40MHz	48
Plot 80. Frequency Stability, 80211ac BW 40MHz	48
Plot 81. Frequency Stability, 80211ac BW 80MHz	48
Plot 82. Frequency Stability, 80211a BW 20MHz	49
Plot 83. Frequency Stability, 80211ac BW 20MHz	49
Plot 84. Frequency Stability, 80211n BW 20MHz	49
Plot 85. Frequency Stability, 80211n BW 40MHz	50
Plot 86. Frequency Stability, 80211ac BW 40MHz	50
Plot 87. Frequency Stability, 80211ac BW 80MHz	50

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dBμA	Decibels above one microamp
dBμV	Decibels above one microvolt
dBμA/m	Decibels above one microamp per meter
dBμV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	Kilohertz
kPa	Kilopascal
kV	Kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μH	Microhenry
μ	Microfarad
μs	Microseconds
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the ARRIS Group, Inc. SBG7400, with the requirements of Part 15, §15.407. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the SBG7400. ARRIS Group, Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the SBG7400, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.407, in accordance with ARRIS Group, Inc., purchase order number AR1098306. All tests were conducted using measurement procedure ANSI C63.4-2014.

FCC Reference	Description	Results
§15.203	Antenna Requirement	Compliant
§15.407 (a)(3)	Maximum Conducted Output Power	Compliant
§15.407 (a)(3)	Maximum Power Spectral Density	Compliant
§15.407 (b)(4)& (6 - 7)	Undesirable Emissions	Compliant
§15.407(b)(6)	Conducted Emission Limits	Compliant
§15.407(e)	6 dB Bandwidth	Compliant
§15.407(f)	RF Exposure	Compliant
§15.407(g)	Frequency Stability	Compliant

Table 1. Executive Summary of EMC Part 15.407 Compliance Testing

II. Equipment Configuration

A. Overview

MET Laboratories, Inc. was contracted by ARRIS Group, Inc. to perform testing on the SBG7400, under ARRIS Group, Inc.'s purchase order number AR1098306.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the ARRIS Group, Inc. SBG7400.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	SBG7400		
Model(s) Covered:	SBG7400		
EUT Specifications:	Primary Power: 12VDC, 2.5A via 115V/60Hz Adapter		
	FCC ID: UIDSBG7400		
	Type of Modulations:	OFDM	
	Equipment Code:	NII	
	Max. RF Output Power:	21.45dBm	
	EUT Frequency Ranges:	5745-5820 MHz	
Analysis:	The results obtained relate only to the item(s) tested.		
Environmental Test Conditions:	Temperature: 15-35° C		
	Relative Humidity: 30-60%		
	Barometric Pressure: 860-1060 mbar		
Evaluated by:	Hadid Jones		
Report Date(s):	March 23, 2017		

Table 2. EUT Summary

B. References

CFR 47, Part 15, Subpart E	Unlicensed National Information Infrastructure Devices (UNII)
ANSI C63.4:2014	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ISO/IEC 17025:2005	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
789033 D02 General UNII Test Procedures New Rules v01r03	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E

Table 3. References

C. Test Site

All testing was performed at MET Laboratories, Inc., 914 West Patapsco Avenue, Baltimore MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Description of Test Sample

The ARRIS Group, Inc. SBG7400, Equipment Under Test (EUT), is identical to TG2482 except no telephony circuitry.

The TG2482 is Telephony Gateway with 802.11ac Dual Band Wireless radios; 3x3 2.4GHz 802.11n and 4x4 5GHz 802.11ac Wave 2.




Figure 1. Block Diagram of Test Configuration

Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Slot #	Name / Description	Model Number	Part Number	Serial Number	Rev. #
4		UUT	SBG7400			

Table 4. Equipment Configuration

E. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number	*Customer Supplied Calibration Data
2s	Laptop	Assorted	N/A	N/A

The 'Customer Supplied Calibration Data' column will be marked as either not applicable, not available, or will contain the calibration date supplied by the customer.

Table 5. Support Equipment

F. Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty	Length as tested (m)	Max Length (m)	Shielded? (Y/N)	Termination Box ID & Port Name
2C	Ethernet	5e Modular 8 pin	1	1	1	No	
3C	DC Input	2 conductor	1	2		No	
4C	Serial	USB to 9 pin D-Sub	1	0.25		No	

Table 6. Ports and Cabling Information

G. Mode of Operation

The provided instructions and software will configure the unit for operation at each required test mode. See Configuration.

H. Method of Monitoring EUT Operation

All indicator lights are active, both Wi-Fi 2.4G and 5 G passing traffic.

I. Modifications

a) Modifications to EUT

No modifications were made to the EUT.

b) Modifications to Test Standard

No modifications were made to the test standard.

J. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to ARRIS Group, Inc. upon completion of testing.

III. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement: § 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results: The EUT as tested is compliant the criteria of §15.203. The EUT has integral antennas. The EUT also has test ports for conducted measurements.

Test Engineer(s): Hadid Jones

Test Date(s): February 26, 2017

Electromagnetic Compatibility Criteria for Intentional Radiators

§15.407(a)(3) Maximum Conducted Output Power

Test Requirements: §15.407(a)(3): For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.


If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power.

Test Procedure: The Maximum Conducted Output Power was measured according to KDB789033 v01r03 Method SA-1. The EUT was connected to the spectrum analyzer through an attenuator. The spectrum analyzer was configured in the following manner. The span was set to encompass the entire emission bandwidth of the signal. The RBW was set to 1MHz and the VBW was set to a value greater than or equal to 3x the RBW. An average detector was used with an auto sweep time. The trace was averaged over at least 100 traces. Power was computed by integrating the spectrum across the EBW of the signal using the instruments band power measurement function.

Test Results: The EUT as tested is compliant with the requirements of this section. Graphical data is presented for chain 0. Tabular data is presented for all chains. Data is uncorrelated for n and ac modes.


Test Engineer(s): Hadid Jones

Test Date(s): February 26, 2017




OutPut Power										
EUT MODE & PWR Setting	CH0 (dBm)	CH1 (dBm)	CH2 (dBm)	CH3 (dBm)	Duty Cycle CF (dB)	Σ (dBm)	Limit (dBm)	Gain (dBi)	Final Limit (dBm)	Margin (dB)
BW 20M_ Ch 5745M_ 80211a MCS0 P3230	15.76	14.47	14.26	14.84	1.02	20.85	30	10.52	25.48	-4.63
BW 20M_ Ch 5745M_ 80211ac MCS24 P3230	11.73	10.13	10.65	9.43	1.08	16.39	30	4.5	30	-13.61
BW 20M_ Ch 5745M_ 80211n MCS16 P3230	11.95	11.14	11.68	12.02	0.96	17.45	30	4.5	30	-12.55
BW 20M_ Ch 5785M_ 80211a MCS0 P3230	16.61	15.09	15.3	15.11	1.02	21.45	30	10.52	25.48	-4.03
BW 20M_ Ch 5785M_ 80211ac MCS24 P3230	13.36	11.95	11.82	12.51	1.08	18.50	30	4.5	30	-11.50
BW 20M_ Ch 5785M_ 80211n MCS16 P3230	12.65	11.08	12.13	12.63	0.96	17.91	30	4.5	30	-12.09
BW 20M_ Ch 5825M_ 80211a MCS0 P3230	16.18	15.41	15.6	15.31	1.02	21.44	30	10.52	25.48	-4.04
BW 20M_ Ch 5825M_ 80211ac MCS24 P3230	12.85	12.39	11.05	12.49	1.08	18.43	30	4.5	30	-11.57
BW 20M_ Ch 5825M_ 80211n MCS16 P3230	13.66	11.93	11.48	11.98	0.96	18.33	30	4.5	30	-11.67
BW 40M_ Ch 5755M_ 80211ac MCS24 P3230	10.76	9.89	9.9	11.24	1.08	16.52	30	4.5	30	-13.48
BW 40M_ Ch 5755M_ 80211n MCS16 P3230	11.39	11.1	11.5	11.55	0.96	17.08	30	4.5	30	-12.92
BW 40M_ Ch 5795M_ 80211ac MCS24 P3230	12.32	10.77	10.24	11.1	1.08	17.30	30	4.5	30	-12.70
BW 40M_ Ch 5795M_ 80211n MCS16 P3230	11.99	10.44	10.77	11.88	0.96	17.22	30	4.5	30	-12.78
BW 80M_ Ch 5775M_ 80211ac MCS24 P3230	10.6	8.71	8.23	9.29	1.08	15.46	30	4.5	30	-14.54


Table 7. Maximum Conducted Output Power, Test Results




Plot 1. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211a, MSC0, P3230, CH0




Plot 2. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211ac, MCS24, P3230 CH0




Plot 3. Maximum Conducted Output Power, BW 20M, Ch 5745M, 80211n, MSC24, P3230, CH0




Plot 4. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211a, MSC0, P3230, CH0




Plot 5. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0




Plot 6. Maximum Conducted Output Power, BW 20M, Ch 5785M, 80211n, MCS24, P3230, CH0




Plot 7. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211a MSC0 P3230, CH0




Plot 8. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211ac, MSC24, P3230, CH0




Plot 9. Maximum Conducted Output Power, BW 20M, Ch 5825M, 80211n MSC24, P3230, CH0




Plot 10. Maximum Conducted Output Power, BW 40M, Ch 5755M, 80211ac, MCS24 P3230, CH0




Plot 11. Maximum Conducted Output Power, BW 40M, Ch 5755M, 80211n, MSC24 P3230, CH0



Plot 12. Maximum Conducted Output Power, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0



Plot 13. Maximum Conducted Output Power, BW 40M, Ch 5795M, 80211n, MSC24, P3230, CH0



Plot 14. Maximum Conducted Output Power, BW 80M, Ch 5775M, 80211ac, MSC24, P3230, CH0

Electromagnetic Compatibility Criteria for Intentional Radiators

§15.407(a)(3) Maximum Power Spectral Density

Test Requirements: §15.407(a)(3): In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.


If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power.

Test Procedure: The Maximum Power Spectral Density was measured according to KDB789033 v01r03 Procedure F. The EUT was connected to the spectrum analyzer through an attenuator. The spectrum analyzer was configured in the following manner. The span was set to encompass the entire emission bandwidth of the signal. The RBW was set to 1MHz, and the VBW was set to a value greater than or equal to 3 times the RBW. An average detector was used with an auto sweep time. The trace was averaged over at least 100 traces. The peak search function was used to find the Maximum PSD over the 1MHz reference bandwidth.

Test Results: The EUT as tested is compliant with the requirements of this section. All chains were evaluated. Data is presented for chain 0. Data is uncorrelated for n and ac modes.


Test Engineer(s): Hadid Jones

Test Date(s): February 26, 2017




Power Spectral Density										
EUT MODE & PWR Setting	CH0 (dBm)	CH1 (dBm)	CH3 (dBm)	CH2 (dBm)	Duty Cycle CF (dB)	Σ (dBm)	Limit (dBm)	Gain (dBi)	Final Limit (dBm)	Margin (dB)
BW 20M_ Ch 5745M_ 80211a MCS0 P3230	5.55	4.52	4.04	5.37	1.02	10.96	30	10.52	12.48	-1.52
BW 20M_ Ch 5745M_ 80211ac MCS24 P3230	2.53	2.50	2.50	2.50	1.08	8.36	30	4.5	17	-8.64
BW 20M_ Ch 5745M_ 80211n MCS16 P3230	3.06	1.89	0.87	2.25	0.96	8.16	30	4.5	17	-8.84
BW 20M_ Ch 5785M_ 80211a MCS0 P3230	6.16	3.91	4.66	4.82	1.02	10.85	30	10.52	12.48	-1.63
BW 20M_ Ch 5785M_ 80211ac MCS24 P3230	3.61	1.65	1.38	2.92	1.08	8.65	30	4.5	17	-8.35
BW 20M_ Ch 5785M_ 80211n MCS16 P3230	2.65	2.03	2.50	3.04	0.96	8.32	30	4.5	17	-8.68
BW 20M_ Ch 5825M_ 80211a MCS0 P3230	5.90	5.49	6.16	4.33	1.02	11.08	30	10.52	12.48	-1.40
BW 20M_ Ch 5825M_ 80211ac MCS24 P3230	3.76	2.52	1.56	2.51	1.08	8.82	30	4.5	17	-8.18
BW 20M_ Ch 5825M_ 80211n MCS16 P3230	3.76	2.69	2.52	1.79	0.96	8.55	30	4.5	17	-8.45
BW 40M_ Ch 5755M_ 80211ac MCS24 P3230	-2.24	-2.54	-2.85	-1.40	1.08	3.82	30	4.5	17	-13.18
BW 40M_ Ch 5755M_ 80211n MCS16 P3230	-0.66	-0.47	-2.46	-2.39	0.96	4.70	30	4.5	17	-12.30
BW 40M_ Ch 5795M_ 80211ac MCS24 P3230	-1.24	-1.75	-3.08	-1.65	1.08	4.31	30	4.5	17	-12.69
BW 40M_ Ch 5795M_ 80211n MCS16 P3230	0.04	-1.56	-0.50	-0.28	0.96	5.18	30	4.5	17	-11.82
BW 80M_ Ch 5775M_ 80211ac MCS24 P3230	-3.93	-7.12	-5.62	-4.68	1.08	0.81	30	4.5	17	-16.19


Table 8. Power Spectral Density, Test Results




Plot 15. Power Spectral Density, BW 20M, Ch 5745M, 80211a, MSC0, P3230, CH0




Plot 16. Power Spectral Density, BW 20M, Ch 5745M, 80211ac, MCS24, P3230, CH0




Plot 17. Power Spectral Density, BW 20M, Ch 5745M, 80211n, MSC24, P3230, CH0




Plot 18. Power Spectral Density, BW 20M, Ch 5785M, 80211a, MSC0, P3230, CH0




Plot 19. Power Spectral Density, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0




Plot 20. Power Spectral Density, BW 20M, Ch 5785M, 80211n, MSC24, P3230, CH0




Plot 21. Power Spectral Density, BW 20M, Ch 5825M, 80211a, MSC0, P3230, CH0




Plot 22. Power Spectral Density, BW 20M, Ch 5825M, 80211ac, MSC24, P3230, CH0




Plot 23. Power Spectral Density, BW 20M, Ch 5825M, 80211n, MSC24, P3230, CH0




Plot 24. Power Spectral Density, BW 40M, Ch 5755M, 80211ac, MCS24, P3230 CH0




Plot 25. Power Spectral Density, BW 40M, Ch 5755M, 80211n, MCS24, P3230, CH0



Plot 26. Power Spectral Density, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0



Plot 27. Power Spectral Density, BW 40M, Ch 5795M, 80211n, MSC24, P3230, CH0



Plot 28. Power Spectral Density, BW 80M, Ch 5775M, 80211ac, MSC24, P3230, CH0

Electromagnetic Compatibility Criteria for Intentional Radiators

§15.407(b)(4) & (6 – 7) Undesirable Emissions

Test Requirements: § 15.407(b)(4): For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

§ 15.407(b)(6): Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Section 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in Section 15.207.

§ 15.407(b)(7): The provisions of Section 15.205 of this part apply to intentional radiators operating under this section.

Test Procedure: Unwanted Emissions were measured according to KDB789033 v01r03 Procedure G. Measurements below 1GHz were made with the EUT on a non-conducting stand 80cm above the ground plane of a semi-anechoic chamber. To find the direction of maximum emissions, the EUT was oriented through its three orthogonal axes while rotating the turntable 360 degrees and varying the height of the receive antenna. Measurements were made with the EUT transmitting on the low, mid, and high channels of each configuration. Final measurements from 30MHz to 1GHz were made using a quasi-peak detector with a RBW of 120 kHz.

Measurements above 1GHz were made with the EUT on a non-conducting stand 1.5m above the ground plane of a fully-anechoic chamber. To find the direction of maximum emissions, the EUT was oriented through its three orthogonal axes while rotating the chamber's turntable 360 degrees and varying the height of the receive antenna. Measurements were made with the EUT transmitting on the low, mid, and high channels of each configuration. Final measurements were made using peak and average detectors. Average measurements were made using a RBW of 1MHz and VBW less than the RBW but not less than 10Hz. Peak Measurements were made with a RBW of 1MHz and a VBW greater than or equal to 3 times the RBW.


Emissions below 30MHz and above 18GHz that were greater than 20dB below the limit are not reported.

The worse-case configuration is reported below 1GHz and above 7GHz.


Test Results: The EUT was compliant with the Radiated Emission limits for Intentional Radiators. See following pages for detailed test results. Data presented is corrected field strength.

Test Engineer(s): Hadid Jones


Test Date(s): February 28, 2017




Plot 29. Undesirable Emissions, BW 20M, Ch 5745M, 80211a, MCS0, P3230




Plot 30. Undesirable Emissions, BW 20M, Ch 5745M, 80211ac, MCS24, P3230




Plot 31. Undesirable Emissions, BW 20M, Ch 5745M, 80211n, MCS24, P3230




Plot 32. Undesirable Emissions, BW 20M, Ch 5825M, 80211a, MCS0, P3230




Plot 33. Undesirable Emissions, BW 20M, Ch 5825M, 80211ac, MCS24, P3230




Plot 34. Undesirable Emissions, BW 20M, Ch 5825M, 80211n, MCS24, P3230




Plot 35. Undesirable Emissions, BW 40M, Ch 5755M, 80211ac, MCS24, P3230




Plot 36. Undesirable Emissions, BW 40M, Ch 5755M, 80211n, MCS24, P3230




Plot 37. Undesirable Emissions, BW 40M, Ch 5795M, 80211ac, MCS24, P3230




Plot 38. Undesirable Emissions, BW 40M, Ch 5795M, 80211n, MCS24, P3230




Plot 39. Undesirable Emissions, BW 80M, Ch 5775M, 7-18GHz



Plot 40. Undesirable Emissions, BW 80M, Ch 5775M, 80211ac, MCS24, P3230




Plot 41. Undesirable Emissions, 7-18GHz




Plot 42. Undesirable Emissions, 30M – 1GHz-18GHz


Radiated Band Edge




Plot 43. Band Edge, BW 20M, Ch 5745M, 80211a, MCS0, P3230




Plot 44. Band Edge, BW 20M, Ch 5745M, 80211ac, MCS24, P3230




Plot 45. Band Edge, BW 20M, Ch 5745M, 80211n, MCS24, P3230




Plot 46. Band Edge, BW 20M, Ch 5825M, 80211a, MCS0, P3230




Plot 47. Band Edge, BW 20M, Ch 5825M, 80211ac, MCS24, P3230




Plot 48. Band Edge, BW 20M, Ch 5825M, 80211n, MCS24, P3230




Plot 49. Band Edge, BW 40M, Ch 5755M, 80211ac, MCS24, P3230




Plot 50. Band Edge, BW 40M, Ch 5755M, 80211n, MCS24, P3230



Plot 51. Band Edge, BW 40M, Ch 5795M, 80211ac, MCS24, P3230



Plot 52. Band Edge, BW 40M, Ch 5795M, 80211n, MCS24, P3230



Plot 53. Band Edge, BW 80M, Ch 5775M, 80211ac, MCS24, P3230

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.407(b)(6) Conducted Emissions

Test Requirement(s): § 15.407 (b)(6): Any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

§ 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Σ line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 – 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

Table 9. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)


Test Procedure: The EUT was placed on a non-metallic table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-2014 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. Scans were performed with the transmitter on.

Test Results: The EUT was compliant with requirements of this section.


The peak data was more than 20dB below the quasi-peak limit in the worst case configuration.

Test Engineer(s): Hadid Jones

Test Date(s): February 26, 2017



Plot 54. Conducted Emissions, Neutral



Plot 55. Conducted Emissions, Phase

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.407(e) 6 dB Bandwidth


Test Requirements: § 15.407(e): Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure: **The 6dB Bandwidth was measured according to 789033 II C. 2.**
The EUT was connected to the spectrum analyzer through an attenuator. The automatic bandwidth measurement capability of the instrument was employed using the X dB bandwidth mode with X set to 6 dB. The RBW was set to 100 kHz. The VBW was set to 300 kHz. The detector was set to peak and trace to max hold. The EUT was operated at its maximum power level on the low, mid, and high test channels. The width of the emission that was 6dB down from the maximum emission was measured.

Test Results The 6 dB Bandwidth was compliant with the requirements of this section. Data is presented for chain 0. All chains are compliant.


Test Engineer(s): Hadid Jones

Test Date(s): February 26, 2017




EUT Mode	6dB BW
6dB_BW 20M_Ch 5745M_80211a MCS0 P3230_CH0	14.462
6dB_BW 20M_Ch 5745M_80211ac MCS24 P3230_CH0	13.853
6dB_BW 20M_Ch 5745M_80211n MCS16 P3230_CH0	15.112
6dB_BW 20M_Ch 5785M_80211a MCS0 P3230_CH0	14.44
6dB_BW 20M_Ch 5785M_80211ac MCS24 P3230_CH0	14.243
6dB_BW 20M_Ch 5785M_80211n MCS16 P3230_CH0	15.047
6dB_BW 20M_Ch 5825M_80211a MCS0 P3230_CH0	15.092
6dB_BW 20M_Ch 5825M_80211ac MCS24 P3230_CH0	13.685
6dB_BW 20M_Ch 5825M_80211n MCS16 P3230_CH0	16.056
6dB_BW 40M_Ch 5755M_80211ac MCS24 P3230_CH0	33.878
6dB_BW 40M_Ch 5755M_80211n MCS16 P3230_CH0	35.328
6dB_BW 40M_Ch 5795M_80211ac MCS24 P3230_CH0	35.046
6dB_BW 40M_Ch 5795M_80211n MCS16 P3230_CH0	35.046
6dB_BW 80M_Ch 5775M_80211ac MCS24 P3230_CH0	75.209


Table 10. 6 dB Bandwidth, Test Results




Plot 56. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211a, MCS0, P3230, CH0




Plot 57. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211ac, MCS24, P3230, CH0




Plot 58. 6 dB Bandwidth, BW 20M, Ch 5745M, 80211n, MCS16, P3230, CH0




Plot 59. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211a, MCS0, P3230, CH0




Plot 60. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211ac, MCS24, P3230, CH0




Plot 61. 6 dB Bandwidth, BW 20M, Ch 5785M, 80211n, MCS16, P3230, CH0




Plot 62. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211a, MCS0, P3230, CH0




Plot 63. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211ac, MCS24, P3230, CH0




Plot 64. 6 dB Bandwidth, BW 20M, Ch 5825M, 80211n, MCS16, P3230, CH0




Plot 65. 6 dB Bandwidth, BW 40M, Ch 5755M, 80211ac, MCS24, P3230, CH0




Plot 66. 6 dB Bandwidth, BW 40M, Ch 5755M, 80211n, MCS16, P3230, CH0



Plot 67. 6 dB Bandwidth, BW 40M, Ch 5795M, 80211ac, MCS24, P3230, CH0



Plot 68. 6 dB Bandwidth, BW 40M, Ch 5795M, 80211n, MCS16, P3230, CH0



Plot 69. 6 dB Bandwidth, BW 80M, Ch 5775M, 80211ac, MCS24, P3230, CH0

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.407(f) Maximum Permissible Exposure

Test Requirement(s): §15.407(f): U-NII devices are subject to the radio frequency radiation exposure requirements specified in §1.1307(b), §2.1091 and §2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a “general population/uncontrolled” environment.

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission’s guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit: EUT’s operating frequencies @ 5725 - 5850 MHz; **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{(PG / 4\pi S)}$$

where, S = Power Density (mW/cm²)
P = Power Input to antenna (mW)
G = Antenna Gain (numeric value)
R = Distance (cm)

Test Results:

FCC									
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Pwr. Density (mW/cm ²)	Limit (mW/cm ²)	Margin	Distance (cm)	Result
5785	23.45	221.309	10.52	11.272	0.49628	1	0.50372	20	Pass
2462	26.18	414.954	7.8	6.026	0.49743	1	0.50257	20	Pass
MPE for co-location					0.99371			20	Pass

Con. Pwr. = maximum power + 2dBm tune-up tolerance

The safe distance where Power Density is less than the MPE Limit listed above was found to be 20 cm.

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.407(g) Frequency Stability

Test Requirements: § 15.407(g): Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


Test Procedure: The EUT was placed in an environmental chamber and powered through a variable supply. The RF port was connected to a spectrum analyzer through an attenuator. The EUT was set to transmit at the low and high channels and evaluated using the marker delta method. For the low channel, marker 1 was placed at the lower band edge frequency and marker 2 at the channels peak amplitude. This was repeated for the high channel. The EUT is considered compliant if the amplitude difference between markers 1 and 2 is at least 26dB. The EUT was evaluated at its extreme operating voltages and temperature conditions in 10 degree C increments. Data is presented for normal and extreme conditions.

Test Results: The EUT was found compliant with the requirements of this section.


Test Engineer(s): Hadid Jones

Test Date(s): March 10, 2017


Frequency Stability -20C 97VAC




Plot 70. Frequency Stability, 80211a BW 20MHz




Plot 71. Frequency Stability, 80211ac BW 20MHz




Plot 72. Frequency Stability, 80211n BW 20MHz



Plot 73. Frequency Stability, 80211n BW 40MHz




Plot 74. Frequency Stability, 80211ac BW 40MHz




Plot 75. Frequency Stability, 80211ac BW 80MHz


Frequency Stability 20C 115VAC




Plot 76. Frequency Stability, 80211a BW 20MHz




Plot 77. Frequency Stability, 80211ac BW 20MHz




Plot 78. Frequency Stability, 80211n BW 20MHz



Plot 79. Frequency Stability, 80211n BW 40MHz




Plot 80. Frequency Stability, 80211ac BW 40MHz




Plot 81. Frequency Stability, 80211ac BW 80MHz


Frequency Stability 40C 133VAC




Plot 82. Frequency Stability, 80211a BW 20MHz




Plot 83. Frequency Stability, 80211ac BW 20MHz




Plot 84. Frequency Stability, 80211n BW 20MHz



Plot 85. Frequency Stability, 80211n BW 40MHz



Plot 86. Frequency Stability, 80211ac BW 40MHz



Plot 87. Frequency Stability, 80211ac BW 80MHz

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1T4300A	SEMI-ANECHOIC CHAMBER # 1 (FCC)	EMC TEST SYSTEMS	NONE	1/31/2014	1/31/2017
1T4563	LISN (10 AMP)	SOLAR ELECTRONICS COMPANY	9322-50-R-10-BNC	8/27/2015	2/27/2017
1T4149	HIGH-FREQUENCY ANECHOIC CHAMBER	RAY PROOF	81	NOT REQUIRED	
1T4751	ANTENNA - BILOG	SUNOL SCIENCES	JB6	2/26/2016	8/26/2017
1T4483	ANTENNA; HORN	ETS-LINDGREN	3117	10/8/2015	4/8/2017
1T4745	ANTENNA, HORN	ETS-LINDGREN	3116	1/21/2017	7/21/2018
1T4612	SPECTRUM ANALYZER	AGILENT TECHNOLOGIES	E4407B	9/1/2015	3/1/2017

Table 11. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

K. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing;*
 - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
 - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
 - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
 - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
 - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
 - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

End of Report