



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

|                            |                                             |
|----------------------------|---------------------------------------------|
| <b>APPLICANT</b>           | NEW POTATO TECHNOLOGIES INC.                |
|                            | 5508 BUSINESS DR<br>WILMINGTON NC 28405 USA |
| <b>FCC ID</b>              | UIVMZA01                                    |
| <b>MODEL NUMBER</b>        | MZA01                                       |
| <b>PRODUCT DESCRIPTION</b> | AUDIO AMPLIFIER W/BT LE CONTROL             |
| <b>STANDARD APPLIED</b>    | CFR 47 Part 2.1091                          |
| <b>PREPARED BY</b>         | Tim Royer                                   |

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## **GENERAL REMARKS**

### **Attestations**

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.  
849 NW State Road 45  
Newberry, FL 32669**



**Authorized Signatory Name:**

Tim Royer, Engineer

**Date: 11/6/2017**

## RF Exposure Requirements

### **General information**

Device type: AUDIO AMPLIFIER W/BT LE CONTROL

### **Antenna**

| Configuration | Antenna p/n | Type | Max. Gain (dBi) |
|---------------|-------------|------|-----------------|
| Fixed mounted | Any         | omni | 0               |
| Integral      | Any         |      | -10dBi          |

### **MPE Calculation:**

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

**Minimum Separation Distance for Mobile or Fixed Devices  
General Population/Uncontrolled Exposure**

**Insert values in yellow highlighted boxes to determine Minimum Separation Distance**

|               |                             |               |                  |                   |
|---------------|-----------------------------|---------------|------------------|-------------------|
| Max Power     | <b>0.00009</b> W            | <i>equals</i> | Max Power        | <b>0.09</b> mW    |
| Duty Cycle    | <b>100</b> %                | <i>equals</i> | Duty Factor      | <b>1</b> numeric  |
| Antenna Gain  | <b>10</b> dBi               | <i>equals</i> | Gain numeric     | <b>10</b> numeric |
| Coax Loss     | <b>0</b> dB                 |               | Gain - Coax Loss | <b>10</b> numeric |
| Power Density | <b>1</b> mW/cm <sup>2</sup> |               |                  |                   |

**Enter power Density from the chart to the right**

Frequency **2462** MHz

**Rule Part 1.1310, Table 1 (B)**

| Frequency range | Power den          | Enter this value   |
|-----------------|--------------------|--------------------|
| MHz             | mW/cm <sup>2</sup> | mW/cm <sup>2</sup> |
| 0.3-1.34        | 100                | <b>100</b>         |
| 1.34-30         | 180/f <sup>2</sup> | <b>0.0</b>         |
| 30-300          | 0.2                | <b>0.2</b>         |
| 300-1,500       | f/1500             | <b>1.6</b>         |
| 1,500-100,000   | 1                  | <b>1</b>           |

f = frequency in MHz

**Minimum Separation Distance**

**0 cm**

**0.00 m**

Minimum Separation in Inches      0.105281 Inches