



(2004)量认(国)字(H2402)号

No.L1659

# FCC Part 15C (Bluetooth) TEST REPORT

*of*

## GSM 850/900/1800/1900 GPRS Mobile Phone

FCC ID: UJQ-06378T

Model No.: Pean

Serial No.: 1041608000001261

Report No.: FCC06-8083

Date: October 24, 2006

*Prepared for*

### Techfaith Wireless Communication Technology Limited

2/FM8 West, No.1 Jiu Xian Qiao Dong Road, Chao Yang District,  
Beijing, 100016, China

*Prepared by*

### ShenZhen Electronic Product Quality Testing Center

Electronic Testing Building, Shahe Road, Xili, Nanshan District, ShenZhen, 518055, P.R.China

Tel: 86 755 26627338 Fax: 86 755 26627238

This test report consists of 44 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

## Table of Contents

|   |                                                       |    |
|---|-------------------------------------------------------|----|
| 1 | Test Report Certification .....                       | 4  |
| 2 | General Information .....                             | 5  |
|   | 2.1 Description of EUT .....                          | 5  |
|   | 2.3 Test Standards and Results .....                  | 6  |
|   | 2.4 List of Test Equipments Used .....                | 6  |
|   | 2.5 Test Facility .....                               | 7  |
|   | 2.6 Environmental conditions .....                    | 7  |
| 3 | Conducted Emission Test .....                         | 8  |
|   | 3.1 Limits of Conducted Emission .....                | 8  |
|   | 3.2 Test Procedure .....                              | 8  |
|   | 3.3 Test Setup .....                                  | 9  |
|   | 3.4 EUT Setup and Operating Conditions .....          | 9  |
|   | 3.5 Test Results .....                                | 10 |
| 4 | Radiated Emission Test .....                          | 12 |
|   | 4.1 Limits of Radiated Emission .....                 | 12 |
|   | 4.2 Test Procedure .....                              | 12 |
|   | 4.3 Test Setup .....                                  | 13 |
|   | 4.4 EUT Setup and Operating Conditions .....          | 13 |
|   | 4.5 Test Results .....                                | 13 |
| 5 | Bandwidth and Carried Frequency Separation .....      | 28 |
|   | 5.1 Definition .....                                  | 28 |
|   | 5.2 Test Procedure .....                              | 28 |
|   | 5.3 Test Setup .....                                  | 28 |
|   | 5.4 EUT Setup and Operating Conditions .....          | 28 |
|   | 5.5 Test Results .....                                | 28 |
| 6 | Hopping Sequence .....                                | 29 |
|   | 6.1 Requirement of the standard .....                 | 29 |
|   | 6.2 Test Results .....                                | 29 |
| 7 | Equal Hopping Frequency Use .....                     | 29 |
|   | 7.1 Requirement of the standard .....                 | 29 |
|   | 7.2 Test Results .....                                | 29 |
| 8 | Receiver Input Bandwidth and Hopping Capability ..... | 29 |

|                                                           |    |
|-----------------------------------------------------------|----|
| 8.1 Requirement of the standard .....                     | 29 |
| 8.2 Test Results .....                                    | 29 |
| 9 Time of Occupancy (Dwell Time) .....                    | 30 |
| 9.1 Requirement of the Standard.....                      | 30 |
| 9.2 Test Procedure .....                                  | 30 |
| 9.3 Test Setup .....                                      | 30 |
| 9.4 EUT Setup and Operating Conditions.....               | 30 |
| 9.5 Test Results .....                                    | 30 |
| 10 Peak Output Power.....                                 | 31 |
| 10.1 Requirement of the standard .....                    | 31 |
| 10.2 Test Procedure .....                                 | 31 |
| 10.3 Test Setup .....                                     | 31 |
| 10.4 EUT Setup and Operating Conditions.....              | 31 |
| 10.5 Test Results .....                                   | 31 |
| 11 Band Edge .....                                        | 32 |
| 11.1 Requirement of the standard .....                    | 32 |
| 11.2 Test Procedure .....                                 | 32 |
| 11.3 Test Setup .....                                     | 32 |
| 11.4 EUT Setup and Operating Conditions.....              | 32 |
| 11.5 Test Results.....                                    | 32 |
| 12 Conducted Spurious Emission .....                      | 34 |
| 12.1 Requirement of the standard .....                    | 34 |
| 12.2 Test Procedure .....                                 | 34 |
| 12.3 Test Setup .....                                     | 34 |
| 12.4 EUT Setup and Operating Conditions.....              | 34 |
| 12.5 Test Results .....                                   | 35 |
| Appendix I : Photographs of the EUT.....                  | 37 |
| Appendix II : Photographs of the Test Configuration ..... | 42 |

# 1 Test Report Certification

**Product:** GSM 850/900/1800/1900 GPRS Mobile Phone

**FCC ID:** UJQ-06378T

**Model No.:** Pean

**Applicant:** Techfaith Wireless Communication Technology Limited

**Applicant Address:** 2/FM8 West, No.1 Jiu Xian Qiao Dong Road, Chao Yang District, Beijing, 100016, China

**Manufacturer:** Techfaith Wireless Communication Technology Limited

**Manufacturer Address:** 2/FM8 West, No.1 Jiu Xian Qiao Dong Road, Chao Yang District, Beijing, 100016, China

**Test Standards:** 47 CFR Part 15, Subpart C

**Test Result:** PASS

We, Shenzhen Electronic Product Quality Testing Center, hereby certify that the submitted samples of the above item, as detailed in chapter 2.1 of this report, has been tested in our facility. The test record, data evaluation and test configuration represented herein are true and accurate accounts of measurements of the sample's EMC characteristics under the conditions herein specified.

Tested by: Lin Xingsun, Date: Oct. 20, 2006  
Lin Xingsun

Checked by: Smart Li, Date: Oct. 24, 2006  
Smart Li

Approved by: Wu Li An, Date: Oct. 24, 2006  
Wu Li An



## 2 General Information

### 2.1 Description of EUT

|                            |                                         |
|----------------------------|-----------------------------------------|
| <b>Description:</b>        | GSM 850/900/1800/1900 GPRS Mobile Phone |
| <b>Model No.:</b>          | Peaen                                   |
| <b>Serial No.:</b>         | 1041608000001261                        |
| <b>Hardware Version:</b>   | P1                                      |
| <b>Software Version:</b>   | TF_WM5_PEAEN_VER_01.02                  |
| <b>Modulation</b>          | FHSS                                    |
| <b>Frequency:</b>          | 2402MHz – 2480 MHz                      |
| <b>Number of Channels:</b> | 79                                      |
| <b>Rated Power:</b>        | $\leq 6\text{dBm}$                      |
| <b>Bluetooth Antenna:</b>  | Permanent attached<br>Gain = -2.8 dBi   |

**NOTE:**

1. The EUT is a GSM mobile phone. It supports Bluetooth function, operating at 2.4GHz ISM band. The Bluetooth modulation is Frequency Hopping Spread Spectrum (FHSS). The Channels and transmitter center frequencies are:  $F(\text{MHz})=2401+1*n$ ,  $1 \leq n \leq 79$ .
2. Please refer to Appendix I for the photographs of the EUT. For a more detailed features description about the EUT, please refer to User's Manual.

### 2.2 Objective

Perform EMC test according to FCC Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiator).

## 2.3 Test Standards and Results

The EUT has been tested according to 47 CFR Part 15, Radio Frequency Devices.

Test items and the results are as bellow:

| No | FCC Rules             | Test Type                                       | Result | Test Date  |
|----|-----------------------|-------------------------------------------------|--------|------------|
| 1  | §15.207               | Conducted Emission                              | PASS   | 2006.10.21 |
| 2  | §15.209<br>§15.247(c) | Radiated Emission                               | PASS   | 2006.10.22 |
| 3  | §15.247(a)            | Bandwidth and Carrier Frequency Separation      | PASS   | 2006.10.20 |
| 4  | §15.247(a)            | Hopping Sequence                                | PASS   | --         |
| 5  | §15.247(a)            | Equal Hopping Frequency Use                     | PASS   | --         |
| 6  | §15.247(a)            | Receiver Input Bandwidth and Hopping Capability | PASS   | --         |
| 7  | §15.247(a)            | Time of Occupancy(Dwell time)                   | PASS   | 2006.10.20 |
| 8  | §15.247(b)            | Peak Output Power                               | PASS   | 2006.10.20 |
| 9  | §15.247(c)            | Band Edge                                       | PASS   | 2006.10.20 |
| 10 | §15.247(c)            | Conducted Spurious Emission                     | PASS   | 2006.10.20 |

## 2.4 List of Test Equipments Used

| Description          | Manufacturer    | Model No.              | Cal. Due Date | Serial No. |
|----------------------|-----------------|------------------------|---------------|------------|
| Test Receiver        | Rohde & Schwarz | ESIB26                 | 2007.06.05    | A0304218   |
| Test Receiver        | Schwarzbeck     | FCKL1528               | 2007.06.05    | A0304230   |
| Spectrum Analyzer    | Rohde & Schwarz | FSP13                  | 2006.12.25    | M-030176   |
| LISN                 | Schwarzbeck     | NSLK8127               | 2007.06.05    | A0304233   |
| Loop Antenna         | Rohde & Schwarz | HFH2-Z2                | 2007.06.05    | A0304220   |
| Ultra Broadband Ant. | Rohde & Schwarz | HL562                  | 2007.06.05    | A0304224   |
| Horn Ant.            | Rohde & Schwarz | HF906                  | 2007.06.05    | 100150     |
| Bluetooth Tester     | Rohde & Schwarz | CBT                    | 2007.09.26    | 100261     |
| Shield Room          | Nanbo Tech      | Site 1                 | 2007.01.17    | A0304188   |
| Anechoic Chamber     | Albatross       | EMC12.8×6.8×<br>6.4(m) | 2007.04.10    | A0304210   |

## 2.5 Test Facility

Shenzhen Electronic Product Quality Testing Center (SET) is a third party testing organization accredited by China National Accreditation Board for Laboratories (CNAL) according to ISO/IEC 17025. The accreditation certificate number is **L1659**.

The EMC chamber site No.1 (EMC12.8×6.8×6.4(m)), and the radiated and conducted Emission test equipments of SET are constructed and calibrated to meet the FCC requirements ANSI C63.4:2001 and CISPR 22/EN 55022. The FCC Registration Number is **261302**.

The EMC chamber site No.1 (EMC12.8×6.8×6.4(m)) also complies with Canada standard RSS 212, and acceptable to Industry Canada for the performance of radiated measurements. The Industry Canada Registration Number is **IC 5915**.

## 2.6 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

### 3 Conducted Emission Test

#### 3.1 Limits of Conducted Emission

According to FCC §15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

| Frequency range<br>(MHz) | Conducted Limit (dB $\mu$ V) |          |
|--------------------------|------------------------------|----------|
|                          | Quasi-peak                   | Average  |
| 0.15 - 0.50              | 66 to 56                     | 56 to 46 |
| 0.50 - 5                 | 56                           | 46       |
| 0.50 - 30                | 60                           | 50       |


**NOTE:**

1. The lower limit shall apply at the band edges.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

#### 3.2 Test Procedure

- a. The EUT was placed on a 0.8m high insulating table and kept 0.4 meters from the conducting wall of shielded room.
- b. The EUT was connected to the power mains through a line impedance stabilization network (LISN). The LISN provide 50 $\Omega$ /50 $\mu$ H of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150 kHz to 30 MHz was searched using CISPR Quasi-Peak and Average detector.

### 3.3 Test Setup



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

### 3.4 EUT Setup and Operating Conditions

The EUT configuration of the emission tests was MS + Battery + Charger.

During the measurement, the EUT was charging empty battery. The charger was powered by 120V 60Hz AC mains supply.

The Bluetooth function was active and an audio link was established between the EUT and a Bluetooth tester.

### 3.5 Test Results


| No. | Freq. (MHz) | Limit Value (dB $\mu$ V) |      | Emission Level (dB $\mu$ V) |      |
|-----|-------------|--------------------------|------|-----------------------------|------|
|     |             | QP                       | AV   | QP                          | AV   |
| 1   | 1.1625      | 56.0                     | 46.0 | 49.4                        | 34.9 |
| 2   | 1.7405      | 56.0                     | 46.0 | 49.7                        | 35.6 |
| 3   | 3.2350      | 56.0                     | 46.0 | 50.3                        | 38.5 |
| 4   | 5.0350      | 60.0                     | 50.0 | 41.4                        | 30.6 |
| 5   | 17.4000     | 60.0                     | 50.0 | 38.9                        | 32.0 |

**NOTE:**


1. QP and AV are abbreviations of the quasi-peak and average individually.
2. If the emission levels measured with QP detector are lower than AV limits, there is unnecessary to measure with AV detector.
3. The emission levels recorded above is the larger ones of both L phase and N phase.

## Test Plots

### 1. Mains terminal disturbance voltage, L phase



### 2. Mains terminal disturbance voltage, N phase



## 4 Radiated Emission Test

### 4.1 Limits of Radiated Emission

According to FCC §15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

According to FCC §15.209 (a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency(MHz) | Field Strength( $\mu$ V/m) | Measurement Distance(m) |
|----------------|----------------------------|-------------------------|
| 0.009 - 0.490  | 2400/F(kHz)                | 300                     |
| 0.490 - 1.705  | 24000/F(kHz)               | 30                      |
| 1.705 - 30.0   | 30                         | 30                      |
| 30 - 88        | 100                        | 3                       |
| 88 - 216       | 150                        | 3                       |
| 216 - 960      | 200                        | 3                       |
| Above 960      | 500                        | 3                       |

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules,


### 4.2 Test Procedure

- The EUT was placed on the top of a ratable 0.8 meters above the ground at a semi-anechoic chamber.
- In the frequency range of 9 kHz to 30 MHz, magnetic field was measured with loop antenna. The antenna was positioned with its plane vertical at 1 m distance from the EUT. The center of the loop was 1 m above the ground. During the measurement the loop antenna rotated about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, ultra-broadband bi-log antenna (30 MHz to 1 GHz) and horn antenna (above 1GHz) were used. Antenna was 3 meters away from the EUT. Antenna height was varied from one meter to four meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The test-receiver system was set to Peak Detector Function and Specified Bandwidth with

Maximum Hold Mode.

- e. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emission that did not have 10 dB margins would be retested one by one using the quasi-peak method.

### 4.3 Test Setup



For the actual test configuration, please refer to the related item-Photographs of the Test Configuration.

### 4.4 EUT Setup and Operating Conditions

A communication link was established between the EUT and a Bluetooth tester. The EUT set to test mode: transmitting 339 bytes DH5 packages with maximum power at low/mid/high channels.

### 4.5 Test Results

#### I. Fundamental Emissions

| EUT Operating Freq.<br>(MHz) | Antenna Polarization | Emission Level (dB $\mu$ V/m) |       |
|------------------------------|----------------------|-------------------------------|-------|
|                              |                      | PK                            | AV    |
| 2402.00                      | Vertical             | 91.65                         | 76.49 |
|                              | Horizontal           | 91.79                         | 76.23 |

|         |            |       |       |
|---------|------------|-------|-------|
| 2441.00 | Vertical   | 91.82 | 75.93 |
|         | Horizontal | 91.09 | 75.84 |
| 2480.00 | Vertical   | 92.16 | 76.14 |
|         | Horizontal | 92.57 | 76.37 |

**NOTE:** Field strength of fundamental emissions were measured and record as a reference for calculation of the band edge emissions according to Marker-Delta Method DA 00-705. See chapter 11.5.


## II. Spurious Emissions



| EUT Operating Freq. (MHz) | Emissions Falling in Restrict Bands (MHz) | Antenna Polarization | Emission Level (dB $\mu$ V/m) |    | QP Limits (dB $\mu$ V/m) |    |
|---------------------------|-------------------------------------------|----------------------|-------------------------------|----|--------------------------|----|
|                           |                                           |                      | PK                            | AV | PK                       | AV |
| 2402.00                   | No peak found                             | Vertical             | --                            | -- | 74                       | 54 |
|                           | No peak found                             | Horizontal           | --                            | -- | 74                       | 54 |
| 2441.00                   | No peak found                             | Vertical             | --                            | -- | 74                       | 54 |
|                           | No peak found                             | Horizontal           | --                            | -- | 74                       | 54 |
| 2480.00                   | No peak found                             | Vertical             | --                            | -- | 74                       | 54 |
|                           | No peak found                             | Horizontal           | --                            | -- | 74                       | 54 |



**NOTE:** The spurious Emissions from 9 kHz to 10th harmonic of the fundamental frequency were researched. Refer to following test plots.

### Test Plots

#### 1. Lowest channel 2402MHz, Vertical

















2. Lowest channel 2402MHz, Horizontal







## 3. Middle channel 2441MHz, Vertical











#### 4. Middle channel 2441MHz, Horizontal













### 5. Highest channel 2480MHz, Vertical









## 6. Highest channel 2480MHz, Horizontal





## 5 Bandwidth and Carried Frequency Separation


### 5.1 Definition

According to FCC §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.2 Test Procedure

- The EUT temporary antenna port was coupled to the spectrum analyzer. The loss of the cables the test system is calibrated to correct the reading.
- The spectrum analyzer was set to Maxpeak Detector function and Maximum Hold mode.
- The resolution bandwidth of the spectrum analyzer was set to at least 1% of the EUT emission bandwidth. RBW=10 kHz, VBW=30 kHz.

### 5.3 Test Setup



For the actual test configuration, please refer to the related item-Photographs of the Test Configuration.

### 5.4 EUT Setup and Operating Conditions

A communication link was established between the EUT and a Bluetooth tester. The EUT set to test mode: transmitting 339 bytes DH5 packages with maximum power at low/mid/high channels.

### 5.5 Test Results

| Operating Frequency ( MHz ) | 20dB Bandwidth(MHz) | Channel Separation |
|-----------------------------|---------------------|--------------------|
| 2402                        | 0.947               | 1.00MHz            |
| 2441                        | 0.950               |                    |
| 2480                        | 0.949               |                    |

The EUT had hopping channel carrier frequencies separated by the 20 dB bandwidth of the hopping channel.

## **6 Hopping Sequence**

### **6.1 Requirement of the standard**

According to FCC §15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies.

### **6.2 Test Results**

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. For details refer to the Bluetooth standard.

## **7 Equal Hopping Frequency Use**

### **7.1 Requirement of the standard**

According to FCC §15.247(a)(1), Each frequency must be used equally on the average by each transmitter.

### **7.2 Test Results**

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

## **8 Receiver Input Bandwidth and Hopping Capability**

### **8.1 Requirement of the standard**

According to FCC §15.247(a)(1), The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals

### **8.2 Test Results**

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

## 9 Time of Occupancy (Dwell Time)

### 9.1 Requirement of the Standard

According to FCC §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems which use fewer than 75 hopping frequencies may employ intelligent hopping techniques to avoid interference to other transmissions. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels are used.

### 9.2 Test Procedure

- a. The EUT temporary antenna port was coupled to the spectrum analyzer. The loss of the cables the test system is calibrated to correct the reading.
- b. The spectrum analyzer was set to Maxpeak Detector function and Maximum Hold mode.
- c. The resolution bandwidth of the spectrum analyzer was comparable to the EUT emission bandwidth. RBW=1 MHz, VBW=3 MHz.

### 9.3 Test Setup

Same as 5.3

### 9.4 EUT Setup and Operating Conditions

Refer to 5.4. The Bluetooth module was operating at maximum power output and hopping-on mode.

### 9.5 Test Results

Number of hopping channels is 79.

A channel was used 107 times within  $0.4 \times 79 = 31.6$  S.

Dwell time of each occupation in this channel is 2.96mS.

$2.96\text{mS} \times 107 = 0.317 \text{ S} < 0.4 \text{ S}$

## 10 Peak Output Power

### 10.1 Requirement of the standard

According to FCC §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band, the maximum peak output power of the intentional radiator shall not exceed 1 Watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts.

### 10.2 Test Procedure

- The EUT was coupled to the spectrum analyzer and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the reading.
- The spectrum analyzer was set to Maxpeak Detector function and Maximum Hold mode.
- The resolution bandwidth of the spectrum analyzer was comparable to the EUT emission bandwidth. RBW=1 MHz, VBW=3 MHz.

### 10.3 Test Setup

Same as 5.3

### 10.4 EUT Setup and Operating Conditions

Same as 5.4

### 10.5 Test Results

| Operating Frequency<br>( MHz ) | Peak Output Power |                      | Limit<br>(W) |
|--------------------------------|-------------------|----------------------|--------------|
|                                | (dBm)             | (W)                  |              |
| 2402                           | 1.6               | $1.4 \times 10^{-3}$ | 1            |
| 2441                           | 1.2               | $1.3 \times 10^{-3}$ | 1            |
| 2480                           | 1.5               | $1.4 \times 10^{-3}$ | 1            |

## 11 Band Edge

### 11.1 Requirement of the standard

According to FCC §15.247(c), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 11.2 Test Procedure

- a. The EUT was coupled to the spectrum analyzer and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the reading.
- b. The spectrum analyzer was set to Maxpeak Detector function and Maximum Hold mode.
- c. According to the standard requirement, the resolution bandwidth of the spectrum analyzer was set to RBW=100 kHz, VBW=300 kHz.

### 11.3 Test Setup

Same as 5.3

### 11.4 EUT Setup and Operating Conditions

Same as 5.4. Tests were also repeated in hopping mode.

### 11.5 Test Results


The radio frequency power beyond the band edges was 20dB below the peak output power, measured with 100 kHz resolution bandwidth. Refer to the following test plots.

Field strength of band edge emission falling in adjacent restricted bands (2310MHz-2390MHz and 2483.5MHz-2500MHz) per section 15.205(a) was calculated according to Marker-Delta Method DA 00-705. Refer to chapter 4.5 for step 1 in-band field strength measurement. The following test plots gave the “Delta Marker” of maximum band edge emissions falling in restricted bands relevant to the fundamental emissions. Calculation results in the following table shows compliance with the radiated emission limits specified in Section 15.209(a).

| Fundamental Emission |                         |          | Freq. of Max. Band Edges Emission (MHz) | Delta Marker (dB) | Calculated Max. Band Edges Emission Level (dBμV/m) | Limit (dBμV/m) |
|----------------------|-------------------------|----------|-----------------------------------------|-------------------|----------------------------------------------------|----------------|
| Freq.                | Field Strength (dBμV/m) | Detector |                                         |                   |                                                    |                |
| 2402.00              | 91.79                   | PK       | 2385.52                                 | 50.37             | 41.42                                              | 74             |
| 2402.00              | 76.49                   | AV       | 2385.52                                 | 50.37             | 26.12                                              | 54             |
| 2480.00              | 92.57                   | PK       | 2486.02                                 | 49.86             | 42.71                                              | 74             |
| 2480.00              | 76.37                   | AV       | 2486.02                                 | 49.86             | 26.51                                              | 54             |


## Band Edge Test Plots

### 1. Lowest channel, 2402MHz



Date: 20.OCT.2006 06:19:40

### 2. Highest channel, 2480MHz



Date: 20.OCT.2006 05:18:01

## 12 Conducted Spurious Emission

### 12.1 Requirement of the standard

According to FCC §15.247(c), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement..

### 12.2 Test Procedure

- a. The EUT was coupled to the spectrum analyzer and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the reading.
- b. The spectrum analyzer was set to Maxpeak Detector function and Maximum Hold mode.
- c. The spurious Emissions from 9 KHz to 10th harmonic of the fundamental frequency were researched.
- d. According to the standard requirement, the resolution bandwidth of the spectrum analyzer was set to RBW=100 kHz, VBW=300 kHz.

### 12.3 Test Setup

Same as 5.3

### 12.4 EUT Setup and Operating Conditions


Same as 5.4

## 12.5 Test Results


The following test plots shows that spurious emissions in the whole frequency range were below the 20dBc limit line.

### Conducted Spurious Emission Test Plots


#### 1. Lowest channel, 2402MHz



## 2. Middle channel, 2441MHz



## 3. Highest channel, 2480MHz



## Appendix I : Photographs of the EUT



### 1. Appearance of the MS



## 2. Inside of the MS









## Appendix II : Photographs of the Test Configuration

### 1. Conducted Emission Test




### 2. Radiated Emission Test (9 kHz -30 MHz)



### 3. Radiated Emission Test (30 MHz – 1 GHz)



### 4. Radiated Emission Test (above 1 GHz)



## 5. Conducted RF Test

