FCC Test Report

Report No.: RF191231C03-1

FCC ID: UK7-C1N

Test Model: C1NF1

Received Date: Dec. 31, 2019

Test Date: Jan. 06, 2020 ~ Feb. 09, 2020

Issued Date: Jul. 07, 2020

Applicant: Fossil Group, Inc.

Address: 901 S. Central Expy, Richardson, Texas, United States, 75080

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : B2F., No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

FCC Registration / Designation Number: 427177 / TW0011

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim any endorsement by TAF.

Table of Contents

Release Control Record **4**

1 Certificate of Conformity **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information **7**

3.1 General Description of EUT 7
3.2 Description of Test Modes 8
3.2.1 Test Mode Applicability and Tested Channel Detail 9
3.3 Duty Cycle of Test Signal 10
3.4 Description of Support Units 11
3.4.1 Configuration of System under Test 11
3.5 General Description of Applied Standards and References 11

4 Test Types and Results **12**

4.1 Radiated Emission and Bandedge Measurement 12
4.1.1 Limits of Radiated Emission and Bandedge Measurement 12
4.1.2 Test Instruments 13
4.1.3 Test Procedures 14
4.1.4 Deviation from Test Standard 14
4.1.5 Test Set Up 15
4.1.6 EUT Operating Conditions 16
4.1.7 Test Results 17
4.2 Conducted Emission Measurement 22
4.2.1 Limits of Conducted Emission Measurement 22
4.2.2 Test Instruments 22
4.2.3 Test Procedures 22
4.2.4 Deviation from Test Standard 23
4.2.5 Test Setup 23
4.2.6 EUT Operating Conditions 23
4.2.7 Test Results 24
4.3 6 dB Bandwidth Measurement 26
4.3.1 Limits of 6 dB Bandwidth Measurement 26
4.3.2 Test Setup 26
4.3.3 Test Instruments 26
4.3.4 Test Procedure 26
4.3.5 Deviation from Test Standard 26
4.3.6 EUT Operating Conditions 26
4.3.7 Test Results 27
4.4 Occupied Bandwidth Measurement 28
4.4.1 Test Setup 28
4.4.2 Test Instruments 28
4.4.3 Test Procedure 28
4.4.4 Deviation from Test Standard 28
4.4.5 EUT Operating Conditions 28
4.4.6 Test Results 29
4.5 Conducted Output Power Measurement 30
4.5.1 Limits of Conducted Output Power Measurement 30
4.5.2 Test Setup 30
4.5.3 Test Instruments 30
4.5.4 Test Procedures 30
4.5.5 Deviation from Test Standard 30
4.5.6 EUT Operating Conditions 30
4.5.7 Test Results 30

4.6 Power Spectral Density Measurement 31
4.6.1 Limits of Power Spectral Density Measurement 31
4.6.2 Test Setup 31
4.6.3 Test Instruments 31
4.6.4 Test Procedure 31
4.6.5 Deviation from Test Standard 31
4.6.6 EUT Operating Condition 31
4.6.7 Test Results 32
4.7 Conducted Out of Band Emission Measurement 33
4.7.1 Limits of Conducted Out of Band Emission Measurement 33
4.7.2 Test Setup 33
4.7.3 Test Instruments 33
4.7.4 Test Procedure 33
4.7.5 Deviation from Test Standard 33
4.7.6 EUT Operating Condition 33
4.7.7 Test Results 34

5 Pictures of Test Arrangements 36

Appendix – Information of the Testing Laboratories 37

Release Control Record

Issue No.	Description	Date Issued
RF191231C03-1	Original Release	Jul. 07, 2020

1 Certificate of Conformity

Product: Smart Watch

Brand: FOSSIL

Test Model: C1NF1

Sample Status: Identical Prototype

Applicant: Fossil Group, Inc.

Test Date: Jan. 06, 2020 ~ Feb. 09, 2020

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** Jul. 07, 2020
Shelly Hsueh / Specialist

Approved by : _____ , **Date:** Jul. 07, 2020
Dylan Chiou / Senior Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	**Test Item**	**Result**	**Remarks**
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -14.06 dB at 0.15800 MHz.
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -7.35 dB at 85.62 MHz.
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Reference only
15.247(b)	Conducted Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.79 dB
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Smart Watch
Brand	FOSSIL
Test Model	C1NF1
Status of EUT	Identical Prototype
Power Supply Rating	3.85 Vdc (Li-ion battery)
Modulation Type	GFSK
Transfer Rate	1 Mbps
Operating Frequency	2402 ~ 2480 MHz
Number of Channel	40
Output Power	1.208 mW
Antenna Type	Loop antenna with -5.15 dBi gain
Antenna Connector	N/A
Accessory Device	Refer to Note as below
Data Cable Supplied	N/A

Note:

1. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.

3.2 Description of Test Modes

40 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1 GHz **RE<1G:** Radiated Emission below 1 GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.
Note: "-"means no effect.

Radiated Emission Test (Above 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Radiated Emission Test (Below 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	19	GFSK	1

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	19	GFSK	1

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
APCM	25 deg. C, 65 % RH	3.85 Vdc	Gavin Wu

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

Duty cycle = 0.388/0.625 = 0.621, Duty factor = 10 * log(1/0.621) = 2.07



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Adapter	ASUS	AD827M	N/A	N/A

No.	Signal Cable Description Of The Above Support Units
1.	1m shielded cable

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Aug. 26, 2019	Aug. 25, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Apr. 15, 2019	Apr. 14, 2020
HORN Antenna ETS-Lindgren	3117	00143293	Nov. 24, 2019	Nov. 23, 2020
BILOG Antenna SCHWARZBECK	VULB 9168	9168-616	Nov. 12, 2019	Nov. 11, 2020
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020
Bluetooth Tester	CBT	100980	Jul. 14, 2019	Jul. 13, 2020
Loop Antenna	EM-6879	269	Sep. 16, 2019	Sep. 15, 2020
Preamplifier Agilent	310N	187226	Jun. 18, 2019	Jun. 17, 2020
Preamplifier Agilent	83017A	MY39501357	Jun. 18, 2019	Jun. 17, 2020
Preamplifier EMCI	EMC 184045	980116	Oct. 08, 2019	Oct. 07, 2020
Power Meter Anritsu	ML2495A	1012010	Sep. 04, 2019	Sep. 03, 2020
Power Sensor Anritsu	MA2411B	1315050	Sep. 04, 2019	Sep. 03, 2020
RF signal cable ETS-LINDGREN RF signal cable ETS-LINDGREN	5D-FB 8D-FB	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-400) Cable-CH1-02(RFC-SMS-100-SMS-24)	Jun. 18, 2019	Jun. 17, 2020
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1.3 Test Procedures

For Radiated Emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz. (RBW = 10 MHz, VBW = 10 MHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Set Up

<Radiated Emission below 30 MHz>



<Radiated Emission 30 MHz to 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

KDB 414788 OFS and Chamber Correlation Justification (For Radiated emission below 30MHz)

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

- Open-field site and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1 GHz Data:

EUT Test Condition		Measurement Detail	
Channel	Channel 0	**Frequency Range**	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2381.01	41.75	37.28	4.47	54	-12.25	179	359	Average
2381.01	52.09	47.62	4.47	74	-21.91	179	359	Peak
2402	80.58	76.06	4.52			179	359	Average
2402	81.58	77.06	4.52			179	359	Peak
4804	42.23	31.88	10.35	54	-11.77	156	284	Average
4804	48.41	38.06	10.35	74	-25.59	156	284	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2387.58	42.36	37.87	4.49	54	-11.64	219	360	Average
2387.58	51.26	46.77	4.49	74	-22.74	219	360	Peak
2402	81.68	77.16	4.52			219	360	Average
2402	82.56	78.04	4.52			219	360	Peak
4804	42.01	31.66	10.35	54	-11.99	127	53	Average
4804	48.14	37.79	10.35	74	-25.86	127	53	Peak

Remarks:

1. Emission Level = Read Level + Factor
   Margin value = Emission level – Limit value
2. 2402 MHz: Fundamental frequency.
3. The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 19	**Frequency Range**	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2376.6	42.02	37.55	4.47	54	-11.98	179	359	Average
2376.6	51.68	47.21	4.47	74	-22.32	179	359	Peak
2440	80.95	76.36	4.59			179	359	Average
2440	81.9	77.31	4.59			179	359	Peak
2488.92	42.3	37.62	4.68	54	-11.7	179	359	Average
2488.92	52.73	48.05	4.68	74	-21.27	179	359	Peak
4880	41.31	31.1	10.21	54	-12.69	184	134	Average
4880	47.61	37.4	10.21	74	-26.39	184	134	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2386.05	41.81	37.32	4.49	54	-12.19	219	360	Average
2386.05	51.13	46.64	4.49	74	-22.87	219	360	Peak
2440	81.71	77.12	4.59			219	360	Average
2440	82.63	78.04	4.59			219	360	Peak
2484.8	**42.39**	**37.73**	**4.66**	**54**	**-11.61**	**219**	**360**	**Average**
2484.8	53.37	48.71	4.66	74	-20.63	219	360	Peak
4880	41.71	31.5	10.21	54	-12.29	153	217	Average
4880	47.93	37.72	10.21	74	-26.07	153	217	Peak

Remarks:

1. Emission Level = Read Level + Factor
   Margin value = Emission level – Limit value
2. 2440 MHz: Fundamental frequency.
3. The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 39	**Frequency Range**	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2480	79.95	75.31	4.64			179	359	Average
2480	80.95	76.31	4.64			179	359	Peak
2487.12	42.31	37.65	4.66	54	-11.69	179	359	Average
2487.12	52.31	47.65	4.66	74	-21.69	179	359	Peak
4960	41.72	31.36	10.36	54	-12.28	171	231	Average
4960	47.96	37.6	10.36	74	-26.04	171	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
2480	81.19	76.55	4.64			219	360	Average
2480	82.27	77.63	4.64			219	360	Peak
2498.32	42.32	37.65	4.67	54	-11.68	219	360	Average
2498.32	51.65	46.98	4.67	74	-22.35	219	360	Peak
4960	41.24	30.88	10.36	54	-12.76	109	135	Average
4960	47.42	37.06	10.36	74	-26.58	109	135	Peak

Remarks:

1. Emission Level = Read Level + Factor
   Margin value = Emission level – Limit value
2. 2480 MHz: Fundamental frequency.
3. The emission levels of other frequencies were very low against the limit.

9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:

EUT Test Condition		Measurement Detail	
Channel	Channel 19	**Frequency Range**	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Karl Lee

Horizontal



Vertical



Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
85.62	**32.65**	**53**	**-20.35**	**40**	**-7.35**	**165**	**18**	**Peak**
195.24	33.2	51.59	-18.39	43.5	-10.3	134	26	Peak
260.85	20.89	37.56	-16.67	46	-25.11	118	208	Peak
378.4	28.06	42.34	-14.28	46	-17.94	178	188	Peak
501.6	28.14	40.43	-12.29	46	-17.86	199	269	Peak
926.5	31.8	37.42	-5.62	46	-14.2	124	163	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Factor (dB/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
91.29	27.69	46.49	-18.8	43.5	-15.81	150	5	Peak
211.98	24.95	43.02	-18.07	43.5	-18.55	111	18	Peak
278.13	27.42	43.86	-16.44	46	-18.58	118	283	Peak
472.2	26.37	39.27	-12.9	46	-19.63	142	127	Peak
720.7	30.14	38.94	-8.8	46	-15.86	105	162	Peak
853.7	29.39	36.12	-6.73	46	-16.61	188	54	Peak

Remarks:

1. Emission Level = Read Level + Factor
   Margin value = Emission level – Limit value
2. The emission levels of other frequencies were very low against the limit.

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Dec. 11, 2019	Dec. 10, 2020
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2019	Sep. 04, 2020
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ENV216	101196	Apr. 16, 2019	Apr. 15, 2020
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-12040.

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.2.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.2.7 Test Results

CONDUCTED WORST-CASE DATA

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH

Phase Of Power : Line (L)										
No	Frequency	Correction Factor	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.15800**	**9.67**	**34.42**	**31.84**	**44.09**	**41.51**	**65.57**	**55.57**	**-21.48**	**-14.06**
2	0.20600	9.66	28.83	26.37	38.49	36.03	63.37	53.37	-24.88	-17.34
3	0.23000	9.66	24.69	21.93	34.35	31.59	62.45	52.45	-28.10	-20.86
4	0.27400	9.67	20.85	18.06	30.52	27.73	61.00	51.00	-30.48	-23.27
5	0.45800	9.69	17.24	15.17	26.93	24.86	56.73	46.73	-29.80	-21.87
6	12.49800	9.95	13.91	11.97	23.86	21.92	60.00	50.00	-36.14	-28.08

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH

Phase Of Power : Neutral (N)										
No	Frequency	Correction Factor	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16600	9.64	29.88	23.93	39.52	33.57	65.16	55.16	-25.64	-21.59
2	0.19000	9.64	26.50	23.16	36.14	32.80	64.04	54.04	-27.90	-21.24
3	0.21400	9.64	23.04	20.89	32.68	30.53	63.05	53.05	-30.37	-22.52
4	0.24164	9.64	20.54	18.39	30.18	28.03	62.04	52.04	-31.86	-24.01
5	0.47400	9.66	16.25	14.63	25.91	24.29	56.44	46.44	-30.53	-22.15
6	6.74600	9.86	14.89	11.60	24.75	21.46	60.00	50.00	-35.25	-28.54

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 6 dB Bandwidth Measurement

4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Set resolution bandwidth (RBW) = 100 kHz
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Results

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.68	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.69	0.5	Pass

Spectrum Plot of Worst Value



4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.4.4 Deviation from Test Standard

No deviation.

4.4.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.6 Test Results

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
0	2402	1.06	Pass
19	2440	1.05	Pass
39	2480	1.05	Pass

Spectrum Plot of Worst Value



4.5 Conducted Output Power Measurement

4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Freq. (MHz)	Peak Power		Average Power		Power Limit (mW)	Pass / Fail
		(mW)	(dBm)	(mW)	(dBm)		
0	2402	0.9183	-0.37	0.869	-0.61	1000	Pass
19	2440	1.208	0.82	1.14	0.57	1000	Pass
39	2480	1.205	0.81	1.138	0.56	1000	Pass

4.6 Power Spectral Density Measurement

4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz band during any time interval of continuous transmission.

.

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d. Set the VBW ≥ 3 × RBW.
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 Test Results

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-15.15	8	Pass
19	2440	-13.90	8	Pass
39	2480	-13.98	8	Pass

Spectrum Plot of Worst Value



4.7 Conducted Out of Band Emission Measurement

4.7.1 Limits of Conducted Out of Band Emission Measurement

Below –20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.

Ch 0





Ch 19





Ch 39





Ch 0 Band Edge	Ch 39 Band Edge
	

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---