

Test report No:
NIE: 53898RAN.005

Assessment report

FCC 47 CFR Part 2.1091

ISED RSS-102 Issue 5:2015

Identification of item tested	Electronic Lock Series including all mechanical variants
Trademark	XS4 Original
Model and /or type reference	W09, W0B, W09W, W0BW, W0J, W0JW
Other identification of the product	FCC ID: UKCW0B IC: 10088A-W0B
Features	Not provided data
Applicant	SALTO Systems, S.L. Arkotz 9, Polígono Lanbarren 20180, Oiartzun, Gipuzkoa, SPAIN
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager  MIGUEL LACAVE GARCÍA 2018.06.27 12:44:54 +02'00'
Date of issue	2018-06-27
Report template No	FAN24_01

Index

- Competences and guarantees3
- General conditions3
- Identification of the client.....3
- General description of the device under evaluation.....4
- Assessment summary.....5
- Appendix A: FCC RF Exposure.....6
 - FCC RF Exposure evaluation for mobile devices.....7
 - FCC MPE Evaluation Results.....8
- Appendix B: ISED RF Exposure.....13
 - ISED RF Exposure evaluation for mobile devices.....14
 - ISED MPE Evaluation Results.....15

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This assessment report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA and the Accreditation Bodies.

Identification of the client

SALTO Systems, S.L.
Arkotz 9, Polígono Lanbarren
20180, Oiartzun, Gipuzkoa, SPAIN

General description of the device under evaluation

The device under evaluation consists of an electronic lock series, with different model variants, which uses the same main board and can support NFC, Bluetooth Smart and 802.15.4 technologies. The electronic and batteries will be installed inside the door. During its normal use the separation distance between the antenna and the user will be greater than 20 cm.

Model	Supported Features			
	NFC ISO 14443-A	NFC ISO 15693	Bluetooth Smart BGM111	802.15.4
XS4 Original W09	Yes	Yes	No	No
XS4 Original W0B	Yes	Yes	Yes	No
XS4 Original W09W	Yes	Yes	No	Yes
XS4 Original W0BW	Yes	Yes	Yes	Yes
XS4 Original W0J	No	Yes	Yes	No
XS4 Original W0JW	No	Yes	Yes	Yes

Table 1: Equipment variants and supported features

The equipment specifications declared by the manufacturer for each supported feature are:

Band (MHz)	Technology	Maximum RF output power (dBm)	Maximum antenna gain (dBi)	Maximum radiated power (E.I.R.P.) (dBm)
13.553-13.567	NFC	25.0	N/A	25.0
2402.0-2480.0	Bluetooth	8.0	1.0	9.0
2405.0-2485.0	802.15.4	5.0	1.7	6.7

Table 2: Equipment specifications

Assessment summary

Radiofrequency radiation exposure limits			
FCC 47 CFR § 2.1091 & ISED RSS-102 Issue 5 (2015-03)			
Assessment	Band (MHz)	Technology	VERDICT (Pass/Fail)
1	13.5	NFC	Pass
2	2450	Bluetooth	Pass
3	2450	802.15.4	Pass

Table 3: Assessment summary

Appendix A: FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

Assessment 1 – NFC – 13.5 MHz Band

Maximum output power (dBm):	25.0
Maximum antenna Gain (dBi):	N/A
Minimum use distance (cm):	20.0
Worst Case Frequency (MHz):	13.56
Maximum EIRP (dBm):	25.0
Maximum EIRP (mW):	316.23
General population - Power density limit (mW/cm ²):	0.98

Power density at minimum use distance:

Power density (mW/cm ²):	0.063
General population - Power density limit (mW/cm ²):	0.98
Verdict for general population:	PASS

The power density level for this transmission mode is below general population exposure power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general population (cm):	5.07
Minimum use distance (cm):	20.0
Verdict for general population:	PASS

The minimum use distance is greater than general population exposure minimum compliance distance.

Assessment 2 – Bluetooth – 2450 MHz Band

Maximum output power (dBm):	8.0
Maximum antenna Gain (dBi):	1.0
Minimum use distance (cm):	20.0
Worst Case Frequency (MHz):	2402.0
Maximum EIRP (dBm):	9.0
Maximum EIRP (mW):	7.94
General population - Power density limit (mW/cm ²):	1.0

Power density at minimum use distance:

Power density (mW/cm ²):	0.0016
General population - Power density limit (mW/cm ²):	1.0
Verdict for general population:	PASS

The power density level for this transmission mode is below general population exposure power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general population (cm):	0.80
Minimum use distance (cm):	20.0
Verdict for general population:	PASS

The minimum use distance is greater than general population exposure minimum compliance distance.

Assessment 3 – 802.15.4 – 2450 MHz Band

Maximum output power (dBm):	5.0
Maximum antenna Gain (dBi):	1.7
Minimum use distance (cm):	20.0
Worst Case Frequency (MHz):	2405.0
Maximum EIRP (dBm):	6.7
Maximum EIRP (mW):	4.68
General population - Power density limit (mW/cm ²):	1.0

Power density at minimum use distance:

Power density (mW/cm ²):	0.001
General population - Power density limit (mW/cm ²):	1.0
Verdict for general population:	PASS

The power density level for this transmission mode is below general population exposure power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general population (cm):	0.61
Minimum use distance (cm):	20.0
Verdict for general population:	PASS

The minimum use distance is greater than general population exposure minimum compliance distance.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

The worst case of simultaneous transmission for all model variants is found for the XS4 Original W09W and W0BW models. This model is able to transmit simultaneously using NFC, Bluetooth Smart and 802.15.4 technology. The multiple frequencies calculation will be as follow:

$$\frac{0.063}{0.98} + \frac{0.002 + 0.001}{1} = 0.064 + 0.003 = 0.067 < 1 \text{ Limit}$$

Appendix B: ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Healths Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ⁻²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if it is in compliance with RSS-102 Issue 5, RF Field Strength Limits for devices used by the General Public.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[W / m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W / m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

Assessment 1 – NFC – 13.5 MHz Band

Maximum output power (dBm):	25.0
Maximum antenna gain (dBi):	N/A
Minimum use distance (m):	0.2
Worst Case Frequency (MHz):	13.56
Maximum EIRP (dBm):	25.0
Maximum EIRP (W):	0.32
General public - Power density limit (W/m ²):	2.0

Power density at minimum use distance:

Power density (W/m ²):	0.63
General public - Power density limit (W/m ²):	2.0
Verdict for general public:	PASS

The power density level for this transmission mode is below general public power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general public (m):	0.112
Minimum use distance (m):	0.2
Verdict for general public:	PASS

The minimum use distance is greater than general public minimum compliance distance.

Assessment 2 – Bluetooth – 2450 MHz Band

Maximum output power (dBm):	8.0
Maximum antenna gain (dBi):	1.0
Minimum use distance (m):	0.2
Worst Case Frequency (MHz):	2402.0
Maximum EIRP (dBm):	9.0
Maximum EIRP (W):	0.01
General public - Power density limit (W/m ²):	5.35

Power density at minimum use distance:

Power density (W/m ²):	0.016
General public - Power density limit (W/m ²):	5.35
Verdict for general public:	PASS

The power density level for this transmission mode is below general public power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general public (m):	0.011
Minimum use distance (m):	0.2
Verdict for general public:	PASS

The minimum use distance is greater than general public minimum compliance distance.

Assessment 3 – 802.15.4 – 2450 MHz Band

Maximum output power (dBm):	5.0
Maximum antenna gain (dBi):	1.7
Minimum use distance (m):	0.2
Worst Case Frequency (MHz):	2405.0
Maximum EIRP (dBm):	6.70
Maximum EIRP (W):	0.005
General public - Power density limit (W/m ²):	1.0

Power density at minimum use distance:

Power density (W/m ²):	0.009
General public - Power density limit (W/m ²):	5.35
Verdict for general public:	PASS

The power density level for this transmission mode is below general public power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for general public (m):	0.008
Minimum use distance (m):	0.2
Verdict for general public:	PASS

The minimum use distance is greater than general public minimum compliance distance.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

The worst case of simultaneous transmission for all model variants is found for the XS4 Original W09W and W0BW models. This model is able to transmit simultaneously using NFC, Bluetooth Smart and 802.15.4 technology. The multiple frequencies calculation will be as follow:

$$\frac{0.63}{2} + \frac{0.016 + 0.009}{5.35} = 0.315 + 0.005 = 0.320 < 1 \text{ Limit}$$