



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM150300107802
Page: 1 of 36

FCC REPORT

Application No. : SZEM1503001078CR
Applicant: Innovation First, Inc.
Product Name: Color Camera
Model No.(EUT): 276-4286
FCC ID: UKU-VEXCAM-TX3
Standards: 47 CFR Part 15, Subpart C (2014)
Date of Receipt: 2015-03-26
Date of Test: 2015-04-01 to 2015-04-20
Date of Issue: 2015-05-08

Test Result:

PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.


The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-05-08		Original

Authorized for issue by:				
Tested By		 (Owen Zhou) /Project Engineer		2015-04-20
				Date
Prepared By		 (Linlin Lv) /Clerk		2015-04-22
				Date
Checked By		 (Eric Fu) /Reviewer		2015-04-22
				Date



3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2009)	PASS
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.249 (a)	ANSI C63.10 (2009)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.249 (a)/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.249(a)/15.205	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.215 (c)	ANSI C63.10 (2009)	PASS



4 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 TEST ENVIRONMENT AND MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 TEST LOCATION	6
5.6 TEST FACILITY	7
5.7 DEVIATION FROM STANDARDS	7
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5.10 EQUIPMENT LIST	8
6 TEST RESULTS AND MEASUREMENT DATA	10
6.1 ANTENNA REQUIREMENT	10
6.2 SPURIOUS EMISSIONS	11
6.2.1 Spurious Emissions	11
6.3 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	22
6.4 20dB BANDWIDTH	32
7 PHOTOGRAPHS.....	35
7.1 RADIATED EMISSION TEST SETUP	35
7.2 EUT CONSTRUCTIONAL DETAILS	36



5 General Information

5.1 Client Information

Applicant:	Innovation First, Inc.
Address of Applicant:	Innovation First, Inc. 1519 INT. 30 W Greenville, TX 75402

5.2 General Description of EUT

Product Name:	Color Camera
Model No.:	276-4286
EUT Function:	Color Camera
Frequency Range:	5725MHz, 5745MHz, 5765MHz, 5805MHz
Modulation Type:	FM
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	2dBi
Power Supply:	Camera unit:DC6V-DC9V Camera Receiver: DC6V(4 x 1.5V "AA" Size Battery)





5.3 Test Environment and Mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

**5.10 Equipment List**

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802


Page : 9 of 36

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2dBi.



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802




Page : 11 of 36

6.2 Spurious Emissions

6.2.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.249 and 15.209				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F (kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F (kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40. 0	Quasi-peak	3
	88MHz-216MHz	150	43. 5	Quasi-peak	3
	216MHz-960MHz	200	46. 0	Quasi-peak	3
	960MHz-1GHz	500	54. 0	Quasi-peak	3
	Above 1GHz	500	54. 0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Limit: (Field strength of the	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.0		Average Value	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

fundamental signal)		114.0	Peak Value
Test Setup:			
			
Figure 1. Below 30MHz			
		Figure 2. 30MHz to 1GHz	
			
		Figure 3. Above 1 GHz	
Test Procedure:	- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as		



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 13 of 36

	specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Instruments Used:	Refer to section 5.10 for details
Test Mode:	Transmitting mode
Test Results:	Pass



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 14 of 36

Measurement Data

6.2.1.1 Field Strength Of The Fundamental Signal

Frequen cy (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Pream p Factor (dB)	Read Level (dBuV)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Remak
5725.00	6.90	35.74	39.21	88.10	91.53	114.00	-22.47	Peak
5725.00	6.90	35.74	39.21	88.10	80.63	94.00	-13.37	Average
5745.00	6.94	35.78	39.21	86.68	90.19	114.00	-23.81	Peak
5745.00	6.94	35.78	39.21	86.68	78.19	94.00	-15.21	Average
5765.00	6.98	35.83	39.21	85.91	89.51	114.00	-27.49	Peak
5765.00	6.98	35.83	39.21	85.91	77.68	94.00	-16.32	Average
5805.00	7.08	35.93	39.20	86.27	90.08	114.00	-23.92	Peak
5805.00	7.08	35.93	39.20	86.27	78.79	94.00	-15.21	Average

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




6.2.1.2 Spurious Emissions

30MHz~1GHz

Test mode:

Transmitting

Vertical



Condition: 47 CFR PART 15.209 3m Vertical

Job No. : 1078CR

Test Mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	18.70	27.36	26.65	18.59	40.00	-21.41
2	32.98	0.60	17.03	27.34	27.01	17.30	40.00	-22.70
3	478.85	2.52	17.80	27.60	39.41	32.13	46.00	-13.87
4	607.79	2.72	20.02	27.53	29.66	24.87	46.00	-21.13
5	771.45	3.12	21.96	27.33	29.89	27.64	46.00	-18.36
6	952.09	3.65	23.30	26.54	29.33	29.74	46.00	-16.26






SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 16 of 36

Horizontal



Condition: 47 CFR PART 15.209 3m Horizontal

Job No. : 1078CR

Test Mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	134.56	1.29	7.88	26.98	47.67	29.86	43.50 -13.64
2	144.33	1.31	8.49	26.94	55.43	38.29	43.50 -5.21
3	287.99	1.85	13.37	26.43	45.47	34.26	46.00 -11.74
4	431.03	2.33	16.52	27.33	36.19	27.71	46.00 -18.29
5	480.60	2.53	17.80	27.60	50.62	43.35	46.00 -2.65
6	962.16	3.66	23.30	26.47	36.26	36.75	54.00 -17.25

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 17 of 36

Above 1GHz								
Test mode:		Transmitting	Frequency :		5725MHz	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1894.154	4.19	30.87	38.42	45.65	42.29	74	-31.71	Vertical
4417.841	4.82	34.29	39.11	46.87	46.87	74	-27.13	Vertical
7562.942	8.65	35.47	39.04	45.69	50.77	74	-23.23	Vertical
8969.161	8.94	35.99	38.33	43.23	49.83	74	-24.17	Vertical
11450.000	10.03	38.19	38.44	52.43	62.21	74	-11.79	Vertical
17175.000	12.63	41.03	41.67	45.50	57.49	74	-16.51	Vertical
1894.154	4.19	30.87	38.42	45.26	41.90	74	-32.10	Horizontal
3746.792	5.75	33.11	38.85	43.41	43.42	74	-30.58	Horizontal
7242.052	8.32	35.59	39.06	43.73	48.58	74	-25.42	Horizontal
9021.160	8.96	36.05	38.30	42.50	49.21	74	-24.79	Horizontal
11450.000	10.03	38.19	38.44	52.13	61.91	74	-12.09	Horizontal
17175.000	12.63	41.03	41.67	45.90	57.89	74	-16.11	Horizontal

Test mode:		Transmitting	Frequency :		5725MHz	Remark:		Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1894.154	4.19	30.87	38.42	36.35	32.99	54	-21.01	Vertical
4417.841	4.82	34.29	39.11	37.57	37.57	54	-16.43	Vertical
7562.942	8.65	35.47	39.04	36.52	41.60	54	-12.40	Vertical
8969.161	8.94	35.99	38.33	34.89	41.49	54	-12.51	Vertical
11450.000	10.03	38.19	38.44	43.62	53.40	54	-0.60	Vertical
17175.000	12.63	41.03	41.67	37.12	49.11	54	-4.89	Vertical
1894.154	4.19	30.87	38.42	36.26	32.90	54	-21.10	Horizontal
3746.792	5.75	33.11	38.85	34.25	34.26	54	-19.74	Horizontal
7242.052	8.32	35.59	39.06	34.26	39.11	54	-14.89	Horizontal
9021.160	8.96	36.05	38.30	33.26	39.97	54	-14.03	Horizontal
11450.000	10.03	38.19	38.44	41.89	51.67	54	-2.33	Horizontal
17175.000	12.63	41.03	41.67	35.28	47.27	54	-6.73	Horizontal

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 18 of 36

Test mode:		Transmitting		Frequency :		5745MHz		Remark:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3587.818	5.85	32.99	38.78	45.44	45.50	74	-28.50	Vertical			
4973.662	5.92	34.87	39.29	45.94	47.44	74	-26.56	Vertical			
7497.646	8.61	35.45	39.04	44.87	49.89	74	-24.11	Vertical			
9475.497	9.30	37.08	38.01	43.12	51.49	74	-22.51	Vertical			
11490.000	10.11	38.31	38.52	53.00	62.90	74	-11.10	Vertical			
17235.000	12.74	41.01	41.69	45.40	57.46	74	-16.54	Vertical			
3703.723	5.78	33.08	38.83	45.22	45.25	74	-28.75	Horizontal			
5090.007	6.06	34.88	39.29	45.04	46.69	74	-27.31	Horizontal			
7390.070	8.49	35.43	39.05	45.76	50.63	74	-23.37	Horizontal			
9725.221	9.20	37.69	37.86	41.95	50.98	74	-23.02	Horizontal			
11490.000	10.06	38.22	38.46	47.54	57.36	74	-16.64	Horizontal			
17235.000	11.66	40.14	41.40	52.14	62.54	74	-11.46	Horizontal			

Test mode:		Transmitting		Frequency :		5745MHz		Remark:		Average	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3587.818	5.85	32.99	38.78	36.26	36.32	54	-17.68	Vertical			
4973.662	5.92	34.87	39.29	36.22	37.72	54	-16.28	Vertical			
7497.646	8.61	35.45	39.04	35.23	40.25	54	-13.75	Vertical			
9475.497	9.30	37.08	38.01	34.25	42.62	54	-11.38	Vertical			
11490.000	10.11	38.31	38.52	43.84	53.74	54	-0.26	Vertical			
17235.000	12.74	41.01	41.69	35.95	48.01	54	-5.99	Vertical			
3703.723	5.78	33.08	38.83	36.23	36.26	54	-17.74	Horizontal			
5090.007	6.06	34.88	39.29	35.86	37.51	54	-16.49	Horizontal			
7390.070	8.49	35.43	39.05	36.58	41.45	54	-12.55	Horizontal			
9725.221	9.20	37.69	37.86	32.11	41.14	54	-12.86	Horizontal			
11490.000	10.06	38.22	38.46	34.56	44.38	54	-9.62	Horizontal			
17235.000	11.66	40.14	41.40	39.26	49.66	54	-4.34	Horizontal			

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 19 of 36

Test mode:		Transmitting		Frequency :		5765MHz		Remark:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3725.195	5.77	33.09	38.84	45.61	45.63	74	-28.37	Vertical			
5002.497	5.99	34.90	39.30	45.51	47.10	74	-26.90	Vertical			
6894.806	7.85	35.78	39.09	45.83	50.37	74	-23.63	Vertical			
8789.516	8.95	35.96	38.45	42.97	49.43	74	-24.57	Vertical			
11530.000	10.08	38.25	38.48	51.53	61.38	74	-12.62	Vertical			
17295.000	12.84	40.98	41.70	48.46	60.58	74	-13.42	Vertical			
3693.033	5.79	33.07	38.83	44.57	44.60	74	-29.40	Horizontal			
4560.559	4.85	34.52	39.16	45.26	45.47	74	-28.53	Horizontal			
6717.762	7.54	35.75	39.11	45.13	49.31	74	-24.69	Horizontal			
8106.200	8.93	35.83	38.92	44.34	50.18	74	-23.82	Horizontal			
11530.000	10.08	38.25	38.48	47.88	57.73	74	-16.27	Horizontal			
17295.000	12.84	40.98	41.70	47.85	59.97	74	-14.03	Horizontal			

Test mode:		Transmitting		Frequency :		5765MHz		Remark:		Average	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3725.195	5.77	33.09	38.84	36.89	36.91	54	-17.09	Vertical			
5002.497	5.99	34.90	39.30	36.21	37.80	54	-16.20	Vertical			
6894.806	7.85	35.78	39.09	36.21	40.75	54	-13.25	Vertical			
8789.516	8.95	35.96	38.45	33.25	39.71	54	-14.29	Vertical			
11530.000	10.08	38.25	38.48	42.17	52.02	54	-1.98	Vertical			
17295.000	12.84	40.98	41.70	36.26	48.38	54	-5.62	Vertical			
3693.033	5.79	33.07	38.83	35.21	35.24	54	-18.76	Horizontal			
4560.559	4.85	34.52	39.16	36.21	36.42	54	-17.58	Horizontal			
6717.762	7.54	35.75	39.11	35.89	40.07	54	-13.93	Horizontal			
8106.200	8.93	35.83	38.92	35.25	41.09	54	-12.91	Horizontal			
11530.000	10.08	38.25	38.48	38.26	48.11	54	-5.89	Horizontal			
17295.000	12.84	40.98	41.70	36.39	48.51	54	-5.49	Horizontal			

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 20 of 36

Test mode:		Transmitting		Frequency :		5805MHz		Remark:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preampl Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3640.045	5.82	33.03	38.80	50.08	50.13	74	-23.87	Vertical			
4959.307	5.89	34.86	39.29	46.23	47.69	74	-26.31	Vertical			
7138.144	8.19	35.69	39.07	44.95	49.76	74	-24.24	Vertical			
9312.588	9.18	36.75	38.11	43.95	51.77	74	-22.23	Vertical			
11610.000	10.06	38.22	38.46	51.14	60.96	74	-13.04	Vertical			
15988.450	11.73	40.28	41.32	47.75	58.44	74	-15.56	Vertical			
3546.577	5.88	32.94	38.76	44.68	44.74	74	-29.26	Horizontal			
4888.151	5.71	34.79	39.26	44.89	46.13	74	-27.87	Horizontal			
6954.852	7.95	35.79	39.09	45.21	49.86	74	-24.14	Horizontal			
9366.577	9.22	36.87	38.08	43.49	51.50	74	-22.50	Horizontal			
11610.000	10.11	38.31	38.52	47.36	57.26	74	-16.74	Horizontal			
17415.000	13.06	40.93	41.74	46.81	59.06	74	-14.94	Horizontal			

Test mode:		Transmitting		Frequency :		5805MHz		Remark:		Average	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization			
3640.045	5.82	33.03	38.80	40.23	40.28	54	-13.72	Vertical			
4959.307	5.89	34.86	39.29	37.21	38.67	54	-15.33	Vertical			
7138.144	8.19	35.69	39.07	35.21	40.02	54	-13.98	Vertical			
9312.588	9.18	36.75	38.11	34.56	42.38	54	-11.62	Vertical			
11610.000	10.06	38.22	38.46	41.50	51.32	54	-2.68	Vertical			
15988.450	11.73	40.28	41.32	38.23	48.92	54	-5.08	Vertical			
3546.577	5.88	32.94	38.76	35.23	35.29	54	-18.71	Horizontal			
4888.151	5.71	34.79	39.26	35.61	36.85	54	-17.15	Horizontal			
6954.852	7.95	35.79	39.09	35.99	40.64	54	-13.36	Horizontal			
9366.577	9.22	36.87	38.08	34.26	42.27	54	-11.73	Horizontal			
11610.000	10.11	38.31	38.52	38.12	48.02	54	-5.98	Horizontal			
17415.000	13.06	40.93	41.74	31.24	43.49	54	-10.51	Horizontal			

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 21 of 36

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .

6.3 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2009		
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit(band edge):	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.		
	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 23 of 36

Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.. i. Repeat above procedures until all frequencies measured was complete.
Instruments Used:	Refer to section 5.10 for details
Test Mode:	Transmitting mode
Test Results:	Pass




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 24 of 36

Band edge (Radiated Emission)						
Worse case mode:	5725MHz	Test channel:	Lowest	Remark:	Peak	Vertical

Data: 119



Site : chamber
Condition: FCC PART C 249 PK 3m Vertical
Job No: : 1078CR
Mode: : 5725 Band edge

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5715.00	6.87	35.70	39.21	65.50	68.86	74.00	-5.14
2 pp	5727.98	6.90	35.74	39.21	88.10	91.53	74.00	17.53

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 25 of 36

Worse case mode:	5725MHz	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------

Data: 121



Site : chamber
Condition: FCC PART C 249 PK 3m Horizontal
Job No: : 1078CR
Mode: : 5725 Band edge

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5715.00	6.87	35.70	39.21	54.24	57.60	74.00	-16.40
2 pp	5727.28	6.90	35.73	39.21	81.77	85.19	74.00	11.19



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 26 of 36

Worse case mode:	5725MHz	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------

Data: 120



Site : chamber
Condition: FCC PART C 249 AV 3m Vertical
Job No: : 1078CR
Mode: : 5725 Band edge

		Cable	Ant	Preamp	Read	Limit	Over
	Freq	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	5715.00	6.87	35.70	39.21	38.01	41.37	54.00 -12.63
2 pp	5724.66	6.89	35.73	39.21	79.87	83.28	54.00 29.28

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 27 of 36

Worse case mode:	5725MHz	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------

Data: 122



Site : chamber
Condition: FCC PART C 249 AV 3m Horizontal
Job No: : 1078CR
Mode: : 5725 Band edge

		Cable	Ant	Preamp	Read	Limit	Over
	Freq	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	5715.00	6.87	35.70	39.21	34.09	37.45	54.00 -16.55
2 pp	5724.66	6.89	35.73	39.21	70.71	74.12	54.00 20.12

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 28 of 36

Worse case mode:	5725MHz	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------

Data: 125



Site : chamber
Condition: FCC PART C 249 PK 3m Vertical
Job No: : 1078CR
Mode: : 5805 Band edge

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5807.94	7.08	35.93	39.20	86.27	90.08	74.00	16.08
2	5860.00	7.20	36.03	39.20	47.43	51.46	74.00	-22.54

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 29 of 36

Worse case mode:	5725MHz	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------

Data: 123



Site : chamber
Condition: FCC PART C 249 PK 3m Horizontal
Job No: : 1078CR
Mode: : 5805 Band edge

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	5807.64	7.08	35.93	39.20	80.29	84.10	74.00
2	5860.00	7.20	36.03	39.20	45.92	49.95	74.00

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 30 of 36

Worse case mode:	5725MHz	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------

Data: 126



Site : chamber
Condition: FCC PART C 249 AV 3m Vertical
Job No: : 1078CR
Mode: : 5805 Band edge

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5804.56	7.07	35.92	39.20	72.71	76.50	54.00	22.50
2	5860.00	7.20	36.03	39.20	33.85	37.88	54.00	-16.12

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802

Page : 31 of 36

Worse case mode:	5725MHz	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------

Data: 124



Site : chamber
Condition: FCC PART C 249 AV 3m Horizontal
Job No: : 1078CR
Mode: : 5805 Band edge

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5804.66	7.07	35.92	39.20	71.76	75.55	54.00	21.55
2	5860.00	7.20	36.03	39.20	33.91	37.94	54.00	-16.06


Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

6.4 20dB Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2009
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Test mode:	Transmitting mode
Limit:	N/A
Test Results:	Pass

Measurement Data

Test channel	20dB bandwidth (MHz)	Results
5725MHz	8.710	Pass
5745MHz	8.582	Pass
5765MHz	8.606	Pass
5805MHz	9.976	Pass




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150300107802


Page : 33 of 36

Test plot as follows:

Test channel:	5725MHz
---------------	---------



Test channel:	5745MHz
---------------	---------



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.


Report No.: SZEM150300107802

Page : 34 of 36

Test channel:	5765MHz
---------------	---------




Test channel:	5805MHz
---------------	---------



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

7 Photographs

7.1 Radiated Emission Test Setup



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



7.2 EUT Constructional Details

The detailed internal and external Photo see:

Appendix A - Photographs of EUT Constructional Details for SZEM1503001078CR