

Hearth & Home Technologies
FCC ID: ULE2564-110
IC: 6732A-2564110
SN: YYYWWWFNNNNN
PN: 2564-110
0°C to +55°C
Made in China

RF Frequency:
US/CAN: 912.2 – 918MHz
AU/NZ: 915.9-920.8 MHz




Product label
SIZE: 30*10MM

PN:
2564-110



PN barcode label
SIZE: 39*6MM



IFT2 Installation Quick Reference

The RC400 remote shipped standard with a new fireplace:

1. The RC400 remote was paired to the fireplace at the factory. It does not need to be re-paired, unless an accessory kit will be added at the time of installation. If no additional accessory will be added, simply follow steps 2 thru 8 below.
2. If installed, remove the batteries from the RC400 remote.
3. Verify the fireplace has power and secure electrical connections.
4. Adjust the ECM selector switch to "REMOTE" mode.
5. Switch the master reset switch to "ON" (if equipped).
- 6.Wait to verify the LED indicator on the ECM stops flashing.
- 7.Install the batteries in the RC400 remote.
8. The RC400 remote will automatically pair to the fireplace, as pre-set at the factory, within four minutes.

The RC400 remote and/or optional powervent, blower, or lights added as new accessory upgrade to a fireplace:

1. The RC400 remote will need to be paired to the ECM.
2. Follow the installation instructions provided.

153MM





Red ESD bubble bag would be changed to white Non-ESD bubble bag