

6. Measurement Data (continued)

6.9. Public Exposure to Radio Frequency Energy Levels ((1.1307 (b)(1)) RSS-GEN, ISSUE 5, RSS 102)

6.9.1. 1.1307 (b)(1) Requirements

Requirement: Portable devices are subject to radio frequency radiation exposure requirements.

For a 1-g SAR, the test exclusion result must be ≤ 3.0 .

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by the following formula:

$$\text{SAR Test Exclusion} = \frac{P_{\text{MAX}}}{d_{\text{MIN}}} \times \sqrt{f_{(\text{GHz})}} \quad (1)$$

P_{MAX} mW Maximum power of channel, including tune-up tolerance

d_{MIN} mm Minimum test separation distance, mm (≤ 50 mm)

$f_{(\text{GHz})}$ GHz $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)

(1) FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Conclusion: Compliant - The device under test meets the exclusion requirement detailed in FCC OET 447498.

Input:	P_{MAX}^1 (mW)	0.3351
	d_{MIN} (mm)	5.0000
	$f_{(\text{GHz})}$	0.9150

Test Exclusion: **0.06410**

Limit Exemption: **3.00000**

¹ Taken from column 5 of the table in Section 7.4 of this test report.

6.9.2. RSS-102 Issue 5 Requirements

Requirement: SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are subject to radio frequency radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5.

Frequency	Separation Distance	Maximum Power	RSS-102 Limit	Result
(MHz)	(mm)	(mW)	(mW)	
915.00	≤ 5	0.3351	16.25	Compliant