



FCC RADIO TEST REPORT

Applicant : ATBS Technology Corporation

Address : 3F, No. 49, Lane 35, Jihu Rd., Neihsu Chiu,
: Taipei, 114, Taiwan

Equipment : TPMS for iPod,iPhone,iPad

Model No. : BT68XXX (X=0-9,A-Z,a-z or blank)

Trade Name : ATBS

FCC ID : UP5-SC-BT6800

I HEREBY CERTIFY THAT :

The sample was received on Mar. 06, 2015 and the testing was carried out on Mar. 18, 2015 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Hill Chen
Manager

Tested by:

Aiden Lu
Engineer

Laboratory Accreditation:

☒ CerpPASS Technology Corporation Test Laboratory



☐ CerpPASS Technology(SuZhou) Co., Ltd.





Contents

1. Summary of Test Procedure and Test Results.....	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels	6
2.3 Test Mode & Test Software	7
2.4 Description of Test System.....	7
2.5 General Information of Test.....	8
3. Test Equipment and Ancillaries Used for Tests.....	9
4. Antenna Requirements.....	10
4.1 Standard Applicable	10
4.2 Antenna Construction and Directional Gain.....	10
5. Test of AC Power Line Conducted Emission	11
5.1 Test Limit	11
5.2 Test Procedures	11
5.3 Typical Test Setup	12
5.4 Test Result and Data	13
5.5 Test Photographs	15
6. Test of Spurious Emission (Radiated)	16
6.1 Test Limit	16
6.2 Test Procedures.....	16
6.3 Typical Test Setup	17
6.4 Test Result and Data (9kHz ~ 30MHz).....	18
6.5 Test Result and Data (30MHz ~ 1GHz).....	18
6.6 Test Result and Data (Above 1GHz)	20
6.7 Restricted Bands of Operation.....	26
6.8 Restrict band emission Measurement Data	27
6.9 Test Photographs (30MHz ~ 1GHz)	29
6.10 Test Photographs (Above 1GHz)	30
7. Test of Spurious Emission (Conducted).....	31
7.1 Test Limit	31
7.2 Test Procedure	31
7.3 Test Setup Layout	31
7.4 Test Result and Data.....	31
8. Occupied Bandwidth Measurement Data	35
8.1 Test Limit	35
8.2 Test Procedures	35
8.3 Test Setup Layout	35
8.4 Test Result and Data	35
9. Frequencies Separation	38
9.1 Test Limit	38



9.2	Test Procedures	38
9.3	Test Setup Layout	38
9.4	Test Result and Data	38
10.	Dwell Time on each channel	41
10.1	Test Limit	41
10.2	Test Procedures	41
10.3	Test Setup Layout	41
10.4	Test Result and Data	42
11.	Number of Hopping Channels	46
11.1	Test Limit	46
11.2	Test Procedures	46
11.3	Test Setup Layout	46
11.4	Test Result and Data	46
12.	Maximum Peak Output Power	48
12.1	Test Limit	48
12.2	Test Procedures	48
12.3	Test Setup Layout	48
12.4	Test Result and Data	48



History of this test report

■ ORIGINAL.

☐ Additional attachment as following record:

[illegible]



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.4: 2009

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. AC Power Line Conducted Emission	Pass
15.209 15.205	. Spurious Emission(Radiated)	Pass
15.247(d)	. Spurious Emission(Conducted)	Pass
15.247(a)(1)	. Channel Carrier Frequencies Separation	Pass
15.247(a)(1)	. 20dB Bandwidth Measurement	Pass
15.247(a)(1)	. Dwell Time	Pass
15.247(b)	. Number of Hopping Channels	Pass
15.247(b)	. Peak Output Power Measurement Data	Pass

This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Frequency Range	2402-2480MHz
Channel Number	79 channels
Data Rate	1Mbps, 2Mbps, 3Mbps
Channel Spacing	1MHz
Antenna Type/ gain	chip antenna/ 0 dBi

2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	*78	2480
19	2421	*39	2441	59	2461	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode & Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4
- b. The complete test system included Notebook and EUT for RF test.
- c. The test program "ISRT_V2.1.9.3409" under WIN XP was executed to keep transmit and receive data via Bluetooth.
- d. Test modes:
Mode 1: GFSK (1Mbps)
Mode 2: $\pi/4$ -DQPSK (2Mbps)
Mode 3: 8DPSK (3Mbps)
Only the worst case is shown in the test report:
AC power Line conducted emission: Mode 1: GFSK (1Mbps);
Radiated spurious emission: Below 1GHz, Mode 1: GFSK (1Mbps)
Above 1GHz, Mode 2: $\pi/4$ -DQPSK (2Mbps)

2.4 Description of Test System

Device	Manufacturer	Model No.	Description
Notebook	DELL	INSPIRON 510m	Power Cable, Unshielding, 1.8m
Test Fixture	N/A	N/A	N/A

Use Cable:

Cable	Quantity	Description
RS232 to USB	1	Unshielding, 1.2m



2.5 General Information of Test

☒	Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582
	FCC	TW1079, TW1061, 390316, 228391, 641184
	IC	4934B-1, 4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-3428, R-4218 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
☐	Test Site	Cerpass Technology (Suzhou) Co.,Ltd Address: No.66, Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China Tel: +86-512-6917-5888 Fax: +86-512-6917-5666
	FCC	916572, 331395
	IC	7290A-1, 7290A-2
	VCCI	T-343 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test G-227 for radiated disturbance above 1GHz
Frequency Range Investigated:		Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25000MHz
Test Distance:		The test distance of radiated emission from antenna to EUT is 3 M.



3. Test Equipment and Ancillaries Used for Tests

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2015/03/07	2016/03/06
PREAMPLIFIER	AGILENT	8449B	3008A01954	2015/03/05	2016/03/04
HORN ANTENNA	EMCO	3115	31589	2015/03/09	2016/03/08
HIGH PASS FILTER	HP	84300-80038	002	N/A	N/A
Bilog Antenna	SchwarzBeck	VULB 9168	275	2014/09/18	2015/09/17
SERIES POWER METER	ANRITSU	ML2495A	1224005	2015/03/05	2016/03/04
POWER SENSOR	ANRITSU	MA2411B	1207295	2015/03/05	2016/03/04
Bluetooth Tester	R&S	CBT	101133	2015/03/12	2016/03/11



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

No.	Antenna Type	Antenna Gain
1	chip antenna	0 dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2009 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup





5.4 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: Mode 1	Temperature	: 26 °C
Test Date	: Mar. 13, 2015	Humidity	: 48 %
Memo		Atmospheric Pressure	: 1008 hpa




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1819	9.99	38.55	48.54	64.39	-15.85	QP	P
2	0.1819	9.99	23.27	33.26	54.39	-21.13	AVG	P
3	0.4900	10.00	28.73	38.73	56.17	-17.44	QP	P
4	0.4900	10.00	22.07	32.07	46.17	-14.10	AVG	P
5	0.7780	10.02	11.52	21.54	56.00	-34.46	QP	P
6	0.7780	10.02	5.85	15.87	46.00	-30.13	AVG	P
7	1.8020	10.09	15.23	25.32	56.00	-30.68	QP	P
8	1.8020	10.09	10.90	20.99	46.00	-25.01	AVG	P
9	5.2980	10.21	14.07	24.28	60.00	-35.72	QP	P
10	5.2980	10.21	9.30	19.51	50.00	-30.49	AVG	P
11	10.5820	10.38	12.13	22.51	60.00	-37.49	QP	P
12	10.5820	10.38	6.33	16.71	50.00	-33.29	AVG	P

Note: Level = Reading + Factor
Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1	Temperature	: 26 °C
Test Date	: Mar. 13, 2015	Humidity	: 48 %
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	10.03	42.79	52.82	65.36	-12.54	QP	P
2	0.1620	10.03	28.24	38.27	55.36	-17.09	AVG	P
3	0.2540	10.03	29.71	39.74	61.62	-21.88	QP	P
4	0.2540	10.03	14.56	24.59	51.62	-27.03	AVG	P
5	0.4940	10.04	28.52	38.56	56.10	-17.54	QP	P
6	0.4940	10.04	21.73	31.77	46.10	-14.33	AVG	P
7	1.1100	10.07	14.05	24.12	56.00	-31.88	QP	P
8	1.1100	10.07	8.53	18.60	46.00	-27.40	AVG	P
9	2.9300	10.17	12.04	22.21	56.00	-33.79	QP	P
10	2.9300	10.17	7.18	17.35	46.00	-28.65	AVG	P
11	5.3300	10.25	11.29	21.54	60.00	-38.46	QP	P
12	5.3300	10.25	5.91	16.16	50.00	-33.84	AVG	P

Note: Level = Reading + Factor
Margin = Level – Limit



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2009. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions. For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V / M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V / M)
30-230	10	30
230-1000	10	37


6.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz-30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1	Temperature	: 22 °C
Test Date	: Mar. 13, 2015	Humidity	: 54 %
Memo	:	Atmospheric Pressure	: 1078 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	42.6100	-18.20	57.57	39.37	40.00	-0.63	peak	102	217
2	42.6100	-18.20	34.15	15.95	40.00	-24.05	QP	102	217
3	196.8400	-21.34	58.73	37.39	43.50	-6.11	peak	102	217
4	214.3000	-21.28	60.24	38.96	43.50	-4.54	peak	102	217
5	281.2300	-18.35	59.92	41.57	46.00	-4.43	peak	102	217
6	366.5900	-15.97	53.87	37.90	46.00	-8.10	peak	102	217
7	562.5300	-11.37	46.48	35.11	46.00	-10.89	peak	102	217


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1	Temperature	: 22 °C
Test Date	: Mar. 13, 2015	Humidity	: 54 %
Memo	:	Atmospheric Pressure	: 1078 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	71.7100	-21.26	55.45	34.19	40.00	-5.81	peak	102	211
2	96.9300	-23.92	62.08	38.16	43.50	-5.34	peak	102	211
3	108.5700	-22.11	60.84	38.73	43.50	-4.77	peak	102	211
4	196.8400	-21.34	61.36	40.02	43.50	-3.48	peak	102	211
5	210.4200	-21.26	61.49	40.23	43.50	-3.27	peak	102	211
6	366.5900	-15.97	50.05	34.08	46.00	-11.92	peak	102	211

Note: Level = Reading + Factor


Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



6.6 Test Result and Data (Above 1GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 0	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4804.000	7.26	42.97	50.23	74.00	-23.77	peak	102	168
2	7206.000	12.18	44.60	56.78	74.00	-17.22	peak	102	168
3	7206.000	12.18	31.99	44.17	54.00	-9.83	AVG	102	168
4	9608.000	15.88	44.72	60.60	74.00	-13.40	peak	102	168
5	9608.000	15.88	31.59	47.47	54.00	-6.53	AVG	102	168
6	12010.000	19.26	44.64	63.90	74.00	-10.10	peak	102	168
7	12010.000	19.26	31.87	51.13	54.00	-2.87	AVG	102	168


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 0	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4804.000	7.26	42.54	49.80	74.00	-24.20	peak	102	174
2	7206.000	12.18	44.66	56.84	74.00	-17.16	peak	102	174
3	7206.000	12.18	32.08	44.26	54.00	-9.74	AVG	102	174
4	9608.000	15.88	43.29	59.17	74.00	-14.83	peak	102	174
5	9608.000	15.88	31.65	47.53	54.00	-6.47	AVG	102	174
6	12010.000	19.26	43.44	62.70	74.00	-11.30	peak	102	174
7	12010.000	19.26	31.82	51.08	54.00	-2.92	AVG	102	174


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 39	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4882.000	7.51	41.73	49.24	74.00	-24.76	peak	104	176
2	7323.000	12.66	44.22	56.88	74.00	-17.12	peak	104	176
3	7323.000	12.66	32.00	44.66	54.00	-9.34	AVG	104	176
4	9764.000	16.05	44.15	60.20	74.00	-13.80	peak	104	176
5	9764.000	16.05	31.79	47.84	54.00	-6.16	AVG	104	176
6	12205.000	19.31	44.00	63.31	74.00	-10.69	peak	104	176
7	12205.000	19.31	31.64	50.95	54.00	-3.05	AVG	104	176


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 39	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4882.000	7.51	40.87	48.38	74.00	-25.62	peak	104	171
2	7323.000	12.66	43.83	56.49	74.00	-17.51	peak	104	171
3	7323.000	12.66	31.63	44.29	54.00	-9.71	AVG	104	171
4	9764.000	16.05	42.52	58.57	74.00	-15.43	peak	104	171
5	9764.000	16.05	31.76	47.81	54.00	-6.19	AVG	104	171
6	12205.000	19.31	43.19	62.50	74.00	-11.50	peak	104	171
7	12205.000	19.31	31.39	50.70	54.00	-3.30	AVG	104	171


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 78	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4960.000	7.76	42.77	50.53	74.00	-23.47	peak	100	176
2	7440.000	13.16	42.00	55.16	74.00	-18.84	peak	100	176
3	7440.000	13.16	31.73	44.89	54.00	-9.11	AVG	100	176
4	9920.000	16.23	42.96	59.19	74.00	-14.81	peak	100	176
5	9920.000	16.23	31.58	47.81	54.00	-6.19	AVG	100	176
6	12400.000	19.37	43.07	62.44	74.00	-11.56	peak	100	176
7	12400.000	19.37	31.96	51.33	54.00	-2.67	AVG	100	176


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2	Temperature	: 20 °C
Test Date	: Mar. 18, 2015	Humidity	: 52 %
Memo	: CH 78	Atmospheric Pressure	: 1088 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	4960.000	7.76	42.11	49.87	74.00	-24.13	peak	100	186
2	7440.000	13.16	44.55	57.71	74.00	-16.29	peak	100	186
3	7440.000	13.16	31.90	45.06	54.00	-8.94	AVG	100	186
4	9920.000	16.23	43.86	60.09	74.00	-13.91	peak	100	186
5	9920.000	16.23	31.59	47.82	54.00	-6.18	AVG	100	186
6	12400.000	19.37	43.60	62.97	74.00	-11.03	peak	100	186
7	12400.000	19.37	31.98	51.35	54.00	-2.65	AVG	100	186

Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

**6.8 Restrict band emission Measurement Data**

Test Date: Mar. 06, 2015

Temperature: 22 °C

Atmospheric pressure: 1078 hPa

Humidity: 53 %

Modulation Standard: GFSK

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2385.900	V	47.10	-1.19	45.91	Peak	74	54	-28.09	45	1.00
---	V	---	---	---	Ave	74	54	---	---	---
2368.052	H	47.02	-1.27	45.75	Peak	74	54	-28.25	313	1.00
---	H	---	---	---	Ave	74	54	---	---	---
Channel 78						Fundamental Frequency: 2480 MHz				
2536.354	V	46.81	-0.59	46.22	Peak	74	54	-27.78	73	1.02
---	V	---	---	---	Ave	74	54	---	---	---
2495.577	H	48.42	-0.78	47.64	Peak	74	54	-26.36	87	1.01
---	H	---	---	---	Ave	74	54	---	---	---

Modulation Standard: $\pi/4$ -DQPSK

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.212	V	47.42	-1.19	46.23	Peak	74	54	-27.77	52	1.02
---	V	---	---	---	Ave	74	54	---	---	---
2376.792	H	47.15	-1.23	45.92	Peak	74	54	-28.08	282	1.02
---	H	---	---	---	Ave	74	54	---	---	---
Channel 78						Fundamental Frequency: 2480 MHz				
2498.965	V	46.00	-0.76	45.24	Peak	74	54	-28.76	76	1.03
---	V	---	---	---	Ave	74	54	---	---	---
2498.965	H	49.43	-0.76	48.67	Peak	74	54	-25.33	78	1.02
---	H	---	---	---	Ave	74	54	---	---	---

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date: Mar. 06, 2015

Temperature: 22 °C

Atmospheric pressure: 1078 hPa

Humidity: 53 %

Modulation Standard: 8DPSK

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2391.236	V	46.94	-1.17	45.77	Peak	74	54	-28.23	77	1.01
---	V	---	---	---	Ave	74	54	---	---	---
2387.740	H	46.85	-1.19	45.66	Peak	74	54	-28.34	303	1.03
---	H	---	---	---	Ave	74	54	---	---	---
Channel 78						Fundamental Frequency: 2480 MHz				
2489.890	V	45.82	-0.79	45.03	Peak	74	54	-28.97	66	1.00
---	V	---	---	---	Ave	74	54	---	---	---
2495.577	H	46.05	-0.78	45.27	Peak	74	54	-28.73	38	1.00
---	H	---	---	---	Ave	74	54	---	---	---

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



7. Test of Spurious Emission (Conducted)


7.1 Test Limit

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

7.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low lose cable.
- Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- The band edges was measured and recorded.



7.3 Test Setup Layout





7.4 Test Result and Data

Test Date	: Mar. 12, 2015	Temperature	: 23°C
Atmospheric pressure	: 1078 hPa	Humidity	: 53%
Test Result	: PASS		

Note: Test plots refer to the following pages.



Modulation Type: GFSK
CH00

CH78









Modulation Type: $\pi/4$ -DQPSK
CH00





CH78



Modulation Type: 8DPSK
CH00

CH78





8. Occupied Bandwidth Measurement Data

8.1 Test Limit


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

8.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 30 KHz and VBW to 100 KHz.
- The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

8.3 Test Setup Layout



8.4 Test Result and Data



Test Date : Mar. 12, 2015

Temperature : 22°C


Atmospheric pressure : 1078 hPa

Humidity : 53%


Modulation Type	Channel	Frequency (MHz)	20dB Bandwidth (KHz)	2/3 20dB Bandwidth(KHz)
GFSK	00	2402	644	429.34
	39	2441	636	424.00
	78	2480	640	426.67
$\pi/4$ -DQPSK	00	2402	1296	864.00
	39	2441	1280	848.00
	78	2480	1272	848.00
8DPSK	00	2402	1276	850.67
	39	2441	1276	850.67
	78	2480	1336	890.67

Modulation Type: GFSK
CH00Modulation Type: $\pi/4$ -DQPSK
CH00


CH39




CH39



CH78




CH78







Modulation Type: 8DSPK
CH00



CH39



CH78





9. Frequencies Separation


9.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

9.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels.



9.3 Test Setup Layout




9.4 Test Result and Data

Test Date : Mar. 12, 2015 Temperature : 22°C
Atmospheric pressure : 1078 hPa Humidity : 53%


Modulation Type	Channel	Frequency (MHz)	Channel Separation (MHz)
GFSK	00	2402	1.036
	39	2441	0.972
	78	2480	0.856
$\pi/4$ -DQPSK	00	2402	1.008
	39	2441	0.988
	78	2480	1.008
8DPSK	00	2402	1.000
	39	2441	1.016
	78	2480	1.008

Modulation Type: GFSK
CH00Modulation Type: $\pi/4$ -DQPSK
CH00


CH39




CH39



CH78




CH78







Modulation Type: 8DPSK
CH00



CH39



CH78





10. Dwell Time on each channel


10.1 Test Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

10.2 Test Procedures

1. The transmitter output was connected to the spectrum analyzer.
2. Adjust the center frequency to measure frequency, then set zero span mode.
2. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz.
4. Measure the time duration of one transmission on the measured frequency.

10.3 Test Setup Layout





10.4 Test Result and Data

Test Date : Mar. 12, 2015 Temperature : 22°C

Atmospheric pressure : 1078 hPa Humidity : 53%

Test Period = 0.4 (second/ channel) x 79 Channel = 31.6 sec

Modulation Type	Channel	Frequency (MHz)	Dwell Time (ms)
GFSK (DH1)	00	2402	124.48
	39	2441	127.68
	78	2480	127.68
GFSK (DH3)	00	2402	265.44
	39	2441	265.44
	78	2480	265.60
GFSK (DH5)	00	2402	309.33
	39	2441	309.33
	78	2480	311.47
$\pi/4$ -DQPSK (2DH5)	00	2402	311.47
	39	2441	311.47
	78	2480	311.47
8DPSK (3DH5)	00	2402	311.47
	39	2441	311.47
	78	2480	311.47

Test period: 0.4(second/ channel) x 79 channel=31.6 second

Example:


CH0,DH1 mode= $0.399 \text{ (ms)} \times (1600/2)/79 \times 31.6 = 127.68 \text{ (ms)}$

CH0,DH3 mode = $1.660 \text{ (ms)} \times (1600/4)/79 \times 31.6 = 265.60 \text{ (ms)}$


CH0,DH5 mode = $2.920 \text{ (ms)} \times (1600/6)/79 \times 31.6 = 311.47 \text{ (ms)}$




Modulation Type: GFSK(DH1)
CH00




Modulation Type: GFSK(DH3)
CH00




CH39




CH39





CH78




CH78




Modulation Type: GFSK(DH5)
CH00Modulation Type: $\pi/4$ -DQPSK
CH00


CH39




CH39



CH78




CH78







Modulation Type: 8DPSK
CH00



CH39



CH78





11. Number of Hopping Channels


11.1 Test Limit

Frequency hopping systems in the 2400 ~ 2483.5 MHz band shall use at least 15 channels.

11.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. 2. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- c. 3. Set the MaxHold function, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been record.

11.3 Test Setup Layout





11.4 Test Result and Data

Test Date : Mar. 12, 2015 Temperature : 22°C
Atmospheric pressure : 1078 hPa Humidity : 53%



Modulation Type	Hopping Channels
GFSK	79
$\pi/4$ -DQPSK	79
8DPSK	79





Modulation Type:GFSK



Modulation Type: $\pi/4$ -DQPSK



Modulation Type: 8DPSK





12. Maximum Peak Output Power


12.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

12.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

12.3 Test Setup Layout




12.4 Test Result and Data

Test Date : Mar. 12, 2015 Temperature : 22°C
Atmospheric pressure : 1078 hPa Humidity : 53%


Modulation Type	Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
GFSK	00	2402	-15.98	0.0252
	39	2441	-17.69	0.0170
	78	2480	-19.56	0.0110
$\pi/4$ -DQPSK	00	2402	-15.95	0.0254
	39	2441	-17.62	0.0173
	78	2480	-24.52	0.0035
8DPSK	00	2402	-22.25	0.0060
	39	2441	-17.45	0.0180
	78	2480	-19.36	0.0116




Modulation Type: GFSK
CH00




Modulation Type: $\pi/4$ -DQPSK
CH00




CH39




CH39



CH78




CH78






Modulation Type: 8DPSK
CH00



CH39



CH78

