

Assessment report No:

NIE: 51696RAN.001

Assessment report

RF EXPOSURE TEST REPORT ACCORDING TO

FCC 47 CFR Part 2.1093

ISED RSS -102 Issue 5:2015

Identification of item tested.....:	Electronic Toothbrush
Trade	Braun, Oral-B
Model and /or type reference	3767
Other identification of the product	FCC ID: USQ3767 IC: 6856A-3767
Final HW version	90876598 HZ01
Final SW version	V002
Features	Short Range Device using Bluetooth 4.0 LE
Manufacturer	BRAUN GMBH Frankfurter Strasse 145, 61476 Kronberg, Germany.
Test method requested, standard.....:	FCC 47 CFR Part 2.1093. (10-1-15 Edition) Radiofrequency radiation exposure evaluation: portable devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager  MIGUEL LACAVE GARCÍA 2016.12.05 11:36:38 +01'00'
Date of issue	2016-12-05
Report template No.....:	FAN24_01

Index

Competences and guarantees.....	3
General conditions.....	3
Identification of the client	3
Assessment summary	5
Appendix A – FCC RF Exposure	6
FCC Exposure evaluation portable or mobile devices.....	7
FCC SAR test exclusion considerations	7
FCC Evaluation Results.....	8
Appendix B – ISED RF Exposure.....	9
ISED SAR test exclusion considerations.....	10
ISED Evaluation Results	11

Competences and guarantees

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Identification of the client

BRAUN GMBH

Frankfurter Strasse 145, 61476 Kronberg, Germany.

General description of the device under test

The device consists on a electric toothbrush with a wireless display. This device can transmit into two diferents modes, Bluetooth and a Proprietary mode.

The manufacturer declares a maximum output power value for each transmission technology of +0.0 dBm, and a maximum antenna gain value of +3.3 dBi.

Mode	Frequency (MHz)	Max. declared output power (dBm)	Max. declared output power (mW)	Max. antenna gain (dBi)
Bluetooth	2402	0.0	1.0	3.3
	2440	0.0	1.0	3.3
	2480	0.0	1.0	3.3
Proximity	2403	0.0	1.0	3.3
	2427	0.0	1.0	3.3
	2452	0.0	1.0	3.3

Table 1: Declared output power and antenna gain values.

The maximum calculated E.I.R.P value for the device will be:

Mode	Frequency (MHz)	Max. E.I.R.P (dBm)	Max. E.I.R.P (mW)
Bluetooth	2402	3.3	2.14
	2440	3.3	2.14
	2480	3.3	2.14
Proximity	2403	3.3	2.14
	2427	3.3	2.14
	2452	3.3	2.14

Table 2: Maximum E.I.R.P values

Assessment summary

Radiofrequency radiation exposure limits		
FCC 47 CFR § 2.1093		
Band (MHz)	Technology	VERDICT (Pass/Fail)
2450	Bluetooth	Pass
2450	Proximity Protocol	Pass

Radiofrequency radiation exposure limits		
ISED RSS-102 Issue 5 (2015-03)		
Band (MHz)	Technology	VERDICT (Pass/Fail)
2450	Bluetooth	Pass
2450	Proximity Protocol	Pass

Table 3: Assessment summary.

Appendix A – FCC RF Exposure

FCC Exposure evaluation portable or mobile devices

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

FCC SAR test exclusion considerations

According to FCC OET KDB 447498 D01 General RF Exposure Guidance:

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied.

- For distances ≤ 50 mm

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}]$$

≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

Where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table:

MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

Table 4: SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

- For distances > 50 mm

At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

[Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz

[Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·10] mW, at > 1500 MHz and ≤ 6 GHz

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	SAR Test Exclusion Threshold (mW)
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

Table 5: SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

FCC Evaluation Results

The maximum conducted output power declared by the manufacturer, including tune-up tolerance, for the device is 0.0 dBm. The evaluation according to an intended use distance of 5 mm will be as follow:

Protocol	Max. Declared Output Power (dBm)		Min. Test Distance (mm)	Freq. (GHz)	Result	Test Exclusion
	(dBm)	(mW)				
Bluetooth	0.0	1.0	5	2.48	0.31	√
Proprietary	0.0	1.0	5	2.45	0.31	√

Table 6: Evaluation Result

The computed value 0.31 is < 3.0, so according to KDB 447498 D01 – General RF Exposure Guidance, this mode qualifies for Standalone SAR test exclusion for 1-g SAR and 10-g extremity SAR.

Appendix B – ISED RF Exposure

ISED SAR test exclusion considerations

According to ISED “RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)”, paragraph “2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation”, the device operates below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1:

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

Output Power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based time-averaged output power. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required

ISED Evaluation Results

According to paragraph “2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation”, the exemption limits for the applicable separation distance have been calculated by linear interpolation for the following operating frequencies:

Technology	Frequency (MHz)	Distance (mm)	Exemption Limits (mW)
Bluetooth	2402	5	4.26
	2440	5	4.05
	2480	5	3.95
Proprietary	2403	5	4.26
	2427	5	4.13
	2452	5	4.00

Table 7: Exemption Limits

The maximum conducted output power value declared by the manufacturer, including tune-up tolerance, for the device is 0.0 dBm.

The device has a radiating antenna with a gain of 3.3 dBi; therefore, the maximum radiated output power of the device is 3.3 dBm, which corresponds to 2.14 mW.

The evaluation for the applicable output power levels and exemption limits for each operating frequency and technology will be as follow:

Technology	Frequency (MHz)	Max. Declared Output Power (dBm)	Antenna Gain (dBi)	Max. Declared Output Power + Antenna gain (dBm)	Max. Declared Output Power + Antenna gain (mW)	ISED Exemption Limits (mW)	Verdict
Bluetooth	2402	0.0	3.3	3.3	2.14	4.26	Pass
	2440	0.0	3.3	3.3	2.14	4.05	Pass
	2480	0.0	3.3	3.3	2.14	3.95	Pass
Proprietary	2403	0.0	3.3	3.3	2.14	4.26	Pass
	2427	0.0	3.3	3.3	2.14	4.13	Pass
	2452	0.0	3.3	3.3	2.14	4.00	Pass

Table 8: Evaluation Results

As all operating frequencies comply with SAR Test Exclusion Thresholds, according to the standard ISED “RSS-102 Issue 5 (2015-03)”, SAR testing is not required.