FCC Test Report

Report No.: AGC02862191002FE04

FCC ID	:	UU8-NTL2000
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	I-Translator
BRAND NAME	:	LEXIBOOK
MODEL NAME	:	NTL2000
CLIENT	:	Lexibook America
DATE OF ISSUE	:	Nov. 14, 2019
STANDARD(S) **TEST PROCEDURE(S)**	:	FCC Part 15.247 KDB 558074 D01 DTS Meas Guidance v04
REPORT VERSION	:	V1.0

Attestation of ***G***lobal ***C***ompliance (Shenzhen) Co., Ltd

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 14, 2019	Valid	Initial Release

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 5
2. GENERAL INFORMATION 6
2.1. PRODUCT DESCRIPTION 6
2.2. TABLE OF CARRIER FREQUENCYS 6
2.3. IEEE 802.11N MODULATION SCHEME 7
2.4. RELATED SUBMITTAL(S) / GRANT (S) 7
2.5. TEST METHODOLOGY 8
2.6. SPECIAL ACCESSORIES 8
2.7. EQUIPMENT MODIFICATIONS 8
3. MEASUREMENT UNCERTAINTY 9
4. DESCRIPTION OF TEST MODES 10
5 SYSTEM TEST CONFIGURATION 11
5.1. CONFIGURATION OF EUT SYSTEM 11
5.2. EQUIPMENT USED IN EUT SYSTEM 11
5.3. SUMMARY OF TEST RESULTS 11
6. TEST FACILITY 12
6. OUTPUT POWER 12
6.1. MEASUREMENT PROCEDURE 13
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 13
6.3. LIMITS AND MEASUREMENT RESULT 14
7. 6DB BANDWIDTH 16
7.1. MEASUREMENT PROCEDURE 16
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16
7.3. LIMITS AND MEASUREMENT RESULTS 17
9. CONDUCTED SPURIOUS EMISSION 20
9.1. MEASUREMENT PROCEDURE 20
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 20
9.3. MEASUREMENT EQUIPMENT USED 20
9.4. LIMITS AND MEASUREMENT RESULT 21
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 28
10.1 MEASUREMENT PROCEDURE 28
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 28
10.3 MEASUREMENT EQUIPMENT USED 28
10.4 LIMITS AND MEASUREMENT RESULT 29
11. RADIATED EMISSION 32

11.1. MEASUREMENT PROCEDURE 32
11.2. TEST SETUP 33
11.3. LIMITS AND MEASUREMENT RESULT 34
11.4. TEST RESULT 35
12. BAND EDGE EMISSION 38
12.1. MEASUREMENT PROCEDURE 38
12.2. TEST SET-UP 38
12.3. TEST RESULT 39
13. FCC LINE CONDUCTED EMISSION TEST 55
13.1. LIMITS OF LINE CONDUCTED EMISSION TEST 55
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 55
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 56
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 57
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 58
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 60

1. VERIFICATION OF CONFORMITY

Applicant	Lexibook America
Address	C/O NATXIS PRAMEX INTERNATIONAL -NORTH AMERICA 1251 avenue of the Americas, NewYork, United States.
Manufacturer	Lexibook America
Address	C/O NATXIS PRAMEX INTERNATIONAL -NORTH AMERICA 1251 avenue of the Americas, NewYork, United States.
Factory	Lexibook America
Address	C/O NATXIS PRAMEX INTERNATIONAL -NORTH AMERICA 1251 avenue of the Americas, NewYork, United States.
Product Designation	I-Translator
Brand Name	LEXIBOOK
Test Model	NTL2000
Date of test	Oct. 30, 2019~Nov. 14, 2019
Deviation	No any deviation from the test method.
Condition of Test Sample	Normal
Report Template	AGCRT-US-BGN/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance(Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

The test results of this report relate only to the tested sample identified in this report.

Prepared By	Donjon Huang (Project Engineer)	Nov. 14, 2019
Reviewed By	Max Zhang (Reviewer)	Nov. 14, 2019
Approved By	Forrest Lei Authorized Officer	Nov. 14, 2019

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as “I-Translator ”. It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.412 GHz～2.462GHz
Output Power	IEEE 802.11b: **13.54**dBm, IEEE 802.11g: **10.11**dBm; IEEE 802.11n(20): **9.91**dBm,IEEE 802.11n(40): **8.14**dBm
Modulation	DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM)
Number of channels	11 Channels (IEEE802.11b/g/n20)& 7 Channels (IEEE802.11n40)
Hardware Version	S630A-V3.0
Software Version	V3.2.2
Antenna Designation	PIFA Antenna
Antenna Gain	2dBi
Power Supply	DC 5V by adapter.

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11
For 802.11n 40MHZ bandwidth system use Channel 3 to Channel 9.

2.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps) 800nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: UU8-NTL2000** filing to comply with the FCC Part 15 requirements.

2.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013).
Radiated testing was performed at an antenna to EUT distance 3 meters.
Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v05.

2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

2.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB
- Uncertainty of total RF power, conducted, Uc = ±0.8dB
- Uncertainty of spurious emissions, conducted, Uc = ±2.7dB
- Uncertainty of Occupied Channel Bandwidth: Uc = ±2 %
- Uncertainty of Dwell Time: Uc = ±2 %
- Uncertainty of Frequency: Uc = ±2 %

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating
Note: Transmit by 802.11b with Date rate (1/2/5.5/11) Transmit by 802.11g with Date rate (6/9/12/18/24/36/48/54) Transmit by 802.11n (20MHz) with Date rate (6.5/13/19.5/26/39/52/58.5/65) Transmit by 802.11n (40MHz) with Date rate (13.5/27/40.5/54/81/108/121.5/135)	

Note:

1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5 SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	I-Translator	NTL2000	UU8-NTL2000	EUT
2	USB Cable	N/A	N/A	AE
3	Adapter	HW-050100C2W	DC5.0V 1A	AE
4	Magnetic ring	V18001	N/A	AE

Note: All the accessories have been used during the test in conduction emission test.

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong,China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

ALL TEST EQUIPMENT LIST

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun. 12, 2019	Jun. 11, 2020
LISN	R&S	ESH2-Z5	100086	Aug. 26, 2019	Aug. 25, 2020

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec. 18, 2019	Dec. 17, 2020
2.4GHz Fliter	EM Electronics	2400-2500MHz	N/A	Feb. 27, 2019	Feb. 26, 2020
Attenuator	ZHINAN	E-002	N/A	Aug. 26, 2019	Aug. 25, 2020
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 09, 2019	Sep. 08, 2021
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 14, 2018	Jun. 13, 2020
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 26, 2018	May. 25, 2020
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 09, 2019	Jan. 08, 2021
Test software	R&S	ES-K1 (Ver. V1.71)	N/A	N/A	N/A
Test software	Tonscend	JS32-RE	N/A	N/A	N/A
Test software	FARA	EZ_EMC (Ver-03A)	N/A	N/A	N/A

6. OUTPUT POWER

6.1. MEASUREMENT PROCEDURE

For max average conducted output power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.

Note：The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

AVERAGE POWER SETUP



6.3. LIMITS AND MEASUREMENT RESULT

TEST ITEM	OUTPUT POWER
TEST MODE	802.11b with data rate 1

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	13.00	30	Pass
2.437	13.16	30	Pass
2.462	**13.54**	30	Pass

TEST ITEM	OUTPUT POWER
TEST MODE	802.11g with data rate 6

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	8.63	30	Pass
2.437	**10.11**	30	Pass
2.462	9.27	30	Pass

TEST ITEM	OUTPUT POWER
TEST MODE	802.11n 20 with data rate 6.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	8.59	30	Pass
2.437	**9.91**	30	Pass
2.462	9.30	30	Pass

TEST ITEM	OUTPUT POWER
TEST MODE	802.11n 40 with data rate 13.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.422	5.88	30	Pass
2.437	**8.14**	30	Pass
2.452	6.25	30	Pass

7. 6dB BANDWIDTH

7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW⩾3×RBW.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



7.3. LIMITS AND MEASUREMENT RESULTS

Mode	Channel	6dB Bandwidth [MHz]	Verdict
11b	LCH	10.04	PASS
	MCH	10.04	PASS
	HCH	10.04	PASS
11g	LCH	15.15	PASS
	MCH	15.46	PASS
	HCH	15.67	PASS
11nHT20	LCH	16.12	PASS
	MCH	16.27	PASS
	HCH	16.29	PASS
11nHT40	LCH	35.47	PASS
	MCH	35.65	PASS
	HCH	35.38	PASS

Test Graph

11b-LCH	11b-MCH
	

11b-HCH	11g-LCH
	

11g-MCH	11g-HCH
	

11nHT20-LCH	11nHT20-MCH
	

11nHT20-HCH	11nHT40-LCH
	

11nHT40-MCH	11nHT40-HCH
	

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW＞RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW＞RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	**Measurement Result**	
	Test Data	**Criteria**
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 30 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	Refer Test Graph	PASS

Test Graph

11B-LCH	11B-LCH
	

11B-LCH	11B-MCH
	

11B-MCH	11B-MCH
	

11B-HCH	11B-HCH
	

11B-HCH	11G-LCH
	

11G-LCH	11G-LCH
	

11G-MCH	11G-MCH
	

11G-MCH	11G-HCH
	

11G-HCH	11G-HCH
	

11nHT20-LCH	11nHT20-LCH
	

11nHT20-LCH	11nHT20-MCH
	

11nHT20-MCH	11nHT20-MCH
	

11nHT20-HCH	11nHT20-HCH
	

11nHT20-HCH	11nHT40-LCH
	

11nHT40-LCH	11nHT40-LCH
	

11nHT40-MCH	11nHT40-MCH
	

11nHT40-MCH	11nHT40-HCH
	

11nHT40-HCH	11nHT40-HCH
	

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1 MEASUREMENT PROCEDURE

(1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
(2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
(3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD-1 in the ANSI C63.10 (2013) item 11.10 was used in this testing.

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

10.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

Mode	Channel	PSD [dBm/20kHz]	Limit[dBm/3kHz]	Verdict
11b	LCH	-2.739	8	PASS
	MCH	0.283	8	PASS
	HCH	-0.783	8	PASS
11g	LCH	-7.021	8	PASS
	MCH	-5.403	8	PASS
	HCH	-5.596	8	PASS
11nHT20	LCH	-5.839	8	PASS
	MCH	-4.870	8	PASS
	HCH	-5.508	8	PASS
11NHT40	LCH	-12.406	8	PASS
	MCH	-9.486	8	PASS
	HCH	-12.910	8	PASS

Test Graph

11b-LCH	11b-MCH
	

11b-HCH	11g-LCH
	

11g-MCH	11g-HCH
	

11nHT20-LCH	11nHT20-MCH
	

11nHT20-HCH	11nHT40-LCH
	

11nHT40-MCH	11nHT40-HCH