




ELECTROMAGNETIC COMPATIBILITY
ELECTRICAL SAFETY
LASER SPECTROSCOPY
ENVIRONMENTAL PHYSICS

G.S.D. S.r.l.
Certified in accordance with
UNI EN ISO 9001:2008
by
TÜV Rheinland Italia S.r.l.
Certificate N. 39 00 1850509

G.S.D. Srl PISA - Italy	Test Report n. FCC-16547	Rev. 00
Manufacturer	CAEN RFID s.r.l.	
Address	Via Vetraia, 11 55049 Viareggio (LU) Italy	
Test Family Name	R4301P ION (UHF)	
Testing Laboratory Name	G.S.D. S.r.l.	
Address	Via Marmiceto, 8 56121 Ospedaletto Pisa (PI) Italy	
Tel/Fax	+39 050 984254 / +39 050 984262	
P.IVA/VAT	01343950505	
http – e-mail	www.gsd.it - info@gsd.it	
FCC Listed. Registration Number: 424037.		
Location and Date of Issue	Pisa, 2016 April 20	
G.S.D. s.r.l. Via Marmiceto, 8 56121 OSPEDALETTO - PISA Tel. 050.984254 - Fax 050.984262 P. IVA 01343950505 SENIOR EMC TEST MANAGER <i>Dr. Gian Luca Genovesi</i>  QUALITY MANAGER <i>Dr. David Pelliccia</i> 		

INDEX

1. MANUFACTURER AND EUT IDENTIFICATION	3
2. REFERENCE STANDARDS.....	5
3. RESULT, CONDITION, MEASUREMENT UNCERTAINTY.....	6
4. RADIATED EMISSIONS.....	8
5. POWER LINES CONDUCTED EMISSIONS.....	34
6. CONDUCTED OPERATION WITHIN THE BAND 902 - 928 MHz.....	47
6.1. NUMBER OF HOPPING CHANNEL.....	47
6.2. CARRIER FREQUENCY SEPARATION.....	49
6.3. TIME OF OCCUPANCY.....	55
6.4. 20 dB BANDWIDTH.....	68
6.5. PEAK OUTPUT POWER.....	75
6.6. BAND EDGE.....	82
6.7. SPURIOUS RF CONDUCTED EMISSIONS	87
7. RADIATED OPERATION WITHIN THE BAND 902 - 928 MHz.....	92
7.1. SPURIOUS RADIATED EMISSIONS	92
8. PHOTO.....	106

Report Revision History

Revision details

<i>Date</i>	<i>Page No.(s)</i>	<i>Details</i>
2016 April 20	110	Rev. 00 Initial issue

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 2 / 110

1. MANUFACTURER AND EUT IDENTIFICATION¹	
Manufacturer	CAEN RFID s.r.l..
Address	Via Vetraia, 11 55049 Viareggio (LU) Italy
Test Family Name	R4301P ION (UHF)
Date of reception	2016 March 04
Sampling	Laboratory sample for certification
Test Item Description	RFID Device
Nominal Input Voltage	24 Vdc
FCC ID	UVECAENRFID022

¹A detailed documentation is preserved in the internal fascicle.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 3 / 110



*Fig. 1.1
Equipment Photo*

2. REFERENCE STANDARDS

Tests and measurements are performed accordingly to the reference standards given in the table below:

<i>TEST</i>	<i>STANDARD</i>
Emissions: Conducted and Radiated – Section 15.207 and 15.209	FCC Rules and Regulations, Title 47 Part 15 – Sub part C ANSI C63.4 2014 – American National Standard for Methods of Measuring of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz ANSI C63.10 2013 – American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Operation within the band 902-928 MHz: Alternative Test Procedures 15.247 (b) and (c) , and (a) Bandwidth and average time of occupancy, Band Edge 15.247 (d)	FCC Rules and Regulations, Title 47 Part 15 – Sub part C DA 00-705 (30 March 2000) – Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems ANSI C63.4 2014 – American National Standard for Methods of Measuring of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz ANSI C63.10 2013 – American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Antenna Requirement: §15.203	FCC Rules and Regulations, Title 47 Part 15 – Sub part C

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 5 / 110

3. RESULT, CONDITION, MEASUREMENT UNCERTAINTYSummary of Test Results

<i>TEST</i>	<i>RESULT</i>
Emissions: conducted Section 15.207	Pass
Emissions: radiated Section 15.209	Pass
Bandwidth and Average Time of Occupancy Section 15.247 (a)	Pass
Operation within the band 902-928 MHz: Section 15.247 (b) and (c)	Pass
Band Edge Section 15.247 (d)	Pass

Measurement uncertainty

<i>TEST</i>	<i>EXPANDED UNCERTAINTY</i>
Conducted Emission – 50Ω/50μH (150 kHz - 30 MHz)	± 3.5 dB
Radiated Emission – (Semianechoic Room) (30 MHz - 18 GHz)	± 4.7 dB

Climatic Conditions

<i>PARAMETER</i>	<i>VALUE</i>
Temperature	(293 ± 3) K
Relative humidity	(50 ± 5) %

Extensions

The results refer only to the sampled EUT and under the specified conditions.

Modulations:


Type 1: PR_ASK_M4_TX40RX250

Type 2: DSB_ASK_FM0_TX160_RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 6 / 110



Conducted and Radiated EUT Test Set-up example (ANSI C63.10 2013)

4. RADIATED EMISSIONS

In the following table you can find the limits established by the reference standard:

FREQUENCY RANGE (MHz)	<i>Field Strenght</i> <i>QUASI-PEAK LIMITS</i> [dB (μV/m)]
0.009 ÷ 0.490	48.15 ÷ 13.8 @ 300m
0.490 ÷ 1.705	33.8 ÷ 23 @ 30m
1.705 ÷ 30	29.5 @ 30m
30 ÷ 88	40
88 ÷ 216	43,5
216 ÷ 960	46
Above 960	54

Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent/Keysight	N9038A	01/2017
Anechoic Chamber	Comtest	CSA01	01/2017
Bilog Antenna	Schaffner	CBL6112B	01/2017
Horn Antenna	EMCO	3115	01/2017
Horn Antenna	Alpha Industries	61932500	01/2017
Controller	Deisel	HD100	01/2017
Turn Table	Deisel	MA240	01/2017
LISN	GSD	NTW06	01/2017

Test procedure: RE22R02**Notes**

Azimuth position EUT-Antenna corresponding to 0° identifies the rotating table orientation (TT) in which the instrument to be tested shows the front part turned towards the antenna. Positive grades individuate clockwise rotations of TT when this one is observed from the top. For negative degrees, TT rotation is counter-clockwise.

Antenna height respect to the mass plane is conventionally individuated with: MA=XXX where XXX indicates the height (always positive and greater than 100) expressed in cm.

Antenna horizontal polarisation is indicated by POL=H.

Antenna vertical polarisation is indicated by POL=V.

EUT was tested in the three orthogonal planes.

Results and conclusions

In all the operative conditions, equipment complied with the standard limits. Graphics in following figures show the most significant registrations of the performed measurements.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 8 / 110

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.1

POL V
 MA: 100 cm
 TT: 0°
 EUT mode: Standby

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 30 – 1000 MHz, Pol. V.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.2

POL H
 MA: 170 cm
 TT: 0°
 EUT mode: Standby

Record of the measurement of radiated emissions (PK)
Maximum disturbance determined in the frequency range 30 – 1000 MHz, Pol. H.

This document may be only fully reproduced.
Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-16547 Rev. 00, page 10 / 110

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.3

POL V
 MA: 100 cm
 TT: 0°
 EUT mode: Modulation type 1

Record of the measurement of radiated emissions (PK)
Maximum disturbance determined in the frequency range 30 – 1000 MHz, Pol. V.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.4

POL H
 MA: 170 cm
 TT: 0°
 EUT mode: Modulation type 1

Record of the measurement of radiated emissions (PK)
Maximum disturbance determined in the frequency range 30 – 1000 MHz, Pol. H.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.5

POL V
 MA: 100 cm
 TT: 0°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 30 – 1000 MHz, Pol. V.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.6

POL H
 MA: 170 cm
 TT: 0°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (PK)
 Disturbance determined in the frequency range 30 – 1000 MHz, Pol. H.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.7

POL H
 MA: 100 cm
 TT: 169°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (PK)
 Disturbance determined in the frequency range 30 – 1000 MHz, Pol. H.

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.8

POL V
MA: 100 cm
TT: 0°
EUT mode: Standby

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.9

POL V
 MA: 100 cm
 TT: 0°
 EUT mode: Standby

*Record of the measurement of radiated emissions (Peak detector)
 Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)



Fig. 4.10

POL H
MA: 100 cm
TT: 0°
EUT mode: Standby

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.11

POL H
MA: 100 cm
TT: 0°
EUT mode: Standby

Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.12

POL V
MA: 100 cm
TT: 0°
EUT mode: Modulation type 1

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.13

POL V
MA: 100 cm
TT: 0°
EUT mode: Modulation type 1

*Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.14

POL H
MA: 100 cm
TT: 0°
EUT mode: Modulation type 1

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.15

POL H
MA: 100 cm
TT: 0°
EUT mode: Modulation type 1

*Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.16

POL V
MA: 100 cm
TT: 0°
EUT mode: Modulation type 2

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.17

POL V
MA: 100 cm
TT: 0°
EUT mode: Modulation type 2

*Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*

Job Number FCC-16547
Test Name Radiated Emissions
EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.18

POL H
MA: 100 cm
TT: 0°
EUT mode: Modulation type 2

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.*

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.19

POL H
 MA: 100 cm
 TT: 0°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (Peak detector)
 Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.20

POL Parallel
 MA: 150 cm
 TT: 0°
 EUT mode: Standby

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Parallel.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.21

POL Orthogonal
 MA: 150 cm
 TT: 0°
 EUT mode: Standby

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Orthogonal.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.22

POL Parallel
 MA: 150 cm
 TT: 0°
 EUT mode: Modulation type 1

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Parallel.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.23

POL Orthogonal
 MA: 150 cm
 TT: 0°
 EUT mode: Modulation type 1

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Orthogonal.

This document may be only fully reproduced.
 Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
 Report n. FCC-16547 Rev. 00, page 31 / 110

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.24

POL Parallel
 MA: 150 cm
 TT: 0°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Parallel.

Job Number FCC-16547
 Test Name Radiated Emissions
 EUT Name CAEN RFID s.r.l. - R4301P ION (UHF)




Fig. 4.25

POL Orthogonal
 MA: 150 cm
 TT: 0°
 EUT mode: Modulation type 2

Record of the measurement of radiated emissions (PK)
 Maximum disturbance determined in the frequency range 0.009 – 30 MHz, Pol. Orthogonal.

5. POWER LINES CONDUCTED EMISSIONS

Equipment shall meet the limits below when using a CISPR16 quasi-peak and average detector receivers.

FCC 15.207

FREQUENCY RANGE (MHz)	QUASI-PEAK LIMIT [dB (μV)]	AVERAGE LIMIT [dB (μV)]
0.15 – 0.50	66 – 56 ^(*)	56 – 46 ^(*)
0.50 – 5	56	46
5 – 30	60	50

^(*) Limit decreasing linearly with logarithm of frequency

Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent/Keysight	N9038A	01/2017
Screened Room	GSD	CSC01	01/2017
LISN	GSD	GSDA01	01/2017
LISN	COMTEST	---	01/2017

Test procedure: CE22R01

The EUT power cable was connected to a LISN and the monitored output of the LISN was connected to a spectrum analyzer by a transient limiter. The conducted emissions from 150 kHz to 30 MHz were monitored and compared to the specification limits

Test method

Test method was in accordance with the reference standard.

EUT modes of operations were tested in order to achieve the maximum level of emission.

Results

Equipment complied with the test specification limits.

Graphics in following figures show some registrations of the frequency spectrum of the conducted emissions.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 34 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.1

Phase 1 of EUT
 EUT mode: Standby
 Auxiliary apparatus: Laptop whit power supply linked
 B Band (0.15 – 30 MHz)

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.2

Phase 2 of EUT
 EUT mode: Standby
 Auxiliary apparatus: Laptop whit power supply linked
 B Band (0.15 – 30 MHz)

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.3

Phase 1 of EUT

EUT mode: Modulation type 1

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 37 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.4

Phase 2 of EUT

EUT mode: Modulation type 1

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 38 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.5

Phase 1 of EUT

EUT mode: Modulation type 2

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 39 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.6

Phase 2 of EUT

EUT mode: Modulation type 2

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 40 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.7

Phase 1 of auxiliary apparatus (worst case)

EUT mode: Standby

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 41 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.8

Phase 2 of auxiliary apparatus (worst case)

EUT mode: Standby

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 42 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.9

Phase 1 of auxiliary apparatus (worst case)

EUT mode: Modulation type 1

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 43 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.10

Phase 2 of auxiliary apparatus (worst case)

EUT mode: Modulation type 1

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 44 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.11

Phase 1 of auxiliary apparatus (worst case)

EUT mode: Modulation type 2

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 45 / 110

Job Number FCC-16547
 Test Name Power line Conducted Emissions
 FCC 15.207
 EUT Name R4301P ION (UHF)




Fig. 5.12

Phase 2 of auxiliary apparatus (worst case)

EUT mode: Modulation type 2

Auxiliary apparatus: Laptop whit power supply linked

B Band (0.15 – 30 MHz)

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 46 / 110

6. CONDUCTED OPERATION WITHIN THE BAND 902 - 928 MHz

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

6.1. NUMBER OF HOPPING CHANNEL

For frequency hopping systems operating in the 902 – 928 MHz band:

- if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies;
- if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies.

The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Measurement




Fig. 6.1
Modulation Type: PR_ASK_M4_TX40RX250




Fig. 6.2

Modulation Type: DSB ASK FM0 TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 48 / 110

6.2. CARRIER FREQUENCY SEPARATION

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Measurement

The following figures show the acquired graphics.





Fig. 6.3


Modulation Type 1; Channels: 0 to 1; Maxhold

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 49 / 110






This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.


Report n. FCC-16547 Rev. 00, page 51 / 110




This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 52 / 110





6.3. *TIME OF OCCUPANCY*

Measurements

Channel	Dwell Time (ms)	Nr. of Transmission for channel (average)	Modulation	Time of Occupancy (ms)
0	39.6	8 (in 20 s)	Type 1	316.8 (in 20 s)
24	34.3	8 (in 20 s)	Type 1	274.4 (in 20 s)
49	39.2	8 (in 20 s)	Type 1	313.6 (in 20 s)
0	11.1	13 (in 20 s)	Type 2	144.3 (in 20 s)
24	11.1	13 (in 20 s)	Type 2	144.3 (in 20 s)
49	12.4	13 (in 20 s)	Type 2	161.2 (in 20 s)

The following figures show the acquired graphics.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 55 / 110

Time of transmission




Fig. 6.9

Channel: 0 (Maxhold)

Modulation Type: PR_ASK_M4_TX40RX250

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 56 / 110

Nr. of Transmission for channel




Fig. 6.10

Channel: 0

Modulation Type: PR_ASK_M4_TX40RX250

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 57 / 110

Time of transmission




Fig. 6.11

Channel: 24 (Maxhold)

Modulation Type: PR_ASK_M4_TX40RX250

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 58 / 110

Nr. of Transmission for channel




Fig. 6.12
Channel: 24
Modulation Type: PR_ASK_M4_TX40RX250

Time of transmission




Fig. 6.13

Channel: 49 (Maxhold)

Modulation Type: PR_ASK_M4_TX40RX250

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 60 / 110

Nr. of Transmission for channel




Fig. 6.14

Channel: 49

Modulation Type: PR_ASK_M4_TX40RX250

Time of transmission




Fig. 6.15

Channel: 0 (maxhold)

Modulation Type: DSB_ASK_FM0_TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 62 / 110

Nr. of Transmission for channel




Fig. 6.16

Channel: 0

Modulation Type: DSB_ASK_FM0_TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 63 / 110

Time of transmission




Fig. 6.17

Channel: 24 (maxhold)

Modulation Type: DSB-ASK-FM0-TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 64 / 110

Nr. of Transmission for channel




Fig. 6.18


Channel: 24

Modulation Type: DSB_ASK_FM0_TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 65 / 110



Nr. of Transmission for channel




Fig. 6.20

Channel: 49

Modulation Type: DSB_ASK_FM0_TX160RX400

6.4. 20 dB BANDWIDTH

Measurements

Modulation: Type 1

Channel	Frequency [MHz]	Bandwidth
0	902.74918	53.9
24	915.74980	53.5
49	927.24966	53.7

Modulation: Type 2

Channel	Frequency [MHz]	Bandwidth [kHz]
0	902.75014	33.0
24	915.74977	32.5
49	927.24965	32.3

The following figures show the acquired graphics.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 68 / 110




Fig. 6.21
Modulation Type: PR_ASK_M4_TX40RX250




Fig. 6.22
Modulation Type: PR_ASK_M4_TX40RX250




Fig. 6.23
Modulation Type: PR_ASK_M4_TX40RX250

Ch 0: Bandwidth




Fig. 6.24

Modulation Type: DSB_ASK_FM0_TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 72 / 110

Ch 24: Bandwidth




Fig. 6.25

Modulation Type: DSB_ASK_FM0_TX160RX400

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 73 / 110

Ch 49: Bandwidth




Fig. 6.26

Modulation Type: DSB_ASK_FM0_TX160RX400

6.5. *PEAK OUTPUT POWER*

Equipment shall meet the limits below.


<i>FREQUENCY RANGE</i> [MHz]	<i>NR OF CHANNEL</i> [#]	<i>RF POWER OUTPUT LIMIT</i> [dBm]
902 – 928	50	30.0 (1 W)
902 – 928	< 50	24.0 (0.25 W)


Measurement


The measured values are:

<i>CHANNEL</i>	Output Power	
	Modulation type 1	Modulation type 2
0	29.7	29.6
24	29.8	29.8
49	29.7	29.4


The following figures show the acquired graphics.















6.6. BAND EDGE
Emissions must be within the band 902-928 MHz.
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
<u>Measurements</u>
The following figures show the acquired graphics.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.


Report n. FCC-16547 Rev. 00, page 82 / 110



This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 83 / 110






Fig. 6.35
Modulation Type: DSB_ASK_FM0_TX160RX400




Fig. 6.36
Modulation Type: DSB_ASK_FM0_TX160RX400

6.7. SPURIOUS RF CONDUCTED EMISSIONS

Measurements







Fig. 6.37
Modulation Type 1, Range: 30 – 1000 MHz, Max Hold







<u>Test Equipment</u>			
EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent/Keysight	N9038A	01/2017
Anechoic Chamber	Comtest	CSA01	01/2017
Bilog Antenna	Schaffner	CBL6112B	01/2017
Horn Antenna	EMCO	3115	01/2017
Controller	Deisel	HD100	01/2017
Turn Table	Deisel	MA240	01/2017
Attenuator	Narda	768-10	01/2017
<u>Test procedure:</u> CT15C01			

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 91 / 110

7. RADIATED OPERATION WITHIN THE BAND 902 - 928 MHz**7.1. SPURIOUS RADIATED EMISSIONS**

Nr Harmonics	AV Level (dBμV/m)						AV Limits (dBμV/m)	Remark
	Ch 0		Ch 24		Ch 49			
	F (MHz)	(dBμV/m)	F (MHz)	(dBμV/m)	F (MHz)	(dBμV/m)		
2	1805.5	--	1830.5	--	1854.5	--	54.0	
3		--		--		--	54.0	
4		--		--		--	54.0	
5		--		--		--	54.0	
6		--		--		--	54.0	
7		--		--		--	54.0	
8		--		--		--	54.0	
9		--		--		--	54.0	
10		--		--		--	54.0	

Note: Levels below 20 dB of limits are indicated with (--).

Nr Harmonics	Peak Level (dBµV/m)						AV Limits (dBµV/m)	Remark
	Ch 0		Ch 24		Ch 49			
	F (MHz)	(dBµV/m)	F (MHz)	(dBµV/m)	F (MHz)	(dBµV/m)		
2	1805.5	--	1830.5	--	1854.5	--	74.0	
3		--		--		--	74.0	
4		--		--		--	74.0	
5		--		--		--	74.0	
6		--		--		--	74.0	
7		--		--		--	74.0	
8		--		--		--	74.0	
9		--		--		--	74.0	
10		--		--		--	74.0	

Note: Levels below 20 dB of limits are indicated with (--).

*This document may be only fully reproduced.**Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.**Report n. FCC-16547 Rev. 00, page 92 / 110*




Fig. 7.1

POL V
MA: 100 cm
TT: 0°
EUT mode: Standby

Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.




Fig. 7.2

POL V
 MA: 100 cm
 TT: 0°
 EUT mode: Standby

*Record of the measurement of radiated emissions (Peak detector)
 Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*




Fig. 7.3

POL H
MA: 100 cm
TT: 0°
EUT mode: Standby

*Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.*




Fig. 7.4

POL H

MA: 100 cm

TT: 0°

EUT mode: Standby

Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 96 / 110




Fig. 7.5

POL V

MA: 100 cm

TT: 0°

EUT mode: Modulation type 1

Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 97 / 110




Fig. 7.6

POL V
MA: 100 cm
TT: 0°
EUT mode: Modulation type 1

*Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.*




Fig. 7.7

POL H

MA: 100 cm

TT: 0°

EUT mode: Modulation type 1

Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 99 / 110




Fig. 7.8

POL H

MA: 100 cm

TT: 0°

EUT mode: Modulation type 1

Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 100 / 110




Fig. 7.9

POL V

MA: 100 cm

TT: 0°

EUT mode: Modulation type 2

Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 101 / 110




Fig. 7.10

POL V

MA: 100 cm

TT: 0°

EUT mode: Modulation type 2

Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. V.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 102 / 110




Fig. 7.11

POL H

MA: 100 cm

TT: 0°

EUT mode: Modulation type 2

Record of the measurement of radiated emissions (AVG detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 103 / 110




Fig. 7.12

POL H

MA: 100 cm

TT: 0°

EUT mode: Modulation type 2

Record of the measurement of radiated emissions (Peak detector)
Maximum disturbance determined in the frequency range 1 – 10 GHz, Pol. H.

<u>Test Equipment</u>			
EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
EMI Receiver	Agilent	E4440	01/2017
MXE EMI Receiver	Agilent/Keysight	N9038A	01/2017
Anechoic Chamber	Comtest	CSA01	01/2017
Bilog Antenna	Schaffner	CBL6112B	01/2017
Horn Antenna	EMCO	3115	01/2017
Controller	Deisel	HD100	01/2017
Turn Table	Deisel	MA240	01/2017
LISN	GSD	NTW06	01/2017
<u>Test procedure:</u> CT15R01			

This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.

Report n. FCC-16547 Rev. 00, page 105 / 110

8. PHOTO




Fig. 8.1

Conducted Emissions Test Set-up




Fig. 8.2

*Radiated Emissions Test Set-up
Range: 30 – 1000 MHz*




Fig. 8.3

Radiated Emissions Test Set-up

Range: 1 – 10 GHz



Fig. 8.4

Radiated Emissions Test Set-up



Fig. 8.5
Conducted Transmission Test Set-up