

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Report No.: RFBCKS-WTW-P25090710-3

FCC ID: UXX-FE990B40NA

Product: 5G NR Module

Brand: Ericsson

Model No.: FE990B40-NAD

Received Date: 2025/9/23

Test Date: 2025/10/1 ~ 2025/11/11

Issued Date: 2025/12/15

Applicant: Ericsson Enterprise Wireless Solutions, Inc.

Address: 1100 West Idaho Street, Boise, Idaho, United States, 83702

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration /
Designation Number: 788550 / TW0003

Approved by: Jeremy Lin , **Date:** 2025/12/15
Jeremy Lin / Project Engineer

This test report consists of 42 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Pettie Chen / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Antenna Description of EUT	9
3.3 Test Mode Applicability and Tested Channel Detail.....	10
3.3.1 NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)	10
3.4 Test Program Used and Operation Descriptions	11
3.5 Connection Diagram of EUT and Peripheral Devices	11
3.6 Configuration of Peripheral Devices and Cable Connections	11
4 Test Instruments	12
4.1 Maximum EIRP	12
4.2 Radiated Spurious Emissions below 1GHz	12
4.3 Radiated Spurious Emissions above 1GHz	13
5 Limits of Test Items.....	14
5.1 Maximum EIRP	14
5.2 Radiated Spurious Emissions below 1GHz	14
5.3 Radiated Spurious Emissions above 1GHz	14
6 Test Arrangements	15
6.1 Maximum EIRP	15
6.1.1 Test Setup	15
6.1.2 Test Procedure	15
6.2 Radiated Spurious Emissions below 1GHz	16
6.2.1 Test Setup	16
6.2.2 Test Procedure	17
6.3 Radiated Spurious Emissions above 1GHz	18
6.3.1 Test Setup	18
6.3.2 Test Procedure	18
7 Test Results of Test Item	19
7.1 Maximum EIRP	19
7.1.1 NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)	19
7.2 Radiated Spurious Emissions below 1GHz	38
7.2.1 NR n48	38
7.3 Radiated Spurious Emissions above 1GHz	40
7.3.1 NR n48	40
8 Pictures of Test Arrangements	41
9 Information of the Testing Laboratories	42

Release Control Record

Issue No.	Description	Date Issued
RFBCKS-WTW-P25090710-3	Original release.	2025/12/15

1 Certificate

Product: 5G NR Module

Brand: Ericsson

Test Model: FE990B40-NAD

Sample Status: Engineering sample

Applicant: Ericsson Enterprise Wireless Solutions, Inc.

Test Date: 2025/10/1 ~ 2025/11/11

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Measurement procedure: ANSI/TIA/EIA-603-E 2016
ANSI C63.26-2015
KDB 971168 D01 Power Meas License Digital Systems v03r01
KDB 940660 D01 Part 96 CBRS Eqpt v03
KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

Standard / Clause	Test Item	Result	Remark
Part 2.1046 Part 96.41(b)	Maximum EIRP	Pass	Meet the requirement of limit.
Part 2.1047	Modulation Characteristics	N/A	Refer to Note
Part 2.1046 Part 96.41(b)	Maximum Power Spectral Density	N/A	This device is End User Device.
Part 96.41(g)	Peak to Average Ratio	N/A	Refer to Note
Part 2.1049	Bandwidth	N/A	Refer to Note
Part 2.1051 Part 96.41(e)	Conducted Spurious Emissions	N/A	Refer to Note
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions below 1GHz	Pass	Minimum passing margin is -10.21 dB at 35.82 MHz
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions above 1GHz	Pass	Minimum passing margin is -7.82 dB at 7249.98 MHz
Part 2.1055	Frequency Stability	N/A	Refer to Note

Note:

- Only test item of Maximum EIRP and radiated spurious emissions was performed for this report. Other testing data please refer to Sporton report no.: FG492402D_R01 for module (Brand: Telit, Model: FE990B40-NAD).
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
Effective Radiated Power and Equivalent Isotropically Radiated Power	-	1.371 dB
Radiated Spurious Emissions below 1GHz	9 kHz ~ 30 MHz	2.44 dB
	30 MHz ~ 1 GHz	2.95 dB
Radiated Spurious Emissions above 1GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	5G NR Module
Brand	Ericsson
Test Model	FE990B40-NAD
Status of EUT	Engineering sample
Power Supply Rating	3.8Vdc
EUT Category	End User Device
Modulation Type	DFT-s-OFDM, CP-OFDM
5G NR support SISO bands	5G NR: n48
5G NR support MIMO bands	5G NR: n48
PC3 for Power Class	5G NR: n48
Band Covered Information	n48 cover n42, n43 (Part 96)

Note:

1. This report is prepared for FCC class II permissive change. The difference compared with original report is listed as below. Therefore, test items for Maximum EIRP and Radiated Spurious Emissions test had been re-tested in this report.
 - a. There are minor changes to the EUT's antenna connector, but these do not affect the RF characteristics & output power.
 - b. Additional antennas are added.
 - c. The output power for some frequency bands will be reduced.

2. EUT Overview

SISO

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)

Output Power: Full Power

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
10 MHz	3555 ~ 3694.98	BPSK	0.119	20.74
		QPSK	0.158	21.98
		16QAM	0.115	20.62
		64QAM	0.109	20.37
		256QAM	0.111	20.46
15 MHz	3557.52 ~ 3692.49	BPSK	0.121	20.81
		QPSK	0.120	20.79
		16QAM	0.117	20.67
		64QAM	0.110	20.40
		256QAM	0.110	20.43
20 MHz	3560.01 ~ 3690	BPSK	0.121	20.82
		QPSK	0.120	20.79
		16QAM	0.117	20.68
		64QAM	0.109	20.38
		256QAM	0.111	20.46
30 MHz	3565.02 ~ 3684.99	BPSK	0.119	20.76
		QPSK	0.121	20.81
		16QAM	0.116	20.66
		64QAM	0.110	20.41
		256QAM	0.112	20.48

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
40 MHz	3570 ~ 3679.98	BPSK	0.121	20.81
		QPSK	0.121	20.84
		16QAM	0.117	20.69
		64QAM	0.111	20.44
		256QAM	0.112	20.49

Output Power: dBm/10 MHz

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
15 MHz	3557.52 ~ 3692.49	BPSK	0.119	20.74
		QPSK	0.118	20.73
		16QAM	0.115	20.60
		64QAM	0.108	20.33
		256QAM	0.109	20.36
20 MHz	3560.01 ~ 3690	BPSK	0.119	20.75
		QPSK	0.118	20.72
		16QAM	0.115	20.61
		64QAM	0.107	20.31
		256QAM	0.110	20.40
30 MHz	3565.02 ~ 3684.99	BPSK	0.117	20.70
		QPSK	0.118	20.72
		16QAM	0.115	20.60
		64QAM	0.108	20.34
		256QAM	0.110	20.42
40 MHz	3570 ~ 3679.98	BPSK	0.120	20.78
		QPSK	0.118	20.73
		16QAM	0.116	20.63
		64QAM	0.109	20.38
		256QAM	0.110	20.42

MIMO

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)

Output Power: Full Power

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
10 MHz	3555 ~ 3694.98	QPSK	0.158	21.98
		16QAM	0.110	20.42
		64QAM	0.096	19.84
		256QAM	0.046	16.64
15 MHz	3557.52 ~ 3692.49	QPSK	0.158	21.98
		16QAM	0.110	20.41
		64QAM	0.096	19.81
		256QAM	0.046	16.65
20 MHz	3560.01 ~ 3690	QPSK	0.158	22.00
		16QAM	0.110	20.43
		64QAM	0.097	19.85
		256QAM	0.046	16.64
30 MHz	3565.02 ~ 3684.99	QPSK	0.158	21.99
		16QAM	0.110	20.42
		64QAM	0.097	19.86
		256QAM	0.046	16.64
40 MHz	3570 ~ 3679.98	QPSK	0.159	22.02
		16QAM	0.111	20.45
		64QAM	0.097	19.88
		256QAM	0.047	16.68

Output Power: dBm/10 MHz

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
15 MHz	3557.52 ~ 3692.49	QPSK	0.155	21.91
		16QAM	0.108	20.34
		64QAM	0.094	19.75
		256QAM	0.045	16.58
20 MHz	3560.01 ~ 3690	QPSK	0.156	21.93
		16QAM	0.109	20.36
		64QAM	0.095	19.79
		256QAM	0.045	16.58
30 MHz	3565.02 ~ 3684.99	QPSK	0.156	21.92
		16QAM	0.108	20.35
		64QAM	0.095	19.79
		256QAM	0.045	16.58
40 MHz	3570 ~ 3679.98	QPSK	0.157	21.95
		16QAM	0.109	20.39
		64QAM	0.096	19.81
		256QAM	0.046	16.61

- For detailed information about each WWAN bands frequency range, bandwidth mode of the product, please refer to section 3.3 of the report.
- The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Band	Frequency Range (MHz)	Gain (dBi)					Worst case Ant	Cable loss		Worst case Ant connected to Net Gain	
		Maxtena Antenna				Ant 170923					
		5G-1	5G-2	5G-3	5G-4						
n2	1850-1910	3.38	3.57	2.8	3.29	2.63	3.57	0.47	0.717	3.1	2.853
n5	824-849	1.06	-0.56	-0.99	-0.76	3.22	3.22	0.339	0.484	2.881	2.736
n7	2500-2570	5.15	5.15	4.55	4.53	2.9	5.15	0.648	1.124	4.502	4.026
n12	699-716	0.64	-0.83	0.16	0.16	3.17	3.17	0.243	0.358	2.927	2.812
n13	777-787	0.06	-2.03	-0.02	-0.49	3.06	3.06	0.339	0.484	2.721	2.576
n14	788-798	0.34	-1.68	0.27	-0.84	3.16	3.16	0.339	0.484	2.821	2.676
n25	1850-1915	3.38	3.57	2.8	3.29	2.63	3.57	0.47	0.717	3.1	2.853
n26	814-849	1.06	-0.56	-0.99	-0.76	3.22	3.22	0.339	0.484	2.881	2.736
n30	2305-2315	4.99	5.27	5.02	4.63	2.89	5.27	0.648	1.124	4.622	4.146
n38	2570-2620	4.72	4.94	4.9	5.11	2.9	5.11	0.648	1.124	4.462	3.986
n41	2496-2690	5.25	5.24	4.9	5.11	3.1	5.25	0.648	1.124	4.602	4.126
n48	3550-3700	5.13	4.95	5.19	4.71	3.24	5.19	0.799	1.174	4.391	4.016
n66	1710-1780	1.84	0.56	1.35	1.29	3.14	3.14	0.47	0.717	2.67	2.423
n70	1695-1710	1.81	0.56	0.56	0.22	3.14	3.14	0.42	0.606	2.72	2.534
n71	663-698	-0.11	-1.35	-0.27	-0.47	2.94	2.94	0.24	0.358	2.697	2.582
n77	3450-3980	5.13	4.95	5.19	5.07	3.48	5.19	0.813	1.31	4.377	3.88
n78	3450-3800	5.13	4.95	5.19	5.07	3.48	5.19	0.813	1.31	4.377	3.88

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.3 Test Mode Applicability and Tested Channel Detail

Following channel(s) was (were) selected for the final test as listed below:

3.3.1 NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)


Test Item	Tx/Rx condition	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum EIRP	1Tx, 2Tx	637000(3555.00 MHz) 641666(3624.99 MHz) 646333(3694.98 MHz)	10 MHz	BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		637168(3557.52 MHz) 641666(3624.99 MHz) 646166(3692.49 MHz)	15 MHz	BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		637334(3560.01 MHz) 641666(3624.99 MHz) 646000(3690.00 MHz)	20 MHz	BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		637668(3565.02 MHz) 641666(3624.99 MHz) 645666(3684.99 MHz)	30 MHz	BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		638000(3570.00 MHz) 641666(3624.99 MHz) 645332(3679.98 MHz)	40 MHz	BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
Radiated Spurious Emissions below 1GHz	2Tx	641666(3624.99 MHz)	40 MHz	QPSK	1 RB
Radiated Spurious Emissions above 1GHz	2Tx	641666(3624.99 MHz)	40 MHz	QPSK	1 RB

3.4 Test Program Used and Operation Descriptions

Set the EUT under transmission condition continuously at specific channel frequency.

3.5 Connection Diagram of EUT and Peripheral Devices

For Maxtena Antenna



Under Table

Remote Site



(B) UXM 5G
Wireless Test
Platform

3.6 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Jig	NA	NA	NA	NA	Supplied by applicant
B	UXM 5G Wireless Test Platform	Keysight	E7515B	MY60102115	NA	-

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1.8	No	1	Supplied by applicant
2	RF Cable	4	0.1	No	0	Supplied by applicant
3	RF Cable	4	3	Yes	0	Supplied by applicant

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Maximum EIRP

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030B	MY57140938	2025/3/24	2026/3/23
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A
UXM 5G Wireless Test Platform Keysight	E7515B	MY60102115	2025/5/26	2026/5/25

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/10/1 ~ 2025/11/11

4.2 Radiated Spurious Emissions below 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-472	2025/9/16	2026/9/15
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC 330H	980112	2025/9/21	2026/9/20
	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2025/10/31

4.3 Radiated Spurious Emissions above 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	7	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-969	2024/11/10	2025/11/9
	BBHA 9170	148	2024/11/10	2025/11/9
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC 184045	980116	2025/9/21	2026/9/20
	EMC118A45SE	980809	2025/4/24	2026/4/23
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2025/6/30	2026/6/29
	EMC102-KM-KM-3000	150929	2025/6/30	2026/6/29
	EMC104-SM-SM- 8000+3000	171005	2025/9/21	2026/9/20
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	2025/9/21	2026/9/20
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2025/10/30

5 Limits of Test Items

5.1 Maximum EIRP

For NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz):

Device Category	Maximum EIRP (dBm/10 MHz)
End User Device	23
Category A CBSD	30
Category B CBSD	47

5.2 Radiated Spurious Emissions below 1GHz

For NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz):

The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz.

5.3 Radiated Spurious Emissions above 1GHz

For NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz):


The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

6 Test Arrangements

6.1 Maximum EIRP

6.1.1 Test Setup

Conducted Power Measurement:



6.1.2 Test Procedure

Conducted Power Measurement:

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology and link to spectrum analyzer measurements. Set the EUT to transmit under low, middle and high channel and record the power level shown on spectrum analyzer. Power measurements use detector average (rms).

Measurement method refers to ANSI C63.26 section 5.2.4.4.

- Set span to 2 × to 3 × the OBW.
- Set RBW = 1% to 5% of the OBW.
- Set VBW ≥ 3 × RBW.
- Set number of measurement points in sweep ≥ 2 × span / RBW.
- Set Sweep time = auto-couple.
- Detector = power averaging (rms).
- Set sweep trigger to “free run.”
- Trace average at least 100 traces in power averaging (rms) mode.
- Use the Band/Channel Power function to determine the integrated power per 10 MHz bandwidth and full bandwidth, according to the 47 CFR FCC Part 96 standard.
- If Duty cycle < 98%, Add 10 log (1/duty cycle) to the measured power level to compute the average power during continuous transmission.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , e.g., dBm or dBW)


P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)


6.2 Radiated Spurious Emissions below 1GHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.2.2 Test Procedure

The EUT is configured to set data modulation and maximum power using WWAN technology.

- a. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following ANSI C63.26 section 5.5 and 5.2.7
- e. $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- f. $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.
2. The amplitude of spurious emissions in the range 9 kHz to 30 MHz which are attenuated more than 20 dB below the permissible value need not be reported.

6.3 Radiated Spurious Emissions above 1GHz

6.3.1 Test Setup

For radiated emission above 1 GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.3.2 Test Procedure

The EUT is configured to set data modulation and maximum power using WWAN technology.

- In the semi-anechoic chamber, EUT placed on the 1.5 m height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- Following ANSI C63.26 section 5.5 and 5.2.7
- $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.

7 Test Results of Test Item

7.1 Maximum EIRP

Environmental Conditions:	23°C, 62% RH	Tested By:	Charles Hsiao
---------------------------	--------------	------------	---------------

7.1.1 NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637000	CH 641666	CH 646332
			3555 MHz	3624.99 MHz	3694.98 MHz
BPSK	1	1	16.14	16.35	16.00
	1	0	16.22	16.25	16.21
QPSK	1	1	16.30	16.32	16.31
	1	0	16.18	16.30	16.17
	1	11	16.20	16.25	16.22
	1	22	16.09	16.20	16.04
	1	23	16.23	16.20	16.13
	12	0	16.37	16.38	16.32
	12	6	16.18	16.29	16.19
	12	12	16.36	16.40	16.31
	24	0	16.28	16.34	16.29
16QAM	1	0	16.23	16.21	16.14
64QAM	1	0	15.96	15.98	15.87
256QAM	1	0	16.02	16.07	16.00

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.00	16.35	20.39	20.74	23
QPSK	16.04	16.40	20.43	20.79	23
16QAM	16.14	16.23	20.53	20.62	23
64QAM	15.87	15.98	20.26	20.37	23
256QAM	16.00	16.07	20.39	20.46	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 15 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637168	CH 641666	CH 646166
			3557.52 MHz	3624.99 MHz	3692.49 MHz
BPSK	1	1	16.11	16.42	16.01
	1	0	16.20	16.31	16.20
QPSK	1	1	16.40	16.40	16.33
	1	0	16.18	16.27	16.18
	1	19	16.17	16.29	16.17
	1	36	16.10	16.24	16.05
	1	37	16.14	16.16	16.14
	18	0	16.28	16.31	16.27
	18	10	16.23	16.35	16.23
	18	20	16.29	16.34	16.25
	36	0	16.27	16.31	16.22
	38	0	16.35	16.37	16.27
16QAM	1	0	16.27	16.28	16.15
64QAM	1	0	16.01	15.95	15.94
256QAM	1	0	15.99	16.04	16.03

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.01	16.42	20.40	20.81	23
QPSK	16.05	16.40	20.44	20.79	23
16QAM	16.15	16.28	20.54	20.67	23
64QAM	15.94	16.01	20.33	20.40	23
256QAM	15.99	16.04	20.38	20.43	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 20 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637334	CH 641666	CH 646000
			3560.01 MHz	3624.99 MHz	3690 MHz
BPSK	1	1	16.09	16.43	16.09
	1	0	16.23	16.31	16.23
QPSK	1	1	16.40	16.36	16.36
	1	0	16.26	16.28	16.13
	1	26	16.15	16.24	16.17
	1	49	16.12	16.26	16.01
	1	50	16.21	16.22	16.20
	25	0	16.32	16.31	16.33
	25	13	16.25	16.32	16.24
	25	26	16.29	16.36	16.29
	50	0	16.31	16.36	16.30
	51	0	16.35	16.35	16.37
16QAM	1	0	16.24	16.29	16.14
64QAM	1	0	15.94	15.99	15.88
256QAM	1	0	16.03	16.01	16.07

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.09	16.43	20.48	20.82	23
QPSK	16.01	16.40	20.40	20.79	23
16QAM	16.14	16.29	20.53	20.68	23
64QAM	15.88	15.99	20.27	20.38	23
256QAM	16.01	16.07	20.40	20.46	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 30 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637668	CH 641666	CH 645666
			3565.02 MHz	3624.99 MHz	3684.99 MHz
BPSK	1	1	16.11	16.37	16.06
	1	0	16.21	16.28	16.13
QPSK	1	1	16.40	16.36	16.37
	1	0	16.25	16.22	16.12
	1	39	16.16	16.32	16.17
	1	76	16.13	16.25	16.02
	1	77	16.14	16.23	16.18
	36	0	16.38	16.33	16.28
	36	21	16.21	16.30	16.19
	36	42	16.38	16.32	16.26
	75	0	16.28	16.34	16.28
	78	0	16.42	16.42	16.35
16QAM	1	0	16.19	16.27	16.14
64QAM	1	0	16.02	15.98	15.89
256QAM	1	0	15.99	16.09	16.05

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.06	16.37	20.45	20.76	23
QPSK	16.02	16.42	20.41	20.81	23
16QAM	16.14	16.27	20.53	20.66	23
64QAM	15.89	16.02	20.28	20.41	23
256QAM	15.99	16.09	20.38	20.48	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 40 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 638000	CH 641666	CH 645332
			3570 MHz	3624.99 MHz	3679.98 MHz
BPSK	1	1	16.18	16.42	16.10
	1	0	16.24	16.31	16.23
QPSK	1	1	16.40	16.45	16.38
	1	0	16.28	16.30	16.20
	1	53	16.25	16.34	16.25
	1	104	16.19	16.27	16.09
	1	105	16.24	16.26	16.20
	50	0	16.38	16.41	16.35
	50	28	16.28	16.38	16.25
	50	56	16.39	16.40	16.33
	100	0	16.36	16.39	16.32
	106	0	16.42	16.42	16.37
16QAM	1	0	16.29	16.30	16.22
64QAM	1	0	16.04	16.05	15.95
256QAM	1	0	16.09	16.10	16.09

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.10	16.42	20.49	20.81	23
QPSK	16.09	16.45	20.48	20.84	23
16QAM	16.22	16.30	20.61	20.69	23
64QAM	15.95	16.05	20.34	20.44	23
256QAM	16.09	16.10	20.48	20.49	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 15 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637168	CH 641666	CH 646166
			3557.52 MHz	3624.99 MHz	3692.49 MHz
BPSK	1	1	16.04	16.35	15.94
	1	0	16.13	16.24	16.14
QPSK	1	1	16.33	16.34	16.26
	1	0	16.12	16.21	16.12
	1	19	16.11	16.23	16.10
	1	36	16.03	16.17	15.98
	1	37	16.07	16.09	16.08
	18	0	16.21	16.25	16.21
	18	10	16.17	16.28	16.17
	18	20	16.23	16.27	16.18
	36	0	16.21	16.25	16.15
	38	0	14.82	14.81	14.71
16QAM	1	0	16.21	16.21	16.08
64QAM	1	0	15.94	15.88	15.88
256QAM	1	0	15.93	15.97	15.96

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	15.94	16.35	20.33	20.74	23
QPSK	14.71	16.34	19.10	20.73	23
16QAM	16.08	16.21	20.47	20.60	23
64QAM	15.88	15.94	20.27	20.33	23
256QAM	15.93	15.97	20.32	20.36	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 20 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637334	CH 641666	CH 646000
			3560.01 MHz	3624.99 MHz	3690 MHz
BPSK	1	1	16.02	16.36	16.02
	1	0	16.16	16.25	16.16
QPSK	1	1	16.33	16.29	16.30
	1	0	16.19	16.21	16.06
	1	26	16.09	16.17	16.10
	1	49	16.06	16.19	15.95
	1	50	16.15	16.16	16.13
	25	0	16.25	16.25	16.26
	25	13	16.19	16.25	16.18
	25	26	16.23	16.29	16.23
	50	0	13.27	13.28	13.29
	51	0	13.35	13.32	13.28
16QAM	1	0	16.18	16.22	16.08
64QAM	1	0	15.88	15.92	15.82
256QAM	1	0	15.97	15.94	16.01

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.02	16.36	20.41	20.75	23
QPSK	13.27	16.33	17.66	20.72	23
16QAM	16.08	16.22	20.47	20.61	23
64QAM	15.82	15.92	20.21	20.31	23
256QAM	15.94	16.01	20.33	20.40	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 30 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 637668	CH 641666	CH 645666
			3565.02 MHz	3624.99 MHz	3684.99 MHz
BPSK	1	1	16.05	16.31	15.99
	1	0	16.14	16.22	16.06
QPSK	1	1	16.33	16.29	16.30
	1	0	16.19	16.16	16.05
	1	39	16.10	16.26	16.10
	1	76	16.07	16.18	15.96
	1	77	16.08	16.16	16.12
	36	0	15.36	15.32	15.22
	36	21	15.19	15.21	15.10
	36	42	15.32	15.25	15.26
	75	0	11.27	11.30	11.28
	78	0	11.35	11.39	11.34
16QAM	1	0	16.13	16.21	16.07
64QAM	1	0	15.95	15.91	15.82
256QAM	1	0	15.92	16.03	15.98

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	15.99	16.31	20.38	20.70	23
QPSK	11.27	16.33	15.66	20.72	23
16QAM	16.07	16.21	20.46	20.60	23
64QAM	15.82	15.95	20.21	20.34	23
256QAM	15.92	16.03	20.31	20.42	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)


NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 40 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 638000	CH 641666	CH 645332
			3570 MHz	3624.99 MHz	3679.98 MHz
BPSK	1	1	16.11	16.39	16.03
	1	0	16.16	16.24	16.17
QPSK	1	1	16.34	16.34	16.31
	1	0	16.21	16.23	16.14
	1	53	16.18	16.27	16.18
	1	104	16.12	16.21	16.03
	1	105	16.18	16.20	16.14
	50	0	13.79	13.84	13.85
	50	28	13.76	13.87	13.73
	50	56	13.88	13.87	13.79
	100	0	9.78	9.81	9.78
	106	0	9.83	9.85	9.78
16QAM	1	0	16.22	16.24	16.15
64QAM	1	0	15.98	15.99	15.89
256QAM	1	0	16.03	16.03	16.03

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
BPSK	16.03	16.39	20.42	20.78	23
QPSK	9.78	16.34	14.17	20.73	23
16QAM	16.15	16.24	20.54	20.63	23
64QAM	15.89	15.99	20.28	20.38	23
256QAM	16.03	16.03	20.42	20.42	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

Spectrum Plot of Worst Value



QPSK CH 641666 (3624.99 MHz)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637000			CH 641666			CH 646332		
			3555 MHz			3624.99 MHz			3694.98 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.20	14.52	17.37	14.18	14.49	17.35	14.14	14.54	17.35
	1	0	12.68	12.98	15.84	12.65	12.99	15.83	12.66	12.91	15.80
	1	11	14.51	14.64	17.59	14.46	14.67	17.58	14.46	14.70	17.59
	1	22	14.15	14.42	17.30	14.12	14.39	17.27	14.16	14.40	17.29
	1	23	12.54	12.84	15.70	12.52	12.84	15.69	12.52	12.85	15.70
	12	0	13.02	13.01	16.03	13.04	13.06	16.06	12.99	12.98	16.00
	12	6	14.47	14.48	17.49	14.54	14.54	17.55	14.51	14.47	17.50
	12	12	12.92	12.96	15.95	12.94	12.92	15.94	12.92	13.00	15.97
	24	0	13.16	13.10	16.14	13.17	13.07	16.13	13.18	13.07	16.14
16QAM	1	0	12.92	13.08	16.01	12.92	13.09	16.02	12.97	13.06	16.03
64QAM	1	0	12.30	12.56	15.44	12.33	12.48	15.42	12.33	12.55	15.45
256QAM	1	0	9.19	9.19	12.20	9.19	9.28	12.25	9.23	9.22	12.24

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.69	17.59	20.08	21.98	23
16QAM	16.01	16.03	20.40	20.42	23
64QAM	15.42	15.45	19.81	19.84	23
256QAM	12.2	12.25	16.59	16.64	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 15 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637168			CH 641666			CH 646166		
			3557.52 MHz			3624.99 MHz			3692.49 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.15	14.46	17.32	14.21	14.51	17.37	14.19	14.47	17.34
	1	0	12.74	12.93	15.85	12.67	12.91	15.80	12.74	12.96	15.86
	1	19	14.52	14.60	17.57	14.46	14.64	17.56	14.48	14.67	17.59
	1	36	14.13	14.40	17.28	14.14	14.38	17.27	14.22	14.45	17.35
	1	37	12.51	12.83	15.68	12.45	12.92	15.70	12.45	12.92	15.70
	18	0	13.02	13.02	16.03	12.94	13.00	15.98	13.00	13.07	16.05
	18	10	14.54	14.49	17.53	14.44	14.50	17.48	14.46	14.55	17.52
	18	20	12.88	12.92	15.91	12.91	12.97	15.95	12.86	13.02	15.95
	36	0	13.20	13.12	16.17	13.23	13.11	16.18	13.23	13.12	16.19
16QAM	1	0	12.97	13.05	16.02	12.92	13.06	16.00	12.96	13.04	16.01
64QAM	1	0	12.36	12.46	15.42	12.33	12.47	15.41	12.31	12.46	15.40
256QAM	1	0	9.18	9.27	12.24	9.16	9.23	12.21	9.22	9.27	12.26

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.68	17.59	20.07	21.98	23
16QAM	16	16.02	20.39	20.41	23
64QAM	15.4	15.42	19.79	19.81	23
256QAM	12.21	12.26	16.60	16.65	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 20 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637334			CH 641666			CH 646000		
			3560.01 MHz			3624.99 MHz			3690 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.18	14.46	17.33	14.21	14.53	17.38	14.12	14.50	17.32
	1	0	12.73	12.99	15.87	12.73	13.00	15.88	12.66	12.99	15.84
	1	26	14.52	14.63	17.59	14.45	14.64	17.56	14.53	14.66	17.61
	1	49	14.21	14.38	17.31	14.22	14.37	17.31	14.20	14.42	17.32
	1	50	12.50	12.89	15.71	12.53	12.89	15.72	12.45	12.93	15.71
	25	0	12.99	12.97	15.99	12.95	13.00	15.99	12.94	13.04	16.00
	25	13	14.51	14.50	17.52	14.47	14.49	17.49	14.52	14.46	17.50
	25	26	12.86	12.94	15.91	12.94	13.01	15.99	12.89	12.95	15.93
	50	0	13.14	13.04	16.10	13.21	13.03	16.13	13.20	13.11	16.17
16QAM	1	0	12.89	13.01	15.96	12.99	13.06	16.04	12.99	13.05	16.03
64QAM	1	0	12.38	12.47	15.44	12.33	12.56	15.46	12.39	12.50	15.46
256QAM	1	0	9.16	9.20	12.19	9.26	9.20	12.24	9.19	9.28	12.25

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.71	17.61	20.10	22.00	23
16QAM	15.96	16.04	20.35	20.43	23
64QAM	15.44	15.46	19.83	19.85	23
256QAM	12.19	12.25	16.58	16.64	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 30 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637668			CH 641666			CH 645666		
			3565.02 MHz			3624.99 MHz			3684.99 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.13	14.55	17.36	14.21	14.45	17.34	14.18	14.55	17.38
	1	0	12.73	12.92	15.84	12.68	12.93	15.82	12.71	12.98	15.86
	1	39	14.53	14.64	17.60	14.53	14.62	17.59	14.44	14.61	17.54
	1	76	14.18	14.45	17.33	14.17	14.38	17.29	14.14	14.44	17.30
	1	77	12.54	12.87	15.72	12.52	12.85	15.70	12.47	12.85	15.67
	36	0	13.04	12.97	16.02	12.96	13.04	16.01	13.00	13.06	16.04
	36	21	14.52	14.51	17.53	14.54	14.50	17.53	14.46	14.46	17.47
	36	42	12.94	12.92	15.94	12.91	12.94	15.94	12.84	13.02	15.94
	75	0	13.14	13.12	16.14	13.19	13.05	16.13	13.21	13.07	16.15
16QAM	1	0	12.89	13.04	15.98	12.92	13.11	16.03	12.95	13.03	16.00
64QAM	1	0	12.37	12.54	15.47	12.40	12.48	15.45	12.34	12.49	15.43
256QAM	1	0	9.20	9.28	12.25	9.24	9.22	12.24	9.25	9.19	12.23

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.67	17.6	20.06	21.99	23
16QAM	15.98	16.03	20.37	20.42	23
64QAM	15.43	15.47	19.82	19.86	23
256QAM	12.23	12.25	16.62	16.64	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 40 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 638000			CH 641666			CH 645332		
			3570 MHz			3624.99 MHz			3679.98 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.19	14.54	17.38	14.22	14.55	17.40	14.18	14.53	17.37
	1	0	12.72	12.93	15.84	12.74	13.00	15.88	12.74	12.96	15.86
	1	53	14.43	14.62	17.54	14.53	14.70	17.63	14.45	14.66	17.57
	1	104	14.17	14.40	17.30	14.22	14.45	17.35	14.15	14.41	17.29
	1	105	12.49	12.87	15.69	12.54	12.93	15.75	12.48	12.91	15.71
	50	0	12.94	13.03	16.00	13.04	13.07	16.07	12.96	13.07	16.03
	50	28	14.45	14.52	17.50	14.54	14.56	17.56	14.49	14.47	17.49
	50	56	12.84	13.00	15.93	12.94	13.02	15.99	12.94	12.97	15.97
	100	0	13.23	13.02	16.14	13.23	13.12	16.19	13.22	13.02	16.13
16QAM	1	0	12.94	13.08	16.02	12.99	13.11	16.06	12.99	13.09	16.05
64QAM	1	0	12.36	12.48	15.43	12.4	12.56	15.49	12.3	12.54	15.43
256QAM	1	0	9.18	9.23	12.22	9.26	9.29	12.29	9.19	9.22	12.22

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.69	17.63	20.08	22.02	23
16QAM	16.02	16.06	20.41	20.45	23
64QAM	15.43	15.49	19.82	19.88	23
256QAM	12.22	12.29	16.61	16.68	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 15 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637168			CH 641666			CH 646166		
			3557.52 MHz			3624.99 MHz			3692.49 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.09	14.39	17.25	14.14	14.45	17.31	14.13	14.40	17.28
	1	0	12.68	12.87	15.79	12.61	12.84	15.74	12.68	12.90	15.80
	1	19	14.45	14.54	17.51	14.39	14.58	17.50	14.42	14.60	17.52
	1	36	14.06	14.33	17.21	14.07	14.32	17.21	14.15	14.38	17.28
	1	37	12.45	12.77	15.62	12.39	12.86	15.64	12.38	12.85	15.63
	18	0	12.96	12.95	15.97	12.87	12.94	15.92	12.94	13.01	15.99
	18	10	14.48	14.43	17.47	14.38	14.43	17.42	14.40	14.49	17.46
	18	20	12.81	12.85	15.84	12.84	12.91	15.89	12.80	12.96	15.89
	36	0	10.16	10.07	13.13	10.22	10.02	13.13	10.23	10.06	13.16
16QAM	1	0	12.90	12.98	15.95	12.86	13.00	15.94	12.90	12.98	15.95
64QAM	1	0	12.30	12.39	15.36	12.27	12.40	15.35	12.24	12.39	15.33
256QAM	1	0	9.12	9.21	12.18	9.10	9.16	12.14	9.15	9.21	12.19

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	13.13	17.52	17.52	21.91	23
16QAM	15.94	15.95	20.33	20.34	23
64QAM	15.33	15.36	19.72	19.75	23
256QAM	12.14	12.19	16.53	16.58	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 20 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637334			CH 641666			CH 646000		
			3560.01 MHz			3624.99 MHz			3690 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.11	14.39	17.26	14.14	14.46	17.31	14.06	14.44	17.26
	1	0	12.66	12.93	15.81	12.67	12.93	15.81	12.60	12.92	15.77
	1	26	14.45	14.56	17.52	14.38	14.58	17.49	14.47	14.58	17.54
	1	49	14.15	14.31	17.24	14.16	14.30	17.24	14.13	14.35	17.25
	1	50	12.43	12.82	15.64	12.46	12.83	15.66	12.38	12.86	15.64
	25	0	12.92	12.91	15.93	12.88	12.93	15.92	12.88	12.97	15.94
	25	13	14.45	14.43	17.45	14.40	14.42	17.42	14.45	14.40	17.44
	25	26	12.80	12.88	15.85	12.87	12.95	15.92	12.82	12.89	15.87
	50	0	10.07	9.99	13.04	10.11	9.96	13.05	10.14	10.03	13.10
16QAM	1	0	12.82	12.95	15.90	12.92	13.00	15.97	12.92	12.98	15.96
64QAM	1	0	12.31	12.41	15.37	12.27	12.50	15.40	12.33	12.44	15.40
256QAM	1	0	9.10	9.13	12.13	9.20	9.14	12.18	9.13	9.22	12.19

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	13.04	17.54	17.43	21.93	23
16QAM	15.9	15.97	20.29	20.36	23
64QAM	15.37	15.4	19.76	19.79	23
256QAM	12.13	12.19	16.52	16.58	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 30 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 637668			CH 641666			CH 645666		
			3565.02 MHz			3624.99 MHz			3684.99 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.06	14.49	17.29	14.15	14.39	17.28	14.11	14.49	17.31
	1	0	12.66	12.85	15.77	12.61	12.87	15.75	12.65	12.92	15.80
	1	39	14.46	14.57	17.53	14.47	14.55	17.52	14.37	14.54	17.47
	1	76	14.12	14.38	17.26	14.10	14.31	17.22	14.08	14.37	17.24
	1	77	12.47	12.81	15.65	12.46	12.78	15.63	12.40	12.78	15.60
	36	0	11.74	11.77	14.77	11.71	11.75	14.74	11.75	11.83	14.80
	36	21	13.24	13.25	16.26	13.24	13.30	16.28	13.20	13.26	16.24
	36	42	11.65	11.70	14.69	11.68	11.66	14.68	11.62	11.77	14.71
	75	0	8.64	8.59	11.63	8.61	8.51	11.57	8.61	8.52	11.58
16QAM	1	0	12.82	12.98	15.91	12.85	13.05	15.96	12.88	12.97	15.94
64QAM	1	0	12.31	12.47	15.40	12.33	12.41	15.38	12.28	12.42	15.36
256QAM	1	0	9.14	9.21	12.19	9.17	9.15	12.17	9.18	9.12	12.16

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	11.57	17.53	15.96	21.92	23
16QAM	15.91	15.96	20.30	20.35	23
64QAM	15.36	15.4	19.75	19.79	23
256QAM	12.16	12.19	16.55	16.58	23


Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

NR n48 SCS 30 kHz (3.55 GHz ~ 3.7 GHz), MIMO, Channel Bandwidth: 40 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)								
			CH 638000			CH 641666			CH 645332		
			3570 MHz			3624.99 MHz			3679.98 MHz		
			TX 1	TX 2	Total	TX 1	TX 2	Total	TX 1	TX 2	Total
QPSK	1	1	14.13	14.48	17.32	14.16	14.49	17.34	14.11	14.47	17.30
	1	0	12.66	12.87	15.78	12.68	12.94	15.82	12.67	12.90	15.80
	1	53	14.36	14.55	17.47	14.46	14.63	17.56	14.39	14.59	17.50
	1	104	14.10	14.33	17.23	14.15	14.39	17.28	14.08	14.35	17.23
	1	105	12.42	12.81	15.63	12.48	12.86	15.68	12.41	12.85	15.65
	50	0	9.86	9.94	12.91	9.99	9.99	13.00	9.95	10.03	13.00
	50	28	11.38	11.42	14.41	11.47	11.46	14.48	11.43	11.42	14.44
	50	56	9.81	9.99	12.91	9.91	9.92	12.93	9.94	9.89	12.93
	100	0	7.15	7.01	10.09	7.21	7.06	10.15	7.21	6.96	10.10
16QAM	1	0	12.87	13.02	15.96	12.93	13.04	16.00	12.91	13.02	15.98
64QAM	1	0	12.3	12.42	15.37	12.33	12.49	15.42	12.23	12.48	15.37
256QAM	1	0	9.11	9.16	12.15	9.19	9.23	12.22	9.12	9.15	12.15

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	10.09	17.56	14.48	21.95	23
16QAM	15.96	16	20.35	20.39	23
64QAM	15.37	15.42	19.76	19.81	23
256QAM	12.15	12.22	16.54	16.61	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)



7.2 Radiated Spurious Emissions below 1GHz


7.2.1 NR n48

RF Mode	NR n48 Channel Bandwidth: 40MHz	Channel	CH 641666 : 3624.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	42.61	-58.57	-40.00	-18.57	2.00 H	52	48.78	-107.35
2	150.28	-57.66	-40.00	-17.66	1.00 H	78	49.81	-107.47
3	279.29	-60.67	-40.00	-20.67	1.50 H	172	46.73	-107.40
4	471.35	-58.84	-40.00	-18.84	2.00 H	121	43.49	-102.33
5	646.92	-57.10	-40.00	-17.10	1.00 H	120	41.69	-98.79
6	831.22	-53.20	-40.00	-13.20	1.50 H	50	42.10	-95.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n48 Channel Bandwidth: 40MHz	Channel	CH 641666 : 3624.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.82	-50.21	-40.00	-10.21	1.00 V	118	57.95	-108.16
2	118.27	-52.92	-40.00	-12.92	1.00 V	191	56.88	-109.80
3	305.48	-61.03	-40.00	-21.03	1.50 V	5	45.67	-106.70
4	510.15	-58.48	-40.00	-18.48	1.00 V	120	42.75	-101.23
5	676.99	-56.10	-40.00	-16.10	2.00 V	274	42.17	-98.27
6	911.73	-52.25	-40.00	-12.25	1.50 V	2	42.68	-94.93

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.3 Radiated Spurious Emissions above 1GHz

7.3.1 NR n48

RF Mode	NR n48 Channel Bandwidth: 40MHz	Channel	CH 641666 : 3624.99 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66% RH
Tested By	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7249.98	-49.36	-40.00	-9.36	1.34 H	185	35.71	-85.07
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7249.98	-47.82	-40.00	-7.82	1.53 V	221	37.25	-85.07

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---