



Product Service

**Choose certainty.
Add value.**

Report On

Limited Radio Testing of the
SRT Marine Technology Ltd
Carbon TRS-418-0003/TR-418-0001 (Type 3)
In accordance with IEC 62320-2: AIS AtoN Type 3 Stations
(Receiver Tests)

COMMERCIAL-IN-CONFIDENCE

Document 75917597 Report 10 Issue 3

March 2013



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

Radio Testing of the
SRT Marine Technology Ltd
Carbon TRS-418-0003/TR-418-0001 (Type 3)
In accordance with IEC 62320-2: AIS AtoN Type 3 Stations
(Receiver Tests)

Document 75917597 Report 10 Issue 3

March 2013

PREPARED FOR

SRT Marine Technology Ltd
Wireless House
Westfield Industrial Estate
Midsomer Norton
Bath
BA3 4BS

PREPARED BY

Natalie Bennett
Senior Administrator (Technical)

APPROVED BY

Mark Jenkins
Authorised Signatory

DATED

06 March 2013

This report has been up-issued to Issue 3 to include revised test results for spurious response rejection, typographical errors corrected and clarification provided.





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Declaration of Build Status 6
1.4	Product Information 7
1.5	Deviations from the Standard 8
1.6	Modification Record 8
2	TEST DETAILS 9
2.1	Sensitivity 10
2.2	Error Behaviour at High Input Levels 12
2.3	Co-channel Rejection 14
2.4	Adjacent Channel Selectivity 16
2.5	Spurious Response Rejection 18
2.6	Intermodulation Response Rejection 21
2.7	Blocking or Desensitisation 23
2.8	Spurious Emissions from the Receiver 25
3	TEST EQUIPMENT USED 27
3.1	Test Equipment Used 28
3.2	Measurement Uncertainty 31
4	PHOTOGRAPHS 32
4.1	Photographs of Equipment Under Test (EUT) 33
5	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 34
5.1	Accreditation, Disclaimers and Copyright 35



Product Service

SECTION 1

REPORT SUMMARY

Radio Testing of the
SRT Marine Technology Ltd Carbon TRS-418-0003/TR-418-0001
In accordance with IEC 62320-2: AIS AtoN Type 3 Stations
(Receiver Tests)



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Radio Testing of the SRT Marine Technology Ltd Carbon TRS-418-0003/TR-418-0001 to the requirements of IEC 62320-2: AIS AtoN Type 3 Stations (Receiver Tests).

Objective	To perform Radio Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	SRT Marine Technology Ltd
Model Number(s)	Carbon
Serial Number(s)	P216FTU021 – TUV TSR Reference 0033
Number of Samples Tested	1
Test Specification/Issue/Date	IEC 62320-2 (2008)
Incoming Release Date	Declaration of Build Status 12 October 2012
Disposal Reference Number Date	Held Pending Disposal Not Applicable Not Applicable
Order Number Date	POR003047 22 March 2012
Start of Test	08 January 2013
Finish of Test	21 January 2013
Name of Engineer(s)	R Henley S Bennett B Airs M Russell



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with IEC 62320-2 is shown below.

Section	Spec Clause	Test Description	Result	Comments/Base Standard
RX1				
2.6	7.1.2.1	Sensitivity	Pass	
2.7	7.1.2.2	Error Behaviour at High Input Levels	Pass	
2.8	7.1.2.3	Co-channel Rejection	Pass	
2.9	7.1.2.4	Adjacent Channel Selectivity	Pass	
2.10	7.1.2.5	Spurious Response Rejection	Pass	
2.11	7.1.2.6	Intermodulation Response Rejection	Pass	
2.12	7.1.2.7	Blocking or Desensitisation	Pass	
2.13	7.1.3.1	Spurious Emissions from the Receiver	Pass	
RX2				
2.6	7.1.2.1	Sensitivity	Pass	
2.7	7.1.2.2	Error Behaviour at High Input Levels	Pass	
2.8	7.1.2.3	Co-channel Rejection	Pass	
2.9	7.1.2.4	Adjacent Channel Selectivity	Pass	
2.10	7.1.2.5	Spurious Response Rejection	Pass	
2.11	7.1.2.6	Intermodulation Response Rejection	Pass	
2.12	7.1.2.7	Blocking or Desensitisation	Pass	
2.13	7.1.3.1	Spurious Emissions from the Receiver	Pass	

**1.3 DECLARATION OF BUILD STATUS**

Manufacturer	<u>SRT Marine Ltd</u>
Country of origin	<u>United Kingdom</u>
UK Agent	<u>SRT Marine Ltd</u>
Technical Description	<u>AtoN (Aids to Navigation)</u>
Model No	<u>TRS & TR</u>
Part No	<u>418-0003 & 418-0001</u>
Serial No	<u>Sample 1- P216-FTU-20, Sample 2- P216-FTU-21, Sample 3- P216-FTU-30.</u>
Drawing Number	<u>418-0003 & 418-0001</u>
Build Status	<u>Mod 11 (supplied)</u>
Software Issue	<u>080200.00.09.11</u>
IC ID	<u>7075A-4180003</u>
FCC ID	<u>UYW-418-0003</u>
Signature	 <u>Richard McMahon</u>
Date	<u>12th October 2012</u>

Note: This document has been prepared to enable manufacturers with no mechanism for producing their own Declaration of Build Status, to declare the build state of the equipment submitted for test.

No responsibility will be accepted by TÜV Product Service as to the accuracy of the information declared in this document by the manufacturer.



Product Service

1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) was a SRT Marine Technology Ltd Carbon TRS-418-0003/TR-418-0001 as shown in the photograph below. A full technical description can be found in the manufacturer's documentation.



Equipment Under Test



Product Service

1.5 DEVIATIONS FROM THE STANDARD

No deviations from the application test standard or test plan were made during testing.

1.6 MODIFICATION RECORD

Modification 0 - No modifications were made to the test sample during testing.



Product Service

SECTION 2

TEST DETAILS

Radio Testing of the
SRT Marine Technology Ltd Carbon TRS-418-0003/TR-418-0001
In accordance with IEC 62320-2: AIS AtoN Type 3 Stations (Receiver Tests)



2.1 SENSITIVITY

2.1.1 Specification Reference

IEC 62320-2, Clause 7.1.2.1

2.1.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.1.3 Date of Test

8 January 2013, 9 January 2013 & 14 January 2013

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Environmental Conditions

Ambient Temperature 22.1 - 22.8°C
Relative Humidity 21.1 - 42.1%

2.1.6 Test Results

The signal level at the input of the receiver shall be set to -107 dBm for a type 3 device and -97 dBm for a type 2 device.

RX1

Test Signal Number 4

Test Conditions		Offset (Hz)	Sensitivity (%)	
			156.025 MHz	162.025 MHz
T _{nom} (22.2°C)	V _{nom} (12 V DC)		0.5	0.5
		500	0.5	0.5
		-500	0.5	0.5
T _{min} (-25.0°C)	V _{min} (9.6 V DC)		0.5	
		500	0.5	
		-500	0.5	
T _{max} (+55.0°C)	V _{max} (31.2 V DC)		0.5	
		500	0.5	
		-500	0.5	

Limit Clause 7.1.2.1.3

Maximum PER of 20%.

RX2Test Signal Number 4

Test Conditions		Offset (Hz)	Sensitivity (%)	
			156.025 MHz	162.025 MHz
$T_{nom}(22.2^{\circ}C)$	$V_{nom}(12\text{ V DC})$		0.5	0.5
		500	0.5	0.5
		-500	0.5	0.5
$T_{min}(-25.0^{\circ}C)$	$V_{min}(9.6\text{ V DC})$		0.5	
		500	0.5	
		-500	0.5	
$T_{max}(+55.0^{\circ}C)$	$V_{max}(31.2\text{ V DC})$		0.5	
		500	0.5	
		-500	0.5	

Limit Clause 7.1.2.1.3

Maximum PER of 20%.



2.2 ERROR BEHAVIOUR AT HIGH INPUT LEVELS

2.2.1 Specification Reference

IEC 62320-2, Clause 7.1.2.2

2.2.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.2.3 Date of Test

9 January 2013

2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.5 Environmental Conditions

Ambient Temperature 22.3 - 22.7°C
Relative Humidity 30.9 - 37.7%

2.2.6 Test Results

RX1

Test Signal Number 4

Test Conditions		Input Signal (dBm)	PER (%)	
			156.025 MHz	162.025 MHz
T _{nom} (22.3°C)	V _{nom} (12 V DC)	*	0.5	0.5
		-77	0.5	0.5
		-7	0.5	0.5

* The level of the wanted signal is 100 dB above the maximum wanted sensitivity.

Limit Clause 7.1.2.2.3

The PER shall not exceed 2% when the level of the input signal is -77 dBm.
The PER shall not exceed 10% when the level of the input signal is -7 dBm.

RX2Test Signal Number 4

Test Conditions		Input Signal (dBm)	PER (%)	
			156.025 MHz	162.025 MHz
T _{nom} (22.3°C)	V _{nom} (12 V DC)	*	0.5	0.5
		-77	0.5	0.5
		-7	0.5	0.5

* The level of the wanted signal is 100 dB above the maximum wanted sensitivity.

Limit Clause 7.1.2.2.3

The PER shall not exceed 2% when the level of the input signal is -77 dBm.
 The PER shall not exceed 10% when the level of the input signal is -7 dBm.



Product Service

2.3 CO-CHANNEL REJECTION

2.3.1 Specification Reference

IEC 62320-2, Clause 7.1.2.3

2.3.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.3.3 Date of Test

21 January 2013

2.3.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.3.5 Environmental Conditions

Ambient Temperature 21.8 - 22.2°C
Relative Humidity 20.3 - 20.6%

2.3.6 Test Results

The level of the wanted signal from generator A shall be adjusted to -101 dBm for a Type 3 device and to -101 dBm for a Type 2 device.

The level of the unwanted signal from generator B shall be adjusted to -111 dBm for a Type 3 device and -117 dBm for a Type 2 device.

RX1

12 V DC Supply

Test Signal Number 4

Test Conditions		Offset (Hz)	Co-channel Rejection (%)	
			156.025 MHz	162.025 MHz
T _{nom} (21.8°C)	V _{nom} (12 V DC)		0.5	0.5
		1000	0.5	0.5
		-1000	0.5	0.5

Please add to list of test equipment which was borrowed from customer: Manufacturer: Sine Qua Non Model: PMG1 Serial Number: 010101-066 Calibration Status: Output Monitored.

Limit Clause 7.1.2.3.3

The PER shall not exceed 20%.



Product Service

RX2

12 V DC Supply

Test Signal Number 4

Test Conditions		Offset (Hz)	Co-channel Rejection (%)	
			156.025 MHz	162.025 MHz
T _{nom} (22.2°C)	V _{nom} (12 V DC)		0.6	1.0
		1000	1.0	0.5
		-1000	0.5	0.5

Please add to list of test equipment which was borrowed from customer: Manufacturer: Sine Qua Non Model: PMG1 Serial Number: 010101-066 Calibration Status: Output Monitored.

Limit Clause 7.1.2.3.3

The PER shall not exceed 20%.



Product Service

2.4 ADJACENT CHANNEL SELECTIVITY

2.4.1 Specification Reference

IEC 62320-2, Clause 7.1.2.4

2.4.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.4.3 Date of Test

9 January 2013

2.4.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.5 Environmental Conditions

Ambient Temperature 21.6 - 22.9°C
Relative Humidity 31.0 - 35.5%

2.4.6 Test Results

The level of the wanted signal from generator A shall be adjusted to -101 dBm for a Type 3 device and to -101 dBm for a Type 2 device.

The level of the unwanted signal from generator B shall be adjusted to -31 dBm for a Type 3 device and -41 dBm for a Type 2 device.

RX1

Test Signal Number 4

Test Conditions		Offset (kHz)	Adjacent Channel Selectivity (%)	
			156.025 MHz	162.025 MHz
T _{nom} (21.6°C)	V _{nom} (12 V DC)	25	1.0	1.0
		-25	1.0	0.5

Limit Clause 7.1.2.4.3

The PER shall not exceed 20%.



Product Service

RX2Test Signal Number 4

Test Conditions		Offset (kHz)	Adjacent Channel Selectivity (%)	
			156.025 MHz	162.025 MHz
T _{nom} (21.6°C)	V _{nom} (12 V DC)	25	0.5	0.5
		-25	2.0	0.5

Limit Clause 7.1.2.4.3

The PER shall not exceed 20%.



Product Service

2.5 SPURIOUS RESPONSE REJECTION

2.5.1 Specification Reference

IEC 62320-2, Clause 7.1.2.5

2.5.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.5.3 Date of Test

16 January 2013, 17 January 2013 & 04 March 2013

2.5.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.5 Environmental Conditions

Ambient Temperature 22.4 - 24.9°C
Relative Humidity 20.2 - 24.7%

2.5.6 Test Results

The level of the wanted signal from generator A shall be adjusted to -101 dBm for a Type 3 device and to -91 dBm for a Type 2 device.

Signal generator B shall be switched on, and the level of the unwanted signal set to -31 dBm.

RX1

12 V DC Supply

Test Signal Number 3

162.000 MHz*

*Manufacturer's specified receiver frequencies did not include 161,975 MHz. 162,000 MHz was used as an alternative.

Spurious Response Frequency (MHz)	PER (%)
-	-

No responses were detected.

The manufacturer declared the following information in order to calculate the limited frequency range:

IF₁ = 19.655MHz
IF₂ = 0.455MHz



Product Service

Switching Range = 6MHz

 F_{LO} is low side, $RF - IF_1$, where RF is 156.025MHz to 162.025MHz $LFR_{LO} = 113.26\text{MHz}$ $LFR_{HI} = 165.48\text{MHz}$

The frequencies where a reduction in SINAD of 3dB or more were detected as follows from the limited frequency search:

152.175MHz, 153.145MHz, 153.230MHz, 154.055MHz, 156.455MHz, 157.365MHz,
157.615MHz, 158.445MHz, 161.090MHz, 162.825MHz.

The following specific frequencies of interest were calculated for $RF = 162.000\text{MHz}$:

$$F_{LO} = 162.000\text{MHz} - 19.655\text{MHz} = 142.345\text{MHz}.$$

265.035MHz, 304.345MHz, 407.380MHz, 446.690MHz, 549.725MHz, 589.035MHz

Limit Clause 7.1.2.5.8

At any frequency separated from the specified frequency of the receiver by 50 kHz or more, the PER shall not exceed 20%.

RX2

12 V DC Supply

Test Signal Number 3

162.000 MHz*

*Manufacturer's specified receiver frequencies did not include 161,975 MHz. 162,000 MHz was used as an alternative.

Spurious Response Frequency (MHz)	PER (%)
-	-

No responses were detected.

The manufacturer declared the following information in order to calculate the limited frequency range:

 $IF_1 = 29.255\text{MHz}$ $IF_2 = 0.455\text{MHz}$

Switching Range = 6MHz

 F_{LO} is high side, $RF - IF_1$, where RF is 156.025MHz to 162.025MHz $LFR_{LO} = 152.57\text{MHz}$ $LFR_{HI} = 223.99\text{MHz}$



Product Service

The frequencies where a reduction in SINAD of 3dB or more were detected as follows from the limited frequency search:

157.615MHz, 161.255MHz, 162.745MHz, 162.910MHz.

The following specific frequencies of interest were calculated for RF = 162.000MHz:

$F_{LO} = 162.000\text{MHz} + 29.255\text{MHz} = 191.255\text{MHz}.$

353.255MHz, 411.765MHz, 544.510MHz, 603.020MHz, 735.765MHz, 794.275MHz

Limit Clause 7.1.2.5.8

At any frequency separated from the specified frequency of the receiver by 50 kHz or more, the PER shall not exceed 20%.



2.6 INTERMODULATION RESPONSE REJECTION

2.6.1 Specification Reference

IEC 62320-2, Clause 7.1.2.6

2.6.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.6.3 Date of Test

10 January 2013

2.6.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.5 Environmental Conditions

Ambient Temperature 22.1°C
Relative Humidity 31.0 - 31.9%

2.6.6 Test Results

The level of the wanted signal from generator A shall be adjusted to -101 dBm for a Type 3 device and to -91 dBm for a Type 2 device.

The signal level from generators B and C shall be set for -36 dBm at the receiver input.

RX1

Test Signal Number 3

Test Conditions		Offset (kHz)	Intermodulation Response Rejection (%)		
			156.025 MHz	162.025 MHz	162.025 MHz
T _{nom} (22.1°C)	V _{nom} (12 V DC)	500/1000	0.1	N/A	0.1
		-500/-1000	0.1	N/A	0.1

Limit Clause 7.1.2.6.3

The PER shall not exceed 20%.



Product Service

RX2Test Signal Number 3

Test Conditions		Offset (kHz)	Intermodulation Response Rejection (%)		
			156.025 MHz	162.025 MHz	162.025 MHz
$T_{nom}(22.1^{\circ}\text{C})$	$V_{nom}(12\text{ V DC})$	500/1000	0.1	N/A	0.1
		-500/-1000	0.1	N/A	0.1

Limit Clause 7.1.2.6.3

The PER shall not exceed 20%.



Product Service

2.7 BLOCKING OR DESENSITISATION**2.7.1 Specification Reference**

IEC 62320-2, Clause 7.1.2.7

2.7.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.7.3 Date of Test

10 January 2013

2.7.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.7.5 Environmental Conditions

Ambient Temperature	21.8°C
Relative Humidity	30.7%

2.7.6 Test Results

The level of the wanted signal from generator A shall be adjusted to -101 dBm for a Type 3 device and to -91 dBm for a Type 2 device.

The RF signal level for signal generator B (unwanted signal) shall be adjusted to – 23 dBm when the frequency setting is less than ± 5 MHz with respect to the frequency setting of RF signal generator A. For frequency settings of signal generator B that are equal to or greater than ± 5 MHz with respect to the frequency setting of generator A, the RF signal level shall be adjusted to –15 dBm. This applies to Type 3 receivers only.

RX1

12 V DC Supply

Test Signal Number 3

Frequency of Unwanted Signal	Blocking Level (%)	
	156.025 MHz	162.025 MHz
Nominal +10MHz	0.1	0.1
+5MHz	0.1	0.1
+2MHz	0.1	0.1
+1MHz	0.1	0.1
+500 kHz	0.1	0.1
-500 kHz	0.1	0.1
-1MHz	0.2	0.1
-2MHz	0.1	0.2
-5MHz	0.1	0.1
-10MHz	0.1	0.1

Limit Clause 7.1.2.7.3

The PER shall not exceed 20%.

RX2

12 V DC Supply

Test Signal Number 3

Frequency of Unwanted Signal	Blocking Level (%)	
	156.025 MHz	162.025 MHz
Nominal +10MHz	0.1	0.1
+5MHz	0.1	0,1
+2MHz	0.1	0.1
+1MHz	0.1	0.1
+500 kHz	0.1	0.1
-500 kHz	0.1	0,1
-1MHz	0.2	0.1
-2MHz	0.1	0.2
-5MHz	0.1	0.1
-10MHz	0.1	0.1

Limit Clause 7.1.2.7.3

The PER shall not exceed 20%.



Product Service

2.8 SPURIOUS EMISSIONS FROM THE RECEIVER**2.8.1 Specification Reference**

IEC 62320-2, Clause 7.1.3.1

2.8.2 Equipment Under Test and Modification State

Carbon S/N: P216FTU021 – TUV TSR Reference 0033 - Modification State 0

2.8.3 Date of Test

14 January 2013

2.8.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.8.5 Environmental Conditions

Ambient Temperature 21.4°C
Relative Humidity 25.4 - 25.8%

2.8.6 Test ResultsRX1

Receiver operating

12 V DC Supply

Frequency (MHz)	Emission result (dBm)
-	-

No emissions were detected within a 6 dB of the limit.

Limit Clause 7.1.3.1.3

Frequency range	9 kHz to 1 GHz	1 GHz to 4 GHz
Limit	-57.0 dBm	-47.0 dBm



Product Service

RX2

Receiver operating

12 V DC Supply

Frequency (MHz)	Emission result (dBm)
-	-

No emissions were detected within a 6 dB of the limit.

Limit Clause 7.1.3.1.3

Frequency range	9 kHz to 1 GHz	1 GHz to 4 GHz
Limit	-57.0 dBm	-47.0 dBm



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.1 - Sensitivity					
Multimeter	White Gold	WG022	190	12	30-Oct-2013
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
0V - 10V to TTL Logic Level Shifter	TUV SUD Product Service	Logic Level Shifter	4032	-	O/P Mon
Section 2.2 - Error Behaviour at High Input Levels					
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
0V - 10V to TTL Logic Level Shifter	TUV SUD Product Service	Logic Level Shifter	4032	-	O/P Mon
Section 2.3- Co Channel Rejection					
Signal Generator	Rohde & Schwarz	SMG	42	12	12-Sep-2013
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	23-Jul-2013
Multimeter	Iso-tech	IDM101	2424	12	10-Sep-2013
Oscilloscope	Lecroy	9370	2832	12	25-Oct-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Function Generator	Thurlby Thandar Instruments	TG2000	3334	-	TU
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
Combiner/Splitter	Weinschel	1506A	3877	12	19-Mar-2013
1 Metre N Type Cable	Rhophase	NPS-1601A-1000-NPS	4104	12	1-Jun-2013
Section 2.4 - Adjacent Channel Selectivity					
Signal Generator	Rohde & Schwarz	SMG	42	12	12-Sep-2013
Multimeter	White Gold	WG022	190	12	30-Oct-2013
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
Combiner/Splitter	Weinschel	1506A	3877	12	19-Mar-2013
0V - 10V to TTL Logic Level Shifter	TUV SUD Product Service	Logic Level Shifter	4032	-	O/P Mon



Product Service

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.5 - Spurious Response Rejection					
Signal Generator	Rohde & Schwarz	SMG	42	12	12-Sep-2013
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Multimeter	Iso-tech	IDM101	2424	12	10-Sep-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Combiner/Splitter	Weinschel	1506A	3877	12	19-Mar-2013
1 Metre N Type Cable	Rhophase	NPS-1601A-1000-NPS	4104	12	1-Jun-2013
Section 2.6 - Intermodulation Response Rejection					
Signal Generator	Rohde & Schwarz	SMG	42	12	12-Sep-2013
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Signal Generator, 9kHz - 3GHz	Rohde & Schwarz	SMA 100A	3504	12	24-Aug-2013
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
'N' - 'N' RF Cable (1m)	Rhophase	NPS-1803-1000-NPS	3700	12	12-Jan-2013
0V - 10V to TTL Logic Level Shifter	TUV SUD Product Service	Logic Level Shifter	4032	-	O/P Mon
2 Metre N Type Cable	Rhophase	NPS-1601A-2000-NPS	4110	12	1-Jun-2013
Section 2.7 - Blocking or Desensitisation					
Signal Generator	Rohde & Schwarz	SMG	42	12	12-Sep-2013
Multimeter	White Gold	WG022	190	12	30-Oct-2013
Power Supply Unit	Farnell	D302T	609	-	O/P Mon
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Signal Generator	Rohde & Schwarz	SMY 01	1109	12	20-Dec-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Programmable Modulation Waveform Generator	Sine Qua Non	PMG1	3291	-	TU
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
'N' - 'N' RF Cable (1m)	Rhophase	NPS-1803-1000-NPS	3700	12	12-Jan-2013
Combiner/Splitter	Weinschel	1506A	3877	12	19-Mar-2013
0V - 10V to TTL Logic Level Shifter	TUV SUD Product Service	Logic Level Shifter	4032	-	O/P Mon



Product Service

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.8 - Spurious Emissions from the Receiver					
Multimeter	White Gold	WG022	190	12	30-Oct-2013
DC Power Supply	Hewlett Packard	6269B	326	-	TU
Power Supply Unit	Farnell	H60-25	1092	-	O/P Mon
Spectrum Analyser	Hewlett Packard	E4407B	1154	12	17-Jul-2013
GPS Frequency Standard	Rapco	GPS-804/3	1312	6	19-Jan-2013
High Pass Filter	Mini-Circuits	NHP-300	1640	12	15-Aug-2013
Multimeter	Iso-tech	IDM101	2424	12	10-Sep-2013
Hygrometer	Rotronic	I-1000	2891	12	21-May-2013
Attenuator (10dB, 50W)	Aeroflex / Weinschel	47-10-34	3166	12	27-Jun-2013
Hygrometer	Rotronic	I-1000	3220	12	13-Jun-2013
Attenuator (20dB, 150W)	Narda	769-20	3367	12	28-May-2013
Attenuator (30dB, 150W)	Narda	769-30	3369	12	28-May-2013
Signal Generator: 10MHz to 20GHz	Rohde & Schwarz	SMR20	3475	12	20-Dec-2012
Signal Analyser	Rohde & Schwarz	FSQ 26	3545	12	9-May-2013
Network Analyser	Rohde & Schwarz	ZVA 40	3548	12	31-Aug-2013
'N' - 'N' RF Cable (1m)	Rhophase	NPS-1803-1000-NPS	3701	12	12-Jan-2013
DC - 8 GHz Attenuator	Lucas Weinschel	24-30-33	3963	12	27-Jun-2013
1 Metre N Type Cable	Rhophase	NPS-1601A-1000-NPS	4102	12	1-Jun-2013

TU – Traceability Unscheduled

O/P MON – Output Monitored with Calibrated Equipment



3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	MU
Frequency Error	± 11 Hz
Carrier Power	± 0.45 dB
Modulation Spectrum Slotted Transmission	± 2.0 dB
Transmitter Output Power Versus Time Function (FATDMA and RATDMA)	± 2.0 dB
Transmitter Test Sequence and Modulation Accuracy	± 2.0 dB
Sensitivity	± 1.406 dB
Spurious Response Rejection	± 3.61 dB
Blocking or Desensitisation	± 3.22 dB
Spurious Emissions from the Receiver	± 2.0 dB
Spurious Emissions from the Transmitter	± 2.0 dB
Co-channel Rejection	± 3.22 dB
Adjacent Channel Selectivity	± 3.22 dB
Intermodulation Response Rejection	± 3.22 dB
Error Behaviour at High Input Levels	± 1.406 dB



Product Service

SECTION 4

PHOTOGRAPHS



Product Service

4.1 PHOTOGRAPHS OF EQUIPMENT UNDER TEST (EUT)



Front View



Rear View



Product Service

SECTION 5

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

5.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2013 TÜV SÜD Product Service