FCC RADIO TEST REPORT

FCC ID	:	**UZ7-RTL10C1**
Equipment	:	**Tablet PC with Windows OS**
Brand Name	:	**Zebra**
Model Name	:	**RTL10C1**
Applicant	:	**Zebra Technologies Corporation 1 Zebra Plaza, Holtsville, NY 11742**
Manufacturer	:	**Zebra Technologies Corporation 1 Zebra Plaza, Holtsville, NY 11742**
Standard	:	**FCC Part 15 Subpart C §15.225**

The product was received on Dec. 09, 2021 and testing was performed from Dec. 17, 2021 to Jan. 18, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1. General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 6
1.3 Modification of EUT 6
1.4 Testing Location 7
1.5 Applicable Standards 7
2. Test Configuration of Equipment Under Test **8**
2.1 Descriptions of Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Table for Supporting Units 10
2.4 EUT Operation Test Setup 10
3. Test Results **11**
3.1 AC Power Line Conducted Emissions Measurement 11
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement 13
3.3 Frequency Stability Measurement 14
3.4 Field Strength of Fundamental Emissions and Mask Measurement 15
3.5 Radiated Emissions Measurement 17
3.6 Antenna Requirements 20
4. List of Measuring Equipment **21**
5. Uncertainty of Evaluation **22**
Appendix A. Test Results of Conducted Emission Test
Appendix B. Test Results of Conducted Test Items
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
Appendix C. Test Results of Radiated Test Items
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)
Appendix D. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR181117	01	Initial issue of report	Feb. 21, 2022

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	14.94 dB under the limit at 0.191 MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 20.85 dBμV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	6.41 dB under the limit at 647.890 MHz
3.6	15.203	Antenna Requirements	Pass	-

Declaration of Conformity:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
   It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to this report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen

Report Producer: Clio Lo

1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC with Windows OS
Brand Name	Zebra
Model Name	RTL10C1
FCC ID	UZ7-RTL10C1
Sample 1	XPAD
Sample 2	XSLATE
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/NFC/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	EV
SW Version	Windows 10 Pro
FW Version	BIOS LRX09E06
MFD	18OCT21
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
Adaptor with CLA cable	**Brand Name**	Zebra	**Model Number**	ADP-65JH HB
Battery	**Brand Name**	ZEBRA	**Model Number**	XLBM1
Power cord	**Brand Name**	Zebra	**Model Number**	450040

Supported Unit Used in Test Configuration and System				
Keyboard	**Brand Name**	Zebra	**Model Number**	L10-KB
98 Whr Extended Battery (Certified)	**Brand Name**	Zebra	**Model Number**	XLBE1
AEI LONG RANGE RFID MODULE	**Brand Name**	Zebra	**Model Number**	M6E-MICRO
PASSIVE SHORT STYLUS	**Brand Name**	Zebra	**Model Number**	440007
ET8X MPP 2.0 ACTIVE STYLUS WITH 5 REPLACEMENT TIPS. AAAA BATTERY INCLUDED	**Brand Name**	Zebra	**Model Number**	SG-ET8X-STYLUS1-01

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.64 KHz
99%OBW	2.24 KHz
Antenna Type	Loop Antenna
Type of Modulation	ASK

Remark: The above EUT's information is declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH03-HY	CO05-HY
Test Engineer	Oscar Chi	Calvin Wang
Temperature	22~24℃	23~26℃
Relative Humidity	53~55%	45~55%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH11-HY (TAF Code: 3786)
Test Engineer	James Chiu
Temperature	20.6~21.6℃
Relative Humidity	53.4~67.3%
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in reader mode with NFC tag (four NFC type A, B, F, V) and without reading tag. Based on the highest field strength of fundamental and spurious emissions, the worst case type (type F) was recorded in this report.

The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Y plane as worst plane.

Test Cases	
AC Conducted Emission	Mode 1 : LTE Band 12 Idle + WLAN Idle + Bluetooth Idle + NFC Link + H Pattern + MPEG4 (Color Bar) + GPS RX + Camera (Front and Rear) + Adaptor with CLA cable (ADP-65JH HB) + Power cord (450040) + USB (Type C) with Monitor + USB 3.0 (Data Link with USB HD) + RJ45 link with WLAN AP + Earphone + SD Card + Keyboard (L10-KB) + PASSIVE SHORT STYLUS (440007) for Sample 2
Remark: Data Link with USB HD means data application transferred mode between EUT and USB HD.	

2.2 Connection Diagram of Test System

<AC Conducted Emission Mode>



<NFC Tx Mode>



2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
7.	LCD Monitor	ASUS	PB27UQ	FCC DoC	Shielded, 1.5m	Unshielded,1.8m
8.	USB HD	ADATA	HV620S-1T	FCC DoC	Shielded, 1.0m	N/A
9.	SD Card	Kingston	SDCS2/32GB	FCC DoC	N/A	N/A
10.	NFC Card	N/A	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT is programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmitting signal (Power Level: Default) at 13.56 MHz and is placed around 0 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB and 99% emission bandwidth in the specific band 13.553~13.567 MHz.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max Hold Mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20 dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed by using a new battery.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT has transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ±100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

Remark:

1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna is fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9 kHz.
   Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated test below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna is varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower is scanned (from 1 M to 4 M) and then the turntable is rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30 MHz, loop antenna has to be used for measurement and the recorded data shall be QP measured by receiver.

3.5.5 Test Setup

For radiated test below 30MHz



For radiated test above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 15, 2021	Dec. 31, 2021	Dec. 14, 2022	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 09, 2021	Dec. 31, 2021	Oct. 08, 2022	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 04, 2021	Dec. 31, 2021	Jan. 03, 2022	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 15, 2021	Dec. 31, 2021	Oct. 14, 2022	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY55420170	20MHz~8.4GHz	Jul. 15, 2021	Dec. 31, 2021	Jul. 14, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102 , SUCOFLEX 104	811852/4,MY 2859/2,MY98 37/4PE	30MHz~18GHz	Nov. 15, 2021	Dec. 31, 2021	Nov. 14, 2022	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Dec. 31, 2021	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Dec. 31, 2021	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Dec. 31, 2021	N/A	Radiation (03CH11-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 05, 2022~ Jan. 18, 2022	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2021	Jan. 05, 2022~ Jan. 18, 2022	Nov. 30, 2022	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2021	Jan. 05, 2022~ Jan. 18, 2022	Nov. 16, 2022	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 03, 2021	Jan. 05, 2022~ Jan. 18, 2022	Dec. 02, 2022	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2021	Jan. 05, 2022~ Jan. 18, 2022	Nov. 15, 2022	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jan. 05, 2022~ Jan. 18, 2022	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	00691	N/A	Jul. 28, 2021	Jan. 05, 2022~ Jan. 18, 2022	Jul. 27, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 30, 2021	Jan. 05, 2022~ Jan. 18, 2022	Dec. 29, 2022	Conduction (CO05-HY)
5kVA AC Power Source	TESEQ	NSG 1007	1521A01677	N/A	Jun. 08, 2021	Dec. 17, 2021	Jun. 07, 2022	Conducted (TH03-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 01, 2021	Dec. 17, 2021	Feb. 28, 2022	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 30, 2021	Dec. 17, 2021	Sep. 29, 2022	Conducted (TH03-HY)
Temperature & Humidity Cabinet Chamber	ESPEC	LHU-113	1012005860	-20℃~85℃	Jan. 18, 2021	Dec. 17, 2021	Jan. 17, 2022	Conducted (TH03-HY)
Coupling loop antenna	EMCI	LF R 400	N/A	100KHz~50MHz	N/A	Dec. 17, 2021	N/A	Conducted (TH03-HY)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.1 dB**

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.7 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.8 dB**

Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Calvin Wang	**Temperature :**	23~26℃
		Relative Humidity :	45~55%

Original

Report NO :	181117
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.186000	---	27.75	54.21	26.46	L1	OFF	19.6
0.186000	46.41	---	64.21	17.80	L1	OFF	19.6
0.206250	---	29.91	53.36	23.45	L1	OFF	19.6
0.206250	46.88	---	63.36	16.48	L1	OFF	19.6
3.509250	---	29.22	46.00	16.78	L1	OFF	19.6
3.509250	37.21	---	56.00	18.79	L1	OFF	19.6
3.657750	---	29.90	46.00	16.10	L1	OFF	19.6
3.657750	38.21	---	56.00	17.79	L1	OFF	19.6
3.864750	---	27.69	46.00	18.31	L1	OFF	19.6
3.864750	36.02	---	56.00	19.98	L1	OFF	19.6
5.102250	---	28.42	50.00	21.58	L1	OFF	19.7
5.102250	37.99	---	60.00	22.01	L1	OFF	19.7
5.239500	---	28.27	50.00	21.73	L1	OFF	19.7
5.239500	36.52	---	60.00	23.48	L1	OFF	19.7
11.582250	---	34.23	50.00	15.77	L1	OFF	19.8
11.582250	42.72	---	60.00	17.28	L1	OFF	19.8
11.789250	---	33.84	50.00	16.16	L1	OFF	19.8
11.789250	42.28	---	60.00	17.72	L1	OFF	19.8
13.560000	---	50.13	50.00	-0.13	L1	OFF	19.8
13.560000	50.31	---	60.00	9.69	L1	OFF	19.8
18.408750	---	29.98	50.00	20.02	L1	OFF	19.8

18.408750	39.07	---	60.00	20.93	L1	OFF	19.8
20.546250	---	28.47	50.00	21.53	L1	OFF	19.8
20.546250	38.62	---	60.00	21.38	L1	OFF	19.8
21.651000	---	33.82	50.00	16.18	L1	OFF	19.8
21.651000	43.24	---	60.00	16.76	L1	OFF	19.8

Report NO : 181117
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	20.19	55.63	35.44	N	OFF	19.6
0.156750	42.27	---	65.63	23.36	N	OFF	19.6
0.190500	---	33.20	54.02	20.82	N	OFF	19.6
0.190500	49.08	---	64.02	14.94	N	OFF	19.6
0.197250	---	34.37	53.73	19.36	N	OFF	19.6
0.197250	49.20	---	63.73	14.53	N	OFF	19.6
0.206250	---	29.23	53.36	24.13	N	OFF	19.6
0.206250	46.98	---	63.36	16.38	N	OFF	19.6
3.378750	---	29.31	46.00	16.69	N	OFF	19.6
3.378750	38.22	---	56.00	17.78	N	OFF	19.6
3.516000	---	29.27	46.00	16.73	N	OFF	19.6
3.516000	38.20	---	56.00	17.80	N	OFF	19.6
3.653250	---	29.29	46.00	16.71	N	OFF	19.6
3.653250	38.04	---	56.00	17.96	N	OFF	19.6
3.792750	---	28.63	46.00	17.37	N	OFF	19.6
3.792750	37.39	---	56.00	18.61	N	OFF	19.6
3.930000	---	27.22	46.00	18.78	N	OFF	19.6
3.930000	36.10	---	56.00	19.90	N	OFF	19.6
4.067250	---	27.12	46.00	18.88	N	OFF	19.6
4.067250	35.98	---	56.00	20.02	N	OFF	19.6
4.895250	---	26.76	46.00	19.24	N	OFF	19.7

4.895250	34.44	---	56.00	21.56	N	OFF	19.7
11.445000	---	33.75	50.00	16.25	N	OFF	19.8
11.445000	42.39	---	60.00	17.61	N	OFF	19.8
11.584500	---	34.49	50.00	15.51	N	OFF	19.8
11.584500	43.17	---	60.00	16.83	N	OFF	19.8
11.721750	---	34.07	50.00	15.93	N	OFF	19.8
11.721750	42.64	---	60.00	17.36	N	OFF	19.8
11.859000	---	33.37	50.00	16.63	N	OFF	19.8
11.859000	41.81	---	60.00	18.19	N	OFF	19.8
13.560000	---	50.16	50.00	-0.16	N	OFF	19.9
13.560000	50.17	---	60.00	9.83	N	OFF	19.9
18.960000	---	29.70	50.00	20.30	N	OFF	19.9
18.960000	40.05	---	60.00	19.95	N	OFF	19.9
19.376250	---	29.26	50.00	20.74	N	OFF	20.0
19.376250	39.08	---	60.00	20.92	N	OFF	20.0
20.478750	---	29.70	50.00	20.30	N	OFF	20.0
20.478750	39.93	---	60.00	20.07	N	OFF	20.0
20.892750	---	31.85	50.00	18.15	N	OFF	20.0
20.892750	40.08	---	60.00	19.92	N	OFF	20.0
21.995250	---	26.47	50.00	23.53	N	OFF	20.0
21.995250	34.32	---	60.00	25.68	N	OFF	20.0
22.409250	---	29.31	50.00	20.69	N	OFF	20.0
22.409250	39.02	---	60.00	20.98	N	OFF	20.0

Terminal

Project No :	181117
TestMode :	Mode 1
Test Voltage :	120Vac/60Hz
phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	22.62	50.00	27.38	L1	OFF	19.8
13.560000	28.65	---	60.00	31.35	L1	OFF	19.8

Project No :	181117
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.17	50.00	24.83	N	OFF	19.9
13.560000	33.46	---	60.00	26.54	N	OFF	19.9

Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56





20dB Bandwidth (kHz)	2.640	99% OccupiedBW(kHz)	2.240
Frequency range (MHz)	**f_L > 13.553**	13.55862	**Test Result**
	f_H < 13.567	13.56126	**Complies**

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
120	13.559940	**-20**	**0**	13.559980
102	13.559930		**2**	13.559980
138	13.559920		**5**	13.559980
			10	13.559980
		-10	**0**	13.559960
			2	13.559960
			5	13.559960
			10	13.559970
		0	**0**	13.559940
			2	13.559950
			5	13.559950
			10	13.559940
		10	**0**	13.559940
			2	13.559940
			5	13.559940
			10	13.559940
		20	**0**	13.559930
			2	13.559920
			5	13.559920
			10	13.559920
		30	**0**	13.559900
			2	13.559900
			5	13.559910
			10	13.559900
		40	**0**	13.559920
			2	13.559920
			5	13.559920
			10	13.559920

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
		50	0	13.559960
			2	13.559950
			5	13.559950
			10	13.559940
Max.Deviation (MHz)	-0.000080	Max.Deviation (MHz)		-0.000100
Max.Deviation (ppm)	-5.8997	Max.Deviation (ppm)		-7.3746
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx for Sample 1	Test Frequency (MHz)	13.56



Site : 03CH11-HY
Condition : 15.225 3m LOOP_ANT(H)_100315 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	19.29	40	-64.71	84	37.89	21.39	0.01	100	38	QP

Test Mode :	NFC Tx for Sample 1	Test Frequency (MHz)	13.56



Site : 03CH11-HY
Condition : 15.225 3m LOOP_ANT(V)_100315 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	20.62	40	-63.38	84	39.22	21.39	0.01	100	155	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

Test Mode :	NFC Tx for Sample 2	Test Frequency (MHz)	13.56



Site : 03CH11-HY
Condition : 15.225 3m LOOP_ANT(H)_100315 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	20.85	40	-63.15	84	39.45	21.39	0.01	100	72	QP

Test Mode :	NFC Tx for Sample 2	Test Frequency (MHz)	13.56



Site : 03CH11-HY
Condition : 15.225 3m LOOP_ANT(V)_100315 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	16.94	40	-67.06	84	35.54	21.39	0.01	100	182	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx for Sample 1	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01925	0.16	80	-41.76	41.92	61.23	18.91	0.02	-	-	Average
0.06621	-27.23	80	-58.42	31.19	33.77	18.98	0.02	-	-	Average
0.09926	-46.97	80	-74.64	27.67	14.89	18.12	0.02	-	-	QP
0.1258	-37.39	80	-63	25.61	24.37	18.22	0.02	-	-	Average
0.19828	-28.99	80	-50.65	21.66	32.45	18.54	0.02	-	-	Average
0.78289	3.23	40	-26.5	29.73	24.2	19.01	0.02	-	-	QP
12.2	-2.48	40	-31.98	29.5	16.26	21.24	0.02	-	-	QP
13.56	19.8	40	-9.7	29.5	38.4	21.39	0.01	-	-	QP
21.796	-1.88	40	-31.38	29.5	15.89	22.17	0.06	-	-	QP
27.675	-1.77	40	-31.27	29.5	15.63	22.41	0.19	-	-	QP

Test Mode :	NFC Tx for Sample 1	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.0192	-2.52	80	-44.46	41.94	58.55	18.91	0.02	-	-	Average
0.06507	-36.86	80	-68.2	31.34	24.11	19.01	0.02	-	-	Average
0.09124	-48.81	80	-77.21	28.4	12.84	18.33	0.02	-	-	QP
0.11548	-43.06	80	-69.41	26.35	18.75	18.17	0.02	-	-	Average
0.19964	-32.3	80	-53.9	21.6	29.13	18.55	0.02	-	-	Average
0.49751	-1.84	40	-35.51	33.67	19.24	18.9	0.02	-	-	QP
8.184	-2.03	40	-31.53	29.5	17.53	20.42	0.02	-	-	QP
13.56	18.34	40	-11.16	29.5	36.94	21.39	0.01	-	-	QP
24.415	-1.99	40	-31.49	29.5	15.64	22.28	0.09	-	-	QP
29.93	-1.78	40	-31.28	29.5	15.44	22.5	0.28	-	-	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

Test Mode :	NFC Tx for Sample 2	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.0192	3.79	80	-38.15	41.94	63.58	20.19	0.02	-	-	Average
0.06351	-26.07	80	-57.62	31.55	33.89	20.02	0.02	-	-	Average
0.10468	-45.96	80	-73.17	27.21	14.08	19.94	0.02	-	-	QP
0.12456	-36.02	80	-61.72	25.7	24.03	19.93	0.02	-	-	Average
0.20304	-25.43	80	-46.88	21.45	34.66	19.89	0.02	-	-	Average
0.74534	5.77	40	-24.39	30.16	25.93	19.82	0.02	-	-	QP
11.88	-4.33	40	-33.83	29.5	15.99	19.66	0.02	-	-	QP
13.56	18.87	40	-10.63	29.5	39.22	19.64	0.01	-	-	QP
18.844	-3.75	40	-33.25	29.5	16.54	19.67	0.04	-	-	QP
28.025	-4.35	40	-33.85	29.5	15.75	19.7	0.2	-	-	QP

Test Mode :	NFC Tx for Sample 2	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01925	-1.54	80	-43.46	41.92	58.25	20.19	0.02	-	-	Average
0.06723	-33.32	80	-64.37	31.05	26.65	20.01	0.02	-	-	Average
0.09352	-47.08	80	-75.27	28.19	12.95	19.95	0.02	-	-	QP
0.12592	-41.6	80	-67.2	25.6	18.45	19.93	0.02	-	-	Average
0.1908	-29.47	80	-51.46	21.99	30.62	19.89	0.02	-	-	Average
0.49751	2.24	40	-31.43	33.67	22.38	19.84	0.02	-	-	QP
8.4	-0.24	40	-29.74	29.5	19.97	19.77	0.02	-	-	QP
13.56	15.69	40	-13.81	29.5	36.04	19.64	0.01	-	-	QP
16.612	-2.38	40	-31.88	29.5	17.98	19.62	0.02	-	-	QP
26.475	-4.76	40	-34.26	29.5	15.26	19.83	0.15	-	-	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx for Sample 1	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
103.72	23.03	-20.47	43.5	37.53	16.2	1.63	32.33	-	-	Peak
153.19	27.85	-15.65	43.5	41.49	16.7	1.95	32.29	-	-	Peak
282.2	28.13	-17.87	46	39.02	18.71	2.59	32.19	-	-	Peak
551.86	38.63	-7.37	46	41.92	25.27	3.68	32.24	-	-	Peak
647.89	37.21	-8.79	46	38.57	26.25	4.6	32.21	-	-	Peak
743.92	35.11	-10.89	46	34.85	27.83	4.59	32.16	-	-	Peak

Test Mode :	NFC Tx for Sample 1	Polarization :	Vertical



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.67	33.37	-6.63	40	45.82	18.89	1.06	32.4	-	-	Peak
129.91	23.03	-20.47	43.5	36.09	17.42	1.82	32.3	-	-	Peak
280.26	23.36	-22.64	46	34.32	18.66	2.58	32.2	-	-	Peak
551.86	35.86	-10.14	46	39.15	25.27	3.68	32.24	-	-	Peak
647.89	39.02	-6.98	46	40.38	26.25	4.6	32.21	-	-	Peak
743.92	32.74	-13.26	46	32.48	27.83	4.59	32.16	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.

Test Mode :	NFC Tx for Sample 2	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
97.9	23.37	-20.13	43.5	38.69	15.41	1.6	32.33	-	-	Peak
171.62	26.54	-16.96	43.5	41.53	15.24	2.05	32.28	-	-	Peak
282.2	28.44	-17.56	46	39.33	18.71	2.59	32.19	-	-	Peak
551.86	36.76	-9.24	46	40.05	25.27	3.68	32.24	-	-	Peak
647.89	36.91	-9.09	46	38.27	26.25	4.6	32.21	-	-	Peak
696.39	35.52	-10.48	46	36.79	26.47	4.43	32.17	-	-	Peak

Test Mode :	NFC Tx for Sample 2	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.67	33.24	-6.76	40	45.69	18.89	1.06	32.4	-	-	Peak
208.48	22.18	-21.32	43.5	37.26	14.95	2.23	32.26	-	-	Peak
236.61	23.39	-22.61	46	36.69	16.58	2.37	32.25	-	-	Peak
551.86	35.41	-10.59	46	38.7	25.27	3.68	32.24	-	-	Peak
647.89	39.59	-6.41	46	40.95	26.25	4.6	32.21	-	-	Peak
888.45	32.74	-13.26	46	29.8	28.85	5.68	31.59	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBµV/m) = 20 log Emission level (µV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.