FCC RF Test Report

FCC ID	:	UZ7EM45B2
EQUIPMENT	:	Enterprise Mobile
BRAND NAME	:	Zebra
MODEL NAME	:	EM45B2
APPLICANT	:	Zebra Technologies Corporation 3 Overlook Point, Lincolnshire, IL 60069 USA
MANUFACTURER	:	Zebra Technologies Corporation 3 Overlook Point, Lincolnshire, IL 60069 USA
STANDARD	:	47 CFR Part 2, and 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Jul. 08, 2024 ~ Aug. 12, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 6
1.3 Modification of EUT 6
1.4 Maximum Conducted Power and Emission Designator 6
1.5 Testing Site 6
1.6 Test Software 7
1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10

3 TEST RESULT **11**

3.1 Conducted Output Power Measurement 11
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement 12
3.3 Emissions Mask Measurement 13
3.4 Emissions Mask – Out Of Band Emissions Measurement 15
3.5 Field Strength of Spurious Radiation Measurement 16
3.6 Frequency Stability Measurement 19

4 LIST OF MEASURING EQUIPMENT **21**

5 MEASUREMENT UNCERTAINTY **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG460508I	Rev. 01	Initial issue of report	Sep. 11, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	—	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	—	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< $50+10\log_{10}$(P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< $43+10\log_{10}$(P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 46.85 dB at 2448.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Mobile
Brand Name	Zebra
Model Name	EM45B2
FCC ID	UZ7EM45B2
IMEI Code	Conducted: 350854420036002/350854420037034 Radiation: 350854420030211/350854420030229
HW Version	EV2.5
SW Version	13-32-08.00-TG-U06-STD-ATH-04
MFD	02AUG24
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessory				
Battery	**Brand Name**	Zebra	**Model**	BT-000501
			Part Number	BT-000501-2000

Supported Unit used in test configuration and system				
AC Adapter 1 (Type C Wall Charger 1)	**Brand Name**	Zebra	**Model**	SAWA-102-22520A
			Part Number	PWR-WUA5V45W1US
AC Adapter 2 (Type A Wall Charger 2)	**Brand Name**	Zebra	**Model**	SAWA-65-20005A
			Part Number	PWR-WUA5V12W0US
Earphone 1 (Wired headset USB-C)	**Brand Name**	Zebra	**Part Number**	HDST-USBC-PTT1-01
Earphone 2 (Rugged Bluetooth Headset)	**Brand Name**	Zebra	**Part Number**	HS3100-OTH
Earphone 3 (3.5mm PTT Headset)	**Brand Name**	Zebra	**Part Number**	HDST-35MM-PTT1-02
Earphone 4 (Rugged Headset)	**Brand Name**	Zebra	**Part Number**	HS2100-OTH
3.5mm to 3.5mm audio connector	**Brand Name**	Zebra	**Part Number**	CBL-HS2100-3MS1-01
Type C-Audio Cable (Type C to 3.5mm)	**Brand Name**	Zebra	**Part Number**	ADP-USBC-35MM1-01
USB Cable 1 (USB-C to C Cable)	**Brand Name**	Zebra	**Part Number**	CBL-EC5X-USBC3A-01
USB Cable 2 (USB-A to C Cable)	**Brand Name**	Zebra	**Part Number**	CBL-TC5X-USBC2A-01
EM45 Protective Case	**Brand Name**	Zebra	Part Number	SG-EM45EXO1-01

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
SCS	15kHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
Antenna Gain	-3.0dBi for Ant0, -2.11 dBi for Ant1
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. 5G NR n26 supports SA mode only.
2. The maximum power of Ant.0 is shown in the report.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Maximum Conducted Power and Emission Designator

5G NR n26		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	**Frequency Range (MHz)**	**Maximum Conducted power(W)**	**Emission Designator (99%OBW)**	**Maximum Conducted power(W)**	**Emission Designator (99%OBW)**
5	816.5 ~ 821.5	0.1936	4M47G7D	0.1560	4M47W7D
10	819	0.1923	9M26G7D	0.1552	9M29W7D
15	821.5	0.1854	14M1G7D	0.1479	14M1W7D
20	824	0.1954	18M9G7D	0.1500	18M9W7D

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH04-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH04-KS	AUDIX	E3	210616

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X Plane).

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)				Modulation					RB #			Test Channel		
		5	10	15	20	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	n26	v	v	v	v	v	v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	n26	v	v	v	v		v	v	v	v			v		v	
Emission masks In-band emissions	n26	v				v	v				v		v	v	v	v
			v		v	v	v				v		v		v	
Emission masks – Out of band emissions	n26	v				v	v				v			v		v
			v		v	v	v				v				v	
Frequency Stability	n26				v		v						v		v	
Radiated Spurious Emission	n26	Worst Case													v	
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. 5G n26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. 4. Frequency Stability：Normal Voltage = 3.85V ；Low Voltage =3.50V.；High Voltage =4.41V															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Anritsu	MT8821	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

The following shows an offset computation example with RF cable loss 4.8 dB attenuator.

Example :

Offset(dB) = RF cable loss(dB).

= 4.8 (dB)

2.5 Frequency List of Low/Middle/High Channels

5G NR n26 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	163800	-
	Frequency	-	819	-
5	Channel	163300	163800	164300
	Frequency	816.5	819	821.5

5G NR n26 Cross-rule Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**-**	**Middle**	**-**
20	Channel	-	164800	-
	Frequency	-	824	-
15	Channel	-	164300	-
	Frequency	-	821.5	-

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 $Log_{10}(f/6.1)$ decibels or 50 + 10 $Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + $10Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
4. battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Jul. 08, 2024~ Jul. 23, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Jul. 08, 2024~ Jul. 23, 2024	NCR	Conducted (TH01-KS)
Temperature &humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2024	Jul. 08, 2024~ Jul. 23, 2024	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 11, 2023	Aug. 02, 2024~ Aug. 12, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11 2023	Aug. 02, 2024~ Aug. 12, 2024	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 18, 2023	Aug. 02, 2024~ Aug. 12, 2024	Aug. 17, 2025	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 23, 2023	Aug. 02, 2024~ Aug. 12, 2024	Oct. 22, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 27, 2024	Aug. 02, 2024~ Aug. 12, 2024	Jan. 26, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	413740	9KHz-1GHz	Jan. 03, 2024	Aug. 02, 2024~ Aug. 12, 2024	Jan. 02, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM18G40GA	060728	18~40GHz	Jan. 02, 2024	Aug. 02, 2024~ Aug. 12, 2024	Jan. 01, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18GA	060840	1Ghz-18Ghz	Oct. 11, 2023	Aug. 02, 2024~ Aug. 12, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
Amplifier	EM	EM01G18GA	060892	1Ghz-18Ghz	Oct. 11, 2023	Aug. 02, 2024~ Aug. 12, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 02, 2024~ Aug. 12, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 02, 2024~ Aug. 12, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 02, 2024~ Aug. 12, 2024	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Peak to Average Ratio	±0.50 dB
Frequency Stability	±0.04 ppm

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82 dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	**Temperature :**	22~23℃
		Relative Humidity :	40~42%

Software Version: 23.06.1602

FR1 N26

Transmitter Conducted Output Power

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	Conducted Power (W)
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	50@25	22.91	0.1954
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	1@1	22.6	0.1820
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	1@104	22.62	0.1828
26	15	20	164800	824	DFT-s-OFDM QPSK	50@25	22.78	0.1897
26	15	20	164800	824	DFT-s-OFDM QPSK	1@1	22.74	0.1879
26	15	20	164800	824	DFT-s-OFDM QPSK	1@104	22.53	0.1791
26	15	20	164800	824	DFT-s-OFDM 16 QAM	50@25	21.76	0.1500
26	15	20	164800	824	DFT-s-OFDM 16 QAM	1@1	21.72	0.1486
26	15	20	164800	824	DFT-s-OFDM 16 QAM	1@104	21.68	0.1472
26	15	20	164800	824	DFT-s-OFDM 64 QAM	50@25	20.33	0.1079
26	15	20	164800	824	DFT-s-OFDM 64 QAM	1@1	20.15	0.1035
26	15	20	164800	824	DFT-s-OFDM 64 QAM	1@104	20.18	0.1042
26	15	20	164800	824	DFT-s-OFDM 256 QAM	50@25	18.12	0.0649
26	15	20	164800	824	DFT-s-OFDM 256 QAM	1@1	18.02	0.0634
26	15	20	164800	824	DFT-s-OFDM 256 QAM	1@104	17.98	0.0628
26	15	20	164800	824	CP-OFDM QPSK	53@26	21.24	0.1330
26	15	20	164800	824	CP-OFDM QPSK	1@1	21.31	0.1352
26	15	20	164800	824	CP-OFDM QPSK	1@104	21.22	0.1324
26	15	5	163300	816.5	DFT-s-OFDM PI/2 BPSK	1@1	22.75	0.1884
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@1	22.86	0.1932
26	15	5	163300	816.5	DFT-s-OFDM 16 QAM	1@1	21.76	0.1500
26	15	5	163800	819	DFT-s-OFDM PI/2 BPSK	1@1	22.66	0.1845
26	15	5	163800	819	DFT-s-OFDM QPSK	1@1	22.87	0.1936
26	15	5	163800	819	DFT-s-OFDM 16 QAM	1@1	21.93	0.1560
26	15	5	164300	821.5	DFT-s-OFDM PI/2 BPSK	1@1	22.78	0.1897
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@1	22.7	0.1862
26	15	5	164300	821.5	DFT-s-OFDM 16 QAM	1@1	21.83	0.1524
26	15	10	163800	819	DFT-s-OFDM PI/2 BPSK	1@1	22.74	0.1879
26	15	10	163800	819	DFT-s-OFDM QPSK	1@1	22.84	0.1923
26	15	10	163800	819	DFT-s-OFDM 16 QAM	1@1	21.91	0.1552
26	15	15	164300	821.5	DFT-s-OFDM PI/2 BPSK	1@1	22.67	0.1849
26	15	15	164300	821.5	DFT-s-OFDM QPSK	1@1	22.68	0.1854
26	15	15	164300	821.5	DFT-s-OFDM 16 QAM	1@1	21.7	0.1479

Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0029	**PASS**	NV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0022	**PASS**	LV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0031	**PASS**	HV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0047	**PASS**	-30℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0041	**PASS**	-20℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0039	**PASS**	-10℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0034	**PASS**	0℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0026	**PASS**	10℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0022	**PASS**	20℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0031	**PASS**	30℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	-0.0029	**PASS**	40℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0023	**PASS**	50℃

Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
26	15	20	164800	824.0	DFT-s-OFDM PI/2 BPSK	100@0	4.41	13	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM PI/2 BPSK	1@0	4.4	13	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	5.72	13	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	5.98	13	**PASS**

N26(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH



N26(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_Mid_CH

N26(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
26	15	5	163800	819.0	CP-OFDM QPSK	25@0	4.4709	4.929
26	15	5	163800	819.0	CP-OFDM 16 QAM	25@0	4.4692	4.849
26	15	5	163800	819.0	CP-OFDM 64 QAM	25@0	4.4707	4.931
26	15	5	163800	819.0	CP-OFDM 256 QAM	25@0	4.4739	4.913
26	15	10	163800	819.0	CP-OFDM QPSK	52@0	9.2638	9.853
26	15	10	163800	819.0	CP-OFDM 16 QAM	52@0	9.2864	9.763
26	15	10	163800	819.0	CP-OFDM 64 QAM	52@0	9.2608	9.758
26	15	10	163800	819.0	CP-OFDM 256 QAM	52@0	9.2776	9.834
26	15	15	164300	821.5	CP-OFDM QPSK	79@0	14.079	14.67
26	15	15	164300	821.5	CP-OFDM 16 QAM	79@0	14.075	14.72
26	15	15	164300	821.5	CP-OFDM 64 QAM	79@0	14.083	14.7
26	15	15	164300	821.5	CP-OFDM 256 QAM	79@0	14.066	14.73
26	15	20	164800	824.0	CP-OFDM QPSK	106@0	18.897	19.67
26	15	20	164800	824.0	CP-OFDM 16 QAM	106@0	18.895	19.72
26	15	20	164800	824.0	CP-OFDM 64 QAM	106@0	18.892	19.6
26	15	20	164800	824.0	CP-OFDM 256 QAM	106@0	18.864	19.65

N26(5M)_CP-OFDM_QPSK_Outer_Full_Mid_CH



N26(5M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH



N26(5M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH



N26(5M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH



N26(10M)_CP-OFDM_QPSK_Outer_Full_Mid_CH

N26(10M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH



N26(10M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH



N26(10M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_QPSK_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_QPSK_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH

N26(20M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH



Conducted Spurious Emissions

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	**---**
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	**---**
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	**PASS**
26	15	5	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	**---**
26	15	5	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	5	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	**---**
26	15	5	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@0	see graph	**---**
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@0	see graph	**---**
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	**---**
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	**---**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	**PASS**

N26(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH



N26(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N26(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH



N26(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH



N26(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



Conducted Band Edge

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	**PASS**
26	15	5	163300	816.5	DFT-s-OFDM BPSK	25@0	see graph	**PASS**
26	15	5	163300	816.5	DFT-s-OFDM QPSK	25@0	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@24	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@24	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM BPSK	25@0	see graph	**PASS**
26	15	5	164300	821.5	DFT-s-OFDM QPSK	25@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@105	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@105	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM BPSK	100@0	see graph	**PASS**
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	see graph	**PASS**

N26(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-OFDM_BPSK_Outer_Full_Low_CH



N26(5M)_DFT-s-OFDM_QPSK_Outer_Full_Low_CH



N26(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_High_CH



N26(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_High_CH



N26(5M)_DFT-s-OFDM_BPSK_Outer_Full_High_CH



N26(5M)_DFT-s-OFDM_QPSK_Outer_Full_High_CH



N26(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N26(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_Mid_CH



N26(20M)_DFT-s-OFDM_BPSK_Outer_Full_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Bruce	Temperature :	23~25℃
		Relative Humidity :	41~42%

n26 SA / NR 20MHz / QPSK for Ant0								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1632	-66.26	-13	-53.26	-73.23	1.58	10.70	H
	2448	-61.79	-13	-48.79	-70.04	2.102	12.50	H
	3264	-60.58	-13	-47.58	-69.47	2.856	13.90	H
	1632	-65.31	-13	-52.31	-72.28	1.58	10.70	V
	2448	-59.85	-13	-46.85	-68.10	2.10	12.50	V
	3264	-60.62	-13	-47.62	-69.51	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.