FCC RF Test Report

FCC ID	:	UZ7ET4015A
EQUIPMENT	:	Enterprise Tablet
BRAND NAME	:	Zebra
MODEL NAME	:	ET4015A
APPLICANT	:	Zebra Technologies Corporation 3 Overlook Point, Lincolnshire, IL 60069 USA
MANUFACTURER	:	Zebra Technologies Corporation 3 Overlook Point, Lincolnshire, IL 60069 USA
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	15E 6 GHz Low Power Dual Client (6CD) (Indoor Low Power UNII-5/6/7/8)
TEST DATE(S)	:	Jun. 19, 2026

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Table of Contents

1 General Description 5
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 6
1.3 Modification of EUT 6
1.4 Testing Location 7
1.5 Test Software 7
1.6 Applicable Standards 7
2 Test Configuration of Equipment Under Test 8
2.1 Carrier Frequency and Channel 8
2.2 Test Mode 10
2.3 Connection Diagram of Test System 11
2.4 EUT Operation Test Setup 11
3 Test Result 12
3.1 Unwanted Emissions Measurement 12
4 List of Measuring Equipment 16
5 Measurement Uncertainty 17
Appendix A. Radiated Spurious Emission
Appendix B. Duty Cycle Plots
Appendix C. Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
FR551202-16E	01	Initial issue of report	Jul. 14, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.407(b)	Unwanted Emissions	Pass	Under limit 1.74 dB at 7125.00 MHz

Note: This is a variant report the change note could be referred to the Product Equality Declaration which is exhibit separately. According to the change, only the related test cases were verified from original report FR551202-09G.

Conformity Assessment Condition:
1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. 2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”
Disclaimer:
The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Tablet
Brand Name	Zebra
Model Name	ET4015A
FCC ID	UZ7ET4015A
SN Code	Radiation: S26140524703899
MFD	20MAY26
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessory				
Battery	**Brand Name**	Zebra	**Model**	BT-000527

Supported Unit used in test configuration and system				
AC Adapter 1 (TYPE C Wall Charger 1)	**Brand Name**	Zebra	**Part Number**	PWR-WUA5V45W1US
Earphone 1 (Wired headset USB-C)	**Brand Name**	Zebra	**Part Number**	HDST-USBC-PTT 1-01
Earphone 2 (Rugged Bluetooth Headset)	**Brand Name**	Zebra	**Part Number**	HS3100-0TH
Earphone 3 (3.5mm PTT Headset)	**Brand Name**	Zebra	**Part Number**	HDST-35MM-PTT 1-02
Earphone 4 (Rugged Headset)	**Brand Name**	Zebra	**Part Number**	HS2100-0TH
Type C-Audio Cable (Type C to 3.5mm)	**Brand Name**	Zebra	**Part Number**	ADP-USBC-35MM1-01
3.5mm to 3.5mm audio connector	**Brand Name**	Zebra	**Part Number**	CBL-HS2100-3MS1-01
USB Cable 1 (USB-C to C Cable)	**Brand Name**	Zebra	**Part Number**	CBL-EC5X-USBC3A-01
USB Cable 3 (USB-C to C Cable)	**Brand Name**	Zebra	**Part Number**	CBL-TN28-USBC2C-01

1.2 Product Specification of Equipment Under Test

<table>
<tr><th colspan="2">Standards-related Product Specification</th></tr>
<tr><td>Tx/Rx Frequency Range</td><td>U-NII-5: 5925 MHz ~ 6425 MHz
U-NII-6: 6425 MHz ~ 6525 MHz
U-NII-7: 6525 MHz ~ 6875 MHz
U-NII-8: 6875 MHz ~ 7125 MHz</td></tr>
<tr><td>Antenna Type / Gain</td><td><5925 MHz ~ 6425 MHz >
<Ant. 6>: IFA Antenna with gain 0.2 dBi
<Ant. 7>: IFA Antenna with gain -0.3 dBi
<6425 MHz ~ 6525 MHz >
<Ant. 6>: IFA Antenna with gain 0.6 dBi
<Ant. 7>: IFA Antenna with gain -0.6 dBi
<6525 MHz ~ 6875 MHz >
<Ant. 6>: IFA Antenna with gain 0 dBi
<Ant. 7>: IFA Antenna with gain -0.4 dBi
<6875 MHz ~ 7125 MHz >
<Ant. 6>: IFA Antenna with gain -0.5 dBi
<Ant. 7>: IFA Antenna with gain -0.2 dBi</td></tr>
<tr><td>Type of Modulation</td><td>802.11a: OFDM (BPSK / QPSK / 16QAM / 64QAM)
802.11ax: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)
802.11be: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM)</td></tr>
<tr><td>Antenna Function Description</td><td><table>
<tr><th></th><th>Ant. 6</th><th>Ant. 7</th></tr>
<tr><td>802.11 a/ax/be SISO</td><td>V</td><td>V</td></tr>
<tr><td>802.11 a/ax/be CDD</td><td colspan="2">V</td></tr>
<tr><td>802.11 ax/be SDM/TXBF</td><td colspan="2">V</td></tr>
</table></td></tr>
</table>

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH05-KS	CN1257	314309

1.5 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH05-KS	AUDIX	E3	210616

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 987594 D02 U-NII 6 GHz EMC Measurement v03
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2020+Cor.1-2023

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency and Channel

<U-NII-5, 6, 7, 8>

BW 20M	**Channel**	1	5	9	13	17	21	25	29
	Freq. (MHz)	5955	5975	5995	6015	6035	6055	6075	6095
BW 40M	**Channel**	3		11		19		27	
	Freq. (MHz)	5965		6005		6045		6085	
BW 80M	**Channel**	7				23			
	Freq. (MHz)	5985				6065			
BW 160M	**Channel**	15							
	Freq. (MHz)	6025							

BW 20M	**Channel**	33	37	41	45	49	53	57	61
	Freq. (MHz)	6115	6135	6155	6175	6195	6215	6235	6255
BW 40M	**Channel**	35		43		51		59	
	Freq. (MHz)	6125		6165		6205		6245	
BW 80M	**Channel**	39				55			
	Freq. (MHz)	6145				6225			
BW 160M	**Channel**	47							
	Freq. (MHz)	6185							
BW 320M	**Channel**	31				63			
	Freq. (MHz)	6105				6265			

BW 20M	Channel	65	69	73	77	81	85	89	93
	Freq. (MHz)	6275	6295	6315	6335	6355	6375	6395	6415
BW 40M	Channel	67		75		83		91	
	Freq. (MHz)	6285		6325		6365		6405	
BW 80M	Channel	71				87			
	Freq. (MHz)	6305				6385			
BW 160M	Channel	79							
	Freq. (MHz)	6345							
BW 320M	Channel	95							
	Freq. (MHz)	6425							

BW 20M	Channel	97	101	105	109	113	117	121	125
	Freq. (MHz)	6435	6455	6475	6495	6515	6535	6555	6575
BW 40M	Channel	99		107		115		123	
	Freq. (MHz)	6445		6485		6525		6565	
BW 80M	Channel	103				119			
	Freq. (MHz)	6465				6545			
BW 160M	Channel	111							
	Freq. (MHz)	6505							

BW 20M	Channel	129	133	137	141	145	149	153	157
	Freq. (MHz)	6595	6615	6635	6655	6675	6695	6715	6735
BW 40M	Channel	131		139		147		155	
	Freq. (MHz)	6605		6645		6685		6725	
BW 80M	Channel	135				151			
	Freq. (MHz)	6625				6705			
BW 160M	Channel	143							
	Freq. (MHz)	6665							
BW 320M	Channel	127							
	Freq. (MHz)	6585							

BW 20M	Channel	161	165	169	173	177	181	185	189
	Freq. (MHz)	6755	6775	6795	6815	6835	6855	6875	6895
BW 40M	Channel	163		171		179		187	
	Freq. (MHz)	6765		6805		6845		6885	
BW 80M	Channel	167				183			
	Freq. (MHz)	6785				6865			
BW 160M	Channel	175							
	Freq. (MHz)	6825							
BW 320M	Channel	159							
	Freq. (MHz)	6745							

BW 20M	Channel	193	197	201	205	209	213	217	221
	Freq. (MHz)	6915	6935	6955	6975	6995	7015	7035	7055
BW 40M	Channel	195		203		211		219	
	Freq. (MHz)	6925		6965		7005		7045	
BW 80M	Channel	199				215			
	Freq. (MHz)	6945				7025			
BW 160M	Channel	207							
	Freq. (MHz)	6985							
BW 320M	Channel	191							
	Freq. (MHz)	6905							

BW 20M	Channel	225	229	233
	Freq. (MHz)	7075	7095	7115
BW 40M	Channel	227		
	Freq. (MHz)	7085		

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11be EHT20	**MCS0**

2.3 Connection Diagram of Test System

Radiated Emission:



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.4 EUT Operation Test Setup

For WLAN RF test items, an engineering test program (QRCT TX Tool) was provided and enabled to make EUT continuously transmit.

3 Test Result

3.1 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.1.1 Limit of Unwanted Emissions

(1) For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an e.i.r.p. of −27 dBm/MHz.

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27 (RMS)	68.2
- 7 (Peak)	88.2

Unwanted emissions outside of restricted bands are measured with a RMS detector.
In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.1.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.1.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A

3.1.7 Duty Cycle

Please refer to Appendix B.

3.1.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

The emission level above 18GHz is checked that the emission level is noise floor only, so it is not reflected in the report.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz; Max 30dBm	Jul. 02, 2025	Jun. 19, 2026	Jul. 01, 2026	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz-44G, MAX 30dB	Oct. 10, 2025	Jun. 19, 2026	Oct. 10, 2026	Radiation (03CH05-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Jun. 19, 2026	Aug. 09, 2026	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	Mar. 23, 2026	Jun. 19, 2026	Mar. 22, 2027	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251694	1GHz~18GHz	Aug. 22, 2025	Jun. 19, 2026	Aug. 21, 2026	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 18, 2025	Jun. 19, 2026	Oct. 19, 2026	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 03, 2025	Jun. 19, 2026	Jul. 02, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Dec. 26, 2025	Jun. 19, 2026	Dec.25, 2026	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz-18Ghz	Dec. 25, 2025	Jun. 19, 2026	Dec.24, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz-18Ghz	Dec. 25, 2025	Jun. 19, 2026	Dec.24, 2026	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 19, 2026	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 19, 2026	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 19, 2026	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.14 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.86 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.32 dB

---------- THE END ----------

Appendix A. Radiated Spurious Emission

Test Engineer :	Jake zhou	**Relative Humidity :**	51 ~ 53 %
		Temperature :	22 ~ 26 ℃

Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	U-NII-5	5.925-6.425	A6+A7	802.11be EHT20	233	7115	MCS0	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	802.11be EHT20	233	7125.00	66.46	68.20	-1.74	H	AVERAGE	Pass	Band Edge
3	802.11be EHT20	233	14230.00	44.89	88.20	-43.31	V	PEAK	Pass	Harmonic

Mode	1	
	Band Edge	
	U-NII-5_5.925-6.425_802.11be EHT20_CH233_7115MHz	
ANT	A6+A7	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.00 73.74 88.20 -14.46 60.83 35.80 13.98 36.87 0.00 100 205 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7115.00 87.72 ------ ------ 74.81 35.80 13.98 36.87 0.00 100 205 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.00 66.46 68.20 -1.74 53.55 35.80 13.98 36.87 0.00 100 205 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7115.00 78.29 ------ ------ 65.39 35.80 13.97 36.87 0.00 100 205 AVERAGE

Mode	1	
	Band Edge	
	U-NII-5_5.925-6.425_802.11be EHT20_CH233_7115MHz	
ANT	A6+A7	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.00 69.08 88.20 -19.12 56.17 35.80 13.98 36.87 0.00 385 226 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7115.00 84.25 ------ ------ 71.35 35.80 13.97 36.87 0.00 385 226 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.00 62.86 68.20 -5.34 49.95 35.80 13.98 36.87 0.00 385 226 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7115.00 73.88 ------ ------ 60.97 35.80 13.98 36.87 0.00 385 226 AVERAGE

Mode	1	
	Harmonic	
	U-NII-5_5.925-6.425_802.11be EHT20_CH233_7115MHz	
ANT	A6+A7	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 14230.00 44.58 88.20 -43.62 50.09 39.06 19.89 64.46 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 14230.00 44.89 88.20 -43.31 50.40 39.06 19.89 64.46 0.00 --- --- PEAK

Mode	1	
	18G-40G	
	U-NII-5_5.925-6.425_802.11be EHT20_CH233_7115MHz	
ANT	A6+A7	
Pol.	Horizontal	Vertical
Peak Avg		

Mode	1	
	30-1G	
	U-NII-5_5.925-6.425_802.11be EHT20_CH233_7115MHz	
ANT	A6+A7	
Pol.	Horizontal	Vertical
Peak		

	Freq	Level	Limit Line	Over Limit	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	79.71	28.84	40.00	-11.16	46.81	13.66	1.03	32.66	0.00	---	---	Peak
2	137.91	33.37	43.50	-10.13	46.96	17.70	1.46	32.75	0.00	---	---	Peak
3	270.08	31.76	46.00	-14.24	43.28	19.23	2.06	32.81	0.00	---	---	Peak
4	503.85	26.34	46.00	-19.66	32.16	24.50	2.82	33.14	0.00	---	---	Peak
5	617.82	25.05	46.00	-20.95	28.71	26.44	3.14	33.24	0.00	---	---	Peak
6	783.69	27.84	46.00	-18.16	28.52	28.69	3.53	32.90	0.00	---	---	Peak

	Freq	Level	Limit Line	Over Limit	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	78.74	36.31	40.00	-3.69	54.44	13.53	1.01	32.67	0.00	---	---	Peak
2	140.34	37.87	43.50	-5.63	51.47	17.68	1.47	32.75	0.00	---	---	Peak
3	251.16	29.97	46.00	-16.03	41.80	18.98	1.98	32.79	0.00	---	---	Peak
4	508.21	27.31	46.00	-18.69	33.12	24.50	2.83	33.14	0.00	---	---	Peak
5	706.82	26.27	46.00	-19.73	29.08	27.01	3.35	33.17	0.00	---	---	Peak
6	876.57	28.77	46.00	-17.23	27.54	29.79	3.73	32.29	0.00	---	---	Peak

Appendix B. Duty Cycle Plots

Band	ANT	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11be EHT20	6+7	100	-	-	10Hz

802.11be EHT20