



FCC RF Test Report

FCC ID : UZ7ET401EB
EQUIPMENT : Enterprise Tablet
BRAND NAME : Zebra
MODEL NAME : ET401EB
APPLICANT : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
MANUFACTURER : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
STANDARD : 47 CFR Part 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Dec. 11, 2025 ~ Dec. 12, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Product Feature of Equipment Under Test	5
1.2 Product Specification of Equipment Under Test	6
1.3 Modification of EUT	6
1.4 Maximum ERP/EIRP Power, and Emission Designator	6
1.5 Testing Location	7
1.6 Test Software	7
1.7 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	9
2.4 Measurement Results Explanation Example	9
2.5 Frequency List of Low/Middle/High Channels	9
3 CONDUCTED TEST RESULT	10
3.1 Measuring Instruments.....	10
3.2 Test Setup	10
3.3 Test Result of Conducted Test.....	10
3.4 Conducted Output Power and ERP/EIRP	11
3.5 Peak-to-Average Ratio	12
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	13
3.7 Conducted Band Edge	14
3.8 Conducted Spurious Emission	15
3.9 Frequency Stability	16
4 RADIATED TEST ITEMS	17
4.1 Measuring Instruments.....	17
4.2 Test Setup	17
4.3 Test Result of Radiated Test.....	18
4.4 Field Strength of Spurious Radiation Measurement	19
5 LIST OF MEASURING EQUIPMENT	20
6 MEASUREMENT UNCERTAINTY	21
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG591015V	Rev. 01	Initial issue of report	Dec. 31, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 35.18 dB at 2472.60 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Tablet
Brand Name	Zebra
Model Name	ET401EB
FCC ID	UZ7ET401EB
IMEI Code	Conducted: 356424630002295/356424630002303 Radiation: 356424630012724/356424630012740
HW Version	EV2
SW Version	qssi_64-userdebug 15 15-11-10.00-VG-U00-PRD-ERS-04 777 release-keys
MFD	13SEP2025
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT: Sample 1 without Scanner and Sample 2 with Scanner. According to the difference, we evaluated Sample 1 to perform full test.

Specification of Accessory				
Battery	Brand Name	Zebra	Model	BT-000528

Supported Unit used in test configuration and system				
AC Adapter 1 (TYPE C Wall Charger 1)	Brand Name	Zebra	Part Number	PWR-WUA5V45W1US
Earphone 1 (Wired headset USB-C)	Brand Name	Zebra	Part Number	HDST-USBC-PTT 1-01
Earphone 2 (Rugged Bluetooth Headset)	Brand Name	Zebra	Part Number	HS3100-0TH
Earphone 3 (3.5mm PTT Headset)	Brand Name	Zebra	Part Number	HDST-35MM-PTT 1-02
Earphone 4 (Rugged Headset)	Brand Name	Zebra	Part Number	HS2100-0TH
Type C-Audio Cable Type C to 3.5mm	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm to 3.5mm audio connector	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
USB Cable 1 USB-C to C Cable	Brand Name	Zebra	Part Number	CBL-EC5X-USBC3A-01
USB Cable 3 USB-C to C Cable	Brand Name	Zebra	Part Number	CBL-TN28-USBC2C-01

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GPRS/EDGE: 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz
Rx Frequency	GPRS/EDGE: 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GPRS/EDGE: 850<ANT8>: 32.49 dBm 1900<ANT1>: 28.04 dBm
Antenna Type	IFA Antenna
Antenna Gain	<ANT8>: Cellular Band: 0 dBi <ANT1>: PCS Band: 0.05 dBi
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Maximum ERP/EIRP Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	GSM850 (GPRS)	824.2 ~ 848.8	GMSK	1.0814	243KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.2612	244KG7W
Part 24	GSM1900 (GPRS)	1850.2 ~ 1909.8	GMSK	0.6442	244KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.2612	243KG7W

1.5 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH02-SZ	CN1256	421272

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22(H), 24(E)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19100 MHz for GSM1900.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS 1 Tx slots Link	■ GPRS 1 Tx slots Link
	■ EDGE 1 Tx slots Link	■ EDGE 1 Tx slots Link
GSM 1900	■ GPRS 1 Tx slots Link	■ GPRS 1 Tx slots Link
	■ EDGE 1 Tx slots Link	■ EDGE 1 Tx slots Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.0 + 10 = 14.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Dec. 12, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V, 3A	Oct. 13, 2025	Dec. 12, 2025	Oct. 12, 2026	Conducted (TH01-SZ)
Power Divider	Titan	P02N005180	923402	0.4GHz~26.5GHz	Nov. 07, 2025	Dec. 12, 2025	Nov. 06, 2026	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Dec. 12, 2025	Jul. 01, 2026	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Dec. 11, 2025	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Dec. 11, 2025	Dec. 27, 2025	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Oct. 24, 2025	Dec. 11, 2025	Oct. 23, 2027	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	Dec. 11, 2025	Jul. 04, 2026	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Dec. 11, 2025	Jul. 03, 2026	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03, 2025	Dec. 11, 2025	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2024	Dec. 11, 2025	Dec. 24, 2025	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 14, 2025	Dec. 11, 2025	Oct. 13, 2026	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 18, 2025	Dec. 11, 2025	Oct. 17, 2026	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Dec. 11, 2025	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Dec. 11, 2025	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Peak to Average Ratio	± 1.34 dB
Frequency Stability	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72 dB
---	---------

----- THE END -----

Appendix A. Test Results of Conducted Test

Test Engineer :	Nina Cheng	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and ERP/EIRP

GSM850_ANT8:

GSM850	Burst Average Power (dBm)			ERP(W)		
TX Channel	128	189	251			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GPRS 1 Tx slot	32.49	32.02	32.32	1.0814	0.9705	1.0399
GPRS 2 Tx slots	32.07	31.59	32.00	0.9817	0.8790	0.9661
GPRS 3 Tx slots	31.73	31.15	31.77	0.9078	0.7943	0.9162
GPRS 4 Tx slots	30.84	30.89	30.91	0.7396	0.7482	0.7516
EDGE 1 Tx slot	26.14	26.32	25.97	0.2506	0.2612	0.2410
EDGE 2 Tx slots	25.91	26.09	25.72	0.2377	0.2477	0.2275
EDGE 3 Tx slots	25.61	25.78	25.37	0.2218	0.2307	0.2099
EDGE 4 Tx slots	25.35	25.45	25.31	0.2089	0.2138	0.2070

GSM1900_ANT1:

GSM1900	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GPRS 1 Tx slot	27.64	27.61	28.04	0.5875	0.5834	0.6442
GPRS 2 Tx slots	27.31	27.01	27.60	0.5445	0.5082	0.5821
GPRS 3 Tx slots	26.86	26.64	27.24	0.4909	0.4667	0.5358
GPRS 4 Tx slots	26.42	26.60	26.51	0.4436	0.4624	0.4529
EDGE 1 Tx slot	23.68	23.46	24.12	0.2360	0.2244	0.2612
EDGE 2 Tx slots	22.97	23.39	23.52	0.2004	0.2208	0.2275
EDGE 3 Tx slots	22.76	23.23	23.36	0.1910	0.2128	0.2193
EDGE 4 Tx slots	22.60	23.06	23.18	0.1841	0.2046	0.2104





A1. GPRS

Peak-to-Average Ratio

Mode	GPRS850(dB)		Limit: 13dB
Mod.	GPRS	EDGE class 8	Result
Lowest CH	0.2	3.27	PASS
Middle CH	0.20	3.54	
Highest CH	0.14	3.27	

Mode	GPRS1900(dB)		Limit: 13dB
Mod.	GPRS	EDGE class 8	Result
Lowest CH	0.23	3.42	PASS
Middle CH	0.20	3.19	
Highest CH	0.20	3.25	







26dB Bandwidth


Mode	GPRS850(MHz)	
Mod.	GPRS	EDGE
Lowest CH	0.32	0.31
Middle CH	0.32	0.31
Highest CH	0.32	0.31

Mode	GPRS1900(MHz)	
Mod.	GPRS	EDGE
Lowest CH	0.32	0.31
Middle CH	0.32	0.31
Highest CH	0.32	0.31



GPRS850


Lowest Channel



Date: 12, DEC, 2025 03:09:28


EDGE850

Lowest Channel




Date: 12, DEC, 2025 02:57:43

Middle Channel




Date: 12, DEC, 2025 03:12:51

Middle Channel




Date: 12, DEC, 2025 03:01:02

Highest Channel



Date: 12, DEC, 2025 03:14:31

Highest Channel




Date: 12, DEC, 2025 03:02:09




GPRS1900

Lowest Channel




EDGE1900


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel





Occupied Bandwidth


Mode	GPRS850(MHz)	
Mod.	GPRS	EDGE class 8
Lowest CH	0.242	0.241
Middle CH	0.243	0.244
Highest CH	0.241	0.242

Mode	GPRS1900(MHz)	
Mod.	GPRS	EDGE class 8
Lowest CH	0.244	0.241
Middle CH	0.243	0.243
Highest CH	0.244	0.241




GPRS850

Lowest Channel



EDGE850


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel





GPRS1900

Lowest Channel




EDGE1900


Lowest Channel




Middle Channel




Middle Channel







Highest Channel



Highest Channel




**Conducted Band Edge****GPRS850****Lowest Band Edge****Highest Band Edge****EDGE850****Lowest Band Edge****Highest Band Edge**



GPRS1900

Lowest Band Edge




Highest Band Edge




EDGE1900

Lowest Band Edge




Highest Band Edge






Conducted Spurious Emission





GPRS1900


Lowest Channel



Date: 12, DEC, 2025 03:49:19


EDGE1900

Lowest Channel




Date: 12, DEC, 2025 03:13:13

Middle Channel




Date: 12, DEC, 2025 03:50:26

Middle Channel




Date: 12, DEC, 2025 03:13:19

Highest Channel



Date: 12, DEC, 2025 03:51:51

Highest Channel



Date: 12, DEC, 2025 03:13:16

**Frequency Stability**

Test Conditions	Middle Channel	GPRS850	EDGE850	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0035	0.0000	PASS
40	Normal Voltage	0.0044	0.0017	
30	Normal Voltage	0.0020	0.0002	
20(Ref.)	Normal Voltage	0.0000	0.0001	
10	Normal Voltage	0.0097	0.0014	
0	Normal Voltage	0.0017	0.0027	
-10	Normal Voltage	0.0036	0.0032	
-20	Normal Voltage	0.0013	0.0014	
-30	Normal Voltage	0.0019	0.0020	
20	Maximum Voltage	0.0023	0.0024	
20	Normal Voltage	0.0000	0.0001	
20	Battery End Point	0.0026	0.0051	

Test Conditions	Middle Channel	GPRS1900	EDGE1900	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Frequency Offset (Δf) (Hz)		Result
50	Normal Voltage	5.3	4.5	PASS
40	Normal Voltage	4.3	5.2	
30	Normal Voltage	7.5	4.9	
20(Ref.)	Normal Voltage	9.8	7.2	
10	Normal Voltage	-5.5	3.5	
0	Normal Voltage	-7.6	4.8	
-10	Normal Voltage	5.6	5.9	
-20	Normal Voltage	5.7	5.7	
-30	Normal Voltage	6.2	6.3	
20	Maximum Voltage	7.5	7.5	
20	Normal Voltage	9.8	7.2	
20	Battery End Point	9.5	9.1	

Note:

1. Normal Voltage = 3.91V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.45 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

$$|MAX(\Delta f)| = 9.8 \text{ Hz}$$

Frequency Stability	GPRS1900 Frequency (MHz)	Limit Line	Result
$f_L - MAX(\Delta f) $	1850.081114	$\geq 1850\text{MHz}$	PASS
$f_H + MAX(\Delta f) $	1909.924886	$\leq 1910\text{MHz}$	

$$|MAX(\Delta f)| = 9.1 \text{ Hz}$$

Frequency Stability	EDGE1900 Frequency (MHz)	Limit Line	Result
$f_L - MAX(\Delta f) $	1850.082111	$\geq 1850\text{MHz}$	PASS
$f_H + MAX(\Delta f) $	1909.924889	$\leq 1910\text{MHz}$	



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	LiangPingZhou	Temperature :	22~25℃
		Relative Humidity :	48~52%

GSM850 (GPRS 1 Tx slots)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-65.21	-13	-52.21	-76.74	-68.44	3.98	9.36	H
	2472.6	-48.18	-13	-35.18	-66.91	-51.73	4.85	10.55	H
	3296.8	-58.66	-13	-45.66	-79.35	-63.59	5.50	12.58	H
	1648.4	-63.97	-13	-50.97	-76.14	-67.20	3.98	9.36	V
	2472.6	-49.91	-13	-36.91	-68.96	-53.46	4.85	10.55	V
	3296.8	-57.46	-13	-44.46	-79.04	-62.39	5.50	12.58	V
Middle	1672.8	-64.83	-13	-51.83	-76.51	-68.08	4.00	9.40	H
	2509.2	-50.14	-13	-37.14	-69.14	-53.71	4.88	10.60	H
	3345.6	-59.19	-13	-46.19	-80.16	-64.12	5.52	12.60	H
	1672.8	-63.86	-13	-50.86	-76.25	-67.11	4.00	9.40	V
	2509.2	-53.60	-13	-40.60	-72.81	-57.17	4.88	10.60	V
	3345.6	-58.55	-13	-45.55	-79.82	-63.48	5.52	12.60	V
Highest	1697.6	-65.31	-13	-52.31	-77.27	-68.48	4.10	9.42	H
	2546.4	-52.19	-13	-39.19	-71.33	-55.77	4.90	10.63	H
	3395.2	-59.61	-13	-46.61	-79.30	-64.53	5.55	12.62	H
	1697.6	-64.45	-13	-51.45	-77.08	-67.62	4.10	9.42	V
	2546.4	-54.24	-13	-41.24	-73.60	-57.82	4.90	10.63	V
	3395.2	-58.45	-13	-45.45	-79.47	-63.37	5.55	12.62	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE 1 Tx slots)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-65.13	-13	-52.13	-76.66	-68.36	3.98	9.36	H
	2472.6	-49.71	-13	-36.71	-68.44	-53.26	4.85	10.55	H
	3296.8	-58.31	-13	-45.31	-79.00	-63.24	5.50	12.58	H
	1648.4	-64.77	-13	-51.77	-76.94	-68.00	3.98	9.36	V
	2472.6	-53.26	-13	-40.26	-72.31	-56.81	4.85	10.55	V
	3296.8	-57.93	-13	-44.93	-79.51	-62.86	5.50	12.58	V
Middle	1672.8	-65.09	-13	-52.09	-76.77	-68.34	4.00	9.40	H
	2509.2	-53.43	-13	-40.43	-72.43	-57.00	4.88	10.60	H
	3345.6	-58.89	-13	-45.89	-79.86	-63.82	5.52	12.60	H
	1672.8	-64.32	-13	-51.32	-76.71	-67.57	4.00	9.40	V
	2509.2	-57.23	-13	-44.23	-76.44	-60.80	4.88	10.60	V
	3345.6	-58.63	-13	-45.63	-79.90	-63.56	5.52	12.60	V
Highest	1697.6	-65.28	-13	-52.28	-77.24	-68.45	4.10	9.42	H
	2546.4	-52.48	-13	-39.48	-71.62	-56.06	4.90	10.63	H
	3395.2	-59.45	-13	-46.45	-79.14	-64.37	5.55	12.62	H
	1697.6	-64.44	-13	-51.44	-77.07	-67.61	4.10	9.42	V
	2546.4	-55.47	-13	-42.47	-74.83	-59.05	4.90	10.63	V
	3395.2	-58.34	-13	-45.34	-79.36	-63.26	5.55	12.62	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GPRS 1 Tx slots)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-56.68	-13	-43.68	-79.62	-63.44	5.82	12.58	H
	5550.6	-56.70	-13	-43.70	-80.99	-62.42	7.28	13.00	H
	7400.8	-54.12	-13	-41.12	-81.04	-57.28	8.32	11.48	H
	3700.4	-54.47	-13	-41.47	-79.1	-61.23	5.82	12.58	V
	5550.6	-56.49	-13	-43.49	-81.21	-62.21	7.28	13.00	V
	7400.8	-54.26	-13	-41.26	-81.15	-57.42	8.32	11.48	V
Middle	3760	-57.04	-13	-44.04	-79.33	-63.79	5.85	12.60	H
	5640	-56.22	-13	-43.22	-80.18	-62.02	7.30	13.10	H
	7520	-54.40	-13	-41.40	-80.89	-57.55	8.35	11.50	H
	3760	-54.53	-13	-41.53	-79.98	-61.28	5.85	12.60	V
	5640	-55.94	-13	-42.94	-80.05	-61.74	7.30	13.10	V
	7520	-54.94	-13	-41.94	-81.41	-58.09	8.35	11.50	V
Highest	3819.6	-57.01	-13	-44.01	-79.75	-63.75	5.88	12.62	H
	5729.4	-56.01	-13	-43.01	-80.44	-61.82	7.32	13.13	H
	7639.2	-55.02	-13	-42.02	-81.15	-58.18	8.38	11.54	H
	3819.6	-55.58	-13	-42.58	-79.92	-62.32	5.88	12.62	V
	5729.4	-55.79	-13	-42.79	-80.7	-61.60	7.32	13.13	V
	7639.2	-54.06	-13	-41.06	-81.22	-57.22	8.38	11.54	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE 1 Tx slots)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-56.22	-13	-43.22	-79.16	-62.98	5.82	12.58	H
	5550.6	-56.62	-13	-43.62	-80.91	-62.34	7.28	13.00	H
	7400.8	-53.69	-13	-40.69	-80.61	-56.85	8.32	11.48	H
	3700.4	-54.04	-13	-41.04	-78.67	-60.80	5.82	12.58	V
	5550.6	-56.62	-13	-43.62	-81.34	-62.34	7.28	13.00	V
	7400.8	-53.86	-13	-40.86	-80.75	-57.02	8.32	11.48	V
Middle	3760	-57.23	-13	-44.23	-79.52	-63.98	5.85	12.60	H
	5640	-56.29	-13	-43.29	-80.25	-62.09	7.30	13.10	H
	7520	-54.94	-13	-41.94	-81.43	-58.09	8.35	11.50	H
	3760	-54.36	-13	-41.36	-79.81	-61.11	5.85	12.60	V
	5640	-56.47	-13	-43.47	-80.58	-62.27	7.30	13.10	V
	7520	-54.90	-13	-41.90	-81.37	-58.05	8.35	11.50	V
Highest	3819.6	-56.60	-13	-43.60	-79.34	-63.34	5.88	12.62	H
	5729.4	-56.15	-13	-43.15	-80.58	-61.96	7.32	13.13	H
	7639.2	-54.92	-13	-41.92	-81.05	-58.08	8.38	11.54	H
	3819.6	-55.86	-13	-42.86	-80.2	-62.60	5.88	12.62	V
	5729.4	-55.42	-13	-42.42	-80.33	-61.23	7.32	13.13	V
	7639.2	-54.54	-13	-41.54	-81.7	-57.70	8.38	11.54	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.