



FCC RF Test Report

FCC ID : UZ7ET401EB
EQUIPMENT : Enterprise Tablet
BRAND NAME : Zebra
MODEL NAME : ET401EB
APPLICANT : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
MANUFACTURER : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
STANDARD : 47 CFR Part 90(S)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Sep. 28, 2025 ~ Nov. 30, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test	6
1.3 Modification of EUT	6
1.4 Maximum Conducted Power and Emission Designator	6
1.5 Testing Site.....	7
1.6 Test Software	7
1.7 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system	9
2.4 Measurement Results Explanation Example	9
2.5 Frequency List of Low/Middle/High Channels.....	9
3 TEST RESULT	10
3.1 Conducted Output Power Measurement.....	10
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	11
3.3 Emissions Mask Measurement	12
3.4 Emissions Mask – Out Of Band Emissions Measurement.....	14
3.5 Field Strength of Spurious Radiation Measurement	15
3.6 Frequency Stability Measurement.....	18
4 LIST OF MEASURING EQUIPMENT	20
5 MEASUREMENT UNCERTAINTY	21
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG5910150	Rev. 01	Initial issue of report	Dec. 31, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	—	Report only	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	—	Report only	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 26.33 dB at 10122.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Tablet
Brand Name	Zebra
Model Name	ET401EB
FCC ID	UZ7ET401EB
IMEI Code	Conducted: 356424630001933/356424630001941 356424630001735/356424630001743 Radiation: 356424630012724/356424630012740 for Sample 1 356424630014761/356424630014779 for Sample 2
HW Version	EV2
SW Version	qssi_64-userdebug 15 15-11-10.00-VG-U00-PRD-ERS-04 777 release-keys
MFD	13SEP2025
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT: Sample 1 without Scanner and Sample 2 with Scanner. According to the difference, we evaluated Sample 1 to perform full test and Sample 2 is verified the worse cases of Sample 1 for RSE test.

Specification of Accessory				
Battery	Brand Name	Zebra	Model	BT-000528

Supported Unit used in test configuration and system				
AC Adapter 1 (TYPE C Wall Charger 1)	Brand Name	Zebra	Part Number	PWR-WUA5V45W1US
Earphone 1 (Wired headset USB-C)	Brand Name	Zebra	Part Number	HDST-USBC-PTT 1-01
Earphone 2 (Rugged Bluetooth Headset)	Brand Name	Zebra	Part Number	HS3100-0TH
Earphone 3 (3.5mm PTT Headset)	Brand Name	Zebra	Part Number	HDST-35MM-PTT 1-02
Earphone 4 (Rugged Headset)	Brand Name	Zebra	Part Number	HS2100-0TH
Type C-Audio Cable (Type C to 3.5mm)	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm to 3.5mm audio connector	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
USB Cable 1 (USB-C to C Cable)	Brand Name	Zebra	Part Number	CBL-EC5X-USBC3A-01
USB Cable 3 (USB-C to C Cable)	Brand Name	Zebra	Part Number	CBL-TN28-USBC2C-01

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
SCS	15kHz
Antenna Gain	<Ant.8>: 0 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. 5G NR n26 support SA mode and NSA mode. According to the maximum power between SA and NSA mode, SA covers NSA mode.
2. All the supported ENDC combinations are verified conducted power, only the ENDC combination with highest power are shown in the report.
3. The EN-DC mode combination could be referred to the product spec.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Maximum Conducted Power and Emission Designator

5G NR n26		PI/2 BPSK/QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
5	816.5 ~ 821.5	0.2992	4M47G7D	0.2317	4M48W7D
10	819.0	0.2897	9M27G7D	0.2296	9M28W7D
15	821.5	0.2985	14M1G7D	0.2388	14M1W7D
20	824	0.2999	18M9G7D	0.2410	18M9W7D

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.5 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH02-SZ	CN1256	421272

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR 90(S)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 971168 D02 Misc Rev Approv License Devices v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)				Modulation					RB #			Test Channel		
		5	10	15	20	PI/2 BPSK	QPSK	16QAM	64 QAM	256 QAM	1	Half	Full	L	M	H
Max. Output Power	n26	v					v	v			v		v	v	v	v
			v	v	v	v	v	v	v	v	v		v		v	
26dB and 99% Bandwidth	n26	v	v	v	v		v	v	v	v			v		v	
Emission masks In-band emissions	n26	v				v	v				v		v	v		v
			v		v	v	v				v		v		v	
Emission masks – Out of band emissions	n26	v				v	v				v			v	v	v
			v		v	v	v				v				v	
Frequency Stability	n26				v		v						v		v	
Radiated Spurious Emission	n26	Worst Case												v	v	v
Note	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. Frequency Stability: Normal Voltage = 3.91V ; Low Voltage =3.5V.; High Voltage =4.45V															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 7.5 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 7.5 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

5G NR n26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	-	164800	-
	Frequency	-	824	-
15	Channel	-	164300	-
	Frequency	-	821.5	-
10	Channel	-	163800	-
	Frequency	-	819	-
5	Channel	163300	163800	164300
	Frequency	816.5	819	821.5

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor $10 \log (1\% \text{ of OBW/measured RBW})(\text{dB})$ was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.5.4 Test Setup


For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
4. battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Nov. 30, 2025	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Nov. 30, 2025	Dec. 27, 2025	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2025	Nov. 30, 2025	Oct. 23, 2027	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	Nov. 30, 2025	Jul. 04, 2026	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Nov. 30, 2025	Jul. 03, 2026	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 03, 2025	Nov. 30, 2025	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz~3GHz	Dec. 25, 2024	Nov. 30, 2025	Dec. 24, 2025	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 14, 2025	Nov. 30, 2025	Oct. 13, 2026	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 18, 2025	Nov. 30, 2025	Oct. 17, 2026	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Nov. 30, 2025	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Nov. 30, 2025	NCR	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Sep. 28, 2025~Nov. 24, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 24, 2024	Sep. 28, 2025~Nov. 24, 2025	Dec. 23, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 13, 2025	Sep. 28, 2025~Nov. 24, 2025	Oct. 12, 2026	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhagroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Sep. 28, 2025~Nov. 24, 2025	Jul. 01, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Peak to Average Ratio	± 1.34 dB
Frequency Stability	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Khan Zhen	Temperature :	22~23℃
		Relative Humidity :	40~42%



FR1 N26

Transmitter Conducted Output Power

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power (dBm)
26	15	5	163300	816.5	DFT-s-OFDM QPSK	12@6	24.59
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@1	24.76
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@23	24.74
26	15	5	163300	816.5	DFT-s-OFDM 16 QAM	12@6	23.4
26	15	5	163300	816.5	DFT-s-OFDM 16 QAM	1@1	23.61
26	15	5	163300	816.5	DFT-s-OFDM 16 QAM	1@23	23.61
26	15	5	163800	819	DFT-s-OFDM QPSK	12@6	24.57
26	15	5	163800	819	DFT-s-OFDM QPSK	1@1	24.74
26	15	5	163800	819	DFT-s-OFDM QPSK	1@23	24.64
26	15	5	163800	819	DFT-s-OFDM 16 QAM	12@6	23.38
26	15	5	163800	819	DFT-s-OFDM 16 QAM	1@1	23.65
26	15	5	163800	819	DFT-s-OFDM 16 QAM	1@23	23.56
26	15	5	164300	821.5	DFT-s-OFDM QPSK	12@6	24.42
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@1	24.67
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@23	24.64
26	15	5	164300	821.5	DFT-s-OFDM 16 QAM	12@6	23.28
26	15	5	164300	821.5	DFT-s-OFDM 16 QAM	1@1	23.53
26	15	5	164300	821.5	DFT-s-OFDM 16 QAM	1@23	23.56
26	15	10	163800	819	DFT-s-OFDM QPSK	25@12	24.55
26	15	10	163800	819	DFT-s-OFDM QPSK	1@1	24.62
26	15	10	163800	819	DFT-s-OFDM QPSK	1@50	24.59
26	15	10	163800	819	DFT-s-OFDM 16 QAM	25@12	23.49
26	15	10	163800	819	DFT-s-OFDM 16 QAM	1@1	23.61
26	15	10	163800	819	DFT-s-OFDM 16 QAM	1@50	23.55
26	15	15	164300	821.5	DFT-s-OFDM QPSK	36@18	24.66
26	15	15	164300	821.5	DFT-s-OFDM QPSK	1@1	24.75
26	15	15	164300	821.5	DFT-s-OFDM QPSK	1@77	24.67
26	15	15	164300	821.5	DFT-s-OFDM 16 QAM	36@18	23.52
26	15	15	164300	821.5	DFT-s-OFDM 16 QAM	1@1	23.71
26	15	15	164300	821.5	DFT-s-OFDM 16 QAM	1@77	23.78
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	50@25	24.62
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	1@1	24.57
26	15	20	164800	824	DFT-s-OFDM PI/2 BPSK	1@104	24.68
26	15	20	164800	824	DFT-s-OFDM QPSK	50@25	24.67
26	15	20	164800	824	DFT-s-OFDM QPSK	1@1	24.7
26	15	20	164800	824	DFT-s-OFDM QPSK	1@104	24.77
26	15	20	164800	824	DFT-s-OFDM 16 QAM	50@25	23.57



NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power (dBm)
26	15	20	164800	824	DFT-s-OFDM 16 QAM	1@1	23.7
26	15	20	164800	824	DFT-s-OFDM 16 QAM	1@104	23.82
26	15	20	164800	824	DFT-s-OFDM 64 QAM	50@25	22.1
26	15	20	164800	824	DFT-s-OFDM 64 QAM	1@1	22.32
26	15	20	164800	824	DFT-s-OFDM 64 QAM	1@104	22.49
26	15	20	164800	824	DFT-s-OFDM 256 QAM	50@25	20.08
26	15	20	164800	824	DFT-s-OFDM 256 QAM	1@1	19.86
26	15	20	164800	824	DFT-s-OFDM 256 QAM	1@104	19.94
26	15	20	164800	824	CP-OFDM QPSK	53@26	23.11
26	15	20	164800	824	CP-OFDM QPSK	1@1	23.13
26	15	20	164800	824	CP-OFDM QPSK	1@104	23.29



Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (Hz)	Verdict	Environment
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0062	PASS	NV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0024	PASS	LV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0013	PASS	HV
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0008	PASS	-30℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0005	PASS	-20℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0006	PASS	-10℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0004	PASS	0℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0023	PASS	10℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0000	PASS	20℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0005	PASS	30℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0016	PASS	40℃
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	0.0044	PASS	50℃



Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
26	15	5	163800	819.0	CP-OFDM QPSK	25@0	4.4748	5.036
26	15	5	163800	819.0	CP-OFDM 16 QAM	25@0	4.4788	5.174
26	15	5	163800	819.0	CP-OFDM 64 QAM	25@0	4.4686	4.994
26	15	5	163800	819.0	CP-OFDM 256 QAM	25@0	4.4826	4.979
26	15	10	163800	819.0	CP-OFDM QPSK	52@0	9.2723	10.07
26	15	10	163800	819.0	CP-OFDM 16 QAM	52@0	9.2802	9.978
26	15	10	163800	819.0	CP-OFDM 64 QAM	52@0	9.2518	9.832
26	15	10	163800	819.0	CP-OFDM 256 QAM	52@0	9.2801	9.965
26	15	15	164300	821.5	CP-OFDM QPSK	79@0	14.07	14.72
26	15	15	164300	821.5	CP-OFDM 16 QAM	79@0	14.069	14.82
26	15	15	164300	821.5	CP-OFDM 64 QAM	79@0	14.039	14.85
26	15	15	164300	821.5	CP-OFDM 256 QAM	79@0	14.064	14.72
26	15	20	164800	824.0	CP-OFDM QPSK	106@0	18.852	19.7
26	15	20	164800	824.0	CP-OFDM 16 QAM	106@0	18.861	19.82
26	15	20	164800	824.0	CP-OFDM 64 QAM	106@0	18.84	19.71
26	15	20	164800	824.0	CP-OFDM 256 QAM	106@0	18.878	19.81



N26(5M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N26(5M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N26(5M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N26(5M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH





N26(10M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N26(10M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N26(10M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N26(10M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N26(15M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N26(15M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N26(15M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH






N26(20M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N26(20M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH






Conducted Spurious Emissions

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	---
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	---
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	5	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	---
26	15	5	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	5	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	---
26	15	5	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@0	see graph	---
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@0	see graph	---
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	---
26	15	10	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	---
26	15	10	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	---
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	---
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	PASS



N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N26(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH






N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N26(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



N26(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N26(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH






N26(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N26(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH






Conducted Band Edge


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
26	15	5	163300	816.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	5	163300	816.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	5	163300	816.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
26	15	5	163300	816.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM BPSK	1@24	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM QPSK	1@24	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
26	15	5	164300	821.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM BPSK	1@51	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM QPSK	1@51	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM BPSK	50@0	see graph	PASS
26	15	10	163800	819.0	DFT-s-OFDM QPSK	50@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM BPSK	1@105	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM QPSK	1@105	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
26	15	20	164800	824.0	DFT-s-OFDM QPSK	100@0	see graph	PASS




N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH_CHP_PASS



N26(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N26(5M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH







N26(5M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH




N26(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH



N26(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH




N26(5M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH







N26(5M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH




N26(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N26(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N26(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_Mid_CH







N26(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_Mid_CH




N26(10M)_DFT-s-
OFDM_BPSK_Outer_Full_Mid_CH



N26(10M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH




N26(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH







N26(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N26(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_Mid_CH



N26(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_Mid_CH




N26(20M)_DFT-s-
OFDM_BPSK_Outer_Full_Mid_CH





N26(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH





Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Kuang Jia	Temperature :	22~25℃
		Relative Humidity :	48~52%

5G NR n26 SA / 5MHz / QPSK / Ant.8 for sample 1									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1628.4	-62.63	-13	-49.63	-72.12	-65.86	3.98	9.36	H
	2442.6	-61.85	-13	-48.85	-75.85	-65.40	4.85	10.55	H
	3256.8	-60.14	-13	-47.14	-76.51	-65.07	5.50	12.58	H
	1628.4	-61.32	-13	-48.32	-70.71	-64.55	3.98	9.36	V
	2442.6	-61.64	-13	-48.64	-75.62	-65.19	4.85	10.55	V
	3256.8	-60.55	-13	-47.55	-76.78	-65.48	5.50	12.58	V
Middle	1633.4	-62.53	-13	-49.53	-72.02	-65.78	4.00	9.40	H
	2450.1	-61.86	-13	-48.86	-75.86	-65.43	4.88	10.60	H
	3266.8	-60.53	-13	-47.53	-76.90	-65.46	5.52	12.60	H
	1633.4	-61.71	-13	-48.71	-71.10	-64.96	4.00	9.40	V
	2450.1	-61.69	-13	-48.69	-75.67	-65.26	4.88	10.60	V
	3266.8	-60.57	-13	-47.57	-76.80	-65.50	5.52	12.60	V
Highest	1638.4	-62.16	-13	-49.16	-71.67	-65.33	4.10	9.42	H
	2457.6	-60.94	-13	-47.94	-74.89	-64.52	4.90	10.63	H
	3276.8	-60.57	-13	-47.57	-76.77	-65.49	5.55	12.62	H
	1638.4	-61.75	-13	-48.75	-71.00	-64.92	4.10	9.42	V
	2457.6	-60.93	-13	-47.93	-74.85	-64.51	4.90	10.63	V
	3276.8	-60.09	-13	-47.09	-76.12	-65.01	5.55	12.62	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

5G NR n26 SA / 20MHz / QPSK / Ant.8 for sample 1									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1629	-63.03	-13	-50.03	-72.52	-66.28	4.00	9.40	H
	2443.5	-61.89	-13	-48.89	-75.89	-65.46	4.88	10.60	H
	3258	-60.20	-13	-47.20	-76.57	-65.13	5.52	12.60	H
	1629	-62.04	-13	-49.04	-71.43	-65.29	4.00	9.40	V
	2443.5	-60.36	-13	-47.36	-74.34	-63.93	4.88	10.60	V
	3258	-60.61	-13	-47.61	-76.84	-65.54	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



EN-DC_7A_n26A / LTE 10MHz + NR 5MHz / QPSK (ANT5+8) for sample 1									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n26 Low	1628.4	-66.01	-13	-53.01	-75.50	-69.24	3.98	9.36	H
	2442.6	-62.92	-13	-49.92	-76.92	-66.47	4.85	10.55	H
	3256.8	-61.15	-13	-48.15	-77.52	-66.08	5.50	12.58	H
	1628.4	-66.09	-13	-53.09	-75.48	-69.32	3.98	9.36	V
	2442.6	-63.19	-13	-50.19	-77.17	-66.74	4.85	10.55	V
	3256.8	-62.02	-13	-49.02	-78.25	-66.95	5.50	12.58	V
LTE Band7 Low	5061.00	-59.73	-25	-34.73	-81.49	-65.29	7.14	12.70	H
	7591.50	-55.43	-25	-30.43	-81.12	-58.73	8.30	11.60	H
	10122.00	-51.47	-25	-26.47	-81.62	-52.99	10.48	12.00	H
	5061.00	-59.24	-25	-34.24	-81.14	-64.80	7.14	12.70	V
	7591.50	-55.66	-25	-30.66	-81.3	-58.96	8.30	11.60	V
	10122.00	-52.87	-25	-27.87	-81.65	-54.39	10.48	12.00	V
NR n26 Middle	1633.4	-66.04	-13	-53.04	-75.53	-69.29	4.00	9.40	H
	2450.1	-62.54	-13	-49.54	-76.54	-66.11	4.88	10.60	H
	3266.8	-61.84	-13	-48.84	-78.21	-66.77	5.52	12.60	H
	1633.4	-65.96	-13	-52.96	-75.35	-69.21	4.00	9.40	V
	2450.1	-62.79	-13	-49.79	-76.77	-66.36	4.88	10.60	V
	3266.8	-61.97	-13	-48.97	-78.20	-66.90	5.52	12.60	V
LTE Band7 Middle	5061.00	-59.43	-25	-34.43	-81.19	-64.99	7.14	12.70	H
	7591.50	-55.67	-25	-30.67	-81.36	-58.97	8.30	11.60	H
	10122.00	-51.33	-25	-26.33	-81.48	-52.85	10.48	12.00	H
	5061.00	-58.62	-25	-33.62	-80.52	-64.18	7.14	12.70	V
	7591.50	-55.62	-25	-30.62	-81.26	-58.92	8.30	11.60	V
	10122.00	-52.60	-25	-27.60	-81.38	-54.12	10.48	12.00	V
NR n26 High	1638.4	-65.63	-13	-52.63	-75.14	-68.80	4.10	9.42	H
	2457.6	-63.02	-13	-50.02	-76.97	-66.60	4.90	10.63	H
	3276.8	-61.91	-13	-48.91	-78.11	-66.83	5.55	12.62	H
	1638.4	-66.33	-13	-53.33	-75.58	-69.50	4.10	9.42	V
	2457.6	-63.03	-13	-50.03	-76.95	-66.61	4.90	10.63	V
	3276.8	-62.19	-13	-49.19	-78.22	-67.11	5.55	12.62	V
LTE Band7 High	5061.00	-59.09	-25	-34.09	-80.85	-64.65	7.14	12.70	H
	7591.50	-55.58	-25	-30.58	-81.27	-58.88	8.30	11.60	H
	10122.00	-51.50	-25	-26.50	-81.65	-53.02	10.48	12.00	H
	5061.00	-59.53	-25	-34.53	-81.43	-65.09	7.14	12.70	V
	7591.50	-55.52	-25	-30.52	-81.16	-58.82	8.30	11.60	V
	10122.00	-52.96	-25	-27.96	-81.74	-54.48	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



EN-DC_7A_n26A / LTE 10MHz + NR 20MHz / QPSK (ANT5+8) for sample 1									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n26 Middle	1629	-65.76	-13	-52.76	-75.25	-69.01	4.00	9.40	H
	2443.5	-62.74	-13	-49.74	-76.74	-66.31	4.88	10.60	H
	3258	-61.90	-13	-48.90	-78.27	-66.83	5.52	12.60	H
	1629	-65.84	-13	-52.84	-75.23	-69.09	4.00	9.40	V
	2443.5	-63.11	-13	-50.11	-77.09	-66.68	4.88	10.60	V
	3258	-61.54	-13	-48.54	-77.77	-66.47	5.52	12.60	V
LTE Band7 Middle	5061.00	-59.13	-25	-34.13	-80.89	-64.69	7.14	12.70	H
	7591.50	-55.47	-25	-30.47	-81.16	-58.77	8.30	11.60	H
	10122.00	-51.57	-25	-26.57	-81.72	-53.09	10.48	12.00	H
	5061.00	-58.70	-25	-33.70	-80.6	-64.26	7.14	12.70	V
	7591.50	-55.45	-25	-30.45	-81.09	-58.75	8.30	11.60	V
	10122.00	-53.14	-25	-28.14	-81.92	-54.66	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



EN-DC_7A_n26A / LTE 10MHz + NR 5MHz / QPSK (ANT5+8) for sample 2									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n26 Low	1628.4	-66.05	-13	-53.05	-75.54	-69.28	3.98	9.36	H
	2442.6	-61.87	-13	-48.87	-75.87	-65.42	4.85	10.55	H
	3256.8	-61.79	-13	-48.79	-78.16	-66.72	5.50	12.58	H
	1628.4	-66.28	-13	-53.28	-75.67	-69.51	3.98	9.36	V
	2442.6	-59.10	-13	-46.10	-73.08	-62.65	4.85	10.55	V
	3256.8	-62.04	-13	-49.04	-78.27	-66.97	5.50	12.58	V
LTE Band7 Low	5002.00	-59.85	-25	-34.85	-81.74	-65.41	7.12	12.68	H
	7503.00	-56.35	-25	-31.35	-82.21	-59.68	8.26	11.59	H
	10004.00	-51.92	-25	-26.92	-82.15	-53.45	10.45	11.98	H
	5002.00	-59.92	-25	-34.92	-81.86	-65.48	7.12	12.68	V
	7503.00	-55.66	-25	-30.66	-81.51	-58.99	8.26	11.59	V
	10004.00	-53.87	-25	-28.87	-82.47	-55.40	10.45	11.98	V
NR n26 Middle	1633.4	-66.03	-13	-53.03	-75.52	-69.28	4.00	9.40	H
	2450.1	-62.33	-13	-49.33	-76.33	-65.90	4.88	10.60	H
	3266.8	-62.41	-13	-49.41	-78.78	-67.34	5.52	12.60	H
	1633.4	-66.29	-13	-53.29	-75.68	-69.54	4.00	9.40	V
	2450.1	-58.23	-13	-45.23	-72.21	-61.80	4.88	10.60	V
	3266.8	-62.41	-13	-49.41	-78.64	-67.34	5.52	12.60	V
LTE Band7 Middle	5052.00	-59.84	-25	-34.84	-81.64	-65.40	7.14	12.70	H
	7578.00	-55.63	-25	-30.63	-81.35	-58.93	8.30	11.60	H
	10104.00	-52.14	-25	-27.14	-82.31	-53.66	10.48	12.00	H
	5052.00	-59.43	-25	-34.43	-81.35	-64.99	7.14	12.70	V
	7578.00	-55.73	-25	-30.73	-81.41	-59.03	8.30	11.60	V
	10104.00	-53.50	-25	-28.50	-82.27	-55.02	10.48	12.00	V
NR n26 High	1638.4	-65.85	-13	-52.85	-75.36	-69.02	4.10	9.42	H
	2457.6	-63.09	-13	-50.09	-77.04	-66.67	4.90	10.63	H
	3276.8	-62.05	-13	-49.05	-78.25	-66.97	5.55	12.62	H
	1638.4	-66.20	-13	-53.20	-75.45	-69.37	4.10	9.42	V
	2457.6	-63.00	-13	-50.00	-76.92	-66.58	4.90	10.63	V
	3276.8	-62.75	-13	-49.75	-78.78	-67.67	5.55	12.62	V
LTE Band7 High	5102.00	-59.62	-25	-34.62	-81.33	-65.18	7.16	12.72	H
	7653.00	-55.52	-25	-30.52	-81.30	-58.82	8.33	11.63	H
	10204.00	-51.74	-25	-26.74	-81.85	-53.34	10.50	12.10	H
	5102.00	-59.57	-25	-34.57	-81.46	-65.13	7.16	12.72	V
	7653.00	-55.81	-25	-30.81	-81.51	-59.11	8.33	11.63	V
	10204.00	-52.27	-25	-27.27	-81.17	-53.87	10.50	12.10	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



EN-DC_7A_n26A / LTE 10MHz + NR 20MHz / QPSK (ANT5+8) for sample 2									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n26 Middle	1629	-65.96	-13	-52.96	-75.45	-69.21	4.00	9.40	H
	2443.5	-61.76	-13	-48.76	-75.76	-65.33	4.88	10.60	H
	3258	-62.51	-13	-49.51	-78.88	-67.44	5.52	12.60	H
	1629	-66.28	-13	-53.28	-75.67	-69.53	4.00	9.40	V
	2443.5	-59.10	-13	-46.10	-73.08	-62.67	4.88	10.60	V
	3258	-62.21	-13	-49.21	-78.44	-67.14	5.52	12.60	V
LTE Band7 Middle	5052.00	-59.70	-25	-34.70	-81.50	-65.26	7.14	12.70	H
	7578.00	-56.25	-25	-31.25	-81.97	-59.55	8.30	11.60	H
	10104.00	-51.80	-25	-26.80	-81.97	-53.32	10.48	12.00	H
	5052.00	-59.65	-25	-34.65	-81.57	-65.21	7.14	12.70	V
	7578.00	-56.31	-25	-31.31	-81.99	-59.61	8.30	11.60	V
	10104.00	-53.68	-25	-28.68	-82.45	-55.20	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.