



FCC RF Test Report

FCC ID : UZ7ET401EB
EQUIPMENT : Enterprise Tablet
BRAND NAME : Zebra
MODEL NAME : ET401EB
APPLICANT : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
MANUFACTURER : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Sep. 24, 2025 ~ Oct. 29, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Location	7
1.5 Test Software.....	7
1.6 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 6dB and 99% Bandwidth Measurement	14
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	18
3.6 AC Conducted Emission Measurement.....	22
3.7 Antenna Requirements.....	24
4 LIST OF MEASURING EQUIPMENT.....	25
5 MEASUREMENT UNCERTAINTY.....	26
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR591015B	Rev. 01	Initial issue of report	Dec. 31, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Conducted Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 30\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.74 dB at 2484.34 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.95 dB at 2.435 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Tablet
Brand Name	Zebra
Model Name	ET401EB
FCC ID	UZ7ET401EB
IMEI / SN Code	Conducted: 252165247E0038 for Sample 1 Conduction: 356424630012781/356424630012799 for Sample 1 Radiation: 356424630015008 for Sample 1 356424630012666 for Sample 2
HW Version	EV2
SW Version	qssi_64-userdebug 15 15-11-10.00-VG-U00-PRD-ERS-04 777 release-keys
MFD	13SEP2025
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT: Sample 1 without Scanner and Sample 2 with Scanner. According to the difference, Sample 1 was chose to perform full test and Sample 2 to verify the worst cases.

Specification of Accessory				
Battery	Brand Name	Zebra	Model	BT-000528

Supported Unit used in test configuration and system				
AC Adapter 1 (TYPE C Wall Charger 1)	Brand Name	Zebra	Part Number	PWR-WUA5V45W1US
Earphone 1 (Wired headset USB-C)	Brand Name	Zebra	Part Number	HDST-USBC-PTT 1-01
Earphone 2 (Rugged Bluetooth Headset)	Brand Name	Zebra	Part Number	HS3100-0TH
Earphone 3 (3.5mm PTT Headset)	Brand Name	Zebra	Part Number	HDST-35MM-PTT 1-02
Earphone 4 (Rugged Headset)	Brand Name	Zebra	Part Number	HS2100-0TH
Type C-Audio Cable Type C to 3.5mm	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm to 3.5mm audio connector	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
USB Cable 1 USB-C to C Cable	Brand Name	Zebra	Part Number	CBL-EC5X-USBC3A-01
USB Cable 3 USB-C to C Cable	Brand Name	Zebra	Part Number	CBL-TN28-USBC2C-01

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	BLE: 2402 MHz ~ 2480 MHz BLE CS GFSK: 2404 MHz ~ 2478 MHz
Number of Channels	BLE: 40 BLE CS GFSK: 72
Maximum Output Power to Antenna	SISO <Ant 6>: BLE 1Mbps: 8.56 dBm (0.0072 W) BLE 2Mbps: 8.58 dBm (0.0072 W) BLE 125Kbps: 8.42 dBm (0.0070 W) BLE 500Kbps: 8.33 dBm (0.0068 W) BLE CS GFSK 1Mbps: 7.94 dBm (0.0062 W) BLE CS GFSK 2Mbps: 8.02 dBm (0.0063 W) SISO <Ant 7>: BLE 1Mbps: 8.29 dBm (0.0067 W) BLE 2Mbps: 8.17 dBm (0.0066 W) BLE 125Kbps: 8.18 dBm (0.0066 W) BLE 500Kbps: 7.95 dBm (0.0062 W) BLE CS GFSK 1Mbps: 7.81 dBm (0.0060 W) BLE CS GFSK 2Mbps: 7.88 dBm (0.0061 W)
99% Occupied Bandwidth	SISO <Ant 6>: BLE 1Mbps:1.019MHz BLE 2Mbps:2.090MHz BLE 125Kbps: 1.035MHz BLE 500Kbps: 1.019MHz BLE CS GFSK 1Mbps: 1.023MHz BLE CS GFSK 2Mbps: 2.046MHz SISO <Ant 7>: BLE 1Mbps:1.015MHz BLE 2Mbps:2.030MHz BLE 125Kbps: 1.035MHz BLE 500Kbps: 1.015MHz BLE CS GFSK 1Mbps: 1.023MHz BLE CS GFSK 2Mbps: 2.042MHz
Antenna Type / Gain	<Ant 6> : IFA Antenna type with gain 0.72 dBi <Ant 7> : IFA Antenna type with gain 1.01 dBi
Type of Modulation	GFSK

Note:

1. CS: Channel Sounding
2. Bluetooth LE Mode is SISO mode only.
3. For BLE 125kbps, 500kbps, 1Mbps & 2Mbps mode, the whole testing has assessed BLE 1Mbps /2Mbps mode by referring to the higher conducted power.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.5 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
BLE	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
BLE CS GFSK	2	2404	29	2431	53	2455
	3	2405	30	2432	54	2456
	4	2406	31	2433	55	2457
	5	2407	32	2434	56	2458
	6	2408	33	2435	57	2459
	7	2409	34	2436	58	2460
	8	2410	35	2437	59	2461
	9	2411	36	2438	60	2462
	10	2412	37	2439	61	2463
	11	2413	38	2440	62	2464
	12	2414	39	2441	63	2465
	13	2415	40	2442	64	2466
	14	2416	41	2443	65	2467
	15	2417	42	2444	66	2468
	16	2418	43	2445	67	2469
	17	2419	44	2446	68	2470
	18	2420	45	2447	69	2471
	19	2421	46	2448	70	2472
	20	2422	47	2449	71	2473
	21	2423	48	2450	72	2474
	22	2424	49	2451	73	2475
	26	2428	50	2452	74	2476
	27	2429	51	2453	75	2477
	28	2430	52	2454	76	2478

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X / Y / Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
	Mode 7: Bluetooth Tx CH00_2402 MHz_BLE 125Kbps
	Mode 8: Bluetooth Tx CH19_2440 MHz_BLE 125Kbps
	Mode 9: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 10: Bluetooth Tx CH00_2402 MHz_BLE 500Kbps
	Mode 11: Bluetooth Tx CH19_2440 MHz_BLE 500Kbps
	Mode 12: Bluetooth Tx CH39_2480 MHz_BLE 500Kbps
	Mode 13: Bluetooth Tx CH02_2404 MHz_BLE CS GFSK_1Mbps
	Mode 14: Bluetooth Tx CH38_2440 MHz_BLE CS GFSK_1Mbps
	Mode 15: Bluetooth Tx CH76_2478 MHz_BLE CS GFSK_1Mbps
	Mode 16: Bluetooth Tx CH02_2404 MHz_BLE CS GFSK_2Mbps
	Mode 17: Bluetooth Tx CH38_2440 MHz_BLE CS GFSK_2Mbps
	Mode 18: Bluetooth Tx CH76_2478 MHz_BLE CS GFSK_2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps




	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps Mode 7: Bluetooth Tx CH02_2404 MHz_BLE CS GFSK_1Mbps Mode 8: Bluetooth Tx CH38_2440 MHz_BLE CS GFSK_1Mbps Mode 9: Bluetooth Tx CH76_2478 MHz_BLE CS GFSK_1Mbps Mode 10: Bluetooth Tx CH02_2404 MHz_BLE CS GFSK_2Mbps Mode 11: Bluetooth Tx CH38_2440 MHz_BLE CS GFSK_2Mbps Mode 12: Bluetooth Tx CH76_2478 MHz_BLE CS GFSK_2Mbps
AC Conducted Emission	Mode 1: WLAN 2.4G Link + Bluetooth Link + USB Cable 1 (CBL-EC5X-USBC3A-01) + AC Adapter 1 (PWR-WUA5V45W1US)
Remark: For Radiated Test Cases, the tests were performance with Adapter1 and USB Cable1.	

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
2.	SD Card	Kingston	8GB	N/A	N/A	N/A
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.11 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.11 + 20 = 22.11 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.8.1 for 6dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. Detector = Peak. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.1.2 PKPM1 Peak power meter or ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 11.11.3
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;Max 30dBm	Jul. 02, 2025	Sep. 24, 2025~Oct. 25, 2025	Jul. 01, 2026	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44G,MAX 30dB	Oct. 10, 2024	Sep. 24, 2025~Oct. 25, 2025	Oct. 10, 2025	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44G,MAX 30dB	Oct. 10, 2025		Oct. 10, 2026	Radiation (03CH05-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Sep. 24, 2025~Oct. 25, 2025	Aug. 09, 2026	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	Mar. 24, 2025	Sep. 24, 2025~Oct. 25, 2025	Mar. 23, 2026	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 14, 2025	Sep. 24, 2025~Oct. 25, 2025	Apr. 13, 2026	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Sep. 24, 2025~Oct. 25, 2025	Oct. 21, 2025	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 18, 2025		Oct. 19, 2026	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380827	9KHz~1GHz	Jul. 03, 2025	Sep. 24, 2025~Oct. 25, 2025	Jul. 02, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 02, 2025	Sep. 24, 2025~Oct. 25, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz~18Ghz	Jan. 02, 2025	Sep. 24, 2025~Oct. 25, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 02, 2025	Sep. 24, 2025~Oct. 25, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 24, 2025~Oct. 25, 2025	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Sep. 24, 2025~Oct. 25, 2025	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Sep. 24, 2025~Oct. 25, 2025	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Oct. 29, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Jul. 03, 2025	Oct. 29, 2025	Jul. 02, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Oct. 29, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Ouhan	APW-130NYT	202201040060	AC 0V~300V,45Hz~1000Hz	Apr. 16, 2025	Oct. 29, 2025	Apr. 15, 2026	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Oct. 24, 2025	Jul. 06, 2026	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2025	Oct. 24, 2025	Jan. 01, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2025	Oct. 24, 2025	Jan. 01, 2026	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.00 dB
Occupied Channel Bandwidth	±0.384%
Conducted Power	±0.90 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.18 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.88 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.36 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2025.10.24

Test Engineer: Jiang Jun

<BLE>


DTS Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant6	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant7	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant6	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant7	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant6	2480	0.68	2479.66	2480.34	0.5	PASS
	Ant7	2480	0.68	2479.66	2480.34	0.5	PASS
BLE_2M	Ant6	2402	1.16	2401.42	2402.58	0.5	PASS
	Ant7	2402	1.16	2401.42	2402.58	0.5	PASS
	Ant6	2440	1.16	2439.42	2440.58	0.5	PASS
	Ant7	2440	1.17	2439.42	2440.59	0.5	PASS
	Ant6	2480	1.17	2479.42	2480.58	0.5	PASS
	Ant7	2480	1.16	2479.42	2480.58	0.5	PASS
BLE_125K	Ant6	2402	0.61	2401.69	2402.30	0.5	PASS
	Ant7	2402	0.61	2401.70	2402.31	0.5	PASS
	Ant6	2440	0.62	2439.69	2440.31	0.5	PASS
	Ant7	2440	0.61	2439.70	2440.31	0.5	PASS
	Ant6	2480	0.61	2479.69	2480.30	0.5	PASS
	Ant7	2480	0.61	2479.70	2480.31	0.5	PASS
BLE_500K	Ant6	2402	0.66	2401.68	2402.34	0.5	PASS
	Ant7	2402	0.66	2401.68	2402.34	0.5	PASS
	Ant6	2440	0.66	2439.68	2440.34	0.5	PASS
	Ant7	2440	0.66	2439.68	2440.34	0.5	PASS
	Ant6	2480	0.66	2479.68	2480.34	0.5	PASS
	Ant7	2480	0.66	2479.68	2480.34	0.5	PASS





Test Graphs


















BLE_125K_Ant6_2402





Date: 24.OCT.2025 13:47:01


BLE_125K_Ant7_2402





Date: 24.OCT.2025 14:47:35














Occupied Channel Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant6	2402	1.019	2401.4965	2402.5155	---	---
	Ant7	2402	1.011	2401.5005	2402.5115	---	---
	Ant6	2440	1.019	2439.4965	2440.5155	---	---
	Ant7	2440	1.015	2439.4965	2440.5115	---	---
	Ant6	2480	1.015	2479.4965	2480.5115	---	---
	Ant7	2480	1.015	2479.4965	2480.5115	---	---
BLE_2M	Ant6	2402	2.034	2401.0010	2403.0350	---	---
	Ant7	2402	2.030	2401.0050	2403.0350	---	---
	Ant6	2440	2.030	2439.0010	2441.0310	---	---
	Ant7	2440	2.030	2439.0050	2441.0350	---	---
	Ant6	2480	2.090	2478.9411	2481.0310	---	---
	Ant7	2480	2.030	2479.0010	2481.0310	---	---
BLE_125K	Ant6	2402	1.035	2401.4805	2402.5155	---	---
	Ant7	2402	1.031	2401.4845	2402.5155	---	---
	Ant6	2440	1.035	2439.4805	2440.5155	---	---
	Ant7	2440	1.031	2439.4845	2440.5155	---	---
	Ant6	2480	1.035	2479.4805	2480.5155	---	---
	Ant7	2480	1.035	2479.4805	2480.5155	---	---
BLE_500K	Ant6	2402	1.015	2401.4965	2402.5115	---	---
	Ant7	2402	1.015	2401.4965	2402.5115	---	---
	Ant6	2440	1.019	2439.4925	2440.5115	---	---
	Ant7	2440	1.015	2439.4965	2440.5115	---	---
	Ant6	2480	1.019	2479.4925	2480.5115	---	---
	Ant7	2480	1.015	2479.4965	2480.5115	---	---





Test Graphs


































Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail	Power Setting
BLE1M	Ant 6	0	8.59	30.00	0.72	9.31	36.00	Pass	Default
		19	8.50	30.00	0.72	9.22	36.00	Pass	Default
		39	8.37	30.00	0.72	9.09	36.00	Pass	Default
BLE2M	Ant 6	0	8.67	30.00	0.72	9.39	36.00	Pass	Default
		19	8.54	30.00	0.72	9.26	36.00	Pass	Default
		39	8.44	30.00	0.72	9.16	36.00	Pass	Default
BLE125K	Ant 6	0	8.57	30.00	0.72	9.29	36.00	Pass	Default
		19	8.47	30.00	0.72	9.19	36.00	Pass	Default
		39	8.34	30.00	0.72	9.06	36.00	Pass	Default
BLE500K	Ant 6	0	8.53	30.00	0.72	9.25	36.00	Pass	Default
		19	8.46	30.00	0.72	9.18	36.00	Pass	Default
		39	8.22	30.00	0.72	8.94	36.00	Pass	Default
BLE1M	Ant 7	0	8.32	30.00	1.01	9.33	36.00	Pass	Default
		19	8.35	30.00	1.01	9.36	36.00	Pass	Default
		39	8.18	30.00	1.01	9.19	36.00	Pass	Default
BLE2M	Ant 7	0	8.29	30.00	1.01	9.30	36.00	Pass	Default
		19	8.32	30.00	1.01	9.33	36.00	Pass	Default
		39	8.21	30.00	1.01	9.22	36.00	Pass	Default
BLE125K	Ant 7	0	8.28	30.00	1.01	9.29	36.00	Pass	Default
		19	8.30	30.00	1.01	9.31	36.00	Pass	Default
		39	8.14	30.00	1.01	9.15	36.00	Pass	Default
BLE500K	Ant 7	0	8.27	30.00	1.01	9.28	36.00	Pass	Default
		19	8.29	30.00	1.01	9.30	36.00	Pass	Default
		39	8.15	30.00	1.01	9.16	36.00	Pass	Default



Test Result Average

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail	Power Setting
BLE1M	Ant 6	0	2.04	8.56	30.00	0.72	9.28	36.00	Pass	Default
		19	2.04	8.40	30.00	0.72	9.12	36.00	Pass	Default
		39	2.04	8.33	30.00	0.72	9.05	36.00	Pass	Default
BLE2M	Ant 6	0	4.83	8.58	30.00	0.72	9.30	36.00	Pass	Default
		19	4.83	8.45	30.00	0.72	9.17	36.00	Pass	Default
		39	4.83	8.38	30.00	0.72	9.10	36.00	Pass	Default
BLE125K	Ant 6	0	0.84	8.42	30.00	0.72	9.14	36.00	Pass	Default
		19	0.84	8.31	30.00	0.72	9.03	36.00	Pass	Default
		39	0.84	8.23	30.00	0.72	8.95	36.00	Pass	Default
BLE500K	Ant 6	0	2.47	8.33	30.00	0.72	9.05	36.00	Pass	Default
		19	2.47	8.20	30.00	0.72	8.92	36.00	Pass	Default
		39	2.47	8.15	30.00	0.72	8.87	36.00	Pass	Default
BLE1M	Ant 7	0	2.04	8.26	30.00	1.01	9.27	36.00	Pass	Default
		19	2.04	8.29	30.00	1.01	9.30	36.00	Pass	Default
		39	2.04	8.15	30.00	1.01	9.16	36.00	Pass	Default
BLE2M	Ant 7	0	4.83	8.07	30.00	1.01	9.08	36.00	Pass	Default
		19	4.83	8.17	30.00	1.01	9.18	36.00	Pass	Default
		39	4.83	8.12	30.00	1.01	9.13	36.00	Pass	Default
BLE125K	Ant 7	0	0.84	8.18	30.00	1.01	9.19	36.00	Pass	Default
		19	0.84	8.15	30.00	1.01	9.16	36.00	Pass	Default
		39	0.84	8.01	30.00	1.01	9.02	36.00	Pass	Default
BLE500K	Ant 7	0	2.44	7.93	30.00	1.01	8.94	36.00	Pass	Default
		19	2.44	7.95	30.00	1.01	8.96	36.00	Pass	Default
		39	2.44	7.83	30.00	1.01	8.84	36.00	Pass	Default




Maximum power spectral density


Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant6	2402	-6.79	≤8.00	PASS
	Ant7	2402	-7.18	≤8.00	PASS
	Ant6	2440	-7.16	≤8.00	PASS
	Ant7	2440	-7.39	≤8.00	PASS
	Ant6	2480	-7.41	≤8.00	PASS
	Ant7	2480	-7.83	≤8.00	PASS
BLE_2M	Ant6	2402	-9.16	≤8.00	PASS
	Ant7	2402	-9.52	≤8.00	PASS
	Ant6	2440	-9.50	≤8.00	PASS
	Ant7	2440	-9.74	≤8.00	PASS
	Ant6	2480	-9.78	≤8.00	PASS
	Ant7	2480	-10.16	≤8.00	PASS
BLE_125K	Ant6	2402	2.12	≤8.00	PASS
	Ant7	2402	1.81	≤8.00	PASS
	Ant6	2440	1.69	≤8.00	PASS
	Ant7	2440	1.53	≤8.00	PASS
	Ant6	2480	1.43	≤8.00	PASS
	Ant7	2480	1.09	≤8.00	PASS
BLE_500K	Ant6	2402	2.00	≤8.00	PASS
	Ant7	2402	1.58	≤8.00	PASS
	Ant6	2440	1.57	≤8.00	PASS
	Ant7	2440	1.32	≤8.00	PASS
	Ant6	2480	1.27	≤8.00	PASS
	Ant7	2480	0.93	≤8.00	PASS





Test Graphs


































Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant6	2402	2402.02	7.74
	Ant7	2402	2402.02	7.40
	Ant6	2440	2440.02	7.35
	Ant7	2440	2440.02	7.12
	Ant6	2480	2480.02	7.07
	Ant7	2480	2480.02	6.69
BLE_2M	Ant6	2402	2402.02	7.71
	Ant7	2402	2402.02	7.35
	Ant6	2440	2440.02	7.32
	Ant7	2440	2440.02	7.10
	Ant6	2480	2480.02	7.06
	Ant7	2480	2480.02	6.69
BLE_125K	Ant6	2402	2402.01	7.53
	Ant7	2402	2402.01	7.23
	Ant6	2440	2440.00	7.13
	Ant7	2440	2440.01	6.98
	Ant6	2480	2480.00	6.87
	Ant7	2480	2480.01	6.55
BLE_500K	Ant6	2402	2401.75	8.20
	Ant7	2402	2401.75	7.87
	Ant6	2440	2439.75	7.82
	Ant7	2440	2439.75	7.63
	Ant6	2480	2479.75	7.57
	Ant7	2480	2479.75	7.23



Test Graphs



















