


RF Exposure Evaluation Report

APPLICANT : Zebra Technologies Corporation
EQUIPMENT : ETHERNET CRADLE
BRAND NAME : Zebra
MODEL NAME : STB3574
FCC ID : UZ7STB3574
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	5
4. RF EXPOSURE LIMIT INTRODUCTION	6
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	7
5.1. Standalone Power Density Calculation	7



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA5N2514	Rev. 01	Initial issue of report	Feb. 17, 2016

**1. Administration Data****1.1. Testing Laboratory**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Zebra Technologies Corporation
Address	1 Zebra Plaza, Holtsville, NY 11742

Manufacturer	
Company Name	Zebra Technologies Corporation
Address	1 Zebra Plaza, Holtsville, NY 11742



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	ETHERNET CRADLE
Brand Name	Zebra
Model Name	STB3574
MFD	09Dec15
FCC ID	UZ7STB3574
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	· Bluetooth v2.1
Antenna Type	SMD Antenna
HW Version	Rev A
SW Version	Rev A
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF average output power among production units

Mode / Band	Average Power (dBm)		
	1Mbps (GFSK)	2Mbps ($\pi/4$ -DQPSK)	3Mbps (8-DPSK)
Bluetooth	6	6	6



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2412.0	2.5	6.0	8.500	0.007	7.079	0.001	1.000

Note: For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.