



FCC RADIO TEST REPORT

FCC ID : UZ7TC530R
Equipment : Touch Computer
Brand Name : Zebra
Model Name : TC530R
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart E §15.407

The product was received on May 09, 2024 and testing was performed from May 21, 2024 to Jul. 05, 2024. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	8
1.4 Testing Location	9
1.5 Applicable Standards.....	9
2 Test Configuration of Equipment Under Test	10
2.1 Carrier Frequency and Channel	10
2.2 Test Mode.....	11
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	14
2.6 Measurement Results Explanation Example.....	14
3 Test Result	15
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	15
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement	19
3.5 AC Conducted Emission Measurement.....	24
3.6 Antenna Requirements.....	26
4 List of Measuring Equipment.....	27
5 Measurement Uncertainty	29
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR430824F	01	Initial issue of report	Jul. 17, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	1.31 dB under the limit at 5635.80 MHz
3.5	15.207	AC Conducted Emission	Pass	18.15 dB under the limit at 3.23 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen

Report Producer: Rebecca Wu



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Touch Computer
Brand Name	Zebra
Model Name	TC530R
FCC ID	UZ7TC530R
EUT supports Radios application	NFC/UHF RFID WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	DV2-2
SW Version	nemesis_A13_userdebug_nonGMS_RelKey_2024-05-25-041 2_main_SE
FW Version	FUSION_QA_6_1.3.0.001_T
MFD	23APR24
EUT Stage	Identical Prototype

Remark: The EUT's information above is declared by manufacturer.

Specification of Accessories				
Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
Battery 1 (1x)	Brand Name	Zebra	Part Number	BT-000442-0020
Battery 2 (1.5x)	Brand Name	Zebra	Part Number	BT-000442-0820
Battery 3 (BLE Battery)	Brand Name	Zebra	Part Number	BT-000442-002B
Battery 4 (Wireless Battery)	Brand Name	Zebra	Part Number	BT-000442-002A
Battery 5 (1x)	Brand Name	Zebra	Part Number	BT-000442-1020
USB TYPE A to TYPE C cable	Brand Name	Zebra	Part Number	CBL-TC5X-USBC2A-01
USB TYPE C to 3.5mm audio connector	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm Earphone	Brand Name	Zebra	Part Number	HDST-35MM-PTT1-01
Rugged Headset	Brand Name	Zebra	Part Number	HS2100-OTH
USB TYPE C Earphone	Brand Name	Zebra	Part Number	HDST-USBC-PTT1-01
Trigger Handle	Brand Name	Zebra	Part Number	TRG-NGTC5-ELEC-01
Soft Holster	Brand Name	Zebra	Part Number	SG-NGTC5TC7-HLSTR-01
TC53/TC58 RUGGED BOOT	Brand Name	Zebra	Part Number	SG-NGTC5EXO1-01

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard			
Tx/Rx Frequency Range	5745 MHz ~ 5825 MHz		
Maximum Output Power to Antenna	MIMO <Ant. 6+7> 802.11a: 24.16 dBm / 0.2570 W 802.11n HT20: 23.96 dBm / 0.2489 W 802.11n HT40: 24.01 dBm / 0.2518 W 802.11ac VHT20: 24.06 dBm / 0.2547 W 802.11ac VHT40: 24.11 dBm / 0.2576 W 802.11ac VHT80: 23.06 dBm / 0.2023 W 802.11ax HE20: 24.16 dBm / 0.2606 W 802.11ax HE40: 24.21 dBm / 0.2636 W 802.11ax HE80: 23.16 dBm / 0.2070 W		
99% Occupied Bandwidth	<Ant. 6> 802.11a: 16.48 MHz 802.11ac VHT20: 17.68 MHz 802.11ac VHT40: 36.36 MHz 802.11ac VHT80: 75.40 MHz 802.11ax HE20: 19.03 MHz 802.11ax HE40: 38.16 MHz 802.11ax HE80: 77.44 MHz <Ant. 7> 802.11a: 16.78 MHz 802.11ac VHT20: 17.93 MHz 802.11ac VHT40: 36.76 MHz 802.11ac VHT80: 75.64 MHz 802.11ax HE20: 19.18 MHz 802.11ax HE40: 38.36 MHz 802.11ax HE80: 77.44 MHz		
Antenna Type / Gain	<Ant. 6> : PIFA Antenna with gain 3.76 dBi <Ant. 7> : PIFA Antenna with gain 3.68 dBi		
Type of Modulation	802.11a/n: OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM) 802.11ax: OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)		
Antenna Function Description		Ant. 6	Ant. 7
	802.11a/n/ac/ax MIMO	V	V
	802.11ax TXBF	V	V

Remark:

1. MIMO Ant. 6+7 Directional Gain is a calculated result from MIMO Ant. 6 and MIMO Ant. 7. The formula used in calculation is documented in section 1.2.1.
2. Power of MIMO Ant. 6 + Ant. 7 is a calculated result from sum of the power MIMO Ant. 6 and MIMO Ant. 7.
3. 802.11ax Support Tx Beamforming mode, and the manufacturer declares that Tx Beamforming power/EIRP is less than CDD mode 3dbm, so CDD mode cover Tx Beamforming mode.
4. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ dBi

Where $G1, G2, \dots, GN$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for	DG for	Power Limit	PSD Limit
	Ant 6	Ant 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.76	3.68	3.76	6.73	0.00	0.73

Calculation example:

If a device has two antenna, $G_{ANT6} = 3.76$ dBi; $G_{ANT7} = 3.68$ dBi

Directional gain of power measurement = $\max(3.76, 3.68) + 0 = 3.76$ dBi

Directional gain of PSD derived from formula which is

$10 \times \log \{ [10^{(3.76 \text{ dBi} / 20)} + 10^{(3.68 \text{ dBi} / 20)}]^2 / 2 \}$

= 6.73 dBi

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)

<TXBF Modes>

The EUT supports beamforming modes , then

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)e)ii)

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The directional gain “DG” is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 6	Ant 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.76	3.68	6.73	6.73	0.73	0.73

Calculation example:

Directional gain is derived from formula which is

$$10 \times \log \{ \{ [10^{\wedge} (3.76 \text{ dBi} / 20) + 10^{\wedge} (3.68 \text{ dBi} / 20)]^{\wedge} 2 \} / 2 \}$$

$$= 6.73 \text{ dBi}$$

$$\text{Power and PSD limit reduction} = \text{Composite gain} - 6\text{dBi, (min = 0)}$$

1.3 Modification of EUT

No modifications made to the EUT during the testing.



1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH02-HY, CO05-HY, 03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151 [*]	5755	159 [*]	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel with "^{*}" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.


Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + USB TYPE A to TYPE C Cable (Charging from Adapter) + Battery 2 (1.5x)
Remark: For Radiated Test Cases, the tests were performed with Battery 1(1x).	

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11ax HE20	802.11ax HE40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-


Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Jlab	Jbuds Mini	2AHYV	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility "QRCT Version 4.0.211.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300kHz.
 - Set VBW $\geq$ 1 MHz.
 - Add $10 \log(500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
 - Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.


6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



**3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 22, 2024	Jun. 03, 2024~Jul. 05, 2024	Apr. 21, 2025	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Feb. 23, 2024	Jun. 03, 2024~Jul. 05, 2024	Feb. 22, 2025	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00075962	1GHz ~ 18GHz	Nov. 27, 2023	Jun. 03, 2024~Jul. 05, 2024	Nov. 26, 2024	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 02, 2023	Jun. 03, 2024~Jul. 05, 2024	Oct. 01, 2024	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 19, 2024	Jun. 03, 2024~Jul. 05, 2024	Apr. 18, 2025	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Mar. 23, 2024	Jun. 03, 2024~Jul. 05, 2024	Mar. 22, 2025	Radiation (03CH07-HY)
Preamplifier	EMEC	EM18G40G	0600789	18-40GHz	Jul. 25, 2023	Jun. 03, 2024~Jul. 05, 2024	Jul. 24, 2024	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Mar. 26, 2024	Jun. 03, 2024~Jul. 05, 2024	Mar. 25, 2025	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz to 18GHz	Feb. 21, 2024	Jun. 03, 2024~Jul. 05, 2024	Feb. 20, 2025	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4	9kHz to 30MHz	Feb. 21, 2024	Jun. 03, 2024~Jul. 05, 2024	Feb. 20, 2025	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126	532078/126E	30MHz~18GHz	Sep. 15, 2023	Jun. 03, 2024~Jul. 05, 2024	Sep. 14, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 21, 2024	Jun. 03, 2024~Jul. 05, 2024	Feb. 20, 2025	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 22, 2024	Jun. 03, 2024~Jul. 05, 2024	Apr. 21, 2025	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Jun. 03, 2024~Jul. 05, 2024	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Jun. 03, 2024~Jul. 05, 2024	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Jun. 03, 2024~Jul. 05, 2024	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jun. 03, 2024~Jul. 05, 2024	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Jun. 03, 2024~Jul. 05, 2024	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Mar. 01, 2024	Jun. 03, 2024~Jul. 05, 2024	Feb. 28, 2025	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz~40GHz	Nov. 24, 2023	Jun. 03, 2024~Jul. 05, 2024	Nov. 23, 2024	Radiation (03CH07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	May 21, 2024~Jul. 01, 2024	Nov. 06, 2024	Conducted (TH02-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 36 (NO:35_144)	10MHz~6GHz	Aug. 23, 2023	May 21, 2024~Jul. 01, 2024	Aug. 22, 2024	Conducted (TH02-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101564	10Hz ~ 40GHz	Sep. 12, 2023	May 21, 2024~Jul. 01, 2024	Sep. 11, 2024	Conducted (TH02-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 19, 2024	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 06, 2023	Jun. 19, 2024	Dec. 05, 2024	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 26, 2023	Jun. 19, 2024	Oct. 25, 2024	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 08, 2023	Jun. 19, 2024	Dec. 07, 2024	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 22, 2023	Jun. 19, 2024	Nov. 21, 2024	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jun. 19, 2024	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 28, 2023	Jun. 19, 2024	Jul. 27, 2024	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 28, 2023	Jun. 19, 2024	Dec. 27, 2024	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sylvia Li and Mina Liu	Temperature:	21~25	°C
Test Date:	2024/05/21 ~ 2024/07/01	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	149	5745	16.48	16.78	20.60	24.21	16.27	16.29	0.5	Pass
11a	6Mbps	2	157	5785	16.48	16.58	20.75	21.86	16.30	16.06	0.5	Pass
11a	6Mbps	2	165	5825	16.48	16.63	20.61	25.66	16.27	16.06	0.5	Pass
VHT20	MCS0	2	149	5745	17.68	17.88	22.02	24.97	17.53	16.30	0.5	Pass
VHT20	MCS0	2	157	5785	17.68	17.93	21.71	23.32	16.52	16.64	0.5	Pass
VHT20	MCS0	2	165	5825	17.68	17.78	20.93	23.38	16.06	16.52	0.5	Pass
VHT40	MCS0	2	151	5755	36.36	36.46	41.92	42.14	36.04	35.69	0.5	Pass
VHT40	MCS0	2	159	5795	36.36	36.76	41.38	43.18	36.03	35.94	0.5	Pass
VHT80	MCS0	2	155	5775	75.40	75.64	82.37	86.72	75.12	75.12	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	21.00	21.10	24.06	30.00		3.76		Pass
11a	6Mbps	2	157	5785	21.20	21.10	24.16	30.00		3.76		Pass
11a	6Mbps	2	165	5825	21.20	21.00	24.11	30.00		3.76		Pass
HT20	MCS0	2	149	5745	21.00	20.90	23.96	30.00		3.76		Pass
HT20	MCS0	2	157	5785	21.10	20.80	23.96	30.00		3.76		Pass
HT20	MCS0	2	165	5825	21.00	20.80	23.91	30.00		3.76		Pass
HT40	MCS0	2	151	5755	20.90	20.50	23.71	30.00		3.76		Pass
HT40	MCS0	2	159	5795	21.00	21.00	24.01	30.00		3.76		Pass
VHT20	MCS0	2	149	5745	21.10	21.00	24.06	30.00		3.76		Pass
VHT20	MCS0	2	157	5785	21.20	20.90	24.06	30.00		3.76		Pass
VHT20	MCS0	2	165	5825	21.10	20.90	24.01	30.00		3.76		Pass
VHT40	MCS0	2	151	5755	21.00	20.60	23.81	30.00		3.76		Pass
VHT40	MCS0	2	159	5795	21.10	21.10	24.11	30.00		3.76		Pass
VHT80	MCS0	2	155	5775	20.10	20.00	23.06	30.00		3.76		Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 MIMO																
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	0.65	0.65	2.22	5.71	6.21	9.22	29.27		6.73		Pass	
11a	6Mbps	2	157	5785	0.65	0.65	2.22	5.61	5.97	8.98	29.27		6.73		Pass	
11a	6Mbps	2	165	5825	0.65	0.65	2.22	5.33	5.89	8.90	29.27		6.73		Pass	
VHT20	MCS0	2	149	5745	0.66	0.65	2.22	5.27	5.34	8.35	29.27		6.73		Pass	
VHT20	MCS0	2	157	5785	0.66	0.65	2.22	4.92	4.94	7.95	29.27		6.73		Pass	
VHT20	MCS0	2	165	5825	0.66	0.65	2.22	5.42	5.38	8.43	29.27		6.73		Pass	
VHT40	MCS0	2	151	5755	0.66	0.66	2.22	3.36	2.93	6.37	29.27		6.73		Pass	
VHT40	MCS0	2	159	5795	0.66	0.66	2.22	3.09	3.02	6.10	29.27		6.73		Pass	
VHT80	MCS0	2	155	5775	0.64	0.64	2.22	-1.21	-1.05	1.96	29.27		6.73		Pass	

Note: PSD Sum = Max PSD(Ant. 6, Ant. 7) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
HE20	MCS0	2	149	5745	Full	18.98	19.13	21.52	30.34	18.38	18.27	0.5	Pass
HE20	MCS0	2	157	5785	Full	18.93	19.18	22.09	29.62	18.87	18.25	0.5	Pass
HE20	MCS0	2	165	5825	Full	19.03	19.13	23.24	30.64	18.73	18.70	0.5	Pass
HE40	MCS0	2	151	5755	Full	37.96	38.16	41.55	47.97	36.72	36.66	0.5	Pass
HE40	MCS0	2	159	5795	Full	38.16	38.36	54.88	63.81	37.14	36.73	0.5	Pass
HE80	MCS0	2	155	5775	Full	77.44	77.44	83.65	87.68	75.94	75.14	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	21.20	21.10	24.16	30.00		3.76		Pass
HE20	MCS0	2	149	5745	26/0	10.00	10.20	13.11	30.00		3.76		Pass
HE20	MCS0	2	149	5745	52/37	13.50	14.00	16.77	30.00		3.76		Pass
HE20	MCS0	2	149	5745	106/53	16.40	16.40	19.41	30.00		3.76		Pass
HE20	MCS0	2	157	5785	Full	21.30	21.00	24.16	30.00		3.76		Pass
HE20	MCS0	2	157	5785	26/4	11.40	11.50	14.46	30.00		3.76		Pass
HE20	MCS0	2	157	5785	52/38	14.20	14.00	17.11	30.00		3.76		Pass
HE20	MCS0	2	157	5785	106/53	17.00	16.80	19.91	30.00		3.76		Pass
HE20	MCS0	2	165	5825	Full	21.20	21.00	24.11	30.00		3.76		Pass
HE20	MCS0	2	165	5825	26/8	11.60	11.40	14.51	30.00		3.76		Pass
HE20	MCS0	2	165	5825	52/40	14.40	14.20	17.31	30.00		3.76		Pass
HE20	MCS0	2	165	5825	106/54	17.10	16.90	20.01	30.00		3.76		Pass
HE40	MCS0	2	151	5755	Full	21.10	20.70	23.91	30.00		3.76		Pass
HE40	MCS0	2	151	5755	242/61	17.90	17.40	20.67	30.00		3.76		Pass
HE40	MCS0	2	159	5795	Full	21.20	21.20	24.21	30.00		3.76		Pass
HE40	MCS0	2	159	5795	242/62	18.00	17.60	20.81	30.00		3.76		Pass
HE80	MCS0	2	155	5775	Full	20.20	20.10	23.16	30.00		3.76		Pass
HE80	MCS0	2	155	5775	484/65	16.80	16.60	19.71	30.00		3.76		Pass
HE80	MCS0	2	155	5775	484/66	16.80	16.30	19.57	30.00		3.76		Pass

TEST RESULTS DATA
Power Spectral Density


U-NII-3 MIMO																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	0.65	0.67	2.22		5.14	5.44	8.45	29.27		6.73		Pass
HE20	MCS0	2	149	5745	26/0	0.63	0.62	2.22		4.18	4.39	7.40	29.27		6.73		Pass
HE20	MCS0	2	149	5745	52/37	0.65	0.64	2.22		4.59	5.31	8.32	29.27		6.73		Pass
HE20	MCS0	2	149	5745	106/53	0.68	0.67	2.22		4.62	5.11	8.12	29.27		6.73		Pass
HE20	MCS0	2	157	5785	Full	0.65	0.67	2.22		5.03	5.23	8.24	29.27		6.73		Pass
HE20	MCS0	2	157	5785	26/4	0.63	0.62	2.22		4.76	5.17	8.18	29.27		6.73		Pass
HE20	MCS0	2	157	5785	52/38	0.65	0.64	2.22		4.98	4.87	7.99	29.27		6.73		Pass
HE20	MCS0	2	157	5785	106/53	0.68	0.67	2.22		4.92	5.20	8.21	29.27		6.73		Pass
HE20	MCS0	2	165	5825	Full	0.65	0.67	2.22		5.35	5.57	8.58	29.27		6.73		Pass
HE20	MCS0	2	165	5825	26/8	0.63	0.62	2.22		5.31	5.35	8.36	29.27		6.73		Pass
HE20	MCS0	2	165	5825	52/40	0.65	0.64	2.22		5.22	5.15	8.23	29.27		6.73		Pass
HE20	MCS0	2	165	5825	106/54	0.68	0.67	2.22		5.07	5.06	8.08	29.27		6.73		Pass
HE40	MCS0	2	151	5755	Full	0.68	0.66	2.22		2.59	2.61	5.62	29.27		6.73		Pass
HE40	MCS0	2	151	5755	242/61	0.69	0.67	2.22		2.59	2.58	5.60	29.27		6.73		Pass
HE40	MCS0	2	159	5795	Full	0.68	0.66	2.22		2.76	2.75	5.77	29.27		6.73		Pass
HE40	MCS0	2	159	5795	242/62	0.69	0.67	2.22		2.52	2.46	5.53	29.27		6.73		Pass
HE80	MCS0	2	155	5775	Full	0.68	0.68	2.22		-1.52	-1.36	1.65	29.27		6.73		Pass
HE80	MCS0	2	155	5775	484/65	0.66	0.66	2.22		-1.57	-1.41	1.60	29.27		6.73		Pass
HE80	MCS0	2	155	5775	484/66	0.66	0.66	2.22		-1.66	-1.74	1.35	29.27		6.73		Pass

Note: PSD Sum = Max PSD(Ant. 6, Ant. 7) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**


MIMO <Ant. 6+7>

<802.11a>






<802.11ac VHT20>






<802.11ac VHT40>






<802.11ac VHT80>






<802.11ax HE20>






<802.11ax HE40>






<802.11ax HE80>




Test Result of Power Spectral Density

<802.11a>




<802.11ac VHT20>






<802.11ac VHT40>




<802.11ac VHT80>






<802.11ax HE20>



<802.11ax HE40>







<802.11ax HE80>

Maximum Power Density Plot (dBm/300kHz)

MIMO Ant. 6



MIMO Ant. 7






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

EUT Information

Report NO : 430824
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.188250	---	32.74	54.11	21.37	L1	OFF	19.8
0.188250	41.56	---	64.11	22.55	L1	OFF	19.8
0.258000	---	31.54	51.50	19.96	L1	OFF	19.8
0.258000	40.02	---	61.50	21.48	L1	OFF	19.8
0.415500	---	26.58	47.54	20.96	L1	OFF	19.8
0.415500	35.78	---	57.54	21.76	L1	OFF	19.8
0.615750	---	27.07	46.00	18.93	L1	OFF	19.8
0.615750	34.41	---	56.00	21.59	L1	OFF	19.8
3.248250	---	27.31	46.00	18.69	L1	OFF	19.9
3.248250	32.23	---	56.00	23.77	L1	OFF	19.9
9.366000	---	27.83	50.00	22.17	L1	OFF	20.2
9.366000	30.26	---	60.00	29.74	L1	OFF	20.2

EUT Information

Report NO : 430824
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.201750	---	31.35	53.54	22.19	N	OFF	19.8
0.201750	40.15	---	63.54	23.39	N	OFF	19.8
0.262500	---	31.38	51.35	19.97	N	OFF	19.8
0.262500	39.98	---	61.35	21.37	N	OFF	19.8
0.404250	---	27.12	47.77	20.65	N	OFF	19.8
0.404250	36.39	---	57.77	21.38	N	OFF	19.8
0.613500	---	27.06	46.00	18.94	N	OFF	19.8
0.613500	34.38	---	56.00	21.62	N	OFF	19.8
3.225750	---	27.85	46.00	18.15	N	OFF	19.9
3.225750	33.05	---	56.00	22.95	N	OFF	19.9
9.143250	---	27.83	50.00	22.17	N	OFF	20.3
9.143250	30.20	---	60.00	29.80	N	OFF	20.3



Appendix C. Radiated Spurious Emission

Test Engineer :	Jesse Wang, Stan Hsieh, and Ken Wu	Temperature :	23.5~26.5°C
		Relative Humidity :	42.8~67.2%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5649.4	48.57	-19.63	68.2	35.42	35	12.85	34.7	141	360	P	H
		5697	53.22	-49.77	102.99	39.84	35.19	12.92	34.73	141	360	P	H
		5718.2	63.73	-46.57	110.3	50.32	35.2	12.95	34.74	141	360	P	H
		5724	69.46	-50.46	119.92	56.05	35.2	12.96	34.75	141	360	P	H
	*	5745	111.61	-	-	98.18	35.2	12.99	34.76	141	360	P	H
	*	5745	103.87	-	-	90.44	35.2	12.99	34.76	141	360	A	H
													H
													H
		5646	51.27	-16.93	68.2	38.14	34.98	12.85	34.7	128	360	P	V
		5698.4	64.4	-39.62	104.02	51.02	35.19	12.92	34.73	128	360	P	V
		5719.8	77.14	-33.6	110.74	63.73	35.2	12.95	34.74	128	360	P	V
		5724.8	80.78	-40.96	121.74	67.37	35.2	12.96	34.75	128	360	P	V
	*	5745	117.79	-	-	104.36	35.2	12.99	34.76	128	360	P	V
	*	5745	110.96	-	-	97.53	35.2	12.99	34.76	128	360	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5601	49.99	-18.21	68.2	37.18	34.71	12.78	34.68	137	0	P	H
		5671.6	50.37	-33.85	84.22	37.12	35.09	12.88	34.72	137	0	P	H
		5714.6	51.11	-58.18	109.29	37.7	35.2	12.95	34.74	137	0	P	H
		5725	50.69	-71.51	122.2	37.28	35.2	12.96	34.75	137	0	P	H
	*	5785	110.03	-	-	96.56	35.2	13.05	34.78	137	0	P	H
	*	5785	103.51	-	-	90.04	35.2	13.05	34.78	137	0	A	H
		5853.6	53.18	-60.81	113.99	39.88	35.01	13.11	34.82	137	0	P	H
		5865.4	52.45	-55.44	107.89	39.12	35.03	13.12	34.82	137	0	P	H
		5875.4	51.45	-53.45	104.9	38.1	35.05	13.13	34.83	137	0	P	H
		5944	50.72	-17.48	68.2	37.39	35.01	13.19	34.87	137	0	P	H
													H
													H
		5637.6	49.57	-18.63	68.2	36.51	34.93	12.83	34.7	104	360	P	V
		5695.6	56.6	-45.36	101.96	43.23	35.18	12.92	34.73	104	360	P	V
		5711	61.86	-46.42	108.28	48.46	35.2	12.94	34.74	104	360	P	V
		5723.4	61.46	-57.09	118.55	48.05	35.2	12.96	34.75	104	360	P	V
	*	5785	118.64	-	-	105.17	35.2	13.05	34.78	104	360	P	V
	*	5785	111.23	-	-	97.76	35.2	13.05	34.78	104	360	A	V
		5853.4	57.72	-56.73	114.45	44.42	35.01	13.11	34.82	104	360	P	V
		5857.8	59.35	-50.66	110.01	46.03	35.02	13.12	34.82	104	360	P	V
		5901	54.64	-31.28	85.92	41.23	35.1	13.15	34.84	104	360	P	V
		5950	52.09	-16.11	68.2	38.77	35	13.19	34.87	104	360	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	112.54	-	-	99.15	35.1	13.09	34.8	382	7	P	H
	*	5825	105.59	-	-	92.2	35.1	13.09	34.8	382	7	A	H
		5850.8	75.2	-45.18	120.38	61.91	35	13.11	34.82	382	7	P	H
		5856.8	67.33	-42.97	110.3	54.02	35.01	13.12	34.82	382	7	P	H
		5876	54.96	-49.5	104.46	41.61	35.05	13.13	34.83	382	7	P	H
		5948	51.49	-16.71	68.2	38.17	35	13.19	34.87	382	7	P	H
													H
													H
	*	5825	118.56	-	-	105.17	35.1	13.09	34.8	105	360	P	V
	*	5825	111.08	-	-	97.69	35.1	13.09	34.8	105	360	A	V
		5852.8	77.78	-38.04	115.82	64.48	35.01	13.11	34.82	105	360	P	V
		5855	74.46	-36.34	110.8	61.16	35.01	13.11	34.82	105	360	P	V
		5878.2	67.78	-35.04	102.82	54.42	35.06	13.13	34.83	105	360	P	V
		5927.6	55.03	-13.17	68.2	41.68	35.04	13.17	34.86	105	360	P	V
													V
													V
													V
Remark 1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													

**Band 4 5725~5850MHz****WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	54.48	-19.52	74	53.82	38.18	19.48	57	100	343	P	H
		11490	43.22	-10.78	54	42.56	38.18	19.48	57	100	343	A	H
		17235	57.03	-11.17	68.2	47.47	41.64	23.91	55.99	138	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11490	49.78	-24.22	74	49.12	38.18	19.48	57	400	355	P	V
		11490	40.34	-13.66	54	39.68	38.18	19.48	57	400	355	A	V
		17235	55.77	-12.43	68.2	46.21	41.64	23.91	55.99	400	324	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		11570	53.45	-20.55	74	52.53	38.24	19.53	56.85	100	344	P	H
		11570	43.75	-10.25	54	42.83	38.24	19.53	56.85	100	344	A	H
		17355	57.83	-10.37	68.2	48.22	41.41	24	55.8	126	1	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11570	52.4	-21.6	74	51.48	38.24	19.53	56.85	227	0	P	V
		11570	41.55	-12.45	54	40.63	38.24	19.53	56.85	227	0	A	V
		17355	52.32	-15.88	68.2	42.71	41.41	24	55.8	-	-	P	V
													V
													V
													V
													V
													V
													V
													V

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE20_Full (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 149 5745MHz		5646.4	52.7	-15.5	68.2	39.57	34.98	12.85	34.7	141	0	P	H
		5686.4	65.83	-29.34	95.17	52.49	35.15	12.91	34.72	141	0	P	H
		5717.2	71.18	-38.84	110.02	57.77	35.2	12.95	34.74	141	0	P	H
		5723.4	73.79	-44.76	118.55	60.38	35.2	12.96	34.75	141	0	P	H
	*	5745	111	-	-	97.57	35.2	12.99	34.76	141	0	P	H
	*	5745	103.64	-	-	90.21	35.2	12.99	34.76	141	0	A	H
													H
													H
		5644	56.53	-11.67	68.2	43.43	34.96	12.84	34.7	128	360	P	V
		5693.4	70.56	-29.77	100.33	57.2	35.17	12.92	34.73	128	360	P	V
		5718.2	84.33	-25.97	110.3	70.92	35.2	12.95	34.74	128	360	P	V
		5724.8	86.76	-34.98	121.74	73.35	35.2	12.96	34.75	128	360	P	V
	*	5745	117.36	-	-	103.93	35.2	12.99	34.76	128	360	P	V
	*	5745	110.92	-	-	97.49	35.2	12.99	34.76	128	360	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 157 5785MHz		5638	51.49	-16.71	68.2	38.42	34.93	12.84	34.7	100	355	P	H
		5700	50.76	-54.44	105.2	37.37	35.2	12.92	34.73	100	355	P	H
		5700.2	54.67	-50.59	105.26	41.27	35.2	12.93	34.73	100	355	P	H
		5721.6	54.3	-60.15	114.45	40.88	35.2	12.96	34.74	100	355	P	H
	*	5785	110.86	-	-	97.39	35.2	13.05	34.78	100	355	P	H
	*	5785	104.05	-	-	90.58	35.2	13.05	34.78	100	355	A	H
		5852.8	56.18	-59.64	115.82	42.88	35.01	13.11	34.82	100	355	P	H
		5859	57.18	-52.5	109.68	43.86	35.02	13.12	34.82	100	355	P	H
		5897.6	51.85	-36.59	88.44	38.44	35.1	13.15	34.84	100	355	P	H
		5933	50.42	-17.78	68.2	37.07	35.03	13.18	34.86	100	355	P	H
													H
													H
		5606.4	50.52	-17.68	68.2	37.67	34.74	12.79	34.68	103	355	P	V
		5696.2	58.16	-44.24	102.4	44.79	35.18	12.92	34.73	103	355	P	V
		5711.6	64.86	-43.59	108.45	51.46	35.2	12.94	34.74	103	355	P	V
		5725	65.59	-56.61	122.2	52.18	35.2	12.96	34.75	103	355	P	V
	*	5785	117.65	-	-	104.18	35.2	13.05	34.78	103	355	P	V
	*	5785	111.41	-	-	97.94	35.2	13.05	34.78	103	355	A	V
		5853.6	61.98	-52.01	113.99	48.68	35.01	13.11	34.82	103	355	P	V
		5856.4	61.94	-48.47	110.41	48.63	35.01	13.12	34.82	103	355	P	V
		5879.4	57.11	-44.82	101.93	43.75	35.06	13.13	34.83	103	355	P	V
		5948.4	51.76	-16.44	68.2	38.44	35	13.19	34.87	103	355	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 165 5825MHz	*	5825	112.46	-	-	99.07	35.1	13.09	34.8	382	8	P	H
	*	5825	105.31	-	-	91.92	35.1	13.09	34.8	382	8	A	H
		5850	74.24	-47.96	122.2	60.95	35	13.11	34.82	382	8	P	H
		5856.8	71	-39.3	110.3	57.69	35.01	13.12	34.82	382	8	P	H
		5875	58.86	-46.34	105.2	45.51	35.05	13.13	34.83	382	8	P	H
		5930.6	50.97	-17.23	68.2	37.62	35.04	13.17	34.86	382	8	P	H
													H
													H
	*	5825	117.96	-	-	104.57	35.1	13.09	34.8	107	0	P	V
	*	5825	110.49	-	-	97.1	35.1	13.09	34.8	107	0	A	V
		5850.8	83.35	-37.03	120.38	70.06	35	13.11	34.82	107	0	P	V
		5855.2	81.93	-28.81	110.74	68.63	35.01	13.11	34.82	107	0	P	V
		5875.4	72.19	-32.71	104.9	58.84	35.05	13.13	34.83	107	0	P	V
		5926.8	56.44	-11.76	68.2	43.08	35.05	13.17	34.86	107	0	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 149 5745MHz		11490	54.65	-19.35	74	53.99	38.18	19.48	57	100	343	P	H
		11490	43.34	-10.66	54	42.68	38.18	19.48	57	100	343	A	H
		17235	56.95	-11.25	68.2	47.39	41.64	23.91	55.99	124	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11490	52.56	-21.44	74	51.9	38.18	19.48	57	235	6	P	V
		11490	41.88	-12.12	54	41.22	38.18	19.48	57	235	6	A	V
		17235	53.53	-14.67	68.2	43.97	41.64	23.91	55.99	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 157 5785MHz		11570	52.61	-21.39	74	51.69	38.24	19.53	56.85	241	0	P	H
		11570	42.02	-11.98	54	41.1	38.24	19.53	56.85	241	0	A	H
		17355	57.46	-10.74	68.2	47.85	41.41	24	55.8	129	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		11570	52.93	-21.07	74	52.01	38.24	19.53	56.85	241	0	P	V
		11570	42.11	-11.89	54	41.19	38.24	19.53	56.85	241	0	A	V
		17355	51.58	-16.62	68.2	41.97	41.41	24	55.8	-	-	P	V
													V
													V
													V
													V
													V
													V

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE20_Partial 106 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Partial 106/53 CH 149 5745MHz		5648.8	55.1	-13.1	68.2	41.96	34.99	12.85	34.7	100	298	P	H
		5682.2	69.33	-22.74	92.07	56.02	35.13	12.9	34.72	100	298	P	H
		5708.2	80.2	-27.3	107.5	66.8	35.2	12.94	34.74	100	298	P	H
		5722.2	78.23	-37.59	115.82	64.81	35.2	12.96	34.74	100	298	P	H
	*	5745	108.22	-	-	94.79	35.2	12.99	34.76	100	298	P	H
	*	5745	102.43	-	-	89	35.2	12.99	34.76	100	298	A	H
													H
													H
		5649.4	63.47	-4.73	68.2	50.32	35	12.85	34.7	100	20	P	V
		5681.8	77.72	-14.05	91.77	64.41	35.13	12.9	34.72	100	20	P	V
		5717.2	88.31	-21.71	110.02	74.9	35.2	12.95	34.74	100	20	P	V
		5724.4	86.8	-34.03	120.83	73.39	35.2	12.96	34.75	100	20	P	V
	*	5745	116.79	-	-	103.36	35.2	12.99	34.76	100	20	P	V
	*	5745	110.97	-	-	97.54	35.2	12.99	34.76	100	20	A	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Partial 106/54 CH 165 5825MHz	*	5825	112.87	-	-	99.48	35.1	13.09	34.8	101	0	P	H
	*	5825	107.03	-	-	93.64	35.1	13.09	34.8	101	0	A	H
		5851.8	87.17	-30.93	118.1	73.88	35	13.11	34.82	101	0	P	H
		5855.6	80.86	-29.77	110.63	67.56	35.01	13.11	34.82	101	0	P	H
		5875	73.34	-31.86	105.2	59.99	35.05	13.13	34.83	101	0	P	H
		5926	58.97	-9.23	68.2	45.61	35.05	13.17	34.86	101	0	P	H
													H
													H
	*	5825	119.96	-	-	106.57	35.1	13.09	34.8	106	0	P	V
	*	5825	112.3	-	-	98.91	35.1	13.09	34.8	106	0	A	V
		5852.4	92.98	-23.75	116.73	79.69	35	13.11	34.82	106	0	P	V
		5861.4	87.27	-21.74	109.01	73.95	35.02	13.12	34.82	106	0	P	V
		5882.6	79.88	-19.68	99.56	66.5	35.07	13.14	34.83	106	0	P	V
		5927.8	65.96	-2.24	68.2	52.61	35.04	13.17	34.86	106	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 151 5755MHz		5649.8	57.42	-10.78	68.2	44.27	35	12.85	34.7	121	0	P	H
		5699.4	66.34	-38.42	104.76	52.95	35.2	12.92	34.73	121	0	P	H
		5712.4	68.95	-39.72	108.67	55.55	35.2	12.94	34.74	121	0	P	H
		5723	72.81	-44.83	117.64	59.39	35.2	12.96	34.74	121	0	P	H
	*	5755	108.54	-	-	95.1	35.2	13	34.76	121	0	P	H
	*	5755	101.15	-	-	87.71	35.2	13	34.76	121	0	A	H
		5854.6	55.76	-55.95	111.71	42.46	35.01	13.11	34.82	121	0	P	H
		5857	57.29	-52.95	110.24	43.98	35.01	13.12	34.82	121	0	P	H
		5890.6	55.46	-38.16	93.62	42.08	35.08	13.14	34.84	121	0	P	H
		5942.4	50.84	-17.36	68.2	37.51	35.02	13.18	34.87	121	0	P	H
													H
													H
		5643	66.24	-1.96	68.2	53.14	34.96	12.84	34.7	108	26	P	V
		5695.6	74.9	-27.06	101.96	61.53	35.18	12.92	34.73	108	26	P	V
		5716.4	80.85	-28.94	109.79	67.44	35.2	12.95	34.74	108	26	P	V
		5724.2	83.42	-36.96	120.38	70.01	35.2	12.96	34.75	108	26	P	V
	*	5755	114.1	-	-	100.66	35.2	13	34.76	108	26	P	V
	*	5755	107.56	-	-	94.12	35.2	13	34.76	108	26	A	V
		5853.8	61.89	-51.65	113.54	48.59	35.01	13.11	34.82	108	26	P	V
		5855.6	64.47	-46.16	110.63	51.17	35.01	13.11	34.82	108	26	P	V
		5880.8	60.25	-40.64	100.89	46.89	35.06	13.13	34.83	108	26	P	V
		5929.8	59.41	-8.79	68.2	46.06	35.04	13.17	34.86	108	26	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 159 5795MHz		5645.4	52	-16.2	68.2	38.88	34.97	12.85	34.7	114	360	P	H
		5700	58.03	-47.17	105.2	44.64	35.2	12.92	34.73	114	360	P	H
		5711.4	60.97	-47.42	108.39	47.57	35.2	12.94	34.74	114	360	P	H
		5722.6	64.16	-52.57	116.73	50.74	35.2	12.96	34.74	114	360	P	H
	*	5795	109.98	-	-	96.51	35.2	13.06	34.79	114	360	P	H
	*	5795	101.94	-	-	88.47	35.2	13.06	34.79	114	360	A	H
		5853.4	66.57	-47.88	114.45	53.27	35.01	13.11	34.82	114	360	P	H
		5863.4	63.65	-44.8	108.45	50.32	35.03	13.12	34.82	114	360	P	H
		5878.2	60.92	-41.9	102.82	47.56	35.06	13.13	34.83	114	360	P	H
		5929.4	56.4	-11.8	68.2	43.05	35.04	13.17	34.86	114	360	P	H
													H
													H
		5646	66.4	-1.8	68.2	53.27	34.98	12.85	34.7	108	17	P	V
		5682	67.23	-24.69	91.92	53.92	35.13	12.9	34.72	108	17	P	V
		5712.6	69.38	-39.35	108.73	55.98	35.2	12.94	34.74	108	17	P	V
		5722.4	70.83	-45.44	116.27	57.41	35.2	12.96	34.74	108	17	P	V
	*	5795	114.31	-	-	100.84	35.2	13.06	34.79	108	17	P	V
	*	5795	107.64	-	-	94.17	35.2	13.06	34.79	108	17	A	V
		5850.4	75.22	-46.07	121.29	61.93	35	13.11	34.82	108	17	P	V
		5858	72.49	-37.47	109.96	59.17	35.02	13.12	34.82	108	17	P	V
		5875.8	68.88	-35.73	104.61	55.53	35.05	13.13	34.83	108	17	P	V
		5925.4	62.51	-5.69	68.2	49.15	35.05	13.17	34.86	108	17	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Harmonic @ 3m)

[illegible]

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Partial 242 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Partial 242/61 CH 151 5755MHz		5630.6	55.45	-12.75	68.2	42.44	34.88	12.82	34.69	122	0	P	H
		5681.2	65.72	-25.61	91.33	52.42	35.12	12.9	34.72	122	0	P	H
		5713	70.73	-38.11	108.84	57.33	35.2	12.94	34.74	122	0	P	H
		5724	74.24	-45.68	119.92	60.83	35.2	12.96	34.75	122	0	P	H
	*	5755	107.44	-	-	94	35.2	13	34.76	122	0	P	H
	*	5755	101.68	-	-	88.24	35.2	13	34.76	122	0	A	H
		5854.6	63.48	-48.23	111.71	50.18	35.01	13.11	34.82	122	0	P	H
		5858.8	58.13	-51.6	109.73	44.81	35.02	13.12	34.82	122	0	P	H
		5882.6	50.97	-48.59	99.56	37.59	35.07	13.14	34.83	122	0	P	H
		5926	51.08	-17.12	68.2	37.72	35.05	13.17	34.86	122	0	P	H
													H
													H
		5648	62.45	-5.75	68.2	49.31	34.99	12.85	34.7	118	16	P	V
		5699.4	79.95	-24.81	104.76	66.56	35.2	12.92	34.73	118	16	P	V
		5717	84.2	-25.76	109.96	70.79	35.2	12.95	34.74	118	16	P	V
		5723	86.39	-31.25	117.64	72.97	35.2	12.96	34.74	118	16	P	V
	*	5755	113.68	-	-	100.24	35.2	13	34.76	118	16	P	V
	*	5755	107.47	-	-	94.03	35.2	13	34.76	118	16	A	V
		5850.2	69.76	-51.98	121.74	56.47	35	13.11	34.82	118	16	P	V
		5863.2	61.06	-47.44	108.5	47.73	35.03	13.12	34.82	118	16	P	V
		5876.6	56.9	-47.11	104.01	43.55	35.05	13.13	34.83	118	16	P	V
		5935.8	55.07	-13.13	68.2	41.72	35.03	13.18	34.86	118	16	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Partial 242/62 CH 159 5795MHz		5629.2	50.27	-17.93	68.2	37.26	34.88	12.82	34.69	106	0	P	H
		5693.8	57.87	-42.76	100.63	44.5	35.18	12.92	34.73	106	0	P	H
		5718.4	64.26	-46.09	110.35	50.85	35.2	12.95	34.74	106	0	P	H
		5720.8	57.86	-54.76	112.62	44.44	35.2	12.96	34.74	106	0	P	H
	*	5795	109.76	-	-	96.29	35.2	13.06	34.79	106	0	P	H
	*	5795	102.7	-	-	89.23	35.2	13.06	34.79	106	0	A	H
		5853	74.27	-41.09	115.36	60.97	35.01	13.11	34.82	106	0	P	H
		5855.2	71.09	-39.65	110.74	57.79	35.01	13.11	34.82	106	0	P	H
		5907	67.43	-14.05	81.48	54.03	35.09	13.16	34.85	106	0	P	H
		5932	56.26	-11.94	68.2	42.9	35.04	13.18	34.86	106	0	P	H
													H
													H
		5645.8	57.44	-10.76	68.2	44.32	34.97	12.85	34.7	100	19	P	V
		5658.4	69.63	-4.81	74.44	56.45	35.03	12.86	34.71	100	19	P	V
		5717.6	71.49	-38.64	110.13	58.08	35.2	12.95	34.74	100	19	P	V
		5723	69.96	-47.68	117.64	56.54	35.2	12.96	34.74	100	19	P	V
	*	5795	114.62	-	-	101.15	35.2	13.06	34.79	100	19	P	V
	*	5795	107.42	-	-	93.95	35.2	13.06	34.79	100	19	A	V
		5853.6	81.2	-32.79	113.99	67.9	35.01	13.11	34.82	100	19	P	V
		5858.8	82.59	-27.14	109.73	69.27	35.02	13.12	34.82	100	19	P	V
		5877.6	72.46	-30.81	103.27	59.1	35.06	13.13	34.83	100	19	P	V
		5942	65.68	-2.52	68.2	52.35	35.02	13.18	34.87	100	19	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE80_Full (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Full CH 155 5775MHz		5642.4	59.03	-9.17	68.2	45.94	34.95	12.84	34.7	116	0	P	H
		5692.6	62.79	-36.95	99.74	49.44	35.17	12.91	34.73	116	0	P	H
		5713.8	65.37	-43.7	109.07	51.96	35.2	12.95	34.74	116	0	P	H
		5722.8	63.78	-53.4	117.18	50.36	35.2	12.96	34.74	116	0	P	H
	*	5775	106.53	-	-	93.07	35.2	13.03	34.77	116	0	P	H
	*	5775	99.3	-	-	85.84	35.2	13.03	34.77	116	0	A	H
		5853.4	65.19	-49.26	114.45	51.89	35.01	13.11	34.82	116	0	P	H
		5855.2	64.4	-46.34	110.74	51.1	35.01	13.11	34.82	116	0	P	H
		5885.4	61.28	-36.2	97.48	47.91	35.07	13.14	34.84	116	0	P	H
		5946	56.14	-12.06	68.2	42.81	35.01	13.19	34.87	116	0	P	H
													H
													H
		5636.2	64.53	-3.67	68.2	51.48	34.92	12.83	34.7	100	22	P	V
		5698.6	70.69	-33.48	104.17	57.31	35.19	12.92	34.73	100	22	P	V
		5719	74.71	-35.81	110.52	61.3	35.2	12.95	34.74	100	22	P	V
		5724.8	71.31	-50.43	121.74	57.9	35.2	12.96	34.75	100	22	P	V
	*	5775	113.22	-	-	99.76	35.2	13.03	34.77	100	22	P	V
	*	5775	105.08	-	-	91.62	35.2	13.03	34.77	100	22	A	V
		5850	69.87	-52.33	122.2	56.58	35	13.11	34.82	100	22	P	V
		5859.2	72.45	-37.17	109.62	59.13	35.02	13.12	34.82	100	22	P	V
		5881.6	67.27	-33.03	100.3	53.9	35.06	13.14	34.83	100	22	P	V
		5926.4	61.69	-6.51	68.2	48.33	35.05	13.17	34.86	100	22	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ax HE80_Full (Harmonic @ 3m)

[illegible]



Band 4 5725~5850MHz

WIFI 802.11ax HE80_Partial 484 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Partial 484/65 CH 155 5775MHz		5639.6	63.33	-4.87	68.2	50.25	34.94	12.84	34.7	123	0	P	H
		5691.8	66.18	-32.97	99.15	52.83	35.17	12.91	34.73	123	0	P	H
		5710.2	68.81	-39.25	108.06	55.41	35.2	12.94	34.74	123	0	P	H
		5722.4	75.7	-40.57	116.27	62.28	35.2	12.96	34.74	123	0	P	H
	*	5775	105.73	-	-	92.27	35.2	13.03	34.77	123	0	P	H
	*	5775	97.75	-	-	84.29	35.2	13.03	34.77	123	0	A	H
		5853	63	-52.36	115.36	49.7	35.01	13.11	34.82	123	0	P	H
		5864.4	60.16	-48.01	108.17	46.83	35.03	13.12	34.82	123	0	P	H
		5916	64.66	-10.18	74.84	51.28	35.07	13.16	34.85	123	0	P	H
		5931.2	59.33	-8.87	68.2	45.98	35.04	13.17	34.86	123	0	P	H
													H
													H
		5630.2	66.17	-2.03	68.2	53.16	34.88	12.82	34.69	132	0	P	V
		5698.8	75.48	-28.84	104.32	62.09	35.2	12.92	34.73	132	0	P	V
		5719.2	79.55	-31.03	110.58	66.14	35.2	12.95	34.74	132	0	P	V
		5720.2	78.75	-32.51	111.26	65.34	35.2	12.95	34.74	132	0	P	V
	*	5775	110.41	-	-	96.95	35.2	13.03	34.77	132	0	P	V
	*	5775	103	-	-	89.54	35.2	13.03	34.77	132	0	A	V
		5850.4	62.74	-58.55	121.29	49.45	35	13.11	34.82	132	0	P	V
		5863.6	67.58	-40.81	108.39	54.25	35.03	13.12	34.82	132	0	P	V
		5903.8	68.34	-15.51	83.85	54.95	35.09	13.15	34.85	132	0	P	V
		5942.4	63.59	-4.61	68.2	50.26	35.02	13.18	34.87	132	0	P	V
													V
													V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Partial 484/66 CH 155 5775MHz		5642.8	65.89	-2.31	68.2	52.79	34.96	12.84	34.7	107	337	P	H
		5695.8	73.79	-28.31	102.1	60.42	35.18	12.92	34.73	107	337	P	H
		5711.8	77.8	-30.71	108.51	64.4	35.2	12.94	34.74	107	337	P	H
		5722	74.13	-41.23	115.36	60.71	35.2	12.96	34.74	107	337	P	H
	*	5775	107.82	-	-	94.36	35.2	13.03	34.77	107	337	P	H
	*	5775	98.22	-	-	84.76	35.2	13.03	34.77	107	337	A	H
		5851.6	71	-47.55	118.55	57.71	35	13.11	34.82	107	337	P	H
		5869.8	79.15	-27.5	106.65	65.81	35.04	13.13	34.83	107	337	P	H
		5880.6	73.48	-27.56	101.04	60.12	35.06	13.13	34.83	107	337	P	H
		5934.4	65.7	-2.5	68.2	52.35	35.03	13.18	34.86	107	337	P	H
													H
													H
		5635.8	66.89	-1.31	68.2	53.85	34.91	12.83	34.7	100	20	P	V
		5680.6	80.15	-10.73	90.88	66.85	35.12	12.9	34.72	100	20	P	V
		5716.6	76.74	-33.11	109.85	63.33	35.2	12.95	34.74	100	20	P	V
		5722.8	74.63	-42.55	117.18	61.21	35.2	12.96	34.74	100	20	P	V
	*	5775	112.72	-	-	99.26	35.2	13.03	34.77	100	20	P	V
	*	5775	103.18	-	-	89.72	35.2	13.03	34.77	100	20	A	V
		5850.6	67.2	-53.63	120.83	53.91	35	13.11	34.82	100	20	P	V
		5862.2	80.33	-28.45	108.78	67.01	35.02	13.12	34.82	100	20	P	V
		5885.8	72.95	-24.23	97.18	59.58	35.07	13.14	34.84	100	20	P	V
		5936.6	66.62	-1.58	68.2	53.27	35.03	13.18	34.86	100	20	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11ax HE80 Full (LF @ 3m)

WIFI	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ax HE80 Full LF		50.52	24.03	-15.97	40	38.32	14.25	1.38	29.92	-	-	P	H
		92.37	29.89	-13.61	43.5	43.05	14.92	1.82	29.9	-	-	P	H
		263.55	33.33	-12.67	46	40.48	19.68	2.99	29.82	-	-	P	H
		744.5	29.28	-16.72	46	26.67	27.25	4.85	29.49	-	-	P	H
		845.3	31.85	-14.15	46	27.79	28.03	5.21	29.18	-	-	P	H
		956.6	32.93	-13.07	46	26.47	29.66	5.42	28.62	-	-	P	H
													H
													H
													H
													H
													H
													H
		30.27	30.24	-9.76	40	34.9	24.21	1.07	29.94	-	-	P	V
		50.79	32.33	-7.67	40	46.73	14.14	1.38	29.92	-	-	P	V
		87.78	28.24	-11.76	40	41.94	14.42	1.79	29.91	-	-	P	V
		755	30.73	-15.27	46	27.9	27.41	4.88	29.46	-	-	P	V
		843.2	32.26	-13.74	46	28.29	27.95	5.2	29.18	-	-	P	V
		958	33.97	-12.03	46	27.44	29.7	5.43	28.6	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												
	3. The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Margin line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a		5850	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 157		5850	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
5785MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin (dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 5850MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Margin (dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 5850MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Margin (dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.






Appendix D. Radiated Spurious Emission Plots




Test Engineer :	Jesse Wang, Stan Hsieh, and Ken Wu	Temperature :	23.5~26.5°C
		Relative Humidity :	42.8~67.2%

Band 4 - 5725~5850MHz




WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site Condition : 03CH07-HY : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	 Site Condition : 03CH07-HY : PEAK(LINII) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto
Avg	Left blank	 Site Condition : 03CH07-HY : AVG_34 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Vertical	Fundamental
Peak		
Avg	Left blank	






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07.RPT Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_34 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN) 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto






Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site Condition : 03CH07-HY : PEAK_RE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	 Site Condition : 03CH07-HY : PEAK(LUN0) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto
Avg	Left blank	 Site Condition : 03CH07-HY : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_S4 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTA:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN1) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_S4 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UNI) 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_34 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto






Band 4 5725~5850MHz
WIFI 802.11ax HE20 Partial 106 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_RE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:3000.000KHz SWTAUTO	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:3000.000KHz SWTAUTO
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:3000.000KHz SWTAUTO






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_F4 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UNI) 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_34 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto






Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site Condition : 03CH07-HY : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	 Site Condition : 03CH07-HY : PEAK(LIN) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto
Avg	Left blank	 Site Condition : 03CH07-HY : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07.001 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LIN)_1 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_14 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site Condition : 03CH07.001 : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site Condition : 03CH07-HY : PEAK_RE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:3000.000KHz SWTAuto	 Site Condition : 03CH07-HY : PEAK(LUNB) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:3000.000KHz SWTAuto
Avg	Left blank	 Site Condition : 03CH07-HY : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VIEW:1.000KHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LNB) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH027-001 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak		
Avg	Left blank	




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(FUN1) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_34 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE80 Partial 484 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak		
Avg	Left blank	




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LIN)_1 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWTAuto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(LIN)_1 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWTAuto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 03CH07-01 Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE(04)_16-24 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto	 Site : 03CH07-HY Condition : PEAK(UN1) 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWTAuto
Avg	Left blank	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWTAuto





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
6+7	Vertical	Fundamental
Peak	 Site Condition : 802.11ax HE80 Partial 484/66 CH155 5775MHz : PEAK_BE(BA)_16-24 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank





Peak
Avg.





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : E8CH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 HORIZONTAL 1: 1 2: 2	 Site : E8CH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 VERTICAL 1: 1 2: 2



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : E8CH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 HORIZONTAL 1: 1 2: 2	 Site : E8CH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 VERTICAL 1: 1 2: 2



Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-HY Condition : PEAK(UNII) 3m HF_ANT_00075962 HORIZONTAL Date: 2024.06.25	 Site : 03CH07-HY Condition : PEAK(UNII) 3m HF_ANT_00075962 VERTICAL Date: 2024.06.25



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : ESCH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 HORIZONTAL 1: 1	Site : ESCH07-RF Condition : PEAK(UNII) 3m HF_ANT_00075962 VERTICAL 1: 1



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
6+7	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2024-06-27 Site : ESCH07-RY Condition : PEAK(UNB) 3m HF_ANT_00075962 HORIZONTAL 1: 5825.000000 2: 5825.000000	Level (dBuV/m) Date: 2024-06-26 Site : ESCH07-RY Condition : PEAK(UNB) 3m HF_ANT_00075962 VERTICAL 1: 5825.000000 2: 5825.000000



Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : 03CH07-HY Condition : PEAK(UNII) 3m HF_ANT_00075962 HORIZONTAL	Site : 03CH07-HY Condition : PEAK(UNII) 3m HF_ANT_00075962 VERTICAL



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : ESCH07-RF Condition : PEAK(UNI) 3m HF_ANT_00075962 HORIZONTAL 1: 5795.000000 2: 5795.000000 3: 5795.000000	Site : ESCH07-RF Condition : PEAK(UNI) 3m HF_ANT_00075962 VERTICAL 1: 5795.000000 2: 5795.000000 3: 5795.000000



Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : 03CH07-HY Condition : PEAK(UNIT) 3m HF_ANT_00075962 HORIZONTAL	Site : 03CH07-HY Condition : PEAK(UNIT) 3m HF_ANT_00075962 VERTICAL



Emission below 1GHz
5GHz WIFI 802.11ax HE80 Full (LF @ 3m)


WIFI	5GHz WIFI	
ANT	802.11ax HE80 Full LF	
6+7	Horizontal	Vertical
QP / Peak	Level (dBuV/m) Date: 2024-07-04 Site : 03C-067-RY Condition : QP 3m LF-ANT-35419(6)_H HORIZONTAL	Level (dBuV/m) Date: 2024-07-04 Site : 03C-067-RY Condition : QP 3m LF-ANT-35419(6)_H VERTICAL



Appendix E. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
6+7	802.11a	85.77	1718	0.58	1kHz
6+7	5GHz 802.11ax HE20 Full RU	89.83	5360	0.19	300Hz
6+7	5GHz 802.11ax HE20 106 RU	90.09	4763	0.21	300Hz
6+7	5GHz 802.11ax HE40 Full RU	94.64	5407	0.18	300Hz
6+7	5GHz 802.11ax HE40 242 RU	85.85	2736	0.37	1kHz
6+7	5GHz 802.11ax HE80 Full RU	94.46	2558	0.39	1kHz
6+7	5GHz 802.11ax HE80 484 RU	85.71	1403	0.71	1kHz

MIMO <Ant. 6+7>







5GHz 802.11ax HE20 106 RU



5GHz 802.11ax HE40 Full RU



5GHz 802.11ax HE40 242 RU



5GHz 802.11ax HE80 Full RU



5GHz 802.11ax HE80 484 RU

