





**Occupied Bandwidth**

Mode	FR1 n13 : 99%OBW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz					
Mod.	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK				
Middle CH	4.47	4.48	8.94	8.96				
Mod.	16QAM		16QAM					
Middle CH	4.50		8.96					




FR1 n13 / 5MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK



QPSK




16QAM






FR1 n13 / 10MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK



QPSK



16QAM







Conducted Band Edge

FR1 n13 / 5MHz / DFT-S OFDM / PI/2 BPSK



Lowest Band Edge / 1RB0

Highest Band Edge / 1RBmax



Lowest Band Edge / Full RB

Highest Band Edge / Full RB







FR1 n13 / 5MHz / DFT-S OFDM / QPSK



Lowest Band Edge / 1RB0

Highest Band Edge / 1RBmax



Lowest Band Edge / Full RB


Highest Band Edge / Full RB






FR1 n13 / 10MHz / DFT-s-OFDM / PI/2 BPSK

Middle Band Edge / Full RB



FR1 n13 / 10MHz / DFT-s-OFDM / QPSK

Middle Band Edge / Full RB







Conducted Spurious Emission

FR1 n13 / 5MHz / DFT-S OFDM / QPSK / 1RB1


Lowest Channel



Middle Channel



Highest Channel



**Frequency Stability**

Test Conditions		FR1 n13 (BPSK) / Middle Channel 10M			
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Frequency Offset (Δf) (Hz)	Within Authorized Frequency Block(Hz)	Result
50	Normal Voltage	0.0008	-0.6	Yes	PASS
40	Normal Voltage	0.0001	-0.1	Yes	
30	Normal Voltage	0.0090	7	Yes	
20(Ref.)	Normal Voltage	0.0000	0	Yes	
10	Normal Voltage	0.0056	-4.4	Yes	
0	Normal Voltage	0.0113	-8.8	Yes	
-10	Normal Voltage	0.0115	-9	Yes	
-20	Normal Voltage	0.0134	-10.5	Yes	
-30	Normal Voltage	0.0037	2.9	Yes	
20	Maximum Voltage	0.0003	-0.2	Yes	
20	Normal Voltage	0.0000	0	Yes	
20	Minimum Voltage	0.0014	1.1	Yes	

Note:

1. Normal Voltage = 3.91 V. ; Minimum Voltage = 3.5 V. ; Maximum Voltage = 4.45 V.
2. The frequency fundamental emissions stay within the authorized frequency block.
3. The frequency variation is sufficient to ensure that the occupied bandwidth of all operation channels stay within the operating frequency block or frequency block group.


**FR1 n14****<SISO Mode> (Ant. 8)****Peak-to-Average Ratio**

Mode	FR1 n14 / 10MHz / DFT-S OFDM				
Mod.	PI/2 BPSK	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	4.26	5.12	6.34	6.48	PASS
Mode	FR1 n14 / 20MHz / DFT-S OFDM				
Mod.	256QAM				Limit: 13dB
RB Size	Full RB				Result
Middle CH	6.84				PASS




FR1 n14 / 10MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK




QPSK




16QAM



64QAM



256QAM




**26dB Bandwidth**

Mode	FR1 n7 : 26dB BW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz					
Mod.	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK				
Middle CH	5.09	5.04	9.79	9.84				
Mod.	16QAM		16QAM					
Middle CH	5.09		9.81					




FR1 n7 / 5MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK



QPSK




16QAM






FR1 n7 / 10MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK



QPSK



16QAM




**Occupied Bandwidth**

Mode	FR1 n14 : 99%OBW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz					
Mod.	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK				
Middle CH	4.48	4.49	8.95	8.96				
Mod.	16QAM		16QAM					
Middle CH	4.49		8.97					




FR1 n14 / 5MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




02:19:02 PM 03/28/2024

QPSK



02:19:53 PM 03/28/2024

16QAM




02:20:43 PM 03/28/2024



FR1 n14 / 10MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK

QPSK



Type	Ref	Freq	Value	Function	Function Result
M1	1	790.602 MHz	16.09 dBm	Occ Bw	8.953 059 907 MHz
T1	1	788.324 8 MHz	10.24 dBm	Occ Bw Centroid	792.801 361 427 MHz
T2	1	797.277 9 MHz	10.47 dBm	Occ Bw Freq Offset	-158.638 572 628 kHz


02:21:36 PM 03/28/2026



Type	Ref	Freq	Value	Function	Function Result
M1	1	793.360 MHz	15.07 dBm	Occ Bw	8.964 847 964 MHz
T1	1	788.317 4 MHz	10.28 dBm	Occ Bw Centroid	792.799 811 843 MHz
T2	1	797.282 2 MHz	10.37 dBm	Occ Bw Freq Offset	-200.188 157 031 kHz

02:22:26 PM 03/28/2026

16QAM



Type	Ref	Freq	Value	Function	Function Result
M1	1	792.760 MHz	15.59 dBm	Occ Bw	8.972 767 688 MHz
T1	1	788.313 5 MHz	9.13 dBm	Occ Bw Centroid	792.799 932 093 MHz
T2	1	797.286 3 MHz	8.64 dBm	Occ Bw Freq Offset	-200.067 907 085 kHz


02:23:17 PM 03/28/2026

Conducted Band Edge

FR1 n14 / 5MHz / DFT-S OFDM / PI/2 BPSK


Lowest Band Edge / 1RB0

Highest Band Edge / 1RBmax



Lowest Band Edge / Full RB

Highest Band Edge / Full RB







FR1 n14 / 5MHz / DFT-S OFDM / QPSK



Lowest Band Edge / 1RB0

Highest Band Edge / 1RBmax



Lowest Band Edge / Full RB


Highest Band Edge / Full RB






FR1 n14 / 10MHz / DFT-s-OFDM / PI/2 BPSK

Middle Band Edge / Full RB



FR1 n14 / 10MHz / DFT-s-OFDM / QPSK

Middle Band Edge / Full RB




**Unwanted Emission (MASK)**

FR1 n14 / 5MHz / DFT-S OFDM / PI/2 BPSK


Lowest Channel

1RB0

1RBmax




04:14:16 PM 04/08/2026



10:25:10 PM 04/14/2026

Full RB



04:15:06 PM 04/08/2026





FR1 n14 / 5MHz / DFT-S OFDM / PI/2 BPSK


Middle Channel

1RB0

1RBmax



Full RB







FR1 n14 / 5MHz / DFT-S OFDM / PI/2 BPSK


Highest Channel

1RB0

1RBmax



Full RB







FR1 n14 / 5MHz / DFT-S OFDM / QPSK


Lowest Channel

1RB0

1RBmax



Full RB







FR1 n14 / 5MHz / DFT-S OFDM / QPSK


Middle Channel

1RB0

1RBmax



Full RB







FR1 n14 / 5MHz / DFT-S OFDM / QPSK


Highest Channel

1RB0

1RBmax



Full RB






FR1 n14 / 10MHz / DFT-S OFDM / BPSK

Middle Channel


Full RB



FR1 n14 / 10MHz / DFT-S OFDM / QPSK

Middle Channel

Full RB







Conducted Spurious Emission


FR1 n14 / 5MHz / DFT-S OFDM / QPSK / 1RB1

Lowest Channel

Middle Channel



Highest Channel



Frequency Stability

Test Conditions		FR1 n14 (BPSK) / Middle Channel 10M			
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Frequency Offset (Δf) (Hz)	Within Authorized Frequency Block(Hz)	Result
50	Normal Voltage	0.0077	-6.1	Yes	PASS
40	Normal Voltage	0.0086	-6.8	Yes	
30	Normal Voltage	0.0052	4.1	Yes	
20(Ref.)	Normal Voltage	0.0000	0	Yes	
10	Normal Voltage	0.0097	7.7	Yes	
0	Normal Voltage	0.0110	8.7	Yes	
-10	Normal Voltage	0.0057	4.5	Yes	
-20	Normal Voltage	0.0006	-0.5	Yes	
-30	Normal Voltage	0.0058	-4.6	Yes	
20	Maximum Voltage	0.0119	9.4	Yes	
20	Normal Voltage	0.0000	0	Yes	
20	Minimum Voltage	0.0078	6.2	Yes	

$|\text{MAX}(\Delta f)| = 9.4\text{Hz}$

Frequency Stability	Frequency (MHz)	Limit Line	Result
$f_L - \text{MAX}(\Delta f) $	788.219991	$\geq 788 \text{ MHz}$	PASS
$f_H + \text{MAX}(\Delta f) $	797.515109	$\leq 799 \text{ MHz}$	

Note:

1. Normal Voltage = 3.91 V. ; Minimum Voltage = 3.91 V. ; Maximum Voltage = 4.45 V.
2. The frequency fundamental emissions stay within the authorized frequency block.
3. The frequency variation is sufficient to ensure that the occupied bandwidth of all operation channels stay within the operating frequency block or frequency block group.


**FR1 n25****<SISO Mode>****Peak-to-Average Ratio**

Mode	FR1 n25 / 20MHz / DFT-S OFDM				
Mod.	PI/2 BPSK	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	4.02	4.56	5.62	5.98	PASS
Mode	FR1 n25 / 20MHz / DFT-S OFDM				
Mod.	256QAM				Limit: 13dB
RB Size	Full RB				Result
Middle CH	6.74				PASS




FR1 n25 / 20MHz / DFT-S OFDM / Middle Channel / Full RB


PI/2 BPSK




QPSK




16QAM



64QAM



256QAM



**26dB Bandwidth**

Mode	FR1 n25 : 26dB BW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK
Middle CH	5.28	5.14	9.73	9.91	14.60	14.62	19.32	19.43
Mod.	16QAM		16QAM		16QAM		16QAM	
Middle CH	5.20		9.94		14.56		19.36	
BW	25MHz		30MHz		35MHz		40MHz	
Mod.	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK	PI/2 BPSK	QPSK
Middle CH	24.36	24.41	31.01	31.20	34.69	34.74	41.05	41.20
Mod.	16QAM		16QAM		16QAM		16QAM	
Middle CH	24.32		31.05		34.66		41.26	