

RF Exposure Report

Report No.: SA151104E03

FCC ID: UZ7VC80

Test Model: VC80

Received Date: Nov. 04, 2015

Test Date: Nov. 17 to 28, 2015

Issued Date: Dec. 16, 2015

Applicant: Zebra Technologies Corporation

Address: 1 Zebra Plaza, Holtsville, NY 11742

Manufacturer: Zebra Technologies Corporation

Address: 1 Zebra Plaza, Holtsville, NY 11742

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
3 Calculation Result Of Maximum Conducted Power	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA151104E03	Original release.	Dec. 16, 2015

1 Certificate of Conformity

Product: Vehicle Computer

Brand: Zebra

Test Model: VC80

Sample Status: ENGINEERING SAMPLE

Applicant: Zebra Technologies Corporation

Test Date: Nov. 17 to 18, 2015

Standards: FCC Part 2 (Section 2.1091)

447498 D01 General RF Exposure Guidance v06

IEEE Std C95.1-2005

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Dec. 16, 2015
Elsie Hsu / Specialist

Approved by :  , **Date:** Dec. 16, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No	PCB Chain No.	Model	Antenna Type	Antenna Connector	Antenna Gain (dBi) Exclude cable loss	Internal cable loss (dB)	External cable loss (dB)	Antenna Gain (dBi) Include cable loss	Internal cable length (mm)	External cable length (mm)	Frequency (GHz to GHz)
1	Int.Chain0	AN000097A01	Patch	i-pex (MHFL4)	5	NA	NA	5	NA	NA	2.4~2.4835
					5	NA	NA	5	NA	NA	5.15~5.85
	Int.Chain1				5	NA	NA	5	NA	NA	2.4~2.4835
					5	NA	NA	5	NA	NA	5.15~5.85
2	ext.Chain0	AN2010	Monopole	RPSMA	2	0.6	1.8	-0.4	147	2850	2.4~2.4835
					2	0.9	2.6	-1.5	147	2850	5.15~5.85
	ext.Chain1				2	0.6	1.8	-0.4	147	2850	2.4~2.4835
					2	0.9	2.6	-1.5	147	2850	5.15~5.85
3	ext.Chain0	AN2020	Monopole	RPSMA	5	0.6	1.8	2.6	147	2850	2.4~2.4835
	ext.Chain1				5	0.6	1.8	2.6	147	2850	2.4~2.4835
4	ext.Chain0	AN2030	Dipole	RPSMA	2	0.6	NA	1.4	147	NA	2.4~2.4835
					3.7	0.9	NA	2.8	147	NA	5.15~5.85
	ext.Chain1				2	0.6	NA	1.4	147	NA	2.4~2.4835
					3.7	0.9	NA	2.8	147	NA	5.15~5.85
5	ext.Chain0	AN2040	Dipole	RPSMA	2	0.6	NA	1.4	147	NA	2.4~2.4835
	ext.Chain1				2	0.6	NA	1.4	147	NA	2.4~2.4835

Note:

1. For 1TX configuration mode: max gain was selected as representative antenna.

3 Calculation Result Of Maximum Conducted Power

For WLAN:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2472	764.224	5	20	0.48078	1
5180-5240	199.739	5	20	0.12566	1
5260-5320	193.688	5	20	0.12185	1
5500-5720	208.673	5	20	0.13128	1
5745-5825	201.444	5	20	0.12673	1

For BT-EDR:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	2.410	5	20	0.00152	1

For BT-LE:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	1.811	5	20	0.00114	1

--- END ---