FCC RADIO TEST REPORT

FCC ID	:	UZ7WCMTB
Equipment	:	Touch Computer
Brand Name	:	Zebra
Model Name	:	WCMTB
Applicant	:	Zebra Technologies Corporation 1 Zebra Plaza, Holtsville, NY 11742
Manufacturer	:	Zebra Technologies Corporation 1 Zebra Plaza, Holtsville, NY 11742
Standard	:	FCC Part 15 Subpart C §15.225

The product was received on Feb. 13, 2023 and testing was performed from Feb. 23, 2023 to Mar. 07, 2023. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1. General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 6
1.3 Modification of EUT 6
1.4 Testing Location 6
1.5 Applicable Standards 7
2. Test Configuration of Equipment Under Test **8**
2.1 Descriptions of Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Table for Supporting Units 10
2.4 EUT Operation Test Setup 10
3. Test Results **11**
3.1 AC Power Line Conducted Emissions Measurement 11
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement 13
3.3 Frequency Stability Measurement 14
3.4 Field Strength of Fundamental Emissions and Mask Measurement 15
3.5 Radiated Emissions Measurement 17
3.6 Antenna Requirements 20
4. List of Measuring Equipment **21**
5. Uncertainty of Evaluation **22**
Appendix A. Test Results of Conducted Emission Test
Appendix B. Test Results of Near Field Test Items
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
Appendix C. Test Results of Radiated Test Items
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)
Appendix D. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR311909D	01	Initial issue of report	Mar. 31, 2023
FR311909D	02	Add Sample 2 information This report is an updated version, replacing the report issued on Mar. 31, 2023.	Apr. 03, 2023

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	17.45 dB under the limit at 0.184 MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 20.85 dBμV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	6.02 dB under the limit at 40.530 MHz
3.6	15.203	Antenna Requirements	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. Please refer to the section ” Uncertainty of Evaluation ” for measurement uncertainty.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Dewi Huang

1. General Description

1.1 Product Feature of Equipment Under Test

Product Information	
Equipment	Touch Computer
Brand Name	Zebra
Model Name	WCMTB
Sample 1	Scanner(SE4710)
Sample 2	Scanner(SE5500)
FCC ID	UZ7WCMTB
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/NFC/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	DV
SW Version	13-09-16.00-TG-U00-STD-ATH-04
FW Version	FUSION_QA_4_1.0.0.017_T
MFD	16MAR23
EUT Stage	Identical Prototype

Remark:

1. The EUT's information above was declared by manufacturer.
2. All the tests were performed with Sample 1.

Specification of Accessories				
Battery 1 Standard Battery (3800mAh)	**Brand Name**	Zebra	**Model Number**	BT-000473

Support Unit used in test configuration and system				
Battery 2 Standard BLE Beacon Battery (3800mAh)	**Brand Name**	Zebra	**Model Number**	BT-000473B
Battery 3 Extended Battery (5200mAh)	**Brand Name**	Zebra	**Model Number**	BT-000473E
Adapter USB Wall Charger	**Brand Name**	Zebra	**Part Number**	PWR-WUA5V12W0US
Earphone 1 3.5mm PTT Headset	**Brand Name**	Zebra	**Part Number**	HDST-35MM-PTT1-01
Earphone 2 USB-C Audio Headset	**Brand Name**	Zebra	**Part Number**	HDST-USBC-PTT1-01
USB Cable (Type C to Type A)	**Brand Name**	Zebra	**Part Number**	CBL-TC5X-USBC2A-01
Type C-Audio Cable (Type C to 3.5mm)	**Brand Name**	Zebra	**Part Number**	ADP-USBC-35MM1-01
Trigger Handle	**Brand Name**	Zebra	**Part Number**	TRG-TC2L-SNP1-01

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.64 kHz
99%OBW	2.24 kHz
Antenna Type	Coil Antenna
Type of Modulation	ASK

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	**Sporton Site No.**		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	Eric Wu	Calvin Wang	Jesse Wang and Stan Hsieh
Temperature	20.4~22.4℃	23~26℃	21.7~23.6℃
Relative Humidity	54.3~56.3%	45~55%	57.8~64.3%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in reader mode with NFC tag (four NFC type A, B, F, V) and without reading tag. Based on the highest field strength of fundamental and spurious emissions, the worst case type (type B) was recorded in this report.

The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

Test Cases	
AC Conducted Emission	Mode 1: NFC Link + Camera (Rear) + Battery 1 + USB Cable (Charging with Adapter) for Sample 1

2.2 Connection Diagram of Test System

<AC Conducted Emission Mode>



<NFC Tx Mode>



2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	NFC Card	N/A	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT is programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmitting signal (Power Level: Default) at 13.56MHz and is placed around 1 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB and 99% emission bandwidth in the specific band 13.553~13.567 MHz.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max Hold Mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20 dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed by using a new battery.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT has transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ±100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

Remark:

1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna is fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9 kHz.
   Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated test below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna is varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower is scanned (from 1 M to 4 M) and then the turntable is rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30 MHz, loop antenna has to be used for measurement and the recorded data shall be QP measured by receiver.
8. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.

3.5.5 Test Setup

For radiated test below 30MHz



For radiated test above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35419 & 03	30MHz~1GHz	Apr. 24, 2022	Feb. 23, 2023~ Feb. 24, 2023	Apr. 23, 2023	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 03, 2022	Feb. 23, 2023~ Feb. 24, 2023	Oct. 02, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15682/4	30MHz to 18GHz	Feb. 22, 2023	Feb. 23, 2023~ Feb. 24, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4	9kHz to 18GHz	Feb. 22, 2023	Feb. 23, 2023~ Feb. 24, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4	9kHz to 18GHz	Feb. 22, 2023	Feb. 23, 2023~ Feb. 24, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Feb. 23, 2023~ Feb. 24, 2023	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Feb. 23, 2023~ Feb. 24, 2023	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Feb. 23, 2023~ Feb. 24, 2023	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Feb. 23, 2023~ Feb. 24, 2023	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Feb. 23, 2023~ Feb. 24, 2023	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Mar. 07, 2022	Feb. 23, 2023~ Feb. 24, 2023	Mar. 06, 2023	Radiation (03CH07-HY)
Signal Analyzer	Keysight	N9010B	MY60241058	N/A	Jul. 07, 2022	Feb. 23, 2023~ Feb. 24, 2023	Jul. 06, 2023	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Feb. 23, 2023~ Feb. 24, 2023	Sep. 19, 2023	Radiation (03CH07-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Mar. 07, 2023	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2022	Mar. 07, 2023	Nov. 30, 2023	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2022	Mar. 07, 2023	Nov. 16, 2023	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 17, 2022	Mar. 07, 2023	Nov. 16, 2023	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Mar. 07, 2023	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Aug. 01, 2022	Mar. 07, 2023	Jul. 31, 2023	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 29, 2022	Mar. 07, 2023	Dec. 28, 2023	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303B	TP210073	N/A	Mar. 18, 2022	Feb. 28, 2023	Mar. 17, 2023	Near Field (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 27, 2022	Feb. 28, 2023	Sep. 26, 2023	Near Field (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 07, 2022	Feb. 28, 2023	Sep. 06, 2023	Near Field (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~4A	Sep. 29, 2022	Feb. 28, 2023	Sep. 28, 2023	Near Field (TH03-HY)
Nearby field probe	LANGER EMV-TECHNIK	LF-U5	02-559	100 kHz up to 50 MHz	Apr. 04, 2022	Feb. 28, 2023	Apr. 03, 2023	Near Field (TH03-HY)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.50 dB

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.80 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.50 dB

Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Calvin Wang	Temperature :	23~26℃
		Relative Humidity :	45~55%

Original

Report NO :	311909
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.183750	---	34.97	54.31	19.34	L1	OFF	19.9
0.183750	46.86	---	64.31	17.45	L1	OFF	19.9
0.195000	---	33.66	53.82	20.16	L1	OFF	19.9
0.195000	45.76	---	63.82	18.06	L1	OFF	19.9
0.260250	---	30.93	51.42	20.49	L1	OFF	19.9
0.260250	42.76	---	61.42	18.66	L1	OFF	19.9
0.546000	---	25.03	46.00	20.97	L1	OFF	19.9
0.546000	30.70	---	56.00	25.30	L1	OFF	19.9
3.520500	---	26.11	46.00	19.89	L1	OFF	20.0
3.520500	28.99	---	56.00	27.01	L1	OFF	20.0
13.560000	---	54.95	50.00	-4.95	L1	OFF	20.4
13.560000	55.47	---	60.00	4.53	L1	OFF	20.4
16.658250	---	27.68	50.00	22.32	L1	OFF	20.4
16.658250	30.73	---	60.00	29.27	L1	OFF	20.4

Report NO : 311909
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.179250	---	32.35	54.52	22.17	N	OFF	19.9
0.179250	44.26	---	64.52	20.26	N	OFF	19.9
0.192750	---	32.21	53.92	21.71	N	OFF	19.9
0.192750	42.70	---	63.92	21.22	N	OFF	19.9
0.255750	---	31.34	51.57	20.23	N	OFF	19.9
0.255750	40.18	---	61.57	21.39	N	OFF	19.9
0.408750	---	25.63	47.67	22.04	N	OFF	19.9
0.408750	34.33	---	57.67	23.34	N	OFF	19.9
3.516000	---	26.86	46.00	19.14	N	OFF	20.0
3.516000	31.51	---	56.00	24.49	N	OFF	20.0
6.533250	---	27.51	50.00	22.49	N	OFF	20.1
6.533250	30.17	---	60.00	29.83	N	OFF	20.1
13.560000	---	57.34	50.00	-7.34	N	OFF	20.4
13.560000	57.64	---	60.00	2.36	N	OFF	20.4

Terminal

Report NO :	311909
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	26.53	50.00	23.47	L1	OFF	20.4
13.560000	29.10	---	60.00	30.90	L1	OFF	20.4

Report NO :	311909
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	26.34	50.00	23.66	N	OFF	20.4
13.560000	28.95	---	60.00	31.05	N	OFF	20.4

Appendix B. Test Results of Near Field Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
			
20dB Bandwidth (kHz)	2.640	**99% OccupiedBW(kHz)**	2.240
Frequency range (MHz)	**f_L > 13.553**	13.55834	**Test Result**
	f_H < 13.567	13.56098	**Complies**

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
3.85	13.559660	**-20**	**0**	13.559770
3.45	13.559660		**2**	13.559770
4.41	13.559660		**5**	13.559760
			10	13.559770
		-10	**0**	13.559770
			2	13.559770
			5	13.559770
			10	13.559770
		0	**0**	13.559760
			2	13.559760
			5	13.559760
			10	13.559760
		10	**0**	13.559750
			2	13.559740
			5	13.559740
			10	13.559730
		20	**0**	13.559720
			2	13.559700
			5	13.559700
			10	13.559680
		30	**0**	13.559660
			2	13.559660
			5	13.559650
			10	13.559640
		40	**0**	13.559630
			2	13.559630
			5	13.559620
			10	13.559620

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
		50	0	13.559620
			2	13.559620
			5	13.559620
			10	13.559620
Max.Deviation (MHz)	-0.000340	Max.Deviation (MHz)		-0.000380
Max.Deviation (ppm)	-25.0737	Max.Deviation (ppm)		-28.0236
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx with Battery 1	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(H)_100488 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBμV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	20.85	40	-63.15	84	41.05	19.4	0.4	100	0	QP

Test Mode :	NFC Tx with Battery 1	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(V)_100488 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	18.98	40	-65.02	84	39.18	19.4	0.4	100	92	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

Test Mode :	NFC Tx with Battery 2	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(H)_100488 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	20.84	40	-63.16	84	41.04	19.4	0.4	100	0	QP

Test Mode :	NFC Tx with Battery 2	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(V)_100488 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	18.84	40	-65.16	84	39.04	19.4	0.4	100	88	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

Test Mode :	NFC Tx with Battery 3	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(H)_100488 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	20.81	40	-63.19	84	41.01	19.4	0.4	100	6	QP

Test Mode :	NFC Tx with Battery 3	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(V)_100488 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	18.7	40	-65.3	84	38.9	19.4	0.4	100	93	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx with Battery 1	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.0192	-21.24	80	-63.18	41.94	38.92	19.82	0.02	-	-	Average
0.06	-35.16	80	-67.2	32.04	25.11	19.7	0.03	-	-	Average
0.09626	-42.35	80	-70.29	27.94	17.97	19.64	0.04	-	-	QP
0.15	-38.27	80	-62.35	24.08	22.08	19.6	0.05	-	-	Average
0.15102	-31.16	80	-55.18	24.02	29.19	19.6	0.05	-	-	Average
0.59514	-3.25	40	-35.36	32.11	17.2	19.5	0.05	-	-	QP
13.56	20.85	40	-8.65	29.5	41.05	19.4	0.4	-	-	QP
13.776	-0.13	40	-29.63	29.5	20.06	19.4	0.41	-	-	QP
17.332	-3.13	40	-32.63	29.5	16.9	19.5	0.47	-	-	QP
25.675	-4.29	40	-33.79	29.5	14.88	20.17	0.66	-	-	QP

Test Mode :	NFC Tx with Battery 1	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.0192	-22.22	80	-64.16	41.94	37.94	19.82	0.02	-	-	Average
0.06354	-37.21	80	-68.75	31.54	23.06	19.7	0.03	-	-	Average
0.09898	-43.99	80	-71.68	27.69	16.36	19.61	0.04	-	-	QP
0.15	-31.49	80	-55.57	24.08	28.86	19.6	0.05	-	-	Average
0.15	-37.92	80	-62	24.08	22.43	19.6	0.05	-	-	Average
4.688	0.87	40	-28.63	29.5	21.11	19.5	0.26	-	-	QP
13.112	-3.64	40	-33.14	29.5	16.56	19.4	0.4	-	-	QP
13.56	18.98	40	-10.52	29.5	39.18	19.4	0.4	-	-	QP
16.072	-4.14	40	-33.64	29.5	16	19.41	0.45	-	-	QP
26.465	-3.8	40	-33.3	29.5	15.28	20.2	0.72	-	-	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

Test Mode :	NFC Tx with Battery 2	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01915	-21.51	80	-63.47	41.96	38.65	19.82	0.02	-	-	Average
0.06837	-36.44	80	-67.35	30.91	23.83	19.7	0.03	-	-	Average
0.09592	-41.07	80	-69.04	27.97	19.25	19.64	0.04	-	-	QP
0.14996	-38.8	80	-62.88	24.08	21.55	19.6	0.05	-	-	Average
0.15034	-30.39	80	-54.45	24.06	29.96	19.6	0.05	-	-	Average
0.50502	-2.45	40	-35.99	33.54	18.01	19.5	0.04	-	-	QP
13.344	-1.57	40	-31.07	29.5	18.63	19.4	0.4	-	-	QP
13.56	20.84	40	-8.66	29.5	41.04	19.4	0.4	-	-	QP
16.702	-3.95	40	-33.45	29.5	16.12	19.47	0.46	-	-	QP
28.375	-4.58	40	-34.08	29.5	14.42	20.12	0.88	-	-	QP

Test Mode :	NFC Tx with Battery 2	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.05	-22.25	80	-55.87	33.62	38.02	19.7	0.03	-	-	Average
0.06828	-37.88	80	-68.8	30.92	22.39	19.7	0.03	-	-	Average
0.0914	-44.37	80	-72.76	28.39	15.9	19.69	0.04	-	-	QP
0.14996	-38.63	80	-62.71	24.08	21.72	19.6	0.05	-	-	Average
0.15204	-31.03	80	-55	23.97	29.32	19.6	0.05	-	-	Average
5.477	-1.89	40	-31.39	29.5	18.34	19.5	0.27	-	-	QP
8.168	-1.81	40	-31.31	29.5	18.4	19.48	0.31	-	-	QP
13.56	18.84	40	-10.66	29.5	39.04	19.4	0.4	-	-	QP
17.341	-4.14	40	-33.64	29.5	15.89	19.5	0.47	-	-	QP
25.73	-4.36	40	-33.86	29.5	14.81	20.17	0.66	-	-	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

Test Mode :	NFC Tx with Battery 3	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.05006	-21.78	80	-55.4	33.62	38.49	19.7	0.03	-	-	Average
0.06741	-37.56	80	-68.59	31.03	22.71	19.7	0.03	-	-	Average
0.09604	-41.74	80	-69.7	27.96	18.58	19.64	0.04	-	-	QP
0.14996	-38.84	80	-62.92	24.08	21.51	19.6	0.05	-	-	Average
0.15136	-30.25	80	-54.25	24	30.1	19.6	0.05	-	-	Average
0.49751	-2.47	40	-36.14	33.67	17.99	19.5	0.04	-	-	QP
12.064	-4.22	40	-33.72	29.5	16	19.4	0.38	-	-	QP
13.56	20.81	40	-8.69	29.5	41.01	19.4	0.4	-	-	QP
20.968	-3.64	40	-33.14	29.5	16.03	19.8	0.53	-	-	QP
26.83	-4.47	40	-33.97	29.5	14.58	20.2	0.75	-	-	QP

Test Mode :	NFC Tx with Battery 3	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.05	-22.34	80	-55.96	33.62	37.93	19.7	0.03	-	-	Average
0.06348	-37.73	80	-69.28	31.55	22.54	19.7	0.03	-	-	Average
0.1001	-43.7	80	-71.3	27.6	16.66	19.6	0.04	-	-	QP
0.14996	-37.98	80	-62.06	24.08	22.37	19.6	0.05	-	-	Average
0.15204	-30.73	80	-54.7	23.97	29.62	19.6	0.05	-	-	Average
0.49751	-2.5	40	-36.17	33.67	17.96	19.5	0.04	-	-	QP
13.344	-1.95	40	-31.45	29.5	18.25	19.4	0.4	-	-	QP
13.56	18.7	40	-10.8	29.5	38.9	19.4	0.4	-	-	QP
19.285	-3.45	40	-32.95	29.5	16.42	19.63	0.5	-	-	QP
28.725	-4.46	40	-33.96	29.5	14.57	20.06	0.91	-	-	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx with Battery 1	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	31.75	-8.25	40	41.55	18.99	1.16	29.95	-	-	Peak
94.8	27.19	-16.31	43.5	40.45	15.15	1.61	30.02	-	-	Peak
216.84	34.58	-11.42	46	47.6	14.61	2.37	30	-	-	Peak
787.2	30.06	-15.94	46	27.13	27.86	4.69	29.62	-	-	Peak
859.3	31.48	-14.52	46	26.92	28.91	4.89	29.24	-	-	Peak
944.7	33.63	-12.37	46	27.39	29.96	5.13	28.85	-	-	Peak

Test Mode :	NFC Tx with Battery 1	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.53	33.98	-6.02	40	43.61	19.16	1.16	29.95	-	-	Peak
67.8	29.68	-10.32	40	46.1	12.03	1.45	29.9	-	-	Peak
87.51	28.34	-11.66	40	42.68	14.15	1.53	30.02	-	-	Peak
407.1	33.74	-12.26	46	38.37	21.97	3.27	29.87	-	-	Peak
624.1	31.9	-14.1	46	32.09	25.69	4.09	29.97	-	-	Peak
947.5	33.7	-12.3	46	27.27	30.14	5.13	28.84	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBµV/m) = 20 log Emission level (µV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.

Test Mode :	NFC Tx with Battery 2	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.53	33.33	-6.67	40	42.96	19.16	1.16	29.95	-	-	Peak
176.34	28.66	-14.84	43.5	41.36	15.14	2.16	30	-	-	Peak
216.84	32.42	-13.58	46	45.44	14.61	2.37	30	-	-	Peak
407.1	35.24	-10.76	46	39.87	21.97	3.27	29.87	-	-	Peak
569.5	32.19	-13.81	46	32.53	25.77	3.91	30.02	-	-	Peak
955.2	33.85	-12.15	46	26.89	30.6	5.16	28.8	-	-	Peak

Test Mode :	NFC Tx with Battery 2	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	33.64	-6.36	40	43.44	18.99	1.16	29.95	-	-	Peak
149.07	29.63	-13.87	43.5	40.56	17.03	2	29.96	-	-	Peak
216.84	28.83	-17.17	46	41.85	14.61	2.37	30	-	-	Peak
407.1	35.48	-10.52	46	40.11	21.97	3.27	29.87	-	-	Peak
569.5	33.81	-12.19	46	34.15	25.77	3.91	30.02	-	-	Peak
948.9	33.95	-12.05	46	27.41	30.23	5.14	28.83	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBµV/m) = 20 log Emission level (µV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.

Test Mode :	NFC Tx with Battery 3	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	32.87	-7.13	40	42.67	18.99	1.16	29.95	-	-	Peak
89.94	27.92	-15.58	43.5	41.81	14.56	1.54	29.99	-	-	Peak
216.84	31.97	-14.03	46	44.99	14.61	2.37	30	-	-	Peak
407.1	35.37	-10.63	46	40	21.97	3.27	29.87	-	-	Peak
569.5	30.03	-15.97	46	30.37	25.77	3.91	30.02	-	-	Peak
958	33.7	-12.3	46	26.68	30.65	5.16	28.79	-	-	Peak

Test Mode :	NFC Tx with Battery 3	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	33.48	-6.52	40	43.28	18.99	1.16	29.95	-	-	Peak
407.1	35.58	-10.42	46	40.21	21.97	3.27	29.87	-	-	Peak
569.5	33.88	-12.12	46	34.22	25.77	3.91	30.02	-	-	Peak
953.1	33.81	-12.19	46	26.98	30.49	5.15	28.81	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBµV/m) = 20 log Emission level (µV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.