



Neutron Engineering Inc.

FCC&IC Radio Test Report

FCC ID: UZZSFQ10

IC: 7633A-SFQ10

This report concerns (check one): ☐ Original Grant ☒ Class II Change

Issued Date : May.19, 2014
Project No. : 1403C077B
Equipment : Pocket Kick
Model Name : SFQ-10
Applicant : Beautiful Enterprise Co., Ltd.
Address : 27th Floor, Beautiful Group Tower, 77
Connaught Road Central, Hong Kong

Tested by: Neutron Engineering Inc. EMC Laboratory
Date of Receipt: May. 08, 2014
Date of Test: May. 08, 2014 ~ May. 16, 2014

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

Neutron Engineering Inc.

No.3,Jinshagang 1st Road, ShiXia,
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (NML) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
REPORT ISSUED HISTORY	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
3.5 DESCRIPTION OF SUPPORT UNITS	12
4. EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.1.6 EUT TEST CONDITIONS	14
4.1.7 TEST RESULTS	14
5 RADIATED EMISSION MEASUREMENT	17
5.1 RADIATED EMISSION LIMITS	17
5.1.1 TEST PROCEDURE	18
5.1.2 DEVIATION FROM TEST STANDARD	18
5.1.3 TEST SETUP	19
5.1.4 EUT OPERATING CONDITIONS	20
5.1.5 EUT TEST CONDITIONS	20
5.1.6 TEST RESULTS (BELOW 30MHZ)	21
5.1.7 TEST RESULTS: 30MHZ - 1000MHZ	22
5.1.8 TEST RESULTS(ABOVE 1000 MHZ)	35
6. MEASUREMENT INSTRUMENTS LIST AND SETTING	50
7. EUT TEST PHOTO	51



REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
NEI-FICP-1-1403C077	Original Issue.	Mar. 24, 2014
NEI- FICP-1-1403C077B	Original Issue. Compared with previous report (NEI-FICP-1-1403C077) The antenna type is change and the again is change to 2.06dbi. Only updated the Conducted Emission; Radiated Spurious Emission test data and include in the test report.	May. 19, 2014



1. CERTIFICATION

Equipment : Pocket Kick
Brand Name : **SOUNDFREAQ®**
Model Name : SFQ-10
Applicant : Beautiful Enterprise Co., Ltd.
Manufacture : Beautiful Enterprise Co., Ltd.
Address : 27th Floor, Beautiful Group Tower, 77 Connaught Road Central, Hong Kong
Factory : Shenzhen Synchron Electronics Co., Ltd.
Address : No. 9 Mei Li Road, Xia Mei Lin, Fu Tian Area, Shenzhen, Guangdong, China
Date of Test : May. 08, 2014 ~ May. 16, 2014
Test Item : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart C(15.247) / ANSI C63.4 : 2009
: FCC Public Notice DA 00-705, March 30, 2000.
: Canada RSS-210:2010
RSS-GEN Issue 3, Dec 2010

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FICP-1-1403C077B) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): 47 CFR Part 15, Subpart C: 2012; Canada RSS-210:2010; RSS-GEN Issue 3, Dec 2010				
Standard(s) Section		Test Item	Judgment	Remark
FCC	IC			
15.207	RSS-GEN Issue 3, Dec 2010 7.2.4	Conducted Emission	PASS	
15.247(d)	RSS-210, Issue 8, Annex 8, A8.5	Antenna conducted Spurious Emission	N/A	
15.247 (a)(1)	RSS-210, Issue 8, Annex 8, A8.1(b)	Hopping Channel Separation	N/A	
15.247 (b)(1)	RSS-210, Issue 8, Annex 8, A8.1(b)	Peak Output Power	N/A	
15.247(d) 15.209	RSS-210, Issue 8, Annex 8, Section 8.5	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	RSS-210, Issue 8, Annex 8, A8.1(d)	Number of Hopping Frequency	N/A	
15.247 (a)(1)(iii)	RSS-210, Issue 8, Annex 8, A8.1(d)	Dwell Time	N/A	
15.205	RSS-GEN Issue 3, Dec 2010 7.2.2	Restricted Bands	N/A	
15.203	-	Antenna Requirement	N/A	

Note:

- (1) "N/A" denotes test is not applicable in this test report
- (2) According to FCC Public Notice DA 00-705, March 30, 2000.



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dong Guan, China.523792

Neutron's test firm number for FCC: 319330

Neutron's test firm number for IC: 4428B-1

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	Note
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	Note
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Pocket Kick	
Brand Name	SOUNDFREQ®	
Model Name	SFQ-10	
Model Difference	N/A	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) π /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	More details of EUT technical specification, please refer to the User's Manual.	
Power Source	DC voltage supplied from USB	
Power Rating	DC5V 1A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	internal	N/A	2.06

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode Note (1)
Mode 2	Bluetooth

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 2	Bluetooth

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode Note (1)

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

3.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING


During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software version	Bluetest		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters-1Mbps	61	50	48
Parameters-3Mbps	60	51	54




3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted TX Mode:



Control Room

Radiated TX Mode:



Control Room



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
-	-	-	-	-	-	

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency (MHz)	Class A (dBUV)		Class B (dBUV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS


Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 'Note'. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.



Test Mode: Bluetooth

Line




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1970	31.08	9.65	40.73	63.74	-23.01	peak	
2	0.2633	22.11	9.66	31.77	61.33	-29.56	peak	
3	0.3297	18.53	9.67	28.20	59.46	-31.26	peak	
4	0.3961	17.00	9.68	26.68	57.93	-31.25	peak	
5	2.3141	15.52	9.84	25.36	56.00	-30.64	peak	
6 *	17.3905	28.97	10.29	39.26	60.00	-20.74	peak	



Test Mode:	Bluetooth
------------	-----------

Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1970	32.43	9.71	42.14	63.74	-21.60	peak	
2		0.2633	22.43	9.72	32.15	61.33	-29.18	peak	
3		0.3297	20.62	9.72	30.34	59.46	-29.12	peak	
4		0.3961	17.74	9.73	27.47	57.93	-30.46	peak	
5	*	17.6484	28.06	10.47	38.53	60.00	-21.47	peak	
6		27.1641	19.22	10.62	29.84	60.00	-30.16	peak	



5 RADIATED EMISSION MEASUREMENT

5.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) & RSS-210 section 2.2& Annex 8 (A8.5), then the 15.209(a) & RSS-Gen limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) =20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector



5.1.1 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.1.2 DEVIATION FROM TEST STANDARD


No deviation

5.1.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz




(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



Note: The antenna can be moved between 1 to 4 meters above the ground.

(C) For radiated emissions below 30MHz



5.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz



5.1.6 TEST RESULTS (BELOW 30MHZ)

Test Mode:	TX Mode
------------	---------

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.00948	0°	68.35	24.30	92.65	128.07	-35.42	AVG
0.00948	0°	72.35	24.30	96.65	148.07	-51.42	PEAK
0.0141	0°	70.35	24.30	94.65	124.62	-29.97	AVG
0.0141	0°	79.35	24.30	103.65	144.62	-40.97	PEAK
0.0252	0°	56.36	23.97	80.33	119.58	-39.25	AVG
0.0252	0°	60.12	23.97	84.09	139.58	-55.49	PEAK
0.0331	0°	61.36	23.47	84.83	117.21	-32.38	AVG
0.0331	0°	65.38	23.47	88.85	137.21	-48.36	PEAK
0.572	0°	18.72	20.03	38.75	72.46	-33.71	QP
1.7545	0°	18.95	19.52	38.47	69.54	-31.07	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.00945	90°	76.35	24.30	100.65	128.10	-27.45	AVG
0.00945	90°	82.36	24.30	106.66	148.10	-41.44	PEAK
0.0242	90°	56.38	24.03	80.41	119.93	-39.51	AVG
0.0242	90°	59.35	24.03	83.38	139.93	-56.54	PEAK
0.0321	90°	57.35	23.53	80.88	117.47	-36.59	AVG
0.0321	90°	58.35	23.53	81.88	137.47	-55.59	PEAK
0.0435	90°	59.35	22.81	82.16	114.83	-32.67	AVG
0.0435	90°	63.35	22.81	86.16	134.83	-48.67	PEAK
0.4919	90°	17.45	19.82	37.27	73.77	-36.50	QP
1.7163	90°	18.63	19.53	38.16	69.54	-31.38	QP

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.



5.1.7 TEST RESULTS: 30MHZ - 1000MHZ


Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.



Test Mode: TX 2402MHz _CH00_1Mbps

Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	109.5400	30.54	-14.80	15.74	43.50	-27.76	peak	
2	209.4500	35.28	-15.25	20.03	43.50	-23.47	peak	
3 *	412.1800	39.71	-9.64	30.07	46.00	-15.93	peak	
4	646.9200	30.40	-5.72	24.68	46.00	-21.32	peak	
5	804.0600	29.58	-3.15	26.43	46.00	-19.57	peak	
6	994.1800	28.82	0.16	28.98	54.00	-25.02	peak	



Test Mode: TX 2402MHz _CH00_1Mbps

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		157.0700	30.47	-13.67	16.80	43.50	-26.70	peak	
2		210.4200	35.10	-15.24	19.86	43.50	-23.64	peak	
3		412.1800	38.25	-9.64	28.61	46.00	-17.39	peak	
4		646.9200	30.44	-5.72	24.72	46.00	-21.28	peak	
5		799.2100	29.55	-3.14	26.41	46.00	-19.59	peak	
6	*	939.8600	30.06	-0.67	29.39	46.00	-16.61	peak	



Test Mode: TX 2441MHz _CH39_1Mbps

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		205.5700	31.91	-15.23	16.68	43.50	-26.82	peak	
2		269.5900	32.95	-13.92	19.03	46.00	-26.97	peak	
3		408.3000	32.64	-9.72	22.92	46.00	-23.08	peak	
4		668.2600	31.85	-5.29	26.56	46.00	-19.44	peak	
5		815.7000	30.13	-3.29	26.84	46.00	-19.16	peak	
6	*	951.5000	29.68	-0.50	29.18	46.00	-16.82	peak	



Test Mode: TX 2441MHz _CH39_1Mbps

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		159.0100	31.20	-13.66	17.54	43.50	-25.96	peak	
2		210.4200	34.71	-15.24	19.47	43.50	-24.03	peak	
3	*	412.1800	38.87	-9.64	29.23	46.00	-16.77	peak	
4		706.0900	30.23	-4.82	25.41	46.00	-20.59	peak	
5		840.9200	30.39	-3.58	26.81	46.00	-19.19	peak	
6		935.0100	29.33	-0.75	28.58	46.00	-17.42	peak	



Test Mode: TX 2480MHz _CH78_ 1Mbps

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		166.7700	35.95	-13.02	22.93	43.50	-20.57	peak	
2		206.5400	35.45	-15.24	20.21	43.50	-23.29	peak	
3	*	412.1800	37.90	-9.64	28.26	46.00	-17.74	peak	
4		649.8300	30.00	-5.58	24.42	46.00	-21.58	peak	
5		739.0700	30.82	-4.88	25.94	46.00	-20.06	peak	
6		979.6300	29.11	-0.05	29.06	54.00	-24.94	peak	



Test Mode: TX 2480MHz _CH78_1Mbps

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		177.4400	30.07	-12.81	17.26	43.50	-26.24	peak	
2		271.5300	31.25	-13.68	17.57	46.00	-28.43	peak	
3		404.4200	31.00	-9.79	21.21	46.00	-24.79	peak	
4		659.5300	30.22	-5.42	24.80	46.00	-21.20	peak	
5		773.0200	30.84	-4.08	26.76	46.00	-19.24	peak	
6	*	953.4400	29.91	-0.48	29.43	46.00	-16.57	peak	



Test Mode: TX 2402MHz _CH00_3Mbps

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		109.5400	30.86	-14.80	16.06	43.50	-27.44	peak	
2		209.4500	35.60	-15.25	20.35	43.50	-23.15	peak	
3		269.5900	32.39	-13.92	18.47	46.00	-27.53	peak	
4	*	412.1800	39.03	-9.64	29.39	46.00	-16.61	peak	
5		804.0600	29.90	-3.15	26.75	46.00	-19.25	peak	
6		994.1800	29.14	0.16	29.30	54.00	-24.70	peak	



Test Mode: TX 2402MHz _CH00_3Mbps

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		210.4200	35.33	-15.24	20.09	43.50	-23.41	peak	
2		412.1800	36.48	-9.64	26.84	46.00	-19.16	peak	
3		544.1000	30.71	-7.97	22.74	46.00	-23.26	peak	
4		646.9200	31.17	-5.72	25.45	46.00	-20.55	peak	
5		799.2100	30.28	-3.14	27.14	46.00	-18.86	peak	
6	*	939.8600	30.79	-0.67	30.12	46.00	-15.88	peak	



Test Mode: TX 2441MHz _CH39_3Mbps

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		205.5700	34.08	-15.23	18.85	43.50	-24.65	peak	
2		269.5900	35.12	-13.92	21.20	46.00	-24.80	peak	
3		408.3000	33.81	-9.72	24.09	46.00	-21.91	peak	
4		703.1800	31.23	-4.81	26.42	46.00	-19.58	peak	
5		815.7000	30.30	-3.29	27.01	46.00	-18.99	peak	
6	*	951.5000	30.85	-0.50	30.35	46.00	-15.65	peak	



Test Mode: TX 2441MHz _CH39_3Mbps

Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	159.0100	31.20	-13.66	17.54	43.50	-25.96	peak	
2	202.6600	33.93	-15.22	18.71	43.50	-24.79	peak	
3	412.1800	35.87	-9.64	26.23	46.00	-19.77	peak	
4	691.5400	32.14	-4.93	27.21	46.00	-18.79	peak	
5	840.9200	31.39	-3.58	27.81	46.00	-18.19	peak	
6 *	935.0100	30.83	-0.75	30.08	46.00	-15.92	peak	



Test Mode: TX 2480MHz _CH78_3Mbps

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		166.7700	36.24	-13.02	23.22	43.50	-20.28	peak	
2		206.5400	36.24	-15.24	21.00	43.50	-22.50	peak	
3	*	416.0600	37.83	-9.57	28.26	46.00	-17.74	peak	
4		539.2500	30.12	-8.23	21.89	46.00	-24.11	peak	
5		739.0700	31.61	-4.88	26.73	46.00	-19.27	peak	
6		992.2400	30.25	0.14	30.39	54.00	-23.61	peak	



Test Mode: TX 2480MHz _CH78_3Mbps

Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		177.4400	31.81	-12.81	19.00	43.50	-24.50	peak	
2		304.5100	30.59	-11.27	19.32	46.00	-26.68	peak	
3		404.4200	31.24	-9.79	21.45	46.00	-24.55	peak	
4		690.5700	30.19	-4.94	25.25	46.00	-20.75	peak	
5		796.3000	30.90	-3.25	27.65	46.00	-18.35	peak	
6	*	953.4400	30.65	-0.48	30.17	46.00	-15.83	peak	



5.1.8 TEST RESULTS(ABOVE 1000 MHZ)

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency;"H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown "*" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



Test Mode:	TX 2402MHz _CH00_1Mbps
------------	------------------------

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	23.02	13.81	34.09	57.11	47.90	74.00	54.00	-16.89	-6.10	X/E
2402.20	V	56.17	46.63	34.12	90.29	80.75					X/F
4803.85	V	38.95	30.18	6.38	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	24.16	13.72	34.09	58.25	47.81	74.00	54.00	-15.75	-6.19	X/E
2402.20	H	51.26	41.25	34.12	85.38	75.37					X/F
4804.04	H	37.23	28.28	6.38	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H

Test Mode:	TX 2441MHz _CH39_1Mbps
------------	------------------------

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2441.20	V	58.19	48.24	34.25	92.44	82.49					X/F
4882.06	V	38.72	29.95	6.61	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2440.80	H	54.35	44.41	34.25	88.60	78.66					X/F
4882.21	H	37.00	28.05	6.61	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H



Test Mode:	TX 2480MHz _CH78_1Mbps
------------	------------------------

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2480.20	V	57.75	47.73	34.36	92.11	82.09					X/F
2483.50	V	22.51	13.92	34.37	56.88	48.29	74.00	54.00	-17.12	-5.71	X/E
4960.08	V	38.50	29.73	6.83	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2480.20	H	55.39	45.61	34.36	89.75	79.97					X/F
2483.50	H	24.11	13.88	34.37	58.48	48.25	74.00	54.00	-15.52	-5.75	X/E
4960.23	H	36.78	27.83	6.83	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H





TX CH00(Above 1000 MHz, Vertical)







TX CH00(Above 1000 MHz, Horizontal)






TX CH39 (Above 1000 MHz, Vertical)







TX CH39 (Above 1000 MHz, Horizontal)







TX CH78 (Above 1000 MHz, Vertical)





TX CH78 (Above 1000 MHz, Horizontal)





Test Mode: TX 2402MHz _CH00_3Mbps

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	23.14	13.73	34.09	57.23	47.82	74.00	54.00	-16.77	-6.18	X/E
2402.20	V	54.51	43.21	34.12	88.63	77.33					X/F
4804.31	V	38.95	30.18	6.38	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	23.33	13.76	34.09	57.42	47.85	74.00	54.00	-16.58	-6.15	X/E
2402.05	H	50.00	38.74	34.12	84.12	72.86					X/F
4804.14	H	37.23	28.28	6.38	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H

Test Mode: TX 2441MHz _CH39_3Mbps

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2441.85	V	58.46	47.57	34.25	92.71	81.82					X/F
4882.37	V	38.72	29.95	6.61	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2441.20	H	52.44	41.59	34.25	86.69	75.84					X/F
4882.09	H	37.00	28.05	6.61	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H



Test Mode: TX 2480MHz _CH78_3Mbps

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2479.85	V	58.52	47.57	34.36	92.88	81.93					X/F
2483.50	V	24.20	13.90	34.37	58.57	48.27	74.00	54.00	-15.43	-5.73	X/E
4960.17	V	38.50	29.73	6.83	45.33	36.56	74.00	54.00	-28.67	-17.44	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2479.85	H	55.39	44.58	34.36	89.75	78.94					X/F
2483.50	H	23.13	13.84	34.37	57.50	48.21	74.00	54.00	-16.50	-5.79	X/E
4960.06	H	36.78	27.83	6.83	43.61	34.66	74.00	54.00	-30.39	-19.34	X/H





TX CH00(Above 1000 MHz, Vertical)







TX CH00(Above 1000 MHz, Horizontal)







TX CH39 (Above 1000 MHz, Vertical)







TX CH39 (Above 1000 MHz, Horizontal)







TX CH78 (Above 1000 MHz, Vertical)





TX CH78 (Above 1000 MHz, Horizontal)





6. MEASUREMENT INSTRUMENTS LIST AND SETTING

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	100087	Nov.09, 2014
3	Test Cable	N/A	C_17	N/A	Mar.14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015


Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 29, 2015
2	Amplifier	HP	8447D	2944A09673	Mar. 29, 2015
3	Test Receiver	R&S	ESCI	100382	Mar. 29, 2015
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 02, 2014
5	Antenna	ETS	3115	00075789	Mar. 29, 2015
6	Amplifier	Agilent	8449B	3008A02274	Mar. 29, 2015
7	Spectrum	Agilent	E4408B	US39240143	Nov. 09, 2014
8	Test Cable	HUBER+SUHNER	C-45	N/A	Apr. 30, 2015
9	Controller	CT	SC100	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	Mar. 29, 2015
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Mar. 29, 2015
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Oct. 22, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.




7. EUT TEST PHOTO

Conducted Measurement Photos





**Radiated Measurement Photos
9K~30MHz**





**Radiated Measurement Photos
30M~1000MHz**



**Radiated Measurement Photos
Above 1000MHz**

