

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2111-0130

2. Customer

- Name (FCC) : Point Mobile Co., LTD. / Name (IC) : POINTMOBILE CO.,LTD
- Address (FCC) : B-9F, Kabul Great Valley 32 Digital-ro 9-gil, Geumcheon-gu Seoul South Korea 153-709
Address (IC) : B-9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu Seoul Korea (Republic Of)

3. Use of Report : FCC & IC Certification

4. Product Name / Model Name : Mobile Computer / PM75

FCC ID : V2X-PM75

IC : 10664A-PM75

5. FCC Regulation(s): Part 15.407

IC Standard(s): RSS-247 Issue 2, RSS-Gen Issue 5

Test Method used: KDB789033 D02v02r01, ANSI C63.10-2013

6. Date of Test : 2021.09.16 ~ 2021.10.12


7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Reviewed by
	Name : SeungMin Gil 	Name : JaeJin Lee  (Signature)

2021 . 11 . 17 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2111-0130	Nov. 17, 2021	Initial issue	SeungMin Gil	JaeJin Lee

CONTENTS

1. General Information	4
1.1. Description of EUT	4
1.2. Declaration by the applicant / manufacturer	5
1.3. Testing Laboratory	5
1.4. Testing Environment	5
1.5. Measurement Uncertainty	5
1.6. Test Equipment List	6
2. Test Methodology	7
2.1. EUT Configuration	7
2.2. EUT Exercise	7
2.3. General Test Procedures	7
2.4. Instrument Calibration	7
2.5. Description of Test Modes	8
3. Antenna Requirements	11
4. Summary of Test Result	12
5. TEST RESULT	13
5.1 Emission Bandwidth (26 dB Bandwidth) & Occupied BW (99 %)	13
5.2 Minimum Emission Bandwidth (6 dB Bandwidth) & Occupied BW (99 %)	32
5.3 Maximum Conducted Output Power	46
5.4 Maximum Power Spectral Density	50
5.5 Unwanted Emissions	77
5.6 AC Power-Line Conducted Emissions	85
APPENDIX I	94
APPENDIX II	95
APPENDIX III	98

1. General Information

1.1. Description of EUT

Equipment Class	Unlicensed National Information Infrastructure TX(NII)
Product Name	Mobile computer
Model Name	PM75
Add Model Name	-
Firmware Version Identification Number	75.00
EUT Serial Number	Conducted : 21196A0012, Radiated: 21197A0022
Power Supply	DC 3.85 V
Modulation Technique	OFDM
Antenna Specification	Antenna Type: LDS Antenna U-NII 1: 2.42 dBi U-NII 2A : 2.22 dBi U-NII 2C : 1.97 dBi U-NII 3: 2.13 dBi

Band	Mode	Tx. frequency(MHz)	Max. conducted power(dBm)	Max. e.i.r.p (dBm)
U-NII 1	802.11a	5 180 ~ 5 240	13.89	16.31
	802.11n(HT20)	5 180 ~ 5 240	13.65	16.07
	802.11ac(VHT20)	5 180 ~ 5 240	13.57	15.99
	802.11n(HT40)	5 190 ~ 5 230	12.85	15.27
	802.11ac(VHT40)	5 190 ~ 5 230	12.81	15.23
	802.11ac(VHT80)	5 210	10.12	12.54
U-NII 2A	802.11a	5 260 ~ 5 320	13.94	16.16
	802.11n(HT20)	5 260 ~ 5 320	13.74	15.96
	802.11ac(VHT20)	5 260 ~ 5 320	13.66	15.88
	802.11n(HT40)	5 270 ~ 5 310	13.01	15.23
	802.11ac(VHT40)	5 270 ~ 5 310	12.96	15.18
	802.11ac(VHT80)	5 290	10.95	13.17
U-NII 2C	802.11a	5 500 ~ 5 720	11.58	13.55
	802.11n(HT20)	5 500 ~ 5 720	11.38	13.35
	802.11ac(VHT20)	5 500 ~ 5 720	11.34	13.31
	802.11n(HT40)	5 510 ~ 5 710	11.46	13.43
	802.11ac(VHT40)	5 510 ~ 5 710	11.42	13.39
	802.11ac(VHT80)	5 530 ~ 5 690	10.75	12.72
U-NII 3	802.11a	5 745 ~ 5 825	11.51	13.64
	802.11n(HT20)	5 745 ~ 5 825	11.33	13.46
	802.11ac(VHT20)	5 745 ~ 5 825	11.27	13.40
	802.11n(HT40)	5 755 ~ 5 795	11.32	13.45
	802.11ac(VHT40)	5 755 ~ 5 795	11.29	13.42
	802.11ac(VHT80)	5 775	10.43	12.56

1.2. Declaration by the applicant / manufacturer

N/A

1.3. Testing Laboratory

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948 according to ANSI C63.4-2014.		
- FCC & IC MRA Designation No. : KR0034		
- ISED#: 5740A		
www.dtnet.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.4. Testing Environment

Ambient Condition	
▪ Temperature	+22 °C ~ +25 °C
▪ Relative Humidity	+42 % ~ +48 %

1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	0.9 dB (The confidence level is about 95 %, $k = 2$)
AC power-line conducted emission	3.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz ~ 18 GHz)	5.0 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	21/08/30	22/08/30	MY46471622
Spectrum Analyzer	Agilent Technologies	N9020A	20/12/16	21/12/16	MY48011700
Spectrum Analyzer	Agilent Technologies	N9020A	21/06/24	22/06/24	US47360812
Spectrum Analyzer	Agilent Technologies	N9030A	20/12/16	21/12/16	MY53310140
DC Power Supply	Agilent Technologies	66332A	21/06/24	22/06/24	US37473422
Multimeter	FLUKE	17B+	20/12/16	21/12/16	36390701WS
Signal Generator	Rohde Schwarz	SMBV100A	20/12/16	21/12/16	255571
Signal Generator	ANRITSU	MG3695C	20/12/16	21/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	20/12/16	21/12/16	120612-1
Thermohygrometer	BODYCOM	BJ5478	20/12/16	21/12/16	120612-2
Thermohygrometer	BODYCOM	BJ5478	21/06/24	22/06/24	N/A
Loop Antenna	ETS-Lindgren	6502	21/01/28	23/01/28	00226186
BILOG ANTENNA	Schwarzbeck	VULB 9160	20/12/16	21/12/16	3362
Horn Antenna	ETS-Lindgren	3117	21/06/24	22/06/24	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	21/06/24	22/06/24	155
PreAmplifier	tsj	MLA-0118-B01-40	20/12/16	21/12/16	1852267
PreAmplifier	tsj	MLA-1840-J02-45	21/06/24	22/06/24	16966-10728
PreAmplifier	H.P	8447D	20/12/16	21/12/16	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	21/06/24	22/06/24	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	21/06/24	22/06/24	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	21/06/24	22/06/24	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	21/06/24	22/06/24	16012202
Attenuator	Aeroflex/Weinschel	56-3	21/06/24	22/06/24	Y2370
Attenuator	SMAJK	SMAJK-2-3	21/06/24	22/06/24	3
Attenuator	SMAJK	SMAJK-2-3	21/06/24	22/06/24	2
Attenuator	Aeroflex/Weinschel	86-20-11	21/06/24	22/06/24	432
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2495A MA2490A	21/06/24	22/06/24	1306007 1249001
EMI Receiver	ROHDE&SCHWARZ	ESU	21/01/19	22/01/19	100538
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	21/08/23	22/08/23	101333
LISN	SCHWARZBECK	NSLK 8128 RC	20/10/23	21/10/23	8128 RC-387
HYGROMETER	TESTO	608-H1	21/01/19	22/01/19	34862883
Cable	DT&C	Cable	21/01/08	22/01/08	G-1
Cable	DT&C	Cable	21/01/08	22/01/08	G-2
Cable	HUBER+SUHNER	SUCOFLEX 100	21/01/08	22/01/08	G-3
Cable	DT&C	Cable	21/01/08	22/01/08	G-4
Cable	Junkosha	MWX241	21/01/08	22/01/08	mmW-1
Cable	Junkosha	MWX241	21/01/08	22/01/08	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	21/01/08	22/01/08	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	21/01/08	22/01/08	M-02
Cable	JUNFLON	MWX241	21/01/08	22/01/08	M-03
Cable	JUNFLON	J12J101757-00	21/01/08	22/01/08	M-07
Cable	HUBER+SUHNER	SUCOFLEX106	21/01/08	22/01/08	M-09
Cable	DT&C	Cable	21/01/05	22/01/05	RFC-11
Cable	DT&C	Cable	21/01/05	22/01/05	RFC-69
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0177
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0170

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

2. Test Methodology

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB 7899033 D02v02r01 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB789033 D02v02r01. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

2.3. General Test Procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB789033 D02v02r01. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on KDB789033 D02v02r01.

The EUT is placed on a non-conductive table, which is 0.8 m above ground plane. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 1 m or 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axis.

2.4. Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.5. Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting.

Transmitting Configuration of EUT

Mode	Data rate
802.11a	6 Mbps ~ 54 Mbps
802.11n(HT20)	MCS 0 ~ 7
802.11ac(VHT20)	MCS 0 ~ 8
802.11n(HT40)	MCS 0 ~ 7
802.11ac(VHT40)	MCS 0 ~ 9
802.11ac(VHT80)	MCS 0 ~ 9

EUT Operation test setup

- Test Software: QRCT_V3.0-00277
- Power setting: Refer to the table below.

Tested frequency and power setting

Band	802.11a						
	Channel	Frequency (MHz)	Power Setting				
			6 ~ 9 Mbps	12 Mbps	18 Mbps	24 ~ 36 Mbps	48 ~ 54 Mbps
U-NII 1	36	5 180	15.0	14.5	13.5	13.0	12.5
	40	5 200	15.0	14.5	13.5	13.0	12.5
	48	5 240	15.0	14.5	13.5	13.0	12.5
U-NII 2A	52	5 260	15.0	14.5	13.5	13.0	12.5
	60	5 300	15.0	14.5	13.5	13.0	12.5
	64	5 320	15.0	14.5	13.5	13.0	12.5
U-NII 2C	100	5 500	13.0	12.5	11.5	11.0	10.5
	116	5 580	13.0	12.5	11.5	11.0	10.5
	144	5 720	13.0	12.5	11.5	11.0	10.5
U-NII 3	149	5 745	13.0	12.5	11.5	11.0	10.5
	157	5 785	13.0	12.5	11.5	11.0	10.5
	165	5 825	13.0	12.5	11.5	11.0	10.5

Band	802.11n(HT20)				
	Channel	Frequency (MHz)	Power Setting		
			MCS 0 ~ 1	MCS 2 ~ 5	MCS 6 ~ 7
U-NII 1	36	5 180	15.0	14.0	13.0
	40	5 200	15.0	14.0	13.0
	48	5 240	15.0	14.0	13.0
U-NII 2A	52	5 260	15.0	14.0	13.0
	60	5 300	15.0	14.0	13.0
	64	5 320	15.0	14.0	13.0
U-NII 2C	100	5 500	13.0	12.0	11.0
	116	5 580	13.0	12.0	11.0
	144	5 720	13.0	12.0	11.0
U-NII 3	149	5 745	13.0	12.0	11.0
	157	5 785	13.0	12.0	11.0
	165	5 825	13.0	12.0	11.0

Band	802.11ac(VHT20)					
	Channel	Frequency (MHz)	Power Setting			
			MCS 0 ~ 1	MCS 2 ~ 5	MCS 6 ~ 7	MCS 8
U-NII 1	36	5 180	15.0	14.0	13.0	12.0
	40	5 200	15.0	14.0	13.0	12.0
	48	5 240	15.0	14.0	13.0	12.0
U-NII 2A	52	5 260	15.0	14.0	13.0	12.0
	60	5 300	15.0	14.0	13.0	12.0
	64	5 320	15.0	14.0	13.0	12.0
U-NII 2C	100	5 500	13.0	12.0	11.0	10.0
	116	5 580	13.0	12.0	11.0	10.0
	144	5 720	13.0	12.0	11.0	10.0
U-NII 3	149	5 745	13.0	12.0	11.0	10.0
	157	5 785	13.0	12.0	11.0	10.0
	165	5 825	13.0	12.0	11.0	10.0

Band	802.11n(HT40)				
	Channel	Frequency (MHz)	Power Setting		
			MCS 0 ~ 1	MCS 2 ~ 5	MCS 6 ~ 7
U-NII 1	38	5 190	11.5	11.0	10.0
	46	5 230	13.5	13.0	12.0
U-NII 2A	54	5 270	13.5	13.0	12.0
	62	5 310	13.5	13.0	12.0
U-NII 2C	102	5 510	12.5	12.0	11.0
	110	5 550	12.5	12.0	11.0
	142	5 710	12.5	12.0	11.0
U-NII 3	151	5 755	12.5	12.0	11.0
	159	5 795	12.5	12.0	11.0

Band	802.11ac(VHT40)						
	Channel	Frequency (MHz)	Power Setting				
			MCS 0 ~ 1	MCS 2 ~ 5	MCS 6 ~ 7	MCS 8	MCS 9
U-NII 1	38	5 190	11.5	11.0	10.0	9.0	8.0
	46	5 230	13.5	13.0	12.0	11.0	10.0
U-NII 2A	54	5 270	13.5	13.0	12.0	11.0	10.0
	62	5 310	13.5	13.0	12.0	11.0	10.0
U-NII 2C	102	5 510	12.5	12.0	11.0	10.0	9.0
	110	5 550	12.5	12.0	11.0	10.0	9.0
	142	5 710	12.5	12.0	11.0	10.0	9.0
U-NII 3	151	5 755	12.5	12.0	11.0	10.0	9.0
	159	5 795	12.5	12.0	11.0	10.0	9.0

Band	802.11ac(VHT80)						
	Channel	Frequency (MHz)	Power Setting				
			MCS 0 ~ 2	MCS 3 ~ 5	MCS 6 ~ 7	MCS 8	MCS 9
U-NII 1	42	5 210	11.0	10.0	9.0	8.0	6.0
U-NII 2A	58	5 290	12.0	11.0	10.0	9.0	7.0
U-NII 2C	106	5 530	12.0	11.0	10.0	9.0	7.0
	138	5 690	12.0	11.0	10.0	9.0	7.0
U-NII 3	155	5 775	12.0	11.0	10.0	9.0	7.0

Tested Mode

Test mode	Mode	Worst case data rate
TM 1	802.11a	6 Mbps
TM 2	802.11n(HT20)	MCS 0
TM 3	802.11n(HT40)	MCS 0
TM 4	802.11ac(VHT80)	MCS 0

Note1: The worst case data rate was determined according to the power measurements.

3. Antenna Requirements

■ **According to Part 15.203**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

**The antenna is attached on the device by means of unique coupling method (Spring Tension).
Therefore this E.U.T complies with the requirement of Part 15.203**

4. Summary of Test Result

FCC Part Section(s)	RSS Section(s)	Test Description	Limit	Test Condition	Status Note 1
15.407(a)	RSS-247[6.2]	Emission Bandwidth (26 dB Bandwidth)	N/A	Conducted	C
15.407(e)	RSS-247[6.2]	Minimum Emission Bandwidth (6 dB Bandwidth)	> 500 kHz in 5 725 ~ 5 850 MHz		C
15.407(a)	RSS-247[6.2]	Maximum Conducted Output Power	Part 15.407(a) (Refer to section 5.3)		C
15.407(a)	RSS-247[6.2]	Peak Power Spectral Density	Part 15.407(a) (Refer to section 5.4)		C
-	RSS-Gen[6.7]	Occupied Bandwidth (99 %)	N/A		C
15.407(h)	RSS-247[6.3]	Dynamic Frequency Selection	Part 15.407(h) (Refer to the DFS test report)		C Note 4
15.205 15.209 15.407(b)	RSS-Gen[8.9] RSS-Gen[8.10] RSS-247[6.2]	Unwanted Emissions	Part 15.209, 15.407(b) (Refer to section 5.5)	Radiated	C Note 3
15.207	RSS-Gen[8.8]	AC Conducted Emissions	FCC 15.207 (Refer to section 5.6)	AC Line Conducted	C
15.203	-	Antenna Requirements	FCC 15.203 (Refer to section 3)	-	C
Note 1: C = Comply NC = Not Comply NT = Not Tested NA = Not Applicable Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS. Note 3: This test item was performed in three orthogonal EUT positions and the worst case data was reported. Note 4: Refer to the DFS test report.					

5. TEST RESULT

5.1 Emission Bandwidth (26 dB Bandwidth) & Occupied BW (99 %)

■ Test Requirements

- Emission Bandwidth (26 dB Bandwidth)

The bandwidth at 26 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The 26 dB bandwidth is used to determine the conducted output power limit.

- Occupied BW (99 %)

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

- Emission Bandwidth (26 dB Bandwidth)

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = approximately **1 %** of the EBW.
2. Set the video bandwidth (**VBW**) > **RBW**.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

- Occupied BW (99 %): RSS-Gen[6.7]

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.


■ Test Results: **Comply**

Test Mode	Band	Channel	Frequency(MHz)	26 dB BW(MHz)	99 % BW(MHz)
TM 1	U-NII 1	36	5 180	22.15	16.59
		40	5 200	22.43	16.58
		48	5 240	24.04	16.63
	U-NII 2A	52	5 260	21.92	16.52
		60	5 300	22.28	16.58
		64	5 320	22.40	16.58
	U-NII 2C	100	5 500	22.07	16.58
		116	5 580	22.17	16.58
		144	5 720	22.13	16.55
TM 2	U-NII 1	36	5 180	22.35	17.81
		40	5 200	23.19	17.79
		48	5 240	22.77	17.84
	U-NII 2A	52	5 260	23.47	17.75
		60	5 300	23.05	17.79
		64	5 320	22.46	17.79
	U-NII 2C	100	5 500	22.43	17.79
		116	5 580	22.96	17.77
		144	5 720	21.89	17.76
TM 3	U-NII 1	38	5 190	41.00	36.17
		46	5 230	41.29	36.17
	U-NII 2A	54	5 270	41.33	36.22
		62	5 310	40.80	36.16
	U-NII 2C	102	5 510	41.14	36.22
		110	5 550	41.26	36.20
TM 4	U-NII 1	42	5 210	83.95	75.74
	U-NII 2A	58	5 290	84.26	75.71
	U-NII 2C	106	5 530	83.26	75.68
		138	5 690	83.38	75.75

Result Plots


26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.36




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.40




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.48




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.52




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.60




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.64




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.100




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.116




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.144




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.36




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.40




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.48




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.52




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.60




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.64




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.100




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.116




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.144




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.38




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.46




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.54




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.62




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.102




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.110




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.142




26 dB Bandwidth & Occupied BW

Test Mode: TM 4 & Ch.42




26 dB Bandwidth & Occupied BW

Test Mode: TM 4 & Ch.58




26 dB Bandwidth & Occupied BW

Test Mode: TM 4 & Ch.106



26 dB Bandwidth & Occupied BW

Test Mode: TM 4 & Ch.138



5.2 Minimum Emission Bandwidth (6 dB Bandwidth) & Occupied BW (99 %)

■ Test Requirements

- Emission Bandwidth (6 dB Bandwidth)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

- Occupied BW (99 %)

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

- Emission Bandwidth (6 dB Bandwidth)

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth $\geq 3 \times \text{RBW}$.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

- Occupied BW (99 %) : RSS-Gen[6.7]

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately $3 \times \text{RBW}$.


■ Test Results: **Comply**

Test Mode	Band	Channel	Frequency(MHz)	6 dB BW(MHz)	99 % BW(MHz)
TM 1	U-NII 3	149	5 745	15.42	16.60
		157	5 785	15.36	16.52
		165	5 825	15.16	16.54
TM 2	U-NII 3	149	5 745	16.30	17.78
		157	5 785	15.65	17.71
		165	5 825	16.07	17.78
TM 3	U-NII 3	151	5 755	35.23	36.19
		159	5 795	35.24	36.17
TM 4	U-NII 3	155	5 775	75.39	75.71

Result Plots

6 dB Bandwidth

Test Mode: TM 1 & Ch.149




6 dB Bandwidth

Test Mode: TM 1 & Ch.157




6 dB Bandwidth

Test Mode: TM 1 & Ch.165




6 dB Bandwidth

Test Mode: TM 2 & Ch.149




6 dB Bandwidth

Test Mode: TM 2 & Ch.157




6 dB Bandwidth

Test Mode: TM 2 & Ch.165




6 dB Bandwidth

Test Mode: TM 3 & Ch.151




6 dB Bandwidth

Test Mode: TM 3 & Ch.159



6 dB Bandwidth


Test Mode: TM 4 & Ch.155



Result Plots


Occupied Bandwidth

Test Mode: TM 1 & Ch.149




Occupied Bandwidth

Test Mode: TM 1 & Ch.157




Occupied Bandwidth

Test Mode: TM 1 & Ch.165



Occupied Bandwidth

Test Mode: TM 2 & Ch.149




Occupied Bandwidth

Test Mode: TM 2 & Ch.157




Occupied Bandwidth

Test Mode: TM 2 & Ch.165




Occupied Bandwidth

Test Mode: TM 3 & Ch.151




Occupied Bandwidth

Test Mode: TM 3 & Ch.159



Occupied Bandwidth

Test Mode: TM 4 & Ch.155



5.3 Maximum Conducted Output Power

■ Test Requirements

Part. 15.407(a)

(1) For the band 5.15 GHz - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15 GHz - 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) **For the 5.25 GHz - 5.35 GHz and 5.47 GHz - 5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.** If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) **For the band 5.725 GHz - 5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.** If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247[6.2]

(1) For band 5 150 MHz – 5 250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

(2) For band 5 250 MHz – 5 350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(3) For band 5 470 MHz – 5 600 MHz and 5 650 MHz – 5 725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5 725 MHz – 5 850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Configuration



Method PM-G

■ Test Procedure

Method PM-G of KDB789033 D02v02r01

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

■ Test Results: **Comply**

Mode	Band	Channel	Frequency (MHz)	Conducted Output Power(dBm)	Antenna Gain(dBi)	e.i.r.p ^{Note1} (dBm)
802.11a	U-NII 1	36	5 180	13.85	2.42	16.27
		40	5 200	13.89	2.42	16.31
		48	5 240	13.77	2.42	16.19
	U-NII 2A	52	5 260	13.86	2.22	16.08
		60	5 300	13.78	2.22	16.00
		64	5 320	13.94	2.22	16.16
	U-NII 2C	100	5 500	11.58	1.97	13.55
		116	5 580	11.51	1.97	13.48
		144	5 720	11.52	1.97	13.49
	U-NII 3	149	5 745	11.46	2.13	13.59
		157	5 785	11.45	2.13	13.58
		165	5 825	11.51	2.13	13.64
802.11n (HT20)	U-NII 1	36	5 180	13.65	2.42	16.07
		40	5 200	13.57	2.42	15.99
		48	5 240	13.48	2.42	15.90
	U-NII 2A	52	5 260	13.58	2.22	15.80
		60	5 300	13.71	2.22	15.93
		64	5 320	13.74	2.22	15.96
	U-NII 2C	100	5 500	11.38	1.97	13.35
		116	5 580	11.29	1.97	13.26
		144	5 720	11.34	1.97	13.31
	U-NII 3	149	5 745	11.24	2.13	13.37
		157	5 785	11.25	2.13	13.38
		165	5 825	11.33	2.13	13.46
802.11ac (VHT20)	U-NII 1	36	5 180	13.57	2.42	15.99
		40	5 200	13.52	2.42	15.94
		48	5 240	13.43	2.42	15.85
	U-NII 2A	52	5 260	13.51	2.22	15.73
		60	5 300	13.64	2.22	15.86
		64	5 320	13.66	2.22	15.88
	U-NII 2C	100	5 500	11.34	1.97	13.31
		116	5 580	11.25	1.97	13.22
		144	5 720	11.28	1.97	13.25
	U-NII 3	149	5 745	11.20	2.13	13.33
		157	5 785	11.22	2.13	13.35
		165	5 825	11.27	2.13	13.40

Mode	Band	Channel	Frequency (MHz)	Conducted Output Power(dBm)	Antenna Gain(dBi)	e.i.r.p ^{Note1} (dBm)
802.11n (HT40)	U-NII 1	38	5 190	10.82	2.42	13.24
		46	5 230	12.85	2.42	15.27
	U-NII 2A	54	5 270	13.01	2.22	15.23
		62	5 310	12.79	2.22	15.01
	U-NII 2C	102	5 510	11.46	1.97	13.43
		110	5 550	11.28	1.97	13.25
		142	5 710	11.34	1.97	13.31
	U-NII 3	151	5 755	11.26	2.13	13.39
		159	5 795	11.32	2.13	13.45
802.11ac (VHT40)	U-NII 1	38	5 190	10.78	2.42	13.2
		46	5 230	12.81	2.42	15.23
	U-NII 2A	54	5 270	12.96	2.22	15.18
		62	5 310	12.75	2.22	14.97
	U-NII 2C	102	5 510	11.42	1.97	13.39
		110	5 550	11.24	1.97	13.21
		142	5 710	11.31	1.97	13.28
	U-NII 3	151	5 755	11.22	2.13	13.35
		159	5 795	11.29	2.13	13.42
802.11ac (VHT80)	U-NII 1	42	5 210	10.12	2.42	12.54
	U-NII 2A	58	5 290	10.95	2.22	13.17
	U-NII 2C	106	5 530	10.34	1.97	12.31
		138	5 690	10.75	1.97	12.72
	U-NII 3	155	5 775	10.43	2.13	12.56

Note 1: e.i.r.p= Conducted Output Power + Antenna Gain

5.4 Maximum Power Spectral Density

■ Test requirements

Part. 15.407(a)

(1) For the band 5.15 GHz - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 GHz - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 GHz - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 GHz - 5.35 GHz and 5.47 GHz - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 GHz - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1,note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

RSS-247[6.2]

(1) For band 5 150 MHz – 5 250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

(2) For band 5 250 MHz – 5 350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(3) For band 5 470 MHz – 5 600 MHz and 5 650 MHz – 5 725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5 725 MHz – 5 850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

Maximum Power Spectral Density is measured using Measurement Procedure of **KDB789033 D02v02r01**

- 1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA - 1, SA - 2, SA - 3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- 2) Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- 3) Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) **If Method SA - 2 or SA - 2 Alternative was used, add $10 \log(1 / x)$, where x is the duty cycle, to the peak of the spectrum.**
 - b) If Method SA - 3 Alternative was used and the linear mode was used in step II.E.2.g (viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- 4) The result is the Maximum PSD over 1 MHz reference bandwidth.
- 5) For devices operating in the bands 5.15 GHz - 5.25 GHz, 5.25 GHz - 5.35 GHz, and 5.47 GHz - 5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in §15.407(a)(5). For devices operating in the band 5.725 GHz - 5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 - a) Set $RBW \geq 1 / T$, where T is defined in section II.B.1.a). (Refer to Appendix II)
 - b) Set $VBW \geq 3 \text{ RBW}$.
 - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz} / \text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log(1 \text{ MHz} / \text{RBW})$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW = 100 kHz is available on nearly all spectrum analyzers.

■ Test Results: **Comply**

Test Mode	Band	Channel	Frequency (MHz)	Reading (dBm)	TF ^{Note 1} (dB)	Power Spectral Density(dBm)	Antenna Gain(dBi)	e.i.r.p Spectral Density (dBm)
TM 1	U-NII 1	36	5 180	3.51	0.08	3.59	2.42	6.01
		40	5 200	3.22	0.08	3.30	2.42	5.72
		48	5 240	2.84	0.08	2.92	2.42	5.34
	U-NII 2A	52	5 260	3.57	0.08	3.65	2.22	5.87
		60	5 300	3.57	0.08	3.65	2.22	5.87
		64	5 320	3.67	0.08	3.75	2.22	5.97
	U-NII 2C	100	5 500	0.95	0.08	1.03	1.97	3.00
		116	5 580	1.07	0.08	1.15	1.97	3.12
		144	5 720	1.83	0.08	1.91	1.97	3.88
	U-NII 3	149	5 745	-7.45	7.07	-0.38	2.13	1.75
		157	5 785	-7.44	7.07	-0.37	2.13	1.76
		165	5 825	-7.68	7.07	-0.61	2.13	1.52
TM 2	U-NII 1	36	5 180	3.06	0.09	3.15	2.42	5.57
		40	5 200	2.73	0.09	2.82	2.42	5.24
		48	5 240	2.52	0.09	2.61	2.42	5.03
	U-NII 2A	52	5 260	2.76	0.09	2.85	2.22	5.07
		60	5 300	2.90	0.09	2.99	2.22	5.21
		64	5 320	3.12	0.09	3.21	2.22	5.43
	U-NII 2C	100	5 500	0.56	0.09	0.65	1.97	2.62
		116	5 580	0.66	0.09	0.75	1.97	2.72
		144	5 720	1.19	0.09	1.28	1.97	3.25
	U-NII 3	149	5 745	-8.10	7.08	-1.02	2.13	1.11
		157	5 785	-7.83	7.08	-0.75	2.13	1.38
		165	5 825	-8.23	7.08	-1.15	2.13	0.98
TM 3	U-NII 1	38	5 190	-2.72	0.16	-2.56	2.42	-0.14
		46	5 230	-1.02	0.16	-0.86	2.42	1.56
	U-NII 2A	54	5 270	-1.12	0.16	-0.96	2.22	1.26
		62	5 310	-0.75	0.16	-0.59	2.22	1.63
	U-NII 2C	102	5 510	-2.15	0.16	-1.99	1.97	-0.02
		110	5 550	-2.57	0.16	-2.41	1.97	-0.44
	U-NII 3	142	5 710	-2.18	0.16	-2.02	1.97	-0.05
		151	5 755	-10.95	7.15	-3.80	2.13	-1.67
TM 4	U-NII 1	159	5 795	-10.29	7.15	-3.14	2.13	-1.01
		42	5 210	-7.33	0.32	-7.01	2.42	-4.59
	U-NII 2A	58	5 290	-5.93	0.32	-5.61	2.22	-3.39
		106	5 530	-6.36	0.32	-6.04	1.97	-4.07
	U-NII 3	138	5 690	-5.66	0.32	-5.34	1.97	-3.37
		155	5 775	-15.25	7.31	-7.94	2.13	-5.81

Note 1: Power Spectral Density = Reading(Measurement Data) + TF

Note 2: e.i.r.p Spectral Density= Power spectral density + EUT Antenna Gain

Note 3: "U-NII 1, 2A, 2C [TF] = DCCF"

"U-NII 3 [TF] = 10*LOG(500 kHz/100 kHz) + DCCF"


Where, TF = Total Factor, DCCF = Duty Cycle Correction Factor

For DCCF(Duty Cycle Correction Factor) please refer to appendix II.

RESULT PLOTS


Maximum Power Spectral Density

Test Mode: TM 1 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.40




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.48




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.64




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.100




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.116




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.165




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.40




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.52




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.60




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.100




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.116




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.144




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.38



Maximum Power Spectral Density

Test Mode: TM 3 & Ch.46



Maximum Power Spectral Density

Test Mode: TM 3 & Ch.54




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.62




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.102




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.110




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.151




Maximum Power Spectral Density

Test Mode: TM 3 & Ch.159



Maximum Power Spectral Density

Test Mode: TM 4 & Ch.155



5.5 Unwanted Emissions

■ Test Requirements

- Part 15.407(b) & RSS-Gen[6.2]

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the **5.15 GHz - 5.25 GHz band**: all emissions outside of the **5.15 GHz - 5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (2) For transmitters operating in the **5.25 GHz - 5.35 GHz band**: all emissions outside of the **5.15 GHz - 5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (3) For transmitters operating in the **5.47 GHz - 5.725 GHz band**: all emissions outside of the **5.47 GHz - 5.725 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (4) For transmitters operating in the **5.725 GHz - 5.85 GHz band**: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (5) Unwanted emissions **below 1 GHz** must comply with the general field strength limits set forth in **Section 15.209**.

Further, any U-NII devices using an **AC power line** are required to comply also with the conducted limits set forth in **Section 15.207**.

- Part 15.209 & RSS-247[8.9]: General requirement

Frequency (MHz)	FCC Limit (uV/m)	IC Limit (uA/m)	Measurement Distance (m)
0.009 – 0.490	2 400 / F (kHz)	6.37/F (F in kHz)	300
0.490 – 1.705	2 4000 / F (kHz)	63.7/F (F in kHz)	30
1.705 – 30.0	30	0.08	30

Frequency (MHz)	FCC Limit (uV/m)	IC Limit (uV/m)	Measurement Distance (m)
30 ~ 88	100 **	100	3
88 ~ 216	150 **	150	3
216 ~ 960	200 **	200	3
Above 960	500	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.


- Part 15.205(a): Restricted band of operation

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.414 25 ~ 8.414 75	108 ~ 121.94	1 300 ~ 1 427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1 435 ~ 1 626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.173 5 ~ 2.190 5	12.519 75 ~ 12.520 25	149.9 ~ 150.05	1 645.5 ~ 1 646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.576 75 ~ 12.577 25	156.524 75 ~ 156.525 25	1 660 ~ 1 710	8.025 ~ 8.5	22.01 ~ 23.12
4.177 25 ~ 4.177 75	13.36 ~ 13.41	156.7 ~ 156.9	1 718.8 ~ 1 722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.207 25 ~ 4.207 75	16.42 ~ 16.423	162.012 5 ~ 167.17	2 200 ~ 2 300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 310 ~ 2 390	10.6 ~ 12.7	36.43 ~ 36.5
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 483.5 ~ 2 500	13.25 ~ 13.4	Above 38.6
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	2 655 ~ 2 900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 260 ~ 3 267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 332 ~ 3 339		
8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1240	3 345.8 ~ 3 358		
			3 600 ~ 4 400		

- RSS-GEN[8.10]: Restricted frequency bands

MHz	MHz	MHz	MHz	MHz	GHz
0.090 ~ 0.110	8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 345.8 ~ 3 358	9.0 ~ 9.2
0.495 ~ 0.505	8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1 427	3 500 ~ 4 400	9.3 ~ 9.5
2.173 5 ~ 2.190 5	8.414 25 ~ 8.414 75	108 ~ 138	1 435 ~ 1 626.5	4 500 ~ 5 150	10.6 ~ 12.7
3.020 ~ 3.026	12.29 ~ 12.293	149.9 ~ 150.05	1 645.5 ~ 1 646.5	5 350 ~ 5 460	13.25 ~ 13.4
4.125 ~ 4.128	12.519 75 ~ 12.520 25	156.524 75 ~	1 660 ~ 1 710	7 250 ~ 7 750	14.47 ~ 14.5
4.177 25 ~ 4.177 75	12.576 75 ~ 12.577 25	156.525 25	1 718.8 ~ 1 722.2	8 025 ~ 8 500	15.35 ~ 16.2
4.207 25 ~ 4.207 75	13.36 ~ 13.41	156.7 ~ 156.9	2 200 ~ 2 300		17.7 ~ 21.4
5.677 ~ 5.683	16.42 ~ 16.423	162.01 25 ~ 167.17	2 310 ~ 2 390		22.01 ~ 23.12
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 483.5 ~ 2 500		23.6 ~ 24.0
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 655 ~ 2 900		31.2 ~ 31.8
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	3 260 ~ 3 267		36.43 ~ 36.5
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 332 ~ 3 339		Above 38.6

■ Test Configuration



■ Test Procedure

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turn table shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 1 m or 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

Radiated spurious emission measured using following Measurement Procedure of KDB789033 D02v02r01

► General Requirements for Unwanted Emissions Measurements

The following requirements apply to all unwanted emissions measurements, both in and outside of the restricted bands:

▪ EUT Duty Cycle

- (1) The EUT shall be configured or modified to **transmit continuously** except as stated in (ii), below. The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (**to no lower than 98 percent**) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.
- (2) If **continuous transmission (or at least 98 percent duty cycle) cannot be achieved** due to hardware limitations of the EUT (e.g., overheating), the following additions to the measurement and reporting procedures are required:
 - The EUT shall be configured to operate at the maximum achievable duty cycle.
 - Measure the duty cycle, x, of the transmitter output signal.
 - Adjustments to measurement procedures (e.g., increasing test time and number of traces averaged) shall be performed as described in the procedures below.
 - The test report shall include the following additional information:
 - The reason for the duty cycle limitation.
 - The duty cycle achieved for testing and the associated transmit duration and interval between transmissions.
 - The sweep time and the amount of time used for trace stabilization during max-hold measurements for peak emission measurements.
- (3) Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

► Measurements below 1 000 MHz

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Compliance shall be demonstrated using **CISPR quasi-peak detection**; however, **peak detection** is permitted as an alternative to quasi-peak detection.

► Measurements Above 1 000 MHz (Peak)

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Peak emission levels are measured by setting the analyzer as follows:
 - (i) **RBW = 1 MHz.**
 - (ii) **VBW ≥ 3 MHz.**
 - (iii) **Detector = Peak.**
 - (iv) Sweep time = Auto.
 - (v) Trace mode = Max hold.
 - (vi) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately 1/x, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

► Measurements Above 1000 MHz (Method AD)

- (i) **RBW = 1 MHz.**
- (ii) **VBW ≥ 3 MHz.**
- (iii) **Detector = RMS**, if $\text{span} / (\# \text{ of points in sweep}) \leq \text{RBW} / 2$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.
- (iv) Averaging type = power (i.e., RMS)
 - As an alternative, the detector and averaging type may be set for linear voltage averaging. Some analyzers require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- (v) Sweep time = Auto.
- (vi) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50 percent duty cycle, at least 200 traces shall be averaged.
- (vii) If tests are performed with the EUT transmitting at a duty cycle less than 98 percent, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - **If power averaging (RMS) mode was used in step (iv) above, the correction factor is $10 \log(1/x)$, where x is the duty cycle.** For example, if the transmit duty cycle was 50 percent, then 3 dB must be added to the measured emission levels.
 - If linear voltage averaging mode was used in step (iv) above, the correction factor is $20 \log(1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50 percent, then 6 dB must be added to the measured emission levels.
 - If a specific emission is demonstrated to be continuous (100 percent duty cycle) rather than turning on and off with the transmit cycle, no duty cycle correction is required for that emission.

Duty Cycle Correction factor

Test Mode	Date rate	T _{on} (ms)	T _{on+off} (ms)	$x = T_{on} / (T_{on+off})$	DCCF = $10 \log(1/x)$ (dB)
TM 1	6 Mbps	2.062	2.102	0.981 0	0.08
TM 2	MCS 0	1.923	1.961	0.980 6	0.09
TM 3	MCS 0	0.948	0.984	0.963 4	0.16
TM 4	MCS 0	0.464	0.500	0.928 0	0.32

Note1: Where, T = Transmission duration / x = Duty cycle

Note2: Please refer to the appendix II for duty cycle plots.

Test Results

Test Notes

- The radiated emissions were investigated 9 kHz to 40 GHz. And no other spurious and harmonic emissions were found below listed frequencies.
- Information of Distance Correction Factor
For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.
In this case, the distance factor is applied to the result.
- Calculation of distance correction factor
At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$
At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$
When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.
- Sample Calculation.
 $\text{Margin} = \text{Limit} - \text{Result} / \text{Result} = \text{Reading} + \text{TF} + \text{DCCF} + \text{DCF} / \text{TF} = \text{AF} + \text{CL} + \text{HL} + \text{AL} - \text{AG}$
Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss, AL = Attenuator Loss, DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E(\text{dBuV/m}) = \text{EIRP}(\text{dBm}) + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Unwanted Emissions data(9 kHz ~ 40 GHz) : TM1 Normal

Band	Tested Frequency (MHz)	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	5 180	5 149.06	H	Z	PK	55.28	2.63	N/A	N/A	57.91	74.00	16.09
		5 149.48	H	Z	AV	42.93	2.63	N/A	N/A	45.56	54.00	8.44
		10 359.65	H	Z	PK	43.91	8.66	N/A	N/A	52.57	68.20	15.63
	5 200	10 400.11	H	Z	PK	44.89	8.68	N/A	N/A	53.57	68.20	14.63
	5 240	10 480.44	H	Z	PK	44.22	8.70	N/A	N/A	52.92	68.20	15.28
U-NII 2A	5 260	10 519.70	H	Z	PK	44.26	8.71	N/A	N/A	52.97	68.20	15.23
		10 599.97	H	Z	PK	45.46	8.62	N/A	N/A	54.08	68.20	14.12
		10 600.01	H	Z	AV	35.68	8.62	N/A	N/A	44.30	54.00	9.70
	5 320	5 351.39	H	Z	PK	53.20	3.77	N/A	N/A	56.97	74.00	17.03
		5 350.18	H	Z	AV	41.99	3.77	N/A	N/A	45.76	54.00	8.24
		10 639.90	H	Z	PK	44.56	8.46	N/A	N/A	53.02	74.00	20.98
		10 640.03	H	Z	AV	35.64	8.46	N/A	N/A	44.10	54.00	9.90
U-NII 2C	5 500	5 456.46	H	Z	PK	51.66	3.56	N/A	N/A	55.22	74.00	18.78
		5 456.38	H	Z	AV	40.10	3.56	N/A	N/A	43.66	54.00	10.34
		5 463.81	H	Z	PK	50.64	3.54	N/A	N/A	54.18	68.20	14.02
		11 000.15	H	Z	PK	45.66	8.05	N/A	N/A	53.71	74.00	20.29
		10 999.83	H	Z	AV	35.63	8.05	N/A	N/A	43.68	54.00	10.32
	5 580	11 159.73	H	Z	PK	45.88	8.45	N/A	N/A	54.33	74.00	19.67
		11 159.87	H	Z	AV	35.51	8.45	N/A	N/A	43.96	54.00	10.04
	5 720	11 439.85	H	Z	PK	44.51	9.01	N/A	N/A	53.52	74.00	20.48
		11 439.99	H	Z	AV	34.03	9.01	N/A	N/A	43.04	54.00	10.96
U-NII 3	5 745	5 713.43	H	Z	PK	52.59	3.20	N/A	N/A	55.79	68.20	12.41
		5 724.34	H	Z	PK	61.59	3.71	N/A	N/A	65.30	78.20	12.90
		11 490.19	H	Z	PK	45.82	9.08	N/A	N/A	54.90	74.00	19.10
		11 490.00	H	Z	AV	35.11	9.08	N/A	N/A	44.19	54.00	9.81
	5 785	11 570.37	H	Z	PK	44.65	9.11	N/A	N/A	53.76	74.00	20.24
		11 570.06	H	Z	AV	34.05	9.11	N/A	N/A	43.16	54.00	10.84
	5 825	5 851.27	H	Z	PK	52.73	4.05	N/A	N/A	56.78	78.20	21.42
		5 860.69	H	Z	PK	51.47	4.16	N/A	N/A	55.63	68.20	12.57
		11 650.40	H	Z	PK	45.18	9.02	N/A	N/A	54.20	74.00	19.80
		11 649.71	H	Z	AV	35.15	9.03	N/A	N/A	44.18	54.00	9.82

Unwanted Emissions data(9 kHz ~ 40 GHz) : **TM2 Normal**

Band	Tested Frequency (MHz)	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	5 180	5 149.26	H	Z	PK	55.47	2.63	N/A	N/A	58.10	74.00	15.90
		5 149.68	H	Z	AV	43.10	2.63	N/A	N/A	45.73	54.00	8.27
		10 359.93	H	Z	PK	44.37	8.66	N/A	N/A	53.03	68.20	15.17
	5 200	10 400.02	H	Z	PK	44.65	8.68	N/A	N/A	53.33	68.20	14.87
	5 240	10 479.96	H	Z	PK	44.54	8.70	N/A	N/A	53.24	68.20	14.96
U-NII 2A	5 260	10 519.83	H	Z	PK	44.06	8.71	N/A	N/A	52.77	68.20	15.43
	5 300	10 599.86	H	Z	PK	45.13	8.62	N/A	N/A	53.75	68.20	14.45
		10 600.01	H	Z	AV	35.68	8.62	N/A	N/A	44.30	54.00	9.70
	5 320	5 350.45	H	Z	PK	53.21	3.77	N/A	N/A	56.98	74.00	17.02
		5 350.98	H	Z	AV	42.06	3.77	N/A	N/A	45.83	54.00	8.17
		10 640.27	H	Z	PK	46.18	8.46	N/A	N/A	54.64	74.00	19.36
		10 640.03	H	Z	AV	35.25	8.46	N/A	N/A	43.71	54.00	10.29
U-NII 2C	5 500	5 456.98	H	Z	PK	51.93	3.56	N/A	N/A	55.49	74.00	18.51
		5 456.70	H	Z	AV	40.34	3.56	N/A	N/A	43.90	54.00	10.10
		5 460.84	H	Z	PK	50.49	3.55	N/A	N/A	54.04	68.20	14.16
		10 999.88	H	Z	PK	45.20	8.05	N/A	N/A	53.25	74.00	20.75
		11 000.05	H	Z	AV	35.57	8.05	N/A	N/A	43.62	54.00	10.38
	5 580	11 159.78	H	Z	PK	44.93	8.45	N/A	N/A	53.38	74.00	20.62
		11 159.75	H	Z	AV	35.32	8.45	N/A	N/A	43.77	54.00	10.23
	5 720	11 439.85	H	Z	PK	44.85	9.01	N/A	N/A	53.86	74.00	20.14
		11 439.90	H	Z	AV	34.00	9.01	N/A	N/A	43.01	54.00	10.99
U-NII 3	5 745	5 711.47	H	Z	PK	53.52	3.20	N/A	N/A	56.72	68.20	11.48
		5 723.74	H	Z	PK	61.72	3.67	N/A	N/A	65.39	78.20	12.81
		11 490.26	H	Z	PK	45.61	9.08	N/A	N/A	54.69	74.00	19.31
		11 489.52	H	Z	AV	35.03	9.08	N/A	N/A	44.11	54.00	9.89
	5 785	11 569.65	H	Z	PK	44.65	9.11	N/A	N/A	53.76	74.00	20.24
		11 569.84	H	Z	AV	34.19	9.11	N/A	N/A	43.30	54.00	10.70
	5 825	5 851.30	H	Z	PK	52.54	4.05	N/A	N/A	56.59	78.20	21.61
		5 860.54	H	Z	PK	52.19	4.15	N/A	N/A	56.34	68.20	11.86
		11 649.74	H	Z	PK	45.26	9.03	N/A	N/A	54.29	74.00	19.71
		11 649.87	H	Z	AV	34.86	9.03	N/A	N/A	43.89	54.00	10.11

Unwanted Emissions data(9 kHz ~ 40 GHz) : **TM3 Normal**

Band	Tested Frequency (MHz)	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	5 190	5 149.62	H	Z	PK	58.60	2.63	N/A	N/A	61.23	74.00	12.77
		5 149.96	H	Z	AV	47.41	2.63	0.16	N/A	50.20	54.00	3.80
		10 379.75	H	Z	PK	43.70	8.67	N/A	N/A	52.37	68.20	15.83
	5 210	10 460.03	H	Z	PK	44.23	8.70	N/A	N/A	52.93	68.20	15.27
U-NII 2A	5 270	10 539.79	H	Z	PK	44.05	8.71	N/A	N/A	52.76	68.20	15.44
	5 310	5 350.38	H	Z	PK	56.39	3.77	N/A	N/A	60.16	74.00	13.84
		5 350.66	H	Z	AV	47.36	3.77	0.16	N/A	51.29	54.00	2.71
		10 619.58	H	Z	PK	45.29	8.54	N/A	N/A	53.83	74.00	20.17
		10 620.06	H	Z	AV	35.48	8.54	0.16	N/A	44.18	54.00	9.82
U-NII 2C	5 510	5 459.89	H	Z	PK	54.42	3.55	N/A	N/A	57.97	74.00	16.03
		5 459.83	H	Z	AV	42.23	3.55	0.16	N/A	45.94	54.00	8.06
		5 469.66	H	Z	PK	58.55	3.52	N/A	N/A	62.07	68.20	6.13
		11 019.74	H	Z	PK	46.47	8.11	N/A	N/A	54.58	74.00	19.42
		11 019.87	H	Z	AV	35.83	8.12	0.16	N/A	44.11	54.00	9.89
	5 550	11 099.65	H	Z	PK	45.63	8.18	N/A	N/A	53.81	74.00	20.19
		11 100.02	H	Z	AV	35.50	8.18	0.16	N/A	43.84	54.00	10.16
	5 710	11 419.81	H	Z	PK	44.82	8.99	N/A	N/A	53.81	74.00	20.19
		11 419.70	H	Z	AV	34.25	8.99	0.16	N/A	43.40	54.00	10.60
U-NII 3	5 755	5 714.52	H	Z	PK	61.48	3.21	N/A	N/A	64.69	68.20	3.51
		5 724.50	H	Z	PK	65.00	3.71	N/A	N/A	68.71	78.20	9.49
		11 509.81	H	Z	PK	44.84	9.10	N/A	N/A	53.94	74.00	20.06
		11 510.41	H	Z	AV	34.77	9.10	0.16	N/A	44.03	54.00	9.97
	5 795	5 852.64	H	Z	PK	51.70	4.06	N/A	N/A	55.76	78.20	22.44
		5 860.54	H	Z	PK	51.25	4.15	N/A	N/A	55.40	68.20	12.80
		11 590.16	H	Z	PK	43.86	9.09	N/A	N/A	52.95	74.00	21.05
		11 589.81	H	Z	AV	33.99	9.09	0.16	N/A	43.24	54.00	10.76

Unwanted Emissions data(9 kHz ~ 40 GHz) : **TM4 Normal**

Band	Tested Frequency (MHz)	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	5 210	5 149.08	H	Z	PK	57.85	2.63	N/A	N/A	60.48	74.00	13.52
		5 148.94	H	Z	AV	47.22	2.63	0.32	N/A	50.17	54.00	3.83
		10 419.84	H	Z	PK	44.19	8.68	N/A	N/A	52.87	68.20	15.33
U-NII 2A	5 230	5 350.21	H	Z	PK	55.94	3.77	N/A	N/A	59.71	74.00	14.29
		5 350.27	H	Z	AV	46.40	3.77	0.32	N/A	50.49	54.00	3.51
		10 580.16	H	Z	PK	44.11	8.66	N/A	N/A	52.77	68.20	15.43
U-NII 2C	5 510	5 459.37	H	Z	PK	56.85	3.55	N/A	N/A	60.40	74.00	13.60
		5 457.99	H	Z	AV	46.14	3.56	0.32	N/A	50.02	54.00	3.98
		5 463.38	H	Z	PK	56.89	3.54	N/A	N/A	60.43	68.20	7.77
		11 060.00	H	Z	PK	46.10	8.21	N/A	N/A	54.31	74.00	19.69
		11 059.86	H	Z	AV	35.96	8.21	0.32	N/A	44.49	54.00	9.51
	5 690	11 380.08	H	Z	PK	44.23	8.90	N/A	N/A	53.13	74.00	20.87
		11 379.79	H	Z	AV	34.69	8.90	0.32	N/A	43.91	54.00	10.09
U-NII 3	5 775	5 713.55	H	Z	PK	60.76	3.20	N/A	N/A	63.96	68.20	4.24
		5 720.27	H	Z	PK	63.54	3.49	N/A	N/A	67.03	78.20	11.17
		5 851.34	H	Z	PK	57.09	4.05	N/A	N/A	61.14	78.20	17.06
		5 863.18	H	Z	PK	55.65	4.27	N/A	N/A	59.92	68.20	8.28
		11 549.56	H	Z	PK	45.62	9.13	N/A	N/A	54.75	74.00	19.25
		11 550.01	H	Z	AV	34.19	9.13	0.32	N/A	43.64	54.00	10.36

5.6 AC Power-Line Conducted Emissions

■ Test Requirements, §15.207 & RSS-Gen [8.8]

An intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5.0	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

■ Test Configuration

See test photographs for the actual connections between EUT and support equipment.

■ Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

■ Test Results: **Comply**

See next pages for actual measured spectrum plots and data for worst case result.

AC Power-Line Conducted Emissions (Graph)

Test Mode: U-NII 1 & TM 1 & 5 180 MHz

Results of Conducted Emission

DTNC


Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5180

Reference No.
Power Supply
Temp/Humi. 23 °C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Power-Line Conducted Emissions (Data List)

Test Mode: U-NII 1 & TM 1 & 5 180 MHz

Results of Conducted Emission

DTNC

Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5180

Reference No.
Power Supply
Temp/Humi. 23 °C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.40743	25.20	18.22	9.91	35.11	28.13	57.70	47.70	22.59	19.57	N
2	0.77280	24.87	13.37	9.92	34.79	23.29	56.00	46.00	21.21	22.71	N
3	1.43532	25.77	13.04	10.05	35.82	23.09	56.00	46.00	20.18	22.91	N
4	18.72989	13.02	6.21	10.44	23.46	16.65	60.00	50.00	36.54	33.35	N
5	0.40645	26.01	16.37	9.91	35.92	26.28	57.72	47.72	21.80	21.44	L
6	0.80478	23.14	13.21	9.92	33.06	23.13	56.00	46.00	22.94	22.87	L
7	1.62605	25.98	13.13	10.06	36.04	23.19	56.00	46.00	19.96	22.81	L
8	18.74009	17.98	6.60	10.44	28.42	17.04	60.00	50.00	31.58	32.96	L

AC Power-Line Conducted Emissions (Graph)

Test Mode: U-NII 2A & TM 1 & 5 320 MHz

Results of Conducted Emission

DTNC


Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5320

Reference No.
Power Supply
Temp/Humi. 23 °C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Power-Line Conducted Emissions (Data List)

Test Mode: U-NII 2A & TM 1 & 5 320 MHz

Results of Conducted Emission

DTNC

Date 2021-10-08

Order No.

PM75

Model No.

Reference No.

Serial No.

Power Supply

Test Condition

5G_a_5320

Temp/Humi.

23 'C / 47 %

Operator

S.M.Gil

Memo

LIMIT : FCC P15.207 QP

FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.40750	24.45	17.36	9.91	34.36	27.27	57.70	47.70	23.34	20.43	N
2	0.79347	23.75	11.89	9.92	33.67	21.81	56.00	46.00	22.33	24.19	N
3	1.44478	25.27	13.41	10.05	35.32	23.46	56.00	46.00	20.68	22.54	N
4	18.47149	12.24	5.21	10.43	22.67	15.64	60.00	50.00	37.33	34.36	N
5	0.39842	25.26	16.06	9.91	35.17	25.97	57.89	47.89	22.72	21.92	L
6	0.81723	23.20	13.61	9.92	33.12	23.53	56.00	46.00	22.88	22.47	L
7	1.63919	25.17	13.39	10.06	35.23	23.45	56.00	46.00	20.77	22.55	L
8	18.28195	17.57	6.62	10.43	28.00	17.05	60.00	50.00	32.00	32.95	L

AC Power-Line Conducted Emissions (Graph)

Test Mode: U-NII 2C & TM 1 & 5 500 MHz

Results of Conducted Emission

DTNC


Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5500

Reference No.
Power Supply
Temp/Humi. 23 °C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Power-Line Conducted Emissions (Data List)

Test Mode: U-NII 2C & TM 1 & 5 500 MHz

Results of Conducted Emission

DTNC

Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5500

Reference No.
Power Supply
Temp/Humi. 23 'C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.40494	23.35	17.43	9.91	33.26	27.34	57.75	47.75	24.49	20.41	N
2	0.76286	21.19	12.52	9.92	31.11	22.44	56.00	46.00	24.89	23.56	N
3	1.43741	23.49	12.34	10.05	33.54	22.39	56.00	46.00	22.46	23.61	N
4	18.59204	9.53	2.59	10.44	19.97	13.03	60.00	50.00	40.03	36.97	N
5	0.39271	24.39	14.93	9.91	34.30	24.84	58.01	48.01	23.71	23.17	L
6	0.81487	22.34	11.67	9.92	32.26	21.59	56.00	46.00	23.74	24.41	L
7	1.49024	24.09	10.72	10.05	34.14	20.77	56.00	46.00	21.86	25.23	L
8	17.93112	15.28	5.18	10.43	25.71	15.61	60.00	50.00	34.29	34.39	L

AC Power-Line Conducted Emissions (Graph)

Test Mode: U-NII 3 & TM 1 & 5 745 MHz

Results of Conducted Emission

DTNC


Date 2021-10-08

Order No.
Model No. PM75
Serial No.
Test Condition 5G_a_5745

Reference No.
Power Supply
Temp/Humi. 23 °C / 47 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Power-Line Conducted Emissions (Data List)

Test Mode: U-NII 3 & TM 1 & 5 745 MHz

Results of Conducted Emission

DTNC

Date 2021-10-08

Order No.

PM75

Model No.

Serial No.

Test Condition

5G_a_5745

Reference No.

Power Supply

Temp/Humi.

Operator

23 'C / 47 %

S.M.Gil

Memo

LIMIT : FCC P15.207 QP


FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.39712	23.91	17.67	9.91	33.82	27.58	57.91	47.91	24.09	20.33	N
2	0.63662	20.03	7.45	9.91	29.94	17.36	56.00	46.00	26.06	28.64	N
3	1.51324	23.49	10.57	10.06	33.55	20.63	56.00	46.00	22.45	25.37	N
4	18.56449	9.08	2.27	10.44	19.52	12.71	60.00	50.00	40.48	37.29	N
5	0.40445	24.53	15.56	9.91	34.44	25.47	57.76	47.76	23.32	22.29	L
6	1.39928	23.36	11.95	10.05	33.41	22.00	56.00	46.00	22.59	24.00	L
7	1.52365	23.69	10.26	10.06	33.75	20.32	56.00	46.00	22.25	25.68	L
8	18.40133	15.19	4.88	10.43	25.62	15.31	60.00	50.00	34.38	34.69	L

APPENDIX I

Conducted Test set up Diagram

▪ Conducted Measurement



APPENDIX II

Duty Cycle Information

■ Test Procedure

Duty Cycle [X = On Time / (On + Off time)] is measured using Measurement Procedure of **KDB789033 D02v02r01**

1. Set the center frequency of the spectrum analyzer to the center frequency of the transmission.
2. Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value.
3. Set VBW $\geq$ RBW. Set detector = peak.
4. Note : The zero-span measurement method shall not be used unless both **RBW and VBW are $> 50 / T$** , where T is defined in section II.B.1.a), and **the number of sweep points across duration T exceeds 100**. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

T : The minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

(T = On time of the above table since the EUT operates with above fixed Duty Cycle and it is the minimum On time)