

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC1911-0281

2. Customer

• Name (FCC) : Point Mobile Co., LTD. / Name (IC) : POINTMOBILE CO.,LTD

• Address (FCC) : B-9F, Kabul Great Valley 32 Digital-ro 9-gil, Geumcheon-gu Seoul South Korea 153-709

Address (IC) : B-9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu Seoul Korea (Republic Of)

3. Use of Report : FCC & IC Original Grant

4. Product Name / Model Name : Mobile Computer / PM90G1

FCC ID : V2X-PM90G1 / IC : 10664A-PM90G1

5. Test Method Used : KDB789033 D02v02r01, ANSI C 63.10-2013

Test Specification : FCC Part 15.407 Subpart E

RSS-247 Issue 2, RSS-GEN Issue 5

6. Date of Test : 2019.06.18 ~ 2019.07.29

7. Testing Environment : Refer to appended test report.

8. Test Result : Refer to the attached test result.

Affirmation	Tested by		Reviewed by	
	Name : JaeJin Lee	(Signature)	Name : GeunKi Son	(Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2019 . 11 . 05 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRTFCC1911-0281	Nov. 05, 2019	Initial issue

CONTENTS

1. EUT DESCRIPTION.....	4
2. Information about test items	5
2.1 Transmitting configuration of EUT	5
2.2 Tested Channel Information.....	5
2.3 Testing Environment.....	6
2.4 EMI Suppression Device(s)/Modifications	6
2.5 Measurement Uncertainty	6
3. SUMMARY OF TESTS.....	7
4. TEST METHODOLOGY	8
4.1 EUT configuration.....	8
4.2 EUT exercise	8
4.3 General test procedures	8
4.4 Description of test modes	8
5. INSTRUMENT CALIBRATION.....	9
6. FACILITIES AND ACCREDITATIONS	9
6.1 Facilities	9
6.2 Equipment	9
7. ANTENNA REQUIREMENTS	9
8. TEST RESULT	10
8.1 Emission Bandwidth (26 dB Bandwidth)	10
8.2 Minimum Emission Bandwidth (6 dB Bandwidth)	28
8.3 Maximum Conducted Output Power.....	35
8.4 Maximum Power Spectral Density.....	39
8.5 Radiated Spurious Emission Measurements.....	66
8.6 AC Conducted Emissions.....	77
8.7 Occupied Bandwidth (99%).....	86
9. LIST OF TEST EQUIPMENT	111
APPENDIX I	112
APPENDIX II	113
APPENDIX III	116

1. EUT DESCRIPTION

Equipment Class	Unlicensed National Information Infrastructure (UNII)
Product	Mobile Computer
Model Name(FCC, IC)	PM90G1
Add Model Name(FCC, IC)	NA
Hardware Version	4
Software Version	90.02
Power Supply	DC 3.85 V
Modulation type	OFDM
Antenna Specification	Antenna type: LDS Antenna Antenna gain U-NII 1: 0.9 dBi U-NII 2A: 0.4 dBi U-NII 2C: 0.1 dBi U-NII 3: 0.3 dBi

5GHz Band	Mode	Frequency range(MHz)	Max power(dBm)
U-NII 1	802.11a	5180 ~ 5240	18.11
	802.11n(HT20)	5180 ~ 5240	17.92
	802.11ac(VHT20)	5180 ~ 5240	17.89
	802.11n(HT40)	5190 ~ 5230	17.36
	802.11ac(VHT40)	5190 ~ 5230	17.32
	802.11ac(VHT80)	5210	15.46
U-NII 2A	802.11a	5260 ~ 5320	18.19
	802.11n(HT20)	5260 ~ 5320	17.87
	802.11ac(VHT20)	5260 ~ 5320	17.85
	802.11n(HT40)	5270 ~ 5310	17.36
	802.11ac(VHT40)	5270 ~ 5310	17.26
	802.11ac(VHT80)	5290	13.71
U-NII 2C	802.11a	5500 ~ 5580, 5660 ~ 5720	18.44
	802.11n(HT20)	5500 ~ 5580, 5660 ~ 5720	17.81
	802.11ac(VHT20)	5500 ~ 5580, 5660 ~ 5720	17.86
	802.11n(HT40)	5510 ~ 5550, 5670 ~ 5710	17.48
	802.11ac(VHT40)	5510 ~ 5550, 5670 ~ 5710	17.46
	802.11ac(VHT80)	5530, 5690	17.96
U-NII 3	802.11a	5745 ~ 5825	18.36
	802.11n(HT20)	5745 ~ 5825	17.89
	802.11ac(VHT20)	5745 ~ 5825	17.88
	802.11n(HT40)	5755 ~ 5795	16.95
	802.11ac(VHT40)	5755 ~ 5795	16.28
	802.11ac(VHT80)	5775	15.01

2. Information about test items

2.1 Transmitting configuration of EUT

Mode	Data rate
802.11a	6~54Mbps
802.11n(HT20)	MCS 0 ~ 7
802.11ac(VHT20)	MCS 0 ~ 8
802.11n(HT40)	MCS 0 ~ 7
802.11ac(VHT40)	MCS 0 ~ 9
802.11ac(VHT80)	MCS 0 ~ 9

2.2 Tested Channel Information

5GHz Band	802.11a/n(HT20)/ac(VHT20)			802.11n(HT40)/ac(VHT40)			802.11ac(VHT80)		
	Channel	Frequency [MHz]	Power setting	Channel	Frequency [MHz]	Power setting	Channel	Frequency [MHz]	Power setting
U-NII 1	36	5180	18	38	5190	16.5	42	5210	17
	40	5200	18	-	-	-	-	-	-
	48	5240	18	46	5230	18.5	-	-	-
U-NII 2A	52	5260	18.5	54	5270	18.5	58	5290	15.5
	60	5300	18.5	-	-	-	-	-	-
	64	5320	18.5	62	5310	16.5	-	-	-
U-NII 2C	100	5500	18.5	102	5510	18	106	5530	17
	116	5580	18.5	110	5550	19	-	-	-
	144	5720	18.5	142	5710	19.5	138	5690	19.5
U-NII 3	149	5745	18.5	151	5755	18	155	5775	18
	157	5785	18.5	-	-	-	-	-	-
	165	5825	18.5	159	5795	19	-	-	-

Operation test setup for EUT

- Software: QRCT V 3.0.277.0
- Refer to the tables above for power setting value

2.3 Testing Environment

Temperature	: 20 °C ~ 25 °C
Relative humidity content	: 35 % ~ 45 %
Details of power supply	: DC 3.85 V

2.4 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing
→ None

2.5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014 and ANSI C 63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Transmitter Output Power	0.7 dB (The confidence level is about 95 %, $k = 2$)
Conducted spurious emission	0.9 dB (The confidence level is about 95 %, $k = 2$)
AC conducted emission	2.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz Below)	5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz ~ 18 GHz)	5.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

3. SUMMARY OF TESTS

FCC Part Section(s)	RSS Section(s)	Parameter	Limit	Test Condition	Status Note 1
15.407(a)	-	Emission Bandwidth (26 dB Bandwidth)	N/A	Conducted	C
15.407(e)	RSS-247[6.2.4]	Minimum Emission Bandwidth (6 dB Bandwidth)	> 500 kHz in 5725 ~ 5850 MHz		C
15.407(a)	RSS-247[6.2]	Maximum Conducted Output Power	Refer to the section 8.3		C
15.407(a)	RSS-247[6.2]	Peak Power Spectral Density	Refer to the section 8.4		C
-	RSS GEN[6.7]	Occupied Bandwidth (99%)	N/A		C
15.407(h)	RSS-247[6.3]	Dynamic Frequency Selection	FCC 15.407(h)		C Note 3
15.205 15.209 15.407(b)	RSS-247[6.2] RSS-GEN[8.9] RSS-GEN[8.10]	Undesirable Emissions	Refer to the section 8.6	Radiated	C Note 4
15.207	RSS-GEN[8.8]	AC Conducted Emissions	FCC 15.207	AC Line Conducted	C
15.203	-	Antenna Requirements	FCC 15.203	-	C

Note 1: **C** = Comply **NC** = Not Comply **NT** = Not Tested **NA** = Not Applicable

Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.

Note 3: Refer to the DFS test report.

Note 4: These test items were performed in each axis and the worst case data was reported.

4. TEST METHODOLOGY

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB 7899033 D02v02r01 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB789033 D02v02r01. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

4.1 EUT configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

4.3 General test procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB789033 D02v02r01. So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB789033 D02v02r01. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on KDB789033 D02v02r01.

The EUT is placed on a non-conductive table, which is 0.8 m above ground plane. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 1 or 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axis.

4.4 Description of test modes

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode with maximum fixed duty cycle. The worst case data rate was determined as below test mode according to the power measurements.

Test mode	Worst case data rate
802.11a	18 Mbps
802.11n(HT20)	MCS 2
802.11n(HT40)	MCS 0
802.11ac(VHT80)	MCS 1

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment , which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 Facilities

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.		
- FCC MRA Accredited Test Firm No. : KR0034		
- IC Test site No. : 5740A		
www.dtcn.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

6.2 Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, loop, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The antenna is attached on the device by means of unique coupling method (Spring Tension).
Therefore this E.U.T Complies with the requirement of §15.203**

8. TEST RESULT

8.1 Emission Bandwidth (26 dB Bandwidth)

■ Test Requirements

The bandwidth at 26 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The 26 dB bandwidth is used to determine the conducted output power limit.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = approximately **1 %** of the EBW.
2. Set the video bandwidth (**VBW**) > **RBW**.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.


■ Test Results: **Comply**

Mode	Band	Channel	Frequency [MHz]	Test Result [MHz]
802.11a	U-NII 1	36	5180	21.31
		40	5200	21.21
		48	5240	20.71
	U-NII 2A	52	5260	20.67
		60	5300	20.68
		64	5320	20.70
	U-NII 2C	100	5500	20.70
		116	5580	20.65
		144	5720	20.65
802.11n (HT20)	U-NII 1	36	5180	21.07
		40	5200	21.48
		48	5240	21.30
	U-NII 2A	52	5260	21.14
		60	5300	21.24
		64	5320	21.14
	U-NII 2C	100	5500	21.11
		116	5580	20.73
		144	5720	21.16
802.11n (HT40)	U-NII 1	38	5190	41.21
		46	5230	41.70
	U-NII 2A	54	5270	41.70
		62	5310	41.33
	U-NII 2C	102	5510	41.05
		110	5550	41.03
802.11ac (VHT80)	U-NII 1	42	5210	86.17
	U-NII 2A	58	5290	83.34
	U-NII 2C	106	5530	87.43
		138	5690	83.76

Result Plots


26 dB Bandwidth

Test Mode: 802.11a & Ch.36




26 dB Bandwidth

Test Mode: 802.11a & Ch.40



26 dB Bandwidth

Test Mode: 802.11a & Ch.48



26 dB Bandwidth

Test Mode: 802.11a & Ch.52



26 dB Bandwidth

Test Mode: 802.11a & Ch.60




26 dB Bandwidth

Test Mode: 802.11a & Ch.64




26 dB Bandwidth

Test Mode: 802.11a & Ch.100



26 dB Bandwidth

Test Mode: 802.11a & Ch.116




26 dB Bandwidth

Test Mode: 802.11a & Ch.144




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.36




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.40



26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.48




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.52



26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.60




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.64



26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.100




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.116




26 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.144




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.38




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.46




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.54




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.62




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.102




26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.110



26 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.142




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & Ch.42




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & Ch.58




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & Ch.106



26 dB Bandwidth

Test Mode: 802.11ac VHT80 & Ch.138



8.2 Minimum Emission Bandwidth (6 dB Bandwidth)

■ Test Requirements

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth $\geq 3 \times \text{RBW}$.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


■ Test Results: **Comply**

Mode	Band	Channel	Frequency [MHz]	Test Result [MHz]
802.11a	U-NII 3	149	5745	15.45
		157	5785	15.48
		165	5825	16.20
802.11n (HT20)	U-NII 3	149	5745	15.97
		157	5785	15.97
		165	5825	17.26
802.11n (HT40)	U-NII 3	151	5755	35.54
		159	5795	36.04
802.11ac (VHT80)	U-NII 3	155	5775	75.48

■ Result Plots


6 dB Bandwidth

Test Mode: 802.11a & Ch.149




6 dB Bandwidth

Test Mode: 802.11a & Ch.157




6 dB Bandwidth

Test Mode: 802.11a & Ch.165




6 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.149




6 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.157




6 dB Bandwidth

Test Mode: 802.11n HT20 & Ch.165




6 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.151




6 dB Bandwidth

Test Mode: 802.11n HT40 & Ch.159



6 dB Bandwidth

Test Mode: 802.11ac VHT80 & Ch.155



8.3 Maximum Conducted Output Power

■ Test Requirements

Part. 15.407(a)

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) **For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands,** the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) **For the band 5.725 - 5.85 GHz,** the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247[6.2]

(1) For band 5150 - 5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

(2) For band 5250 - 5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(3) For band 5470 - 5600 MHz and 5650 - 5725 MHz


The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5725 - 5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Configuration



Method PM-G

■ Test Procedure

Method PM-G of KDB789033 D02v02r01

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

■ Test Results: **Comply**

- Output Power

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11a	36	5180	18.01	0.90	18.91
	40	5200	18.11	0.90	19.01
	48	5240	17.99	0.90	18.89
	52	5260	18.19	0.40	18.59
	60	5300	18.18	0.40	18.58
	64	5320	18.05	0.40	18.45
	100	5500	18.44	0.10	18.54
	116	5580	18.03	0.10	18.13
	144	5720	18.01	0.10	18.11
	149	5745	18.00	0.30	18.30
	157	5785	18.07	0.30	18.37
	165	5825	18.36	0.30	18.66

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11n(HT20)	36	5180	17.88	0.90	18.78
	40	5200	17.92	0.90	18.82
	48	5240	17.82	0.90	18.72
	52	5260	17.59	0.40	17.99
	60	5300	17.58	0.40	17.98
	64	5320	17.87	0.40	18.27
	100	5500	17.79	0.10	17.89
	116	5580	17.76	0.10	17.86
	144	5720	17.81	0.10	17.91
	149	5745	17.85	0.30	18.15
	157	5785	17.89	0.30	18.19
	165	5825	17.73	0.30	18.03

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11ac(VHT20)	36	5180	17.88	0.90	18.78
	40	5200	17.89	0.90	18.79
	48	5240	17.84	0.90	18.74
	52	5260	17.65	0.40	18.05
	60	5300	17.51	0.40	17.91
	64	5320	17.85	0.40	18.25
	100	5500	17.71	0.10	17.81
	116	5580	17.86	0.10	17.96
	144	5720	17.56	0.10	17.66
	149	5745	17.86	0.30	18.16
	157	5785	17.88	0.30	18.18
	165	5825	17.81	0.30	18.11

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11n(HT40)	38	5190	15.36	0.90	16.26
	46	5230	17.36	0.90	18.26
	54	5270	17.36	0.40	17.76
	62	5310	15.01	0.40	15.41
	102	5510	16.71	0.10	16.81
	110	5550	17.48	0.10	17.58
	142	5710	17.29	0.10	17.39
	151	5755	16.95	0.30	17.25
	159	5795	16.13	0.30	16.43

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11ac(VHT40)	38	5190	15.27	0.90	16.17
	46	5230	17.32	0.90	18.22
	54	5270	17.26	0.40	17.66
	62	5310	15.08	0.40	15.48
	102	5510	16.27	0.10	16.37
	110	5550	17.46	0.10	17.56
	142	5710	17.30	0.10	17.40
	151	5755	15.47	0.30	15.77
	159	5795	16.28	0.30	16.58

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
802.11ac(VHT80)	42	5210	15.46	0.90	16.36
	58	5290	13.71	0.40	14.11
	106	5530	14.82	0.10	14.92
	138	5690	17.96	0.10	18.06
	155	5775	15.01	0.30	15.31

Note 1: e.i.r.p = Conducted Output Power + Antenna Gain

8.4 Maximum Power Spectral Density

■ Test requirements

Part. 15.407(a)

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1,note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

RSS-247[6.2]

(1) For band 5150 - 5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

(2) For band 5250 - 5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less.

The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(3) For band 5470 - 5600 MHz and 5650 - 5725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5725 - 5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Configuration

Refer to the APPENDIX I.

■ Test procedure

Maximum Power Spectral Density is measured using Measurement Procedure of KDB789033 D02v02r01

- 1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA - 1, SA - 2, SA - 3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- 2) Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- 3) Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) **If Method SA - 2 or SA - 2 Alternative was used, add $10 \log(1 / x)$, where x is the duty cycle, to the peak of the spectrum.**
 - b) If Method SA - 3 Alternative was used and the linear mode was used in step II.E.2.g (viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- 4) The result is the Maximum PSD over 1 MHz reference bandwidth.
- 5) For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in §15.407(a)(5). For devices operating in the band 5.725 - 5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 - a) Set $RBW \geq 1 / T$, where T is defined in section II.B.1.a). (Refer to Appendix II)
 - b) Set $VBW \geq 3$ RBW.
 - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz} / \text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log(1 \text{ MHz} / \text{RBW})$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW = 100 kHz is available on nearly all spectrum analyzers.

■ Test results: **Comply**

Mode	Channel	Frequency [MHz]	Reading [dBm]	T.F ^{Note 1} [dB]	Power Spectral Density[dBm]	Antenna Gain [dBi]	e.i.r.p Spectral Density [dBm]
802.11a	36	5180	6.35	0.51	6.86	0.90	7.76
	40	5200	6.72		7.23	0.90	8.13
	48	5240	6.25		6.76	0.90	7.66
	52	5260	6.44		6.95	0.40	7.35
	60	5300	6.59		7.10	0.40	7.50
	64	5320	6.62		7.13	0.40	7.53
	100	5500	6.52		7.03	0.10	7.13
	116	5580	6.54		7.05	0.10	7.15
	144	5720	6.98		7.49	0.10	7.59
	149	5745	-2.06	7.50	5.44	0.30	5.74
	157	5785	-2.36		5.14	0.30	5.44
	165	5825	-2.15		5.35	0.30	5.65
802.11n (HT20)	36	5180	5.77	0.54	6.31	0.90	7.21
	40	5200	6.23		6.77	0.90	7.67
	48	5240	5.88		6.42	0.90	7.32
	52	5260	5.46		6.00	0.40	6.40
	60	5300	5.67		6.21	0.40	6.61
	64	5320	6.19		6.73	0.40	7.13
	100	5500	5.38		5.92	0.10	6.02
	116	5580	5.52		6.06	0.10	6.16
	144	5720	6.32		6.86	0.10	6.96
	149	5745	-2.61	7.53	4.92	0.30	5.22
	157	5785	-3.26		4.27	0.30	4.57
	165	5825	-2.92		4.61	0.30	4.91
802.11n (HT40)	38	5190	1.33	0.39	1.72	0.90	2.62
	46	5230	3.38		3.77	0.90	4.67
	54	5270	3.02		3.41	0.40	3.81
	62	5310	0.85		1.24	0.40	1.64
	102	5510	2.83		3.22	0.10	3.32
	110	5550	3.48		3.87	0.10	3.97
	142	5710	4.16		4.55	0.10	4.65
	151	5755	-6.48	7.38	0.90	0.30	1.20
	159	5795	-5.51		1.87	0.30	2.17
802.11ac (VHT80)	42	5210	-2.91	1.31	-1.60	0.90	-0.70
	58	5290	-4.24		-2.93	0.40	-2.53
	106	5530	-2.92		-1.61	0.10	-1.51
	138	5690	1.33		2.64	0.10	2.74
	155	5775	-9.81	8.30	-1.51	0.30	-1.21

Note 1: "U-NII 1, 2A, 2C [T.F] = DCCF"

"U-NII 3 [T.F] = 10*LOG(500kHz/100kHz) + DCCF"

For DCCF(Duty Cycle Correction Factor) please refer to appendix II.

Note 2: Test Result = Measurement Data + T.F


Note 3: e.i.r.p Spectral Density= Power spectral density + Antenna Gain

RESULT PLOTS

- Power spectral density


Maximum Power Spectral Density

Test Mode: 802.11a & Ch.36




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.40




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.48




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.64




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.144




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.149




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.157




Maximum Power Spectral Density

Test Mode: 802.11a & Ch.165




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.36




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.40




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.48




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.64




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.144




Maximum Power Spectral Density

Test Mode: 802.11n HT20 & Ch.165




Maximum Power Spectral Density

Test Mode: 802.11n HT40 & Ch.38




Maximum Power Spectral Density

Test Mode: 802.11n HT40 & Ch.46




Maximum Power Spectral Density

Test Mode: 802.11n HT40 & Ch.142



Maximum Power Spectral Density

Test Mode: 802.11ac VHT80 & Ch.155



8.5 Radiated Spurious Emission Measurements

■ Test Requirements

• FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

• FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.52025	160.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	12.57675 ~	160.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	12.57725	160.7 ~ 160.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	13.36 ~ 13.41	162.0125 ~ 167.17	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.42 ~ 16.423	167.72 ~ 173.2	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	16.69475 ~	240 ~ 285	2655 ~ 2900		
8.291 ~ 8.294	16.69525	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	16.80425 ~	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	16.80475	608 ~ 614	3345.8 ~ 3358		
	25.5 ~ 25.67	960 ~ 1240	3600 ~ 4000		
	37.5 ~ 38.25				
	73 ~ 74.6				
	74.8 ~ 75.2				

• **FCC Part 15.205(b):** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

• **FCC Part 15.407 (b):** Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the **5.15-5.25 GHz band**: all emissions outside of the **5.15-5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (2) For transmitters operating in the **5.25-5.35 GHz band**: all emissions outside of the **5.15-5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (3) For transmitters operating in the **5.47-5.725 GHz band**: all emissions outside of the **5.47-5.725 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (4) For transmitters operating in the **5.725-5.85 GHz band**: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions **below 1 GHz** must comply with the general field strength limits set forth in **Section 15.209**. Further, any U-NII devices using an **AC power line** are required to comply also with the conducted limits set forth in **Section 15.207**.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turn table shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 1m or 3 m away from the receiving antenna, which is varied from 1m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

Radiated spurious emission measured using following Measurement Procedure of **KDB789033 D02v02r01**

► General Requirements for Unwanted Emissions Measurements

The following requirements apply to all unwanted emissions measurements, both in and outside of the restricted bands:

▪ EUT Duty Cycle

- (1) The EUT shall be configured or modified to **transmit continuously** except as stated in (ii), below. The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (**to no lower than 98 percent**) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.
- (2) If **continuous transmission (or at least 98 percent duty cycle) cannot be achieved** due to hardware limitations of the EUT (e.g., overheating), the following additions to the measurement and reporting procedures are required:
 - The EUT shall be configured to operate at the maximum achievable duty cycle.
 - Measure the duty cycle, x, of the transmitter output signal.
 - Adjustments to measurement procedures (e.g., increasing test time and number of traces averaged) shall be performed as described in the procedures below.
 - The test report shall include the following additional information:
 - The reason for the duty cycle limitation.
 - The duty cycle achieved for testing and the associated transmit duration and interval between transmissions.
 - The sweep time and the amount of time used for trace stabilization during max-hold measurements for peak emission measurements.
- (3) Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

► **Measurements below 1000 MHz**

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Compliance shall be demonstrated using **CISPR quasi-peak detection**; however, **peak detection** is permitted as an alternative to quasi-peak detection.

► **Measurements Above 1000 MHz (Peak)**

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Peak emission levels are measured by setting the analyzer as follows:
 - (i) **RBW = 1 MHz.**
 - (ii) **VBW ≥ 3 MHz.**
 - (iii) **Detector = Peak.**
 - (iv) Sweep time = Auto.
 - (v) Trace mode = Max hold.
 - (vi) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

► **Measurements Above 1000 MHz (Method AD)**

- (i) **RBW = 1 MHz.**
- (ii) **VBW ≥ 3 MHz.**
- (iii) **Detector = RMS**, if $\text{span} / (\# \text{ of points in sweep}) \leq \text{RBW} / 2$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.
- (iv) Averaging type = power (i.e., RMS)
 - As an alternative, the detector and averaging type may be set for linear voltage averaging. Some analyzers require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- (v) Sweep time = Auto.
- (vi) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of $1/x$, where x is the duty cycle. For example, with 50 percent duty cycle, at least 200 traces shall be averaged.
- (vii) If tests are performed with the EUT transmitting at a duty cycle less than 98 percent, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - **If power averaging (RMS) mode was used in step (iv) above, the correction factor is $10 \log(1/x)$, where x is the duty cycle.** For example, if the transmit duty cycle was 50 percent, then 3 dB must be added to the measured emission levels.
 - If linear voltage averaging mode was used in step (iv) above, the correction factor is $20 \log(1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50 percent, then 6 dB must be added to the measured emission levels.
 - If a specific emission is demonstrated to be continuous (100 percent duty cycle) rather than turning on and off with the transmit cycle, no duty cycle correction is required for that emission.

Please refer to Appendix II for the duty correction factor

Test Results:

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11a

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	36 (5180 MHz)	5141.63	H	X	PK	62.50	2.62	N/A	N/A	65.12	74.00	8.88
		5141.73	H	X	AV	45.10	2.62	0.51	N/A	48.23	54.00	5.77
		10359.95	H	Z	PK	46.35	6.32	N/A	N/A	52.67	68.20	15.53
	40 (5200 MHz)	10399.54	H	Z	PK	45.73	6.40	N/A	N/A	52.13	68.20	16.07
	48 (5240 MHz)	10479.74	H	Z	PK	46.31	6.55	N/A	N/A	52.86	68.20	15.34
U-NII 2A	52 (5260 MHz)	10520.03	H	Z	PK	45.91	6.62	N/A	N/A	52.53	68.20	15.67
	60 (5300 MHz)	10600.46	H	Z	PK	45.61	6.75	N/A	N/A	52.36	74.00	21.64
		10600.10	H	Z	AV	35.23	6.75	0.51	N/A	42.49	54.00	11.51
	64 (5320 MHz)	5358.39	H	Z	PK	56.75	3.46	N/A	N/A	60.21	74.00	13.79
		5358.34	H	Z	AV	43.03	3.46	0.51	N/A	47.00	54.00	7.00
		10640.15	H	Z	PK	45.17	6.82	N/A	N/A	51.99	74.00	22.01
		10639.65	H	Z	AV	34.41	6.82	0.51	N/A	41.74	54.00	12.26

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{-9.54 \text{ dB}}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11a

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	100 (5500 MHz)	5458.00	H	X	PK	58.87	3.59	N/A	N/A	62.46	74.00	11.54
		5457.62	H	X	AV	41.96	3.59	0.51	N/A	46.06	54.00	7.94
		5469.37	H	X	PK	60.34	3.61	N/A	N/A	63.95	68.20	4.25
		11000.05	H	Z	PK	45.73	7.42	N/A	N/A	53.15	74.00	20.85
		10999.69	H	z	AV	35.09	7.42	0.51	N/A	43.02	54.00	10.98
	116 (5580 MHz)	11199.61	H	Z	PK	45.88	7.94	N/A	N/A	53.82	74.00	20.18
		11199.85	H	Z	AV	35.31	7.94	0.51	N/A	43.76	54.00	10.24
	144 (5720 MHz)	11440.09	H	Z	PK	46.28	8.57	N/A	N/A	54.85	74.00	19.15
		11439.59	H	Z	AV	35.12	8.57	0.51	N/A	44.20	54.00	9.80
U-NII 3	149 (5745 MHz)	5714.39	H	X	PK	60.19	4.58	N/A	N/A	64.77	68.20	3.43
		5724.56	H	X	PK	65.41	4.43	N/A	N/A	69.84	78.20	8.36
		11490.15	H	Z	PK	45.65	8.70	N/A	N/A	54.35	74.00	19.65
		11489.71	H	Z	AV	34.93	8.70	0.51	N/A	44.14	54.00	9.86
	157 (5785 MHz)	11570.45	H	Z	PK	46.17	8.74	N/A	N/A	54.91	74.00	19.09
		11570.11	H	Z	AV	34.99	8.74	0.51	N/A	44.24	54.00	9.76
	165 (5825 MHz)	5850.76	H	X	PK	58.42	6.08	N/A	N/A	64.50	78.20	13.70
		5863.74	H	X	PK	58.61	6.56	N/A	N/A	65.17	68.20	3.03
		11650.14	H	Z	PK	46.85	8.75	N/A	N/A	55.60	74.00	18.40
		11650.38	H	Z	AV	35.48	8.75	0.51	N/A	44.74	54.00	9.26

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11n(HT20)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	36 (5180 MHz)	5149.20	H	X	PK	60.48	2.63	N/A	N/A	63.11	74.00	10.89
		5149.03	H	X	AV	43.02	2.63	0.54	N/A	46.19	54.00	7.81
		10360.50	H	Z	PK	46.01	6.32	N/A	N/A	52.33	68.20	15.87
	40 (5200 MHz)	10399.90	H	Z	PK	45.77	6.40	N/A	N/A	52.17	68.20	16.03
	48 (5240 MHz)	10479.65	H	Z	PK	46.02	6.55	N/A	N/A	52.57	68.20	15.63
U-NII 2A	52 (5260 MHz)	10519.57	H	Z	PK	46.25	6.62	N/A	N/A	52.87	68.20	15.33
	60 (5300 MHz)	10600.17	H	Z	PK	45.58	6.75	N/A	N/A	52.33	74.00	21.67
		10600.04	H	Z	AV	35.16	6.75	0.54	N/A	42.45	54.00	11.55
	64 (5320 MHz)	5351.22	H	X	PK	55.62	3.45	N/A	N/A	59.07	74.00	14.93
		5351.13	H	X	AV	41.55	3.45	0.54	N/A	45.54	54.00	8.46
		10639.84	H	Z	PK	45.04	6.82	N/A	N/A	51.86	74.00	22.14
		10640.36	H	Z	AV	34.18	6.82	0.54	N/A	41.54	54.00	12.46

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{-9.54 \text{ dB}}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11n(HT20)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	100 (5500 MHz)	5458.90	H	X	PK	55.20	3.59	N/A	N/A	58.79	74.00	15.21
		5458.30	H	X	AV	41.57	3.59	0.54	N/A	45.70	54.00	8.30
		5466.56	H	X	PK	57.47	3.60	N/A	N/A	61.07	68.20	7.13
		10999.63	H	Z	PK	45.44	7.42	N/A	N/A	52.86	74.00	21.14
		10999.98	H	Z	AV	35.05	7.42	0.54	N/A	43.01	54.00	10.99
	116 (5580 MHz)	11200.26	H	Z	PK	45.99	7.94	N/A	N/A	53.93	74.00	20.07
		11199.72	H	Z	AV	35.40	7.94	0.54	N/A	43.88	54.00	10.12
	144 (5720 MHz)	11440.47	H	Z	PK	46.25	8.57	N/A	N/A	54.82	74.00	19.18
		11439.98	H	Z	AV	35.21	8.57	0.54	N/A	44.32	54.00	9.68
U-NII 3	149 (5745 MHz)	5714.92	H	X	PK	60.43	4.58	N/A	N/A	65.01	68.20	3.19
		5724.89	H	X	PK	65.49	4.42	N/A	N/A	69.91	78.20	8.29
		11490.44	H	Z	PK	45.27	8.70	N/A	N/A	53.97	74.00	20.03
		11489.67	H	Z	AV	34.71	8.70	0.54	N/A	43.95	54.00	10.05
	157 (5785 MHz)	11569.68	H	Z	PK	45.75	8.74	N/A	N/A	54.49	74.00	19.51
		11569.58	H	Z	AV	35.04	8.74	0.54	N/A	44.32	54.00	9.68
	165 (5825 MHz)	5856.97	H	X	PK	59.22	6.16	N/A	N/A	65.38	78.20	12.82
		5860.99	H	X	PK	58.98	6.29	N/A	N/A	65.27	68.20	2.93
		11649.69	H	Z	PK	45.75	8.74	N/A	N/A	54.49	74.00	19.51
		11649.88	H	Z	AV	35.43	8.74	0.54	N/A	44.71	54.00	9.29

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11n(HT40)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	38 (5190 MHz)	5149.68	H	X	PK	59.13	2.63	N/A	N/A	61.76	74.00	12.24
		5149.75	H	X	AV	47.98	2.63	0.39	N/A	51.00	54.00	3.00
		10380.24	H	Z	PK	46.04	6.36	N/A	N/A	52.40	68.20	15.80
	46 (5230 MHz)	10460.52	H	Z	PK	45.79	6.51	N/A	N/A	52.30	68.20	15.90
U-NII 2A	54 (5270 MHz)	10540.23	H	Z	PK	45.80	6.65	N/A	N/A	52.45	68.20	15.75
	62 (5310 MHz)	5351.02	H	X	PK	58.93	3.45	N/A	N/A	62.38	74.00	11.62
		5350.08	H	X	AV	47.27	3.45	0.39	N/A	51.11	54.00	2.89
		10619.71	H	Z	PK	46.10	6.78	N/A	N/A	52.88	74.00	21.12
		10620.49	H	Z	AV	35.17	6.79	0.39	N/A	42.35	54.00	11.65

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11n(HT40)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	102 (5510 MHz)	5458.76	H	X	PK	60.02	3.59	N/A	N/A	63.61	74.00	10.39
		5459.69	H	X	AV	45.84	3.59	0.39	N/A	49.82	54.00	4.18
		5469.82	H	X	PK	61.98	3.61	N/A	N/A	65.59	68.20	2.61
		11019.65	H	Z	PK	46.03	7.47	N/A	N/A	53.50	74.00	20.50
		11020.18	H	Z	AV	35.24	7.47	0.39	N/A	43.10	54.00	10.90
	110 (5550 MHz)	11179.86	H	Z	PK	46.45	7.89	N/A	N/A	54.34	74.00	19.66
		11179.86	H	Z	AV	35.24	7.89	0.39	N/A	43.52	54.00	10.48
	142 (5710 MHz)	11419.46	H	Z	PK	45.90	8.52	N/A	N/A	54.42	74.00	19.58
		11420.19	H	Z	AV	35.64	8.52	0.39	N/A	44.55	54.00	9.45
U-NII 3	151 (5755 MHz)	5712.68	H	X	PK	59.61	4.57	N/A	N/A	64.18	68.20	4.02
		5724.34	H	X	PK	60.65	4.43	N/A	N/A	65.08	78.20	13.12
		11509.71	H	Z	PK	45.76	8.73	N/A	N/A	54.49	74.00	19.51
		11509.87	H	Z	AV	35.34	8.73	0.39	N/A	44.46	54.00	9.54
	159 (5795 MHz)	5854.38	H	X	PK	60.23	6.15	N/A	N/A	66.38	78.20	11.82
		5863.18	H	X	PK	58.85	6.49	N/A	N/A	65.34	68.20	2.86
		11590.28	H	Z	PK	46.81	8.74	N/A	N/A	55.55	74.00	18.45
		11590.35	H	Z	AV	35.50	8.74	0.39	N/A	44.63	54.00	9.37

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{-9.54 \text{ dB}}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : 802.11ac(VHT80)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	42 (5210 MHz)	5149.92	H	X	PK	63.79	2.63	N/A	N/A	66.42	74.00	7.58
		5149.90	H	X	AV	46.75	2.63	1.31	N/A	50.69	54.00	3.31
		10419.57	H	Z	PK	46.22	6.43	N/A	N/A	52.65	68.20	15.55
U-NII 2A	58 (5290 MHz)	5350.15	H	X	PK	55.85	3.45	N/A	N/A	59.30	74.00	14.70
		5350.18	H	X	AV	46.07	3.45	1.31	N/A	50.83	54.00	3.17
		10580.42	H	Z	PK	46.01	6.72	N/A	N/A	52.73	68.20	15.47

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

Radiated Spurious Emissions data(9 kHz ~ 40 GHz) 802.11ac(VHT80)

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	106 (5530 MHz)	5458.91	H	X	PK	55.76	3.59	N/A	N/A	59.35	74.00	14.65
		5459.65	H	X	AV	45.07	3.59	1.31	N/A	49.97	54.00	4.03
		5467.45	H	X	PK	57.74	3.61	N/A	N/A	61.35	68.20	6.85
		11059.84	H	Z	PK	46.29	7.58	N/A	N/A	53.87	74.00	20.13
		11060.07	H	Z	AV	35.69	7.58	1.31	N/A	44.58	54.00	9.42
	138 (5690 MHz)	11379.74	H	X	PK	45.92	8.41	N/A	N/A	54.33	74.00	19.67
		11380.38	H	X	AV	34.84	8.42	1.31	N/A	44.57	54.00	9.43
U-NII 3	155 (5775 MHz)	5713.24	H	X	PK	60.25	4.57	N/A	N/A	64.82	68.20	3.38
		5722.84	H	X	PK	61.04	4.45	N/A	N/A	65.49	78.20	12.71
		5850.76	H	X	PK	58.77	6.08	N/A	N/A	64.85	78.20	13.35
		5867.56	H	X	PK	57.70	6.92	N/A	N/A	64.62	68.20	3.58
		11549.70	H	Z	PK	46.04	8.73	N/A	N/A	54.77	74.00	19.23
		11549.62	H	Z	AV	35.47	8.73	1.31	N/A	45.51	54.00	8.49

Note.

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- Information of Distance Factor
For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.
- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$
When distance factor is "N/A", the distance is 3 m and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- The limit is converted to field strength.
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$

8.6 AC Conducted Emissions

■ Test Requirements and limit, §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

■ Test Configuration

See test photographs for the actual connections between EUT and support equipment.

■ Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m $\times$ 3.5 m $\times$ 3.5 m (L $\times$ W $\times$ H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) $\times$ 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

■ Test Results: **Comply**

Note 1: See next pages for actual measured spectrum plots and data for worst case result.

AC Line Conducted Emissions (Graph)

Test Mode: U-NII 1 & 802.11a & 5180 MHz

Results of Conducted Emission

DTNC



Date 2019-07-19

Order No.
Model No. PM90G
Serial No.
Test Condition 5.1G

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 °C / 35 %
Operator WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Line Conducted Emissions (Data List)

Test Mode: U-NII 1 & 802.11a & 5180 MHz

Results of Conducted Emission

DTNC

Date 2019-07-19

Order No.		Reference No.	
Model No.	PM90G	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 'C / 35 %
Test Condition	5.1G	Operator	WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.15620	27.47	16.65	9.94	37.41	26.59	65.66	55.66	28.25	29.07	N
2	0.42516	31.56	25.87	9.95	41.51	35.82	57.35	47.35	15.84	11.53	N
3	0.61310	23.28	13.79	9.96	33.24	23.75	56.00	46.00	22.76	22.25	N
4	0.94756	24.85	16.20	9.97	34.82	26.17	56.00	46.00	21.18	19.83	N
5	1.66440	23.02	14.81	10.01	33.03	24.82	56.00	46.00	22.97	21.18	N
6	3.07840	17.91	12.10	10.07	27.98	22.17	56.00	46.00	28.02	23.83	N
7	7.59260	12.21	6.40	10.24	22.45	16.64	60.00	50.00	37.55	33.36	N
8	14.35840	5.40	0.56	10.48	15.88	11.04	60.00	50.00	44.12	38.96	N
9	16.92460	8.83	3.19	10.51	19.34	13.70	60.00	50.00	40.66	36.30	N
10	0.15688	25.88	18.60	9.94	35.82	28.54	65.63	55.63	29.81	27.09	L1
11	0.41831	28.82	19.29	9.95	38.77	29.24	57.48	47.48	18.71	18.24	L1
12	0.96802	23.51	13.66	9.97	33.48	23.63	56.00	46.00	22.52	22.37	L1
13	1.68900	23.02	11.70	10.01	33.03	21.71	56.00	46.00	22.97	24.29	L1
14	3.08080	17.73	8.28	10.06	27.79	18.34	56.00	46.00	28.21	27.66	L1
15	6.22820	16.15	6.19	10.20	26.35	16.39	60.00	50.00	33.65	33.61	L1
16	12.70940	10.46	1.29	10.41	20.87	11.70	60.00	50.00	39.13	38.30	L1
17	16.95920	12.91	3.63	10.49	23.40	14.12	60.00	50.00	36.60	35.88	L1
18	19.67520	8.12	-0.71	10.53	18.65	9.82	60.00	50.00	41.35	40.18	L1

AC Line Conducted Emissions (Graph)

Test Mode: U-NII 2A & 802.11a & 5260 MHz

Results of Conducted Emission

DTNC


Date 2019-07-19

Order No.
Model No. PM90G
Serial No.
Test Condition 5.3G

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 'C / 35 %
Operator WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Line Conducted Emissions (Data List)

Test Mode: U-NII 2A & 802.11a & 5260 MHz

Results of Conducted Emission

DTNC

Date 2019-07-19

Order No.
Model No. PM90G
Serial No.
Test Condition 5.3G

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 'C / 35 %
Operator WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16138	26.37	14.02	9.94	36.31	23.96	65.39	55.39	29.08	31.43	N
2	0.42150	30.70	25.44	9.95	40.65	35.39	57.42	47.42	16.77	12.03	N
3	0.85530	24.15	13.59	9.97	34.12	23.56	56.00	46.00	21.88	22.44	N
4	0.89550	23.99	15.93	9.97	33.96	25.90	56.00	46.00	22.04	20.10	N
5	2.04480	19.27	13.91	10.03	29.30	23.94	56.00	46.00	26.70	22.06	N
6	2.21800	17.21	11.10	10.03	27.24	21.13	56.00	46.00	28.76	24.87	N
7	4.12200	14.87	9.69	10.12	24.99	19.81	56.00	46.00	31.01	26.19	N
8	8.65400	10.81	5.13	10.29	21.10	15.42	60.00	50.00	38.90	34.58	N
9	16.69160	10.36	4.78	10.51	20.87	15.29	60.00	50.00	39.13	34.71	N
10	0.15727	26.91	18.36	9.94	36.85	28.30	65.61	55.61	28.76	27.31	L1
11	0.42723	29.23	19.45	9.95	39.18	29.40	57.31	47.31	18.13	17.91	L1
12	1.24400	21.89	11.41	9.98	31.87	21.39	56.00	46.00	24.13	24.61	L1
13	1.66840	22.66	11.33	10.01	32.67	21.34	56.00	46.00	23.33	24.66	L1
14	3.01080	16.56	7.24	10.06	26.62	17.30	56.00	46.00	29.38	28.70	L1
15	5.98700	14.33	5.02	10.18	24.51	15.20	60.00	50.00	35.49	34.80	L1
16	11.21220	12.51	2.14	10.37	22.88	12.51	60.00	50.00	37.12	37.49	L1
17	16.72860	15.12	5.35	10.48	25.60	15.83	60.00	50.00	34.40	34.17	L1

AC Line Conducted Emissions (Graph)

Test Mode: U-NII 2C & 802.11a & 5720 MHz

Results of Conducted Emission

DTNC



Date 2019-07-19

Order No.
Model No. PM90G
Serial No.
Test Condition 5.5G

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 °C / 35 %
Operator WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Line Conducted Emissions (Data List)

Test Mode: U-NII 2C & 802.11a & 5720 MHz

Results of Conducted Emission

DTNC

Date 2019-07-19

Order No.		Reference No.	
Model No.	PM90G	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 °C / 35 %
Test Condition	5.5G	Operator	WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16885	26.00	14.79	9.94	35.94	24.73	65.02	55.02	29.08	30.29	N
2	0.42348	30.55	25.47	9.95	40.50	35.42	57.38	47.38	16.88	11.96	N
3	0.70620	22.92	14.99	9.97	32.89	24.96	56.00	46.00	23.11	21.04	N
4	1.54360	21.75	11.66	10.01	31.76	21.67	56.00	46.00	24.24	24.33	N
5	3.25200	15.42	10.02	10.09	25.51	20.11	56.00	46.00	30.49	25.89	N
6	5.85380	13.39	8.31	10.18	23.57	18.49	60.00	50.00	36.43	31.51	N
7	12.70440	8.32	2.19	10.42	18.74	12.61	60.00	50.00	41.26	37.39	N
8	16.73560	10.37	4.67	10.51	20.88	15.18	60.00	50.00	39.12	34.82	N
9	0.16928	25.26	15.54	9.94	35.20	25.48	65.00	55.00	29.80	29.52	L1
10	0.18114	24.89	14.49	9.94	34.83	24.43	64.43	54.43	29.60	30.00	L1
11	0.42807	29.12	19.50	9.95	39.07	29.45	57.29	47.29	18.22	17.84	L1
12	0.74780	22.92	13.06	9.96	32.88	23.02	56.00	46.00	23.12	22.98	L1
13	1.61460	21.89	10.44	10.01	31.90	20.45	56.00	46.00	24.10	25.55	L1
14	3.02080	16.40	7.21	10.06	26.46	17.27	56.00	46.00	29.54	28.73	L1
15	7.72100	13.15	2.95	10.24	23.39	13.19	60.00	50.00	36.61	36.81	L1
16	16.05740	14.54	5.52	10.47	25.01	15.99	60.00	50.00	34.99	34.01	L1

AC Line Conducted Emissions (Graph)

Test Mode: U-NII 3 & 802.11a & 5745 MHz

Results of Conducted Emission

DTNC



Date 2019-07-19

Order No.
Model No. PM90G
Serial No.
Test Condition 5.7G

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 °C / 35 %
Operator WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



AC Line Conducted Emissions (Data List)

Test Mode: U-NII 3 & 802.11a & 5745 MHz

Results of Conducted Emission

DTNC

Date 2019-07-19

Order No.		Reference No.	
Model No.	PM90G	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 'C / 35 %
Test Condition	5.7G	Operator	WooHyunLim

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16726	26.59	15.17	9.94	36.53	25.11	65.10	55.10	28.57	29.99	N
2	0.25808	21.91	7.65	9.94	31.85	17.59	61.49	51.49	29.64	33.90	N
3	0.42659	30.73	25.54	9.95	40.68	35.49	57.32	47.32	16.64	11.83	N
4	0.95724	21.64	12.02	9.97	31.61	21.99	56.00	46.00	24.39	24.01	N
5	1.66640	20.57	10.93	10.01	30.58	20.94	56.00	46.00	25.42	25.06	N
6	3.99780	14.95	9.94	10.12	25.07	20.06	56.00	46.00	30.93	25.94	N
7	6.22820	13.23	7.64	10.20	23.43	17.84	60.00	50.00	36.57	32.16	N
8	6.31100	12.08	6.86	10.20	22.28	17.06	60.00	50.00	37.72	32.94	N
9	16.78980	9.76	4.19	10.51	20.27	14.70	60.00	50.00	39.73	35.30	N
10	22.94060	5.06	-2.85	10.61	15.67	7.76	60.00	50.00	44.33	42.24	N
11	0.17472	25.62	12.06	9.94	35.56	22.00	64.73	54.73	29.17	32.73	L1
12	0.43315	27.87	18.34	9.95	37.82	28.29	57.19	47.19	19.37	18.90	L1
13	0.74798	23.42	14.11	9.96	33.38	24.07	56.00	46.00	22.62	21.93	L1
14	1.29000	20.31	10.49	9.98	30.29	20.47	56.00	46.00	25.71	25.53	L1
15	1.87060	20.74	10.14	10.03	30.77	20.17	56.00	46.00	25.23	25.83	L1
16	5.23080	14.76	4.27	10.16	24.92	14.43	60.00	50.00	35.08	35.57	L1
17	16.39540	16.10	6.28	10.48	26.58	16.76	60.00	50.00	33.42	33.24	L1
18	22.24280	5.35	-2.38	10.57	15.92	8.19	60.00	50.00	44.08	41.81	L1
19	23.15900	5.09	-2.77	10.59	15.68	7.82	60.00	50.00	44.32	42.18	L1