

FCC TEST REPORT

(PART 27)


Applicant:	POINTMOBILE CO.,LTD
Address:	9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu, Seoul, Korea 08512

Manufacturer or Supplier:	POINTMOBILE CO.,LTD
Address:	9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu, Seoul, Korea 08512
Product:	Moblie computer
Brand Name:	Point mobile
Model Name:	PM95
FCC ID:	V2X-PM95
Date of tests:	Jan. 08, 2024 ~ May. 10, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 27** ☒ **ANSI/TIA/EIA-603-D**
☒ **FCC Part 2** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: May. 10, 2024	 Date: May. 10, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: W7L-P23120020RF03

TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS	6
1.1 MEASUREMENT UNCERTAINTY	8
1.2 TEST SITE AND INSTRUMENTS	9
2 GENERAL INFORMATION	11
2.1 GENERAL DESCRIPTION OF EUT	11
2.2 CONFIGURATION OF SYSTEM UNDER TEST	16
2.3 DESCRIPTION OF SUPPORT UNITS	17
2.4 TEST ITEM AND TEST CONFIGURATION	17
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	24
3 TEST TYPES AND RESULTS	25
3.1 OUTPUT POWER MEASUREMENT	25
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	25
3.1.2 TEST PROCEDURES	25
3.1.3 TEST SETUP	26
3.1.4 TEST RESULTS	27
3.2 FREQUENCY STABILITY MEASUREMENT	60
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	60
3.2.2 TEST PROCEDURE	60
3.2.3 TEST SETUP	60
3.2.4 TEST RESULTS	61
3.3 OCCUPIED BANDWIDTH MEASUREMENT	62
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	62
3.3.2 TEST SETUP	62
3.3.3 TEST PROCEDURES	62
3.3.4 TEST RESULTS	63
3.4 BAND EDGE MEASUREMENT	64
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	64
3.4.2 TEST SETUP	65
3.4.3 TEST PROCEDURES	66
3.4.4 TEST RESULTS	67
3.5 CONDUCTED SPURIOUS EMISSIONS	68
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	68
3.5.2 TEST PROCEDURE	68
3.5.3 TEST SETUP	68
3.5.4 TEST RESULTS	68
3.6 RADIATED EMISSION MEASUREMENT	70
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	70
3.6.2 TEST PROCEDURES	70
3.6.3 DEVIATION FROM TEST STANDARD	70
3.6.4 TEST SETUP	71
3.6.5 TEST RESULTS	73
3.7 PEAK TO AVERAGE RATIO	125
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	125
3.7.2 TEST SETUP	125
3.7.3 TEST PROCEDURES	125
3.7.4 TEST RESULTS	126



Test Report No.: W7L-P23120020RF03

4 INFORMATION ON THE TESTING LABORATORIES	127
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB. 128	
6 APPENDIX	129
WCDMA BAND4	129
PEAK-TO-AVERAGE RATIO	129
TEST RESULT	129
TEST GRAPHS	130
26DB BANDWIDTH AND OCCUPIED BANDWIDTH	131
TEST RESULT	131
TEST GRAPHS	132
BAND EDGE	133
TEST RESULT	133
TEST GRAPHS	134
CONDUCTED SPURIOUS EMISSION.....	135
TEST RESULT	135
TEST GRAPHS	136
FREQUENCY STABILITY	138
TEST RESULT	138
LTE BAND7	139
PEAK-TO-AVERAGE RATIO(CCDF).....	139
TEST RESULT	139
TEST GRAPHS	140
26DB BANDWIDTH AND OCCUPIED BANDWIDTH	146
TEST RESULT	146
TEST GRAPHS	147
BAND EDGE	159
TEST RESULT	159
TEST GRAPHS	160
CONDUCTED SPURIOUS EMISSION.....	176
TEST RESULT	176
TEST GRAPHS	177
FREQUENCY STABILITY	189
TEST RESULT	189
LTE BAND12 (INCLUDING B17).....	191
PEAK-TO-AVERAGE RATIO(CCDF).....	191
TEST RESULT	191
TEST GRAPHS	192
26DB BANDWIDTH AND OCCUPIED BANDWIDTH	198
TEST RESULT	198
TEST GRAPHS	199
BAND EDGE	211
TEST RESULT	211
TEST GRAPHS	212
CONDUCTED SPURIOUS EMISSION.....	228
TEST RESULT	228
TEST GRAPHS	229
FREQUENCY STABILITY	241
TEST RESULT	241
LTE BAND13.....	243
PEAK-TO-AVERAGE RATIO(CCDF).....	243
TEST RESULT	243
TEST GRAPHS	244



Test Report No.: W7L-P23120020RF03

26DB BANDWIDTH AND OCCUPIED BANDWIDTH	246
TEST RESULT	246
TEST GRAPHS	247
BAND EDGE	251
TEST RESULT	251
TEST GRAPHS	252
CONDUCTED SPURIOUS EMISSION	259
TEST RESULT	259
TEST GRAPHS	260
FREQUENCY STABILITY	264
TEST RESULT	264
LTE BAND71	265
PEAK-TO-AVERAGE RATIO(CCDF)	265
TEST RESULT	265
TEST GRAPHS	266
26DB BANDWIDTH AND OCCUPIED BANDWIDTH	272
TEST RESULT	272
TEST GRAPHS	273
BAND EDGE	285
TEST RESULT	285
TEST GRAPHS	286
CONDUCTED SPURIOUS EMISSION	302
TEST RESULT	302
TEST GRAPHS	303
FREQUENCY STABILITY	315
TEST RESULT	315



Test Report No.: W7L-P23120020RF03

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P23120020RF03	Original release	May. 10, 2024

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 27 & PART 2			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
§2.1046	Conducted Output Power	Compliance	A
§27.50(b)(10) §27.50(c)(10)	Effective Radiated Power (Band 12) (Band 13) (Band 17) (Band 71)	Compliance	A
§27.50(d)(4) §27.50(h)(2)	Equivalent Isotropically Radiated Power (WCMDA Band 4)(Band 7)	Compliance	A
§2.1055 §27.54	Frequency Stability	Compliance	A
§2.1049	Occupied Bandwidth	Compliance	A
§2.1051 §27.53(c)(2)(4) §27.53(g) §27.53(h) §27.53(m)(4)(6)	Conducted Band Edge Measurements (WCMDA Band 4) (Band 7) (Band 12) (Band 13) (Band 17) (Band 71)	Compliance	A
§2.1051 §27.53(c)(2)(4) §27.53(g) §27.53(h) §27.53(m)(4)(6)	Conducted Spurious Emissions (WCMDA Band 4)(Band 7) (Band 12) (Band 13) (Band 17) (Band 71)	Compliance	A
§2.1053 §27.53(c)(2)(4) §27.53(f) §27.53(g) §27.53(h) §27.53(m)(4)(6)	Radiated Spurious Emissions (WCMDA Band 4)(Band 7) (Band 12) (Band 13) (Band 17) (Band 71)	Compliance	A
NA	Peak to average ratio	Compliance	A



Test Report No.: W7L-P23120020RF03

***Test Lab Information Reference**

Lab A:

BV 7Layers Communications Technology (Shenzhen) Co., Ltd

Lab Address:

Room B37, Warehouse A5, No.3 Chiwan 4th Road, Zhaoshang Street, Nanshan District Shenzhen, Guangdong, People's Republic of China

Accredited Test Lab Cert 3939.01

The FCC Site Registration No. : 525120; Designation No. : CN1171;

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 27,24	Mar. 26,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,23	May.09,24
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.09,24	May.08,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.02,23	Sep.01,24
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,23	Feb. 17,24
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 17,24	Feb. 16,25
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,23	Feb. 17,24
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 17,24	Feb. 16,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.03, 23	Sep.02, 24
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,23	Feb. 13,24
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 13,24	Feb. 12,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,23	May. 05,24
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 05,24	May. 04,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,23	May.09,24
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.09,24	May.08,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,23	Feb.16,24
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb.16,24	Feb.15,25
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,23	May. 05,24
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 05,24	May. 04,25
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,23	Feb. 13,24
Power Meter	Anritsu	ML2495A	1506002	Feb. 13,24	Feb. 12,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,23	Feb. 13,24
Power Sensor	Anritsu	MA2411B	1339352	Feb. 13,24	Feb. 12,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,23	May. 05,24
Temperature Chamber	ESPEC	SH-242	93000855	May. 05,24	May. 04,25
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,23	Feb. 13,24
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 13,24	Feb. 12,25



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.10,23	May.09,24
Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.09,24	May.08,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,23	Aug. 10,24
N9010B keysight SN	KEYSIGHT	N9010B	MY62170516	Aug. 01,23	Jul. 31, 24

- NOTE:**
1. The calibration interval of the above test instruments is 12/ 36 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
 3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile computer	
BRAND NAME	Point mobile	
MODEL NAME	PM95	
NOMINAL VOLTAGE	5.0Vdc (adapter) 3.87Vdc (battery)	
MODULATION TECHNOLOGY	WCDMA IV	BPSK, QPSK
	LTE	QPSK, 16QAM, 64QAM, 256QAM
FREQUENCY RANGE	WCDMA IV	1712.4MHz ~ 1752.6MHz
	LTE Band 7 Channel Bandwidth: 5MHz	2502.5MHz ~ 2567.5MHz
	LTE Band 7 Channel Bandwidth: 10MHz	2505MHz ~ 2565MHz
	LTE Band 7 Channel Bandwidth: 15MHz	2507.5MHz ~ 2562.5MHz
	LTE Band 7 Channel Bandwidth: 20MHz	2510MHz ~ 2560MHz
	LTE Band 12 Channel Bandwidth: 1.4MHz	699.7MHz ~ 715.3MHz
	LTE Band 12 Channel Bandwidth: 3MHz	700.5MHz ~ 714.5MHz
	LTE Band 12 Channel Bandwidth: 5MHz	701.5MHz ~ 713.5MHz
	LTE Band 12 Channel Bandwidth: 10MHz	704MHz ~ 711MHz
	LTE Band 13 Channel Bandwidth: 5MHz	779.5MHz ~ 784.5MHz
	LTE Band 13 Channel Bandwidth: 10MHz	782MHz
	LTE Band 17 Channel Bandwidth: 5MHz	706.5MHz ~ 713.5MHz
	LTE Band 17 Channel Bandwidth: 10MHz	709MHz ~ 711 MHz
	LTE Band 30 Channel Bandwidth: 5MHz	2307.5MHz ~ 2312.5MHz
	LTE Band 30 Channel Bandwidth: 10MHz	2310MHz

FREQUENCY RANGE	LTE Band 71 Channel Bandwidth: 5MHz	665.5MHz ~ 695.5MHz
	LTE Band 71 Channel Bandwidth: 10MHz	668MHz ~ 693MHz
	LTE Band 71 Channel Bandwidth: 15MHz	670.5MHz ~ 690.5MHz
	LTE Band 71 Channel Bandwidth: 20MHz	673MHz ~ 688MHz
	LTE CA	The following only support downlink: CA_7A-12A CA_7A-13A CA_7A-26A CA_7A-29A CA_7A-66A CA_7A-7A CA_7B CA_7C CA_7A-71A CA_12A-12A CA_12A-25A CA_12A-66A CA_12B CA_12A-30A CA_13A-48A CA_13A-66A CA_13A-48A-48A CA_13A-66A-66A
MAX. EIRP POWER	WCDMA IV	197.7mW
	LTE Band 7 Channel Bandwidth: 5MHz	121.9mW
	LTE Band 7 Channel Bandwidth: 10MHz	123.03mW
	LTE Band 7 Channel Bandwidth: 15MHz	122.18mW
	LTE Band 7 Channel Bandwidth: 20MHz	125.31mW
	LTE Band 12 Channel Bandwidth: 1.4MHz	97.72mW
	LTE Band 12 Channel Bandwidth: 3MHz	98.63mW

MAX. EIRP POWER	LTE Band 12 Channel Bandwidth: 5MHz	99.08mW
	LTE Band 12 Channel Bandwidth: 10MHz	99.77mW
	LTE Band 13 Channel Bandwidth: 5MHz	104.23mW
	LTE Band 13 Channel Bandwidth: 10MHz	105.44mW
	LTE Band 17 Channel Bandwidth: 5MHz	101.39mW
	LTE Band 17 Channel Bandwidth: 10MHz	103.99mW
	LTE Band 71 Channel Bandwidth: 5MHz	98.63mW
	LTE Band 71 Channel Bandwidth: 10MHz	98.63mW
	LTE Band 71 Channel Bandwidth: 15MHz	99.54mW
	LTE Band 71 Channel Bandwidth: 20MHz	100.23mW
	ENDC LTE Band 7 Channel Bandwidth: 5MHz	119.4mW
	ENDC LTE Band 7 Channel Bandwidth: 10MHz	120.23mW
	ENDC LTE Band 7 Channel Bandwidth: 15MHz	120.23mW
	ENDC LTE Band 7 Channel Bandwidth: 20MHz	122.46mW
EMISSION DESIGNATOR	WCDMA IV	4M16F9W
	LTE Band 7 Channel Bandwidth: 5MHz	QPSK: 4M52G7D
		16QAM: 4M53W7D
	LTE Band 7 Channel Bandwidth: 10MHz	QPSK: 9M03G7D
		16QAM: 9M03W7D
	LTE Band 7 Channel Bandwidth: 15MHz	QPSK: 13M5G7D
		16QAM: 13M5W7D
	LTE Band 7 Channel Bandwidth: 20MHz	QPSK: 18M0G7D
		16QAM: 18M0W7D

EMISSION DESIGNATOR	LTE Band 12 Channel Bandwidth: 1.4MHz	QPSK: 1M11G7D 16QAM: 1M10W7D
	LTE Band 12 Channel Bandwidth: 3MHz	QPSK: 2M70G7D 16QAM: 2M70W7D
	LTE Band 12 Channel Bandwidth: 5MHz	QPSK: 4M53G7D 16QAM: 4M52W7D
	LTE Band 12 Channel Bandwidth: 10MHz	QPSK: 9M02G7D 16QAM: 9M00W7D
	LTE Band 13 Channel Bandwidth: 5MHz	QPSK: 4M53G7D 16QAM: 4M52W7D
	LTE Band 13 Channel Bandwidth: 10MHz	QPSK: 8M97G7D 16QAM: 8M98W7D
	LTE Band 71 Channel Bandwidth: 5MHz	QPSK: 4M53G7D 16QAM: 4M52W7D
	LTE Band 71 Channel Bandwidth: 10MHz	QPSK: 9M02G7D 16QAM: 9M03W7D
	LTE Band 71 Channel Bandwidth: 15MHz	QPSK: 13M5G7D 16QAM: 13M5W7D
	CLTE Band 71 Channel Bandwidth: 20MHz	QPSK: 18M0G7D 16QAM: 18M0W7D
ANTENNA TYPE	ANT0: Internal Antenna with 0.1dBi gain for WCDMA IV Internal Antenna with -0.28dBi gain for LTE B12 Internal Antenna with -0.19dBi gain for LTE B13 Internal Antenna with -0.28dBi gain for LTE B17 Internal Antenna with 0.21dBi gain for LTE B71 ANT6: Internal Antenna with -1.7dBi gain for LTE B7	
HW VERSION	MP	
SW VERSION	95.00	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable: non-shielded cable, with w/o ferrite core, 1.5meter	
EXTREME TEMPERATURE	-20-60 °C	
EXTREME VOLTAGE	3.5V – 4.45V	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.





MODULATION MODE	TX FUNCTION
WCDMA	1TX/2RX
LTE	1TX/4RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.
5. The worst-case scenario for all measurements is based on an engineering evaluation made on different modulations. Then, QPSK and 16QAM were observed as the worst mode to LTE bands respectively and set for all conducted and radiated. Output power measurements were measured on QPSK, 16QAM, 64QAM, and 256QAM modulations, and tests other than output power are performed only in worse-case QPSK and 16QAM modulations.

List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery	N/A	Shenzhen Guangwei Electronic Technology CO., LTD	95-BTSC	Capacity: 3.87Vdc, 4820mAh
AC Adapter 1	N/A	Shenzhen Shi Ying Yuan Electronics Co Ltd	ICP12-050-2000D(ICP12-xxx-yyyf)	I/P: 100-240Vac, 0.3mA, O/P: 5.0Vdc, 2A
AC Adapter 2	N/A	SHENZHEN AQUILSTAR TECHNOLOGY CO.,LTD.	ASUC71w-050912300	I/P: 100-240V~50/60Hz, 0.7A O/P: 5.0Vdc, 3A or 9.0Vdc, 2A or 12.0Vdc, 1.5A
USB Cable	N/A	Dongguan DAWEI PRECISION Technology Co., Ltd.	SC-109B205	USB3.0, 1.5m

2.2 CONFIGURATION OF SYSTEM UNDER TEST FOR RADIATION EMISSION TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Unshielded, Detachable, 1.5m;

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with WCDMA or LTE link
B	EUT + DC Supply /Battery with WCDMA or LTE link

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
B	FREQUENCY STABILITY	1312 to 1513	1312, 1413, 1513	WCDMA
A	OCCUPIED BANDWIDTH	1312 to 1513	1312, 1413, 1513	WCDMA
A	BAND EDGE	1312 to 1513	1312, 1513	WCDMA
A	PEAK TO AVERAGE RATIO	1312 to 1513	1312, 1413, 1513	WCDMA
A	CONDUCTED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA
A	RADIATED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA

LTE BAND 7 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDT H	MODULATION	MODE
A	EIRP	20775 to 21425	20775, 21100, 21425	5MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	20800 to 21400	20800, 21100, 21400	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	20775 to 21425	20775, 21100, 21425	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK,16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK,16QAM	100 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	20850 to 21350	20850, 21100, 21350	20MHz	QPSK,16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
A	BAND EDGE	20775 to 21425	20775	5MHz	QPSK,16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			21425	5MHz	QPSK,16QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		20800 to 21400	20800	10MHz	QPSK,16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			21400	10MHz	QPSK,16QAM	1 RB / 49 RB Offset 50 RB / 0 RB Offset
		20825 to 21375	20825	15MHz	QPSK,16QAM	1 RB / 0 RB Offset 75 RB / 0 RB Offset
			21375	15MHz	QPSK,16QAM	1 RB / 74 RB Offset 75 RB / 0 RB Offset
		20850 to 21350	20850	20MHz	QPSK,16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
			21350	20MHz	QPSK,16QAM	1 RB / 99 RB Offset 100 RB / 0 RB Offset
A	CONDUCTED EMISSION	20775 to 21425	20775, 21100, 21425	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK,16QAM	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	20775 to 21425	21100	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 12 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
A	BAND EDGE	23017 to 23173	23017	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			23173	1.4MHz	QPSK,16QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset
		23025 to 23165	23025	3MHz	QPSK,16QAM	1 RB / 0 RB Offset 15 RB / 0 RB Offset
			23165	3MHz	QPSK,16QAM	1 RB / 14 RB Offset 15 RB / 0 RB Offset
		23035 to 23155	23035	5MHz	QPSK,16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			23155	5MHz	QPSK,16QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK,16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			23130	10MHz	QPSK,16QAM	1 RB / 49 RB Offset 50 RB / 0 RB Offset
A	CONDUCTED EMISSION	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 13 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
A	BAND EDGE	23205 to 23255	23205	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			23255	5MHz	QPSK, 16QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
A	CONDUCTED EMISSION	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	23205 to 23255	23205, 23230, 23255	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 17 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	23755 to 23825	23755, 23790, 23825	5MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

2. LTE Band 17 are covered by LTE Band 12, Because it is a subset of LTE Band 12 with the same output power and supported bandwidths, So the conducted test data and RSE test data please refer to LTE Band 12

LTE BAND 71

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	133147 to 133447	133147, 133297, 133447	5MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		133172 to 133422	133172, 133297, 133422	10MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		133197 to 133397	133197, 133297, 133397	15MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
		133222 to 133372	133222, 133322, 133372	20MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	133172 to 133422	133172, 133297, 133422	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	133147 to 133447	133147, 133297, 133447	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		133172 to 133422	133172, 133297, 133422	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
		133197 to 133397	133197, 133297, 133397	15MHz	QPSK,16QAM	75 RB / 0 RB Offset
		133222 to 133372	133222, 133322, 133372	20MHz	QPSK,16QAM	100 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	133222 to 133372	133222, 133322, 133372	20MHz	QPSK,16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
A	BAND EDGE	133147 to 133447	133147	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
		133147 to 133447	133447	5MHz	QPSK,16QAM	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		133172 to 133422	133172	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
		133172 to 133422	133422	10MHz	QPSK,16QAM	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

		133197 to 133397	133197	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
		133222 to 133372	133397	15MHz	QPSK,16QAM	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
			133222	20MHz	QPSK,16QAM	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
A	CONDUCTED EMISSION	133147 to 133447 133172 to 133422 133197 to 133397 133222 to 133372	133147, 133297, 133447	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
			133172, 133297 133422	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
			133197, 133297, 133397	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
			133222, 133322, 133372	20MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	133147 to 133447 133172 to 133422 133197 to 133397 133222 to 133372	133147, 133297, 133447	5MHz	QPSK	1 RB / 0 RB Offset
			133297	10MHz	QPSK	1 RB / 0 RB Offset
			133297	15MHz	QPSK	1 RB / 0 RB Offset
			133322	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP&EIRP	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu
FREQUENCY STABILITY	23deg. C, 70%RH	DC 3.5V/ 3.87V/ 4.45V By Battery	Jace Hu
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu
BAND EDGE	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu
CONDUCTED EMISSION	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu
RADIATED EMISSION	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 5.0Vdc by Adapter	Jace Hu



Test Report No.: W7L-P23120020RF03

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “User stations are limited to 2 watts” and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP

According to the specific rule Part 27.50(b)(10) and 27.50(c)(10) Fixed, mobile, and Portable stations (hand-held devices) transmitting in the 698-746 MHz, 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_{T} = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_{C} = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

CONDUCTED POWER MEASUREMENT:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



Test Report No.: W7L-P23120020RF03

3.1.3 TEST SETUP

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA IV(ANT0)		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	22.85	22.86	22.83
HSDPA Subtest-1	21.89	21.89	21.90
HSDPA Subtest-2	21.82	21.88	21.86
HSDPA Subtest-3	21.30	21.35	21.33
HSDPA Subtest-4	21.41	21.44	21.41
DC-HSDPA Subtest-1	21.86	21.92	21.90
DC-HSDPA Subtest-2	21.87	21.87	21.83
DC-HSDPA Subtest-3	21.35	21.38	21.41
DC-HSDPA Subtest-4	21.40	21.45	21.35
HSUPA Subtest-1	21.90	21.87	21.90
HSUPA Subtest-2	19.86	19.81	19.84
HSUPA Subtest-3	20.80	20.94	20.82
HSUPA Subtest-4	19.93	19.85	19.86
HSUPA Subtest-5	21.82	21.86	21.87
HSPA+ Subtest-1	19.36	19.38	19.41



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

MAIN ANT

LTE Band 7(ANT6)

Band/BW	Modulation	RB Size	RB Offset	Low CH 20775	Mid CH 21100	High CH 21425
				Frequency 2502.5 MHz	Frequency 2535 MHz	Frequency 2567.5 MHz
7/ 5	QPSK	1	0	22.26	22.43	22.33
		1	12	22.30	22.45	22.48
		1	24	22.38	22.53	22.56
		12	0	21.31	21.38	21.40
		12	6	21.33	21.48	21.54
		12	13	21.57	21.61	21.58
		25	0	21.42	21.38	21.47
	16QAM	1	0	21.55	21.62	21.69
		1	12	21.69	21.66	21.69
		1	24	21.63	21.71	21.81
		12	0	20.48	20.48	20.37
		12	6	20.40	20.46	20.50
		12	13	20.53	20.70	20.61
		25	0	20.40	20.57	20.57
	64QAM	1	0	20.40	20.47	20.43
		1	12	20.45	20.62	20.69
		1	24	20.54	20.71	20.59
		12	0	19.36	19.47	19.43
		12	6	19.38	19.58	19.49
		12	13	19.51	19.59	19.73
		25	0	19.49	19.54	19.42
	256QAM	1	0	17.31	17.36	17.48
		1	12	17.32	17.51	17.50
		1	24	17.29	17.42	17.55
		12	0	16.10	16.31	16.28
		12	6	16.41	16.39	16.42
		12	13	16.35	16.35	16.34
		25	0	16.33	16.29	16.33

Band/BW	Modulation	RB Size	RB Offset	Low CH 20800	Mid CH 21100	High CH 21400
				Frequency 2505 MHz	Frequency 2535 MHz	Frequency 2565 MHz
7/ 10	QPSK	1	0	22.31	22.43	22.32
		1	24	22.40	22.41	22.51
		1	49	22.47	22.49	22.60
		25	0	21.34	21.39	21.43
		25	12	21.46	21.47	21.61
		25	25	21.46	21.55	21.53
		50	0	21.32	21.45	21.54
	16QAM	1	0	21.59	21.71	21.67
		1	24	21.71	21.66	21.76
		1	49	21.69	21.77	21.80
		25	0	20.45	20.50	20.41
		25	12	20.45	20.54	20.54
		25	25	20.46	20.70	20.63
		50	0	20.40	20.59	20.49
	64QAM	1	0	20.49	20.45	20.43
		1	24	20.46	20.62	20.67
		1	49	20.57	20.65	20.58
		25	0	19.41	19.44	19.52
		25	12	19.43	19.51	19.58
		25	25	19.52	19.60	19.60
		50	0	19.42	19.55	19.55
	256QAM	1	0	17.37	17.26	17.58
		1	24	17.43	17.52	17.50
		1	49	17.30	17.45	17.52
		25	0	16.05	16.27	16.36
		25	12	16.42	16.48	16.47
		25	25	16.35	16.32	16.40
		50	0	16.24	16.27	16.27

Band/BW	Modulation	RB Size	RB Offset	Low CH 20825	Mid CH 21100	High CH 21375
				Frequency 2507.5 MHz	Frequency 2535 MHz	Frequency 2562.5 MHz
7/ 15	QPSK	1	0	22.31	22.42	22.40
		1	37	22.37	22.42	22.48
		1	74	22.44	22.44	22.57
		36	0	21.32	21.32	21.43
		36	19	21.37	21.47	21.53
		36	39	21.48	21.60	21.62
		75	0	21.38	21.34	21.53
	16QAM	1	0	21.59	21.71	21.77
		1	37	21.74	21.80	21.74
		1	74	21.69	21.70	21.81
		36	0	20.45	20.51	20.40
		36	19	20.43	20.44	20.57
		36	39	20.53	20.75	20.55
		75	0	20.39	20.49	20.59
	64QAM	1	0	20.48	20.43	20.54
		1	37	20.43	20.67	20.65
		1	74	20.59	20.74	20.61
		36	0	19.36	19.58	19.46
		36	19	19.35	19.55	19.52
		36	39	19.59	19.61	19.73
		75	0	19.52	19.55	19.48
	256QAM	1	0	17.29	17.32	17.54
		1	37	17.39	17.51	17.56
		1	74	17.27	17.43	17.52
		36	0	16.17	16.34	16.32
		36	19	16.43	16.39	16.41
		36	39	16.44	16.31	16.34
		75	0	16.34	16.24	16.24

Band/BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz
7/ 20	QPSK	1	0	22.37	22.50	22.44
		1	50	22.45	22.55	22.52
		1	99	22.49	22.57	22.68
		50	0	21.46	21.45	21.53
		50	25	21.48	21.53	21.63
		50	50	21.60	21.65	21.68
		100	0	21.44	21.49	21.57
	16QAM	1	0	21.64	21.76	21.80
		1	50	21.78	21.81	21.83
		1	99	21.74	21.82	21.90
		50	0	20.52	20.54	20.52
		50	25	20.48	20.55	20.60
		50	50	20.59	20.78	20.70
		100	0	20.53	20.60	20.63
	64QAM	1	0	20.50	20.51	20.57
		1	50	20.57	20.71	20.78
		1	99	20.68	20.76	20.71
		50	0	19.50	19.59	19.55
		50	25	19.50	19.66	19.60
		50	50	19.65	19.70	19.75
		100	0	19.56	19.65	19.57
	256QAM	1	0	17.42	17.37	17.59
		1	50	17.45	17.64	17.61
		1	99	17.36	17.53	17.61
		50	0	16.20	16.35	16.42
		50	25	16.55	16.49	16.53
		50	50	16.47	16.44	16.47
		100	0	16.36	16.37	16.39



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE Band 12(ANT0)

Band/BW	Modulation	RB Size	RB Offset	Low CH 23017	Mid CH 23095	High CH 23173
				Frequency 699.7 MHz	Frequency 707.5 MHz	Frequency 715.3 MHz
12/ 1.4	QPSK	1	0	22.19	22.08	22.27
		1	2	22.33	22.11	22.20
		1	5	22.33	22.18	22.26
		3	0	21.96	21.97	22.03
		3	1	22.07	22.11	22.04
		3	3	22.09	22.18	22.02
		6	0	21.26	21.22	21.32
	16QAM	1	0	21.46	21.29	21.45
		1	2	21.41	21.40	21.38
		1	5	21.49	21.40	21.52
		3	0	21.30	21.19	21.29
		3	1	21.43	21.37	21.46
		3	3	21.43	21.43	21.40
		6	0	20.37	20.33	20.26
	64QAM	1	0	20.50	20.34	20.34
		1	2	20.43	20.42	20.33
		1	5	20.51	20.43	20.35
		3	0	20.12	20.24	20.23
		3	1	20.50	20.26	20.36
		3	3	20.45	20.32	20.49
		6	0	19.23	19.29	19.31
	256QAM	1	0	17.37	17.12	17.26
		1	2	17.32	17.30	17.28
		1	5	17.25	17.36	17.28
		3	0	17.07	17.14	17.34
		3	1	17.31	17.18	17.27
		3	3	17.24	17.08	17.26
		6	0	17.14	17.30	17.21

Band/BW	Modulation	RB Size	RB Offset	Low CH 23025	Mid CH 23095	High CH 23165
				Frequency 700.5 MHz	Frequency 707.5 MHz	Frequency 714.5 MHz
12/ 3	QPSK	1	0	22.24	22.20	22.18
		1	7	22.25	22.18	22.19
		1	14	22.37	22.21	22.19
		8	0	21.21	21.23	21.24
		8	3	21.35	21.28	21.22
		8	7	21.37	21.31	21.32
		15	0	21.30	21.30	21.35
	16QAM	1	0	21.49	21.37	21.33
		1	7	21.48	21.48	21.45
		1	14	21.50	21.46	21.48
		8	0	20.27	20.18	20.30
		8	3	20.43	20.34	20.44
		8	7	20.44	20.41	20.28
		15	0	20.32	20.31	20.37
	64QAM	1	0	20.44	20.27	20.28
		1	7	20.41	20.43	20.41
		1	14	20.37	20.41	20.37
		8	0	19.17	19.21	19.28
		8	3	19.43	19.18	19.34
		8	7	19.34	19.28	19.47
		15	0	19.33	19.32	19.31
	256QAM	1	0	17.40	17.24	17.18
		1	7	17.29	17.31	17.34
		1	14	17.30	17.40	17.26
		8	0	17.08	17.12	17.26
		8	3	17.35	17.20	17.39
		8	7	17.19	17.11	17.36
		15	0	17.21	17.23	17.21

Band/BW	Modulation	RB Size	RB Offset	Low CH 23035	Mid CH 23095	High CH 23155
				Frequency 701.5 MHz	Frequency 707.5 MHz	Frequency 713.5 MHz
12/ 5	QPSK	1	0	22.30	22.16	22.16
		1	12	22.29	22.25	22.19
		1	24	22.39	22.15	22.29
		12	0	21.23	21.15	21.27
		12	6	21.25	21.28	21.26
		12	13	21.29	21.36	21.28
		25	0	21.24	21.25	21.26
	16QAM	1	0	21.48	21.28	21.43
		1	12	21.51	21.38	21.45
		1	24	21.53	21.37	21.41
		12	0	20.33	20.22	20.30
		12	6	20.32	20.34	20.38
		12	13	20.41	20.43	20.38
		25	0	20.38	20.29	20.35
	64QAM	1	0	20.38	20.28	20.34
		1	12	20.42	20.34	20.36
		1	24	20.51	20.48	20.42
		12	0	19.21	19.26	19.23
		12	6	19.39	19.24	19.33
		12	13	19.41	19.27	19.47
		25	0	19.21	19.27	19.21
	256QAM	1	0	17.42	17.11	17.27
		1	12	17.32	17.33	17.26
		1	24	17.37	17.32	17.33
		12	0	17.05	17.08	17.34
		12	6	17.42	17.20	17.32
		12	13	17.31	17.08	17.34
		25	0	17.13	17.22	17.13

Band/BW	Modulation	RB Size	RB Offset	Low CH 23060	Mid CH 23095	High CH 23130
				Frequency 704 MHz	Frequency 707.5 MHz	Frequency 711 MHz
12/ 10	QPSK	1	0	22.32	22.23	22.28
		1	24	22.39	22.26	22.34
		1	49	22.42	22.28	22.34
		25	0	21.29	21.24	21.31
		25	12	21.36	21.39	21.31
		25	25	21.40	21.40	21.35
		50	0	21.39	21.32	21.38
	16QAM	1	0	21.51	21.43	21.47
		1	24	21.53	21.49	21.52
		1	49	21.54	21.52	21.56
		25	0	20.36	20.27	20.35
		25	12	20.47	20.38	20.49
		25	25	20.47	20.44	20.41
		50	0	20.44	20.34	20.39
	64QAM	1	0	20.51	20.37	20.39
		1	24	20.48	20.48	20.48
		1	49	20.52	20.56	20.49
		25	0	19.27	19.29	19.37
		25	12	19.51	19.33	19.44
		25	25	19.48	19.37	19.51
		50	0	19.35	19.42	19.32
	256QAM	1	0	17.47	17.25	17.28
		1	24	17.42	17.42	17.35
		1	49	17.38	17.45	17.38
		25	0	17.17	17.23	17.36
		25	12	17.44	17.21	17.40
		25	25	17.34	17.23	17.37
		50	0	17.23	17.32	17.24



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE Band 13(ANT0)

Band/BW	Modulation	RB Size	RB Offset	Low CH 23205	Mid CH 23230	High CH 23255
				Frequency 779.5 MHz	Frequency 782.0 MHz	Frequency 784.5 MHz
13/ 5	QPSK	1	0	22.46	22.48	22.52
		1	12	22.47	22.46	22.45
		1	24	22.37	22.47	22.40
		12	0	21.43	21.53	21.50
		12	6	21.52	21.42	21.52
		12	13	21.54	21.47	21.56
		25	0	21.50	21.43	21.45
	16QAM	1	0	21.70	21.63	21.67
		1	12	21.65	21.58	21.67
		1	24	21.52	21.63	21.53
		12	0	20.43	20.46	20.55
		12	6	20.57	20.46	20.56
		12	13	20.57	20.58	20.56
		25	0	20.54	20.58	20.53
	64QAM	1	0	20.71	20.61	20.68
		1	12	20.78	20.72	20.79
		1	24	20.56	20.53	20.49
		12	0	19.50	19.49	19.56
		12	6	19.51	19.45	19.55
		12	13	19.50	19.48	19.54
		25	0	19.45	19.48	19.44
	256QAM	1	0	17.57	17.65	17.64
		1	12	17.53	17.57	17.61
		1	24	17.51	17.41	17.42
		12	0	17.41	17.52	17.52
		12	6	17.39	17.30	17.37
		12	13	17.51	17.45	17.58
		25	0	17.41	17.43	17.47

Band/BW	Modulation	RB Size	RB Offset	/	Mid CH 23230	/
				/	Frequency 782.0 MHz	/
13/ 10	QPSK	1	0	/	22.54	/
		1	24	/	22.57	/
		1	49	/	22.48	/
		25	0	/	21.57	/
		25	12	/	21.55	/
		25	25	/	21.58	/
		50	0	/	21.56	/
	16QAM	1	0	/	21.71	/
		1	24	/	21.73	/
		1	49	/	21.65	/
		25	0	/	20.56	/
		25	12	/	20.60	/
		25	25	/	20.62	/
		50	0	/	20.59	/
	64QAM	1	0		20.74	
		1	24		20.80	
		1	49		20.63	
		25	0		19.58	
		25	12		19.56	
		25	25		19.61	
		50	0		19.58	
	256QAM	1	0	/	17.66	/
		1	24	/	17.65	/
		1	49	/	17.56	/
		25	0	/	17.55	/
		25	12	/	17.41	/
		25	25	/	17.60	/
		50	0	/	17.52	/



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE Band 17(ANT0)

Band/BW	Modulation	RB Size	RB Offset	Low CH 23755	Mid CH 23790	High CH 23825
				Frequency 706.5 MHz	Frequency 710 MHz	Frequency 713.5 MHz
17/ 5	QPSK	1	0	22.36	22.47	22.22
		1	12	22.45	22.47	22.41
		1	24	22.45	22.49	22.42
		12	0	21.28	21.48	21.31
		12	6	21.46	21.45	21.26
		12	13	21.47	21.53	21.49
		25	0	21.40	21.38	21.38
	16QAM	1	0	21.57	21.58	21.45
		1	12	21.60	21.61	21.60
		1	24	21.51	21.50	21.54
		12	0	20.32	20.28	20.25
		12	6	20.45	20.46	20.47
		12	13	20.51	20.57	20.46
		25	0	20.54	20.51	20.43
	64QAM	1	0	20.52	20.48	20.37
		1	12	20.62	20.60	20.56
		1	24	20.48	20.58	20.49
		12	0	19.38	19.46	19.41
		12	6	19.50	19.41	19.49
		12	13	19.42	19.50	19.42
		25	0	19.50	19.41	19.32
	256QAM	1	0	17.43	17.41	17.25
		1	12	17.60	17.50	17.51
		1	24	17.37	17.55	17.40
		12	0	17.31	17.32	17.29
		12	6	17.30	17.38	17.43
		12	13	17.31	17.53	17.37
		25	0	17.43	17.38	17.26

Band/BW	Modulation	RB Size	RB Offset	Low CH 23780	Mid CH 23790	High CH 23800
				Frequency 709 MHz	Frequency 710 MHz	Frequency 711 MHz
17/ 10	QPSK	1	0	22.48	22.50	22.37
		1	24	22.50	22.52	22.47
		1	49	22.52	22.60	22.44
		25	0	21.41	21.56	21.37
		25	12	21.51	21.46	21.39
		25	25	21.54	21.58	21.56
		50	0	21.41	21.52	21.41
	16QAM	1	0	21.67	21.66	21.58
		1	24	21.64	21.69	21.68
		1	49	21.63	21.59	21.58
		25	0	20.34	20.42	20.29
		25	12	20.50	20.49	20.54
		25	25	20.61	20.60	20.51
		50	0	20.58	20.55	20.55
	64QAM	1	0	20.62	20.58	20.51
		1	24	20.71	20.63	20.63
		1	49	20.60	20.68	20.54
		25	0	19.46	19.50	19.43
		25	12	19.55	19.51	19.52
		25	25	19.55	19.63	19.52
		50	0	19.58	19.53	19.42
	256QAM	1	0	17.55	17.55	17.37
		1	24	17.61	17.51	17.52
		1	49	17.45	17.62	17.52
		25	0	17.44	17.36	17.31
		25	12	17.44	17.47	17.46
		25	25	17.41	17.57	17.43
		50	0	17.47	17.45	17.28



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE Band 71(ANT0)

Band/BW	Modulation	RB Size	RB Offset	Low CH 133147	Mid CH 133247	High CH 133447
				Frequency 665.5MHz	Frequency 675.5MHz	Frequency 695.5MHz
71/ 5	QPSK	1	0	22.30	22.18	22.16
		1	12	21.99	22.02	21.96
		1	24	22.07	22.02	21.99
		12	0	21.22	21.27	21.06
		12	6	21.17	21.10	21.16
		12	13	21.21	21.08	21.16
		25	0	21.20	21.12	21.19
	16QAM	1	0	21.48	21.55	21.43
		1	12	21.47	21.38	21.39
		1	24	21.51	21.41	21.43
		12	0	20.37	20.45	20.26
		12	6	20.18	20.18	20.04
		12	13	20.17	20.31	20.15
		25	0	20.24	20.27	20.21
	64QAM	1	0	20.51	20.42	20.33
		1	12	20.38	20.30	20.26
		1	24	20.42	20.39	20.25
		12	0	19.28	19.37	19.20
		12	6	19.27	19.32	19.26
		12	13	19.44	19.28	19.32
		25	0	19.28	19.26	19.26
	256QAM	1	0	17.53	17.29	17.23
		1	12	17.35	17.25	17.29
		1	24	17.36	17.38	17.25
		12	0	17.21	17.21	17.14
		12	6	17.18	17.37	17.21
		12	13	17.45	17.28	17.17
		25	0	17.16	17.25	17.16

Band/BW	Modulation	RB Size	RB Offset	Low CH 133172	Mid CH 133272	High CH 133172
				Frequency 668MHz	Frequency 678MHz	Frequency 693MHz
71/ 10	QPSK	1	0	22.30	22.28	22.17
		1	24	21.99	22.12	21.97
		1	49	22.17	21.97	22.00
		25	0	21.14	21.18	21.13
		25	12	21.14	21.20	21.16
		25	25	21.18	21.12	21.09
		50	0	21.27	21.16	21.11
	16QAM	1	0	21.47	21.53	21.34
		1	24	21.53	21.40	21.43
		1	49	21.46	21.37	21.50
		25	0	20.47	20.43	20.31
		25	12	20.18	20.21	20.10
		25	25	20.26	20.31	20.11
		50	0	20.22	20.26	20.13
	64QAM	1	0	20.56	20.39	20.36
		1	24	20.36	20.30	20.25
		1	49	20.40	20.42	20.24
		25	0	19.29	19.39	19.28
		25	12	19.30	19.39	19.29
		25	25	19.44	19.35	19.23
		50	0	19.35	19.36	19.34
	256QAM	1	0	17.52	17.30	17.13
		1	24	17.31	17.30	17.19
		1	49	17.31	17.26	17.22
		25	0	17.24	17.22	17.21
		25	12	17.22	17.35	17.19
		25	25	17.45	17.27	17.20
		50	0	17.16	17.27	17.22

Band/BW	Modulation	RB Size	RB Offset	Low CH 133197	Mid CH 133297	High CH 133397
				Frequency 670.5MHz	Frequency 680.5MHz	Frequency 690.5MHz
71/ 15	QPSK	1	0	22.34	22.31	22.08
		1	37	22.00	22.08	21.86
		1	74	22.20	21.98	21.93
		36	0	21.25	21.15	21.15
		36	19	21.15	21.15	21.10
		36	39	21.23	21.05	21.13
		75	0	21.30	21.08	21.17
	16QAM	1	0	21.57	21.45	21.35
		1	37	21.48	21.39	21.46
		1	74	21.53	21.35	21.41
		36	0	20.36	20.42	20.36
		36	19	20.29	20.21	20.15
		36	39	20.20	20.26	20.16
		75	0	20.22	20.21	20.12
	64QAM	1	0	20.45	20.33	20.39
		1	37	20.37	20.32	20.25
		1	74	20.34	20.38	20.35
		36	0	19.22	19.38	19.18
		36	19	19.24	19.35	19.38
		36	39	19.47	19.26	19.30
		75	0	19.26	19.34	19.37
	256QAM	1	0	17.56	17.35	17.15
		1	37	17.30	17.22	17.15
		1	74	17.35	17.32	17.24
		36	0	17.26	17.19	17.13
		36	19	17.16	17.33	17.22
		36	39	17.44	17.27	17.27
		75	0	17.13	17.17	17.18

Band/BW	Modulation	RB Size	RB Offset	Low CH 133222	Mid CH 133322	High CH 133372
				Frequency 673MHz	Frequency 683MHz	Frequency 688MHz
71/ 20	QPSK	1	0	22.37	22.32	22.21
		1	50	22.07	22.16	22.00
		1	99	22.21	22.11	22.07
		50	0	21.28	21.23	21.21
		50	25	21.29	21.28	21.24
		50	50	21.27	21.15	21.21
		100	0	21.35	21.20	21.25
	16QAM	1	0	21.61	21.56	21.49
		1	50	21.55	21.50	21.51
		1	99	21.57	21.50	21.51
		50	0	20.51	20.46	20.38
		50	25	20.32	20.28	20.18
		50	50	20.32	20.38	20.19
		100	0	20.34	20.30	20.27
	64QAM	1	0	20.60	20.47	20.43
		1	50	20.43	20.44	20.35
		1	99	20.44	20.43	20.36
		50	0	19.33	19.43	19.30
		50	25	19.38	19.44	19.40
		50	50	19.51	19.39	19.37
		100	0	19.39	19.39	19.38
	256QAM	1	0	17.58	17.36	17.28
		1	50	17.36	17.32	17.30
		1	99	17.38	17.39	17.35
		50	0	17.31	17.29	17.22
		50	25	17.23	17.38	17.30
		50	50	17.50	17.31	17.31
		100	0	17.26	17.28	17.27

EIRP

WCDMA IV

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
1312	1712.4	22.85	0.1	22.95	197.24	1
1413	1732.6	22.86	0.1	22.96	197.7	1
1513	1752.6	22.83	0.1	22.93	196.34	1

LTE BAND 7

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	22.38	-1.7	20.68	116.95	2
21100	2535.0	22.53	-1.7	20.83	121.06	2
21425	2567.5	22.56	-1.7	20.86	121.9	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	21.69	-1.7	19.99	99.77	2
21100	2535.0	21.71	-1.7	20.01	100.23	2
21425	2567.5	21.81	-1.7	20.11	102.57	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	20.54	-1.7	18.84	76.56	2
21100	2535	20.71	-1.7	19.01	79.62	2
21425	2567.5	20.69	-1.7	18.99	79.25	2

CHANNEL BANDWIDTH: 5MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	17.32	-1.7	15.62	36.48	2
21100	2535	17.51	-1.7	15.81	38.11	2
21425	2567.5	17.55	-1.7	15.85	38.46	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	22.47	-1.7	20.77	119.4	2
21100	2535.0	22.49	-1.7	20.79	119.95	2
21400	2565.0	22.6	-1.7	20.9	123.03	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	21.71	-1.7	20.01	100.23	2
21100	2535.0	21.77	-1.7	20.07	101.62	2
21400	2565.0	21.8	-1.7	20.1	102.33	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505	20.57	-1.7	18.87	77.09	2
21100	2535	20.65	-1.7	18.95	78.52	2
21400	2565	20.67	-1.7	18.97	78.89	2

CHANNEL BANDWIDTH: 10MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505	17.43	-1.7	15.73	37.41	2
21100	2535	17.52	-1.7	15.82	38.19	2
21400	2565	17.58	-1.7	15.88	38.73	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	22.44	-1.7	20.74	118.58	2
21100	2535.0	22.44	-1.7	20.74	118.58	2
21375	2562.5	22.57	-1.7	20.87	122.18	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	21.74	-1.7	20.04	100.93	2
21100	2535.0	21.8	-1.7	20.1	102.33	2
21375	2562.5	21.81	-1.7	20.11	102.57	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	20.59	-1.7	18.89	77.45	2
21100	2535	20.74	-1.7	19.04	80.17	2
21375	2562.5	20.65	-1.7	18.95	78.52	2

CHANNEL BANDWIDTH: 15MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	17.39	-1.7	15.69	37.07	2
21100	2535	17.51	-1.7	15.81	38.11	2
21375	2562.5	17.56	-1.7	15.86	38.55	2



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	22.49	-1.7	20.79	119.95	2
21100	2535.0	22.57	-1.7	20.87	122.18	2
21350	2560.0	22.68	-1.7	20.98	125.31	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	21.78	-1.7	20.08	101.86	2
21100	2535.0	21.82	-1.7	20.12	102.8	2
21350	2560.0	21.9	-1.7	20.2	104.71	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510	20.68	-1.7	18.98	79.07	2
21100	2535	20.76	-1.7	19.06	80.54	2
21350	2560	20.78	-1.7	19.08	80.91	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510	17.45	-1.7	15.75	37.58	2
21100	2535	17.64	-1.7	15.94	39.26	2
21350	2560	17.61	-1.7	15.91	38.99	2

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	22.33	-0.28	19.9	97.72	3
23095	707.5	22.18	-0.28	19.75	94.41	3
23173	715.3	22.27	-0.28	19.84	96.38	3

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	21.49	-0.28	19.06	80.54	3
23095	707.5	21.43	-0.28	19	79.43	3
23173	715.3	21.52	-0.28	19.09	81.1	3

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	20.51	-0.28	18.08	64.27	3
23095	707.5	20.43	-0.28	18	63.1	3
23173	715.3	20.49	-0.28	18.06	63.97	3

CHANNEL BANDWIDTH: 1.4MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	17.37	-0.28	14.94	31.19	3
23095	707.5	17.36	-0.28	14.93	31.12	3
23173	715.3	17.34	-0.28	14.91	30.97	3

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	22.37	-0.28	19.94	98.63	3
23095	707.5	22.21	-0.28	19.78	95.06	3
23165	714.5	22.19	-0.28	19.76	94.62	3

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	21.5	-0.28	19.07	80.72	3
23095	707.5	21.48	-0.28	19.05	80.35	3
23165	714.5	21.48	-0.28	19.05	80.35	3

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	20.44	-0.28	18.01	63.24	3
23095	707.5	20.43	-0.28	18	63.1	3
23165	714.5	20.41	-0.28	17.98	62.81	3

CHANNEL BANDWIDTH: 3MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	17.4	-0.28	14.97	31.41	3
23095	707.5	17.4	-0.28	14.97	31.41	3
23165	714.5	17.39	-0.28	14.96	31.33	3

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	22.39	-0.28	19.96	99.08	3
23095	707.5	22.25	-0.28	19.82	95.94	3
23155	713.5	22.29	-0.28	19.86	96.83	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	21.53	-0.28	19.1	81.28	3
23095	707.5	21.38	-0.28	18.95	78.52	3
23155	713.5	21.45	-0.28	19.02	79.8	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	20.51	-0.28	18.08	64.27	3
23095	707.5	20.48	-0.28	18.05	63.83	3
23155	713.5	20.42	-0.28	17.99	62.95	3

CHANNEL BANDWIDTH: 5MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	17.42	-0.28	14.99	31.55	3
23095	707.5	17.33	-0.28	14.9	30.9	3
23155	713.5	17.34	-0.28	14.91	30.97	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	22.42	-0.28	19.99	99.77	3
23095	707.5	22.28	-0.28	19.85	96.61	3
23130	711	22.34	-0.28	19.91	97.95	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	21.54	-0.28	19.11	81.47	3
23095	707.5	21.52	-0.28	19.09	81.1	3
23130	711	21.56	-0.28	19.13	81.85	3

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	20.52	-0.28	18.09	64.42	3
23095	707.5	20.56	-0.28	18.13	65.01	3
23130	711	20.49	-0.28	18.06	63.97	3

CHANNEL BANDWIDTH: 10MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	17.47	-0.28	15.04	31.92	3
23095	707.5	17.45	-0.28	15.02	31.77	3
23130	711	17.4	-0.28	14.97	31.41	3

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	22.47	-0.19	20.13	103.04	3
23230	782	22.48	-0.19	20.14	103.28	3
23255	784.5	22.52	-0.19	20.18	104.23	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	21.7	-0.19	19.36	86.3	3
23230	782	21.63	-0.19	19.29	84.92	3
23255	784.5	21.67	-0.19	19.33	85.7	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	20.78	-0.19	18.44	69.82	3
23230	782	20.72	-0.19	18.38	68.87	3
23255	784.5	20.79	-0.19	18.45	69.98	3

CHANNEL BANDWIDTH: 5MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	17.57	-0.19	15.23	33.34	3
23230	782	17.65	-0.19	15.31	33.96	3
23255	784.5	17.64	-0.19	15.3	33.88	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	22.57	-0.19	20.23	105.44	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	21.73	-0.19	19.39	86.9	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	20.8	-0.19	18.46	70.15	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	17.66	-0.19	15.32	34.04	3
-	-	-	-	-	-	-

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

LTE BAND 17

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	22.45	-0.28	20.02	100.46	3
23790	710	22.49	-0.28	20.06	101.39	3
23825	713.5	22.42	-0.28	19.99	99.77	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	21.6	-0.28	19.17	82.6	3
23790	710	21.61	-0.28	19.18	82.79	3
23825	713.5	21.6	-0.28	19.17	82.6	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	20.62	-0.28	18.19	65.92	3
23790	710	20.6	-0.28	18.17	65.61	3
23825	713.5	20.56	-0.28	18.13	65.01	3

CHANNEL BANDWIDTH: 5MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	17.6	-0.28	15.17	32.89	3
23790	710	17.55	-0.28	15.12	32.51	3
23825	713.5	17.51	-0.28	15.08	32.21	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	22.52	-0.28	20.09	102.09	3
23790	710	22.6	-0.28	20.17	103.99	3
23800	711	22.47	-0.28	20.04	100.93	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	21.67	-0.28	19.24	83.95	3
23790	710	21.69	-0.28	19.26	84.33	3
23800	711	21.68	-0.28	19.25	84.14	3

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	20.71	-0.28	18.28	67.3	3
23790	710	20.68	-0.28	18.25	66.83	3
23800	711	20.63	-0.28	18.2	66.07	3

CHANNEL BANDWIDTH: 10MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	17.61	-0.28	15.18	32.96	3
23790	710	17.62	-0.28	15.19	33.04	3
23800	711	17.52	-0.28	15.09	32.28	3

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

LTE BAND 71

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133147	665.5	22.3	-0.21	19.94	98.63	3
133297	680.5	22.18	-0.21	19.82	95.94	3
133447	695.5	22.16	-0.21	19.8	95.5	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133147	665.5	21.51	-0.21	19.15	82.22	3
133297	680.5	21.55	-0.21	19.19	82.99	3
133447	695.5	21.43	-0.21	19.07	80.72	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133147	665.5	20.51	-0.21	18.15	65.31	3
133297	680.5	20.42	-0.21	18.06	63.97	3
133447	695.5	20.33	-0.21	17.97	62.66	3

CHANNEL BANDWIDTH: 5MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133147	665.5	17.53	-0.21	15.17	32.89	3
133297	680.5	17.38	-0.21	15.02	31.77	3
133447	695.5	17.29	-0.21	14.93	31.12	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133172	668	22.3	-0.21	19.94	98.63	3
133297	680.5	22.28	-0.21	19.92	98.17	3
133422	693	22.17	-0.21	19.81	95.72	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133172	668	21.53	-0.21	19.17	82.6	3
133297	680.5	21.53	-0.21	19.17	82.6	3
133422	693	21.5	-0.21	19.14	82.04	3

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133172	668	20.56	-0.21	18.2	66.07	3
133297	680.5	20.42	-0.21	18.06	63.97	3
133422	693	20.36	-0.21	18	63.1	3

CHANNEL BANDWIDTH: 10MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133172	668	17.52	-0.21	15.16	32.81	3
133297	680.5	17.35	-0.21	14.99	31.55	3
133422	693	17.22	-0.21	14.86	30.62	3

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133197	670.5	22.34	-0.21	19.98	99.54	3
133297	680.5	22.31	-0.21	19.95	98.86	3
133397	690.5	22.08	-0.21	19.72	93.76	3

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133197	670.5	21.57	-0.21	19.21	83.37	3
133297	680.5	21.45	-0.21	19.09	81.1	3
133397	690.5	21.46	-0.21	19.1	81.28	3

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133197	670.5	20.45	-0.21	18.09	64.42	3
133297	680.5	20.38	-0.21	18.02	63.39	3
133397	690.5	20.39	-0.21	18.03	63.53	3

CHANNEL BANDWIDTH: 15MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133197	670.5	17.56	-0.21	15.2	33.11	3
133297	680.5	17.35	-0.21	14.99	31.55	3
133397	690.5	17.27	-0.21	14.91	30.97	3

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133222	673	22.37	-0.21	20.01	100.23	3
133322	683	22.32	-0.21	19.96	99.08	3
133372	688	22.21	-0.21	19.85	96.61	3

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133222	673	21.61	-0.21	19.25	84.14	3
133322	683	21.56	-0.21	19.2	83.18	3
133372	688	21.51	-0.21	19.15	82.22	3

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133222	673	20.6	-0.21	18.24	66.68	3
133322	683	20.47	-0.21	18.11	64.71	3
133372	688	20.43	-0.21	18.07	64.12	3

CHANNEL BANDWIDTH: 20MHz 256QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
133222	673	17.58	-0.21	15.22	33.27	3
133322	683	17.39	-0.21	15.03	31.84	3
133372	688	17.35	-0.21	14.99	31.55	3

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





Test Report No.: W7L-P23120020RF03

3.2.4 TEST RESULTS

Please Refer to Appendix Of this test report.


Note: VL = Low voltage(3.5V); VN/NV = Normal voltage(3.87V); VH = High voltage(4.45V);
NT = Normal temperature (25°C)

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.



Test Report No.: W7L-P23120020RF03

3.3.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT


According to FCC 27.53(c) specified that For operations in the 746-758 MHz band and the 776-788 MHz band , the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emission in an 6.25kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P(dBW), by at least $65 + 10 \log 10p(P)$, dB, for mobile and portable equipment.

According to FCC 27.53(g) specified that For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

According to FCC 27.53(h) specified that For operations in the 1710-1755 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

According to FCC 27.53(m)(4) specified that For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. For mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

- a) All measurements were done at low and high operational frequency range
- b) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- c) Tune the analyzer to the nominal center frequency of the emission bandwidth
(EBW)
- d) .Set the resolution bandwidth (RBW) $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
- e) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- f) Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
- g) Select the average power (RMS) display detector.
- h) Set the number of measurement points to ≥ 1001 .
- i) Use auto-coupled sweep time.
- j) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- k) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- l) Record the max trace plot into the test report.



Test Report No.: W7L-P23120020RF03

3.4.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.5 CONDUCTED SPURIOUS EMISSIONS

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .


For: LTE Band7

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25dBm .

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9kHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP



3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB



Test Report No.: W7L-P23120020RF03

below the permissible value is not required in the report.

Please Refer to Appendix Of this test report.

3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

For: LTE Band7/ Band41

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.


NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

3.6.3 DEVIATION FROM TEST STANDARD


No deviation

3.6.4 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.6.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

LTE Band 13

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23205	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	90.140	-64.10	-51.37	-13.00	-51.10	-12.73	Peak	Horizontal
2 PP	200.720	-49.03	-33.73	-13.00	-36.03	-15.30	Peak	Horizontal
3	243.400	-53.44	-41.70	-13.00	-40.44	-11.74	Peak	Horizontal
4	299.660	-53.99	-45.17	-13.00	-40.99	-8.82	Peak	Horizontal
5	341.370	-61.34	-53.31	-13.00	-48.34	-8.03	Peak	Horizontal
6	458.740	-68.99	-63.20	-13.00	-55.99	-5.79	Peak	Horizontal






Test Report No.: W7L-P23120020RF03

MODE	TX channel 23205	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	34.850	-63.84	-42.87	-13.00	-50.84	-20.97	Peak	Vertical
2	68.800	-63.65	-43.36	-13.00	-50.65	-20.29	Peak	Vertical
3 PP	193.930	-45.47	-37.91	-13.00	-32.47	-7.56	Peak	Vertical
4	252.130	-51.56	-47.83	-13.00	-38.56	-3.73	Peak	Vertical
5	269.590	-52.78	-49.17	-13.00	-39.78	-3.61	Peak	Vertical
6	409.270	-65.02	-60.77	-13.00	-52.02	-4.25	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

ABOVE 1GHz


Note: For higher frequency, the emission is too low to be detected.

WCDMA Band IV:

CH 1312

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3424.800	-51.84	-60.35	-13.00	-38.84	8.51	Peak	Horizontal
2 PP	5131.000	-48.00	-59.25	-13.00	-35.00	11.25	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3431.000	-51.69	-60.36	-13.00	-38.69	8.67	Peak	Vertical
2 PP	5137.200	-47.80	-59.44	-13.00	-34.80	11.64	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CH 1413

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3465.000	-51.34	-59.88	-13.00	-38.34	8.54	Peak	Horizontal
2 PP	5197.800	-49.16	-60.51	-13.00	-36.16	11.35	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd


Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CH 1513

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3499.000	-51.12	-59.68	-13.00	-38.12	8.56	Peak	Horizontal
2 PP	5257.800	-49.33	-60.77	-13.00	-36.33	11.44	Peak	Horizontal




BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3505.200	-51.43	-60.07	-13.00	-38.43	8.64	Peak	Vertical
2 PP	5250.000	-47.91	-59.76	-13.00	-34.91	11.85	Peak	Vertical






Test Report No.: W7L-P23120020RF03

LTE Band 7

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	5075.000	-48.14	-59.31	-25.00	-23.14	11.17	Peak	Horizontal
2		7605.000	-48.56	-63.08	-25.00	-23.56	14.52	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-48.60	-60.11	-25.00	-23.60	11.51	Peak	Vertical
2	7600.000	-49.64	-63.09	-25.00	-24.64	13.45	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5075.000	-49.16	-60.33	-25.00	-24.16	11.17	Peak	Horizontal
2 PP	7605.000	-48.68	-63.20	-25.00	-23.68	14.52	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-47.95	-59.46	-25.00	-22.95	11.51	Peak	Vertical
2	7600.000	-50.05	-63.50	-25.00	-25.05	13.45	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

**CHANNEL BANDWIDTH: 15MHz / QPSK
CH20825**

SPECIFICATIONS			
MODE	TX channel 20825	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 20825	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5025.000	-47.55	-58.97	-25.00	-22.55	11.42	Peak	Vertical
2	7522.500	-49.04	-62.16	-25.00	-24.04	13.12	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CH21100

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-48.00	-59.16	-25.00	-23.00	11.16	Peak	Horizontal
2	7600.000	-48.52	-63.03	-25.00	-23.52	14.51	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5075.000	-47.29	-58.81	-25.00	-22.29	11.52	Peak	Vertical
2	7605.000	-48.85	-62.33	-25.00	-23.85	13.48	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CH21375

CH21375			
MODE	TX channel 21375	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5125.000	-49.37	-60.62	-25.00	-24.37	11.25	Peak	Horizontal
2 PP	7687.500	-48.86	-63.52	-25.00	-23.86	14.66	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 21375	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5125.000	-48.19	-59.80	-25.00	-23.19	11.61	Peak	Vertical
2	7700.000	-49.70	-63.59	-25.00	-24.70	13.89	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
Freq	Level	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
MHz	dBm/m	dBm	dBm/m		dB	dB/m		
1 PP 5075.000	-48.08	-59.25	-25.00	-23.08	11.17	Peak	Horizontal	
2 7605.000	-48.82	-63.34	-25.00	-23.82	14.52	Peak	Horizontal	



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-48.41	-59.92	-25.00	-23.41	11.51	Peak	Vertical
2	7600.000	-49.36	-62.81	-25.00	-24.36	13.45	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1415.000	-45.57	-48.51	-13.00	-32.57	2.94	Peak	Horizontal
2	2120.000	-52.62	-57.69	-13.00	-39.62	5.07	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1413.000	-45.80	-48.72	-13.00	-32.80	2.92	Peak	Vertical
2	2122.500	-55.12	-59.56	-13.00	-42.12	4.44	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 3MHz / QPSK

CH23025

07/200210			
MODE	TX channel 23025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1399.000	-45.15	-48.04	-13.00	-32.15	2.89	Peak	Horizontal
2		2101.500	-53.04	-58.06	-13.00	-40.04	5.02	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1401.000	-44.30	-47.19	-13.00	-31.30	2.89	Peak	Vertical
2	2099.000	-54.62	-58.97	-13.00	-41.62	4.35	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CH23095

CH230955			
MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1413.000	-45.40	-48.33	-13.00	-32.40	2.93	Peak	Horizontal
2	2122.500	-50.99	-56.07	-13.00	-37.99	5.08	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

			Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase	
MHz	dBm/m	dBm	dBm/m	dB	dB/m			
1 PP 1415.000	-45.55	-48.47	-13.00	-32.55	2.92	Peak	Vertical	
2 2120.000	-54.75	-59.18	-13.00	-41.75	4.43	Peak	Vertical	



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




BUREAU
VERITAS

Test Report No.: W7L-P23120020RF03

CH23165

MODE	TX channel 23165	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1429.000	-43.50	-46.48	-13.00	-30.50	2.98	Peak	Horizontal
2		2141.000	-52.73	-57.86	-13.00	-39.73	5.13	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23165	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1427.000	-43.36	-46.31	-13.00	-30.36	2.95	Peak	Vertical
2	2143.500	-56.01	-60.52	-13.00	-43.01	4.51	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1415.000	-49.15	-52.09	-13.00	-36.15	2.94	Peak	Horizontal
2		2120.000	-49.76	-54.83	-13.00	-36.76	5.07	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1413.000	-46.96	-49.88	-13.00	-33.96	2.92	Peak	Vertical
2	2122.500	-52.69	-57.13	-13.00	-39.69	4.44	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1413.000	-56.02	-58.95	-13.00	-43.02	2.93	Peak	Horizontal
2 PP	2122.500	-55.11	-60.19	-13.00	-42.11	5.08	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1415.000	-47.14	-50.06	-13.00	-34.14	2.92	Peak	Vertical
2		2120.000	-53.95	-58.38	-13.00	-40.95	4.43	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03


LTE B13

CHANNEL BANDWIDTH: 5MHz / QPSK

CH23205

MODE	TX channel 23205	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1559.000	-43.07	-46.45	-40.00	-3.07	3.38	Peak	Horizontal
2	2337.000	-53.35	-59.01	-13.00	-40.35	5.66	Peak	Horizontal




BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

MODE	TX channel 23205	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1560.000	-47.47	-50.70	-40.00	-7.47	3.23	Peak	Vertical
2	2338.500	-55.16	-60.37	-13.00	-42.16	5.21	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P23120020RF03

CH23230

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1567.000	-44.55	-47.96	-40.00	-4.55	3.41	Peak	Horizontal
2		2346.000	-52.33	-58.01	-13.00	-39.33	5.68	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1564.000	-50.14	-53.38	-40.00	-10.14	3.24	Peak	Vertical
2	2344.000	-54.96	-60.18	-13.00	-41.96	5.22	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CH23255

MODE	TX channel 23255	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1567.000	-45.58	-48.99	-40.00	-5.58	3.41	Peak	Horizontal
2		2353.500	-54.27	-59.97	-13.00	-41.27	5.70	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 23255	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1569.000	-47.24	-50.49	-40.00	-7.24	3.25	Peak	Vertical
2	2351.000	-54.01	-59.26	-13.00	-41.01	5.25	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 10MHz /QPSK

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1567.000	-44.36	-47.77	-40.00	-4.36	3.41	Peak	Horizontal
2	2346.000	-53.89	-59.57	-13.00	-40.89	5.68	Peak	Horizontal




BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			





Test Report No.: W7L-P23120020RF03


LTE B71

CHANNEL BANDWIDTH: 5MHz / QPSK

CH133147

SPECIFICATIONS			
MODE	TX channel 133147	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1336.000	-56.04	-58.73	-13.00	-43.04	2.69	Peak	Horizontal
2	PP 2004.000	-54.66	-59.42	-13.00	-41.66	4.76	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 133147	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1336.000	-56.01	-58.74	-13.00	-43.01	2.73	Peak	Vertical
2 PP	2004.000	-54.91	-58.92	-13.00	-41.91	4.01	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



BUREAU
VERITAS


Test Report No.: W7L-P23120020RF03

CH133297

DATA SHEET:

MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1348.000	-56.06	-58.79	-13.00	-43.06	2.73	Peak	Horizontal
2 PP	2025.000	-55.18	-60.00	-13.00	-42.18	4.82	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1348.000	-55.65	-58.41	-13.00	-42.65	2.76	Peak	Vertical
2		2025.000	-55.97	-60.06	-13.00	-42.97	4.09	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com




BUREAU
VERITAS

Test Report No.: W7L-P23120020RF03

CH133447

SPECIFICATIONS			
MODE	TX channel 133447	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1384.000	-56.10	-58.94	-13.00	-43.10	2.84	Peak	Horizontal
2 PP	2079.000	-55.56	-60.52	-13.00	-42.56	4.96	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 133447	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1384.000	-56.73	-59.58	-13.00	-43.73	2.85	Peak	Vertical
2 PP	2079.000	-56.11	-60.39	-13.00	-43.11	4.28	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd


Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

CHANNEL BANDWIDTH: 10MHz / QPSK

CHANNEL BANDWIDTH: 10MHz 7 QPSK			
MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1354.000	-55.50	-58.25	-13.00	-42.50	2.75	Peak	Horizontal
2 PP	2034.000	-53.85	-58.69	-13.00	-40.85	4.84	Peak	Horizontal






Test Report No.: W7L-P23120020RF03

MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1356.000	-55.96	-58.74	-13.00	-42.96	2.78	Peak	Vertical
2 PP	2034.000	-55.58	-59.70	-13.00	-42.58	4.12	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd


Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

CHANNEL BANDWIDTH: 15MHz / QPSK


CHANNEL BANDWIDTH: 10MHz 7 QPSK			
MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1360.000	-56.01	-58.78	-13.00	-43.01	2.77	Peak	Horizontal
2 PP	2040.000	-54.01	-58.87	-13.00	-41.01	4.86	Peak	Horizontal



MODE	TX channel 133297	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1360.000	-55.86	-58.65	-13.00	-42.86	2.79	Peak	Vertical
2 PP	2040.000	-55.63	-59.77	-13.00	-42.63	4.14	Peak	Vertical






Test Report No.: W7L-P23120020RF03

CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 133322	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1366.000	-54.86	-57.65	-13.00	-41.86	2.79	Peak	Horizontal
2	2049.000	-55.06	-59.94	-13.00	-42.06	4.88	Peak	Horizontal



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com



Test Report No.: W7L-P23120020RF03

MODE	TX channel 133322	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1366.000	-54.06	-56.87	-13.00	-41.06	2.81	Peak	Vertical
2	2049.000	-55.16	-59.33	-13.00	-42.16	4.17	Peak	Vertical



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email:
customerservice.sw@bureauveritas.com

3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



Test Report No.: W7L-P23120020RF03

3.7.4 TEST RESULTS

Please Refer to Appendix Of this test report.



Test Report No.: W7L-P23120020RF03

4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: W7L-P23120020RF03

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



Test Report No.: W7L-P23120020RF03

6 APPENDIX


WCDMA BAND4

PEAK-TO-AVERAGE RATIO

Test Result

Band	Channel	Peak-to-Average Ratio(dB)	Limit(dBm)	Verdict
Band4	1312	2.98	13	PASS
Band4	1413	3	13	PASS
Band4	1513	2.97	13	PASS

Test Graphs





Test Report No.: W7L-P23120020RF03

26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (kHz)	26dB Bandwidth (kHz)	Limit(kHz)	Verdict
Band4	1312	4.1500	4.718	---	PASS
Band4	1413	4.1529	4.712	---	PASS
Band4	1513	4.1588	4.721	---	PASS

Test Graphs






Test Report No.: W7L-P23120020RF03

BAND EDGE

Test Result

Band	Channel	Frequency (MHz)	Result (dBm)	Limit(dBm)	Verdict
Band4	1312	1710.00	-25.96	-13	PASS
Band4	1513	1755.00	-25.99	-13	PASS

Test Graphs





Test Report No.: W7L-P23120020RF03

CONDUCTED SPURIOUS EMISSION

Test Result

Band	Channel	Frequency Range (Mhz)	Frequency (dBm)	Result (dBm)	Limit (dBm)	Verdict
Band4	1312	30~1000MHz	871.96	-49.78	-13	PASS
Band4	1312	1000~20000MHz	19157.83	-41.52	-13	PASS
Band4	1413	30~1000MHz	876.33	-49.71	-13	PASS
Band4	1413	1000~20000MHz	19107.95	-41.33	-13	PASS
Band4	1513	30~1000MHz	902.03	-49.74	-13	PASS
Band4	1513	1000~20000MHz	19283.23	-41.13	-13	PASS

Test Graphs

