TEST REPORT

Dt&C Co., Ltd.
42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2405-0059
2. Customer
   - Name (FCC) : Point Mobile Co., LTD.
   - Address (FCC) : B-9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu, Seoul, South Korea, 08512
3. Use of Report : FCC Certification
4. Product Name / Model Name : MOBILE COMPUTER / PM95
   FCC ID : V2X-PM95
5. FCC Regulation(s): Part 15.247
   Test Method used: ANSI C63.10-2013, KDB789033 D02v02r01, KDB662911 D01v02r01
6. Date of Test : 2024.03.28 ~ 2024.04.29
7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing
8. Testing Environment : See appended test report.
9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by Name : SeungMin Gil (Signature)	Technical Manager Name : JaeJin Lee (Signature)

2024 . 05 . 30 .

Dt&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2405-0059	May, 30. 2024	Initial issue	SeungMin Gil	JaeJin Lee

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Table of Contents

1. General Information 4
1.1. Description of EUT 4
1.2. Declaration by the applicant / manufacturer 4
1.3. Testing Laboratory 5
1.4. Testing Environment 5
1.5. Measurement Uncertainty 5
1.6. Test Equipment List 6
2. Test Methodology 7
2.1. EUT Configuration 7
2.2. EUT Exercise 7
2.3. General Test Procedures 7
2.4. Instrument Calibration 7
2.5. Description of Test Modes 8
3. Antenna Requirements 10
4. Summary of Test Result 11
5. Test Result 12
5.1. Maximum Peak Output Power 12
5.1.1. Test Setup 12
5.1.2. Test Procedures 12
5.1.3. Test Results 12
5.2. 6 dB Bandwidth 16
5.2.1. Test Setup 16
5.2.2. Test Procedures 16
5.2.3. Test Results 17
5.3. Power Spectral Density 26
5.3.1. Test Setup 26
5.3.2. Test Procedures 26
5.3.3. Test Results 27
5.4. Unwanted Emissions (Conducted) 36
5.4.1. Test Setup 36
5.4.2. Test Procedures 36
5.4.3. Test Results 37
5.5. Unwanted Emissions (Radiated) 101
5.5.1. Test Setup 102
5.5.2. Test Procedures 102
5.5.3. Test Results 104
5.6. AC Power-Line Conducted Emissions 106
5.6.1. Test Setup 106
5.6.2. Test Procedures 106
5.6.3. Test Results 106
APPENDIX I 109
APPENDIX II 110
APPENDIX III 116

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

1. General Information

1.1. Description of EUT

Equipment Class	Digital Transmission System (DTS)
Product Name	MOBILE COMPUTER
Model Name	PM95
Add Model Name	-
Firmware Version Identification Number	95.00xx
EUT Serial Number	Conducted: 4b486b0c , Radiated: 536a3c99
Power Supply	DC 3.87 V
Modulation Technique	▪ 802.11ax: OFDM, OFDMA
Antenna Specification	Antenna type: LDS Antenna Antenna gain: Refer to the clause 3 in test report.

Band	Mode	Tx. frequency(MHz)	Max. conducted power(dBm)
2.4 GHz	802.11ax (HE20)	2 412 ~ 2 462	26.15
	802.11ax (HE40)	2 422 ~ 2 452	27.06

1.2. Declaration by the applicant / manufacturer

N/A

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

1.3. Testing Laboratory

Dt&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of Part 2.948 according to ANSI C63.4-2014. **- FCC & IC MRA Designation No. : KR0034** **- ISED#: 5740A**		
www.dtnc.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.4. Testing Environment

Ambient Condition	
▪ Temperature	+21 ℃ ~ +23 ℃
▪ Relative Humidity	+38 % ~ +43 %

1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of *k* = 2 to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	0.9 dB (The confidence level is about 95 %, k = 2)
AC power-line conducted emission	3.4 dB (The confidence level is about 95 %, k = 2)
Radiated emission (1 GHz Below)	5.0 dB (The confidence level is about 95 %, k = 2)
Radiated emission (1 GHz ~ 18 GHz)	4.8 dB (The confidence level is about 95 %, k = 2)
Radiated emission (18 GHz Above)	5.7 dB (The confidence level is about 95 %, k = 2)

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	KEYSIGHT	N9020A	23/12/15	24/12/15	MY48011146
Spectrum Analyzer	KEYSIGHT	N9020A	23/12/15	24/12/15	MY52440526
Spectrum Analyzer	Agilent Technologies	N9020A	23/06/23	24/06/23	US47360812
Spectrum Analyzer	Agilent Technologies	N9020A	23/12/15	24/12/15	MY50110097
DC Power Supply	Agilent Technologies	66332A	23/12/15	24/12/15	66332A _220926-1
Multimeter	FLUKE	17B+	23/12/15	24/12/15	36390701WS
Signal Generator	Rohde Schwarz	SMBV100A	23/12/15	24/12/15	255571
Signal Generator	ANRITSU	MG3695C	23/12/15	24/12/15	173501
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	120612-1
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	090205-4
Thermohygrometer	BODYCOM	BJ5478	23/06/23	24/06/23	N/A
Loop Antenna	ETS-Lindgren	6502	23/11/09	24/11/09	00060496
Hybrid Antenna	Schwarzbeck	VULB 9160	23/12/15	24/12/15	3362
Horn Antenna	ETS-Lindgren	3117	23/06/23	24/06/23	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	23/06/23	24/06/23	155
PreAmplifier	tsj	MLA-0118-B01-40	23/12/15	24/12/15	1852267
PreAmplifier	tsj	MLA-1840-J02-45	23/06/23	24/06/23	16966-10728
PreAmplifier	H.P	8447D	23/12/15	24/12/15	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	23/06/23	24/06/23	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	23/06/23	24/06/23	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	23/06/23	24/06/23	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	23/06/23	24/06/23	16012202
Attenuator	Aeroflex/Weinschel	56-3	23/06/23	24/06/23	Y2370
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	3
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	2
Attenuator	Aeroflex/Weinschel	86-10-11	23/06/23	24/06/23	408
Attenuator	Aeroflex/Weinschel	86-20-11	23/06/23	24/06/23	432
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A MA2490A MA2411B	23/12/15	24/12/15	1338004 1249303 1911481
EMI Test Receiver	ROHDE&SCHWARZ	ESCI7	24/01/29	25/01/29	100910
PULSE LIMITER	ROHDE&SCHWARZ	ESH3-Z2	23/08/21	24/08/21	101333
LISN	SCHWARZBECK	NSLK 8128 RC	23/10/26	24/10/26	8128 RC-387
Digital Thermo Hygrometer	CAS	TE-303N	24/02/07	25/02/07	220502531
Cable	DT&C	Cable	24/01/03	25/01/03	G-2
Cable	HUBER+SUHNER	SUCOFLEX 100	24/01/03	25/01/03	G-3
Cable	DT&C	Cable	24/01/03	25/01/03	G-4
Cable	OMT	YSS21S	24/01/03	25/01/03	G-5
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-1
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-1
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-2
Cable	JUNKOSHA	MWX241/B	24/01/03	25/01/03	M-3
Cable	JUNKOSHA	J12J101757-00	24/01/03	25/01/03	M-7
Cable	HUBER+SUHNER	SUCOFLEX106	24/01/03	25/01/03	M-9
Cable	Dt&C	Cable	24/01/03	25/01/03	RFC-69
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0185
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0190

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.
Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

2. Test Methodology

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.
The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.
So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.
The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on section 12.1 of the KDB558074 D01v05r02.
The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

2.4. Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

2.5. Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting.

Transmitting Configuration of EUT

Mode	SISO		MIMO(CDD)	MIMO(SDM)
	Ant 1	Ant 2	Ant 1 & 2	Ant 1 & 2
802.11ax(HE20)	O	O	O	O
802.11ax(HE40)	O	O	O	O

O = Support, X = Not Support
SDM = Spatial Diversity Multiplexing, CDD = Cycle Delay Diversity

Test Mode

Test mode		Worst case data rate					
		26T	52T	106T	242T	484T	SU
TM 1	802.11ax(HE20)	MCS0	MCS0	MCS0	MCS5	NA	MCS5
TM 2	802.11ax(HE40)	MCS0	MCS0	MCS0	MCS0	MCS5	MCS5

Note1: The worst case data rate was determined according to the power measurements.

EUT Operation test setup

- **Test Software:** Qualcomm Radio Control Toolkit v4.0
- **Power setting:** Refer to the table next page.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Tested frequency and power setting

Tones(RU Index)	802.11ax(HE20)		
	Channel	Frequency (MHz)	Power Setting
26(0, 4, 8)	1	2 412	12
	6	2 437	12
	11	2 462	12
52(37, 38, 40)	1	2 412	12
	6	2 437	12
	11	2 462	12
106(53, 54)	1	2 412	12
	6	2 437	12
	11	2 462	12
242(61)	1	2 412	12
	6	2 437	12
	11	2 462	12
SU	1	2 412	12
	6	2 437	12
	11	2 462	12

Tones(RU Index)	802.11ax(HE40)		
	Channel	Frequency (MHz)	Power Setting
26(0, 8, 17)	3	2 422	
	6	2 437	12
	9	2 452	12
52(37, 40, 44)	3	2 422	12
	6	2 437	12
	9	2 452	12
106(53, 54, 56)	3	2 422	12
	6	2 437	12
	9	2 452	12
242(61, 62)	3	2 422	12
	6	2 437	12
	9	2 452	12
484(65)	3	2 422	12
	6	2 437	12
	9	2 452	12
SU	3	2 422	12
	6	2 437	12
	9	2 452	12

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

3. Antenna Requirements

▣ **According to Part 15.203**

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

The antenna is attached on the device by means of unique coupling method.
Therefore this E.U.T complies with the requirement of Part 15.203

Directional antenna gain:

Bands	SISO		MIMO (CDD) Note 1.	MIMO (SDM) Note 2
	ANT 1 [dBi]	ANT 2 [dBi]	Directional Gain[dBi]	Directional Gain[dBi]
2.4 GHz	3.51	5.46	**7.55**	4.59

Note 1. Directional gain(correlated signal with unequal antenna gain and equal transmit power)

$10 \log [(10^{G1/20} + 10^{G2/20} + \ldots + 10^{GN/20})^2 / N^{ANT}]$ dBi

Note 2. Directional gain(completely uncorrelated signal with unequal antenna gain and equal transmit power)

$10 \log [(10^{G1/10} + 10^{G2/10} + \ldots + 10^{GN/10}) / N^{ANT}]$ dBi

4. Summary of Test Result

FCC part section(s)	Test Description	Limit	Test Condition	Status Note 1
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Maximum Peak Output Power	< 1 Watt (conducted)		C
15.247(d)	Unwanted Emissions(Conducted)	20 dBc in any 100 kHz BW		C
15.247(e)	Power Spectral Density	< 8 dBm / 3 kHz		C
15.247(d) 15.205 15.209	Unwanted Emissions(Radiated)	Part 15.209 limits (Refer to section 5.5)	Radiated	C Note 3
15.207	AC Power-Line Conducted Emissions	Part 15.207 limits (Refer to section 5.6)	AC Line Conducted	C
15.203	Antenna Requirements	Part 15.203 (Refer to section 3)	-	C

Note 1: **C** = Comply **NC** = Not Comply **NT** = Not Tested **NA** = Not Applicable
Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.
Note 3: This test item was performed in three orthogonal EUT positions and the worst case data was reported.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

5. Test Result

5.1. Maximum Peak Output Power

▣ Test Requirements and limit, Part 15.247(b)

The maximum permissible conducted output power is 1 Watt.

5.1.1. Test Setup



5.1.2. Test Procedures

- **KDB558074 D01v05r02 - Section 8.3.1.3**
- **ANSI C63.10-2013 – Section 11.9.1.3**

RBW ≥ DTSPKPM1 Peak-reading power meter method

The maximum conducted output powers were measured using a broadband peak RF power meter which has greater video bandwidth than DUT's DTS bandwidth and utilize a fast-responding diode detector.

- **KDB558074 D01v05r02 - Section 8.3.2.3**
- **ANSI C63.10-2013 – Section 11.9.2.3**

Method AVGPM-G

The average conducted output powers were measured using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

5.1.3. Test Results

- Refer to the next page

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

ANT	Tones	RU Index	Det.	Maximum Peak Conducted Output Power (dBm) for *802.11ax(HE20)*					
				Freq.(MHz)					
				CDD			SDM		
				2 412	2 437	2 462	2 412	2 437	2 462
ANT 1	26	0	PK	20.90	21.88	21.49	20.68	21.82	21.01
			AV	11.83	12.26	12.40	11.51	11.83	12.04
		4	PK	20.32	21.33	21.44	20.26	20.85	21.36
			AV	11.86	12.00	12.12	11.41	11.56	12.01
		8	PK	21.62	21.35	21.44	21.18	21.07	21.26
			AV	12.44	11.86	12.23	12.17	11.71	11.86
	52	37	PK	21.23	21.27	21.45	20.78	20.78	21.00
			AV	11.73	12.07	12.22	11.49	12.01	11.79
		38	PK	21.08	21.34	21.58	20.84	20.97	21.29
			AV	11.46	12.10	12.06	11.17	11.90	11.63
		40	PK	20.84	21.20	21.51	20.56	21.03	21.12
			AV	12.39	11.74	12.21	12.24	11.60	11.73
	106	53	PK	21.42	21.05	21.49	21.13	20.76	21.03
			AV	11.72	12.24	12.25	11.34	11.91	12.09
		54	PK	21.30	20.54	21.53	21.13	20.27	21.14
			AV	12.22	11.95	12.28	12.14	11.45	12.06
	242	61	PK	21.23	21.46	21.33	20.88	21.32	21.01
			AV	11.97	12.09	12.37	11.71	11.98	12.24
	SU		PK	21.22	21.26	21.37	20.80	21.16	21.19
			AV	12.10	12.23	12.22	11.69	11.77	11.81
ANT 2	26	0	PK	24.44	24.11	23.96	24.34	23.83	23.56
			AV	13.33	13.22	13.70	13.20	12.98	13.65
		4	PK	23.77	23.81	23.99	23.32	23.69	23.53
			AV	13.10	13.05	13.43	12.74	12.97	13.30
		8	PK	24.09	24.03	24.11	23.87	23.57	23.68
			AV	13.89	13.63	13.24	13.60	13.39	13.08
	52	37	PK	24.45	23.93	24.08	24.05	23.80	23.60
			AV	13.09	13.08	13.85	12.95	12.90	13.53
		38	PK	23.87	23.85	24.27	23.59	23.74	24.08
			AV	12.91	13.07	13.61	12.44	12.60	13.20
		40	PK	23.85	23.82	24.00	23.58	23.59	23.76
			AV	13.72	13.37	13.16	13.51	12.87	12.92
	106	53	PK	24.23	23.95	24.19	23.86	23.66	23.72
			AV	13.16	13.30	13.85	12.71	13.15	13.39
		54	PK	24.21	23.83	23.81	24.05	23.61	23.41
			AV	13.69	13.31	13.29	13.28	12.99	12.99
	242	61	PK	23.89	23.81	23.94	23.72	23.60	23.89
			AV	13.41	13.46	13.53	12.99	13.33	13.48
	SU		PK	23.97	23.86	23.88	23.89	23.66	23.80
			AV	13.42	13.39	13.49	13.25	12.94	13.24
Sum (ANT 1+2)	26	0	PK	26.03	26.15	25.91	25.89	25.95	25.48
		4	PK	25.39	25.75	25.91	25.06	25.51	25.59
		8	PK	26.04	25.90	25.99	25.74	25.51	25.65
	52	37	PK	26.14	25.81	25.97	25.73	25.56	25.50
		38	PK	25.71	25.78	26.14	25.44	25.58	25.92
		40	PK	25.61	25.71	25.94	25.34	25.51	25.65
	106	53	PK	26.06	25.75	26.06	25.72	25.46	25.59
		54	PK	26.00	25.50	25.83	25.84	25.26	25.43
	242	61	PK	25.77	25.80	25.84	25.54	25.62	25.69
	SU		PK	25.82	25.76	25.81	25.62	25.60	25.70

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

ANT	Tones	RU Index	Det.	Maximum Peak Conducted Output Power (dBm) for *802.11ax(HE40)*					
				Freq.(MHz)					
				CDD			SDM		
				2 422	2 437	2 452	2 422	2 437	2 452
ANT 1	26	0	PK	21.43	22.44	20.78	21.31	22.34	20.56
			AV	11.28	11.81	12.35	11.07	11.40	12.09
		8	PK	20.68	22.46	20.74	20.60	22.18	20.37
			AV	11.88	12.21	11.86	11.81	11.82	11.52
		17	PK	22.27	20.88	20.83	21.81	20.43	20.76
			AV	12.46	12.16	11.95	12.07	12.00	11.67
	52	37	PK	21.46	21.93	21.77	21.31	21.43	21.31
			AV	11.36	11.99	12.45	11.07	11.52	12.39
		40	PK	20.60	21.15	20.77	20.36	20.93	20.46
			AV	11.81	12.21	12.00	11.42	12.02	11.52
		44	PK	21.76	21.55	21.66	21.48	21.22	21.37
			AV	12.46	12.16	12.19	12.03	11.96	12.12
	106	53	PK	20.82	20.97	21.60	20.37	20.88	21.44
			AV	11.29	12.18	12.35	10.84	11.78	12.07
		54	PK	20.03	22.26	20.48	19.66	22.21	20.38
			AV	11.77	12.20	11.92	11.32	12.11	11.55
		56	PK	21.57	21.20	20.93	21.46	21.13	20.45
			AV	12.44	12.16	12.17	12.07	12.07	11.70
	242	61	PK	20.78	20.88	20.28	20.46	20.75	20.16
			AV	11.55	12.14	12.09	11.10	11.85	11.93
		62	PK	21.05	21.84	20.43	20.98	21.79	20.30
			AV	12.33	12.08	12.18	12.08	11.87	12.05
	484	65	PK	21.66	21.49	21.76	21.38	21.07	21.71
			AV	12.11	12.43	12.33	12.04	12.03	12.02
	SU		PK	20.46	20.92	20.67	19.97	20.56	20.47
			AV	11.59	12.17	12.32	11.40	11.96	12.12
ANT 2	26	0	PK	24.14	25.22	23.65	23.83	25.08	23.19
			AV	12.71	13.13	13.24	12.43	12.92	13.13
		8	PK	23.54	24.89	23.72	23.13	24.67	23.63
			AV	13.13	13.07	13.21	13.03	12.85	13.13
		17	PK	24.39	23.78	23.66	24.04	23.65	23.28
			AV	13.29	13.48	12.86	13.15	13.28	12.52
	52	37	PK	23.93	23.98	24.06	23.65	23.63	23.85
			AV	12.83	13.24	12.44	12.41	13.16	12.08
		40	PK	23.56	13.65	23.74	23.16	13.18	23.55
			AV	13.26	13.22	13.44	13.03	12.90	13.10
		44	PK	23.74	23.91	24.01	23.65	23.50	23.64
			AV	13.49	13.44	12.99	13.39	13.09	12.75
	106	53	PK	23.81	23.27	23.11	23.33	22.80	23.04
			AV	12.96	13.11	13.32	12.46	12.81	12.82
		54	PK	22.86	24.37	23.25	22.74	24.24	23.04
			AV	13.27	13.18	13.36	13.13	12.90	12.91
		56	PK	23.79	23.71	24.02	23.29	23.63	23.72
			AV	13.49	13.44	13.14	13.32	13.23	13.09
	242	61	PK	23.81	23.44	23.30	23.46	23.03	23.14
			AV	13.00	13.14	13.24	12.60	12.71	13.17
		62	PK	23.15	24.04	23.10	22.99	23.63	22.70
			AV	13.27	13.39	13.19	13.00	13.03	12.82
	484	65	PK	23.59	23.47	23.49	23.26	23.14	23.29
			AV	13.41	13.30	13.44	12.96	13.24	12.97
	SU		PK	24.29	24.61	24.88	23.98	24.53	24.79
			AV	13.22	13.41	13.73	12.82	13.13	13.61

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Sum (ANT 1+2)	26	0	PK	26.00	27.06	25.46	25.76	26.93	25.08
		8	PK	25.35	26.85	25.49	25.06	26.61	25.31
		17	PK	26.47	25.58	25.48	26.08	25.34	25.21
	52	37	PK	25.88	26.09	26.07	25.65	25.68	25.77
		40	PK	25.34	21.86	25.51	24.99	21.60	25.28
		44	PK	25.87	25.90	26.00	25.71	25.52	25.66
	106	53	PK	25.58	25.28	25.43	25.11	24.96	25.32
		54	PK	24.68	26.45	25.09	24.48	26.35	24.92
		56	PK	25.83	25.64	25.75	25.48	25.57	25.40
	242	61	PK	25.56	25.36	25.06	25.22	25.05	24.91
		62	PK	25.24	26.09	24.98	25.11	25.82	24.67
	484	65	PK	25.74	25.60	25.72	25.43	25.24	25.58
	SU		PK	25.79	26.16	26.28	25.43	25.99	26.16

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

5.2. 6 dB Bandwidth

▣ Test Requirements and limit, Part 15.247(a)

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the EUT's antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

5.2.1. Test Setup

Refer to the APPENDIX I.

5.2.2. Test Procedures

- **KDB558074 D01v05r02 - Section 8.2**
- **ANSI C63.10-2013 – Section 11.8.2**

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = **Peak**.
4. Trace mode = **max hold**.
5. Sweep = **auto couple**.
6. Allow the trace to stabilize.
7. Option 1 - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

   Option 2 - The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

5.2.3. Test Results

TM 1

ANT	Tones	RU Index	Test Results[MHz]		
			2 412	2 437	2 462
ANT 1	26	0	2.13	**2.09**	2.09
		4	2.68	2.69	2.67
		8	**2.09**	2.12	**2.09**
	242	61	19.12	19.10	19.11
	SU		19.11	19.12	19.12
ANT 2	26	0	2.15	2.11	2.09
		4	2.72	2.66	2.70
		8	**2.10**	**2.09**	**2.06**
	242	61	19.11	19.12	19.10
	SU		19.09	19.10	19.13

TM 2

ANT	Tones	RU Index	Test Results[MHz]		
			2 422	2 437	2 452
ANT 1	26	0	2.18	**2.08**	**2.07**
		8	2.16	2.13	2.22
		17	**2.15**	2.13	2.15
	484	65	38.11	38.17	38.13
	SU		38.16	38.19	38.15
ANT 2	26	0	**2.10**	2.17	**2.08**
		8	2.14	2.16	2.23
		17	2.15	**2.15**	2.12
	484	65	38.14	38.15	38.13
	SU		38.15	38.16	38.13

Note 1: The worst-case plots(Minimum 6dB Bandwidth) were attached to the next page.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

6 dB Bandwidth

TM 1 & ANT 1 & 26 Tone & 8 RU & 2 412



6 dB Bandwidth

TM 1 & ANT 1 & 26 Tone & 0 RU & 2 437



6 dB Bandwidth

TM 1 & ANT 1 & 26 Tone & 8 RU & 2 462



6 dB Bandwidth TM 1 & ANT 2 & 26 Tone & 8 RU & 2 412



6 dB Bandwidth TM 1 & ANT 2 & 26 Tone & 8 RU & 2 437



6 dB Bandwidth

TM 1 & ANT 2 & 26 Tone & 8 RU & 2 462



6 dB Bandwidth

TM 2 & ANT 1 & 26 Tone & 17 RU & 2 412



6 dB Bandwidth

TM 2 & ANT 1 & 26 Tone & 0 RU & 2 437



6 dB Bandwidth

TM 2 & ANT 1 & 26 Tone & 0 RU & 2 452



6 dB Bandwidth TM 2 & ANT 2 & 26 Tone & 0 RU & 2 422



6 dB Bandwidth TM 2 & ANT 2 & 26 Tone & 17 RU & 2 437



This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

6 dB Bandwidth

TM 2 & ANT 2 & 26 Tone & 0 RU & 2 452



5.3. Power Spectral Density

▣ Test requirements and limit, Part 15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.3.1. Test Setup

Refer to the APPENDIX I.

5.3.2. Test Procedures

- **KDB558074 D01v05r02 - Section 8.4**
- **ANSI C63.10-2013 – Section 11.10.2**

Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to **1.5 times** the DTS bandwidth.
3. Set the RBW : **3 kHz ≤ RBW ≤ 100 kHz**.
4. Set the VBW ≥ **3 x RBW.**
5. Detector = **peak.**
6. Sweep time = **auto couple.**
7. Trace mode = **max hold.**
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

5.3.3. Test Results

ANT	Tones	RU Index	RBW	Power Spectral Density (dBm) for *802.11ax(HE20)*			
				2 412 MHz	2 437 MHz	2 462 MHz	Limit (dBm / 3 kHz)
ANT 1	26	0	3 kHz	-3.71	-3.43	-3.11	8.00
		4	3 kHz	-3.07	-2.77	-2.84	8.00
		8	3 kHz	**-1.70**	**-3.22**	**-2.71**	8.00
	242	61	3 kHz	-12.64	-12.67	-12.61	8.00
	SU		3 kHz	-12.34	-12.10	-11.29	8.00
ANT 2	26	0	3 kHz	-4.42	-4.50	-3.70	8.00
		4	3 kHz	-3.66	-3.65	-4.20	8.00
		8	3 kHz	**-3.21**	**-2.93**	**-3.41**	8.00
	242	61	3 kHz	-13.71	-13.43	-13.12	8.00
	SU		3 kHz	-13.31	-13.37	-13.44	8.00
Sum (ANT 1+2)	26	0	3 kHz	-1.04	-0.92	-0.38	4.45
		4	3 kHz	-0.34	-0.18	-0.46	4.45
		8	3 kHz	**0.62**	**-0.06**	**-0.04**	4.45
	242	61	3 kHz	-10.13	-10.02	-9.85	4.45
	SU		3 kHz	-9.79	-9.68	-9.22	4.45

ANT	Tones	RU Index	RBW	Power Spectral Density (dBm) for *802.11ax(HE40)*			
				2 422 MHz	2 437 MHz	2 452 MHz	Limit (dBm / 3 kHz)
ANT 1	26	0	3 kHz	-4.43	-3.24	**-2.53**	8.00
		8	3 kHz	-3.73	-3.61	-4.02	8.00
		17	3 kHz	**-3.47**	**-3.40**	-3.76	8.00
	484	65	3 kHz	-15.98	-15.79	-14.84	8.00
	SU		3 kHz	-15.15	-15.34	-13.99	8.00
ANT 2	26	0	3 kHz	-3.69	-5.37	**-4.11**	8.00
		8	3 kHz	-4.82	-4.36	-4.22	8.00
		17	3 kHz	**-4.22**	**-4.14**	-4.82	8.00
	484	65	3 kHz	-15.81	-15.02	-16.21	8.00
	SU		3 kHz	-15.15	-15.78	-16.06	8.00
Sum (ANT 1+2)	26	0	3 kHz	-1.03	-1.17	**-0.24**	4.45
		8	3 kHz	-1.23	-0.96	-1.11	4.45
		17	3 kHz	**-0.82**	**-0.74**	-1.25	4.45
	484	65	3 kHz	-12.88	-12.38	-12.46	4.45
	SU		3 kHz	-12.14	-12.54	-11.89	4.45

Note 1: The worst-case plots were attached to the next page.
Note 2: The limit is reduced by the amount of dB above which the antenna gain exceeds 6 dBi.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Power Spectral Density TM 1 & ANT 1 & 26 Tone & 8 RU & 2 412



Power Spectral Density TM 1 & ANT 1 & 26 Tone & 8 RU & 2 437



Power Spectral Density TM 1 & ANT 1 & 26 Tone & 8 RU & 2 462



Power Spectral Density

TM 1 & ANT 2 & 26 Tone & 8 RU & 2 412



Power Spectral Density

TM 1 & ANT 2 & 26 Tone & 8 RU & 2 437



This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Power Spectral Density TM 1 & ANT 2 & 26 Tone & 8 RU & 2 462



Power Spectral Density TM 2 & ANT 1 & 26 Tone & 17 RU & 2 422



Power Spectral Density TM 2 & ANT 1 & 26 Tone & 17 RU & 2 437



Power Spectral Density TM 2 & ANT 1 & 26 Tone & 0 RU & 2 452



Power Spectral Density TM 2 & ANT 2 & 26 Tone & 17 RU & 2 422



Power Spectral Density TM 2 & ANT 2 & 26 Tone & 17 RU & 2 437



This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

Power Spectral Density TM 2 & ANT 2 & 26 Tone & 0 RU & 2 452



5.4. Unwanted Emissions (Conducted)

▣ **Test requirements and limit, Part 15.247(d)**

In any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions :

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured inband average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

5.4.1. Test Setup

Refer to the APPENDIX I including path loss

5.4.2. Test Procedures

- **KDB558074 D01v05r02 - Section 8.5**
- **ANSI C63.10-2013 – Section 11.11**

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to ≥ 1.5 times the DTS bandwidth.
3. Set the RBW = 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level

   LIMIT LINE = 20 dB below of the reference level.

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 100 kHz.(Actual 1 MHz , See below note)
3. Set the VBW ≥ 3 x RBW.(Actual 3 MHz, See below note)
4. Detector = peak.
5. Ensure that the number of measurement points ≥ span / RBW
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use the peak marker function to determine the maximum amplitude level.

Note: The unwanted emission(conducted) was tested with below settings.

Frequency range	RBW	VBW	Detector	Trace	Sweep Point
9 kHz ~ 30 MHz	100 kHz	300 kHz	Peak	Max Hold	40 001
30 MHz ~ 10 GHz	1 MHz	3 MHz			
10 GHz ~ 25 GHz	1 MHz	3 MHz			

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.

This test report is prohibited to copy or reissue in whole or in part without the approval of Dt&C Co., Ltd.

5.4.3. Test Results

TM 1 & ANT 1 & 26 Tone & 0 RU & 2 412

Reference



Low Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & ANT 1 & 26 Tone & 8 RU & 2 437

Reference



Conducted Spurious Emissions



Conducted Spurious Emissions





TM 1 & ANT 1 & 26 Tone & 8 RU & 2 462

Reference



High Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & ANT 1 & SU & 2 412

Reference



Low Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & ANT 1 & SU & 2 437

Reference



Conducted Spurious Emissions



Conducted Spurious Emissions





TM 1 & ANT 1 & SU & 2 462

Reference



High Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & ANT 2 & 26 Tone & 0 RU & 2 412

Reference



Low Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & ANT 2 & 26 Tone & 8 RU & 2 437

Reference



Conducted Spurious Emissions



Conducted Spurious Emissions





TM 1 & ANT 2 & 26 Tone & 8 RU & 2 462

Reference



High Band-edge



Conducted Spurious Emissions





Conducted Spurious Emissions