FCC PART 15.247

TEST REPORT

For

Hantat Technology Ltd.

3/F., C Building, Fuxinlin Industrial Park, Hangch Xixiang Town, Banan District, Shenzhen, China

FCC ID: V3NHB127

Report Type:	**Product Type:**
Original Report	Bluetooth Speaker

Test Engineer:	Lion Xiao
Report Number:	RDG160713801-00
Report Date:	2016-09-08
Reviewed By:	Dean Liu RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
TEST FACILITY 4
SYSTEM TEST CONFIGURATION **5**
DESCRIPTION OF TEST CONFIGURATION 5
EUT EXERCISE SOFTWARE 5
EQUIPMENT MODIFICATIONS 5
SUPPORT EQUIPMENT LIST AND DETAILS 5
EXTERNAL CABLE 5
BLOCK DIAGRAM OF TEST SETUP 6
SUMMARY OF TEST RESULTS **7**
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE **8**
APPLICABLE STANDARD 8
FCC §15.203 - ANTENNA REQUIREMENT **9**
APPLICABLE STANDARD 9
ANTENNA CONNECTOR CONSTRUCTION 9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **10**
APPLICABLE STANDARD 10
MEASUREMENT UNCERTAINTY 10
EUT SETUP 10
EMI TEST RECEIVER SETUP 11
TEST PROCEDURE 11
CORRECTED AMPLITUDE & MARGIN CALCULATION 11
TEST EQUIPMENT LIST AND DETAILS 12
TEST DATA 12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **15**
APPLICABLE STANDARD 15
MEASUREMENT UNCERTAINTY 15
EUT SETUP 15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 16
TEST PROCEDURE 16
TEST EQUIPMENT LIST AND DETAILS 17
CORRECTED AMPLITUDE & MARGIN CALCULATION 17
TEST DATA 17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST **23**
APPLICABLE STANDARD 23
TEST EQUIPMENT LIST AND DETAILS 23
TEST PROCEDURE 23
TEST DATA 23
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING **29**
APPLICABLE STANDARD 29

TEST PROCEDURE 29
TEST EQUIPMENT LIST AND DETAILS....29
TEST DATA 29

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST 35

APPLICABLE STANDARD 35
TEST PROCEDURE 35
TEST EQUIPMENT LIST AND DETAILS....35
TEST DATA 35

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)....39

APPLICABLE STANDARD 39
TEST PROCEDURE 39
TEST EQUIPMENT LIST AND DETAILS....39
TEST DATA 39

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 55

APPLICABLE STANDARD 55
TEST PROCEDURE 55
TEST EQUIPMENT LIST AND DETAILS....55
TEST DATA 55

FCC §15.247(d) - BAND EDGES TESTING 61

APPLICABLE STANDARD 61
TEST PROCEDURE 61
TEST EQUIPMENT LIST AND DETAILS....61
TEST DATA 62

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Hantat Technology Ltd.*'s product, model number: *HB127(FCC ID: V3NHB127)* (the "EUT") in this report was a *Bluetooth Speaker,* which was measured approximately: 59.5 mm (L) x 59.5 mm (W) x 49.5 mm (H), rated input voltage: DC3.7V rechargeable Li-ion battery.

All measurement and test data in this report was gathered from production sample serial number: 160713801 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-14.

Objective

This report is prepared on behalf of *Hantat Technology Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The software 'BK3256 RFTest_V1.3.exe' was used during testing, the maxmum output power setting configured by the software as below list:

Test Software Version	BK3256 RFTest_V1.3.exe		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	2	2	2
π/4-DQPSK	2	2	2
8DPSK	2	2	2

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Posh	Switching Adapter	C01-L640	N/A

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	0.50	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to§15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum power including tune-up tolerance is -1.0dBm (0.79 mW).
[(max. power of channel, mW)/(min. test separation distance, mm)][√f(GHz)]
= 0.79/5*(√2.480) = 0.3 < 3.0

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one integral antenna arrangement for buletooth and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by ($U_{lab} - U_{cispr}$), exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by ($U_{lab} - U_{cispr}$), exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$V_C = V_R + A_C + VDF$

Herein,
V_C: corrected voltage amplitude
V_R: reading voltage amplitude
A_c: attenuation caused by cable loss
VDF: voltage division factor of AMN or ISN

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2016-04-07	2017-04-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.2 °C
Relative Humidity:	47 %
ATM Pressure:	100.1 kPa

The testing was performed by Lion Xiao on 2016-07-14.

Test Result: Compliance

Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.192030	48.4	9.000	L1	10.2	15.5	63.9	Compliance
0.446873	41.5	9.000	L1	10.2	15.4	56.9	Compliance
0.472507	42.2	9.000	L1	10.1	14.3	56.5	Compliance
0.576662	50.2	9.000	L1	10.2	5.8	56.0	Compliance
0.915445	44.8	9.000	L1	10.4	11.2	56.0	Compliance
1.181325	42.4	9.000	L1	10.4	13.6	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.480097	34.2	9.000	L1	10.1	12.1	46.3	Compliance
0.576662	41.5	9.000	L1	10.2	4.5	46.0	Compliance
0.624492	34.4	9.000	L1	10.3	11.6	46.0	Compliance
0.768247	29.6	9.000	L1	10.4	16.4	46.0	Compliance
0.915445	36.7	9.000	L1	10.4	9.3	46.0	Compliance
1.363512	30.6	9.000	L1	10.4	15.4	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.188994	47.8	9.000	N	10.2	16.3	64.1	Compliance
0.472507	37.4	9.000	N	10.1	19.1	56.5	Compliance
0.567545	45.2	9.000	N	10.1	10.8	56.0	Compliance
0.614619	36.1	9.000	N	10.3	19.9	56.0	Compliance
0.915445	37.1	9.000	N	10.4	18.9	56.0	Compliance
1.181325	37.8	9.000	N	10.4	18.2	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.461346	31.6	9.000	N	10.1	15.1	46.7	Compliance
0.567545	40.6	9.000	N	10.1	5.4	46.0	Compliance
0.614619	29.5	9.000	N	10.3	16.5	46.0	Compliance
0.709407	29.2	9.000	N	10.4	16.8	46.0	Compliance
0.915445	34.5	9.000	N	10.4	11.5	46.0	Compliance
1.374420	31.4	9.000	N	10.4	14.6	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by ($U_{lab} - U_{cispr}$), exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by ($U_{lab} - U_{cispr}$), exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa

** The testing was performed by Lion Xiao on 2016-07-14.*

1) Below 1GHz:

Test mode: Tansmitting(BDR middle channel was worst case)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
41.6400	39.55	QP	-7.65	31.90	40.00	8.10
85.2900	36.69	QP	-12.19	24.50	40.00	15.50
147.3700	34.18	QP	-7.08	27.10	43.50	16.40
256.0100	46.45	QP	-7.65	38.80	46.00	7.20
297.7200	34.45	QP	-5.85	28.60	46.00	17.40
384.0500	41.99	QP	-4.09	37.90	46.00	8.10

Vertical:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
31.9400	24.60	QP	-0.50	24.10	40.00	15.90
62.9800	35.23	QP	-12.73	22.50	40.00	17.50
141.5500	30.10	QP	-6.80	23.30	43.50	20.20
256.0100	45.45	QP	-7.65	37.80	46.00	8.20
382.1100	42.64	QP	-4.14	38.50	46.00	7.50
450.0100	28.59	QP	-2.49	26.10	46.00	19.90

BDR Mode (GFSK):

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	FCC 15.247	
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	(dB)	(dB)	(dBµV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	87.60	PK	H	25.65	3.66	27.32	89.59	N/A	N/A
2402	80.41	AV	H	25.65	3.66	27.32	82.40	N/A	N/A
2402	82.70	PK	V	25.65	3.66	27.32	84.69	N/A	N/A
2402	75.65	AV	V	25.65	3.66	27.32	77.64	N/A	N/A
2400	61.28	PK	H	25.64	3.65	27.32	63.25	74.00	10.75
2400	43.82	AV	H	25.64	3.65	27.32	45.79	54.00	8.21
4804	47.19	PK	H	30.59	5.06	27.41	55.43	74.00	18.57
4804	42.56	AV	H	30.59	5.06	27.41	50.80	54.00	3.20
7206	38.28	PK	H	34.09	6.61	25.91	53.07	74.00	20.93
7206	30.24	AV	H	34.09	6.61	25.91	45.03	54.00	8.97
9608	32.91	PK	H	36.74	8.53	27.55	50.63	74.00	23.37
9608	20.17	AV	H	36.74	8.53	27.55	37.89	54.00	16.11
3328	46.79	PK	H	28.25	4.94	27.26	52.72	74.00	21.28
3328	44.72	AV	H	28.25	4.94	27.26	50.65	54.00	3.35
Middle Channel: 2441 MHz									
2441	88.10	PK	H	25.75	3.76	27.34	90.27	N/A	N/A
2441	81.22	AV	H	25.75	3.76	27.34	83.39	N/A	N/A
2441	83.69	PK	V	25.75	3.76	27.34	85.86	N/A	N/A
2441	76.69	AV	V	25.75	3.76	27.34	78.86	N/A	N/A
4882	47.47	PK	H	30.79	5.19	27.42	56.03	74.00	17.97
4882	42.23	AV	H	30.79	5.19	27.42	50.79	54.00	3.21
7323	38.81	PK	H	34.38	6.75	25.88	54.06	74.00	19.94
7323	30.47	AV	H	34.38	6.75	25.88	45.72	54.00	8.28
9764	32.39	PK	H	36.81	8.62	27.20	50.62	74.00	23.38
9764	20.54	AV	H	36.81	8.62	27.20	38.77	54.00	15.23
3328	46.56	PK	H	28.25	4.94	27.26	52.49	74.00	21.51
3328	44.40	AV	H	28.25	4.94	27.26	50.33	54.00	3.67
3610	37.31	PK	H	29.04	4.61	27.28	43.68	74.00	30.32
3610	25.57	AV	H	29.04	4.61	27.28	31.94	54.00	22.06
High Channel: 2480 MHz									
2480	89.58	PK	H	25.85	3.68	27.36	91.75	N/A	N/A
2480	82.41	AV	H	25.85	3.68	27.36	84.58	N/A	N/A
2480	84.64	PK	V	25.85	3.68	27.36	86.81	N/A	N/A
2480	77.46	AV	V	25.85	3.68	27.36	79.63	N/A	N/A
2483.5	60.72	PK	H	25.86	3.67	27.36	62.89	74.00	11.11
2483.5	42.33	AV	H	25.86	3.67	27.36	44.50	54.00	9.50
4960	47.13	PK	H	31.00	5.34	27.43	56.04	74.00	17.96
4960	42.82	AV	H	31.00	5.34	27.43	51.73	54.00	2.27
7440	38.06	PK	H	34.66	6.89	25.97	53.64	74.00	20.36
7440	28.91	AV	H	34.66	6.89	25.97	44.49	54.00	9.51
9920	32.33	PK	H	36.87	8.71	26.66	51.25	74.00	22.75
9920	20.61	AV	H	36.87	8.71	26.66	39.53	54.00	14.47
3328	46.65	PK	H	28.25	4.94	27.26	52.58	74.00	21.42
3328	44.41	AV	H	28.25	4.94	27.26	50.34	54.00	3.66

EDR Mode (π/4-DQPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	86.35	PK	H	25.65	3.66	27.32	88.34	N/A	N/A
2402	76.92	AV	H	25.65	3.66	27.32	78.91	N/A	N/A
2402	81.99	PK	V	25.65	3.66	27.32	83.98	N/A	N/A
2402	71.04	AV	V	25.65	3.66	27.32	73.03	N/A	N/A
2400	63.28	PK	H	25.64	3.65	27.32	65.25	74.00	8.75
2400	43.60	AV	H	25.64	3.65	27.32	45.57	54.00	8.43
4804	47.36	PK	H	30.59	5.06	27.41	55.60	74.00	18.40
4804	42.36	AV	H	30.59	5.06	27.41	50.60	54.00	3.40
7206	37.30	PK	H	34.09	6.61	25.91	52.09	74.00	21.91
7206	25.29	AV	H	34.09	6.61	25.91	40.08	54.00	13.92
9608	32.59	PK	H	36.74	8.53	27.55	50.31	74.00	23.69
9608	20.56	AV	H	36.74	8.53	27.55	38.28	54.00	15.72
3328	46.55	PK	H	28.25	4.94	27.26	52.48	74.00	21.52
3328	44.29	AV	H	28.25	4.94	27.26	50.22	54.00	3.78
Middle Channel: 2441 MHz									
2441	87.03	PK	H	25.75	3.76	27.34	89.20	N/A	N/A
2441	77.89	AV	H	25.75	3.76	27.34	80.06	N/A	N/A
2441	82.72	PK	V	25.75	3.76	27.34	84.89	N/A	N/A
2441	72.08	AV	V	25.75	3.76	27.34	74.25	N/A	N/A
4882	47.47	PK	H	30.79	5.19	27.42	56.03	74.00	17.97
4882	42.56	AV	H	30.79	5.19	27.42	51.12	54.00	2.88
7323	37.18	PK	H	34.38	6.75	25.88	52.43	74.00	21.57
7323	25.8	AV	H	34.38	6.75	25.88	41.05	54.00	12.95
9764	31.03	PK	H	36.81	8.62	27.20	49.26	74.00	24.74
9764	19.21	AV	H	36.81	8.62	27.20	37.44	54.00	16.56
3328	46.92	PK	H	28.25	4.94	27.26	52.85	74.00	21.15
3328	44.39	AV	H	28.25	4.94	27.26	50.32	54.00	3.68
3610	37.58	PK	H	29.04	4.61	27.28	43.95	74.00	30.05
3610	25.69	AV	H	29.04	4.61	27.28	32.06	54.00	21.94
High Channel: 2480 MHz									
2480	88.83	PK	H	25.85	3.68	27.36	91.00	N/A	N/A
2480	78.60	AV	H	25.85	3.68	27.36	80.77	N/A	N/A
2480	83.17	PK	V	25.85	3.68	27.36	85.34	N/A	N/A
2480	73.49	AV	V	25.85	3.68	27.36	75.66	N/A	N/A
2483.5	62.85	PK	H	25.86	3.67	27.36	65.02	74.00	8.98
2483.5	44.15	AV	H	25.86	3.67	27.36	46.32	54.00	7.68
4960	47.71	PK	H	31.00	5.34	27.43	56.62	74.00	17.38
4960	42.77	AV	H	31.00	5.34	27.43	51.68	54.00	2.32
7440	37.25	PK	H	34.66	6.89	25.97	52.83	74.00	21.17
7440	25.89	AV	H	34.66	6.89	25.97	41.47	54.00	12.53
9920	32.26	PK	H	36.87	8.71	26.66	51.18	74.00	22.82
9920	20.77	AV	H	36.87	8.71	26.66	39.69	54.00	14.31
3328	46.20	PK	H	28.25	4.94	27.26	52.13	74.00	21.87
3328	44.02	AV	H	28.25	4.94	27.26	49.95	54.00	4.05

EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	87.73	PK	H	25.65	3.66	27.32	89.72	N/A	N/A
2402	77.74	AV	H	25.65	3.66	27.32	79.73	N/A	N/A
2402	83.98	PK	V	25.65	3.66	27.32	85.97	N/A	N/A
2402	73.98	AV	V	25.65	3.66	27.32	75.97	N/A	N/A
2400	62.02	PK	H	25.64	3.65	27.32	63.99	74.00	10.01
2400	43.53	AV	H	25.64	3.65	27.32	45.50	54.00	8.50
4804	47.62	PK	H	30.59	5.06	27.41	55.86	74.00	18.14
4804	42.85	AV	H	30.59	5.06	27.41	51.09	54.00	2.91
7206	37.07	PK	H	34.09	6.61	25.91	51.86	74.00	22.14
7206	25.58	AV	H	34.09	6.61	25.91	40.37	54.00	13.63
9608	32.38	PK	H	36.74	8.53	27.55	50.10	74.00	23.90
9608	20.56	AV	H	36.74	8.53	27.55	38.28	54.00	15.72
3328	46.08	PK	H	28.25	4.94	27.26	52.01	74.00	21.99
3328	44.60	AV	H	28.25	4.94	27.26	50.53	54.00	3.47
Middle Channel: 2441 MHz									
2441	88.96	PK	H	25.75	3.76	27.34	91.13	N/A	N/A
2441	78.94	AV	H	25.75	3.76	27.34	81.11	N/A	N/A
2441	84.91	PK	V	25.75	3.76	27.34	87.08	N/A	N/A
2441	74.74	AV	V	25.75	3.76	27.34	76.91	N/A	N/A
4882	47.57	PK	H	30.79	5.19	27.42	56.13	74.00	17.87
4882	42.85	AV	H	30.79	5.19	27.42	51.41	54.00	2.59
7323	37.91	PK	H	34.38	6.75	25.88	53.16	74.00	20.84
7323	25.98	AV	H	34.38	6.75	25.88	41.23	54.00	12.77
9764	31.15	PK	H	36.81	8.62	27.20	49.38	74.00	24.62
9764	19.83	AV	H	36.81	8.62	27.20	38.06	54.00	15.94
3328	46.65	PK	H	28.25	4.94	27.26	52.58	74.00	21.42
3328	44.20	AV	H	28.25	4.94	27.26	50.13	54.00	3.87
3610	38.08	PK	H	29.04	4.61	27.28	44.45	74.00	29.55
3610	26.70	AV	H	29.04	4.61	27.28	33.07	54.00	20.93
High Channel: 2480 MHz									
2480	89.35	PK	H	25.85	3.68	27.36	91.52	N/A	N/A
2480	79.61	AV	H	25.85	3.68	27.36	81.78	N/A	N/A
2480	85.94	PK	V	25.85	3.68	27.36	88.11	N/A	N/A
2480	75.89	AV	V	25.85	3.68	27.36	78.06	N/A	N/A
2483.5	61.14	PK	H	25.86	3.67	27.36	63.31	74.00	10.69
2483.5	43.08	AV	H	25.86	3.67	27.36	45.25	54.00	8.75
4960	47.81	PK	H	31.00	5.34	27.43	56.72	74.00	17.28
4960	42.77	AV	H	31.00	5.34	27.43	51.68	54.00	2.32
7440	37.61	PK	H	34.66	6.89	25.97	53.19	74.00	20.81
7440	25.89	AV	H	34.66	6.89	25.97	41.47	54.00	12.53
9920	31.43	PK	H	36.87	8.71	26.66	50.35	74.00	23.65
9920	19.20	AV	H	36.87	8.71	26.66	38.12	54.00	15.88
3328	46.97	PK	H	28.25	4.94	27.26	52.90	74.00	21.10
3328	44.63	AV	H	28.25	4.94	27.26	50.56	54.00	3.44

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	49 %
ATM Pressure:	98.9 kPa

** The testing was performed by Lion Xiao 2016-08-18.*

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency	Channel Separation	Limit	Result
		MHz	MHz	MHz	
BDR (GFSK)	Low	2402	1.000	0.55	Compliance
	Middle	2441	1.000	0.55	
	High	2480	1.000	0.55	
EDR (π/4-DQPSK)	Low	2402	1.004	0.75	Compliance
	Middle	2441	1.004	0.75	
	High	2480	1.000	0.75	
EDR (8DPSK)	Low	2402	1.000	0.77	Compliance
	Middle	2441	1.000	0.78	
	High	2480	1.000	0.78	

Note: Limit= (2/3)×20dB bandwidth

BDR Mode (GFSK):

Low Channel



Date: 18.AUG.2016 00:07:31

Middle Channel



Date: 18.AUG.2016 00:06:45

High Channel



Date: 18.AUG.2016 00:06:07

EDR Mode (π/4-DQPSK):

Low Channel



Date: 18.AUG.2016 00:03:38

Middle Channel



Date: 18.AUG.2016 00:04:24

High Channel



Date: 18.AUG.2016 00:05:20

EDR Mode (8-DPSK):

Low Channel



Date: 18.AUG.2016 00:02:53

Middle Channel



Date: 18.AUG.2016 00:02:05

High Channel



Date: 18.AUG.2016 00:01:28

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.2 °C
Relative Humidity:	47 %
ATM Pressure:	98.9 kPa

** The testing was performed by Lion Xiao on 2016-08-17.*

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.82
	Middle	2441	0.82
	High	2480	0.82
EDR Mode (π/4-DQPSK):	Low	2402	1.12
	Middle	2441	1.12
	High	2480	1.12
EDR Mode (8-DPSK):	Low	2402	1.16
	Middle	2441	1.17
	High	2480	1.17

BDR Mode (GFSK):

Low Channel



Date: 17.AUG.2016 23:47:57

Middle Channel



Date: 17.AUG.2016 23:49:32

High Channel



Date: 17.AUG.2016 23:50:33

EDR Mode (π/4-DQPSK):

Low Channel



Date: 17.AUG.2016 23:55:12

Middle Channel



Date: 17.AUG.2016 23:54:07

High Channel



Date: 17.AUG.2016 23:52:28

EDR Mode (8-DPSK):

Low Channel



Date: 17.AUG.2016 23:57:03

Middle Channel



Date: 17.AUG.2016 23:58:38

High Channel



Date: 17.AUG.2016 23:59:41

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	49 %
ATM Pressure:	98.9 kPa

** The testing was performed by Lion Xiao on 2016-08-18.*

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	⩾15

Number of Hopping Channels



Date: 18.AUG.2016 00:34:25

EDR Mode (π/4-DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	⩾15

Number of Hopping Channels



Date: 18.AUG.2016 00:32:36

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	⩾15

Number of Hopping Channels



Date: 18.AUG.2016 00:24:29

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	49 %
ATM Pressure:	98.9 kPa

** The testing was performed by Lion Xiao on 2016-08-18.*

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.388	0.124	0.4	Compliance
	Middle	0.390	0.125	0.4	Compliance
	High	0.388	0.124	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Low	1.656	0.265	0.4	Compliance
	Middle	1.650	0.264	0.4	Compliance
	High	1.662	0.266	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Low	2.910	0.310	0.4	Compliance
	Middle	2.910	0.310	0.4	Compliance
	High	2.910	0.310	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Low Channel



Date: 18.AUG.2016 00:08:53

DH1: Middle Channel



Date: 18.AUG.2016 00:09:12

DH1: High Channel



Date: 18.AUG.2016 00:09:28

DH3: Low Channel



Date: 18.AUG.2016 00:09:56

DH3: Middle Channel



Date: 18.AUG.2016 00:10:28

DH3: High Channel



Date: 18.AUG.2016 00:10:45

DH5: Low Channel



Date: 18.AUG.2016 00:11:35

DH5: Middle Channel



Date: 18.AUG.2016 00:11:44

DH5: High Channel



Date: 18.AUG.2016 00:12:00

EDR Mode (π/4-DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.394	0.126	0.4	Compliance
	Middle	0.396	0.127	0.4	Compliance
	High	0.396	0.127	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
2DH3	Low	1.662	0.266	0.4	Compliance
	Middle	1.656	0.265	0.4	Compliance
	High	1.662	0.266	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
2DH5	Low	2.910	0.310	0.4	Compliance
	Middle	2.910	0.310	0.4	Compliance
	High	2.920	0.311	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

2DH1: Low Channel



Date: 18.AUG.2016 00:15:08

2DH1: Middle Channel



Date: 18.AUG.2016 00:15:27

2DH1: High Channel



Date: 18.AUG.2016 00:15:37

2DH3: Low Channel



Date: 18.AUG.2016 00:14:16

2DH3: Middle Channel



Date: 18.AUG.2016 00:14:34

2DH3: High Channel



Date: 18.AUG.2016 00:14:44

2DH5: Low Channel



Date: 18.AUG.2016 00:12:39

2DH5: Middle Channel



Date: 18.AUG.2016 00:12:52

2DH5: High Channel



Date: 18.AUG.2016 00:13:06

EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.396	0.127	0.4	Compliance
	Middle	0.396	0.127	0.4	Compliance
	High	0.396	0.127	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
3DH3	Low	1.656	0.265	0.4	Compliance
	Middle	1.656	0.265	0.4	Compliance
	High	1.662	0.266	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
3DH5	Low	2.920	0.311	0.4	Compliance
	Middle	2.920	0.311	0.4	Compliance
	High	2.910	0.310	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

3DH1: Low Channel



Date: 18.AUG.2016 00:16:10

3DH1: Middle Channel



Date: 18.AUG.2016 00:16:27

3DH1: High Channel



Date: 18.AUG.2016 00:16:37

3DH3: Low Channel



Date: 18.AUG.2016 00:17:03

3DH3: Middle Channel



Date: 18.AUG.2016 00:17:12

3DH3: High Channel



Date: 18.AUG.2016 00:17:42

3DH5: Low Channel



Date: 18.AUG.2016 00:18:30

3DH5: Middle Channel



Date: 18.AUG.2016 00:18:43

3DH5: High Channel



Date: 18.AUG.2016 00:18:56

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.2 °C ~ 27.4°C
Relative Humidity:	47% ~ 49 %
ATM Pressure:	98.9 kPa~100 kPa

** The testing was performed by Lion Xiao from 2016-08-17 to 2016-08-18.*

Test Result: Compliance.

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	-2.39	30
	Middle	2441	-1.54	30
	High	2480	-1.29	30
EDR Mode (π/4-DQPSK)	Low	2402	-4.01	30
	Middle	2441	-2.36	30
	High	2480	-1.93	30
EDR Mode (8-DPSK)	Low	2402	-3.67	30
	Middle	2441	-2.27	30
	High	2480	-1.63	30

Note: The data above was tested in conducted mode.

BDR Mode (GFSK):

Output Power, Low Channel



Date: 17.AUG.2016 23:48:24

Output Power, Middle Channel



Date: 17.AUG.2016 23:49:57

Output Power, High Channel



Date: 17.AUG.2016 23:50:59

EDR Mode (π/4-DQPSK):

Output Power, Low Channel



Date: 17.AUG.2016 23:55:53

Output Power, Middle Channel



Date: 17.AUG.2016 23:54:48

Output Power, High Channel



Date: 17.AUG.2016 23:52:55

EDR Mode (8-DPSK):

Output Power, Low Channel



Date: 17.AUG.2016 23:57:29

Output Power, Middle Channel



Date: 17.AUG.2016 23:59:08

Output Power, High Channel



Date: 18.AUG.2016 00:00:07

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.2 °C ~ 27.4°C
Relative Humidity:	47% ~ 49 %
ATM Pressure:	98.9 kPa~100 kPa

** The testing was performed by Lion Xiao from 2016-08-17to 2016-08-18.*

Test Result: Compliance

BDR Mode (GFSK):

Band Edge, Left Side



Date: 17.AUG.2016 23:48:48

Band Edge, Right Side



Date: 17.AUG.2016 23:51:43

EDR Mode (π/4-DQPSK):

Band Edge, Left Side



Date: 17.AUG.2016 23:56:37

Band Edge, Right Side



Date: 17.AUG.2016 23:53:41

EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 17.AUG.2016 23:58:07

Band Edge, Right Side



Date: 18.AUG.2016 00:00:42

*******END OF REPORT*******