

TEST REPORT
of the accredited test laboratory

TÜV Nr.:INE-AT/FG-19/102

Applicant: AKG Acoustics GmbH
Salzgasse 2
5400 Hallein, Austria

Tested Product: wireless microphone bodyworn transmitter

Type: PT45 RF Band A

Manufacturer: VTech Communications Ltd.
Xia Ling Bei Management Zone, Liaobu, Dongguan,
Guangdong Province
523411 China

Output power: 6 mW **power supply:** 1,5V DC
internal battery

Frequency range: 530 – 560 MHz **Channel separation:** 200kHz

Standard: EN 300 422-1 V2.1.2 ; 47 CFR Part 74 (Oct. 2018 Edition);
RSS-210 Issue 9

Testing Laboratory,
Inspection Body,
Certification Body,
Calibration Laboratory,
VerifizierungsstelleNotified Body 0408
IC 2932K-1Non-executive
Board of Directors:
KR DI Johann
MarthartManagement:
DI Dr. Stefan Haas
Mag. Christoph
WerningerRegistered Office:
Deutschstrasse 10
1230 Vienna/AustriaBranch Offices:
www.tuv.at/standorteCompany Register
Court / - Number:
Vienna / FN 288476 fBank Details:
IBAN
AT131200052949001066
BIC BKAUATWWIBAN
AT153100000104093282
BIC RZBAATWWVAT ATU63240488
DVR 3002476TÜV AUSTRIA SERVICES GMBH
Test laboratory for EMC

Supervisor of EMC-laboratory:

Ing. Wilhelm Seier

01.02.2019

Copy Nbr.: 01

checked by:

Ing. Michael Emminger

A publication of this test report is only permitted literally.
Copying or reproduction of partial sections needs a written permission of TÜV AUSTRIA
SERVICES GMBH.

The results of this test report only refer to the provided equipment.

Contents

	Designation	PAGE
1.	Applicant	3
2.	Description of EUT	4
3.	Standards / Final result	5
4.	Test results	
	List of measurements according to EN 300 422-1 V2.1.2	
	Transmitter parameters	
4.1	Frequency stability	6-7
4.2	Rated output power	8
4.3	Necessary bandwidth	9-12
4.4	Spurious emissions	13-16
4.5	Transmitter intermodulation distortion	17
	Receiver	
	Spurious emissions	---
	Receiver sensitivity	---
	Receiver adjacent channel selectivity	---
	Receiver blocking	---
Appendix	Designation	PAGES
1	Test equipment used	4
2	Photodocumentation	7

1. Applicant

Company: AKG Acoustics GmbH

Department: R&D

Address: Salzgasse 2
5400 Hallein, Austria

Contact person: Mr. Gabor Mikovics

EUT received on: 16.10.2018

Tests were performed on: 16.01. till 29.01.2019

2. Description of EUT

EUT:	Wireless microphone bodyworn transmitter 'PT45 RF Band A'
Serial Number:	Prototype
Manufacturer:	AKG Acoustics GmbH Salzgasse 2 5400 Hallein, Austria
Description:	AKG Acoustics GmbH provided the following configuration for the measurements: Prototype
Operating mode:	The measurements were carried out at the following running states: Transmitting
Technical data EUT:	Rated voltage: 1,5VDC Rated current: 500mA Rated frequency: DC Mains voltage during the tests: 1,5VDC via internal battery
Climatic conditions in the emc laboratory:	Relative humidity: 19% Temperature: 25°C

3. Standards / Final result

Name	Title	Deviation	Result
EN 300422-1 V2.1.2	Wireless Microphones; Audio PMSE up to 3 GHz; Part 1: Class A Receivers; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU	none	OK
47 CFR Part 74 (Oct. 2018 Edition)	EXPERIMENTAL RADIO, AUXILIARY, SPECIAL BROADCAST AND OTHER PROGRAM DISTRIBUTIONAL SERVICES; Subpart H—Low Power Auxiliary Stations	none	OK
RSS-210 Issue 9	Licence-Exempt Radio Apparatus: Category I Equipment; Annex G—Low-Power Radio Apparatus Operating in the Television Bands	none	OK
Result: Opinions and interpretation of testing laboratory OK: EUT passed NOK: EUT failed			

4. TEST RESULT

4.1. Frequency stability

SUBCLAUSE 8.1

ETSI requirements

Rated output power: 6 mW

Operating condition		Frequency Error kHz			Frequency Error ppm		
		530 MHz	545 MHz	560 MHz	530 MHz	545 MHz	560 MHz
T_{nom} (25)°C	V_{nom} (1,5)V	-0,188	-0,230	-0,274	-0,36	-0,42	-0,49
T_{min} (-20)°C	V_{min} (1)V	-2,001	-2,093	-2,183	-3,78	-3,84	-3,90
	V_{nom} (1,5)V	-2,112	-2,218	-2,295	-3,99	-4,07	-4,10
T_{max} (55)°C	V_{min} (1)V	-1,641	-1,693	-1,780	-3,10	-3,11	-3,18
	V_{nom} (1,5)V	-1,651	-1,718	-1,797	-3,12	-3,15	-3,21
Measurement uncertainty					$\pm 0,1$ ppm		

LIMIT

SUBCLAUSE 8.1.3

The frequency error shall not exceed 20 parts per million for frequencies below 1 GHz, 15 parts per million between 1 GHz and 2 GHz and 10 ppm above 2 GHz.

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-207; EMV-205; M-1200

Frequency stability

SUBCLAUSE 74.861 / G3.3

FCC/ISED requirements

Rated output power: 6 mW

Operating condition	Frequency Error kHz			Frequency Error ppm		
	530 MHz	545 MHz	560 MHz	530 MHz	545 MHz	560 MHz
Operating voltage at 20°C ambient temperature						
1,5 V	-0,215	-0,255	-0,290	-0,41	-0,47	-0,52
1 V	-0,226	-0,268	-0,307	-0,43	-0,49	-0,55
Measurement uncertainty				± 0,1 ppm		

Operating condition	Frequency Error kHz			Frequency Error ppm		
	530 MHz	545 MHz	560 MHz	530 MHz	545 MHz	560 MHz
ambient temperature at 1,5V operating voltage						
-30°C	-6,268	-6,505	-6,742	-11,83	-11,94	-12,04
-20°C	-2,165	-2,218	-2,334	-4,09	-4,07	-4,17
-10°C	-0,496	-0,555	-0,610	-0,94	-1,02	-1,09
0°C	0,246	0,233	0,219	0,46	0,43	0,39
10°C	0,209	0,158	0,174	0,39	0,29	0,31
20°C	-0,215	-0,255	-0,302	-0,41	-0,47	-0,54
30°C	-0,146	-0,193	-0,229	-0,28	-0,35	-0,41
40°C	-1,164	-1,180	-1,276	-2,20	-2,17	-2,28
50°C	-1,625	-1,693	-1,791	-3,07	-3,11	-3,20
Measurement uncertainty				± 0,1 ppm		

LIMIT

SUBCLAUSE 74.861(e)(4) / Table G.1

The frequency tolerance of the transmitter shall be 0,005 percent (50ppm).

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-207; EMV-205; M-1200

4.2 Rated output power

SUBCLAUSE 8.2

Radiated Measurement

Rated output power: 6 mW

Test conditions		Transmitter power (mW) (erp)		
		530 MHz	545 MHz	560 MHz
T_{nom} (25)°C	V_{nom} (1,5)V	3,02	4,47	4,68
Maximum deviation from rated output power under normal test conditions (%)		-49,7	-25,6	-22,0
Measurement uncertainty		$\pm 0,75$ dB		

LIMIT

SUBCLAUSE 8.2.3

The measured value shall be within +20 % and -50 % of the manufacturers declared rated output power.

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-207

4.3 NECESSARY BANDWIDTH

SUBCLAUSE 8.3

LIMIT

SUBCLAUSE 8.3.2.2




Figure 3 shows the spectrum mask for all analogue systems in the band. The -90 dBc point shall be $\pm 1 \text{ MHz}$ from f_c measured with an average detector. To comply, a measured value shall fall below the mask limit as shown in figure 3.


NECESSARY BANDWIDTH

SUBCLAUSE 8.3

The operating Bandwidth was measured at an acoustic input level 12 dB higher than the limiting threshold, determined with 500 Hz signal.

Rated output power: 6 mW

Measurement with weighted noise source signal @ 530 MHz centered.



Date: 4.APR.2019 10:42:06

TEST EQUIPMENT USED: EMV-205


NECESSARY BANDWIDTH

SUBCLAUSE 8.3

The operating Bandwidth was measured at an acoustic input level 12 dB higher than the limiting threshold, determined with 500 Hz signal.

Rated output power: 6 mW

Measurement with weighted noise source signal @ 545 MHz centered.



Date: 4.APR.2019 10:48:05

TEST EQUIPMENT USED: EMV-205


NECESSARY BANDWIDTH

SUBCLAUSE 8.3

The operating Bandwidth was measured at an acoustic input level 12 dB higher than the limiting threshold, determined with 500 Hz signal.

Rated output power: 6 mW

Measurement with weighted noise source signal @ 560 MHz centered.



Date: 4.APR.2019 10:45:42

TEST EQUIPMENT USED: EMV-205


4.4 TRANSMITTER SPURIOUS EMISSIONS radiated

SUBCLAUSE 8.4

Operating mode: transmitter operating at 530 MHz

Rated output power: 6 mW

Modulation: unmodulated carrier



LIMIT

SUBCLAUSE 8.4.3

47 MHz to 74 MHz 87,5 MHz to 137 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	Other frequencies $\leq$ 1000 MHz	Frequencies > 1000 MHz
4,0 nW (-54 dBm)	250 nW (-36 dBm)	1,00 μ W (-30 dBm)

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-139; NT-337; NT-207


TRANSMITTER SPURIOUS EMISSIONS radiated

SUBCLAUSE 8.4

Operating mode: transmitter operating at 545 MHz

Rated output power: 6 mW

Modulation: unmodulated carrier



LIMIT

SUBCLAUSE 8.4.3

47 MHz to 74 MHz 87,5 MHz to 137 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	Other frequencies $\leq$ 1000 MHz	Frequencies > 1000 MHz
4,0 nW (-54 dBm)	250 nW (-36 dBm)	1,00 μ W (-30 dBm)

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-139; NT-337; NT-207


TRANSMITTER SPURIOUS EMISSIONS radiated

SUBCLAUSE 8.4

Operating mode: transmitter operating at 560 MHz

Rated output power: 6 mW

Modulation: unmodulated carrier



LIMIT

SUBCLAUSE 8.4.3

47 MHz to 74 MHz 87,5 MHz to 137 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	Other frequencies ≤ 1000 MHz	Frequencies > 1000 MHz
4,0 nW (-54 dBm)	250 nW (-36 dBm)	1,00 µW (-30 dBm)

Test Equipment used: NT-100; NT-110/1; NT-111/1; NT-112/1; NT-131/1; NT-139; NT-337; NT-207

TRANSMITTER SPURIOUS EMISSIONS radiated

SUBCLAUSE 8.4

Operating mode: transmitter standby

Because the transmitter is operating after switching on, there is no standby mode available and no measurement was performed.

4.5 Transmitter intermodulation distortion

SUBCLAUSE 8.5

Radiated measurement

Unwanted Signal	TX-IMD (dBc)		
	530 MHz	545 MHz	560 MHz
fw + 5 MHz	-54,8	-52,9	-53,4
fw – 5 MHz	-55,3	-52,9	-52,1
Measurement uncertainty	± 3dB		

LIMIT

SUBCLAUSE 8.5.3

The maximum resulting IMD product shall be at least 40 dB below the output power of the DUT.

Measuring equipment used:

NT-100; NT-111/1; NT-112/1; NT-113/1; NT-131/1; NT-210; NT-310; NT-310/1; EMV-205

Appendix 1

Test equipment used

☐ Anechoic Chamber with 3m measurement distance	NT-100	☐ Power quality analyzer Fluke 1760 (complete set)	NT-160 - NT-173
☐ Stripline according to ISO 11452-5	NT-108	☐ Spectrum analyzer – FSP7 9 kHz – 7 GHz	NT-200
☐ MA4000 - Antenna mast 1 - 4 m height	NT-110/1	☐ ESCI - Test receiver 9 kHz - 7 GHz	NT-203/1
☐ DS - Turntable 0 - 400 ° Azimuth	NT-111/1	☐ ESI26 – Test receiver 20 Hz – 26,5 GHz	NT-207
☐ CO3000 Controller Mast+Turntable	NT-112/1	☐ Digital Radio Tester CTS55	NT-208
☐ HUF-Z3 - Log. Per. Antenna 200 - 1000 MHz	NT-121	☐ Noise-gen., ITU-R 559-2 20 Hz – 20 kHz	NT-209
☐ FMZB1513 - Loop Antenna 9 kHz - 30 MHz	NT-122/1	☐ CMTA - Radiocommunication analyzer ; 0,1 - 1000 MHz	NT-210
☐ HFH-Z6 - Rod Antenna 9 kHz - 30 MHz	NT-123	☐ 3271 - Spectrum analyzer 100 Hz - 26,5 GHz	NT-211
☐ 3121C - Dipole Antenna 28 - 1000 MHz	NT-124	☐ Digital Radio Tester Aeroflex 3920	NT-212/1
☐ 3115 - Horn Antenna 1 - 18 GHz (immunity)	NT-125	☐ Mixer M28HW 26,5 GHz - 40 GHz	NT-214
☐ 3116 - Horn Antenna 18 - 40 GHz	NT-126	☐ RubiSource T&M Timing reference	NT-216
☐ SAS-200/543 - Bicon. Antenna 20 MHz - 300 MHz	NT-127	☐ Radiocommunication analyzer SWR 1180 MD	NT-217
☐ AT-1080 - Log. Per. Antenna 80 - 1000 MHz	NT-128	☐ Mixer M19HWD 40 GHz – 60 GHz	NT-218
☐ HK-116 - bicon. Antenna 20 MHz - 300 MHz	NT-129	☐ Mixer M12HWD 60 GHz – 90 GHz	NT-219
☐ HK-116 - bicon. Antenna 20 MHz - 300 MHz	NT-130	☐ DSO9104 Digital scope	NT-220/1
☐ 3146 - Log. Per. Antenna 200 – 1000 MHz	NT-131	☐ TPS 2014 Digital scope	NT-222
☐ VULB 9163 Trilog Antenna 30 – 3000 MHz	NT-131/1	☐ Artificial Ear according to IEC 60318	NT-224
☐ Loop Antenna H-Field	NT-132	☐ 1 kHz Sound calibrator	NT-225
☐ Horn Antenna 500 MHz - 2900 MHz	NT-133	☐ B10 - Harmonics and flicker analyzer	NT-232
☐ Horn Antenna 500 MHz - 6000 MHz	NT-133/1	☐ SRM-3006 Spectrum analyzer	NT-233/1a
☐ Log. per. Antenna 800 MHz - 2500 MHz	NT-134	☐ E-field probe SRM 75 MHz – 3 GHz	NT-234
☐ Log. per. Antenna 800 MHz - 2500 MHz	NT-135	☐ Field Meter NBM-500 incl. E- and H-Field probes	NT-240a-e
☐ BiConiLog Antenna 26 MHz – 2000 MHz	NT-137	☐ Hall-Teslameter ETM-1	NT-241
☐ Conical Dipol Antenna PCD8250	NT-138	☐ EFA-3 H-field- / E-field probe	NT-243
☐ HF 906 - Horn Antenna 1 - 18 GHz (emission)	NT-139	☐ EHP-50F H-field- / E-field probe	NT-243/1
☐ HZ-1 Antenna tripod	NT-150	☐ Field Meter EMR-200 100 kHz – 3 GHz	NT-244
☐ BN 1500 Antenna tripod	NT-151	☐ E-field probe 100 kHz – 3 GHz	NT-245
☐ Ant. tripod for EN61000-4-3 Model TP1000A	NT-156	☐ H-field probe 300 kHz – 30 MHz	NT-246

Division:
Industry & Energy

Department: FG

Test report number:
INE-AT/FG-19/102

Page: 1 of 4

Date: 01.02.2019

Appendix 1 (continued) Test equipment used

☐ E-field probe 3 MHz – 18 GHz	NT-247	☐ T82-50 RF-Amplifier 2 GHz – 8 GHz	NT-331
☐ H-field probe 27 MHz – 1 GHz	NT-248	☐ 500W1000M7 - RF-Amplifier 80 - 1000 MHz / 500 W	NT-332
☐ ELT-400 1 Hz – 400 kHz	NT-249	☐ AS0102-65R - RF-Amplifier 1 GHz - 2 GHz	NT-333
☐ MDS 21 - Absorbing clamp 30 - 1000 MHz	NT-250	☐ APA01 - RF-Amplifier 0,5 GHz – 2,5 GHz	NT-334
☐ FCC-2031 EM Injection clamp	NT-251	☐ Preamplifier 1 GHz - 4 GHz	NT-335
☐ FCC-2031-DCN Ferrite decoupling network	NT-252	☐ Preamplifier for GPS MKU 152 A	NT-336
☐ PR50 Current Probe	NT-253	☐ Preamplifier 100 MHz – 23 GHz	NT-337
☐ i310s Current Probe	NT-254/1	☐ DC Block 10 MHz – 18 GHz Model 8048	NT-338
☐ Fluke 87 V True RMS Multimeter	NT-260	☐ 2-97201 Electronic load	NT-341
☐ Model 2000 Digital Multimeter	NT-261	☐ TSX3510P - Power supply 0-30 V / 0 - 10 A	NT-344
☐ Fluke 87 V Digital Multimeter	NT-262/1	☐ TSX3510P - Power supply 0-30 V / 0 - 10 A	NT-345
☐ ESH2-Z5-U1 Artificial mains network 4x25A	NT-300	☐ VDS 200 Mobil-impuls-generator	NT-350
☐ ESH3-Z5-U1 Artificial mains network 2x10A	NT-301	☐ LD 200 Mobil-impuls-generator	NT-351
☐ ESH3-Z6-U1 Artificial mains network 1x100A	NT-302	☐ MPG 200 Mobil-Impuls-Generators	NT-352
☐ ESH3-Z6-U1 Artificial mains network 1x100A	NT-302a	☐ EFT 200 Mobil-impuls-generator	NT-353
☐ PHE 4500/B Power amplifier	NT-304	☐ AN 200 S1 Artificial Network	NT-354
☐ EZ10 T-Artificial Network	NT-305	☐ FP-EFT 32M 3 ph. Coupling filter (Burst)	NT-400/1
☐ SMG - Signal generator 0,1 - 1000 MHz	NT-310	☐ PHE 4500 - Mains impedance network	NT-401
☐ SMA100A - Signal generator 9 kHz - 6 GHz	NT-310/1	☐ IP 6.2 Coupling filter for data lines (Surge)	NT-403
☐ RefRad Reference generator	NT-312	☐ TK 9421 High Power Volt. Probe 150 kHz - 30 MHz	NT-409
☐ SMP 02 Signal generator 10 MHz - 20 GHz	NT-313	☐ ESH2-Z3 - Probe 9 kHz - 30 MHz	NT-410
☐ 40 MHz Arbitrary Generator TGA1241	NT-315	☐ IP 4 - Capacitive clamp (Burst)	NT-411
☐ Artificial mains network NSLK 8127-PLC	NT-316	☐ Highpass-Filter 100 MHz – 3 GHz	NT-412
☐ ESD 30 System up to 25 kV	NT-321	☐ Highpass-Filter 600 MHz – 4 GHz	NT-413
☐ PSURGE 4.1 Surge generator	NT-324	☐ Highpass-Filter 1250 MHz – 4 GHz	NT-414
☐ IMU4000 Immunity test system	NT-325/1	☐ Highpass-Filter 1800 MHz – 16 GHz	NT-415
☐ VCS 500-M6 Surge-Generator	NT-326		
☐ Oscillatory Wave Simulator incl. Coupling networks	NT-328a+b+c		
☐ BTA-250 - RF-Amplifier 9 kHz - 220 MHz / 250 W	NT-330		

Division:
Industry & Energy

Department: FG

Test report number:
INE-AT/FG-19/102

Page: 2 of 4

Date: 01.02.2019

Appendix 1 (continued)

Test equipment used

☐ Highpass-Filter 3500 MHz – 18 GHz	NT-416	☐ FCC-801-AF10 Coupling decoupling network	NT-461
☐ RF-Attenuator 10 dB DC – 18 GHz / 50 W	NT-417	☐ FCC-801-S25 Coupling decoupling network	NT-462
☐ RF-Attenuator 6 dB DC – 18 GHz / 50 W	NT-418	☐ FCC-801-T4 Coupling decoupling network	NT-463
☐ RF-Attenuator 3 dB DC – 18 GHz / 50 W	NT-419	☐ FCC-801-C1 Coupling decoupling network	NT-464
☐ RF-Attenuator 20 dB DC - 1000 MHz / 25 W	NT-421	☐ SW 9605 - Current probe 150 kHz – 30 MHz	NT-465/1
☐ RF-Attenuator 30 dB DC - 1000 MHz / 1 W	NT-423	☐ 95242-1 – Current probe 1 MHz – 400 MHz	NT-468
☐ RF-Attenuator 30 dB	NT-424	☐ 94106-1L-1 – Current probe 100 kHz – 450 MHz	NT-471
☐ RF-Attenuator 6 dB DC - 1000 MHz / 1 W	NT-425	☐ GA 1240 Power amplifier according to EN 61000-4-16	NT-480
☐ RF-Attenuator 6 dB DC - 1000 MHz / 1 W	NT-426	☐ Coupling networks according to EN 61000-4-16	NT-481 - NT-483
☐ RF-Attenuator 6 dB	NT-428	☐ Van der Hoofden Test Head	NT-484
☐ RF-Attenuator 0 dB - 81 dB	NT-429	☐ EMC Video/Audiosystem	NT-511/1
☐ WRU 27 - Band blocking 27 MHz	NT-430	☐ ES-K1 Version 1.71 SP2 Test software	NT-520
☐ WHJ450C9 AA - High pass 450 MHz	NT-431	☐ EMC32 Version 10.50.00 Test software	NT-520/1
☐ WHJ250C9 AA - High pass 250 MHz	NT-432	☐ SRM-TS Version 1.3 software for SRM-3000	NT-522
☐ RF-Load 150 W	NT-433	☐ SRM-TS Version 1.3.1 software for SRM-3006	NT-522/1
☐ Impedance transducer 1:4 ; 1:9 ; 1:16	NT-435	☐ Spitzenberger und Spies Test software V4.1	NT-525
☐ RF-Attenuator DC – 18 GHz 6 dB	NT-436	☐ Noise power test apparatus according to EN 55014	NT-530
☐ RF-Attenuator DC – 18 GHz 6 dB	NT-437	☐ Vertical coupling plane (ESD)	NT-531
☐ RF-Attenuator DC – 18 GHz 10 dB	NT-438	☐ Test cable #4 for EN 61000-4-6	NT-553
☐ RF-Attenuator DC – 18 GHz 20 dB	NT-439	☐ Test cable #3 for conducted emission	NT-554
☐ I+P 7780 Directional coupler 100 - 2000 MHz	NT-440	☐ Test cable #5+#6 ESD-cable (2x470k)	NT-555 + NT-556
☐ ESH3-Z2 - Pulse limiter 9 kHz - 30 MHz	NT-441	☐ Test cable #8 Sucoflex 104EA	NT-559
☐ Power Divider 6 dB/1 W/50 Ohm	NT-443	☐ Test cable #9 (for outdoor measurements)	NT-580
☐ Directional coupler 0,1 MHz – 70 MHz	NT-444	☐ Test cable #10 (for outdoor measurements)	NT-581
☐ Directional coupler 0,1 MHz – 70 MHz	NT-445	☐ Test cable #13 Sucoflex 104PE	NT-584
☐ Tube imitations according to EN 55015	NT-450	☐ Test cable #21 for SRM-3000	NT-592
☐ FCC-801-M3-16A Coupling decoupling network	NT-458	☐ Shield chamber	NT-600
☐ FCC-801-M2-50A Coupling decoupling network	NT-459	☐ Climatic chamber	M-1200
☐ FCC-801-M5-25 Coupling decoupling network	NT-460		

Division:
Industry & Energy

Department: FG

Test report number:
INE-AT/FG-19/102

Page: 3 of 4

Date: 01.02.2019

Appendix 1 (continued)

Test equipment used

☐	Anechoic Chamber 3 m / 5 m measuring distance	EMV-100	☐	Log.per Antenna 0,7 – 9 GHz STLP9149	EMV-305
☐	Turntabel 6 m diameter	EMV-101	☐	HF- Amplifier 9 kHz-250 MHz BBA150 (low noise)	EMV-306
☐	Antenna mast 1 – 4 m	EMV-102	☐	Load Dump Generator LD 200N	EMV-350
☐	Mast and Turntable controller FC-06	EMV-103	☐	Ultra Compact Symulator UCS 200N100	EMV-351
☐	EMC Video/Audiosystem	EMV-104	☐	Automotive Power fail module PFM 200N100.1	EMV-352
☐	EMC Software EMC32 Version 10.50.00	EMV-105	☐	Voltage Drop Symulator VDS 200Q100	EMV-353
☐	Hornantenna 1 – 18 GHz HF 907	EMV-110	☐	Arb. Generator AutoWave	EMV-354
☐	Antennapre.amp. 1 – 18 GHz ERZ-LNA0200-1800-30-2	EMV-111	☐	Ultra Compact Symulator UCS 500N7	EMV-355
☐	Trilog Antenna 30-3000 MHz VULB9163	EMV-112	☐	Coupling decoupling network CNI 503B7 / 32 A	EMV-356
☐	Monopol 9 kHz – 30 MHz VAMP 9243	EMV-113	☐	Coupling decoupling network CNI 503B7 / 63 A	EMV-357
☐	Antennapre.amp 18 – 40 GHz BBV 9721	EMV-114	☐	Telecom Surge Generator TSurge 7	EMV-358
☐	Hornantenna 200 – 2000 MHz AH-220	EMV-115	☐	Coupling decoupling network CNI 508N2	EMV-359
☐	DC Artificial Network PVDC 8300	EMV-150	☐	Coupling decoupling network CNV 504N2.2	EMV-360
☐	AC Artificial Network NNLK 8121 RC	EMV-151	☐	Immunity generator NSG4060/NSG4060-1	EMV-361
☐	EMI Receiver ESR26	EMV-200	☐	Coupling network CDND M316-2	EMV-362
☐	Signalgenerator 9 kHz – 40 GHz N5173B	EMV-201	☐	Coupling network CT419-5	EMV-363
☐	GPS Frequency normal B-88	EMV-202	☐	ESD Generator NSG 437	EMV-364
☐	DC Power supply N5745A	EMV-203	☐	Pulse Limiter VTSD 9561-F BNC	EMV-405
☐	Spektrum Analyzator FSV40	EMV-205	☐	Transient emission BSM200N40+BS200N100	EMV-450+451
☐	Thd Multimeter Model 2015	EMV-206	☐	Cap. Coupling Clamp HFK	EMV-455
☐	Poweramplifier PAS15000	EMV-207/abc	☐	Mag. Field System MS100N+MC26100+MC2630	EMV-456-458
☐	Inrush Current Source	EMV-208/abc	☐	Coupling network CDN M2-100A	EMV-459
☐	Arb.-generator Sycore	EMV-209	☐	Coupling network CDN M3-32A	EMV-460
☐	Harmonics/Flicker analyzer ARS 16/3	EMV-210	☐	Coupling network CDN M5-100A	EMV-461
☐	HF- Amplifier 9 kHz-250 MHz BBA150	EMV-300	☐	Current Clamp CIP 9136A	EMV-462
☐	HF- Amplifier 80 -1000 MHz BBA150	EMV-301	☐	DC Artificial Network HV-AN 150	EMV-464+465
☐	HF- Amplifier 0,8 - 6 GHz BBA150	EMV-302	☐	Coupling Clamp EM 101	EMV-466
☐	High Power Ant. 20-200 MHz VHBD 9134	EMV-303	☐	Decoupling Clamp FTC 101	EMV-467
☐	Log.per Antenna 80-2700 MHz STLP 9128 E special	EMV-304	☐	Power attenuator 10 dB / 250 Watt	EMV-469/2

Division:
Industry & Energy

Department: FG

Test report number:
INE-AT/FG-19/102

Page: 4 of 4

Date: 01.02.2019