

**FCC PART 22H, PART 24E
TEST REPORT**

For

Advanced Card Systems Limited

Units 4107 - 4110, 41st Floor, Manhattan Place, 23 Wang Tai Road, Kowloon Bay, Hong Kong

FCC ID: V5MACR900

Report Type: Original Report	Product Type: Banking POS Terminal
Report Number: RSZ170512001-00D	
Report Date: 2017-07-03	
Oscar Ye	
Reviewed By:	Engineer <i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH	16
APPLICABLE STANDARD	16
TEST PROCEDURE	16
TEST DATA	16
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	40

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Advanced Card Systems Limited's* product, model number: *ACR900 (FCC ID: V5MACR900)* or the "EUT" in this report was a *Banking POS Terminal*, which was measured approximately: 192mm (L) x 83mm (W) x 68mm (H), rated with input voltage: DC 7.4V rechargeable Li-ion battery or DC 9.0V from adapter.

Adapter Information:

Model: YJS11-0903000U

Input: AC100-240V, 50/60Hz, 1000 mA

Output: DC9.0V, 3000 mA

**All measurement and test data in this report was gathered from production sample serial number: 1700962 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-05-12.*

Objective

This type approval report is prepared on behalf of *Advanced Card Systems Limited* in accordance with Part 2, Part 22-Subpart H, Part 24-Subpart E of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.225 DXX, Part 15.247 DTS submissions with FCC ID: V5MACR900.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
RF conducted test with spectrum		$\pm 0.9\text{dB}$
Radiated emission	30MHz~1GHz	$\pm 5.91\text{dB}$
	Above 1G	$\pm 4.92\text{dB}$
Occupied Bandwidth		$\pm 0.5\text{kHz}$
Temperature		$\pm 1.0^{\circ}\text{C}$
Humidity		$\pm 6\%$

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Bay Area Compliance Laboratories Corp. (Kunshan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L9963). And accredited to ISO/IEC 17025 by A2LA(Lab code: 4323.01), the FCC Designation No. CN1185 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Kunshan) was registered with ISED Canada under ISED Canada Registration Number 3062E.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§2.1053, §22.917 & §24.238	Spurious Radiated Emissions	Compliance
§ 22.917 (a); § 24.238 (a)	Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ170512001-20.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrument	Amplifier	330	171377	2016-10-21	2017-10-21
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2019-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29
ETS	Horn Antenna	3116	2516	2016-12-12	2019-12-12
Heatsink Required	Amplifier	QLW-18405536-J0	15963243365	2017-05-21	2018-05-21
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
WEINSCHEL	3dB Attenuator	5326	N/A	2017-06-18	2018-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2017-06-12	2018-06-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ170512001-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.


FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER**Applicable Standard**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

Test Procedure*Conducted method:*

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.

*Radiated method:*

TIA 603-D section 2.2.17

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Alisa Gao on 2017-06-27.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	31.61	30.61	28.93	27.59	38.45
	190	836.6	31.67	30.68	29.02	27.67	38.45
	251	848.8	31.59	30.62	28.99	27.65	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	27.10	25.47	23.52	22.15	38.45
	190	836.6	27.05	25.37	23.52	22.07	38.45
	251	848.8	26.86	25.14	23.29	21.86	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.28	22.13	22.22
		HSDPA	1	20.94	20.63	20.86
			2	20.85	20.56	20.78
			3	21.00	20.66	20.91
			4	20.84	20.58	20.75

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	24.91	24.54	22.17	21.06	33
	661	1880.0	25.06	24.52	22.33	21.14	33
	810	1909.8	25.32	24.74	22.36	21.22	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	1850.2	25.09	23.81	21.35	20.28	33
	190	1880.0	24.85	23.49	21.06	19.92	33
	251	1909.8	24.97	23.55	21.02	19.90	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		21.67	21.64	21.57
		HSDPA	1	20.75	20.56	20.59
			2	20.66	20.45	20.49
			3	20.87	20.63	20.64
			4	20.67	20.44	20.48

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GPRS	Low	0.48	13
	Middle	0.36	13
	High	0.44	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.48	13
	Middle	0.36	13
	High	0.44	13

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	3.18	13
	Middle	2.99	13
	High	3.15	13
HSDPA (16QAM)	Low	3.16	13
	Middle	2.94	13
	High	3.13	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GPRS	Low	0.57	13
	Middle	0.34	13
	High	0.56	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	2.62	13
	Middle	2.46	13
	High	2.67	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.24	13
	Middle	3.09	13
	High	3.28	13
HSDPA (16QAM)	Low	3.27	13
	Middle	3.04	13
	High	3.25	13

Radiated Power**GPRS Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	87.11	134	1.7	H	17.4	0.26	4.75	21.89	38.45	16.56
836.6	97.73	305	2.3	V	24.0	0.26	4.75	28.49	38.45	9.96
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	73.19	237	1.8	H	11.7	0.45	8.84	20.09	33	12.91
1880.00	82.72	90	2.0	V	19.0	0.45	8.84	27.39	33	5.61

EGPRS Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	84.61	18	1.2	H	14.9	0.26	4.75	19.39	38.45	19.06
836.6	93.83	30	1.8	V	20.1	0.26	4.75	24.59	38.45	13.86
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	71.59	269	1.6	H	10.1	0.45	8.84	18.49	33	14.51
1880.00	78.92	329	1.8	V	15.2	0.45	8.84	23.59	33	9.41

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Low Channel										
826.4	81.11	15	2.3	H	11.4	0.26	4.75	15.89	38.45	22.56
826.4	90.03	319	1.3	V	16.3	0.26	4.75	20.79	38.45	17.66
EIRP for WCDMA Band II (Part 24E), Low Channel										
1852.40	69.19	228	1.1	H	7.7	0.45	8.84	16.09	33	16.91
1852.40	76.62	69	1.8	V	12.9	0.45	8.84	21.29	33	11.71

Note:

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level


FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH**Applicable Standard**

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (GSM) & 100 kHz (WCDMA) and the 26 dB & 99% bandwidth was recorded.

**Test Data****Environmental Conditions**

Temperature:	24~26 °C
Relative Humidity:	50~58 %
ATM Pressure:	100.0~103.0 kPa

The testing was performed by Alisa Gao from 2017-06-27 to 2017-07-05.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GPRS)	836.6	248.5	316.6
EGPRS(8PSK)	836.6	248.5	320.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.208	4.870
HSDPA (16QAM)	836.6	4.208	4.870


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GPRS)	1880.0	240.5	320.6
EGPRS(8PSK)	1880.0	244.5	308.4


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.208	4.910
HSDPA (16QAM)	1880.0	4.208	4.890



Cellular Band (Part 22H)

99% Occupied Bandwidth & 26 dB Emissions Bandwidth for GSM (GMSK) Mode




99% Occupied Bandwidth & 26 dB Emissions Bandwidth for EDGE Mode




99% Occupied Bandwidth & 26 dB Emissions Bandwidth for RMC (BPSK) Mode**99% Occupied Bandwidth & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode**



PCS Band (Part 24E)

99% Occupied Bandwidth & 26 dB Emissions Bandwidth for GSM (GMSK) Mode



99% Occupied Bandwidth & 26 dB Emissions Bandwidth for EDGE Mode



99% Occupied Bandwidth & 26 dB Emissions Bandwidth for RMC (BPSK) Mode**99% Occupied Bandwidth & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode**

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	24~26 °C
Relative Humidity:	50~58 %
ATM Pressure:	100.0~103.0 kPa


The testing was performed by Alisa Gao from 2017-06-27 to 2017-06-30.

EUT operation mode: Transmitting

Test result: Compliance, please refer to the following plots.


Cellular Band (Part 22H)

30 MHz – 1 GHz (GPRS Mode)




Fundamental test


1 GHz – 10 GHz (GPRS Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)




PCS Band (Part 24E)

30 MHz – 1 GHz (GPRS Mode)




1 GHz – 2 GHz (GPRS Mode)




Fundamental test


2 GHz – 20 GHz (GPRS Mode)




30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 2 GHz (WCDMA Mode)



2 GHz – 20 GHz (WCDMA Mode)



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-06-30.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:**Cellular Band (Part 22H)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GPRS Mode, Middle channel										
242.15	42.26	119	1.8	H	-62.7	0.14	2.05	-60.79	-13	47.79
242.15	40.50	61	1.2	V	-64.9	0.14	2.05	-62.99	-13	49.99
1673.20	61.50	357	1.7	H	-40.3	0.40	8.52	-32.18	-13	19.18
1673.20	60.17	80	1.8	V	-43.6	0.40	8.52	-35.48	-13	22.48
WCDMA Mode, Middle channel										
242.15	42.16	59	1.3	H	-62.8	0.14	2.05	-60.89	-13	47.89
242.15	40.80	316	1.7	V	-64.6	0.14	2.05	-62.69	-13	49.69
1673.20	47.50	73	1.9	H	-54.3	0.40	8.52	-46.18	-13	33.18
1673.20	52.07	281	1.0	V	-51.7	0.40	8.52	-43.58	-13	30.58

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GPRS Mode, Middle channel										
242.15	42.36	204	1.4	H	-62.6	0.14	2.05	-60.69	-13	47.69
242.15	40.90	96	1.9	V	-64.5	0.14	2.05	-62.59	-13	49.59
3760.00	38.12	199	1.6	H	-57.9	0.59	9.72	-48.77	-13	35.77
3760.00	40.01	167	1.0	V	-57.1	0.59	9.72	-47.97	-13	34.97
WCDMA Mode, Middle channel										
242.15	42.46	333	2.1	H	-62.5	0.14	2.05	-60.59	-13	47.59
242.15	40.50	273	1.0	V	-64.9	0.14	2.05	-62.99	-13	49.99
3760.00	37.02	302	1.6	H	-59.0	0.59	9.72	-49.87	-13	36.87
3760.00	38.21	123	1.1	V	-58.9	0.59	9.72	-49.77	-13	36.77

Note:

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Data

Environmental Conditions


Temperature:	24~26 °C
Relative Humidity:	50~58 %
ATM Pressure:	100.0~103.0 kPa

The testing was performed by Alisa Gao from 2017-06-27 to 2017-07-05.


EUT operation mode: Transmitting



Test Result: Compliance. Please refer to the following plots.



Cellular Band, Left Band Edge for GSM (GPRS) Mode




Cellular Band, Right Band Edge for GSM (GPRS) Mode




Cellular Band, Left Band Edge for EDGE Mode**Cellular Band, Right Band Edge for EDGE Mode**

Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**



Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




PCS Band, Left Band Edge for GSM (GPRS) Mode




PCS Band, Left Band Edge for EDGE Mode




PCS Band, Right Band Edge for EDGE Mode




PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode



PCS Band, Left Band Edge for HSDPA (16QAM) Mode



PCS Band, Right Band Edge for HSDPA (16QAM) Mode



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055, §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Alisa Gao on 2017-06-27.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	7.4	17	0.02032	2.5
-20		17	0.02032	2.5
-10		13	0.01514	2.5
0		13	0.01514	2.5
10		13	0.01514	2.5
20		11	0.01315	2.5
30		13	0.01514	2.5
40		15	0.01793	2.5
50		17	0.02032	2.5
25	$V_{min.} = 6.3$	20	0.02391	2.5
25	$V_{max.} = 8.4$	23	0.02749	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	7.4	17	0.02032	2.5
-20		17	0.02032	2.5
-10		15	0.01193	2.5
0		13	0.01514	2.5
10		13	0.01514	2.5
20		10	0.01195	2.5
30		13	0.01514	2.5
40		15	0.01793	2.5
50		17	0.02032	2.5
25	$V_{min.} = 6.3$	20	0.02391	2.5
25	$V_{max.} = 8.4$	24	0.02869	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	7.4	-12	-0.01434	2.5
-20		-12	-0.01434	2.5
-10		-12	-0.01434	2.5
0		-9	-0.01076	2.5
10		-9	-0.01076	2.5
20		-7	-0.00837	2.5
30		-9	-0.01076	2.5
40		-10	-0.01195	2.5
50		-12	-0.01434	2.5
25	$V_{min.} = 6.3$	-15	-0.01793	2.5
25	$V_{max.} = 8.4$	-18	-0.02152	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_o = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	7.4	11	0.00585	Pass
-20		11	0.00585	Pass
-10		7	0.00372	Pass
0		7	0.00372	Pass
10		7	0.00372	Pass
20		5	0.00266	Pass
30		7	0.00372	Pass
40		10	0.00532	Pass
50		13	0.00691	Pass
25	$V_{min.} = 6.3$	15	0.00798	Pass
25	$V_{max.} = 8.4$	17	0.00904	Pass

EDGE Mode

Middle Channel, $f_o = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	7.4	11	0.00585	Pass
-20		11	0.00585	Pass
-10		9	0.00479	Pass
0		9	0.00479	Pass
10		9	0.00479	Pass
20		8	0.00426	Pass
30		9	0.00479	Pass
40		10	0.00532	Pass
50		13	0.00691	Pass
25	$V_{min.} = 6.3$	15	0.00798	Pass
25	$V_{max.} = 8.4$	15	0.00798	Pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	7.4	-8	-0.00426	Pass
-20		-8	-0.00426	Pass
-10		-8	-0.00426	Pass
0		-6	-0.00319	Pass
10		-6	-0.00319	Pass
20		-5	-0.00266	Pass
30		-6	-0.00319	Pass
40		-7	-0.00372	Pass
50		-8	-0.00426	Pass
25	$V_{min} = 6.3$	-9	-0.00479	Pass
25	$V_{max} = 8.4$	-10	-0.00532	Pass

***** END OF REPORT *****