



FCC RF Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Mobile Payment Terminal
BRAND NAME : PAX
MODEL NAME : D220
MARKETING NAME : D220
FCC ID : V5P-D2204GBW
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jul. 11, 2017 and testing was completed on Aug.09, 2017. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

Approved by: Eric Shih / Manager



Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 6dB Bandwidth Measurement	14
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	20
3.5 Radiated Band Edges and Spurious Emission Measurement	30
3.6 AC Conducted Emission Measurement.....	34
3.7 Antenna Requirements	38
4 LIST OF MEASURING EQUIPMENT	39
5 UNCERTAINTY OF EVALUATION	40
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR771112C	Rev. 01	Initial issue of report	Aug. 24, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.96 dB at 2483.60 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.32 dB at 0.20 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Payment Terminal
Brand Name	PAX
Model Name	D220
Marketing Name	D220
FCC ID	V5P-D2204GBW
EUT supports Radios application	WCDMA/HSPA /HSPA+/LTE/NFC WLAN2.4G 802.11b/g/n HT20 Bluetooth V3.0 + EDR/Bluetooth V4.0 LE
IMEI Code	Conducted: 864669020130370 Conduction: N/A Radiation: 864669020130396/864669020130438
HW Version	D220-xxx-xx4-xxxx
SW Version	14.00.xx.xxxx
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 19.07 dBm (0.0807 W) 802.11g : 24.01 dBm (0.2518 W) 802.11n HT20 : 23.57 dBm (0.2275 W)
Antenna Type / Gain	PIFA Antenna type with gain 0.8 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No are CN5018 and CN5019

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	TH01-SZ	CO01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	03CH03-SZ		577730

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM1900 Idle + Bluetooth Link + WLAN Link + USB Cable(Charging from Adapter)

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	TCL	VFD-90	FCC DoC	N/A	N/A
5.	Notebook	lenovo	E450	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Occupied Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup








3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Sam Zheng









Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11b Channel 06**100kHz PSD reference Level****Mid Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Sam Zheng


WLAN 802.11b Channel 11**100kHz PSD reference Level****High Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Sam Zheng

WLAN 802.11g Channel 01**100kHz PSD reference Level**


Date: 21.JUL.2017 02:44:51

Low Channel Plot

Date: 21.JUL.2017 02:45:56

Spurious Emission 30MHz~3GHz

Date: 21.JUL.2017 02:46:09

Spurious Emission 2GHz~25GHz


Date: 21.JUL.2017 02:46:17



Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Sam Zheng


WLAN 802.11g Channel 06

100kHz PSD reference Level




Mid Channel Plot

Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Sam Zheng

WLAN 802.11g Channel 11**100kHz PSD reference Level**


Date: 21 JUL 2017 02:59:30

High Channel Plot

Date: 21 JUL 2017 03:01:50

Spurious Emission 30MHz~3GHz


Date: 21 JUL 2017 03:03:09

Spurious Emission 2GHz~25GHz

Date: 21 JUL 2017 03:03:17




Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Sam Zheng






Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Sam Zheng





Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Sam Zheng



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup




3.6.5 Test Result of AC Conducted Emission





Test Mode :	Mode 2	Temperature :	24 ~25℃
Test Engineer :	HaoHai YE	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + USB Cable(Charging from Adapter)		



Site : CO01-SZ
Condition: FCC 15C_QP LISN_20170301_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.20	40.35	-13.32	53.67	30.10	0.03	10.22	Average
2	0.20	46.15	-17.52	63.67	35.90	0.03	10.22	QP
3	0.63	27.19	-18.81	46.00	17.00	0.02	10.17	Average
4	0.63	37.69	-18.31	56.00	27.50	0.02	10.17	QP
5	0.87	20.99	-25.01	46.00	10.79	0.04	10.16	Average
6	0.87	34.59	-21.41	56.00	24.39	0.04	10.16	QP
7	1.24	19.90	-26.10	46.00	9.70	0.05	10.15	Average
8	1.24	32.50	-23.50	56.00	22.30	0.05	10.15	QP
9	1.67	19.01	-26.99	46.00	8.80	0.05	10.16	Average
10	1.67	30.21	-25.79	56.00	20.00	0.05	10.16	QP
11	4.01	21.00	-25.00	46.00	10.70	0.05	10.25	Average
12	4.01	29.20	-26.80	56.00	18.90	0.05	10.25	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~40GHz	Jan. 06, 2017	Jul. 21, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	Jul. 21, 2017	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	Jul. 21, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	Jul. 21, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	Aug. 09, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	Aug. 09, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	Aug. 09, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Aug. 09, 2017	Jul. 18, 2018	Conduction (CO01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 20, 2017	Jul. 13, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 20, 2017	Jul. 13, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May. 14, 2017	Jul. 13, 2017	May. 13, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May. 14, 2017	Jul. 13, 2017	May. 13, 2018	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Jul. 09, 2017	Jul. 13, 2017	Jul. 08, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Jun. 16, 2017	Jul. 13, 2017	Jun. 15, 2018	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Jul. 13, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Jul. 13, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 06, 2017	Jul. 13, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jul. 13, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 13, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 13, 2017	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5 dB
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5 dB
---	------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Sam Zheng	Temperature:	24~26	°C
Test Date:	2017/7/26	Relative Humidity:	50~53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.09	8.99	0.50	Pass
11b	1Mbps	1	6	2437	14.14	9.01	0.50	Pass
11b	1Mbps	1	11	2462	14.14	9.03	0.50	Pass
11g	6Mbps	1	1	2412	18.23	15.80	0.50	Pass
11g	6Mbps	1	6	2437	18.33	16.00	0.50	Pass
11g	6Mbps	1	11	2462	18.33	16.02	0.50	Pass
HT20	MCS0	1	1	2412	18.88	17.52	0.50	Pass
HT20	MCS0	1	6	2437	18.88	17.52	0.50	Pass
HT20	MCS0	1	11	2462	19.03	17.52	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	18.71	30.00	0.80	19.51	36.00	Pass
11b	1Mbps	1	6	2437	18.94	30.00	0.80	19.74	36.00	Pass
11b	1Mbps	1	11	2462	19.07	30.00	0.80	19.87	36.00	Pass
11g	6Mbps	1	1	2412	23.81	30.00	0.80	24.61	36.00	Pass
11g	6Mbps	1	6	2437	23.84	30.00	0.80	24.64	36.00	Pass
11g	6Mbps	1	11	2462	24.01	30.00	0.80	24.81	36.00	Pass
HT20	MCS0	1	1	2412	23.20	30.00	0.80	24.00	36.00	Pass
HT20	MCS0	1	6	2437	23.31	30.00	0.80	24.11	36.00	Pass
HT20	MCS0	1	11	2462	23.57	30.00	0.80	24.37	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	16.24
11b	1Mbps	1	6	2437	0.10	16.38
11b	1Mbps	1	11	2462	0.10	16.66
11g	6Mbps	1	1	2412	0.59	15.46
11g	6Mbps	1	6	2437	0.59	15.61
11g	6Mbps	1	11	2462	0.59	15.77
HT20	MCS0	1	1	2412	0.63	14.49
HT20	MCS0	1	6	2437	0.63	14.64
HT20	MCS0	1	11	2462	0.63	14.84

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.59	0.80	8.00	Pass
11b	1Mbps	1	6	2437	-5.32	0.80	8.00	Pass
11b	1Mbps	1	11	2462	-4.63	0.80	8.00	Pass
11g	6Mbps	1	1	2412	-9.55	0.80	8.00	Pass
11g	6Mbps	1	6	2437	-9.28	0.80	8.00	Pass
11g	6Mbps	1	11	2462	-8.81	0.80	8.00	Pass
HT20	MCS0	1	1	2412	-10.55	0.80	8.00	Pass
HT20	MCS0	1	6	2437	-10.22	0.80	8.00	Pass
HT20	MCS0	1	11	2462	-9.48	0.80	8.00	Pass



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preampl	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2383.605	50.49	-23.51	74	52.25	27.44	5.02	34.22	106	62	P	H
		2383.815	42.19	-11.81	54	43.95	27.44	5.02	34.22	106	62	A	H
	*	2412	102.6	-	-	104.17	27.57	5.06	34.2	106	62	P	H
	*	2412	99.31	-	-	100.88	27.57	5.06	34.2	106	62	A	H
		2381.715	49.14	-24.86	74	50.9	27.44	5.02	34.22	101	313	P	V
		2385.915	39.62	-14.38	54	41.27	27.51	5.06	34.22	101	313	A	V
	*	2412	97.2	-	-	98.77	27.57	5.06	34.2	101	313	P	V
	*	2412	95.28	-	-	96.85	27.57	5.06	34.2	101	313	A	V
802.11b CH 06 2437MHz		2340.66	48.95	-25.05	74	50.9	27.31	4.98	34.24	100	59	P	H
		2386.58	38.16	-15.84	54	39.81	27.51	5.06	34.22	100	59	A	H
	*	2437	103.29	-	-	104.65	27.7	5.12	34.18	100	59	P	H
	*	2437	99.65	-	-	101.01	27.7	5.12	34.18	100	59	A	H
		2489.5	48.95	-25.05	74	49.99	27.9	5.19	34.13	100	59	P	H
		2487.19	39.49	-14.51	54	40.6	27.83	5.19	34.13	100	59	A	H
		2365.02	48.32	-25.68	74	50.14	27.38	5.02	34.22	100	216	P	V
		2389.94	37.79	-16.21	54	39.42	27.51	5.06	34.2	100	216	A	V
	*	2437	101.13	-	-	102.49	27.7	5.12	34.18	100	216	P	V
	*	2437	97.47	-	-	98.83	27.7	5.12	34.18	100	216	A	V
		2486.35	48.58	-25.42	74	49.69	27.83	5.19	34.13	100	216	P	V
		2487.33	38.57	-15.43	54	39.68	27.83	5.19	34.13	100	216	A	V



802.11b CH 11 2462MHz	*	2462	103.49	-	-	104.75	27.77	5.12	34.15	100	59	P	H
	*	2462	100.37	-	-	101.63	27.77	5.12	34.15	100	59	A	H
		2491	51.51	-22.49	74	52.55	27.9	5.19	34.13	100	59	P	H
		2490.4	43.19	-10.81	54	44.23	27.9	5.19	34.13	100	59	A	H
	*	2462	99.51	-	-	100.77	27.77	5.12	34.15	100	216	P	V
	*	2462	96.14	-	-	97.4	27.77	5.12	34.15	100	216	A	V
		2490.04	50.83	-23.17	74	51.87	27.9	5.19	34.13	100	216	P	V
		2491.12	41.15	-12.85	54	42.19	27.9	5.19	34.13	100	216	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	41.73	-32.27	74	59.89	31.59	8.59	58.34	107	360	P	H
		4824	43.85	-30.15	74	62.01	31.59	8.59	58.34	107	360	P	V
802.11b CH 06 2437MHz		4874	42.32	-31.68	74	60.34	31.71	8.6	58.33	120	360	P	H
		7311	46.58	-27.42	74	59.47	36.27	10.24	59.4	174	100	P	H
		4874	43.35	-30.65	74	61.37	31.71	8.6	58.33	120	360	P	V
		7311	48.59	-25.41	74	61.48	36.27	10.24	59.4	174	100	P	V
802.11b CH 11 2462MHz		4924	41.79	-32.21	74	59.65	31.83	8.64	58.33	133	360	P	H
		7386	46.69	-27.31	74	59.55	36.38	10.2	59.44	145	274	P	H
		4924	45.04	-28.96	74	62.9	31.83	8.64	58.33	133	0	P	V
		7386	49.04	-24.96	74	61.9	36.38	10.2	59.44	145	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2390	61.46	-12.54	74	63.09	27.51	5.06	34.2	106	62	P	H
		2390	48.62	-5.38	54	50.25	27.51	5.06	34.2	106	62	A	H
	*	2412	103.03	-	-	104.6	27.57	5.06	34.2	106	62	P	H
	*	2412	96.33	-	-	97.9	27.57	5.06	34.2	106	62	A	H
		2390	58.33	-15.67	74	59.96	27.51	5.06	34.2	132	213	P	V
		2390	44.21	-9.79	54	45.84	27.51	5.06	34.2	132	213	A	V
	*	2412	99.53	-	-	101.1	27.57	5.06	34.2	132	213	P	V
	*	2412	91.98	-	-	93.55	27.57	5.06	34.2	132	213	A	V
802.11g CH 06 2437MHz		2385.88	49.58	-24.42	74	51.23	27.51	5.06	34.22	106	62	P	H
		2389.66	39.01	-14.99	54	40.66	27.51	5.06	34.22	106	62	A	H
	*	2437	103.99	-	-	105.35	27.7	5.12	34.18	106	62	P	H
	*	2437	95.81	-	-	97.17	27.7	5.12	34.18	106	62	A	H
		2483.97	51.19	-22.81	74	52.3	27.83	5.19	34.13	106	62	P	H
		2483.83	40.09	-13.91	54	41.2	27.83	5.19	34.13	106	62	A	H
		2385.04	47.93	-26.07	74	49.65	27.44	5.06	34.22	100	215	P	V
		2388.96	37.83	-16.17	54	39.48	27.51	5.06	34.22	100	215	A	V
	*	2437	99.79	-	-	101.15	27.7	5.12	34.18	100	215	P	V
	*	2437	92.81	-	-	94.17	27.7	5.12	34.18	100	215	A	V
		2489.15	49.33	-24.67	74	50.37	27.9	5.19	34.13	100	215	P	V
		2483.5	38.55	-15.45	54	39.66	27.83	5.19	34.13	100	215	A	V



802.11g CH 11 2462MHz	*	2462	104.11	-	-	105.37	27.77	5.12	34.15	106	62	P	H
	*	2462	96.2	-	-	97.46	27.77	5.12	34.15	106	62	A	H
		2484	65.27	-8.73	74	66.38	27.83	5.19	34.13	106	62	P	H
		2483.6	52.04	-1.96	54	53.15	27.83	5.19	34.13	106	62	A	H
	*	2462	99.91	-	-	101.17	27.77	5.12	34.15	128	207	P	V
	*	2462	93.36	-	-	94.62	27.77	5.12	34.15	128	207	A	V
		2483.52	62.61	-11.39	74	63.72	27.83	5.19	34.13	128	207	P	V
		2483.52	46.54	-7.46	54	47.65	27.83	5.19	34.13	128	207	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	40.85	-33.15	74	59.01	31.59	8.59	58.34	164	360	P	H
		4824	40.07	-33.93	74	58.23	31.59	8.59	58.34	164	360	P	V
802.11g CH 06 2437MHz		4874	40.04	-33.96	74	58.06	31.71	8.6	58.33	163	360	P	H
		7311	46.63	-27.37	74	59.52	36.27	10.24	59.4	174	100	P	H
		4874	41.41	-32.59	74	59.43	31.71	8.6	58.33	163	360	P	V
		7311	49.27	-24.73	74	62.16	36.27	10.24	59.4	174	100	P	V
802.11g CH 11 2462MHz		4924	41.23	-32.77	74	59.09	31.83	8.64	58.33	162	360	P	H
		7386	46.23	-27.77	74	59.09	36.38	10.2	59.44	145	274	P	H
		4924	42.15	-31.85	74	60.01	31.83	8.64	58.33	162	360	P	V
		7386	48.25	-25.75	74	61.11	36.38	10.2	59.44	145	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.695	59.32	-14.68	74	60.97	27.51	5.06	34.22	108	62	P	H
		2390	48.59	-5.41	54	50.22	27.51	5.06	34.2	108	62	A	H
	*	2412	102.57	-	-	104.14	27.57	5.06	34.2	108	62	P	H
	*	2412	94.91	-	-	96.48	27.57	5.06	34.2	108	62	A	H
		2388.96	57.03	-16.97	74	58.68	27.51	5.06	34.22	135	213	P	V
		2390	44.79	-9.21	54	46.42	27.51	5.06	34.2	135	213	A	V
	*	2412	98.61	-	-	100.18	27.57	5.06	34.2	135	213	P	V
	*	2412	90.81	-	-	92.38	27.57	5.06	34.2	135	213	A	V
802.11n HT20 CH 06 2437MHz		2357.46	48.72	-25.28	74	50.56	27.38	5.02	34.24	100	62	P	H
		2384.62	38.76	-15.24	54	40.48	27.44	5.06	34.22	100	62	A	H
	*	2437	102.04	-	-	103.4	27.7	5.12	34.18	100	62	P	H
	*	2437	94.59	-	-	95.95	27.7	5.12	34.18	100	62	A	H
		2484.74	50.76	-23.24	74	51.87	27.83	5.19	34.13	100	62	P	H
		2484.39	40.2	-13.8	54	41.31	27.83	5.19	34.13	100	62	A	H
		2348.5	48.47	-25.53	74	50.38	27.31	5.02	34.24	100	202	P	V
		2388.96	38.49	-15.51	54	40.14	27.51	5.06	34.22	100	202	A	V
	*	2437	98.65	-	-	100.01	27.7	5.12	34.18	100	202	P	V
	*	2437	91.81	-	-	93.17	27.7	5.12	34.18	100	202	A	V
		2485.58	48.34	-25.66	74	49.45	27.83	5.19	34.13	100	202	P	V
		2485.93	39.09	-14.91	54	40.2	27.83	5.19	34.13	100	202	A	V



802.11n HT20 CH 11 2462MHz	*	2462	102.82	-	-	104.08	27.77	5.12	34.15	106	62	P	H
	*	2462	95.72	-	-	96.98	27.77	5.12	34.15	106	62	A	H
		2483.52	65.92	-8.08	74	67.03	27.83	5.19	34.13	106	62	P	H
		2484.04	50.77	-3.23	54	51.88	27.83	5.19	34.13	106	62	A	H
	*	2462	99.91	-	-	101.17	27.77	5.12	34.15	130	209	P	V
		2462	92.44	-	-	93.7	27.77	5.12	34.15	130	209	A	V
		2483.8	62.27	-11.73	74	63.38	27.83	5.19	34.13	130	209	P	V
		2483.56	46.5	-7.5	54	47.61	27.83	5.19	34.13	130	209	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	39.47	-34.53	74	57.63	31.59	8.59	58.34	162	360	P	H
		4824	40.51	-33.49	74	58.67	31.59	8.59	58.34	162	360	P	V
802.11n HT20 CH 06 2437MHz		4874	40.72	-33.28	74	58.74	31.71	8.6	58.33	162	360	P	H
		7311	46.52	-27.48	74	59.41	36.27	10.24	59.4	174	100	P	H
		4874	40.62	-33.38	74	58.64	31.71	8.6	58.33	162	360	P	V
		7311	49.01	-24.99	74	61.9	36.27	10.24	59.4	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	40.39	-33.61	74	58.25	31.83	8.64	58.33	162	360	P	H
		7386	46.09	-27.91	74	58.95	36.38	10.2	59.44	145	274	P	H
		4924	40.59	-33.41	74	58.45	31.83	8.64	58.33	162	360	P	V
		7386	48.97	-25.03	74	61.83	36.38	10.2	59.44	145	274	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	26.33	-13.67	40	31.07	26.7	0.56	32	130	60	P	H
		95.96	27.23	-16.27	43.5	39.58	18.4	1.01	31.76	-	-	P	H
		166.77	23.62	-19.88	43.5	36.67	17.07	1.33	31.45	-	-	P	H
		250.19	31.96	-14.04	46	43.69	18	1.66	31.39	-	-	P	H
		711.91	31.46	-14.54	46	32.2	27.61	2.89	31.24	-	-	P	H
		996.12	34	-20	54	31.45	30.32	3.47	31.24	-	-	P	H
		30	29.44	-10.56	40	34.18	26.7	0.56	32	-	-	P	V
		52.31	36.65	-3.35	40	52.21	15.62	0.74	31.92	135	100	P	V
		90.14	24.18	-19.32	43.5	37.18	17.8	0.98	31.78	-	-	P	V
		166.77	24.36	-19.14	43.5	37.41	17.07	1.33	31.45	-	-	P	V
		208.48	26.13	-17.37	43.5	39.95	16.02	1.5	31.34	-	-	P	V
		847.71	32.37	-13.63	46	32.36	28.07	3.2	31.26	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(KHz)	VBW Setting
802.11b	97.72	12.420	0.081	100Hz
802.11g	87.31	2.064	0.484	1KHz
802.11n HT20	86.49	1.920	0.521	1KHz


802.11b



Date: 13 JUL 2017 18:20:41




802.11g



Date: 13 JUL 2017 18:28:12

802.11n HT20



Date: 13 JUL 2017 18:34:16